



HAL
open science

Large-Eddy Simulation of Flame Dynamics during Ignition of a Swirling Injector Unit and Comparison with Experiments

Karl Töpperwien, T. Lancien, S. Puggelli, G Vignat, K Prieur []], D. Durox, S. Candel, R. Vicquelin

► To cite this version:

Karl Töpperwien, T. Lancien, S. Puggelli, G Vignat, K Prieur []], et al.. Large-Eddy Simulation of Flame Dynamics during Ignition of a Swirling Injector Unit and Comparison with Experiments. 9th European Combustion Meeting, Apr 2019, Lisbon, Portugal. hal-02496953

HAL Id: hal-02496953

<https://hal.science/hal-02496953v1>

Submitted on 3 Mar 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Q Scope

- A **safe and reliable ignition** of combustion chambers must be ensured for aeronautical applications and gas turbines.
- A **flame flashback** has been observed experimentally [1] during the ignition of spray flames which might have a **damaging effect** on the injection unit.
- Large eddy simulations (LES) can help to investigate and better understand the **dynamic flame behaviour** during ignition.

Experimental Setup

The SICCA combustor is a swirled single-injector spray combustor operated at ambient pressure.

- $P_{th} \approx 5 \text{ kW}$
- Fuel: liquid n-heptane (C_7H_{16}) at $T = 298 \text{ K}$
- Global equivalence ratio: $\phi = 0.89$




(a) 4.17 ms (b) 12.5 ms (c) 20.8 ms (d) 29.2 ms (e) 37.5 ms
Experimental ignition sequence recorded by a high-speed camera with OH* filter [1].



Numerical Setup






The numerical domain and the solver setup are based on previous work published in [2].

- LES solver: AVBP (CERFACS/IFPEN)
- SGS model: Wall Adapting Local Eddy-Viscosity (WALE) model
- Combustion model: Dynamic TFLES with PEA
- Two phase modeling: monodisperse Eulerian-Eulerian model ($d_{inj} = 15.3 \mu\text{m}$)
- Evaporation model: Abramzon-Sirignano
- Prescribed temperature profile ranging between $T = 773$ and $T = 1173 \text{ K}$



LES Ignition Sequence

- Ignition with a spherical volume of high temperature burnt gases
- Penetration into the swirler
- Flame edge attached to the swirler
- After a characteristic time: quenching of the lower flame part
- Flame lift-off and stabilization at a distance from the swirler





Flame shape based on progress variable $c = 0.5$ colored by temperature.

Conclusion


- Capability of LES to properly capture the flame dynamics during ignition including:
 - the stabilization of the flame attached to the swirler
 - the lift-off after a characteristic time
- Good qualitative agreement of the governing mechanisms in each phase with experimental data

Penetration into the Injector



Phase I: Stabilization and anchoring


- Growth of the initial flame kernel [I]
- Burnt gas expansion causes acoustic pressure disturbance [II]
- Temporary stagnation of the mass flow rate [III]
- Flame flashback and anchoring attached to the swirler, despite pre-ignition mass flow rates are re-established [IV]
- Transient stabilization in qualitative agreement with experimental data [V]





Flame Lift-Off

Phase II: Flame lift-off and shape transition


- Lower flame part quenched after a characteristic time related to the cooling of the recirculating burnt gases near the combustor walls [VI]
- Flame lift-off and stabilization detached from the swirler [VII]
- Detached flame shape different with respect to attached flame [VIII]
- Lift-off delay qualitatively retrieves experimental trends [IX]



Heat release rate and contour of the progress variable $c = 0.5$ at the combustor mid-plane.



Cooling of the IRZ and ORZ [VI].



Line of sight integrated heat release at 25.1 ms [IX].

References

- [1] K. Prieur, D. Durox, G. Vignat, T. Schuller, S. Candel, Proceedings of ASME Turbo Expo, 4B, (GT2018-76840) (2018).
- [2] T. Lancien, K. Prieur, D. Durox, S. Candel, R. Vicquelin, Journal of Engineering for Gas Turbines and Power 140 (2017).