



**HAL**  
open science

## Toward a Dempster-Shafer theory of concepts

Sabine Frittella, Krishna Manoorkar, Alessandra Palmigiano, Apostolos Tzimoulis, Nachoem M. Wijnberg

► **To cite this version:**

Sabine Frittella, Krishna Manoorkar, Alessandra Palmigiano, Apostolos Tzimoulis, Nachoem M. Wijnberg. Toward a Dempster-Shafer theory of concepts. *International Journal of Approximate Reasoning*, 2020, 125, pp.14-25. 10.1016/j.ijar.2020.05.004 . hal-02504595

**HAL Id: hal-02504595**

**<https://hal.science/hal-02504595>**

Submitted on 22 Aug 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

# Toward a Dempster-Shafer theory of concepts

SABINE FRITTELLA, INSA Centre Val de Loire, Univ. Orléans, LIFO EA 4022, France

KRISHNA MANOORKAR, Technion, Haifa, Israel

ALESSANDRA PALMIGIANO, VU School of Business and Economics, Amsterdam, the Netherlands,  
and Department of Mathematics and Applied Mathematics, University of Johannesburg, South Africa

APOSTOLOS TZIMOULIS, VU School of Business and Economics, The Netherlands

NACHOEM WIJNBERG, Amsterdam Business School, the Netherlands and College of Business and  
Economics, University of Johannesburg, South Africa

In this paper, we generalize the basic notions and results of Dempster-Shafer theory from predicates to formal concepts. Results include the representation of conceptual belief functions as inner measures of suitable probability functions, and a Dempster-Shafer rule of combination on belief functions on formal concepts.

*Keywords.* Formal Concept Analysis, Dempster-Shafer theory, epistemic logic.

## ACM Reference Format:

Sabine Frittella, Krishna Manoorkar, Alessandra Palmigiano, Apostolos Tzimoulis, and Nachoem Wijnberg. 2020. Toward a Dempster-Shafer theory of concepts. 1, 1 (April 2020), 15 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

## 1 INTRODUCTION

*Dempster-Shafer theory.* Dempster-Shafer theory [5, 19] is a formal framework for decision-making under uncertainty in situations in which some predicates cannot be assigned subjective probabilities. The core proposal of Dempster-Shafer theory is that, in such cases, the missing value can be replaced by a range of values, the lower and upper bounds of which are assigned by *belief* and *plausibility* functions (cf. Definition 2). This situation can be captured with probabilistic tools via *probability spaces*. The latter are structures  $\mathbb{X} = (S, \mathbb{A}, \mu)$  where  $S$  is a nonempty (finite) set,  $\mathbb{A}$  is a  $\sigma$ -algebra of subsets of  $S$ , and  $\mu : \mathbb{A} \rightarrow [0, 1]$  is a probability measure. In probability spaces, belief and plausibility functions naturally arise as the *inner* and *outer measures* induced by  $\mu$  (cf. [6, Proposition 3.1]). Moreover, every belief function can be *represented* as the inner measure of some probability space (cf. [6, Theorem 3.3]). In [9, 26], generalisations of Dempster-Shafer theory from Boolean algebras to so-called De Morgan type lattices and distributive lattices are presented.

---

The research of Sabine Frittella was partially funded by the grant PHC VAN GOGH 2019, project n°42555PE and by the grant ANR JCJC 2019, project PRELAP (ANR-19-CE48-0006).

Authors' addresses: Sabine Frittella, INSA Centre Val de Loire, Univ. Orléans, LIFO EA 4022, Bourges, France, [sabine.frittella@insa-cvl.fr](mailto:sabine.frittella@insa-cvl.fr); Krishna Manoorkar, Technion, Haifa, Israel; Alessandra Palmigiano, VU School of Business and Economics, Amsterdam, the Netherlands, and Department of Mathematics and Applied Mathematics, University of Johannesburg, South Africa; Apostolos Tzimoulis, VU School of Business and Economics, Amsterdam, The Netherlands; Nachoem Wijnberg, Amsterdam Business School, the Netherlands and College of Business and Economics, University of Johannesburg, South Africa.

---

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

© 2020 Association for Computing Machinery.

XXXX-XXXX/2020/4-ART \$15.00

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>

*Combination of beliefs.* Central to Dempster-Shafer theory is the rule of combination of beliefs (representing e.g. evidence, hints, or preferences) (see [19]). It allows to combine possibly conflicting beliefs proceeding from multiple independent sources. Intuitively, the combined belief according to the Dempster-Shafer rule highlights the converging portions of evidence, and downplays the conflicting ones.

*Formal concept analysis.* Formal concept analysis (FCA) [7] is a successful and very elegant theory in data analysis based on algebraic and lattice-theoretic facts. In formal concept analysis, databases are represented as formal contexts, i.e. structures  $(A, X, I)$  such that  $A$  and  $X$  are sets, and  $I \subseteq A \times X$  is a binary relation. Intuitively,  $A$  is understood as a collection of objects,  $X$  as a collection of features, and for any object  $a$  and feature  $x$ , the tuple  $(a, x)$  belongs to  $I$  exactly when object  $a$  has feature  $x$ . Every formal context  $(A, X, I)$  can be associated with the lattice of its formal concepts (see Section 3.1 for more details). FCA relies on Birkhoff's representation theory of complete lattices [4] that states that any complete lattice can dually be represented by a formal context and vice-versa.

*Connections between FCA, rough set theory and decision theory.* Connections between Rough Set Theory [17] and Dempster-Shafer theory have been made since the beginning of the development of Rough Set Theory [15, 16], with particular regard to the (epistemic) *logical* perspective on approximation spaces [6, 14, 18, 23], and also to the study of several types of *algebraic* structures arising from and generalizing approximation spaces [10, 24, 27]. Recent work in this vein concerns the application of the notion of three-way decisions to FCA [25] and rough sets [21, 22]. On the basis of algebraic and logical insights, in [1] a methodology has been introduced which generalizes Rough Set Theory (RST) from sets to *formal concepts*, thus paving the way for a mathematical theory that simultaneously generalises FCA and RST, establishes systematic connections between these theories and logic [2, 3] and paves the way to a systematic analysis of the proof theoretic aspects of this generalization [11, 12]. This generalized environment allows for the natural generalization and transfer of connections successfully established by FCA and RST with other theories. The present paper is a case in point: building on [1, Section 7.3], we propose a generalization of Dempster-Shafer theory to formal concepts.

*Structure of the paper.* This paper develops preliminary theoretical results on the generalization of Dempster-Shafer theory applied to formal concepts and illustrates its potential at formalizing decision-making problems concerning categorization.

In Section 2, we provide the preliminaries on probability spaces, belief functions and plausibility functions, then we propose an order-theoretic analysis of the toggle between finite probability spaces and belief functions on finite sets, with a particular focus on [6, Theorem 3.3].

In Section 3, we generalise the result of [6, Theorem 3.3] from probability spaces to formal concepts. In Section 3.1, we provide preliminaries on formal concepts, introduce conceptual *DS*-structures and generalise the notions of belief functions and probability spaces for conceptual *DS*-structures. In Section 3.2, we prove that belief and plausibility functions on conceptual *DS*-structures can be represented as the inner and outer measures of some probability space (see Theorem 3.4). We provide both a purely algebraic proof and a frame theoretic proof of that result. The former highlights why the construction provides belief and plausibility functions, while the latter allows the reader to understand the structure of conceptual probability space on which the inner and outer measures are interpreted. In Section 3.3, we show how to adapt Dempster-Shafer combination of evidence to formal concepts.

In Sections 4 and 5, we present two examples to illustrate how Dempster-Shafer theory can be used for formal concepts. In Section 4, we illustrate how Dempster-Shafer combination of evidence

can be used to aggregate preferences. In Section 5, we show how Dempster-Shafer theory can be used to make categorisation decision. Namely to answer the question: to which category does an unknown object belongs?

## 2 ORDER-THEORETIC ANALYSIS

Belief and plausibility functions are one proposal among others to generalise probabilities to situations in which some predicates cannot be assigned subjective probabilities. In this section, we collect preliminaries on belief and plausibility functions on sets (for more details on imprecise probabilities see [20]), finite probability spaces, and develop an order theoretic analysis of these notions which leads to an algebraic reformulation of [6, Theorem 3.3].

*Belief, plausibility and mass functions.* A *belief function* (cf. [19, Chapter 1, page 5]) on a set  $S$  is a map  $\text{bel} : \mathcal{P}(S) \rightarrow [0, 1]$  such that  $\text{bel}(S) = 1$ , and for every  $n \in \mathbb{N}$ ,

$$\text{bel}(A_1 \cup \dots \cup A_n) \geq \sum_{\emptyset \neq I \subseteq \{1, \dots, n\}} (-1)^{|I|+1} \text{bel} \left( \bigcap_{i \in I} A_i \right). \quad (1)$$

A *plausibility function* on  $S$  is a map  $\text{pl} : \mathcal{P}(S) \rightarrow [0, 1]$  such that  $\text{pl}(S) = 1$ , and for every  $n \in \mathbb{N}$ ,

$$\text{pl}(A_1 \cup A_2 \cup \dots \cup A_n) \leq \sum_{\emptyset \neq I \subseteq \{1, 2, \dots, n\}} (-1)^{|I|+1} \text{pl} \left( \bigcap_{i \in I} A_i \right). \quad (2)$$

Belief and plausibility functions on sets are interchangeable notions: for every belief function  $\text{bel}$  as above, the assignment  $X \mapsto 1 - \text{bel}(X)$  defines a plausibility function on  $S$ , and for every plausibility function  $\text{pl}$  as above, the assignment  $X \mapsto 1 - \text{pl}(X)$  defines a belief function on  $S$ . A *mass function* on a set  $S$  is a map  $m : \mathcal{P}(S) \rightarrow [0, 1]$  such that

$$\sum_{X \subseteq S} m(X) = 1. \quad (3)$$

On finite sets, belief (resp. plausibility) functions and mass functions are interchangeable notions: any mass function  $m$  as above induces the belief function  $\text{bel}_m : \mathcal{P}(S) \rightarrow [0, 1]$  defined as

$$\text{bel}_m(X) := \sum_{Y \subseteq X} m(Y) \quad \text{for every } X \subseteq S, \quad (4)$$

and conversely, any belief function  $\text{bel}$  as above induces the mass function  $m_{\text{bel}} : \mathcal{P}(S) \rightarrow [0, 1]$  defined as

$$m_{\text{bel}}(X) := \text{bel}(X) - \sum_{Y \subset X} (-1)^{|X \setminus Y|} \text{bel}(Y) \quad \text{for every } X \subseteq S. \quad (5)$$

A *DS-structure*<sup>1</sup> is a tuple  $(S, m)$  where  $S$  is a set and  $m : \mathcal{P}(S) \rightarrow [0, 1]$  is a mass function. As every mass function can equivalently be represented by a belief function and vice versa, a *DS-structure* can also be represented as a tuple  $(S, \text{bel})$  where  $\text{bel} : \mathcal{P}(S) \rightarrow [0, 1]$  is a belief function. Central to Dempster-Shafer theory is the rule of combination of beliefs (representing e.g. evidence, hints, or preferences) (see [19]). Given two *DS-structures*  $(S, m_1)$  and  $(S, m_2)$  over a set  $S$ , Dempster-Shafer rule for combining beliefs provides a procedure to compute a new *DS-structure*  $(S, m_{1 \oplus 2})$

<sup>1</sup> *DS-structures* are also known in the literature as tuples  $(S, \text{bel}, \pi)$  (cf. [6]) where  $\pi$  is a valuation. This valuation is necessary to show [6, Proposition 3.4] which shows the equivalence between arbitrary and finite *DS-structures*. Since in this paper we restrict ourselves to finite structures the valuation here is redundant.

that represents the aggregate mass obtained by aggregating mass functions  $m_1$  and  $m_2$ . To compute the aggregated mass function, one combines the mass functions  $m_1$  and  $m_2$  as follows:

$$m_{1 \oplus 2} : \mathcal{P}(S) \rightarrow [0, 1] \quad (6)$$

$$X \mapsto \begin{cases} 0 & \text{if } X = \emptyset \\ \frac{\sum \{m_1(X_1) \cdot m_2(X_2) \mid X_1 \cap X_2 = X\}}{\sum \{m_1(X_1) \cdot m_2(X_2) \mid X_1 \cap X_2 \neq \emptyset\}} & \text{otherwise.} \end{cases}$$

Aggregate mass function corresponds to the aggregate belief obtained by combining the information obtained from  $m_1$  and  $m_2$ . Dempster-Shafer rule allows to combine possibly conflicting beliefs proceeding from multiple independent sources. Intuitively, the combined belief according to the Dempster-Shafer rule highlights the converging portions of evidence, and downplays the conflicting ones.

Recall that a  $\sigma$ -algebra on a set  $S$  is a collection  $\Sigma$  of subsets of  $S$  that includes  $S$  itself, is closed under complement, and is closed under countable unions. A *probability space* (cf. [6, Section 2, page 3]) is a structure  $\mathbb{X} = (S, \mathbb{A}, \mu)$  where  $S$  is a nonempty (finite) set,  $\mathbb{A}$  is a  $\sigma$ -algebra on  $S$ , and  $\mu : \mathbb{A} \rightarrow [0, 1]$  is a countably additive probability measure. Let  $e : \mathbb{A} \hookrightarrow \mathcal{P}(S)$  denote the natural embedding of  $\mathbb{A}$  into the powerset algebra of  $S$ . Any  $\mu$  as above induces the *inner* and *outer measures*  $\mu_*, \mu^* : \mathcal{P}(S) \rightarrow [0, 1]$  (cf. [6, Section 2, page 4]), respectively defined as

$$\mu_*(Z) := \sup\{\mu(b) \mid b \in \mathbb{A} \text{ and } e(b) \subseteq Z\} \quad \text{and} \quad \mu^*(Z) := \inf\{\mu(b) \mid b \in \mathbb{A} \text{ and } Z \subseteq e(b)\}. \quad (7)$$

By construction,  $\mu_*(e(b)) = \mu(b) = \mu^*(e(b))$  for every  $b \in \mathbb{A}$  and  $\mu^*(Z) = 1 - \mu_*(Z)$  for every  $Z \subseteq S$ . Moreover, for every probability space  $\mathbb{X} = (S, \mathbb{A}, \mu)$ , the inner (resp. outer) measure induced by  $\mu$  is a belief (resp. plausibility) function on  $S$  (cf. [6, Proposition 3.1]). For more details on probability spaces, we refer the reader to [13].

*Order-theoretic analysis.* In a finite probability space  $\mathbb{X}$  as above, the natural embedding  $e : \mathbb{A} \hookrightarrow \mathcal{P}(S)$  is a *complete* lattice homomorphism (in fact, it is a complete Boolean algebra homomorphism, but in the context of Boolean algebras, these two notions collapse). Hence, the right and left adjoints of  $e$  exist, denoted  $\iota, \gamma : \mathcal{P}(S) \rightarrow \mathbb{A}$  respectively, and defined as

$$\iota(Y) := \bigcup \{a \in \mathbb{A} \mid e(a) \subseteq Y\} \quad \text{and} \quad \gamma(Y) := \bigcap \{a \in \mathbb{A} \mid Y \subseteq e(a)\}. \quad (8)$$

LEMMA 2.1. *For every finite probability space  $\mathbb{X} = (S, \mathbb{A}, \mu)$ , and every  $Y \in \mathcal{P}(S)$ ,*

$$\mu_*(Y) = \mu(\iota(Y)) \quad \text{and} \quad \mu^*(Y) = \mu(\gamma(Y)). \quad (9)$$

PROOF. We only show the first identity. From the definitions of  $\mu_*, \iota$  and the additivity of  $\mu$ , we get:  $\mu_*(Y) = \bigvee \{\mu(a) \mid a \in \mathbb{A} \text{ and } e(a) \subseteq Y\} = \mu(\bigcup \{a \mid a \in \mathbb{A} \text{ and } e(a) \subseteq Y\}) = \mu(\iota(Y))$ .  $\square$

The next proposition is an algebraic reformulation of [6, Theorem 3.3].

THEOREM 2.2. *For any belief function  $\text{bel} : \mathcal{P}(S) \rightarrow [0, 1]$  on a finite set  $S$ , there exists a finite probability space  $\mathbb{X} = (S', \mathbb{A}, \mu)$  and a Boolean algebra embedding  $h : \mathcal{P}(S) \hookrightarrow \mathcal{P}(S')$  such that  $\text{bel}(X) = \mu_*(h(X))$ .*

PROOF. Let  $S' := \{(X, u) \mid X \subseteq S \text{ and } u \in X\}$ , and let  $\mathbb{A}$  be the Boolean subalgebra of  $\mathcal{P}(S')$  generated by  $\{X^* \mid X \in \mathcal{P}(S)\}$ , where  $X^* := \{(X, u) \mid u \in X\}$  for every  $X \in \mathcal{P}(S)$ . Since  $S'$  is finite - as discussed above - we can assume that  $\text{bel}$  arises from a mass function  $m$  on  $\mathcal{P}(S)$ .

Notice that, for every  $X, Y \in \mathcal{P}(S)$ , if  $X \neq Y$ , then  $X^* \cap Y^* = \emptyset$ . Hence, the elements  $\{X^* \mid X \in \mathcal{P}(S)\}$  are the atoms of  $\mathbb{A}$ . Therefore, we can define the probability measure  $\mu : \mathbb{A} \rightarrow [0, 1]$  by taking  $\mu(X^*) := m(X)$  for any  $X \in \mathcal{P}(S)$ , and then extending it by additivity to the whole domain of  $\mathbb{A}$ .

Let  $h : \mathcal{P}(S) \rightarrow \mathcal{P}(S')$  be defined by the assignment  $h(X) := \{(Y, u) \in S' \mid u \in X\}$ . It is routine to check that  $h$  is an injective Boolean algebra homomorphism.

Finally, let us show that  $\mu_*(h(X)) = \text{bel}(X)$  for any  $X \in \mathcal{P}(S)$ . Notice that we have

$$\mu_*(h(X)) = \mu(\iota(h(X))) = \mu\left(\bigcup\{a \in \mathbb{A} \mid e(a) \subseteq h(X)\}\right) = \mu\left(\bigcup\{Y^* \mid Y \in \mathcal{P}(S) \text{ and } Y^* \subseteq h(X)\}\right).$$

Indeed, since  $\mathbb{A}$  is a finite Boolean algebra, every  $a \in \mathbb{A}$  is join-generated by the atoms below it. Since  $Y^* \subseteq h(X)$  iff  $Y \subseteq X$  and since every two distinct generators are disjoint, we have that  $\mu(W) = \sum_{Y \subseteq X} \mu(Y^*) = \sum_{Y \subseteq X} m(Y) = \text{bel}(X)$ , as required.  $\square$

### 3 CONCEPTUAL DS-STRUCTURES AND CONCEPTUAL PROBABILITY SPACES

In this section, we generalise the result of [6, Theorem 3.3] from probability spaces to formal concepts. In Section 3.1, we provide preliminaries on formal concepts, introduce conceptual DS-structures and generalise the notions of belief functions and probability spaces for conceptual DS-structures. In Section 3.2, we prove that belief and plausibility functions on conceptual DS-structures can be represented as the inner and outer measures of some probability space. We provide both a purely algebraic proof and a frame theoretic proof of that result. In Section 3.3, we show how to adapt Dempster-Shafer combination of evidence to formal concepts.

#### 3.1 Preliminaries and definitions

*Formal contexts and their concept lattices.* A formal context [7] is a structure  $\mathbb{P} = (A, X, I)$  such that  $A$  and  $X$  are sets, and  $I \subseteq A \times X$  is a binary relation. Formal contexts can be thought of as abstract representations of databases, where elements of  $A$  and  $X$  represent objects and features, respectively, and the relation  $I$  records whether a given object has a given feature. Every formal context as above induces maps  $(\cdot)^\uparrow : \mathcal{P}(A) \rightarrow \mathcal{P}(X)$  and  $(\cdot)^\downarrow : \mathcal{P}(X) \rightarrow \mathcal{P}(A)$ , respectively defined by the assignments

$$B^\uparrow := \{x \in X \mid \forall a(a \in B \Rightarrow aIx)\} \quad \text{and} \quad Y^\downarrow := \{a \in A \mid \forall x(x \in Y \Rightarrow aIx)\}. \quad (10)$$

A formal concept of  $\mathbb{P}$  is a pair  $c = (\llbracket c \rrbracket, \llbracket c \rrbracket)$  such that  $\llbracket c \rrbracket \subseteq A$ ,  $\llbracket c \rrbracket \subseteq X$ , and  $\llbracket c \rrbracket^\uparrow = \llbracket c \rrbracket$  and  $\llbracket c \rrbracket^\downarrow = \llbracket c \rrbracket$ . A subset  $B \subseteq A$  (resp.  $Y \subseteq X$ ) is said to be *closed* if  $B = B^{\uparrow\downarrow}$  (resp.  $Y = Y^{\downarrow\uparrow}$ ). The set of objects  $\llbracket c \rrbracket$  is intuitively understood as the *extension* of the concept  $c$ , while the set of features  $\llbracket c \rrbracket$  is understood as its *intension*. The set  $L(\mathbb{P})$  of the formal concepts of  $\mathbb{P}$  can be partially ordered as follows: for any  $c, d \in L(\mathbb{P})$ ,

$$c \leq d \quad \text{iff} \quad \llbracket c \rrbracket \subseteq \llbracket d \rrbracket \quad \text{iff} \quad \llbracket d \rrbracket \subseteq \llbracket c \rrbracket. \quad (11)$$

With this order,  $L(\mathbb{P})$  is a complete lattice, the *concept lattice*  $\mathbb{P}^+$  of  $\mathbb{P}$ . As is well known, any complete lattice  $\mathbb{L}$  is isomorphic to the concept lattice  $\mathbb{P}^+$  of some formal context  $\mathbb{P}$ . A formal context  $\mathbb{P}$  is *finite* if its associated concept lattice  $\mathbb{P}^+$  is a finite lattice.<sup>2</sup>

*Conceptual DS-structures and conceptual probability spaces.* The notions of DS-structures and probability spaces can be generalized from sets to formal contexts as follows.

*Definition 3.1.* If  $\mathbb{P} = (A, X, I)$  is a (finite) formal context, a *mass function* on  $\mathbb{P}$  is a map  $m : \mathbb{P}^+ \rightarrow [0, 1]$  such that  $\sum_{c \in \mathbb{P}^+} m(c) = 1$ , and if  $\llbracket \perp \rrbracket = \emptyset$  then  $m(\perp) = 0$ .

A *conceptual DS-structure* is a tuple  $\mathbb{D} = (\mathbb{P}, m)$  such that  $\mathbb{P}$  is finite formal context, and  $m$  is a mass function on  $\mathbb{P}$ .

<sup>2</sup>Notice that if  $\mathbb{P} = (A, X, I)$  is such that  $A$  and  $X$  are finite sets then  $\mathbb{P}^+$  is a finite lattice, but the converse is not true in general. For instance, if  $\mathbb{P} = (A, X, I)$  gives rise to a finite lattice, then so does  $\mathbb{P}' := (A', X, I')$  where  $A' := A \cup \mathbb{N}$  and  $a'I'x$  iff  $a' \in A$  and  $aIx$ .

Notice that for a formal context  $\mathbb{P} = (A, X, I)$ , the bottom element of  $\mathbb{P}^+$  is defined as  $\perp = (\llbracket \perp \rrbracket, (\lceil \perp \rceil))$ , where  $(\lceil \perp \rceil) := X$  and  $(\llbracket \perp \rrbracket) := (\lceil \perp \rceil)^\downarrow = \{a \in A \mid \forall x(aIx)\}$ . Hence, the extension of  $\perp$  might in some cases be nonempty. If so, it is implausible to require the mass of  $\perp$  to always be zero. This explains the requirement that  $m(\perp) = 0$  applies only if  $(\llbracket \perp \rrbracket) = \emptyset$ .

Belief and plausibility functions arise from conceptual DS-structures as follows.

*Definition 3.2.* For any conceptual DS-structure  $\mathbb{D} = (\mathbb{P}, m)$ , let  $\text{bel}_m : \mathbb{P}^+ \rightarrow [0, 1]$  and  $\text{pl}_m : \mathbb{P}^+ \rightarrow [0, 1]$  be defined by the following assignments: for every  $c \in \mathbb{P}^+$ ,

$$\text{bel}_m(c) := \sum_{c' \leq c} m(c') \quad \text{and} \quad \text{pl}_m(c) := \sum_{(\llbracket c' \wedge c \rrbracket) \neq \emptyset} m(c'). \quad (12)$$

*Definition 3.3.* A *conceptual probability space* is a structure  $\mathbb{X} = (\mathbb{P}, \mathbb{A}, \mu)$  where  $\mathbb{P}$  is a finite formal context,  $\mathbb{A}$  is a  $\sigma$ -algebra of concepts of  $\mathbb{P}$ , i.e. a lattice embedding  $e : \mathbb{A} \hookrightarrow \mathbb{P}^+$  exists of  $\mathbb{A}$  into the concept lattice of  $\mathbb{P}$ , and  $\mu : \mathbb{A} \rightarrow [0, 1]$  is a countably additive probability measure.

In any conceptual probability space  $\mathbb{X}$  as above, the embedding  $e : \mathbb{A} \hookrightarrow \mathbb{P}^+$  is a *complete* lattice homomorphism, and hence, similarly to the Boolean setting, the right and left adjoints of  $e$  exist, denoted  $\iota, \gamma : \mathbb{P}^+ \rightarrow \mathbb{A}$  respectively, and defined as

$$\iota(c) := \bigvee \{a \in \mathbb{A} \mid e(a) \leq c\} \quad \text{and} \quad \gamma(c) := \bigwedge \{a \in \mathbb{A} \mid c \leq e(a)\}. \quad (13)$$

Using these maps, we can define the *inner* and *outer measures*  $\mu_*, \mu^* : \mathbb{P}^+ \rightarrow [0, 1]$  as follows: for every  $c \in \mathbb{P}^+$ ,

$$\mu_*(c) = \mu(\iota(c)) \quad \text{and} \quad \mu^*(c) = \mu(\gamma(c)). \quad (14)$$

### 3.2 Representing conceptual DS-structures as conceptual probability spaces

The aim of this section is to prove Theorem 3.4. We provide both a purely algebraic proof and a frame theoretic proof of that result. The former highlights why the construction provides belief and plausibility functions, while the latter allows the reader to understand the structure of conceptual probability space on which the inner and outer measures are interpreted.

**THEOREM 3.4.** *For any conceptual DS-structure  $\mathbb{D} = (\mathbb{P}, m)$  there exists a finite conceptual probability space  $\mathbb{X} = (\mathbb{P}', \mathbb{A}, \mu)$ , and a meet-preserving embedding  $h : \mathbb{P}^+ \hookrightarrow \mathbb{P}'^+$  such that, for every  $c \in \mathbb{P}^+$ , we have  $\text{bel}_m(c) = \mu_*(h(c))$  and  $\text{pl}_m(c) = \mu^*(h(c))$ .*

**Algebraic proof of Theorem 3.4.** Let  $\mathbb{D} = (\mathbb{P}, m)$  be a finite conceptual DS-structure. Let  $\mathbb{P}^+$  be the lattice of concepts associated to the formal context  $\mathbb{P}$ . Notice that  $\mathbb{P}^+$  is finite. By definition, we have  $m : \mathbb{P}^+ \rightarrow [0, 1]$  such that  $\sum_{a \in \mathbb{P}^+} m(a) = 1$ .

For every  $a \in \mathbb{P}^+$ , let  $\mathbb{L}_a := \{b \in \mathbb{P}^+ \mid b \leq a\}$ .  $\mathbb{L}_a$  is a sublattice of  $\mathbb{P}^+$ . For every  $b \in \mathbb{P}^+$ , let  $b_a \in \mathbb{L}_a$  be the element such that  $b_a = b \wedge a$ . Let  $\mathbb{L}' := \prod_{a \in \mathbb{A}} \mathbb{L}_a$  be the product of these lattices. For every  $b \in \mathbb{P}^+$ , let  $b^* \in \mathbb{L}'$  be defined as follows, for every  $a \in \mathbb{P}^+$ ,

$$b^*(a) = \begin{cases} b & \text{if } b = a, \\ \perp & \text{otherwise.} \end{cases} \quad (15)$$

Let us show that the sublattice  $\mathbb{A}$  generated by  $\{b^* \in \mathbb{L}' \mid b \in \mathbb{P}^+\}$  is a Boolean algebra. Notice that  $\{b^* \in \mathbb{L}' \mid b \in \mathbb{P}^+\}$  are exactly the atoms of  $\mathbb{A}$ . Hence, every element  $c \in \mathbb{A}$  can be written as  $\bigvee_{b \in S} b^*$  for some  $S \subseteq \mathbb{P}^+$ . Define  $\neg c := \bigvee_{b \in \mathbb{P}^+ \setminus S} b^*$ . It's immediate that  $\neg$  is a Boolean negation. This completes the proof that  $\mathbb{A}$  is a Boolean algebra. Let  $\mathbb{P}'$  be a finite formal context associated to  $\mathbb{L}'$ . Hence,  $\mathbb{A}$  is trivially a  $\sigma$ -algebra of concepts of  $\mathbb{P}'$ . Let  $\mu : \mathbb{A} \rightarrow [0, 1]$  be defined as follows. For every  $b \in \mathbb{P}^+$ , we take  $\mu(b^*) := m(b)$ . Then, we extend the map  $\mu$  using the fact that every  $a \in \mathbb{A}$  is the join of the  $b^*$  below it and the fact that  $\mu$  is additive. Then  $\mathbb{X} := (\mathbb{P}', \mathbb{A}, \mu)$  is a finite conceptual

probability space. The embedding  $e : \mathbb{A} \rightarrow \mathbb{L}'$  is the natural embedding that sends each element in  $\mathbb{A}$  to its corresponding element in  $\mathbb{L}'$ .

Let  $h : \mathbb{P}^+ \rightarrow \mathbb{L}'$  be such that

$$h(b)(a) = b_a = b \wedge a. \quad (16)$$

For every  $a, c, d \in \mathbb{P}^+$ , we have

$$[h(c) \wedge h(d)](a) = c_a \wedge d_a = (c \wedge a) \wedge (d \wedge a) = (c \wedge d) \wedge a = h(c \wedge d)(a).$$

Hence,  $h(c) \wedge h(d) = h(c \wedge d)$  and  $h$  is meet-preserving.

Let us show that  $\text{bel}(c) = \mu_*(h(c))$  for every  $c \in \mathbb{P}^+$ . Since  $\mathbb{A}$  is an atomic Boolean algebra, every element is equal to the join of the atoms below it. Furthermore, notice that  $d \leq c$  if and only if  $d^* \leq h(c)$ . Therefore, we have:

$$\begin{aligned} \mu_*(h(c)) &= \mu(u(h(c))) = \mu\left(\bigvee \{a \in \mathbb{A} \mid e(a) \leq h(c)\}\right) \\ &= \mu\left(\bigvee \{d^* \in \mathbb{A} \mid d \in \mathbb{P}^+ \text{ and } d^* \leq h(c)\}\right) \\ &\quad \text{(because each } a \in \mathbb{A} \text{ is equal to the join of the atoms below it)} \\ &= \mu\left(\bigvee \{d^* \in \mathbb{A} \mid d \leq c\}\right) \\ &= \sum \{\mu(d^*) \mid d \leq c\} && \text{(because } \mu \text{ is additive)} \\ &= \sum \{m(d) \mid d \leq c\} && \text{(by definition of } \mu) \\ &= \text{bel}_m(c). && \text{(by definition of bel)} \end{aligned}$$

Finally, let us show that  $\text{pl}(c) = \mu^*(h(c))$  for every  $c \in \mathbb{P}^+$ . Let  $U \subseteq \mathbb{P}^+$  and  $c \in \mathbb{P}^+$ . Notice that if  $h(c)(d) \neq \perp$ , then  $h(c)(e) = c \wedge e \leq \bigvee_{d \in U} d^*(e)$  if and only if  $e \in U$ . Indeed,  $\bigvee_{d \in U} d^*(e) = e$  if  $e \in U$  and  $\perp$  otherwise. We have:

$$\begin{aligned} \bigwedge \left\{ \bigvee_{d \in U} d^* \mid U \subseteq \mathbb{P} \text{ and } h(c) \leq \bigvee_{d \in U} d^* \right\} &= \bigwedge \left\{ \bigvee_{d \in U} d^* \mid U \subseteq \mathbb{P} \text{ and } d \wedge c \neq \perp \text{ implies } d \in U \right\} \\ &= \bigvee \{d^* \mid d \wedge c \neq \perp\}. \end{aligned} \quad (17)$$

The last equality holds because  $\mathbb{A}$  is a Boolean algebra. Hence, we have:

$$\begin{aligned} \mu^*(h(c)) &= \mu(\gamma(h(c))) = \mu\left(\bigwedge \{a \in \mathbb{A} \mid h(c) \leq e(a)\}\right) \\ &= \mu\left(\bigwedge \left\{ \bigvee_{d \in U} d^* \mid U \subseteq \mathbb{P} \text{ and } h(c) \leq \bigvee_{d \in U} d^* \right\}\right) \\ &\quad \text{(because each } a \in \mathbb{A} \text{ is equal to the join of the atoms } d^* \text{ below it)} \\ &= \mu\left(\bigvee \{d^* \mid c \wedge d \neq \perp\}\right) && \text{(see (17))} \\ &= \sum \{\mu(d^*) \mid c \wedge d \neq \perp\} && \text{(because } \mu \text{ is additive)} \\ &= \sum \{m(d) \mid c \wedge d \neq \perp\} && \text{(by definition of } \mu) \\ &= \text{pl}_m(c). && \text{(by definition of pl)} \end{aligned}$$



**Frame theoretic proof of Theorem 3.4.** We proceed via a series of lemmas. Let  $\mathbb{P} = (A, X, I)$  be a finite formal context and  $\mathbb{P}^+$  be its lattice of concepts. We can assume without loss of generality that  $X^\downarrow = \emptyset$ . We define the formal context  $\mathbb{P}' = (A', X', I')$  as follows:

- $A' := \{(c, a) \mid c \in \mathbb{P}^+ \text{ and } a \in \llbracket c \rrbracket\}$ ;
- $X' := \{(c, x) \mid c \in \mathbb{P}^+ \text{ and } x \in X\}$ ;
- $(c, a)I'(d, x)$  if and only if  $c \neq d$  or  $aIx$ .

For every  $c \in \mathbb{P}^+$ , let  $c^* = (\{(c, a) \mid a \in \llbracket c \rrbracket\}, \{(c, a) \mid a \in \llbracket c \rrbracket\}^\uparrow)$ .

LEMMA 3.5. *For every  $c \in \mathbb{P}^+$ , the set  $\{(c, a) \mid a \in \llbracket c \rrbracket\}$  is the extension of a formal concept.*

PROOF. Notice that  $\{(c, a) \mid a \in \llbracket c \rrbracket\}^\uparrow = \{(d, x) \in X' \mid d \neq c\} \cup \{(c, x) \in X' \mid x \in \llbracket c \rrbracket\}$ . Since, by assumption,  $X^\downarrow = \emptyset$ , it follows that  $\{(d, x) \in X' \mid d \neq c\}^\downarrow = \{(c, a) \in A' \mid a \in \llbracket c \rrbracket\}$ . Since the map  $(\cdot)^\downarrow$  is antitone,  $\{(c, a) \mid a \in \llbracket c \rrbracket\}^\uparrow \leq \{(d, x) \in X' \mid d \neq c\}^\downarrow = \{(c, a) \in A' \mid a \in \llbracket c \rrbracket\}$ .  $\square$

The lemma above implies that  $c^* \in \mathbb{P}'^+$ . Let  $\mathbb{A}$  be the sub join-semilattice of  $\mathbb{P}'^+$  join-generated by  $\{c^* \mid c \in \mathbb{P}^+\}$ .

LEMMA 3.6. *The lattice  $\mathbb{A}$  is a finite Boolean algebra, generated by the set of its atoms  $\{c^* \mid c \in \mathbb{P}^+\}$*

PROOF. That the generators are atoms follows immediately from the fact that if  $c \neq d$ , then  $\llbracket c^* \rrbracket \cap \llbracket d^* \rrbracket = \emptyset$ . To show that  $\mathbb{A}$  is a Boolean algebra, it is enough to show that for any  $U \subseteq \mathbb{P}^+$ , the set  $\bigcup_{c \in U} \llbracket c^* \rrbracket$  is a closed subset of  $A'$ . We have  $(\bigcup_{c \in U} \llbracket c^* \rrbracket)^\uparrow = \bigcap_{c \in U} \llbracket c^* \rrbracket^\uparrow$ . As discussed in the lemma above,  $\llbracket c^* \rrbracket^\uparrow = \{(d, x) \in X' \mid d \neq c\} \cup \{(c, x) \in X' \mid x \in \llbracket c \rrbracket\}$ . Therefore  $\bigcap_{c \in U} \llbracket c^* \rrbracket^\uparrow \supseteq \{(d, x) \in X' \mid d \notin U\}$ . Since  $X^\downarrow = \emptyset$ , it follows that  $\{(d, x) \in X' \mid d \notin U\}^\downarrow = \{(c, a) \in A' \mid c \in U\} = \bigcup_{c \in U} \llbracket c^* \rrbracket$ . Therefore  $(\bigcup_{c \in U} \llbracket c^* \rrbracket)^\uparrow \leq (\bigcap_{c \in U} \llbracket c^* \rrbracket^\uparrow)^\downarrow \subseteq \bigcup_{c \in U} \llbracket c^* \rrbracket$ , as required.  $\square$

REMARK 1. *The reader familiar with the proof of [6, Theorem 3.3] will notice that the algebra  $\mathbb{P}'^+$  is comparatively as large as the one used to prove [6, Theorem 3.3]. Had we chosen to define  $\mathbb{P}'^+$  in a simpler way, e.g. as the power set Boolean algebra  $\mathcal{P}(P^+)$  over the set of concepts (which, modulo isomorphism, can be identified with the concept lattice of the formal context  $(P^+, P^+, \neq)$ ), we would have run into problems because  $\mathcal{P}(P^+)$  would have forced inner and outer measures, hence belief and plausibility functions, to coincide. Indeed, for the inner and outer measure to be different, there need to be unmeasurable sets as witnesses; however,  $\mathcal{P}(P^+)$  is not large enough to have non-measurable sets.*

Since  $\mathbb{A}$  is a Boolean algebra, we can define the map  $\mu : \mathbb{A} \rightarrow [0, 1]$  first on the generators of  $\mathbb{A}$ , by letting  $\mu(c^*) = m(c)$  for every  $c \in \mathbb{P}^+$ , and uniquely extend it to a measure on  $\mathbb{A}$ . Let  $e : \mathbb{A} \hookrightarrow \mathbb{P}'^+$  be the natural embedding. By construction,  $e$  is a lattice homomorphism, hence the right and left adjoint of  $e$  exist, denoted  $\iota$  and  $\gamma$ , respectively.

Let us define the map  $h : \mathbb{P}^+ \hookrightarrow \mathbb{P}'^+$  as follows: for every  $c \in \mathbb{P}^+$ ,

$$h(c) = (\{(d, a) \in A' \mid a \in \llbracket c \rrbracket\}, \{(d, a) \in A' \mid a \in \llbracket c \rrbracket\}^\uparrow). \quad (18)$$

In the two lemmas below we show that  $h$  is indeed well defined:

LEMMA 3.7.  $\{(d, a) \mid a \in \llbracket c \rrbracket\}^\uparrow = \{(e, x) \in X' \mid x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow\}$ .

PROOF. Left to right inclusion: Assume  $(e, x) \in \{(d, a) \mid a \in \llbracket c \rrbracket\}^\uparrow$ . If  $e \neq d$  for all  $(d, a) \in \{(d, a) \mid a \in \llbracket c \rrbracket\}$ , then  $\llbracket e \rrbracket \cap \llbracket c \rrbracket = \emptyset$ , hence  $x \in (\emptyset)^\uparrow$ . If  $d = e$ , then  $aIx$  for all  $a \in \llbracket e \rrbracket \cap \llbracket c \rrbracket$ , hence  $x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow$ .

Right to left inclusion: Let  $(e, x) \in \{(e, x) \in X' \mid x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow\}$  and let  $(e, a) \in \{(d, a) \mid a \in \llbracket c \rrbracket\}$ . Since  $x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow$  by assumption, it follows that  $aIx$ .  $\square$

LEMMA 3.8.  $\{(e, x) \in X' \mid x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow\}^\downarrow \subseteq \{(d, a) \in A' \mid x \in \llbracket c \rrbracket\}$

PROOF. Let  $(d, a)$  be such that  $a \notin \llbracket c \rrbracket$ . Then  $a \notin \llbracket c \rrbracket \cap \llbracket d \rrbracket$  and there exists  $x_0 \in (\llbracket d \rrbracket \cap \llbracket c \rrbracket)^\uparrow$  such that  $(a, x_0) \notin I$ . Hence,  $(d, x_0) \in \{(e, x) \in X' \mid x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow\}$  and  $(d, a) \notin \{(e, x) \in X' \mid x \in (\llbracket e \rrbracket \cap \llbracket c \rrbracket)^\uparrow\}^\downarrow$ .  $\square$

LEMMA 3.9. *The map  $h$  defined above is a meet-preserving embedding.*

PROOF. Let  $c, d \in \mathbb{P}^+$ . If  $c \neq d$ , it is immediate that  $h(c) \neq h(d)$ . Now, let us show that  $h$  is meet-preserving:

$$\begin{aligned} \llbracket h(c) \rrbracket \cap \llbracket h(d) \rrbracket &= \{(e, a) \mid x \in \llbracket c \rrbracket\} \cap \{(e, a) \mid x \in \llbracket d \rrbracket\} \\ &= \{(e, a) \mid x \in \llbracket c \rrbracket \cap \llbracket d \rrbracket\} = \{(e, a) \mid x \in \llbracket c \wedge d \rrbracket\} = \llbracket h(c \wedge d) \rrbracket. \end{aligned}$$

$\square$

Let us show that  $\text{bel}(c) = \mu_*(h(c))$  for every  $c \in \mathbb{P}^+$ . Since  $\mathbb{A}$  is an atomic Boolean algebra, every element is equal to the join of the atoms below it. Furthermore, notice that  $d \leq c$  if and only if  $d^* \leq h(c)$ . Therefore, we have:

$$\begin{aligned} \mu_*(h(c)) &= \mu(\iota(h(c))) = \mu\left(\bigvee \{a \in \mathbb{A} \mid a \leq h(c)\}\right) \\ &= \mu\left(\bigvee \{d^* \in \mathbb{A} \mid d \in \mathbb{P}^+ \text{ and } d^* \leq h(c)\}\right) \\ &\quad \text{(because each } a \in \mathbb{A} \text{ is equal to the join of the atoms below it)} \\ &= \mu\left(\bigvee \{d^* \in \mathbb{A} \mid d \leq c\}\right) = \Sigma\{\mu(d^*) \mid d \leq c\} = \Sigma\{m(c) \mid d \leq c\} = \text{bel}_m(V(p)). \end{aligned}$$

Finally, let us show that  $\text{pl}(c) = \mu^*(h(c))$  for every  $c \in \mathbb{P}^+$ . Let  $U \subseteq \mathbb{P}^+$ ,  $c \in \mathbb{P}^+$  and  $(d, a) \in A'$ . If  $(d, a) \in h(c)$ , then  $(d, a) \in \bigvee_{d \in U} d^*$  if and only if  $d \in U$ . Furthermore,  $(d, a) \in h(c)$  if and only if  $a \in \llbracket c \rrbracket \cap \llbracket d \rrbracket$ . Hence,  $(d, a) \in h(c)$  implies that  $\llbracket c \rrbracket \cap \llbracket d \rrbracket \neq \emptyset$ . We have:

$$\begin{aligned} \bigwedge \left\{ \bigvee_{d \in U} d^* \mid U \subseteq \mathbb{P} \text{ and } h(c) \leq \bigvee_{d \in U} d^* \right\} &= \bigwedge \left\{ \bigvee_{d \in U} d^* \mid \llbracket d \rrbracket \cap \llbracket c \rrbracket \neq \emptyset \text{ implies } d \in U \right\} \\ &= \bigvee \{d^* \mid \llbracket d \rrbracket \cap \llbracket c \rrbracket \neq \emptyset\}. \end{aligned} \quad (19)$$

The last equality holds because  $\mathbb{A}$  is a Boolean algebra. Hence, we have:  $\bigwedge \{a \in \mathbb{A} \mid c \leq e(a)\}$

$$\begin{aligned} \mu^*(h(c)) &= \mu(\gamma(h(c))) = \mu\left(\bigwedge \{a \in \mathbb{A} \mid h(c) \leq e(a)\}\right) \\ &= \mu\left(\bigwedge \left\{ \bigvee_{d \in U} d^* \mid U \subseteq \mathbb{P} \text{ and } h(c) \leq \bigvee_{d \in U} d^* \right\}\right) \\ &\quad \text{(because each } a \in \mathbb{A} \text{ is equal to the join of the atoms } d^* \text{ below it)} \\ &= \mu\left(\bigvee \{d^* \mid \llbracket c \rrbracket \cap \llbracket d \rrbracket \neq \emptyset\}\right) \quad \text{(see (19))} \\ &= \Sigma\{\mu(d^*) \mid \llbracket c \rrbracket \cap \llbracket d \rrbracket \neq \emptyset\} \quad \text{(because } \mu \text{ is additive)} \\ &= \Sigma\{m(d) \mid \llbracket c \rrbracket \cap \llbracket d \rrbracket \neq \emptyset\} = \text{pl}_m(c). \end{aligned}$$

This concludes the proof of Theorem 3.4.

### 3.3 Combination of evidence

Here, we propose a generalized version of Dempster-Shafer rule for concepts. Let  $\mathbb{P} = (A, X, I)$  be a finite formal context and  $m_1, m_2$  be two mass functions on  $\mathbb{P}$ . We build the combined mass function  $m_{1 \oplus 2}$  following Dempster-Shafer's procedure. For all  $c_1, c_2 \in \mathbb{P}^+$ , if  $\sum \{m_1(c_1) \cdot m_2(c_2) \mid \llbracket c_1 \wedge c_2 \rrbracket \neq \emptyset\} \neq 0$ , then the combined mass function  $m_{1 \oplus 2}$  is defined as follows:

$$m_{1 \oplus 2} : \mathbb{P}^+ \rightarrow [0, 1] \quad (20)$$

$$c \mapsto \begin{cases} 0 & \text{if } \llbracket c \rrbracket = \emptyset \\ \frac{\sum \{m_1(c_1) \cdot m_2(c_2) \mid c_1 \wedge c_2 = c\}}{\sum \{m_1(c_1) \cdot m_2(c_2) \mid \llbracket c_1 \wedge c_2 \rrbracket \neq \emptyset\}} & \text{otherwise.} \end{cases}$$


It is straightforward to verify that  $m_{1 \oplus 2}$  is a mass function on  $\mathbb{P}$ .

## 4 EXAMPLE: PREFERENCE AGGREGATION

In this section, we illustrate how the mass functions can be used to encode preferences and how Dempster-Shafer combination of evidence can be used to aggregate them. In Section 5, we show how Dempster-Shafer theory can be used to make categorisation decision. Namely to answer the question: to which category does an unknown object belong?

*The scenario.* Alice and Bob wish to watch a movie together, and query a movie database by expressing their independent (graded) preferences. The software interface interprets their preferences as mass functions on the database (modelled as a formal context), and combines them using the rule of Section 3.3.

**Case 1. Conflict with no resolution.** Alice wishes to watch a romantic comedy and Bob a chainsaw horror movie. The database they are querying, and its associated concept lattice, look as follows:



The diagram on the left represents the database with movies  $a, b$  and  $c$  and features  $x, y$  and  $z$ . The line between  $a$  and  $x$  means that the movie  $a$  has feature  $f$ . The lattice on the right represents the lattice of concepts associated to the database.

The system interprets the categories 'romantic comedy' and 'chainsaw horror movie' as the formal concepts  $c_1$  and  $c_3$ , respectively, and encodes Alice and Bob's preferences as the following mass functions:

	$c_{\perp}$	$c_1$	$c_2$	$c_3$	$c_{\top}$
$m_1$	0	0.9	0	0	0.1
$m_2$	0	0	0	0.9	0.1

The combination of the two masses above indicates that there is no way to accommodate both preferences in the database:

	$c_{\perp}$	$c_1$	$c_2$	$c_3$	$c_{\top}$
$m_{1\oplus 2}$	0	0.47	0	0.47	0.06


**Case 2. Reaching a compromise.** Alice wishes to watch a romantic comedy but would consider an action movie, while Bob much prefers a chainsaw horror movie but would consider an action movie. The database they are querying, and its associated concept lattice, are as in the case above. The system interprets the categories ‘romantic comedy’, ‘action movie’ and ‘chainsaw horror movie’ as the formal concepts  $c_1$ ,  $c_2$  and  $c_3$ , respectively, and encodes Alice and Bob’s preferences as the following mass functions:

	$c_{\perp}$	$c_1$	$c_2$	$c_3$	$c_{\top}$
$m_1$	0	0.9	0.1	0	0
$m_2$	0	0	0.1	0.9	0

The combination of the two masses above disregards the conflict and highlights the convergence, as in the original Dempster-Shafer setting:

	$c_{\perp}$	$c_1$	$c_2$	$c_3$	$c_{\top}$
$m_{1\oplus 2}$	0	0	1	0	0

**Case 3. Solution to the conflict.** Alice wishes to watch a romantic comedy and Bob an action movie. This time, the database they are querying, and its associated concept lattice, look as follows:



That is, this database contains an object  $c$  that happens to be both a romantic comedy and an action movie. The system interprets the categories ‘romantic comedy’, and ‘action movie’ as the formal concepts  $c_1$  and  $c_3$ , respectively, and encodes Alice and Bob’s preferences as the following mass functions:

	$c_{\perp}$	$c_1$	$c_3$	$c_{\top}$
$m_1$	0	0.9	0	0.1
$m_2$	0	0	0.9	0.1


The combination of the two masses points at the solution that simultaneously satisfies Alice and Bob’s preferences:

	$c_{\perp}$	$c_1$	$c_3$	$c_{\top}$
$m_{1\oplus 2}$	0.81	0.09	0.09	0.01


**5 EXAMPLE: CATEGORIZATION THEORY**

In the present section, we discuss how the basic tools of Dempster-Shafer theory on formal contexts and their associated concept lattices introduced in the previous sections can be applied to the formalization of categorization decisions in various areas. The application we propose here builds on [2, 3], where formal contexts are regarded as abstract representations of databases (e.g. of market products and their relevant features) and their associated formal concepts as categories, each admitting both an extensional characterization (in terms of the objects that are members of the given category) and an intensional characterization (in terms of the features that are part of the description of the given category).

*Music databases.* Consider the problem of categorizing a given song  $S$  on the base of user-inputs. The categorization procedure consists in aggregating the replies of users to a questionnaire about  $S$ . The questionnaire makes reference to the objects of a database, which, for the sake of simplicity, we represent as the following formal context  $\mathbb{P} = (A, X, I)$ , with  $A = \{a, b, c\}$  a given set of songs ( $a = A\text{-ha} - Take\ on\ me$ ,  $b = Beyonce - Crazy\ in\ love$ ,  $c = Marvin\ Gaye - Sexual\ healing$ ) and  $X = \{w, x, y, z\}$  a set of relevant features:  $w = keyboards$ ,  $x = upbeat\ tempo$ ,  $y = gospel\text{-}trained\ singers$ ,  $z = whispering\ voices$ .



The questionnaire makes also reference to the (names of) the categories-as-formal-concepts arising from  $\mathbb{P}$ , i.e. the elements of the following lattice  $\mathbb{C}$ :



Specifically, the questionnaire contains statements of the following types:

- “Song  $S$  is similar to song  $e$ ”, for  $e \in A$ ;
- “Song  $S$  belongs to category  $C$ ”, for  $C \in \mathbb{C}$ .

Each user chooses one or more such statements and grades it on the following scale:

$$\{0, 0.1, 0.2, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1\}.$$

Three users give the following responses:

- User 1: “Song  $S$  is similar to  $a$ ”, graded 0.2.
- User 2: “Song  $S$  is similar to  $a$ ” graded 0.6, and “Song  $S$  is similar to  $b$ ” graded 0.6, and “Song  $S$  belongs to E-Pop” graded 0, and “Song  $S$  belongs to Pop-R&B” graded 0.
- User 3: “Song  $S$  belongs to Pop-R&B” graded 0.2 and “Song  $S$  belongs to Funk” graded 0.6 and “Song  $S$  belongs to category  $\perp$ ” graded 0.

*The pieces of evidence.* The users’ responses constitute three pieces of evidence that we will represent as mass functions  $m : \mathbb{C} \rightarrow [0, 1]$ , to each of which we can then associate belief and plausibility functions as follows: for any  $c \in \mathbb{C}$ ,

$$\text{bel}_m(c) = \Sigma\{m(d) \mid d \leq c\} \quad \text{and} \quad \text{pl}_m(c) = \Sigma\{m(d) \mid c \wedge d \neq \perp\}.$$

Notice that, in order for the evidence to represent a mass and not a belief, it needs to specify the probability that an object is in a category without being in any of its subcategories.

- To model User 1’s response, we need a mass function that assigns mass 0.2 to the smallest category containing the song  $a$ , that is, the category that most accurately describes the song  $a$ . This category is the category the extension of which is the closure of the singleton  $\{a\}$ . In our example, this category is E-Pop =  $(a, wx)$ . Hence, this statement translates into the mass function  $m_1 : \mathbb{C} \rightarrow [0, 1]$  that maps E-Pop to 0.2, the category  $\top$  of all songs in the database to 0.8 and all other categories to 0.
- Similarly, User 2’s response translates into the mass function  $m_2 : \mathbb{C} \rightarrow [0, 1]$  that maps the smallest category containing both objects  $a$  and  $b$  (which is the category Pop =  $(ab, x)$ ) to 0.6, the category  $\top$  to 0.4 and the remaining categories to 0.
- Finally, User 3’s response translates into the mass function  $m_3 : \mathbb{C} \rightarrow [0, 1]$  that maps Pop-R&B to 0.2, the category Funk to 0.6, the category  $\top$  to 0.2, and the remaining categories to 0. Notice that  $\perp$  might not be the empty category in general; indeed, by definition, the members of  $\perp$  are the objects that share all the features in  $X$ .

The following table reports the values of the mass functions.

	$\perp$	E-Pop	Pop-R&B	Funk	Pop	R&B	$\top$
$m_1$	0	0.2	0	0	0	0	0.8
$m_2$	0	0	0	0	0.6	0	0.4
$m_3$	0	0	0.2	0.6	0	0	0.2

The following table reports the belief and plausibility functions corresponding to the mass functions above:

	$\perp$	E-Pop	Pop-R&B	Funk	Pop	R&B	$\top$
$\text{bel}_{m_1}$	0	0.2	0	0	0.2	0	1
$\text{pl}_{m_1}$	0	1	0.8	0.8	1	0.8	1
$\text{bel}_{m_2}$	0	0	0	0	0.6	0	1
$\text{pl}_{m_2}$	0	1	1	0.4	0.6	1	1
$\text{bel}_{m_3}$	0	0	0.2	0.6	0.2	0.8	1
$\text{pl}_{m_3}$	0	0.2	0.4	0.8	0.4	1	1

*Combining pieces of evidence.* Using the combination rule (20), we get the following aggregated mass function, and its associated belief and plausibility functions:

	$\perp$	E-Pop	Pop-R&B	Funk	Pop	R&B	$\top$
$m_{1\oplus 2\oplus 3}$	0	0.07	0.29	0.35	0.17	0	0.12
$\text{bel}_{m_{1\oplus 2\oplus 3}}$	0	0.07	0.29	0.35	0.54	0.64	1
$\text{pl}_{m_{1\oplus 2\oplus 3}}$	0	0.36	0.58	0.46	0.65	0.93	1

*Analysis of the result.* Dempster's rule of combination treats every user's piece of evidence as a constraint for other users' pieces of evidence. For example, if User 1 reports that  $S$  is definitely a Pop song ( $m_1(\text{Pop}) = 1$ ) and User 2 that  $S$  is definitely an R&B song ( $m_2(\text{R\&B}) = 1$ ), then the corresponding aggregated mass assignments yields  $m_{1\oplus 2}(\text{Pop-R\&B}) = 1$ , suggesting that  $S$  can be definitely categorized as a member of the greatest common subcategory of Pop and R&B.

Notice that, in the example above, individual mass values for Funk and Pop are identical, hence one cannot a priori tell which category best describes song  $S$ . However, the aggregated mass function assigns Funk a greater value than Pop. Hence, combining evidence provides us with more information and allows for a more accurate categorization of the given song  $S$ .

Notice also that  $m_1(\top) = 0.8$  is a much higher value than  $m_2(\top)$  and  $m_3(\top)$ . Saying that song  $S$  belongs to  $\top$  provides the least accurate categorization of  $S$ , which implies that User 1's response has the smallest impact on the combined evidence. Indeed, when combining mass functions  $m_1$  and  $m_2$ , if one of them, say  $m_2$ , is such that  $m_2(\top) = 1$ , then the combined mass function  $m_{1\oplus 2}$  coincides with  $m_1$ , that is,  $m_2$  provides no information.

Notice that if  $m_i(\top) = 0$  for any  $i = 1, 2, 3$  then  $m_{1\oplus 2\oplus 3}(\top) = 0$ . Indeed, if  $C$  is any category for which some mass function  $m$  satisfies  $m(C') = 0$ , for all  $C' \geq C$ , then, on combining it with any other mass function, the combined mass function  $m'$  will also satisfy  $m'(C') = 0$  for all  $C' \geq C$ . This shows that categorization based on combined mass is at least as informative as categorization based on any individual piece of evidence.

Looking at the belief and plausibility functions obtained by combining evidence, one can see that the highest belief and plausibility (while excluding  $\top$ ) are assigned to R&B. This is the case because User 3 provides a more significant piece of evidence than Users 1 and 2 and this piece of evidence supports  $S$  being a member of Pop-R&B and Funk. Hence, in the aggregate, the mass values of Pop-R&B and Funk are higher than the mass values of the other categories. The same reasoning explains why the mass value of Pop is higher than that of E-Pop. Since R&B is a super-category of Pop-R&B and Funk, the value of the combined belief function in R&B turns out to be higher than that of the other categories.

## 6 CONCLUSION

We have introduced a framework which generalizes basic notions and results of Dempster-Shafer theory from predicates to formal concepts, and give preliminary examples showing how some of these notions apply to reasoning and decision-making under uncertainty for categorization problems.

*Understanding belief and plausibility functions on concepts.* As we have seen in the examples presented in this paper the notion of mass function is a very versatile tool to formalize decision-making problems in a variety of cases. In future work, we plan to gain a better understanding of belief and plausibility functions and to apply them in the formalization of concrete situations.

*Towards a logical theory of conceptual evidence.* In this paper we have not pursued an explicitly logical approach; however, the structures introduced in Section 3.1 lend themselves naturally as bases for models of an epistemic/probabilistic logic of categories generalizing the epistemic logics for Dempster-Shafer theory introduced in [8, 18].

## REFERENCES

- [1] W. Conradie, S. Frittella, K. Manoorkar, S. Nazari, A. Palmigiano, A. Tzimoulis, and N.M. Wijnberg. 2019. Rough concepts. *Submitted* (2019). arXiv:1907.00359
- [2] W. Conradie, S. Frittella, A. Palmigiano, M. Piazzai, A. Tzimoulis, and N.M. Wijnberg. 2016. Categories: How I Learned to Stop Worrying and Love Two Sorts. In *Proc. WoLLIC 2016 (LNCS)*, Vol. 9803. 145–164.
- [3] W. Conradie, S. Frittella, A. Palmigiano, M. Piazzai, A. Tzimoulis, and N.M. Wijnberg. 2017. Toward an epistemic-logical theory of categorization. In *Proc. TARK 2017 (EPTCS)*, Vol. 251. 167–186.
- [4] Brian A. Davey and Hilary A. Priestley. 2002. *Introduction to Lattices and Order, Second Edition*. Cambridge University Press. <https://doi.org/10.1017/CBO9780511809088>
- [5] Arthur P Dempster. 1968. A generalization of Bayesian inference. *Journal of the Royal Statistical Society: Series B (Methodological)* 30, 2 (1968), 205–232.
- [6] Ronald Fagin and Joseph Y Halpern. 1991. Uncertainty, belief, and probability. *Computational Intelligence* 7, 3 (1991), 160–173.
- [7] B. Ganter and R. Wille. 2012. *Formal concept analysis: mathematical foundations*. Springer.
- [8] Lluís Godo, Petr Hájek, and Francesc Esteve. 2003. A fuzzy modal logic for belief functions. *Fundamenta Informaticae* 57, 2-4 (2003), 127–146.
- [9] Michel Grabisch. 2008. Belief functions on lattices. *CoRR* abs/0811.3373 (2008).
- [10] Michel Grabisch. 2009. Belief functions on lattices. *International Journal of Intelligent Systems* 24, 1 (2009), 76–95.
- [11] G. Greco, P. Jipsen, K. Manoorkar, A. Palmigiano, and A. Tzimoulis. 2019. Logics for Rough Concept Analysis. In *Proc. ICLA 2019 (LNCS)*, Vol. 11600. 144–159.
- [12] Giuseppe Greco, Fei Liang, Krishna Manoorkar, and Alessandra Palmigiano. 2019. Proper Multi-Type Display Calculi for Rough Algebras. In *Post-proceedings LSFA 2018 (Electr. Notes Theor. Comput. Sci.)*, Vol. 344. 101–118.
- [13] Paul R. Halmos. 1950. *Measure Theory*. Springer-Verlag New York Inc.
- [14] Ewa Orłowska. 1984. A logic of indiscernibility relations. In *Symposium on Computation Theory*. Springer, 177–186.
- [15] Zdzisław Pawlak. 1982. Rough sets. *International journal of computer & information sciences* 11, 5 (1982), 341–356.
- [16] Zdzisław Pawlak. 1984. Rough probability. *Bull. Pol. Acad. Sci. Math* 32 (1984), 607–615.
- [17] Z. Pawlak. 1998. Rough set theory and its applications to data analysis. *Cybernetics & Systems* 29, 7 (1998), 661–688.
- [18] Enrique H Ruspini. 1986. *The logical foundations of evidential reasoning*. SRI International Menlo Park, CA.
- [19] Glenn Shafer. 1976. *A mathematical theory of evidence*. Vol. 42. Princeton university press.
- [20] Peter Walley. 1991. *Statistical Reasoning with Imprecise Probabilities*. Chapman & Hall.
- [21] Yiyu Yao. 2010. Three-way decisions with probabilistic rough sets. *Inf. Sci.* 180, 3 (2010), 341–353. <https://doi.org/10.1016/j.ins.2009.09.021>
- [22] Yiyu Yao. 2020. Three-way granular computing, rough sets, and formal concept analysis. *Int. J. Approx. Reason.* 116 (2020), 106–125. <https://doi.org/10.1016/j.ijar.2019.11.002>
- [23] YY Yao and Tsau Young Lin. 1996. Generalization of rough sets using modal logics. *Intelligent Automation & Soft Computing* 2, 2 (1996), 103–119.
- [24] YY Yao and PJ Lingras. 1998. Interpretations of belief functions in the theory of rough sets. *Information Sciences* 104, 1-2 (1998), 81–106.
- [25] Huilai Zhi, Jianjun Qi, Ting Qian, and Ling Wei. 2019. Three-way dual concept analysis. *Int. J. Approx. Reason.* 114 (2019), 151–165. <https://doi.org/10.1016/j.ijar.2019.08.010>
- [26] Chunlai Zhou. 2013. Belief functions on distributive lattices. *Artif. Intell.* 201 (2013), 1–31. <https://doi.org/10.1016/j.artint.2013.05.003>
- [27] Chunlai Zhou. 2013. Belief functions on distributive lattices. *Artificial Intelligence* 201 (2013), 1–31.