



Deposition of doped and undoped HfO₂ for fast and low energy consumption ferroelectric devices

Jordan Bouaziz, Bertrand Vilquin, Pedro Rojo Romeo, Nicolas Baboux,
Bruno Masenelli

► To cite this version:

Jordan Bouaziz, Bertrand Vilquin, Pedro Rojo Romeo, Nicolas Baboux, Bruno Masenelli. Deposition of doped and undoped HfO₂ for fast and low energy consumption ferroelectric devices. 6th International Conference SENSO Workshop, Jun 2018, Gardanne, France. hal-02506625

HAL Id: hal-02506625

<https://hal.science/hal-02506625>

Submitted on 13 Mar 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Deposition of doped and undoped HfO₂ for fast and low energy consumption ferroelectric devices

Jordan Bouaziz^{1,2}


Bertrand Vilquin¹, Pedro Rojo Romeo¹, Nicolas Baboux², Bruno Masenelli²

¹Université de Lyon, Ecole Centrale de Lyon, Institut des Nanotechnologies de Lyon, CNRS UMR5270

²Université de Lyon, INSA de Lyon, Institut des Nanotechnologies de Lyon, CNRS UMR5270, 7 avenue Capelle, 69621 Villeurbanne cedex, France


IoT sensor node requires edge computing, which means processing data at the source. These systems need highly energy efficient microprocessor units (MCU) using embedded non-volatile memories (eNVM). However eFLASH technology is limited by low write speed, high power and low endurance. Alternative fast, low power and high endurance eNVM could greatly enhance energy efficiency. FeRAM has the highest endurance of all emerging NVMs. However perovskite based eFeRAM is incompatible with Si CMOS, it does not easily scale and has manufacturability and cost issues.

Recently discovered doped HfO₂ [1] is a promising candidate to solve these problems. HfO₂ processes are already integrated in Si CMOS industry and in theory its ferroelectric properties allow us to use oxide layer thinner than 10nm. Nevertheless the endurance properties should be improved for industrial applications and the nucleation and stabilization of the ferroelectric phase (f-phase) is not well understood [2].



Motivations and objectives


- Ferroelectric phase discovered in 2011 [1]
- Many advantages compared to « traditional » perovskite ferroelectrics
- Need Engineering :**
 - Strain from bottom AND top electrodes
 - Doping
 - Annealing



Materials Developpement

(Hf,Zr)O₂ solid solution from a Hf/Zr target on Pt and comparison with ZrO₂ and HfO₂

Sputtering



$$\%Zr = \frac{\%Zr_s \times v_{Hf}}{v_{Zr} + \%Zr_s(v_{Hf} - v_{Zr})}$$


- Amorphous deposition at RT
- See below deposition at 350° C

Issues :


In literature, Rapid Thermal Annealing (RTA) > 400° C lead to the deposition of polycrystalline HfO₂. For time being, we didn't observe any polycrystalline HfO₂ or (Hf,Zr)O₂

(Hf,Zr)O₂ on other substrates at 350° C

⇒ Appearance of the same monoclinic phase




TiN electrodes by reactive sputtering



How to choose a recipe ?

- Autopolarisation curves
- Color of the sample
- Resistivity
- Structural study of the growth


1. Autopolarisation curves



2. Resistivity

- Four-probes

Qualitative Graph



Other TiN measured fabricated in the lab IMN : 83-357 a.Ω.cm

• Hall effect

Receipe	Thickness (nm)	Resistivity (a.Ω.cm)	Bulk resistivity(a.Ω.cm)
IMN	1000	73,284	20-25
300W RF - 60V DC	350 +/- 10	31,119	20-25
200W RF - 40V DC	~115	72,543	20-25
300W RF - 60V DC	50	61,978	20-25

3. Resistivity


- Four-probes

4. Structural study

Chosen Receipe : 300W RF + 60V Bias – 700° C



Growth :

- Epitaxy ?
- Fiber ?
- Powder ?




- The material seems to be a fiber (or maybe a powder).
- However the peaks position matches very well with theory → Further studies need to be done.



Electrical characterization of Metal/Insulator/Metal capacitors



Theoretical values of ϵ_r are in objectives and motivations



ϵ_r matches with monoclinic phase (see theoretical ϵ_r in objectives and motivations)



no apparent ferroelectricity but only one cycle

Conclusion and prospects

- XRD measurements ⇔ Hf_{1-x}Zr_xO₂, HfO₂ and ZrO₂.
- Hf_{1-x}Zr_xO₂ phase diagram : monoclinic phase (probably paraelectric) by in-situ annealing at 350° C => undesirable low-K phase
- Apparently no high-K or ferroelectric phase...
- New studies on technological steps process (etching,...) needed for capacitors and devices
- The growth of TiN by reactive sputtering seems to lead to undesirable fiber or powder textures => further investigations required
- The growth processes could be changed to non-reactive sputtering in the future processes
- Understand RTA issues and growth in-situ annealing processes

References

- [1] T. S. Bööske et al., "Ferroelectricity in Hafnium Oxide Thin Films," Applied Physics Letters 99, no. 10 (September 5, 2011): 102903, doi:10.1063/1.3634052.
- [2] G. Karbasian et al., "Stabilization of ferroelectric phase in tungsten capped Hf0.8Zr0.2O2," Appl. Phys. Lett. 111 (2017) 8–12, doi:10.1063/1.4993739.
- [3] Zhen Chen et al., "Ferroelectric HfO₂-Based Materials for next-Generation Ferroelectric Memories," Journal of Advanced Dielectrics 6, no. 2 (June 2016): 1630003, doi:10.1142/S2010135X16300036.
- [4] Nanbo Gong and Tso-Ping Ma, "Why Is FE-HfO₂ More Suitable Than PZT or SBT for Scaled Nonvolatile 1-T Memory Cell? A Retention Perspective," IEEE Electron Device Letters 37, no. 9 (September 2016): 1123–26, doi:10.1109/LED.2016.2593627.
- [5] Min Hyuk Park et al., "Ferroelectricity and Antiferroelectricity of Doped Thin HfO₂-Based Films," Advanced Materials, 2015, 1811–31, doi:10.1002/adma.201404531.