



HAL
open science

Design of a combinatorial double auction for local energy markets

Diego Kiedanski, Daniel Kofman, Ariel Orda

► **To cite this version:**

Diego Kiedanski, Daniel Kofman, Ariel Orda. Design of a combinatorial double auction for local energy markets. International Conference on NETwork Games, Control and Optimisation, Mar 2020, Corsica, France. hal-02520216v1

HAL Id: hal-02520216

<https://hal.science/hal-02520216v1>

Submitted on 26 Mar 2020 (v1), last revised 30 Jun 2020 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Design of a combinatorial double auction for local energy markets

Diego Kiedanski¹, Daniel Kofman¹, and Ariel Orda²

¹ Télécom ParisTech

² Technion

Abstract. Local energy markets allow neighbours to exchange energy among them. Their traditional implementation using sequential auctions has proven to be inefficient and even counterproductive in some cases. In this paper we propose a combinatorial double auction for the exchange of energy for several time-slots simultaneously. We suppose that participants have a flexible demand; flexibility being obtained, for example, by the usage of a battery. We show the benefits of the approach and we provide an example of how it can improve the utility of all the participants in the market.

Keywords: Auction, Smart Grids, Local Energy Markets

1 Introduction

Local energy markets (LEMs) have been proposed as a paradigm to better exploit the benefits of distributed local energy generation. The various proposed market mechanisms target to encourage neighbours to exchange energy locally - within the same low voltage distribution grid, for example - in order to reduce their energy bill or even to generate revenue. In most implementations, the market mechanisms consist of a sequence of auctions that allow the participants to trade energy for the next time-slot (usually 15 or 30 minutes long). For a review of different proposals and implementations, the reader is referred to [?], [?] and the references therein. LEMs are usually implemented as double auctions, with players (households) submitting both buying and selling bids. In particular, a house with renewable generation can be a buyer or a seller, depending on the time-slot. In addition, if households have flexibility in their consumption profiles (for example, thanks to energy storage systems), they will schedule their load to obtain the most out of the market. In spite of this, it is known that the system architecture involving sequential auctions does not fully exploit the available flexibility and can even be counterproductive in some cases [?]. In this paper, we put forward the design of an approach based on a combinatorial double auction [?], [?], [?] that improves the utility of all players and increases the total traded energy.

2 Mathematical model of players

Let \mathcal{N} denote the number of players and \mathcal{T} the number of time-slots in a given day. Each player can consume energy buy using appliances (water heater, A/C, charging electric vehicles, TV, etc.) and might produce energy (e.g. photovoltaic generation). Let x_t^i denote the demand of player i at time-slot t , where a positive value of x_t^i represents excess of consumption while a negative value stands for a surplus of renewable energy (the definition of x is independent of possible flows with a battery, those flows will be introduced through additional variables). The demand profile $x^i = (x_1^i, \dots, x_T^i)$ of player i is assumed fixed and known.

To simplify the presentation, we suppose that the flexibility of each player is introduced only by batteries (for example, the demand of the appliances is not shifted in time). Let \mathbf{S}^i denote the total capacity of player i 's battery (possibly 0), \mathbf{S}_0^i the initial state of charge and s_t^i the amount of charged ($s_t^i \geq 0$) or discharged ($s_t^i < 0$) energy at time-slot t . The feasible set of charging/discharging decisions \mathcal{F}^i is given by Equation (1).

$$\mathcal{F}^i = \left\{ s^i : \mathbf{S}_0^i + \sum_{t=1}^j s_t^i \in [0, \mathbf{S}^i], \forall j = 1, \dots, T; s^i \in R^T \right\} \quad (1)$$

Furthermore, we will denote by $n^i = s^i + x^i$, with $s^i \in \mathcal{F}^i$, the net consumption of player i as seen from the grid.

In addition to trading in the market, households can trade with their traditional electricity company (TEC). If we denote β_t^i player i 's cost of buying electricity from the TEC and ζ_t^i the cost of selling to the TEC at time-slot t , then the cost at time-slot t associated with a load of w_t^i is given by: $C_t^i(w_t) = \beta_t^i \max\{w_t^i, 0\} - \zeta_t^i \max\{-w_t^i, 0\}$.

2.1 Utility of players trading in the market and with the TEC

We introduce here the definition we use of the utility of any given player when trading in the local market.

At time-slot t , player i might be able to trade a fraction $\lambda_t^i \in [0, 1]$ of her net load n_t^i in the local market. If player i trades $\lambda_t^i n_t^i$ in the local market, then it will have to trade the quantity $(1 - \lambda_t^i)n_t^i$ with the TEC. Denoting \mathcal{P}^i the payment of player i associated with the total quantity traded in the local market (positive if buying, negative if selling), the utility of player i is given by:

$$u^i(n^i, \lambda^i, \mathcal{P}^i) = \begin{cases} -\mathcal{P}^i - \sum_{t=1}^T C_t^i((1 - \lambda_t^i)n_t^i) & \text{if } (n^i - x^i \in \mathcal{F}^i) \\ -\infty & \text{otherwise} \end{cases} \quad (2)$$

3 Auction model

We put forward the design of a combinatorial double auction that exploits the flexibility available for players. Unlike the traditional auctions used for LEMs in

which players bid the quantity they want to buy or sell for a single time-slot, we allow players express in their bids they desire to acquire specific profiles of energy spanning multiple periods. We proceed to explain the bidding format, the allocation and the pricing rules.

3.1 Bidding format and allocation rule

In the proposed auction, each player expresses all her acceptable trading profiles and the utility associated with each one of them. To do so, each player bids a feasible set of consumption profiles $\hat{\mathcal{F}}^i$ (this can be done by bidding the battery capacity, initial state of charge and the player's demand \hat{x}^i) and her utility function u^i , such as the one defined in Equation (2). Here, we use the \hat{h} notation to emphasize that the bid needs not to be truthful. From the bids, we can obtain $\hat{a}^i = \max_{s^i \in \hat{\mathcal{F}}^i} u^i(s^i + \hat{x}^i, 0, 0)$, the maximum utility that player i can guarantee without trading in the local market.

Observe that to bid the utility function u^i , it suffices to bid the set of buying and selling prices β^i, ζ^i .

Regarding the allocation rule, it will be derived from the optimal solution of optimization problem (3a). We chose to maximize the value of the local trades as the objective of the allocation problem, as this is analogous to finding the clearing price in double auctions such as [?].

$$\max_{n^i, \lambda^i, \mathcal{P}^i} \sum_{i \in \mathcal{N}} \sum_{t \in \mathcal{T}} C_t^i (\lambda_t^i n_t^i) \quad (3a)$$

$$\text{subject to:} \quad \sum_{i \in \mathcal{N}} \mathcal{P}^i \geq 0 \quad (3b)$$

$$\mathcal{P}^i + \sum_{t=1}^T C_t^i [1 - \lambda_t^i n_t^i] \leq -\hat{a}^i \quad \forall n \in \mathcal{N} \quad (3c)$$

$$\sum_{n \in \mathcal{N}} \lambda_t^i n_t^i = 0 \quad \forall t \in \mathcal{T} \quad (3d)$$

$$n^i \in \hat{\mathcal{F}}^i + \hat{x}^i \quad \forall i \in \mathcal{N} \quad (3e)$$

The first constraint (3b) ensures that if the equality holds, all the money is redistributed among the participants according to the market decisions, while if the inequality is strict, the market maker obtains a profit. Constraint (3c) guarantees that the auction is individually rational, i.e., each players is at least as good as if she had not participated in the local market. It's important to note that encoding all of the \mathcal{N} constraints (3c) requires a total of $\mathcal{N}\mathcal{T}$ additional binary variables. Equalities (3d) ensure that the amount of sold energy is equal to the energy bought in every time-slot. The last constraint guarantees that only feasible net consumption profiles are used. Finally, the amount of energy traded by player i at time-slot t is given by $\lambda^{i*} n^{i*}$, where λ^{i*} and n^{i*} are the optimal solutions of optimization problem (3a).

3.2 Payment rule

As a payment rule, one alternative is to use the value of \mathcal{P}^{i*} in the optimal solution of (3a). For the cases in which the values of \mathcal{P}^{i*} will not be unique, a predefined rule can be used to choose among the possible values. One such rule can be the set of values \mathcal{P}^{i*} that distributes the gains of the market as fairly as possible.

We proceed to illustrate our proposal with an example.

3.3 A simple example

Consider two players 1 and 2 such that: $x^1 = (0, -1, 0)$, $x^2 = (0, 0, 1)$, $\beta^1 = \beta^2 = (2, 3, 3)$, $\zeta^1 = \zeta^2 = (1, 1, 1)$, $\mathbf{S}^1 = \mathbf{S}^2 = 1$, $\mathbf{S}_0^1 = \mathbf{S}_0^2 = 0$. If none of them trades in the market, their optimal utilities are given by $\alpha^1 = 1$ and $\alpha^2 = -2$, and their net consumption profiles by $n^1 = (0, -1, 0)$, $n^2 = (1, 0, 1)$.

We will now assume that the two players decide to participate in the auction and they do so truthfully. In the optimal solution of the allocation problem defined by their bids, it holds that $n^1 = (0, -1, 0) = -n^2$, $\lambda^1 = \lambda^2 = (0, 1, 0)$. Furthermore, the maximum value is attained at: $3 \times (1) + 1 \times (-1) = 2$

Regarding the payments, we have that for player 1: $\mathcal{P}^{1*} \leq -1$ and for player 2: $\mathcal{P}^{2*} \leq 2$. Consequently, any payment from player 2 to player 1 in the interval $\mathcal{P}^{2*} \in (1, 2)$ will leave both players better off than before.

3.4 General properties of the solution

First, observe that in (3a), the scenario without trades ($\mathcal{P}_t^i = \lambda_t^i = 0, \forall i, \forall t$) is always feasible and therefore, a solution exists. This solution needs not to be unique, as discussed in subsection 3.2. Secondly, when all players bid truthfully, the proposed auction obtains the consumption and trading profiles that maximize the value of the trades. The obtained allocation outperforms the results obtained when players maximize their individually utility and attempt to trade later using sequential auctions. An example of this was given in the previous subsection. There, the total utility of players went from -1 , had they tried to trade in sequential auctions using the net profiles that maximized their individual utilities, to 0 by trading in the proposed auction.

4 Conclusion

In this paper we introduced a combinatorial double auction to be used in local energy markets as a replacement to run several sequential auctions in the same day, one for each time-slot. The proposed model maximizes the value of the trades in the local market by exploiting the latent flexibility of the players, given that players bid truthfully. Future lines of research include variations of the proposed mechanism that are strategy-proof or that require less binary variables.

References

1. Huang, P., Scheller-Wolf, A., Sycara, K.: Design of a multi-unit double auction e-market. *Computational Intelligence* **18**(4), 596–617 (2002)
2. Kok, J.K., Warmer, C.J., Kamphuis, I.: Powermatcher: multiagent control in the electricity infrastructure. In: *Proceedings of the fourth international joint conference on Autonomous agents and multiagent systems*. pp. 75–82 (2005)
3. LI, L., an LIU, Y., ming LIU, K., lei MA, X., YANG, M.: Pricing in combinatorial double auction-based grid allocation model. *The Journal of China Universities of Posts and Telecommunications* **16**(3), 59 – 65 (2009). [https://doi.org/https://doi.org/10.1016/S1005-8885\(08\)60228-9](https://doi.org/https://doi.org/10.1016/S1005-8885(08)60228-9), <http://www.sciencedirect.com/science/article/pii/S1005888508602289>
4. Lopez-Rodriguez, I., Hernandez-Tejera, M., Lopez, A.L.: Methods for the management of distributed electricity networks using software agents and market mechanisms: A survey. *Electric Power Systems Research* **136**, 362–369 (2016)
5. Samimi, P., Teimouri, Y., Mukhtar, M.: A combinatorial double auction resource allocation model in cloud computing. *Information Sciences* **357**, 201 – 216 (2016). <https://doi.org/https://doi.org/10.1016/j.ins.2014.02.008>, <http://www.sciencedirect.com/science/article/pii/S0020025514001054>
6. Weinhardt, C., Mengelkamp, E., Cramer, W., Hambridge, S., Hobert, A., Kremers, E., Otter, W., Pinson, P., Tiefenbeck, V., Zade, M.: How far along are local energy markets in the dach+ region? a comparative market engineering approach. In: *Proceedings of the Tenth ACM International Conference on Future Energy Systems*. pp. 544–549 (2019)
7. Xia, M., Stallaert, J., Whinston, A.B.: Solving the combinatorial double auction problem. *European Journal of Operational Research* **164**(1), 239 – 251 (2005). <https://doi.org/https://doi.org/10.1016/j.ejor.2003.11.018>, <http://www.sciencedirect.com/science/article/pii/S0377221703008981>