

# Experimental protocol to evaluate lung parenchyma properties under inflation

Thierry Pallière, Adrien Lanel, A. Bel-Brunon, Karine Bruyere-Garnier, Nans Biboulet, Antonius Lubrecht

## ▶ To cite this version:

Thierry Pallière, Adrien Lanel, A. Bel-Brunon, Karine Bruyere-Garnier, Nans Biboulet, et al.. Experimental protocol to evaluate lung parenchyma properties under inflation. 44ème Congrès de la Société de Biomécanique, Oct 2019, Poitiers, France. hal-02525866

# HAL Id: hal-02525866 https://hal.science/hal-02525866

Submitted on 31 Mar 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Experimental protocol to evaluate lung parenchyma properties under inflation

T. Pallière<sup>a</sup>, A. Lanel<sup>a</sup>, A. Bel-Brunon<sup>a,\*</sup>, K. Bruyère-Garnier<sup>b</sup>, N. Biboulet<sup>a</sup> and T. Lubrecht<sup>a</sup>

<sup>a</sup>Univ Lyon, INSA-Lyon, CNRS UMR5259, LaMCoS, 69621, France; <sup>b</sup>Univ Lyon, Université Claude Bernard Lyon 1, Ifsttar, LBMC UMR\_T9406, 69622, Lyon, France

#### 1. Introduction

Lung parenchyma is a multiscale foam-like tissue with several intricate phenomena. During inspiration, the diaphragm creates a depression on the lung cavity forcing air to enter; alveoli dilatation is favoured by the presence of surfactant, a biofilm which decreases the surface tension on the inner surface of the alveoli. Lung parenchyma is composed of vasculature, air ducts, alveolar walls, surfactant; a loss of equilibrium between these components can lead to pathologies, such as fibrosis or emphysema, causing a mechanical vicious circle (Hinz and Suki, 2016). Understanding how lung parenchyma behaves mechanically with its different components is still a challenge. Experimental characterization has been performed at the organ scale (Richardson et al. 2017) or on tissue strips (BelBrunon et al. 2014) but the former includes structural effects while the latter does not allow for realistic loading (inflation), leading to a poor identification of the constitutive law. The aim of the presented protocol is to acquire experimental data related to lung parenchyma inflation to build and identify a component-based constitutive law for this tissue, focusing on small scales (from alveoli to sub-segment). So to reach a sufficient imaging resolution, the protocol is designed for sub-segment lobules.

#### 2. Method

#### 2.1. Lung segment sampling

Samples with an approximate volume of 0.4 L are withdrawn from extracted pig lungs at rest. They are subtrees from the respiratory tree: they can *breathe* independently from any other lung segment and with no leaks. The withdrawal is conducted by progressively following the respiratory tree, cutting along the bronchus and bronchioles until reaching the desired sample size, around generation 5 or 6. For each extraction, the lung segment is pressurized to identify and remove superfluous matter belonging to other subtrees.



Figure 1. Left: Lung segment in the enclosure with applied speckle pattern – Right: Max principal strain pattern during inflation.



**Figure 2.** Reconstruction of a segment (a) tree structure (b) lobules generated as Voronoï cells from an equivalent cumulative resistance criterion.

#### 2.2. Set-up

The lung segment is placed in a 27 L enclosure made out of PMMA acrylic and filled with air initially at atmospheric pressure. A syringe, connected to the enclosure, is activated by hand to remove air, in order to mimic the depression caused by the diaphragm. The bronchial end of the sample is connected with the external environment by a Foley catheter to ensure the atmospheric pressure of the air circulating in the lung segment. The Foley catheter passes through the lid in a hermetic seal and holds the sample by its tip, without it touching the sides of the enclosure. The segment is anatomically divided in sub-volumes, called lobules; due to the Foley catheter, some lobules may be disconnected to the atmospheric pressure during the experiment, and therefore would not inflate under external depression.

#### 2.3. Measurements and loading

A pressure sensor is placed inside the enclosure to quantify the depression. A pressure sensor and a flow sensor are used inside the catheter outside the enclosure to characterize the pseudo-breathing. The lung segment is speckled and two cameras placed outside the enclosure record its motion. The surface deformation on the front face of the sample are deduced from these records by a Stereo-DIC analysis using the sequential correlation algorithm from Vic-3D v7.

The 1.5 L syringe used to remove air from the enclosure is alternatively filled and emptied at different rates, simulating a pseudo-breathing on the lung segment. The resulting flow rate inside the segment is between 0.02 and 0.04 L/s; the maximum inspired volume is about 0.15 L.

#### 2.4. CT-imaging and reconstruction

CT images of each sample were acquired at CERMEP (CERMEP-Imagerie du Vivant, Université de Lyon, Bron, France) after loading. The segment is maintained slightly inflated with a Foley catheter to ensure an optimal visibility of the respiratory tree. The CTscan uses a 55  $\mu$ m resolution. The outer and inner segment geometry are reconstructed from the images to simulate the experiment. One of the aims of imaging and reconstructing the inner structure is to match the heterogeneous experimental behaviour of the segment, which does not inflate homogeneously. Although they are visible on CT-images, lobules could not be automatically segmented and reconstructed; we rely therefore on the respiratory tree segmentation to identify extremities from which lobules could be artificially grown. The respiratory tree is segmented by region growing, then skeletonized and labelled by generation. The lobules are generated by the 3DVoronoï algorithm applied to extremities of the respiratory tree defined by a similar cumulative resistance to air flow. The reconstruction is a gapless assembly of welded lobules that fill the total segment volume extracted from the images.

#### 3. Results and discussion

#### **3.1. Inflation test**

Preliminary tests showed that using a 2mm thick layer of PMMA has no significant influence on the stereo DIC computed fields for the area of interest and an optical set-up typical of our experiment. An example of a strain field is presented in Figure 1; it can be computed for most of the anterior side of the segment. Due to geometric effects and regional inflation, this field is very heterogeneous.

The time evolution of the strain field from DIC is consistent with the measured air flow at the tip of the catheter. There is no observation of any inertial effect of the inflation compared to the pressure profile measured in the enclosure. However, the depression is not perfectly controlled. For the inflation to be representative of the in-vivo mechanism, depression should be driven following a repeatable and realistic breathing cycle in order to avoid viscoelasticity misrepresentation or overload complications. To control such an inflation cycle, the enclosure and syringe can be filled with an incompressible fluid such as water instead of air. The induced refraction is then to be corrected; however, the preliminary study has shown that even with water, refraction effects on the stereo-DIC results are negligible for our experiments.

#### 3.2. Geometric reconstruction

As shown in Figure 2, and contrary to human anatomy, the respiratory tree does not exhibit symmetric divisions. So tree extremities of the same generation do not seem relevant as seeds to grow lobules of similar volume. Tree cumulative resistance seems more relevant, based on a visual comparison between 3D lobule reconstruction (Figure 2b) and segment CTimages. However this observation requires further quantitative analysis.

CT-scan images are captured using horizontally positioned segments. To improve the protocol robustness, the horizontal position can be used during the experiments so that experimental and imaging boundary conditions are the same (particularly gravity effect) and therefore avoid any registration step.

#### 4. Conclusions

With this first set-up, we obtained more insight into lung segment inflation which is useful to increase robustness of the existing set-up. We also plan to evaluate inflation before and after bronchoalveolar lavage to evaluate the mechanical contribution of surfactant to the resulting lung parenchyma behaviour.

#### References

- Bel-Brunon A, Kehl S, Martin C, Uhlig S, Wall WA. 2014. Numerical identification method for the nonlinear viscoelastic compressible behavior of soft tissue using uniaxial tensile tests and image registration-application to rat lung parenchyma. J Mech Behav Biomed Mater, 29:360-374.
- Hinz B, Suki B. 2016. Does breathing amplify fibrosis? Am J Respir Crit Care Med. 114(1):9–11.
- Richardson S, Gamage TPB, HajiRassouliha A, Jackson T, Hedges K, Clark A, ... and Nielsen PM. 2017. Towards a real-time full-field stereoscopic imaging system for tracking lung surface deformation under pressure