

Spatial and temporal variation of tritium concentrations during a dam flushing operation

Lepage Hugo, Frédérique Eyrolle, Loic Ducros, David Claval

▶ To cite this version:

Lepage Hugo, Frédérique Eyrolle, Loic Ducros, David Claval. Spatial and temporal variation of tritium concentrations during a dam flushing operation. Journal of Environmental Radioactivity, 2020, 218, pp.106261. 10.1016/j.jenvrad.2020.106261. hal-02531823

HAL Id: hal-02531823 https://hal.science/hal-02531823v1

Submitted on 7 Jul2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial - NoDerivatives 4.0 International License

Manuscript Details

Manuscript number	JENVRAD_2020_65_R1
Title	Spatial and temporal variation of tritium concentrations during a dam flushing operation
Article type	Research Paper

Abstract

Tritium is a radionuclide commonly observed worldwide in riverine systems. In the Rhône River downstream the Lake Geneva (Switzerland and France), its occurrence is also related to its use for its luminescent properties in watchmaking paints. In fact, tritium is regularly observed at anomalous levels in this river and extreme events such as flushing operations might conduct to its transport downstream. In the Rhône River, characterized by 21 dams downstream the Geneva Lake, such operations are regularly organized to remove the sediments and limit problematic consequences such as siltation and increased flooding hazards. The consequences of dam flushing operations on tritium concentrations were thus investigated. Samples of Suspended Particulate Matter (SPM) and water were collected in the Rhone River downstream of Geneva in June 2012, during a planned flushing operation of three upstream reservoirs (Verbois, Chancy-Pougny and Génissiat). The concentrations of tritiated water (HTO) and organically bound Tritium (OBT) were measured and compared to reference concentrations. The flushing operations had no impact on the HTO concentration while the increases observed were related to the authorized releases of HTO from a nuclear power plant located downstream the dams. High increases of OBT concentrations in SPM were observed at two stations (Creys-Malville and Jons) without clear spatial or temporal trends. These anomalous peaks could be explained by the heterogeneous spatial distribution of technogenic tritium leading to large variations of tritium concentrations within the samples even though collected in areas close to each other. The results highlight the need to investigate the amount of such technogenic tritium currently stored in the upstream Rhone River as it might be significant.

Keywords	Radionuclide; Technogenic tritium; organically bound Tritium; sediment; suspended particulate matter; watchmaking paint
Taxonomy	River Basin Management, Environmental Science, Environmental Radioactivity
Corresponding Author	Hugo LEPAGE
Corresponding Author's Institution	IRSN
Order of Authors	Hugo LEPAGE, Frédérique Eyrolle, Loïc Ducros, David CLAVAL
Suggested reviewers	Shinji Ueda, C. Le Gal La Salle, Sang Bog Kim
Opposed reviewers	Philippe pjb@lsce.ipsl.fr

Submission Files Included in this PDF

File Name [File Type] Response to Reviewers .docx [Response to Reviewers (without Author Details)] Manuscript_Revised_with_marks.docx [Revised Manuscript with Changes Marked (without Author Details)] Highlights.docx [Highlights] Abstract_revised.docx [Abstract] Graphical Abstract_revised.pdf [Graphical Abstract] Title page.docx [Title Page (with Author Details)] Manuscript_Revised.docx [Manuscript (without Author Details)] Figure captions_revised.docx [Figure] Figure 1.pdf [Figure] Figure 3_revised.pdf [Figure] Table.docx [Table] declaration-of-competing-interests.docx [Conflict of Interest] ESM_revised.docx [e-Component]

To view all the submission files, including those not included in the PDF, click on the manuscript title on your EVISE Homepage, then click 'Download zip file'.

Comments from reviewer	Answers from corresponding author	Correction in the manuscript
Reviewer 1	 Explanation for the use of SPM and sediment in the manuscript: SPM is used to characterize the particles that are transported by the river. It is what we sampled to measure the OBT. Sediment characterized the particles stored either in the studied dams or along the river. Sediment could be resuspended (for example during the flushing operations) and thereafter considered as SPM as well as SPM could be stored 	
	by sedimentation and considered as sediment. Since the reviewers 2 and 3 did not complain on that point, we did not changed the terminology of SPM and sediments.	
- Line 12: Insert (SPM)	Added	Samples of Suspended Particulate Matter (SPM) and water were collected in the Rhone River downstream of Geneva in June 2012 []
- Line 18: High increase of OBT concentration from SPM or sediment? I am confused between sediment and SPM through whole manuscript. Is SPM a part of sediment?	See first comment for SPM and sediment definition. Although the increase was observed in the SPM sampled at two of the four stations, it was directly related to the resuspension during the flushing operations of the sediments stored in the dams or in the river.	High increases of OBT concentrations in SPM were observed at two stations (Creys-Malville and Jons) without clear spatial or temporal trends.

- Line 36: "the nuclear sector is allowed to release low-activity liquid effluent into rivers". Is it including SPM or OBT? If yes, insert a reference.	Nuclear industries release radionuclides as dissolved species only. No particles are released. However, dissolved species can fix to suspended solid particles transported by the river. Tritium is transferred in the environment predominantly as dissolved free HTO and is known to be a conservative radionuclide during water mass transfer and mixing. Part of tritium can associate to particulate organic matter during photosynthesis (OBT).	
- Line 40: These forms?	OBT – corrected in the text	Part of OBT do not easily exchange with the surrounding water molecules and persist in the environment until organic compounds are biodegraded.
- Line 56: 0.6 x 10 ⁹ . Is it suspended or precipitated in the bottom?	It is particles that were suspended but got stored by sedimentation.	
- Line 61-62: What is a difference between contaminated sediments and SPM?	See first comment for SPM and sediment definition. Sediments stored in the dam might be either contaminated or depleted so as the SPM.	
- Line 71: soil washout by rain?	Soil erosion. Corrected	[] or finally progressively transferred due to soil erosion (Schürch et al., 2003).
- Line 99-110: Format error? All stations (A,B,C,D) have different sampling periods from 6 days to 30 days. Do you have any specific reason?	Unfortunately, due to logistic constraint, periods of sampling differed depending on the stations. Sampling at station A and B needed specific authorization due to safety rules during the flushing operations and sampling were only authorized during the flushing of the closest dams. Detail added to the manuscript.	To characterize the impact of the dam flushing operations on the concentrations of HTO (water samples) and OBT (SPM samples), samples were collected at four stations (Figure 1, Table 1) with different sampling periods due to logistic constrain

- Line 118: For SPM sampling, is any water depth related to?	At Station A B and D, Particle Trap were set in the bottom of the river while for Station C, the sampling were conducted approx. 50cm below the surface in order to side step potential heterogeneity of SPM throughout the river cross- section. Detail added to the manuscript.	Due to logistic constrain, the PT were set on the bottom of the river at Stations A, B and D while at Station C it was approx. 50 cm below the surface.
- Line 132: detection limit of HTO and OBT?	With used detection limit and detection threshold to determine the concentration in our samples as described in Currie (1968). For both methods, detection limit was approx. 0.6 Bq.L ⁻¹ with a detection threshold of approx. 1.2 Bq.L ⁻¹ . Information added in the manuscript.	For both methods, detection limit was approx. 0.6 Bq.L ⁻¹ with a detection threshold of approx. 1.2 Bq.L ⁻¹ (Currie, 1968; Eyrolle et al., 2018).
- Line 182: How much tritium released annually from the NPP?	In the Rhône River, almost 80% of HTO come from the NPP, it is the most released radionuclide in term of quantity (Eyrolle-Boyer et al., 2015). In 2012, almost 210 TBq of HTO were released in the Rhône River (with 200 TBq only by NPP).	
- Line 224: What is the relationship between sediment and SPM?	Corrected, OBT is heterogeneously distributed in the sediments.	However, OBT is heterogeneously distributed in sediments of the Rhône River and large amounts of this radionuclide are still stored in the Upper Rhône sediments.
- Table S1: In C station, MDA is 1.2 or 1.5 but in D station, can be detected up to 0.6 Bq/L. Are they use the same technique?	The same technique was used, it depended not only on the detection limit but also on the detection threshold. See information on detection limit in the comment above.	
Reviewer 2		

1. In order to determine how turbid in the river water collected in this study, please indicate and explain the SPM amount (mg/L) of the river water.	The discharge of the river and its SPM concentration were investigated in a thesis in French (Launay, 2014), while the data are available online (Thollet et al,. 2018). A specific focus on Jons was conducted in Lepage et al. (2020). These references and additional information were added in the manuscript and in the electronic supplementary materials.	Discharge varied from 129 m ³ s ⁻¹ to 631 m ³ s ⁻¹ in the vicinity of Chancy-Pougny during the flushing periods (Figure ESM1 in electronic supplementary materials). Discharge increased from upstream to downstream and reached maximal values (1600 m ³ s ⁻¹) at Jons (Station D in Figure 1) on the 06/14, which correspond to discharges observed for biennial flood (Lepage et al., 2020). SPM concentration reached 16.6 g L ⁻¹ near Génissiat during its flushing and the highest SPM concentration was observed during the flushing of Verbois and Chancy-Pougny with 48.6 g L ⁻¹ observed at Chancy-Pougny (Figure ESM1 in electronic supplementary materials). The SPM concentrations decreased with distance and the maximum concentrations observed at Jons was 0.9 g L ⁻¹ . It has to be noted that floods occurred in two tributaries (Ain and Fier – Figure 1) with a limited impact on the transport of SPM (Launay, 2014; Lepage et al., 2020).
 2. Can you estimate the tritium load into a downstream using the amount of sediment released during flushing operations of 3 dams and data of OBT concentration in SPM? You should describe the effect of tritium on the downstream caused by the dam flushing operation. 3. Please add information such as organic matter quantity (TOC, TN, etc.) to clarify the composition in SPM. 	Fluxes of SPM related to these flushing operations were calculated in Lepage et al. (2020) and might be used to estimate the flux of OBT. However due to its heterogeneous distribution in the SPM it is difficult to evaluate an accurate load of OBT exported. The particulate organic carbon and grain size distribution were added in the Table S2 and in the manuscript (in Mat & Met., Results and Discussion)	

4. By the way, are there an impact of high- concentration tritium SPM on ecosystems? Is there bioaccumulation through the food chain by SPM? If so, please describe in the "introduction", "discussion" or "conclusion".	To our knowledge, any investigation was conducted on the radiotoxicity of the technogenic tritium observed in the Rhône River. Additional information was added to the manuscript.	The radiotoxicity of free tritium (HTO) or organically bound tritium to naturally occurring organic compounds (OBT) are low comparing to most other natural or artificial radionuclides. Nevertheless, the specific radiotoxicity of organically bound tritium to synthetic organic particles are unknown to our knowledge as well as their transfer rates toward living organisms.
5. Precipitation information is needed to distinguish the effects of dam flushing and precipitation. Provide information about precipitation during the observation period and please write that the SPM in the river water is not affected by precipitation.	During the flushing operations, floods occurred in two upstream tributaries (Ain and Fier rivers), downstream Stations A and B (Figure 1). Their impacts remained low as the input of SPM by these tributaries was strongly lower than the flux from the flushing operations (Launay. 2014; Lepage et al., 2020).	It has to be noted that floods occurred in two tributaries (Ain and Fier – Figure 1) with a limited impact on the transport of SPM (Launay, 2014; Lepage et al., 2020).
1. Change from unit of "Bq.L-1" to "Bq L-1" in manuscript. No period required.	Corrected for the whole manuscript.	
2. Line 45: Change from "coastal rivers" to "mountainous rivers".	Corrected	[] HTO concentrations in two small mountainous rivers were shown to be higher during flood events than in baseflow conditions (Ueda <i>et al.</i> , 2015) []
3. It is easier to understand if you insert tritium concentration ranges in the river water and sediments of the Rhone River in Figures 2 and 3. For example, see Fig. 3 of Science of the Total Environment Eyrolle et al (2018) Vol 643, pp40-51.	Ranges of HTO and OBT concentrations were added to the figures 2 and 3.	
Reviewer 3		
- The graphical abstract looks inconsistent with the findings. Heterogeneous distribution of OBT is the key finding in my understanding. If so, the	Graphical abstract was improved	

heterogeneity should be illustrated in the graphical abstract.		
- More information is needed for heterogeneity for OBT. I remember that the author(s) don't have the data for the bed sediment, but how about the concentration of SPM (kg/L) in river water? That information helps the division of heterogeneity of SPM concentration and heterogeneity of OBT concentration (probably the unit should be Bq/kg instead of Bq/L in this case). I'm not familiar with the Rhone river but imagine heterogeneity of SPM concentration is large during such dam flushing operations.	Variation of discharge and SPM concentration were added in the electronic supplementary materials and in the manuscript. However, it is difficult to link the OBT to the SPM as the samples were collected during several hours in order to get a sufficient amount of SPM to realize the analysis. The Bq L ⁻¹ of combustive water as described in our paper directly express the content of tritium associated with organic compounds. Bq kg ⁻¹ can conduct to erroneous interpretation of OBT results because it doesn't consider organic matter content in suspended or deposited sediment samples. However, results in Bq kg ⁻¹ were added in the ESM in the Table ESM2	This result highlights that these tritiated particles most probably come from the sediment stored in the dams and flushed during the operations. It also confirms their heterogeneously distribution as such increase of OBT concentration was not observed in Stations A and B.

Spatial and temporal variation of tritium concentrations during a dam flushing operation

3 Abstract

4 Tritium is a radionuclide commonly observed worldwide in riverine systems. In the Rhône 5 River downstream the Lake Geneva (Switzerland and France), its occurrence is also related to 6 its use for its luminescent properties in watchmaking paints. In fact, tritium is regularly 7 observed at anomalous levels in this river and extreme events such as flushing operations 8 might conduct to its transport downstream. In the Rhône River, characterized by 21 dams downstream the Geneva Lake, such operations are regularly organized to remove the 9 10 sediments and limit problematic consequences such as siltation and increased flooding 11 hazards. The consequences of dam flushing operations on tritium concentrations were thus 12 investigated. Samples of Suspended Particulate Matter (SPM) and water were collected in the 13 Rhone River downstream of Geneva in June 2012, during a planned flushing operation of three 14 upstream reservoirs (Verbois, Chancy-Pougny and Génissiat). The concentrations of tritiated 15 water (HTO) and organically bound Tritium (OBT) were measured and compared to reference 16 concentrations. The flushing operations had no impact on the HTO concentration while the 17 increases observed were related to the authorized releases of HTO from a nuclear power plant 18 located downstream the dams. High increases of OBT concentrations in SPM were observed 19 at two stations (Creys-Malville and Jons) without clear spatial or temporal trends. These 20 anomalous peaks could be explained by the heterogeneous spatial distribution of technogenic 21 tritium leading to large variations of tritium concentrations within the samples even though 22 collected in areas close to each other. The results highlight the need to investigate the amount of such technogenic tritium currently stored in the upstream Rhone River as it might besignificant.

25 Keywords

Radionuclide; Technogenic tritium; organically bound Tritium; sediment; suspended
 particulate matter; watchmaking paint

28 Introduction

29 Tritium (³H - half-life = 12.3 years) is a radionuclide commonly observed for several 30 decades in the environment (Eisenbud et al., 1979). In rivers, ³H can be liquid (tritiated water 31 - HTO) or incorporated in particulate organic compounds (Organically Bound Tritium - OBT) 32 (Kim et al., 2013). The HTO is the predominant form of tritium in the environment and it closely 33 follows the water cycle (Ciffroy et al., 2006; Eyrolle-Boyer et al., 2015). It is commonly used as 34 a tracer in hydrogeology and marine studies (Ducros et al., 2018). The HTO is also the most 35 released aqueous radionuclide from nuclear facilities, with levels of activity currently 1000 times higher than the sum of artificial gamma emitters discharged (Eyrolle et al., 2018). In fact, 36 37 in compliance with the legislation, the nuclear sector is allowed to release low-activity liquid 38 effluent into rivers. The OBT is part of the organic matter cycle and has been measured in 39 sediments and suspended particulate matter (SPM) for decades (Eyrolle et al., 2018). Some of 40 these forms the OBT do not easily exchange with the surrounding water molecules and persist 41 in the environment until organic compounds are biodegraded. These forms of tritium are 42 expected to be stored in sediments associated with particulate organic matter (Eyrolle-Boyer 43 et al., 2014) and might be affected by extreme events such as flood events or dam flushing 44 operations. In fact, these events strongly affect the behavior of dissolved and particulate 45 contaminants including tritium. For example, after the deposition of tritium following the

46 Fukushima accident in march 2011, HTO concentrations in two small coastal mountainous 47 rivers were shown to be higher during flood events than in baseflow conditions (Ueda et al., 48 2015) but decreased rapidly the following years to reach background concentration in 2014. Dams on rivers considerably impact SPM transport, by reducing flow velocity and increasing 49 50 SPM deposition (Syvitski et al., 2005) and that of their related contaminants (Lepage et al., 51 2020). Contaminants associated with deposited sediments may also be resuspended and 52 disseminated (Peter et al., 2014) or transferred to the dissolved phase (Bretier et al., 2019; 53 Kalnejais et al., 2010).

54 In France, the Rhône River is characterized by the presence of 21 hydropower plants 55 and is one of the most nuclearized rivers in the world, with 5 nuclear power plants (NPP) 56 including one in dismantlement, nuclear fuel production, reprocessing plants and research laboratories. From 0.2 to 0.6 10⁹ kg of SPM are stored each year along the Rhône River 57 58 (Bravard and Clémens, 2008), mostly in dam reservoirs (Provansal et al., 2014). Resuspension 59 processes, such as dam flushing operations, are regularly organized to remove stored 60 sediments and limit problematic consequences such as siltation and increased flooding hazards (Brown, 1944; Peteuil et al., 2013). Such dam operations lead either to the 61 62 resuspension of contaminated sediments stored in the dams, or to the dilution of 63 contaminated SPM by flushing non-contaminated sediments (Lepage et al., 2020).

Moreover, in the past century, most of the OBT was originate from other industrial plants present in the Rhône River and especially in its upstream part that produced luminescent paint used in watches (Eyrolle *et al.*, 2018; Jean-Baptiste *et al.*, 2018). These companies have released fine particles of tritiated compounds (usually tiny tritiated polystyrene spherules a few tens of microns in diameter) used in luminous paints (Jean-Baptiste *et al.*, 2007; Krejci and Zeller, 1979; Schürch *et al.*, 2003). In fact, these tritiated

70 technogenic particles (hot tritiated particles) could have been released directly into the river 71 by the industrial plants, or transferred into the environment during the waste incineration 72 process, or finally progressively transferred due to soil washout erosion (Schürch et al., 2003). 73 These refractory particles that accumulate in sediments are expected to persist in the 74 environment for a very long time (Eyrolle et al., 2018; Morereau et al., in prep.) and have also 75 been observed in the Mediterranean Sea near the outlet of the Rhône River (Jean-Baptiste et 76 al., 2018). Although a recent review written by Eyrolle et al. (2018) summarized results on its 77 specific behavior in the Rhône River, reports on the impact of hydrological events on OBT 78 concentrations remain rare especially its dynamics during dam flushing operations.

This field study was conducted in the Rhône River downstream the Lake Geneva during the flushing operations of several dams in June 2012. Water and SPM samples were collected at different locations for different periods. The tritium concentrations were characterized and the results were then compared with the contents recorded before the event.

83 Materials and Method

84 Dam location and description of the flushing operations

85 This study was conducted along the Upper Rhône River in France and Switzerland, 86 downstream the Lake Geneva (Figure 1). This basin (95,600 km² at Beaucaire station) 87 constitutes the main SPM input flowing into the Western Mediterranean Sea with a mean SPM 88 flux of 6.5 Mt₋year⁻¹ from 2000 to 2015 (Poulier *et al.*, 2019). This work focuses on flushing 89 operations conducted in June 2012 in three reservoirs located downstream of Lake Geneva in 90 Switzerland (Figure 1): Verbois, Chancy-Pougny, and Génissiat. These flushing operations are 91 described in Lepage et al. (2020). In brief, the water level of the three dams was lowered 92 following the drawdown flushing method (Fruchard and Camenen, 2012) in order to remove

93 stored sediments. The large-volume Génissiat reservoir located downstream of the two other 94 dams was flushed first (4-12 June 2012) in order to compensate for the deposition of the SPM 95 released from the Chancy-Pougny (9-16 June 2012) and Verbois dams (9-22 June 2012). Discharge varied from 129 m³ s⁻¹ to 631 m³ s⁻¹ in the vicinity of Chancy-Pougny during the 96 97 flushing periods (Figure ESM1 in electronic supplementary materials). Discharge increased 98 from upstream to downstream and reached maximal values (1600 m³ s⁻¹) at Jons (Station D in 99 Figure 1) on the 06/14, which correspond to discharges observed for biennial flood (Lepage et 100 al., 2020). SPM concentration reached 16.6 g L⁻¹ near Génissiat during its flushing and the 101 highest SPM concentration was observed during the flushing of Verbois and Chancy-Pougny 102 with 48.6 g L⁻¹ observed at Chancy-Pougny (Figure ESM1 in electronic supplementary 103 materials). The SPM concentrations decreased with distance and the maximum 104 concentrations observed at Jons was 0.9 g L⁻¹. It has to be noted that floods occurred in two tributaries (Ain and Fier - Figure 1) with a limited impact on the transport of SPM (Launay, 105 106 2014; Lepage et al., 2020).

107 Sampling and samples

To characterize the impact of the dam flushing operations on the concentrations of
HTO (water samples) and OBT (SPM samples), samples were collected at four stations (Figure
1, Table 1) with different sampling periods due to logistic constrain:

- Station A at Pougny, in the downstream vicinity of Chancy-Pougny and Verbois
 dams. Samples were collected from the 06/09/2012 to the 06/20/2012 during
 the flushing operations of these two dams.
- Station B at Seyssel, downstream Génissiat dam and during its flushing
 operation with samples collected from the 06/04/2012 to the 06/10/2012.

Station C at Creys-Malville in a monitoring station used to supply the regulatory
 control of the releases from NPPs (IRSN, 2015) and used in this study for
 temporal comparison. Sampling was conducted before, during and after the
 flushing operations, from the 05/25/2012 to the 07/01/2012.

- Station D at Jons in a monitoring station (Masson *et al.*, 2018; Thollet *et al.*,
 2018) located downstream a NPP (Figure 1) with samples collected for the main
 period of flushing operations, from the 06/04/2012 to the 07/03/2012.
- 123

124 Two different sampling methods were used to collect water samples (Table 1). 125 Instantaneous water samples were obtained manually using a stainless-steel bucket (approx. 126 4 L) at stations A, B and D, and by an Automatic Water Sampler (AWS) at station C. The AWS 127 used for water sampling was a Bühler 4011 (HachLange, Germany) and set to collect 10 mL 128 every 65 minutes to constitute time integrated raw water samples (6 days) stored in glass 129 bottles. Samples were all stored in dark glass bottles at 4°C until analyses.

130 For OBT measurement, SPM samples were collected using Particle Trap (PT). These 131 samplers were built following the German Environmental Specimen Bank model (Masson et 132 al., 2018; Schulze et al., 2007). Water flows through the high-quality stainless steel box and its 133 velocity is reduced by two baffles. SPM settle in two sedimentation basins in the box. Samples 134 were collected every 1 to 4 days (see Table ESMS1 in electronic supplementary materials). 135 Due to logistic constrain, the PT were set on the bottom of the river at Stations A, B and D 136 while at Station C it was approx. 50 cm below the surface. Prior to analysis, SPM samples were stored in the dark at 4°C, deep-frozen, freeze-dried, and homogenized through a 2 mm 137 138 stainless steel sieve. Dried samples were then immediately sealed under soft vacuum in aluminized bags until analyses in order to avoid the exchange of water molecules with theatmosphere.

141 Grain-size distribution

For the measure of volumetric grain size distribution, a representative aliquot of each
 wet sample was taken before processing and was analyzed on a CILAS 1190 laser particle size
 analyzer (Masson et al., 2018) according to the ISO 13320 standard method (AFNOR, 2009).
 Clay (<1.95 μm), Silt (<63 μm) and Sand (<2000 μm) were estimated.

146 Particulate Organic Carbon analysis

147The determination of Particulate Organic Carbon (POC) in SPM samples was performed148using a carbon analyzer (Thermo Electron, CHN Flash 2000) by INRA laboratory (Arras, France).149Decarbonation was completed using hydrochloric acid according to the NF ISO 10694 standard150method (AFNOR, 1995). The limit of quantification (LQ) was estimated to be 0.05 g kg⁻¹ and151analytical uncertainty varied between ~3% and ~6% (k=2), depending on the POC152concentration.

153

154 Tritium analyses

The concentrations of the two main forms of tritium (HTO and OBT) were investigated.
The HTO analyses were performed on 20ml of filtered water (< 0.2 μm) either directly filtered
in the field for punctual samples or in the laboratory for time-integrated ones sampled by
AWS. Filtered waters were analyzed by classical scintillation counting for HTO content (Tricarb
3180 TR/SL), by taking an aliquot of 10 mL and adding 10 mL of scintillation liquid (UltimaGold
LLT).

OBT analyses were conducted using the Helium-3 ingrowth method after placing the sample in a vacuum (10^{-6} mbar) and storing it for 3 to 4 months (Cossonnet *et al.*, 2009). The Helium-3 is a decay product of tritium—and its concentration is measured by mass spectrometry (Jean-Baptiste *et al.*, 2010). OBT concentrations were converted in Becquerel per liter of combustion water ($Bq:Bq L^{-1}_{cw}$) by using the percentage of hydrogen measured in each sample by a CHNS elemental analyzer (Elementar, vario MICROcube).

For both methods, detection limit was around 0.6 Bq L⁻¹ with a detection threshold of
 <u>1.2 Bq L⁻¹</u> (Currie, 1968; Eyrolle et al., 2018). All the measured concentrations were corrected
 for radioactive decay to the sampling date.

170 **Results**

171 Variation of HTO contents

172 The concentrations of HTO measured during this study were similar at Stations A and 173 B (Figure 2; Table <u>S1ESM1</u>) with respectively a mean HTO concentration of 1.1 Bq.Bq L⁻¹ (with 174 standard deviation sd = 0.3 $\frac{Bq}{Bq}L^{-1}$ and 1.2 $\frac{Bq}{Bq}L^{-1}$ (sd = 0.2 $\frac{Bq}{Bq}L^{-1}$). At station C, the 175 only value observed above the detection limit (0.8 \pm 0.7 Bq.Bq L⁻¹) was not significantly 176 different to the two upstream stations. The HTO concentration at this station remained very 177 low as several values were lower than the detection limit. For these three stations, no 178 significant variation of HTO contents were observed during the flushing operations. At station 179 D, two significant increases were observed during the flushing operation the 06/05/2012 and 180 the 06/16/2012 with respectively 13.1 ± 1.0 $\frac{Bq}{Bq}L^{-1}$ and 11.8 ± 1.0 $\frac{Bq}{Bq}L^{-1}$. The other 181 concentrations measured at station D were similar to the values observed at the other stations 182 with $1.1 \frac{Bq}{Bq} L^{-1}$ (sd = 0.3 $\frac{Bq}{Bq} L^{-1}$).

183 **OBT**

184	During the period studied, OBT contents ranged from 180 ± 40 $\frac{Bq}{Bq}L^{-1}cw$ to 11,700 ±
185	2,300 Bq.Bq L ⁻¹ _{cw} (Figure 3 - Table S3ESM2) with a mean value of 1,640 Bq.Bq L ⁻¹ _{cw} (sd = 2,600
186	Bq.<u>Bq</u> L⁻¹_{cw}). The mean OBT concentration at stations A and B were similar with respectively
187	850 Bq.<u>B</u>q L ⁻¹ _{cw} (sd = 320 Bq.<u>B</u>q L ⁻¹ _{cw}) and 890 Bq.<u>B</u>q L ⁻¹ _{cw} (sd = 330 Bq.<u>B</u>q L ⁻¹ _{cw}) while significant
188	variations of OBT were observed at the two other stations. At station C, the first value
189	measured was significantly higher than the other with 11,700 \pm 2,300 $\frac{Bq}{Bq}$ L ⁻¹ _{cw} observed the
190	06/09/12, then decreased to reach similar level than the upstream stations A and B. At station
191	D, a high concentration of OBT was observed 48h afterwards that of station C (6,670 \pm 340
192	Bq.Bq L ⁻¹ cw the 06/11/12). The other values measured during dam flushing operations (mean
193	= 680 sd 400 Bq-Bq L ⁻¹ cw) were similar to those of station A and B.
194	Silt particles always constituted the major part of the SPM whatever the station with
195	proportions ranging from 35.8 to 94.2% (Table ESM2). Sand particles were mostly observed at
196	stations A and B, close to the studied dams. Those particles were rapidly stored in the Upper
197	Rhône River as the proportion of sand were very low at Stations C and D. The POC
198	concentration observed at Station A and C remained constant while some variations were
199	observed at the two other stations (Table ESM2). Maximal concentration was observed at
200	Station D with $36.0 \pm 1.8 \text{ mg kg}^{-1}$.

201

202 Discussion

203 Most of the HTO concentrations measured at the four stations were similar to those 204 observed from 2003 to 2015 by the Swiss Federal office of public health (OFSP, 2015) in water 205 samples collected near station A (1.03 Bq-Bq L⁻¹ with sd = 0.41 Bq-Bq L⁻¹) and not affected by 206 NPP releases. Furthermore, the concentrations remained in the range of values observed for 207 the natural background in waters of French pristine rivers (Ducros et al., 2018). Although, the 208 increases observed at station D was strictly related to the releases of HTO by the NPP and not 209 related to the dam flushing operations. As mentioned in the introduction, NPPs are allowed 210 to release radionuclides into river systems conforming to liquid flow rate thresholds. The 211 sampling performed at station D for this study was conducted during short radionuclide 212 release operations with 12 events from 3 to 12 hours (Electricité De France, personal 213 communication). The absence of higher HTO concentrations in the other samples of station D 214 was due to the time lapse between the NPP's release operations and the samplings, 215 performed 10 hours after the end of the operations. The transit time between the NPP and 216 the sampling station has been validated by modeling using the hydrological model CASTEAUR 217 (Beaugelin-Seiller et al., 2002). The increase was only observed at station D as the NPP is 218 downstream the other stations (Figure 1). Overall, the values measured during this NPP's 219 operations were similar to the mean concentrations recorded during radionuclide release 220 operations at this NPP from 2011 to 2014 (12 Bq.Bq L⁻¹) (IRSN, 2015). Therefore, despite the 221 input of high quantity of water from the flushing operations and characterized by a lower level 222 of HTO than from the NPP releases, no significant effect of dilution was observed. In the Upper 223 Rhône River, dam flushing operations do not affect HTO concentrations in the water column 224 and, in the absence of NPP releases, these concentrations remain similar from upstream to 225 downstream. Thus, in contrast with certain trace metals remobilized during such events such 226 as arsenic (Bretier et al., 2019; Monnin et al., 2018), no significant transfer of tritium from 227 sediment remobilization to the dissolved phase was observed. Moreover, these results did not 228 show any significant contribution of tritium either from HTO potentially stored in the pore 229 waters of remobilized sediments, or from OBT associated to fine particles (<0.45µm) towards 230 waters.

231 Despite the high concentrations of OBT observed at stations C and D, all the 232 concentrations remained in the same range as those reported by Eyrolle et al., (2018) (from 233 4 to 30,200 Bq.Bq L⁻¹_{cw}) and confirmed the high variability due to the presence of tritiated 234 technogenic particles in the Rhône River. In fact, OBT concentrations are generally expected 235 to be rather close to HTO concentrations in most other cases (Eyrolle-Boyer et al., 2015). For 236 example, in the sediments of the Rhône's tributaries not affected by luminous paints, 237 background values were lower than 10 Bq.Bq L⁻¹cw (Eyrolle et al., 2018). Since neither 238 significant temporal nor spatial trends were observed in OBT concentrations, we hypothesize 239 that these results can be explained by the heterogeneous distribution of technogenic tritium 240 in suspended or deposited sedimentary particles leading to large variations of tritium 241 concentrations within the samples even though collected in areas close to each other. Also, 242 this result is confirmed by the absence of relation between OBT and POC concentrations. In 243 the Rhône River, OBT is not only bound to organic matter of natural origin, but would very 244 likely be trapped inside fine polystyrene particles from technogenic tritium (Eyrolle et al., 245 2018). Regarding grain size, any specific relation was observed but the highest level of OBT at Jons (6670 Bq L⁻¹_{cw}) was observed in a sample characterized by a high level of sand (42.2%) 246 247 (Table ESM2). This result highlights that these tritiated particles most probably come from the 248 sediment stored in the dams and flushed during the operations. It also confirms their 249 heterogeneously distribution as such increase of OBT concentration was not observed in 250 Stations A and B. Furthermore, with the evolution of technologies and the introduction of 251 guidelines for the protection of the environment (Morereau et al., in prep.), OBT should no 252 longer be emitted at this level in the environment and its occurrence should be mainly related 253 to its long-time presence in the sediments of the Rhône River (Eyrolle et al., 2018). The highest 254 concentrations observed below the dams might be related to the resuspension of old contaminated sediments stored in the studied dams as observed for PAHs by Lepage et al.
(2020). The OBT is expected to be transported downstream and its concentration should
decrease from upstream to downstream in the following decades.

258

259 Conclusion

260 The consequences of dam flushing operations on tritium concentrations were 261 investigated in the Rhône River downstream Lake Geneva by characterizing the HTO and OBT 262 concentrations respectively in filtered water and suspended particulate matter (SPM) samples 263 collected downstream three dams flushed in June 2012. Our results demonstrate that dam 264 flushing operations do not significantly affect tritium concentrations in the water column as 265 they remained similar to those previously recorded during normal flow conditions. Analyses 266 of OBT in the SPM demonstrated transient increases in concentration during the dam flushing 267 operations. This increase was Those are most probably linked explained by to the resuspension 268 of fine tritiated particles from watchmaking activities. As the increases were transient and not 269 observed at all the stations, no significant temporal nor spatial trend following dam flushing 270 operations can be drawn clearly trend could be linked to the dam flushing operations. 271 However, OBT is heterogeneously distributed in sediments of the Rhône River and SPM and a 272 large amounts of OBT-this radionuclide are stillmight be currently stored in the Upper Rhône 273 River-sediments. Extreme events and could be redistributed following extreme events such as 274 dam flushing operations can redistribute these storages to the downstream part of the River. 275 The radiotoxicity of free tritium (HTO) or organically bound tritium to naturally occurring 276 organic compounds (OBT) are low comparing to most other natural or artificial radionuclides. 277 Nevertheless, the specific radiotoxicity of organically bound tritium to synthetic organic 278 particles are unknown to our knowledge as well as their transfer rates toward living organisms.

279 Acknowledgements

This study was supported by the Rhône Sediment Observatory (OSR), a multi-partner research program partly funded by the Rhône Plan and by the European Regional Development Fund (ERDF) allocated by the European Union. We thank the teams of OSR, especially those of INRAE and CEREGE, for their contribution in the field for water and sediment sampling. We are very grateful to CNR, DREAL ARA, SIG and EDF services for cooperating with OSR and sharing their monitoring data.

286 **References**

- AFNOR, 2009. NF ISO 10694: Particle Size Analysis Laser Diffraction Methods. 51 pp.
- AFNOR, 1995. NF ISO 10694: Soil quality Determination of organic and total carbon after dry
 combustion (elementary analysis). 7 pp.
- 290 Beaugelin-Seiller, K., Boyer, P., Garnier-Laplace, J., Adam, C., 2002. Casteaur: A simple tool to
- assess the transfer of radionuclides in waterways. Health Phys. 83, 539–542.

292 https://doi.org/10.1097/00004032-200210000-00013

- Bravard, J.-P., Clémens, A., 2008. Le Rhône en 100 questions. Méditerranée (report in French)
 294 295 pp.
- Bretier, M., Dabrin, A., Bessueille-Barbier, F., Coquery, M., Barbier-Bessueille, F., Coquery, M.,

296 2019. Comparison of integrative passive sampling and discrete monitoring to assess the

- impact of dam flushing event on dissolved trace elements concentrations. Sci. Total
- 298 Environ. 656, 433-446. https://doi.org/10.1016/j.scitotenv.2018.11.303
- Brown, C.B., 1944. The control of reservoir silting. US Gov. Print. Off. 521, 168 pp.
- 300 Ciffroy, P., Siclet, F., Damois, C., Luck, M., 2006. A dynamic model for assessing radiological
- 301 consequences of tritium routinely released in rivers. Application to the Loire River. J.

302 Environ. Radioact. 90, 110–139. https://doi.org/10.1016/j.jenvrad.2006.06.012

Cossonnet, C., Neiva Marques, A.M., Gurriaran, R., 2009. Experience acquired on
 environmental sample combustion for organically bound tritium measurement. Appl.
 Radiat. Isot. 67, 809-811. https://doi.org/10.1016/j.apradiso.2009.01.039

- 306 Currie, L.A., 1968. Limits for Qualitative Detection and Quantitative Determination:
 307 Application to Radiochemistry. Anal. Chem. 40, 586-593.
 308 https://doi.org/10.1021/ac60259a007
- Ducros, L., Eyrolle, F., Vedova, C. Della, Charmasson, S., Leblanc, M., Mayer, A., Babic, M.,
 Antonelli, C., Mourier, D., Giner, F., 2018. Tritium in river waters from French

311 Mediterranean catchments: Background levels and variability. Sci. Total Environ. 612,

312 672-682. https://doi.org/10.1016/j.scitotenv.2017.08.026

313 Eisenbud, M., Bennett, B., Blanco, R.E., 1979. Tritium in the environment. NCRP Report No.
314 62. Behav. Tritium Environ.

315 Eyrolle-Boyer, F., Boyer, P., Claval, D., Charmasson, S., Cossonnet, C., 2014. Apparent

enrichment of organically bound tritium in rivers explained by the heritage of our past. J.

317 Environ. Radioact. 136, 162–168. https://doi.org/10.1016/j.jenvrad.2014.05.019

318 Eyrolle-Boyer, F., Claval, D., Cossonnet, C., Zebracki, M., Gairoard, S., Radakovitch, O., Calmon,

P., Leclerc, E., 2015. Tritium and 14C background levels in pristine aquatic systems and their potential sources of variability. J. Environ. Radioact. 139, 24–32.

321 https://doi.org/10.1016/j.jenvrad.2014.09.015

322 Eyrolle, F., Lepage, H., Copard, Y., Ducros, L., Claval, D., Saey, L., Cossonnet, C., Giner, F.,

323 Mourier, D., 2018. A brief history of the origins and contents of Organically Bound Tritium

324 (OBT) and 14C in the sediments of the Rhône watershed. Sci. Total Environ. in review,

325 40-51. https://doi.org/10.1016/j.scitotenv.2018.06.074

326 Fruchard, F., Camenen, B., 2012. Reservoir sedimentation: different type of flushing-friendly

- flushing example of genissiat dam flushing. ICOLD Int. Symp. Dams a Chang. world 6 pp.
- 328 IRSN, 2015. Bilan de l'état radiologique de l'environnement français de juin 2011 à décembre
- 329 2014. PRP-ENV (french report) 253p.
- IRSN, 2013. Constat radiologique Vallée du Rhône. Rapport final relatif au milieu aquatique.
 PRP-ENV/SESURE (french report) 37, 68p.
- Jean-Baptiste, P., Baumier, D., Fourré, E., Dapoigny, A., Clavel, B., 2007. The distribution of
 tritium in the terrestrial and aquatic environments of the Creys-Malville nuclear power
- 334 plant (2002-2005). J. Environ. Radioact. 94, 107-118.
 335 https://doi.org/10.1016/j.jenvrad.2007.01.010
- Jean-Baptiste, P., Fontugne, M., Fourré, E., Marang, L., Antonelli, C., Charmasson, S., Siclet, F.,
 2018. Tritium and radiocarbon levels in the Rhône river delta and along the French
 Mediterranean coastline. J. Environ. Radioact. 187, 53-64.
 https://doi.org/10.1016/j.jenvrad.2018.01.031
- Kalnejais, L.H., Martin, W.R., Bothner, M.H., 2010. The release of dissolved nutrients and
 metals from coastal sediments due to resuspension. Mar. Chem. 121, 224-235.
 https://doi.org/10.1016/j.marchem.2010.05.002
- Kim, S.B., Baglan, N., Davis, P.A., 2013. Current understanding of organically bound tritium
 (OBT) in the environment. J. Environ. Radioact. 126, 83-91.
 https://doi.org/10.1016/j.jenvrad.2013.07.011
- Krejci, K., Zeller, J., 1979. Tritium pollution in the Swiss luminous compound industry, in:
 International Symposium on the Behaviour of Tritium in the Environment. IAEA, Vienna,
 pp. 65–77.
- Launay, M., 2014. Flux de matières en suspension, de mercure et de PCB particulaires dans le

350 Rhône, du Léman à la Méditerranée. Thesis (in French) 434.
351 https://doi.org/10.1002/oby.20222

Lepage, H., Launay, M., Le Coz, J., Angot, H., Miège, C., Gairoard, S., Radakovitch, O., Coquery, 352 353 M., 2020. Impact of dam flushing operations on sediment dynamics and quality in the 354 Rhône 109886. upper River, France. J. Environ. Manage. 255, 355 https://doi.org/10.1016/j.jenvman.2019.109886

356 Masson, M., Angot, H., Le Bescond, C., Launay, M., Dabrin, A., Miège, C., Le Coz, J., Coquery,

357 M., 2018. Sampling of suspended particulate matter using particle traps in the Rhône

358 River: Relevance and representativeness for the monitoring of contaminants. Sci. Total

359 Environ. 637–638, 538–549. https://doi.org/10.1016/j.scitotenv.2018.04.343

Monnin, L., Ciffroy, P., Garnier, J.M., Ambrosi, J.P., Radakovitch, O., 2018. Remobilization of
trace metals during laboratory resuspension of contaminated sediments from a dam
reservoir. J. Soils Sediments 18, 2596–2613. https://doi.org/10.1007/s11368-018-19315

- Morereau, A., Lepage, H., Claval, D., Cossonnet, C., Radakovitch, O., Ambrosi, J.-P., Mourier,
 B., Eyrolle, F., n.d. Technogenic tritium contamination from watchmaking industry and its
 resiliency in river sediments of the Rhône River (France).
- 367 OFSP, 2015. Radenviro.ch [WWW Document]. URL http://www.radenviro.ch/fr368 CH/measures/274 (accessed 7.5.16).

369 Peter, D.H., Castella, E., Slaveykova, V.I., 2014. Effects of a reservoir flushing on trace metal

- 370 partitioning, speciation and benthic invertebrates in the floodplain. Environ. Sci. Process.
- 371 Impacts 16, 2692–2702. https://doi.org/10.1039/c4em00387j
- Peteuil, C., Fruchart, F., Abadie, F., Reynaud, S., Camenen, B., Guertault, L., 2013. Sustainable
 management of sediment fluxes in reservoir by environmental friendly flushing : the case

study of the Genissiat dam on the upper Rhone River (France), in: 12th International
Conference on River Sedimentation. Kyoto (Japan), pp. 1147–1156.

Poulier, G., Launay, M., Le Bescond, C., Thollet, F., Coquery, M., 2019. Combining flux
monitoring and estimation to establish annual budgets of suspended particulate matter

- and associated pollutants in the Rhône River from Lake Geneva to the Mediterranean
- 379 Sea. Sci. Total Environ. 658, 457–473. https://doi.org/10.1016/J.SCITOTENV.2018.12.075
- 380 Provansal, M., Dufour, S., Sabatier, F., Anthony, E.J., Raccasi, G., Robresco, S., 2014. The

381 geomorphic evolution and sediment balance of the lower Rhône River (southern France)

382 over the last 130 years: Hydropower dams versus other control factors. Geomorphology

- 383 219, 27-41. https://doi.org/10.1016/j.geomorph.2014.04.033
- Schulze, T., Ricking, M., Schröter-Kermani, C., Körner, A., Denner, H.-D., Weinfurtner, K.,
 Winkler, A., Pekdeger, A., 2007. The German Environmental Specimen Bank Sampling,
 processing, and archiving sediment and suspended particulate matter. J. Soils Sediments
- 387 7, 361–367. https://doi.org/10.1065/jss2007.08.248
- 388 Schürch, M., Kozel, R., Schotterer, U., Tripet, J.-P.P., Sch??rch, M., Kozel, R., Schotterer, U.,

Tripet, J.-P.P., 2003. Observation of isotopes in the water cycle—the Swiss National

390 Network (NISOT). Environ. Geol. 45, 1–11. https://doi.org/10.1007/s00254-003-0843-9

391 Syvitski, J.P.M., Vörösmarty, C.J., Kettner, A.J., Green, P., 2005. Impact of humans on the flux

- of terrestrial sediment to the global coastal ocean. Science (80-.). 308, 376-380.
- 393 https://doi.org/10.1126/science.1109454
- 394 Thollet, F., Le Bescond, C., Lagouy, M., Gruat, A., Grisot, G., Le Coz, J., Coquery, M., Lepage, H.,
- Gairoard, S., Gattacceca, J.C., Ambrosi, J.-P., Radakovitch, O., 2018. Observatoire des

396 sédiments du Rhône. https://doi.org/10.17180/OBS.OSR

397 Ueda, S., Hasegawa, H., Kakiuchi, H., Ochiai, S., Akata, N., Hisamatsu, S., 2015. Nuclear


- 398 accident-derived ³H in river water of Fukushima Prefecture during 2011-2014. J. Environ.
- 399 Radioact. 146, 102–109. https://doi.org/10.1016/j.jenvrad.2015.04.014

Highlights

- Tritium were monitored during dam regulations in the Rhone River.
- Dam flushing operations had no impact on HTO concentration in water.
- Increase of HTO contents were only related to the releases from a nuclear plant.
- Flushing operations resuspended contaminated sediments by watches industries.
- Sporadic high OBT contents in SPM reflect its heterogeneous distribution.


Abstract

Tritium is a radionuclide commonly observed worldwide in riverine systems. In the Rhône River downstream the Lake Geneva (Switzerland and France), its occurrence is also related to its use for its luminescent properties in watchmaking paints. In fact, tritium is regularly observed at anomalous levels in this river and extreme events such as flushing operations might conduct to its transport downstream. In the Rhône River, characterized by 21 dams downstream the Geneva Lake, such operations are regularly organized to remove the sediments and limit problematic consequences such as siltation and increased flooding hazards. The consequences of dam flushing operations on tritium concentrations were thus investigated. Samples of Suspended Particulate Matter (SPM) and water were collected in the Rhone River downstream of Geneva in June 2012, during a planned flushing operation of three upstream reservoirs (Verbois, Chancy-Pougny and Génissiat). The concentrations of tritiated water (HTO) and organically bound Tritium (OBT) were measured and compared to reference concentrations. The flushing operations had no impact on the HTO concentration while the increases observed were related to the authorized releases of HTO from a nuclear power plant located downstream the dams. High increases of OBT concentrations in SPM were observed at two stations (Creys-Malville and Jons) without clear spatial or temporal trends. These anomalous peaks could be explained by the heterogeneous spatial distribution of technogenic tritium leading to large variations of tritium concentrations within the samples even though collected in areas close to each other. The results highlight the need to investigate the amount of such technogenic tritium currently stored in the upstream Rhone River as it might be significant.



After dam flushing operation Dam flushed Survey station HTO: HTO concentration **OBT:** OBT concentration = constant ↗ increase Mix of suspended, fresh and old sediments Dam HTO =

Spatial variation of tritium during the flushing operations



Confirmed the heterogeneous distribution of OBT

1 Spatial and temporal variation of tritium concentrations during a

2 dam flushing operation

3 Lepage Hugo^{a*}, Eyrolle Frédérique^a, Ducros Loïc^b, Claval David^a.

4
5 ^a Institut de Radioprotection et de Sureté Nucléaire (IRSN), PSE-ENV, SRTE/LRTA,
6 SEREN/LEREN, BP 3, 13115 Saint-Paul-lez-Durance, France

7

^b Université de Nîmes, EA7352 CHROME, Laboratoire GIS, Parc scientifique et technique G.
Besse, 150 rue Georges Besse, 30000 Nîmes, France

10

11 *corresponding author

Spatial and temporal variation of tritium concentrations during a dam flushing operation

3 Abstract

4 Tritium is a radionuclide commonly observed worldwide in riverine systems. In the Rhône 5 River downstream the Lake Geneva (Switzerland and France), its occurrence is also related to 6 its use for its luminescent properties in watchmaking paints. In fact, tritium is regularly 7 observed at anomalous levels in this river and extreme events such as flushing operations 8 might conduct to its transport downstream. In the Rhône River, characterized by 21 dams downstream the Geneva Lake, such operations are regularly organized to remove the 9 10 sediments and limit problematic consequences such as siltation and increased flooding 11 hazards. The consequences of dam flushing operations on tritium concentrations were thus 12 investigated. Samples of Suspended Particulate Matter (SPM) and water were collected in the 13 Rhone River downstream of Geneva in June 2012, during a planned flushing operation of three 14 upstream reservoirs (Verbois, Chancy-Pougny and Génissiat). The concentrations of tritiated 15 water (HTO) and organically bound Tritium (OBT) were measured and compared to reference 16 concentrations. The flushing operations had no impact on the HTO concentration while the 17 increases observed were related to the authorized releases of HTO from a nuclear power plant 18 located downstream the dams. High increases of OBT concentrations in SPM were observed 19 at two stations (Creys-Malville and Jons) without clear spatial or temporal trends. These 20 anomalous peaks could be explained by the heterogeneous spatial distribution of technogenic 21 tritium leading to large variations of tritium concentrations within the samples even though collected in areas close to each other. The results highlight the need to investigate the amount 22

of such technogenic tritium currently stored in the upstream Rhone River as it might besignificant.

25 Keywords

Radionuclide; Technogenic tritium; organically bound Tritium; sediment; suspended
particulate matter; watchmaking paint

28 Introduction

29 Tritium (³H - half-life = 12.3 years) is a radionuclide commonly observed for several decades in the environment (Eisenbud et al., 1979). In rivers, ³H can be liquid (tritiated water 30 31 - HTO) or incorporated in particulate organic compounds (Organically Bound Tritium - OBT) 32 (Kim et al., 2013). The HTO is the predominant form of tritium in the environment and it closely 33 follows the water cycle (Ciffroy et al., 2006; Eyrolle-Boyer et al., 2015). It is commonly used as 34 a tracer in hydrogeology and marine studies (Ducros et al., 2018). The HTO is also the most 35 released aqueous radionuclide from nuclear facilities, with levels of activity currently 1000 times higher than the sum of artificial gamma emitters discharged (Eyrolle et al., 2018). In fact, 36 37 in compliance with the legislation, the nuclear sector is allowed to release low-activity liquid 38 effluent into rivers. The OBT is part of the organic matter cycle and has been measured in 39 sediments and suspended particulate matter (SPM) for decades (Eyrolle et al., 2018). Some of 40 the OBT do not easily exchange with the surrounding water molecules and persist in the 41 environment until organic compounds are biodegraded. These forms of tritium are expected 42 to be stored in sediments associated with particulate organic matter (Eyrolle-Boyer et al., 43 2014) and might be affected by extreme events such as flood events or dam flushing 44 operations. In fact, these events strongly affect the behavior of dissolved and particulate 45 contaminants including tritium. For example, after the deposition of tritium following the 46 Fukushima accident in march 2011, HTO concentrations in two small mountainous rivers were 47 shown to be higher during flood events than in baseflow conditions (Ueda et al., 2015) but 48 decreased rapidly the following years to reach background concentration in 2014. Dams on rivers considerably impact SPM transport, by reducing flow velocity and increasing SPM 49 50 deposition (Syvitski et al., 2005) and that of their related contaminants (Lepage et al., 2020). 51 Contaminants associated with deposited sediments may also be resuspended and 52 disseminated (Peter et al., 2014) or transferred to the dissolved phase (Bretier et al., 2019; 53 Kalnejais et al., 2010).

54 In France, the Rhône River is characterized by the presence of 21 hydropower plants 55 and is one of the most nuclearized rivers in the world, with 5 nuclear power plants (NPP) 56 including one in dismantlement, nuclear fuel production, reprocessing plants and research laboratories. From 0.2 to 0.6 10⁹ kg of SPM are stored each year along the Rhône River 57 58 (Bravard and Clémens, 2008), mostly in dam reservoirs (Provansal et al., 2014). Resuspension 59 processes, such as dam flushing operations, are regularly organized to remove stored 60 sediments and limit problematic consequences such as siltation and increased flooding hazards (Brown, 1944; Peteuil et al., 2013). Such dam operations lead either to the 61 62 resuspension of contaminated sediments stored in the dams, or to the dilution of 63 contaminated SPM by flushing non-contaminated sediments (Lepage et al., 2020).

Moreover, in the past century, most of the OBT was originate from other industrial plants present in the Rhône River and especially in its upstream part that produced luminescent paint used in watches (Eyrolle *et al.*, 2018; Jean-Baptiste *et al.*, 2018). These companies have released fine particles of tritiated compounds (usually tiny tritiated polystyrene spherules a few tens of microns in diameter) used in luminous paints (Jean-Baptiste *et al.*, 2007; Krejci and Zeller, 1979; Schürch *et al.*, 2003). In fact, these tritiated

70 technogenic particles (hot tritiated particles) could have been released directly into the river 71 by the industrial plants, or transferred into the environment during the waste incineration 72 process, or finally progressively transferred due to soil erosion (Schürch et al., 2003). These 73 refractory particles that accumulate in sediments are expected to persist in the environment 74 for a very long time (Eyrolle et al., 2018; Morereau et al., in prep.) and have also been observed 75 in the Mediterranean Sea near the outlet of the Rhône River (Jean-Baptiste et al., 2018). 76 Although a recent review written by Eyrolle et al. (2018) summarized results on its specific 77 behavior in the Rhône River, reports on the impact of hydrological events on OBT 78 concentrations remain rare especially its dynamics during dam flushing operations.

This field study was conducted in the Rhône River downstream the Lake Geneva during the flushing operations of several dams in June 2012. Water and SPM samples were collected at different locations for different periods. The tritium concentrations were characterized and the results were then compared with the contents recorded before the event.

83 Materials and Method

84 Dam location and description of the flushing operations

85 This study was conducted along the Upper Rhône River in France and Switzerland, 86 downstream the Lake Geneva (Figure 1). This basin (95,600 km² at Beaucaire station) 87 constitutes the main SPM input flowing into the Western Mediterranean Sea with a mean SPM flux of 6.5 Mt year⁻¹ from 2000 to 2015 (Poulier et al., 2019). This work focuses on flushing 88 89 operations conducted in June 2012 in three reservoirs located downstream of Lake Geneva in 90 Switzerland (Figure 1): Verbois, Chancy-Pougny, and Génissiat. These flushing operations are 91 described in Lepage et al. (2020). In brief, the water level of the three dams was lowered 92 following the drawdown flushing method (Fruchard and Camenen, 2012) in order to remove

93 stored sediments. The large-volume Génissiat reservoir located downstream of the two other 94 dams was flushed first (4-12 June 2012) in order to compensate for the deposition of the SPM 95 released from the Chancy-Pougny (9-16 June 2012) and Verbois dams (9-22 June 2012). Discharge varied from 129 m³ s⁻¹ to 631 m³ s⁻¹ in the vicinity of Chancy-Pougny during the 96 97 flushing periods (Figure ESM1 in electronic supplementary materials). Discharge increased 98 from upstream to downstream and reached maximal values (1600 m³ s⁻¹) at Jons (Station D in 99 Figure 1) on the 06/14, which correspond to discharges observed for biennial flood (Lepage et al., 2020). SPM concentration reached 16.6 g L⁻¹ near Génissiat during its flushing and the 100 101 highest SPM concentration was observed during the flushing of Verbois and Chancy-Pougny 102 with 48.6 g L⁻¹ observed at Chancy-Pougny (Figure ESM1 in electronic supplementary 103 materials). The SPM concentrations decreased with distance and the maximum 104 concentrations observed at Jons was 0.9 g L⁻¹. It has to be noted that floods occurred in two 105 tributaries (Ain and Fier - Figure 1) with a limited impact on the transport of SPM (Launay, 106 2014; Lepage et al., 2020).

107 Sampling and samples

To characterize the impact of the dam flushing operations on the concentrations of
HTO (water samples) and OBT (SPM samples), samples were collected at four stations (Figure
1, Table 1) with different sampling periods due to logistic constrain:

- Station A at Pougny, in the downstream vicinity of Chancy-Pougny and Verbois
 dams. Samples were collected from the 06/09/2012 to the 06/20/2012 during
 the flushing operations of these two dams.
- Station B at Seyssel, downstream Génissiat dam and during its flushing
 operation with samples collected from the 06/04/2012 to the 06/10/2012.

Station C at Creys-Malville in a monitoring station used to supply the regulatory
 control of the releases from NPPs (IRSN, 2015) and used in this study for
 temporal comparison. Sampling was conducted before, during and after the
 flushing operations, from the 05/25/2012 to the 07/01/2012.

- Station D at Jons in a monitoring station (Masson *et al.*, 2018; Thollet *et al.*,
 2018) located downstream a NPP (Figure 1) with samples collected for the main
 period of flushing operations, from the 06/04/2012 to the 07/03/2012.
- 123

124 Two different sampling methods were used to collect water samples (Table 1). 125 Instantaneous water samples were obtained manually using a stainless-steel bucket (approx. 126 4 L) at stations A, B and D, and by an Automatic Water Sampler (AWS) at station C. The AWS 127 used for water sampling was a Bühler 4011 (HachLange, Germany) and set to collect 10 mL 128 every 65 minutes to constitute time integrated raw water samples (6 days) stored in glass 129 bottles. Samples were all stored in dark glass bottles at 4°C until analyses.

130 For OBT measurement, SPM samples were collected using Particle Trap (PT). These 131 samplers were built following the German Environmental Specimen Bank model (Masson et 132 al., 2018; Schulze et al., 2007). Water flows through the high-quality stainless steel box and its 133 velocity is reduced by two baffles. SPM settle in two sedimentation basins in the box. Samples 134 were collected every 1 to 4 days (see Table ESM1 in electronic supplementary materials). Due 135 to logistic constrain, the PT were set on the bottom of the river at Stations A, B and D while at 136 Station C it was approx. 50 cm below the surface. Prior to analysis, SPM samples were stored 137 in the dark at 4°C, deep-frozen, freeze-dried, and homogenized through a 2 mm stainless steel 138 sieve. Dried samples were then immediately sealed under soft vacuum in aluminized bags until 139 analyses in order to avoid the exchange of water molecules with the atmosphere.

140 Grain-size distribution

For the measure of volumetric grain size distribution, a representative aliquot of each
wet sample was taken before processing and was analyzed on a CILAS 1190 laser particle size
analyzer (Masson et al., 2018) according to the ISO 13320 standard method (AFNOR, 2009).
Clay (<1.95 μm), Silt (<63 μm) and Sand (<2000 μm) were estimated.

145 **Particulate Organic Carbon analysis**

The determination of Particulate Organic Carbon (POC) in SPM samples was performed using a carbon analyzer (Thermo Electron, CHN Flash 2000) by INRA laboratory (Arras, France). Decarbonation was completed using hydrochloric acid according to the NF ISO 10694 standard method (AFNOR, 1995). The limit of quantification (LQ) was estimated to be 0.05 g kg⁻¹ and analytical uncertainty varied between ~3% and ~6% (k=2), depending on the POC concentration.

152 **Tritium analyses**

The concentrations of the two main forms of tritium (HTO and OBT) were investigated.
The HTO analyses were performed on 20ml of filtered water (< 0.2 μm) either directly filtered
in the field for punctual samples or in the laboratory for time-integrated ones sampled by
AWS. Filtered waters were analyzed by classical scintillation counting for HTO content (Tricarb
3180 TR/SL), by taking an aliquot of 10 mL and adding 10 mL of scintillation liquid (UltimaGold
LLT).

OBT analyses were conducted using the Helium-3 ingrowth method after placing the sample in a vacuum (10^{-6} mbar) and storing it for 3 to 4 months (Cossonnet *et al.*, 2009). The Helium-3 is a decay product of tritium—and its concentration is measured by mass spectrometry (Jean-Baptiste *et al.*, 2010). OBT concentrations were converted in Becquerel per liter of combustion water (Bq L⁻¹_{cw}) by using the percentage of hydrogen measured in each
sample by a CHNS elemental analyzer (Elementar, vario MICROcube).

For both methods, detection limit was around 0.6 Bq L⁻¹ with a detection threshold of 166 1.2 Bq L⁻¹ (Currie, 1968; Eyrolle et al., 2018). All the measured concentrations were corrected 167 for radioactive decay to the sampling date.

168 **Results**

169 Variation of HTO contents

The concentrations of HTO measured during this study were similar at Stations A and 170 171 B (Figure 2; Table ESM1) with respectively a mean HTO concentration of 1.1 Bq L⁻¹ (with 172 standard deviation sd = 0.3 Bq L^{-1}) and 1.2 Bq L^{-1} (sd = 0.2 Bq L^{-1}). At station C, the only value 173 observed above the detection limit (0.8 ± 0.7 Bq L⁻¹) was not significantly different to the two 174 upstream stations. The HTO concentration at this station remained very low as several values 175 were lower than the detection limit. For these three stations, no significant variation of HTO 176 contents were observed during the flushing operations. At station D, two significant increases were observed during the flushing operation the 06/05/2012 and the 06/16/2012 with 177 178 respectively 13.1 ± 1.0 Bg L⁻¹ and 11.8 ± 1.0 Bg L⁻¹. The other concentrations measured at 179 station D were similar to the values observed at the other stations with 1.1 Bq L^{-1} (sd = 0.3 Bq L⁻¹). 180

181 **OBT**

During the period studied, OBT contents ranged from 180 ± 40 Bq L⁻¹_{cw} to $11,700 \pm 2,300$ Bq L⁻¹_{cw} (Figure 3 - Table ESM2) with a mean value of 1,640 Bq L⁻¹_{cw} (sd = 2,600 Bq L⁻¹_{cw}). The mean OBT concentration at stations A and B were similar with respectively 850 Bq L⁻¹_{cw} (sd = 320 Bq L⁻¹_{cw}) and 890 Bq L⁻¹_{cw} (sd = 330 Bq L⁻¹_{cw}) while significant variations of OBT were

186 observed at the two other stations. At station C, the first value measured was significantly higher than the other with 11,700 \pm 2,300 Bq L⁻¹_{cw} observed the 06/09/12, then decreased to 187 188 reach similar level than the upstream stations A and B. At station D, a high concentration of 189 OBT was observed 48h afterwards that of station C (6,670 \pm 340 Bq L⁻¹_{cw} the 06/11/12). The 190 other values measured during dam flushing operations (mean = 680 sd 400 Bq L^{-1}_{cw}) were 191 similar to those of station A and B. Silt particles always constituted the major part of the SPM whatever the station with proportions ranging from 35.8 to 94.2% (Table ESM2). Sand 192 193 particles were mostly observed at stations A and B, close to the studied dams. Those particles 194 were rapidly stored in the Upper Rhône River as the proportion of sand were very low at 195 Stations C and D. The POC concentration observed at Station A and C remained constant while 196 some variations were observed at the two other stations (Table ESM2). Maximal 197 concentration was observed at Station D with $36.0 \pm 1.8 \text{ mg kg}^{-1}$.

198

199 Discussion

200 Most of the HTO concentrations measured at the four stations were similar to those 201 observed from 2003 to 2015 by the Swiss Federal office of public health (OFSP, 2015) in water 202 samples collected near station A (1.03 Bq L^{-1} with sd = 0.41 Bq L^{-1}) and not affected by NPP 203 releases. Furthermore, the concentrations remained in the range of values observed for the 204 natural background in waters of French pristine rivers (Ducros et al., 2018). Although, the 205 increases observed at station D was strictly related to the releases of HTO by the NPP and not 206 related to the dam flushing operations. As mentioned in the introduction, NPPs are allowed 207 to release radionuclides into river systems conforming to liquid flow rate thresholds. The 208 sampling performed at station D for this study was conducted during short radionuclide 209 release operations with 12 events from 3 to 12 hours (Electricité De France, personal 210 communication). The absence of higher HTO concentrations in the other samples of station D 211 was due to the time lapse between the NPP's release operations and the samplings, 212 performed 10 hours after the end of the operations. The transit time between the NPP and 213 the sampling station has been validated by modeling using the hydrological model CASTEAUR 214 (Beaugelin-Seiller et al., 2002). The increase was only observed at station D as the NPP is downstream the other stations (Figure 1). Overall, the values measured during this NPP's 215 216 operations were similar to the mean concentrations recorded during radionuclide release 217 operations at this NPP from 2011 to 2014 (12 Bq L⁻¹) (IRSN, 2015). Therefore, despite the input 218 of high quantity of water from the flushing operations and characterized by a lower level of 219 HTO than from the NPP releases, no significant effect of dilution was observed. In the Upper 220 Rhône River, dam flushing operations do not affect HTO concentrations in the water column 221 and, in the absence of NPP releases, these concentrations remain similar from upstream to 222 downstream. Thus, in contrast with certain trace metals remobilized during such events such 223 as arsenic (Bretier et al., 2019; Monnin et al., 2018), no significant transfer of tritium from 224 sediment remobilization to the dissolved phase was observed. Moreover, these results did not 225 show any significant contribution of tritium either from HTO potentially stored in the pore 226 waters of remobilized sediments, or from OBT associated to fine particles (<0.45µm) towards 227 waters.

Despite the high concentrations of OBT observed at stations C and D, all the concentrations remained in the same range as those reported by Eyrolle *et al.*, (2018) (from 4 to 30,200 Bq L^{-1}_{cw}) and confirmed the high variability due to the presence of tritiated technogenic particles in the Rhône River. In fact, OBT concentrations are generally expected to be rather close to HTO concentrations in most other cases (Eyrolle-Boyer *et al.*, 2015). For 233 example, in the sediments of the Rhône's tributaries not affected by luminous paints, background values were lower than 10 Bq L⁻¹cw (Eyrolle et al., 2018). Since neither significant 234 235 temporal nor spatial trends were observed in OBT concentrations, we hypothesize that these 236 results can be explained by the heterogeneous distribution of technogenic tritium in 237 suspended or deposited sedimentary particles leading to large variations of tritium 238 concentrations within the samples even though collected in areas close to each other. Also, 239 this result is confirmed by the absence of relation between OBT and POC concentrations. In 240 the Rhône River, OBT is not only bound to organic matter of natural origin, but would very 241 likely be trapped inside fine polystyrene particles from technogenic tritium (Eyrolle et al., 242 2018). Regarding grain size, any specific relation was observed but the highest level of OBT at 243 Jons (6670 Bq L^{-1}_{cw}) was observed in a sample characterized by a high level of sand (42.2%) 244 (Table ESM2). This result highlights that these tritiated particles most probably come from the 245 sediment stored in the dams and flushed during the operations. It also confirms their 246 heterogeneously distribution as such increase of OBT concentration was not observed in 247 Stations A and B. Furthermore, with the evolution of technologies and the introduction of 248 guidelines for the protection of the environment (Morereau et al., in prep.), OBT should no 249 longer be emitted at this level in the environment and its occurrence should be mainly related 250 to its long-time presence in the sediments of the Rhône River (Eyrolle et al., 2018). The highest 251 concentrations observed below the dams might be related to the resuspension of old 252 contaminated sediments stored in the studied dams as observed for PAHs by Lepage et al. 253 (2020). The OBT is expected to be transported downstream and its concentration should 254 decrease from upstream to downstream in the following decades.

255

256 Conclusion

257 The consequences of dam flushing operations on tritium concentrations were 258 investigated in the Rhône River downstream Lake Geneva by characterizing HTO and OBT 259 concentrations respectively in filtered water and suspended particulate matter (SPM) samples 260 collected downstream three dams flushed in June 2012. Our results demonstrate that dam 261 flushing operations do not significantly affect tritium concentrations in the water column as 262 they remained similar to those previously recorded during normal flow conditions. Analyses 263 of OBT in the SPM demonstrate transient increases in concentration during dam flushing 264 operations. Those are most probably explained by the resuspension of fine tritiated particles 265 from watchmaking activities. As the increases were transient and not observed at all the 266 stations, no significant temporal nor spatial trend following dam flushing operations can be 267 drawn clearly. However, OBT is heterogeneously distributed in sediments of the Rhône River 268 and large amounts of this radionuclide are still stored in the Upper Rhône sediments. Extreme 269 events such as dam flushing operations can redistribute these storages to the downstream 270 part of the River. The radiotoxicity of free tritium (HTO) or organically bound tritium to 271 naturally occurring organic compounds (OBT) are low comparing to most other natural or 272 artificial radionuclides. Nevertheless, the specific radiotoxicity of organically bound tritium to 273 synthetic organic particles are unknown to our knowledge as well as their transfer rates 274 toward living organisms.

275 Acknowledgements

This study was supported by the Rhône Sediment Observatory (OSR), a multi-partner research program partly funded by the Rhône Plan and by the European Regional Development Fund (ERDF) allocated by the European Union. We thank the teams of OSR,

especially those of INRAE and CEREGE, for their contribution in the field for water and sediment sampling. We are very grateful to CNR, DREAL ARA, SIG and EDF services for cooperating with OSR and sharing their monitoring data.

282 **References**

- AFNOR, 2009. NF ISO 10694: Particle Size Analysis Laser Diffraction Methods. 51 pp.
- AFNOR, 1995. NF ISO 10694: Soil quality Determination of organic and total carbon after dry
 combustion (elementary analysis). 7 pp.
- 286 Beaugelin-Seiller, K., Boyer, P., Garnier-Laplace, J., Adam, C., 2002. Casteaur: A simple tool to
- assess the transfer of radionuclides in waterways. Health Phys. 83, 539-542.
 https://doi.org/10.1097/00004032-200210000-00013
- Bravard, J.-P., Clémens, A., 2008. Le Rhône en 100 questions. Méditerranée (report in French)
 290 295 pp.
- Bretier, M., Dabrin, A., Bessueille-Barbier, F., Coquery, M., Barbier-Bessueille, F., Coquery, M.,
- 292 2019. Comparison of integrative passive sampling and discrete monitoring to assess the
- impact of dam flushing event on dissolved trace elements concentrations. Sci. Total
- 294 Environ. 656, 433-446. https://doi.org/10.1016/j.scitotenv.2018.11.303
- Brown, C.B., 1944. The control of reservoir silting. US Gov. Print. Off. 521, 168 pp.

296 Ciffroy, P., Siclet, F., Damois, C., Luck, M., 2006. A dynamic model for assessing radiological

- consequences of tritium routinely released in rivers. Application to the Loire River. J.
- 298 Environ. Radioact. 90, 110–139. https://doi.org/10.1016/j.jenvrad.2006.06.012
- 299 Cossonnet, C., Neiva Marques, A.M., Gurriaran, R., 2009. Experience acquired on 300 environmental sample combustion for organically bound tritium measurement. Appl.
- 301 Radiat. Isot. 67, 809–811. https://doi.org/10.1016/j.apradiso.2009.01.039

- 302 Currie, L.A., 1968. Limits for Qualitative Detection and Quantitative Determination:
 303 Application to Radiochemistry. Anal. Chem. 40, 586-593.
 304 https://doi.org/10.1021/ac60259a007
- Ducros, L., Eyrolle, F., Vedova, C. Della, Charmasson, S., Leblanc, M., Mayer, A., Babic, M.,
 Antonelli, C., Mourier, D., Giner, F., 2018. Tritium in river waters from French
 Mediterranean catchments: Background levels and variability. Sci. Total Environ. 612,
 672-682. https://doi.org/10.1016/j.scitotenv.2017.08.026
- 309 Eisenbud, M., Bennett, B., Blanco, R.E., 1979. Tritium in the environment. NCRP Report No.
 310 62. Behav. Tritium Environ.
- Eyrolle-Boyer, F., Boyer, P., Claval, D., Charmasson, S., Cossonnet, C., 2014. Apparent
 enrichment of organically bound tritium in rivers explained by the heritage of our past. J.
- 313 Environ. Radioact. 136, 162–168. https://doi.org/10.1016/j.jenvrad.2014.05.019
- Eyrolle-Boyer, F., Claval, D., Cossonnet, C., Zebracki, M., Gairoard, S., Radakovitch, O., Calmon,
- 315 P., Leclerc, E., 2015. Tritium and 14C background levels in pristine aquatic systems and
- their potential sources of variability. J. Environ. Radioact. 139, 24–32.
 https://doi.org/10.1016/j.jenvrad.2014.09.015
- 318 Eyrolle, F., Lepage, H., Copard, Y., Ducros, L., Claval, D., Saey, L., Cossonnet, C., Giner, F.,
- 319 Mourier, D., 2018. A brief history of the origins and contents of Organically Bound Tritium
- 320 (OBT) and 14C in the sediments of the Rhône watershed. Sci. Total Environ. in review,
- 321 40-51. https://doi.org/10.1016/j.scitotenv.2018.06.074
- 322 Fruchard, F., Camenen, B., 2012. Reservoir sedimentation: different type of flushing-friendly
- flushing example of genissiat dam flushing. ICOLD Int. Symp. Dams a Chang. world 6 pp.
- 324 IRSN, 2015. Bilan de l'état radiologique de l'environnement français de juin 2011 à décembre
- 325 2014. PRP-ENV (french report) 253p.

326 IRSN, 2013. Constat radiologique Vallée du Rhône. Rapport final relatif au milieu aquatique.
 327 PRP-ENV/SESURE (french report) 37, 68p.

Jean-Baptiste, P., Baumier, D., Fourré, E., Dapoigny, A., Clavel, B., 2007. The distribution of
tritium in the terrestrial and aquatic environments of the Creys-Malville nuclear power
plant (2002-2005). J. Environ. Radioact. 94, 107-118.
https://doi.org/10.1016/j.jenvrad.2007.01.010

Jean-Baptiste, P., Fontugne, M., Fourré, E., Marang, L., Antonelli, C., Charmasson, S., Siclet, F.,
2018. Tritium and radiocarbon levels in the Rhône river delta and along the French
Mediterranean coastline. J. Environ. Radioact. 187, 53-64.
https://doi.org/10.1016/j.jenvrad.2018.01.031

- Kalnejais, L.H., Martin, W.R., Bothner, M.H., 2010. The release of dissolved nutrients and
 metals from coastal sediments due to resuspension. Mar. Chem. 121, 224-235.
 https://doi.org/10.1016/j.marchem.2010.05.002
- Kim, S.B., Baglan, N., Davis, P.A., 2013. Current understanding of organically bound tritium
 (OBT) in the environment. J. Environ. Radioact. 126, 83-91.
 https://doi.org/10.1016/j.jenvrad.2013.07.011
- Krejci, K., Zeller, J., 1979. Tritium pollution in the Swiss luminous compound industry, in:
 International Symposium on the Behaviour of Tritium in the Environment. IAEA, Vienna,
 pp. 65-77.
- Launay, M., 2014. Flux de matières en suspension, de mercure et de PCB particulaires dans le
 Rhône, du Léman à la Méditerranée. Thesis (in French) 434.
 https://doi.org/10.1002/oby.20222
- Lepage, H., Launay, M., Le Coz, J., Angot, H., Miège, C., Gairoard, S., Radakovitch, O., Coquery,
 M., 2020. Impact of dam flushing operations on sediment dynamics and quality in the

350 upper Rhône River, France. J. Environ. Manage. 255, 109886.
 351 https://doi.org/10.1016/j.jenvman.2019.109886

352 Masson, M., Angot, H., Le Bescond, C., Launay, M., Dabrin, A., Miège, C., Le Coz, J., Coquery,

353 M., 2018. Sampling of suspended particulate matter using particle traps in the Rhône

- River: Relevance and representativeness for the monitoring of contaminants. Sci. Total
- 355 Environ. 637–638, 538–549. https://doi.org/10.1016/j.scitotenv.2018.04.343
- Monnin, L., Ciffroy, P., Garnier, J.M., Ambrosi, J.P., Radakovitch, O., 2018. Remobilization of
 trace metals during laboratory resuspension of contaminated sediments from a dam
 reservoir. J. Soils Sediments 18, 2596–2613. https://doi.org/10.1007/s11368-018-19315
- 360 Morereau, A., Lepage, H., Claval, D., Cossonnet, C., Radakovitch, O., Ambrosi, J.-P., Mourier,
- B., Eyrolle, F., n.d. Technogenic tritium contamination from watchmaking industry and its
 resiliency in river sediments of the Rhône River (France).
- 363 OFSP, 2015. Radenviro.ch [WWW Document]. URL http://www.radenviro.ch/fr364 CH/measures/274 (accessed 7.5.16).
- 365 Peter, D.H., Castella, E., Slaveykova, V.I., 2014. Effects of a reservoir flushing on trace metal

366 partitioning, speciation and benthic invertebrates in the floodplain. Environ. Sci. Process.

367 Impacts 16, 2692–2702. https://doi.org/10.1039/c4em00387j

368 Peteuil, C., Fruchart, F., Abadie, F., Reynaud, S., Camenen, B., Guertault, L., 2013. Sustainable

- 369 management of sediment fluxes in reservoir by environmental friendly flushing : the case
- study of the Genissiat dam on the upper Rhone River (France), in: 12th International
 Conference on River Sedimentation. Kyoto (Japan), pp. 1147–1156.
- Poulier, G., Launay, M., Le Bescond, C., Thollet, F., Coquery, M., 2019. Combining flux
 monitoring and estimation to establish annual budgets of suspended particulate matter


and associated pollutants in the Rhône River from Lake Geneva to the Mediterranean
Sea. Sci. Total Environ. 658, 457–473. https://doi.org/10.1016/J.SCITOTENV.2018.12.075
Provansal, M., Dufour, S., Sabatier, F., Anthony, E.J., Raccasi, G., Robresco, S., 2014. The
geomorphic evolution and sediment balance of the lower Rhône River (southern France)


- 378 over the last 130 years: Hydropower dams versus other control factors. Geomorphology
- 379 219, 27-41. https://doi.org/10.1016/j.geomorph.2014.04.033
- Schulze, T., Ricking, M., Schröter-Kermani, C., Körner, A., Denner, H.-D., Weinfurtner, K.,
 Winkler, A., Pekdeger, A., 2007. The German Environmental Specimen Bank Sampling,
- 382 processing, and archiving sediment and suspended particulate matter. J. Soils Sediments
- 383 7, 361-367. https://doi.org/10.1065/jss2007.08.248
- Schürch, M., Kozel, R., Schotterer, U., Tripet, J.-P.P., Sch??rch, M., Kozel, R., Schotterer, U.,
 Tripet, J.-P.P., 2003. Observation of isotopes in the water cycle—the Swiss National
 Network (NISOT). Environ. Geol. 45, 1–11. https://doi.org/10.1007/s00254-003-0843-9
- 387 Syvitski, J.P.M., Vörösmarty, C.J., Kettner, A.J., Green, P., 2005. Impact of humans on the flux
- of terrestrial sediment to the global coastal ocean. Science (80-.). 308, 376-380.
 https://doi.org/10.1126/science.1109454
- 390 Thollet, F., Le Bescond, C., Lagouy, M., Gruat, A., Grisot, G., Le Coz, J., Coquery, M., Lepage, H.,
- 391 Gairoard, S., Gattacceca, J.C., Ambrosi, J.-P., Radakovitch, O., 2018. Observatoire des
 392 sédiments du Rhône. https://doi.org/10.17180/OBS.OSR
- 393 Ueda, S., Hasegawa, H., Kakiuchi, H., Ochiai, S., Akata, N., Hisamatsu, S., 2015. Nuclear
- 394 accident-derived ³H in river water of Fukushima Prefecture during 2011-2014. J. Environ.
- 395 Radioact. 146, 102–109. https://doi.org/10.1016/j.jenvrad.2015.04.014

Figure 1 – Location of the studied dams, the nuclear power plant and the sampling stations in the Rhône River.

Figure 2 – Concentration of tritium in filtered waters (HTO in Bq L⁻¹) measured at the four stations during the flushing operations of Génissiat, Chancy-Pougny and Verbois dams and range of the concentrations observed on the water of the Rhône River in 2012 (IRSN, 2013). * samples with HTO concentration below the detection limit.

Figure 3 - Concentration of organically bound tritium (OBT in Bq L^{-1}_{cw}) measured in SPM collected at the four stations during the flushing operations of Génissiat, Chancy-Pougny and Verbois dams and range of the concentrations observed on sediment and SPM of the Rhône River in 2012 (Eyrolle *et al.*, (2018)).









 Table 1 - Number (n) of samples collected during the studied flushing operations for tritiated water (HTO) and organically bound tritium (OBT) and associated sampling method used. AWS = automatic water sampler, PT = particle trap.

Location	Latitude (WGS 1984)	Longitude (WGS 1984)	НТО	ОВТ
A	+46.1442	+5.9644	Manual (n=7)	PT (n=5)
В	+45.9642	+5.8310	Manual (n=6)	PT (n=6)
С	+45.80	+5.4322	AWS (n=6)	PT (n=5)
D	+5.0896	+45.8121	Manual (n=13)	PT (n=6)

Declaration of interests

I The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

□ The authors declare the following financial interests/personal relationships which may be considered as potential competing interests:






Table ESM1 - Tritiated water concentration in the water samples collected for this study. "<" indicate concentration under the detection limit.

r	limit.	тт
Station	Sampling date	Concentration (Bq L ⁻¹)
A	06/09/2012 10:20	1.5 ± 0.7
A	06/10/2012 12:20	1.0 ± 0.7
A	06/11/2012 11:30	1.0 ± 0.7
A	06/12/2012 11:15	1.2 ± 0.7
A	06/13/2012 10:55	< 1.2
A	06/14/2012 11:00	0.9 ± 0.6
A	06/15/2012 11:00	0.8 ± 0.6
В	06/04/2012 12:05	1.0 ± 0.6
В	06/05/2012 14:00	1.4 ± 0.6
В	06/06/2012 14:00	1.5 ± 0.6
В	06/07/2012 14:15	1.2 ± 0.6
В	06/08/2012 16:15	1.1 ± 0.6
В	06/09/2012 12:15	1.1 ± 0.6
С	05/25/2012 09:00	< 1.4
С	06/01/2012 09:00	< 1.5
С	06/07/2012 09:00	0.8 ± 0.7
С	06/13/2012 09:00	< 1.2
С	06/19/2012 09:00	< 1.3
С	06/25/2012 09:00	< 1.2
D	06/04/2012 12:00	0.7±0.6
D	06/05/2012 12:00	13.1 ± 1.0
D	06/06/2012 12:00	0.9±0.6
D	06/07/2012 12:00	1.2 ± 0.6
D	06/08/2012 12:00	1.1 ± 0.6
D	06/09/2012 12:00	1.2 ± 1.2
D	06/10/2012 12:00	1.7 ± 0.7
D	06/11/2012 12:00	1.2 ± 0.7
D	06/12/2012 12:00	1.3 ± 0.7
D	06/13/2012 12:00	0.8 ± 0.6
D	06/14/2012 12:00	0.6 ± 0.6
D	06/15/2012 12:00	0.8 ± 0.6
D	06/16/2012 12:00	11.8 ± 1.0

 Table ESM2 - Organically bound tritium concentrations, clay/silt/sand content and POC concentrations in the suspended particulate matters (SPM) samples collected by particles trap for this study. n.a.: not analyzed; ± analytical uncertainty.

Ctation		Compliant and	Concentration	Concentration	Clay	Silt	Sand	POC
Station	Sampling start	Sampling end	(Bq kg ⁻¹)	(Bq L⁻¹ _{cw})	(%)	(%)	(%)	(mg.kg ⁻¹)
Α	06/10/2012 11:00	06/11/2012 07:00	16 ± 8	1180 ± 400	3.4	72.8	23.8	9.2 ± 0.5
A	06/11/2012 11:15	06/12/2012 07:00	7 ± 1	750 ± 40	2.5	50.4	47.1	9.8 ± 0.5
A	06/14/2012 08:00	06/15/2012 08:00	5 ± 1	360 ± 20	2.0	41.1	56.8	9.6 ± 0.5
Α	06/15/2012 08:00	06/16/2012 08:00	8 ± 1	870 ± 40	n.a	n.a	n.a	n.a
A	06/16/2012 12:00	06/20/2012 11:59	15 ± 1	1090 ± 60	n.a	n.a	n.a	n.a
В	06/05/2012 12:00	06/06/2012 11:59	17 ± 1	750 ± 160	2.2	59.9	37.9	22.8 ± 0.9
В	06/06/2012 12:00	06/07/2012 11:59	12 ± 1	940 ± 330	2.0	53.1	44.9	18.8 ± 0.8
В	06/07/2012 12:00	06/08/2012 11:59	6 ± 1	540 ± 220	2.8	68.0	29.3	15.3 ± 0.7
В	06/08/2012 12:00	06/09/2012 11:59	24 ± 2	1500 ± 420	1.5	35.8	62.7	6.8 ± 0.4
В	06/09/2012 12:00	06/10/2012 11:59	6 ± 1	870 ± 580	1.6	42.7	55.7	12.1 ± 0.6
В	06/10/2012 12:00	06/11/2012 11:59	5 ± 1	730 ± 460	1.9	47.3	50.8	11.9 ± 0.6
С	06/09/2012 12:00	06/11/2012 11:59	279 ± 14	11700 ± 2300	7.1	92.7	0.2	15.3 ± 0.7
С	06/11/2012 12:00	06/14/2012 11:59	51 ± 3	2250 ± 120	4.4	94.2	1.3	11.8 ± 0.5
С	06/14/2012 12:00	06/16/2012 11:59	23 ± 1	1100 ± 60	5.2	93.2	1.7	11.3 ± 0.5
С	06/16/2012 12:00	06/20/2012 11:59	8 ± 1	340 ± 20	4.7	87.9	7.4	n.a
С	06/20/2012 12:00	07/03/2012 11:59	21 ± 2	1130 ± 60	n.a	n.a	n.a	n.a

D	06/05/2012 12:00	06/07/2012 11:59	4 ± 1	180 ± 40	4.8	83.9	11.4	15.8 ± 0.7
D	06/09/2012 12:00	06/11/2012 11:59	32 ± 2	1210 ± 210	4.7	93.2	2.1	17.1 ± 0.8
D	06/11/2012 12:00	06/14/2012 11:59	174 ± 9	6670 ± 340	3.2	54.6	42.2	8.1 ± 0.5
D	06/14/2012 12:00	06/16/2012 11:59	5 ± 1	400 ± 20	3.6	93.0	3.5	12.1 ± 0.6
D	06/16/2012 12:00	06/20/2012 11:59	10 ± 1	730 ± 40	5.6	92.5	1.9	n.a
D	06/20/2012 12:00	07/03/2012 11:59	20 ± 1	860 ± 40	4.9	93.0	2.0	36.0 ± 1.8