

Agent-based Decision Making for Adoption of Smart Energy Solutions

Kristoffer Christensen, Zheng Ma, Magnus Verbak, Yves Demazeau, Bo Nørregaard Jørgensen

▶ To cite this version:

Kristoffer Christensen, Zheng Ma, Magnus Verbak, Yves Demazeau, Bo Nørregaard Jørgensen. Agentbased Decision Making for Adoption of Smart Energy Solutions. 2019 IEEE Sciences and Humanities International Research Conference (SHIRCON), Nov 2019, Lima, Peru. pp.05-08, 10.1109/SHIR-CON48091.2019.9024880. hal-02874977

HAL Id: hal-02874977

https://hal.science/hal-02874977

Submitted on 10 Dec 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Agent-based Decision Making for Adoption of Smart Energy Solutions

Kristoffer Christensen
Center for Energy Informatics
Mærsk Mc-Kinney Møller Institute
University of Southern Denmark
Odense, Denmark
kric@mmmi.sdu.dk

Yves Demazeau

Laboratoire d'Informatique de
Grenoble

Centre National de la Recherche
Scientifique
Grenoble, France
yves.demazeau@imag.fr

Zheng Ma
Center for Energy Informatics
Mærsk Mc-Kinney Møller Institute
University of Southern Denmark
Odense, Denmark
zma@mmmi.sdu.dk

Bo Nørregaard Jørgensen
Center for Energy Informatics
Mærsk Mc-Kinney Møller Institute
University of Southern Denmark
Odense, Denmark
bnj@mmmi.sdu.dk

Magnus Værbak
Center for Energy Informatics
Mærsk Mc-Kinney Møller Institute
University of Southern Denmark
Odense, Denmark
mavar@mmmi.sdu.dk

Abstract— Agent-based simulation of the decision-making process for adoption of smart energy solutions can provide evidence for smart energy solutions' providers to decide for a business strategy which results in the best adoption rate. The adoption rate of smart energy solutions is important in achieving climate goals, such as the Danish goal to have 100% renewable electricity production by 2030. This paper shows how agent-based simulation can be used to investigate the decision-making process for adoption of smart energy solutions. The study investigates a case about Danish commercial greenhouse growers' adoption of a demand response program. The simulation outputs an adoption curve and grower information. The results provide the maximum monetary cost for achieving an adoption rate of 50% in 5 years.

Keywords—agent-based simulation, smart energy solutions, decision making, innovation adoption.

I. INTRODUCTION

The Paris Agreement was made with 181 parties [1] in 2015. The Paris Agreement is about keeping a global temperature rise below 2—above pre-industrial levels and to pursue efforts to limit the temperature increase even further to 1.5—in this century [2]. Denmark takes part in this agreement and has designed its own climate goals in accordance with the Paris Agreement. Denmark's Energy Agreement from 2018 states that by 2030, 100% of electricity production comes from renewable energy sources [3]. A long-term objective of the agreement is for Denmark to be a low-emission society in 2050, independent of fossil fuels [3, 4]. In the future, energy use should be more efficient as well as more intelligent that there is a balance between the consumption and the fluctuating renewable energy sources.

In order to achieve this goal, the entire energy system must be designed to integrate fluctuating energy generation and consumers have to adopt technologies that allow them to use energy more flexible [5]. One way to do so is to invest heavily in expanding the energy infrastructure. Another and cheaper way is to use Demand Response (DR), which allows the use of energy flexibility at the consumption side.

However, introducing new smart energy solutions in the energy system does not mean the solutions will be adopted and utilized by consumers, and many factors affect the decision making of adopting and implementing a new solution. One factor is the adoption rate that depends on the barriers for adopting an innovation and the triggers which

are used to overcome these barriers [6]. A great tool for studying decision-making is agent-based modeling which can simulate consumer behavior in a specific environment. By simulating consumer's adoption behaviors, the solution providers can make strategies that promote and increase the adoption rate of an innovative solution.

Therefore, this paper aims to investigate the adoption of DR with a case study of Danish commercial greenhouses and use agent-based simulation to identify how the monetary costs affect the adoption rate of DR by commercial greenhouse growers.

This paper is organized as follows: first, the research background aims to give an understanding of this research; second, the simulation design is described to introduce the simulation logic; third, the case study is described, and the results are presented and discussed; last, a conclusion including the research findings is presented.

II. RESEARCH BACKGROUND

Smart grid is a modernized electrical grid allowing for two-way communication. Smart grid consists of a wide range of technologies including advanced sensors, energy storage, and smart meters [7]. One of the most important technologies is smart meters which enable two-way communication [7]. Flexibility is the ability of electrical systems to maintain the balance between energy supply and demand [8]. DR is voluntary changes in consumers' electricity usage patterns – in response to market signals [8]. It is possible to utilize consumer energy flexibility through DR by use of two-way communication.

DR provides the ability to reduce the use of peak load generation, electricity cost, and to improve system reliability [9]. DR programs aim to incentivize changes in the electricity consumption patterns in response to the varying electricity prices or incentivize payments to lower electricity consumption at times with high market prices [10]. There are two DR approaches called explicit- and implicit DR.

Explicit DR is a program that gives the end-users the possibility to compete in the wholesale market with producers, balancing and ancillary services. This is possible with services provided by aggregators or single large consumers. Aggregators trade aggregated load in the electricity markets, receive payment comparable with the

generation, and consumers receive direct payment in the explicit DR [10, 11].

Implicit DR program refers to consumers being exposed to time-varying electricity prices that reflect electricity prices in different time periods. Consumers react to those price differences without commitment. These prices are agreed beforehand as part of their electricity supply contract. This program, therefore, does not allow consumers to participate alongside generation in the electricity markets [10, 11].

In Denmark, DR aggregation can only take place through suppliers, as independent aggregators are not allowed. The balancing programs are mainly designed for production and not consumption [11]. Therefore, consumers only have the opportunity to participate in the implicit DR program in Denmark. Hence, this paper chooses the implicit DR for the case study.

This paper investigates the decision-making process for adoption of smart energy solutions such as DR. A decision-making process consists, according to [12], of the following 7 steps: 1) identify the decision, 2) gather information, 3) identify alternatives, 4) weigh the evidence, 5) choose among alternatives, 6) take action, and 7) review your decision. By knowing the adoption behavior of consumers, the adoption of smart energy solutions can be studied using agent-based simulation. This model can then help solution providers to simulate decision alternatives- step 5 of the decision-making process, and to choose the right actions (step 6).

However, the agent-based model relies on detailed innovation adoption behavior of the consumers. Innovation adoption means that consumers make full use of the innovation [6]. The decision that has to be taken should encourage the adoption of smart energy solutions (step 1, identifying the decision). The adoption rate is the simulation factor which measures what decision is the best. The adoption rate is an important element for the investigation of the market reaction towards an innovation. Adoption rate is defined by [13] as "The rate of adoption is the pace at which new technology is acquired and used by the public." This can be represented by the number of members of the society who start using new technology or innovation during a specific period of time. Hence, the decision alternative with the highest adoption rate will be used.

III. SIMULATION DESIGN

The agent-based simulation is used in this paper for studying the adoption of a smart energy solution. The agents in this paper consist of a population of commercial greenhouse growers in Denmark. The implicit DR program is chosen as a smart energy solution.

Agent-based simulation is one of the artificial intelligence methods which allows agents to behave as close to real-life as possible. The agents are designed to operate in a certain environment and have knowledge about how to behave and to react to different changes. This knowledge is fed into the agent logic through data (e.g. historical data for how an agent behaves to a specific change in the environment) [14].

The model is designed and developed in the software tool- AnyLogic. AnyLogic is a single simulation software tool that supports three simulation modeling methods:

system dynamics, discrete event, and agent-based modeling and allows you to create multi-method models [15].

The simulation logic is to check each simulation hour if any adoption has been taken and to stop the simulation when 50% of the population has adopted it (Fig. 1, green flowchart). The decision logic of the simulation is shown in the orange flow chart, in Fig. 1. There are many parameters determining the adoption rate. In this specific case, for simplicity, the decision is only the monetary benefits. The simulation uses a retrospective method which looks at the possible saving if the smart energy solution is adopted from day one in the simulation by use of the historical data. Hence, when the accumulated saving during the simulation time equals the cost of adopting the smart energy solution, the consumer adopts the innovation.

This paper mainly investigates monetary benefits. Hence, important parameters are the adoption cost structure (e.g. one-time payment) and electricity price structure (e.g. subsidize DR programs by reducing electricity taxes).

Fig. 2 is a screenshot of the model developed in AnyLogic, and shows the running simulation: 1) shows the information of the simulation time and also provides information about which type of agents adopt the solution, including the Return on Investment (ROI) time 2) are the input parameters which allow changes to simulate a specific strategies 3) represents a 24-hour forecast of the solar irradiations based on the historical data starting from 2015 4) illustrates a 24-hour forecast of the electricity spot price also based on historical data from 2015 5) is a calculated forecast of the photosynthesis gain per spot price to determine when the plant obtains the highest photosynthesis at the lowest price. This is found from the solar irradiation and spot price forecast. The photosynthesis gain as a function to the solar irradiation is non-linear. Hence, the extra gain added by supplementing the natural light by artificial light during the day may be low compared to the gain from artificial light alone during the night.




Fig. 1. Flowcharts of the model simulation logic. [Orange: Decision logic] [Green: Simulation logic].




Fig. 2. Screenshot of the interface from the developed simulation model in AnyLogic.

To illustrate this, a second graph is added with a different light consumption of 20 Watts per square meters. Comparing these two graphs, it can be seen that the differences in photosynthesis gain are high during the nights and low during the daytime. 6) shows the obtained artificial light schedule based on the hours with the highest photosynthesis gain per spot price where it is on at '1' and off at '0'. The number of hours with artificial light depends on when the plant's required light sum (daily required amount of light) has been reached. Furthermore, the plant requirements for dark hours have to be considered too. 7) is the light schedule before implementing the smart energy solution which is used to find the achieved savings by adopting the new solution. The light schedule is based on information from a commercial greenhouse in Denmark. 8) is the adoption curve showing the percentage of the population who have adopted the solution.

IV. CASE STUDY

Commercial greenhouses in Denmark are chosen due to their large electricity consumption. In 2017, 436 commercial greenhouse growers consumed electricity corresponding to 0.7% of the total Danish consumption [16, 17]. 75% of the consumed electricity is estimated to come from supplemental lighting [18]. These numbers show the potential of the electricity cost reduction if the commercial greenhouses participate in DR programs.

Commercial greenhouses produce plants, similar to other industries that produce goods. However, the production process depends on the types of plants. The plants are placed in different greenhouse areas based on the phases of the growing process [19]. This is due to the requirements of lighting and temperature change during the process. Therefore, artificial lighting varies in installation and usage in different greenhouses. According to a plant expert, Prof. Carl-Otto Ottosen, Department of Food Science, Aarhus University, the installed artificial lighting

power depends on the required light sum (the daily required light for a plant) for the specific plant species. Hence, a population of different commercial greenhouse growers is made based on their types of plants.

The population has been created based on data and information from the plant expert and 2017 nurseries statistics from Statistics Denmark (the national authority on Danish statistics) [20]. First, they are divided into the plant types: tomatoes, cucumbers, herbs, pot plants, and salad. These categories include information about the necessary installed artificial light power to meet the plant type's required light sums. Each of the categories is divided into 7 segments based on the greenhouse area. The population is implemented in the model by setting up in an excel sheet and imported to AnyLogic, which creates a population of agents. The case study investigates at what time 50% of the population has adopted technologies for participating in an implicit DR program. This simulation will be used to find the maximum cost of 50% adoption within 5 years by changing the investment parameter (see Fig. 2). The simulation starts in 2015 (corresponding to the historical data) and the adoption occurs when savings equal to the cost of adoption, and the adoption time equals to the ROI time. A ROI time of 5 years is estimated to be reasonable for medium-sized industries like commercial greenhouses. Furthermore, the simulation identifies the commercial greenhouse segments who adopt and at what rate.

V. RESULTS AND DISCUSSION

The simulation output is shown in Fig. 3 and Table I. Fig. 3 illustrates the adoption curve which predicts the adoption rate based on the model setup. The information behind the curve can be found in Table I. Table I shows the type of commercial greenhouses who have adopted the solution and at what time. From the graph and table, it can be found that 50% of the adoption happens after 4 years, 10 months, and 19 days. This adoption is for a one-time

payment cost structure with a maximum adoption cost of 1.765 million DKK (€ 0.236 million) for each consumer. It means if the adoption cost equals to or is less than 1.765 million DKK per commercial greenhouse, 50% of the Danish commercial greenhouses will adopt this solution within 5 years under the current Danish electricity cost structure.




Fig. 3. Adoption curve for commercial greenhouses' adoption of DR. [Xaxis: Hours] [Y-axis: Adoption percentage of the population]

Furthermore, the simulation shows (in TABLE I) that the commercial greenhouses who adopt first are the ones that produce either pot plants, tomatoes, cucumbers or herbs, and all with an area of more than 20,000 m². These results suggest that if the monetary cost for adoption is more than DKK 1.765 million it is necessary to incentivize commercial greenhouses in other ways to reach a 50% adoption rate of 5 years.

TABLE I. ADOPTING AGENTS' TYPE AND RATE

Plant type	Grower segment [m²]	ROI time: years	ROI time: months	ROI time: days
Pot plants	>20,000	0	3	14
Tomatoes	>20,000	0	3	20
Cucumber	>20,000	0	4	1
Herbs	>20,000	0	6	13
Pot plants	15,000-19,999	0	8	6
Salad	>20,000	0	8	10
Salad	15,000-19,999	0	9	3
Tomatoes	10,000-14,999	1	1	15
Cucumber	10,000-14,999	1	2	22
Pot plants	10,000-14,999	1	3	13
Herbs	10,000-14,999	1	4	6
Salad	10,000-14,999	1	5	9
Tomatoes	5,000-9,999	1	10	10
Pot plants	5,000-9,999	2	2	11
Cucumber	5,000-9,999	2	3	20
Herbs	5,000-9,999	2	5	11
Pot plants	2,000-4,999	4	10	19

VI. CONCLUSION

This paper investigates how the monetary factor affects the adoption of smart energy solutions. The agent-based simulation in this paper mainly helps strategy decision support. The paper presents how agent-based simulation can be used in the decision-making for adoption of smart energy solutions. The case study demonstrates that agent-based simulation works well as a tool for studying decisionmaking behavior. The simulation result estimates that it is possible to reach an adoption rate of 50% under 5 years with a maximum adoption cost of 1.765 million DKK with the current electricity price structure. However, if a higher adoption cost applies, regulation is needed to incentivize the consumers to adopt new solutions with the adoption rate of 50% under 5 years. In reality, besides the monetary factors, many other factors such as social, compatibility, and

complexity factors affect the adoption of an innovation [21]. Therefore, a model considering more factors is recommended for future research. Furthermore, this paper suggests a future research to identify the innovators, early adopters, and early majorities in the adoption curve.

REFERENCES

- United_Nations_Treaty_Collection. "7. d Paris Agreement." [1] https://treaties.un.org/Pages/ViewDetails.aspx?src=TREATY &mtdsg_no=XXVII-7-d&chapter=27&clang=_en_ 10/13/2018).
- [2] United Nations Climate Change. "The Paris Agreement." https://unfccc.int/process-and-meetings/the-parisagreement/the-paris-agreement (accessed 10/13/2018)
- [3] Danish Energy Agency. "Energiaftale - af 29. juni 2018." https://efkm.dk/media/12222/energiaftale2018.pdf (accessed 10/13/2018).
- U. a. C. Danish_Ministry_of_Energy. "The climate initiative in [4] Denmark." https://en.efkm.dk/climate-and-weather/theclimate-initiative-in-denmark/ (accessed 09/27/2019).
- E. a. B. Danish_Ministry_of_Climate. "Smart Grid Strategy." [5] https://ens.dk/sites/ens.dk/files/Globalcooperation/smart_grid_ strategy eng.pdf (accessed 09/27/2019).
- R. Reinhardt, N. Hietschold, and S. Gurtner, "Overcoming [6] consumer resistance to innovations - an analysis of adoption triggers," 2017.
- K. T. Raimi and A. R. Carrico, "Understanding and beliefs about smart energy technology," *Energy Research & Social* [7] 68-74. 2016. Science. vol. 12. pp. 10.1016/j.erss.2015.12.018.
- [8] Z. Ma, J. D. Billanes, and B. N. Jørgensen, "Aggregation Potentials for Buildings-Business Models of Demand Response and Virtual Power Plants," energies, pp. 1-19, 2017. [Online]. https://www.mdpi.com/1996-1073/10/10/1646 Available: (accessed 04/11/2019).
- [9] M. Minou, G. D. Stamoulis, G. Thanos, and V. Chandan, "Incentives and targeting policies for automated demand response contracts. ," In Proceedings of the 2015 IEEE International Conference on Smart Grid Communications (SmartGridComm), pp. 557-562, 2-5 November2015. [Online]. Available:http://nes.aueb.gr/publications/SMARTGRIDCOM _camera_ready_final_v1.pdf_(accessed 04/11/2019).
- P. Bertoldi, P. Zancanella, and B. Boza-Kiss, "Demand Response status in EU Member States," *EUR 27998 EN*, pp. 1-[10] 140, 2016, doi: 10.2790/962868.
- SEDC, "Mapping Demand Response in Europe Today 2015," [11] Smart Energy Demand Coalation (SEDC), pp. 1-187, 2015.
- [12] University of Massachusetts Darthmouth. "Decision-making https://www.umassd.edu/fycm/decisionmaking/process/ (accessed 06/07/2019).
- [13] W. Kenton and Investopedia. "Rate of Adoption." Investopedia. https://www.investopedia.com/terms/r/rate-of-adoption.asp (accessed 04/11/2019).
- [14] A. Wodecki, Artificial Intelligence In Value Creation -Improving Competitive Advantage. 2019, p. 340.
- I. Grigoryev, "Anylogic in three days," 2016. [15]
- Danmarks Statistik. "Energiforbruget i væksthuse halveret på 15 år."https://www.dst.dk/da/Statistik/nyt/NytHtml?cid=25153 [16] (accessed 04/09/2019).
- [17] Energistyrelsen, "Energistatistik 2017," pp. 1-58, 2017. [Online]. Available: https://ens.dk/sites/ens.dk/files/Statistik/pub2017dk.pdf (accessed 04/11/2019).
- [18] J. C. Sørensen, K. H. Kiaer, C.-O. Ottosen, and B. N. Jørgensen. "DynaGrow - Multi-Objective Optimization for Energy Costefficient Control of Supplemental Light in Greenhouses," 8th International Joint Conference on Computational Intelligence (IJCCI 2016), vol. 1: ECTA, pp. 41-48, 2016.
- Γ19**1**
- J. Korsgaard, "Energy Flexible Industry 4.0," pp. 16-18, 2018. Statistics Denmark, "Tabeller til Energistyrelsen og Dansk [20] Gartneri, landbrugs- og gartneritællingen 2018, tal om væksthuse " 2018.
- [21] E. M. Rogers, Diffusion of Innovations, Fifth ed. Free Press, 2003, p. 551.