



HAL
open science

Review of the mechanisms of debris-flow impact against barriers

S Poudyal, C. Choi, D Song, G G D Zhou, C y Yune, Y. Cui, A. Leonardi, M Busslinger, C Wendeler, Guillaume Piton, et al.

► To cite this version:

S Poudyal, C. Choi, D Song, G G D Zhou, C y Yune, et al.. Review of the mechanisms of debris-flow impact against barriers. International Conference on Debris-Flow Hazards Mitigation: Mechanics, Prediction, and Assessment, Jun 2019, Golden, United States. pp.1027-1033. hal-02923131

HAL Id: hal-02923131

<https://hal.science/hal-02923131>

Submitted on 26 Aug 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Review of the mechanisms of debris-flow impact against barriers

S. Poudyal^{a,*}, C.E. Choi^{a,b}, D. Song^{c,d}, G.G.D. Zhou^d, C.Y. Yune^e, Y. Cui^a, A. Leonardif,
M. Busslinger^g, C. Wendeler^h, G. Pitonⁱ, E. Moase^j & A. Strouth^j

^a Department of Civil and Environmental Engineering, The Hong Kong University of Science and Technology, Hong Kong

^b HKUST Jockey Club Institute for Advanced Study, The Hong Kong University of Science and Technology, Hong Kong

^c University of Chinese Academy of Sciences, Beijing, China

^d Institute of Mountain Hazards and Environment, Chinese Academy of Sciences & Ministry of Water Conservancy, Chengdu, China

^e Gangneung-Wonju National University, South Korea

^f Politecnico di Torino, Turin, Italy

^g Tetra Tech Canada Inc, Vancouver Geotechnical Engineering, Vancouver, Canada

^h Geobrugg AG, Switzerland

ⁱ Institut national de recherche en sciences et technologies pour l'environnement et l'agriculture (IRSTEA), France

^j BGC Engineering, Vancouver

Abstract

Our limited understanding of the mechanisms pertaining to the force exerted by debris flows on barriers makes it difficult to ascertain whether a design is inadequate, adequate, or over-designed. The main scientific challenge is because flow-type landslides impacting a rigid barrier is rarely captured in the field, and no systematic, physical experimental data is available to reveal the impact mechanisms. An important consideration in flow-structure interaction is that the impact dynamics can differ radically depending on the composition of the flow. Currently, no framework exists that can characterize the impact behavior for a wide range of flow compositions. This review paper examines recent works on debris-flow structure interactions and the limitations of commonly used approaches to estimate the impact load for the design of barriers. Key challenges faced in this area and outlook for further research are discussed.

Keywords: Debris flows, barriers, impact mechanisms, flow compositions,

1. Background

The Association of Geohazard Professionals (AGHP) is an industry association that was created in 2013 to support the development of standards, specifications, and best practices for the design and implementation of geohazard-related technologies and products; and to provide education to the geohazard community. The AGHP Debris Flow and Steep Creek Hazards Mitigation Committee (Committee) was formed in 2017 and currently includes members from North America, Asia, and Europe. The first committee workshop was held on June 3, 2018 in Canmore Alberta, Canada and included a discussion of the wide range of design guidelines that are available. The Committee recognized that design practices for debris-flow mitigation structures vary between different world regions, and some aspects of practice are not well described in the existing guidelines. This paper is a collective effort by AGHP members and focuses specifically on current understanding of debris-flow impact mechanism against barriers.

Steep creek flows made of mixtures of soil, rock and water, surge downslope at high velocities. These flows include floods, hyper-concentrated flows, debris flows, and rock avalanches (Hung et al., 2014). To mitigate these hazardous flows, rigid barriers (e.g., Takahashi, 2014) and flexible barriers (e.g., DeNatale et al., 1999; Wendeler, 2008; Bugnion et al., 2012) are commonly installed in the predicted flow paths. Correspondingly, a reliable estimate of impact load is required to design these barriers. However, current design approaches for estimating impact loads relies heavily on empiricism and do not explicitly consider the composition of the flow, including the particle size and the ratio of solids

* Corresponding author e-mail address: spoudyal@connect.ust.hk

to fluids. Such approaches make it difficult to ascertain whether a barrier design is robust, inadequate, or over-designed.

Our present knowledge in this area is deficient for three main reasons. First, debris flows impacting structures are rarely captured in the field. Second, debris flows are scale-dependent phenomena (Iverson, 1997; Zhou and Ng, 2010). More specifically, small-scale physical experiments (e.g., Canelli et al., 2012; Scheidl et al., 2013) cannot holistically model the absolute stress state in a granular assembly, the timescale for pore pressure dissipation, and the degree of viscous shearing observed in prototype flows (Iverson, 2015). To capture the granular and fluid stresses in real flows more holistically, centrifuge model tests (Bowman et al., 2010) or large-scale physical experiments are necessary (Iverson, 2015). Third, depending on flow composition, specifically the ratio of solids to fluids (Iverson, 1997; Iverson and George, 2014) and particle size (Faug, 2015; Song, 2016; Song et al., 2017a and 2017b), the impact dynamics of debris flows can vary drastically. A framework that characterizes the impact mechanism of debris flows by considering a wide range of flow compositions—solid-fluid interaction and particle size effects—is necessary to make reliable estimations of the impact load.

2. Impact Models

Current opportunities for advancing our understanding of the impact mechanism of debris flows are reflected in international guidelines (VanDine, 1996; MLR, 2006; NILIM, 2007; Kwan, 2012). An estimate of impact force exerted by debris flows, assuming continuum-like behavior, is based on force equilibrium in hydrostatic models and momentum conservation in hydrodynamic models. Another type of loading that needs to be considered is discrete loading, which is created by short duration impulses from large particles (Ng et al., 2018). Existing approaches for estimating loading are discussed below.

2.1. Continuum loading

Continuum-based approaches adopt empirical coefficients to account for various uncertainties, including unknown impact mechanisms and flow composition. For example, the momentum-based equation for estimating impact (Hungri et al., 1984; Kwan, 2012; Volkwein et al., 2014) is given as follows:

$$F = \alpha \rho v^2 h w \tag{1}$$

where α is the empirical pressure coefficient, ρ is the bulk density, v is the impact velocity, h is the flow thickness and w is the channel width. Clearly, flow composition is not explicitly considered in equation 1, and α accounts for the complexity of variables involved in natural geological material and natural settings. To highlight the empiricism of equation 1, a literature review shows that α values are not consistent (Table 1). For example, α of 3.5 is recommended for less viscous flows and 1.0 to 5.3 for more viscous flows (Scotton and Deganutti, 1997). Thurber Consultants Ltd. (1984) recommended α value of 3 to 5 for flow compositions in Austria and Switzerland. Kwan (2012) recommended α values from 2.0 to 2.5, depending on the type of structural countermeasure. Sovilla et al. (2016) demonstrates that the dimensions of the structure also fundamentally influence the impact pressure. Clearly, a scientifically based approach is urgently required to characterize the impact behavior for a wide range of debris flows.

Table 1. Summary of hydrodynamic models for estimating debris flow impact on a rigid barrier

Pressure coefficient (α)	Reference
$\alpha = 1.0$	VanDine (1996)
$\alpha = 3.0$ to 5.0	Zhang (1993)
$\alpha = 1.0$ for circular structure	MLR (2004)
$\alpha = 1.3$ for rectangular structure	
$\alpha = 1.5$ for square structure	
$\alpha = 2.5$ to 3.0	Lo (2000), Kwan (2012)
$\alpha = 2.0$	Vagnon and Segalini (2016)
$\alpha = 1.5$ to 5.5	Canelli et al., (2012)
$\alpha = 2.0$ to 4.0	Hübl and Holzinger (2003)
$\alpha = 1.0$	NILIM (2007)
$\alpha = 1.0$	SWCB (2005)

Ancey and Bain (2015), Faug (2015), Ashwood and Hungr (2016), and Song (2016) all suggest that to more appropriately characterize impact, both static and dynamic loading must be explicitly considered as follows:

$$F = 0.5k\rho g(\beta h)^2 w + \alpha' \rho v^2 h w \tag{2}$$

where α' is the coefficient for dynamic effect only, k is the coefficient for static effect only, and β is the ratio between the height of the static deposit and flow thickness before impact. Song et al. (2017b) further characterized the pressure coefficient to represent both dynamic and static loading with clearer physical meaning as portrayed by the following relationship:

$$\alpha = \frac{\kappa' \beta^2}{2} \frac{1}{F_r^2} + \alpha' \tag{3}$$

where F_r is the Froude number (v/\sqrt{gh}). The F_r is characterised by the ratio of inertial to gravitational forces of flow-type landslides in an open channel flow (Hübl et al., 2009; Choi et al., 2015a).

2.2. Discrete loading

Discrete loading is generated from large particles entrained in debris flows. These particles exert a concentrated impulse that can destroy structures in the flow path. To capture discrete loads exerted by these large particles, the Hertz equation is often used in design guidelines (Lo, 2000; NILIM, 2007; Swiss Federal Road Authority, 2008). The impact force calculated based on the Hertz contact theory (Johnson, 1985) assumes an elastic impact scenario which is given as follows:

$$F = \frac{4E}{3} R^{\frac{1}{2}} x^{\frac{3}{5}} \tag{4}$$

where E is the effective modulus of elasticity, which is given as $1/E = (1 - \nu_1^2)/E_1 + (1 - \nu_2^2)/E_2$ (subscripts 1 and 2 denote parameters relating to the barrier and boulder, respectively) and ν is the Poisson's ratio. R is the equivalent radius, which is given as $1/R = 1/R_1 + 1/R_2$, (R_1, R_2 are the radius of curvature of contacting bodies) and x is the deformation, which is given as follows:

$$x = \frac{15mv^2}{16ER^{\frac{1}{2}}} \tag{5}$$

where, m is the mass of boulder and v is the impact velocity.

Kwan (2012) introduced a modified version of Eqn. 4 for design to estimate the impact force between a granite boulder and a reinforced concrete rigid barrier. The equation is given as follows:

$$F = K_c 4000 v^{1.2} R^2 \tag{6}$$

where, K_c is a load-reduction factor, v is the velocity of the boulder and R is the radius of the boulder.

A fully elastic solution is generally believed to be over conservative (Hungr et al., 1984; Lo, 2000; Sun et al., 2005). Therefore, a load-reduction factor K_c was introduced. This factor is empirical and recommended values vary in the literature (Table 2). Equation 6 is for a single boulder and an equation that can capture the mechanics of a cluster of boulders impacting a surface simultaneously remains a crucial scientific challenge that needs to be addressed.

Table 2. Summary of Hertz equations for estimating boulder impact load on rigid barrier

Load reduction factor K_c	Reference
$K_c = 0.1$	Lo (2000)
$K_c < 0.1$	NILIM (2007)
$0.2 < K_c < 0.5$	SWCB (2005)

3. Impact Mechanisms

Equation 2 is convenient for engineering design, but fails to explicitly capture the key mechanisms of impact observed in physical experiments. These key mechanisms include the accumulation of static deposits called ‘dead zones’ (Chanut et al., 2010; Faug et al., 2009, 2011, 2012 and 2015; Choi et al., 2017), the pile-up of highly frictional flows (Koo et al., 2016) or the vertical-jet-like behavior of viscous flows (Choi et al., 2015a). Physical experiments have demonstrated that the impact mechanism strongly influences the impact load, and consequently the load distribution along a structure (Song et al., 2017a). As such, more details pertaining to impact mechanisms in two most extreme types of geophysical flows: dry granular flow and water flow are discussed below.

3.1. Pileup and vertical-jet mechanisms

To illustrate how the impact mechanism is governed by flow composition, let us consider two of the most extreme types of geophysical flows, specifically dry granular flow and water, impacting a rigid barrier. A dry granular flow is highly frictional with air as the interstitial fluid, which has a low viscosity and plays a relatively insignificant role in regulating the flow dynamics. Instead, frictional and inertial grain stresses dominate. Choi et al., (2015a) demonstrated that when a dry granular flow composed of Leighton Buzzard (LB) fraction C sand with uniform grain diameters of about 0.6 mm, impacts a rigid barrier, a pileup mechanism develops (Fig. 1a).




Fig. 1 (a) Observed pileup impact mechanism for supercritical dry sand impacting an orthogonal barrier (b) Observed vertical-jet mechanism for supercritical water flow impacting a vertical barrier installed along a channel inclined at 5° (redrawn from Choi et al., 2015a)

This mechanism exhibits a rapid attenuation of flow kinetic energy from the high degree of enduring frictional contacts between grains and their boundaries. Furthermore, a granular material with angular grains, such as sand, exhibits a high degree of bulk compressibility, assuming fragmentation does not occur. This feature is controlled by the changes in void ratio from elastic shear distortions of angular grain contacts (Iverson, 2015). High compressibility leads to bulk deformation during impact through shearing between grains, which is a very effective dissipater of flow kinetic energy compared to viscous shearing contributed by the interstitial fluid (Choi et al., 2015b). The properties of dry sand therefore inherently limit accretion along the free surface upon impacting a barrier. Instead, bulk deformation, for F_r within the transitional range (Faug, 2015), leads to the development of a granular bore that propagates or piles-up along the upstream direction in the channel.

Compared to dry granular flow, water exhibits a vertical-jet mechanism upon impact if the initial F_r conditions are supercritical (Armanini, 1997; Choi et al., 2015a). This impact mechanism is characterized by the redirection of flow vertically along the barrier (Fig. 1b). A vertical-jet mechanism develops because the inertia of the flow is significantly

larger than the restoring gravitational field, which is responsible for ‘pulling’ the flow towards the channel. The obvious transfer of flow momentum in the vertical direction for water, compared to dry sand, is because less flow kinetic energy is lost during the impact process. The energy loss is only limited to viscous shearing of the fluid and shearing along its boundaries (Choi et al., 2015b). The effects of viscous shearing in the dissipation of flow kinetic energy is less significant compared to enduring frictional-grain stresses in dry sand. Furthermore, water, has a relatively low bulk compressibility compared to that of dry sand. This lower bulk compressibility promotes run-up upon impact in the only unconfined boundary within a channel, and that is the free surface. By contrast, dry granular flow can compress along the slope-parallel direction during impact and can also pileup towards the free surface of the channel.

Aside from the flow composition, the dynamics of channelized flow, specifically the F_r before impact also strongly influences the resulting impact mechanism (c.f., equation 3). Physical model tests have already demonstrated that water in supercritical flows exhibit a vertical-jet mechanism. By contrast, water in subcritical flow exhibits a reflective-wave mechanism upon impacting a rigid barrier. This mechanism can be characterized by limited transfer of momentum along the vertical direction or free-surface of the channel, the flow impacts the barriers and is allowed to reflect back upstream. Any disturbance to the flow in the channel, such as the barrier, will transfer energy as a wave. The flow inertia for subcritical flows is less than the restoring gravitational field. Therefore, a reflective-wave mechanism is exhibited for subcritical flows. For granular flows, the F_r of the flow before impact strongly influences whether gravitational or inertial effects are dominant (Faug, 2015; Sovilla et al., 2016).

4. Flow composition effects on dynamic response

4.1. Solid-fluid interaction

The complex flow dynamics of debris flows are governed by the interaction between the solid and the fluid phases. Solid-fluid interactions control the changes in the pore fluid pressure, which in turn regulates the Coulomb friction within and at the boundaries of a landslide (McArdell et al., 2007; Iverson and George, 2014; George and Iverson, 2014). The degree of interaction between the solid and fluid phases in the flow can be represented by the solid fraction, or the proportion of solids to fluids by volume (Cui et al., 2015). Flows with a higher solid fraction more readily dissipate flow energy by shearing between grains (Choi et al., 2015b).

Although a great foundation has been established for the structural response of different types of barriers (DeNatale et al., 1999; Wendeler et al., 2006; 2007; Kwan et al., 2014), there remains a knowledge gap on how different flow types can result in very different impact loads. To remedy this gap in the literature, Ng et al., (2016a; 2016b) and Song et al., (2017a; 2017b) carried out a set of centrifuge tests to model the impact mechanisms of debris flows, dry sand and viscous flows, with varying flow composition, on rigid and flexible barriers. Depending on the flow composition, the impact behavior differed drastically. For dry granular flows, the dissipation of the flow kinetic energy was significantly enhanced via stress-dependent friction, unlike viscous flows, which dissipated the flow kinetic energy less readily.

As discussed, a dead zone is useful for attenuating the impact load on an obstacle or barrier, but it can also contribute to the overall load acting on a structure. Song et al., (2017b) carried out a series of centrifuge experiments modelling the impact of two-phase flows on a rigid barrier. In these experiments, the solid fraction was progressively increased from 0 to 0.5. As expected, as the solid fraction increased, particle image velocimetry analysis (White et al., 2003) showed large dead zones. The larger the dead zone observed, the higher the resulting peak impact load measured on the barrier. These findings confirmed that the impact process for two-phase flows is as much a dynamic process as it is a static process. The higher the solid-fraction in the flow, the more pronounced the dead zones. These deposits in turn augment the overall load acting on the orthogonally-configured barrier (Fig. 2a).

4.2. Influence of particle size

Another important feature that adds to the complexity of investigating the impact mechanisms of debris flows is the effects of particle size. Song (2016), Song et al., (2017b), and Song et al., (2018) demonstrated that as the particle size increases, more discrete loads with higher magnitudes are generated. The impact dynamics resulting from large glass spheres differ significantly from dry sand or a two-phase mixture, with the same equivalent volume and F_r conditions before impact. Dry sand exhibits a progressive loading pattern to its static state without an obvious dynamic peak or sharp impulses. The two-phase mixture, however, exhibits a continuous loading behavior, which reaches its

peak load before softening towards a static state. The two-phase mixture is fluidized and takes a longer time to reach a static state because of a lack of shear resistance in the flow. Clearly, a comparison of the different flow types highlight the distinct loading pattern exerted by a cluster of large particles compared to dry sand and two-phase flows.




Fig. 2 (a) Influence of solid fraction on dynamic response of rigid barrier (redrawn from Song et al., 2017b) (b) Effects of particle size on dynamic response of rigid barrier (redrawn from Song et al., 2018)

A comparison of the loading time-histories with existing impact models show that both the dry sand and two-phase mixture are bounded by the superposition of both equations 2 and 3. However, the cluster of glass sphere, resembling a bouldery flow, generates sharp impulses that exceed the superposition of equations 2 and 3. These results indicate that the entrainment of large and hard inclusions in debris flows warrants consideration in the design of structural countermeasures, to safeguard against local damage.

To further investigate the effects of particle size, the performance of the hydrodynamic approach, based on different normalized particle sizes was investigated (Song, 2016). The peak loads were compared (Fig. 2b), and results showed that continuum-based mechanics (equation 3) fail to capture sharp impulse loads at a normalized particle size of 22 mm, based on the recommended dynamic coefficient of 2.5 (Kwan, 2012). Although a solution for capturing the impulse loads for a cluster of large particles was not provided, test results help to evaluate the current impact models for discerning the effects of particle size. A crucial challenge remains to account for impulse loads from a cluster of large particles and to distinguish what particle size is generating impulses that cannot be captured using continuum mechanics (equation 3).

Sharp impulses can be attenuated by increasing the contact time between a particle and a surface. Depending on overall stiffness of a structure, the effects of particle size can diminish. For instance, flexible barriers were originally adopted for capturing rock fall and have been adopted for resisting debris flows in the past decade (Kwan et al., 2014). Another approach for attenuating sharp impulses is to install cushioning materials in front of rigid barriers to diminish these loads (Ng et al., 2017).

5. Summary

Examination of the current state of research on the impact mechanisms of debris flows is presented in this paper. This study highlights the importance of considering the composition of a debris flow to assess the resulting dynamic response and impact mechanisms induced on a rigid barrier. Some key aspects from this review paper is summarized as follows:

- 1) The effects of the particle size are manifested in the inertial grain stresses of the flow during impact. As the particle size increases, the debris-flow transitions from contact-dominated (continuum) to inertial-dominated (discrete) grain stresses. The larger the particle size, the higher the magnitude and number of sharp impulses that are induced on a barrier.
- 2) The effects of solid-fluid interaction, specifically the ratio of solids to fluids dictates the force exerted on a barrier.

The higher the solid fraction, the more predominant grain-contact stresses are, thereby inducing higher static loads on the barrier during impact.

- 3) The flow type governs the mechanism of impact on rigid barriers. Granular flow, which consist of angular grains, readily dissipate flow kinetic energy through enduring shear contacts between grains and deformation from its high bulk compressibility. By contrast, inviscid flow does not readily dissipate flow kinetic energy from internal viscous shearing and viscous shearing along its boundaries. The ratio of inertial to gravitational forces before impact dictate the impact mechanism. These mechanisms are critical for discerning the design load and distribution on barriers.

Acknowledgements

Members of the Association of Geohazard Professionals provided valuable input to this paper during and after the June 2018 workshop organized by the Debris Flow and Steep Creek Hazards Mitigation Committee. The authors are grateful for the financial sponsorship from the National Natural Science Foundation of China (51709052), the theme-based research grant T22-603/15-N and the General Research Fund 16209717 provided by the Research Grants Council of the Government of Hong Kong Special Administrative Region, China, by the H2020 project NAIAD [grant no. 730497] from the European Union's Horizon 2020 research and innovation program. The authors would like to gratefully acknowledge the support of the HKUST Jockey Club Institute for Advanced Study and the Hong Kong Club Charities Trust and the Hong Kong Jockey Club Disaster Preparedness and Response Institute (HKJCDPRI18EG01). The first author gratefully acknowledges generous support from Hong Kong PhD Fellowship for his PhD study. Support from Tetra Tech Canada Inc. for preparation of this manuscript is gratefully acknowledged.

References

- Ancey, C., and Bain, V., 2015, Dynamics of glide avalanches and snow gliding: *Reviews of Geophysics*, v. 53, no. 3, p. 745-784.
- Armanini, A., 1997, On the dynamic impact of debris flows. In *recent developments on debris flows*: Springer Berlin Heidelberg, p. 208–226.
- Ashwood, W., and Hungr, O., 2016, Estimating total resisting force in flexible barrier impacted by a granular avalanche using physical and numerical modelling: *Canadian Geotechnical Journal*, v. 53, no. 10, p. 1700–1717.
- Bowman, E.T., Laue, J., Imre, B., and Springman, S.M., 2010, Experimental modelling of debris flow behaviour using a geotechnical centrifuge: *Canadian Geotechnical Journal*, v. 47, no. 7, p. 742–762.
- Bugnon, L., McArdell, B.W., Bartelt, P., and Wendeler, C., 2012, Measurements of hillslope debris flow impact pressure on obstacles: *Landslides*, v. 9, no. 2, p. 179–187.
- Canelli, L., Ferrero, A.M., Migliazza, M., and Segalini, A., 2012, Debris flow risk mitigation by the means of rigid and flexible barriers—experimental tests and impact analysis: *Natural Hazards Earth System Sciences*, v. 12, no. 5, p. 1693–1699.
- Chanut, B., Faug, T., and Naaim, M., 2010, Time-varying force from dense granular avalanches on a wall: *Physical Review E*, v. 82, no. 4, 041302.
- Choi, C. E., Cui, Y., Liu, L. H. D., Ng, C. W. W., and Lourenço, S. D. N., 2017, Impact mechanisms of granular flow against curved barriers: *Géotechnique Letters*, v. 7, n. 4, p. 330-338.
- Choi, C.E., Au-Yeung, S.C.H. and Ng, C.W.W., 2015a, Flume investigation of landslide granular debris and water run-up mechanisms: *Géotechnique Letters*, v. 5, n. 1, p. 28–32.
- Choi, C.E., Ng, C.W.W., Au-Yeung, S.C.H. and Goodwin, G., 2015b, Froude scaling of landslide debris in flume modelling: *Landslides*, v. 12, no. 6, p. 1197–1206.
- Cui, P., Zeng, C. and Lei, Y., 2015, Experimental analysis on the impact forces of viscous debris flow: *Earth Surface Processes Landform*, v. 40, no. 12, p. 1644–1655.
- DeNatale, J.S., Iverson, R.M., Major, J.J., LaHusen, R.G., Fiegel, G.L. and Duffy, J.D., 1999, Experimental testing of flexible barriers for containment of debris flows: US Department of the Interior, US Geological Survey, p. 45.
- Faug, T., 2015, Macroscopic force experienced by extended objects in granular flows over a very broad Froude-number range: *European Physical Journal E*, v. 38, no. 24, p. 1–10.
- Faug, T., Beguin, R. and Chanut, B., 2009, Mean steady granular force on a wall overflowed by free-surface gravity-driven dense flows. *Physical Review E*, v. 80, no. 2, p. 021305.
- Faug, T., Caccamo, P. and Chanut B., 2011, Equation for the force experienced by a wall overflowed by a granular avalanche: experimental verification: *Physical Review E*, v. 84, no. 5, p. 051301.
- Faug, T., Caccamo, P. and Chanut, B., 2012, A scaling law for impact force of a granular avalanche flowing past a wall. *Geophysics Research Letters*, v. 39, no. 23, L23401.
- George D.L. and Iverson R.M., 2014, A depth-averaged debris-flow model that include the effects of evolving dilatancy. II. Numerical predictions and experimental tests: *Proceedings of Royal Society A: Mathematical, Physical and Engineering Sciences*, v. 470, no. 2170.
- Hübl, J. & Holzinger, G., 2003, Entwicklung von Grundlagen zur Dimensionierung kronenoffener Bauwerke für die Geschiebemanagement in Wildbächen: Klassifikation von Wildbachsperren: WLS Report 50. Im Auftrag des BMLFUW VC 7a (unveröffentlicht). Wien: Institut für Alpine Naturgefahren, Universität für Bodenkultur.
- Hübl, J., Suda, J., Proske, D., Kaitna, R. and Scheidl, C., 2009, Debris flow impact estimation. In *Proceedings of the 11th international symposium on water management and hydraulic engineering*, Ohrid, Macedonia (eds. C. Popovska and M. Jovanovski), Skopje, Macedonia: University of Ss. Cyril and Methodius, p. 1–5.

- Hungr, O., Leroueil, S., Picarelli, L., 2014, The Varnes Classification of Landslide Types, an Update: *Landslides*, v. 11, no. 2, p. 167-194.
- Hungr, O., Morgan, G.C. and Kellerhals, R., 1984, Quantitative analysis of debris torrent hazards for design of remedial measures: *Canadian Geotechnical Journal*, v. 21, no. 4, p. 663-677.
- Iverson, R.M., 2015, Scaling and design of landslide and debris-flow experiments: *Geomorphology*, v. 244, p. 9-20.
- Iverson, R.M., 1997, The physics of debris flows: *Reviews of Geophysics*, v. 35, no. 3, p. 245-296.
- Iverson, R. M., and George, D. L., 2014, A depth-averaged debris-flow model that includes the effects of evolving dilatancy. I. Physical basis: *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, v. 470, no. 2170, 20130819.
- Johnson, K.L., 1985, *Contact mechanics*: Cambridge University Press, London, UK.
- Koo, R.C.H., Kwan, J.S.H., Ng, C.W.W., Lam, C., Choi, C.E. and Song D., 2016, Velocity attenuation of debris flows and a new momentum-based load model for rigid barriers: *Landslides*, v. 14, no. 2, p. 617-629.
- Kwan, J.H.S., Chan, S.L., Cheuk, J.Y.C. and Koo, R.C.H., 2014, A case study on an open hillside landslide impacting on a flexible rockfall barrier at Jordan Valley, Hong Kong: *Landslides*, v. 11, no. 6, p. 1037-1050.
- Kwan, J.S.H., 2012, Supplementary technical guidance on design of rigid debris-resisting barriers, Report No. 270. Kowloon, Hong Kong: Geotechnical Engineering Office.
- Lo, D.O.K., 2000, Review of natural terrain landslide debris resisting barrier design, Report No. 104. Kowloon, Hong Kong: Geotechnical Engineering Office.
- McArdell, B.W., Bartelt, P. and Kowalski, J., 2007, Field observations of basal forces and fluid pore pressure in a debris flow: *Geophysics Research Letters*, v. 34, no. L07406, p. 1-4.
- Ministry of Land and Resources, 2004, Design standards for debris flow hazard mitigation measures (DZ/T0239-2004). Beijing, China: Chinese Geological Survey, Ministry of Land and Resources (in Chinese).
- Ng, C.W.W., Choi, C.E., Su, A.Y., Kwan, J.S.H. and Lam, C., 2016a, Large-scale successive impacts on a rigid barrier shielded by gabions: *Canadian Geotechnical Journal*, v. 53, no.10, p. 1688-1699.
- Ng, C.W.W., Song, D., Choi, C.E., Kwan, J.S.H., Shiu, H.Y.K. and Koo, R.C.H., 2016b, Centrifuge modelling of dry granular and viscous impact on rigid and flexible barriers: *Canadian Geotechnical Journal*, v. 54, no. 2, p. 188-206.
- Ng, C.W.W., Song, D., Choi, C.E., Koo, C.H., and Kwan, J.S.H., 2016c, A flexible barrier for landslide impact in centrifuge: *Géotechnique Letters* v. 6, no. 3, p. 221-225.
- National Institute for Land and Infrastructure Management, 2007, Manual of technical standards for designing Sabo facilities against debris flow and Driftwood, Technical Note of NILIM No. 365. Tsukuba, Japan: National Institute for Land and Infrastructure Management, Ministry of Land, Infrastructure and Transport (in Japanese).
- Scheidt, C., Chiari, M., Kaitna, R., Müllegger, M., Krawtschuk, A., Zimmermann, T. and Proske, D., 2013, Analyzing debris-flow impact models, based on a small-scale modelling approach: *Surveys in Geophysics*, v. 34, no. 1, p. 121-140.
- Scotton, P. and Deganutti, A.M., 1997, Phreatic line and dynamic impact in laboratory debris flow experiments: *Proceedings of the 1st International Conference on Debris Flow Hazards Mitigation: Mechanics, Prediction and Assessment*, San Francisco, USA.
- Soil and Water Conservation Bureau, 2005, *Soil and water conservation handbook*. Nantou, Taiwan: Soil and Water Conservation Bureau of the Council of Agriculture, Executive Yuan and Chinese Soil and Water Conservation Society (in Chinese).
- Song, D., 2016, Mechanisms of debris flow impact on rigid and flexible barriers [PhD Thesis]: HKUST, HKSAR.
- Song, D., Choi, C. E., Zhou, G. G. D., Kwan, J. S. H., and Sze, H. Y., 2018, Impulse Load Characteristics of Boulderly Debris Flow Impact: *Géotechnique Letters*, v. 8, no. 2, p. 111-117.
- Song, D., Choi, C.E., Ng, C.W.W. and Zhou, G.G.D., 2017a, Geophysical flows impacting a flexible barrier: effects of solid-fluid Interaction: *Landslides*, v. 15, no. 1, p. 99-110, <https://doi.org/10.1007/s10346-017-0856-1>
- Song, D., Ng, C.W.W., Choi, C.E., Kwan, J.S.H. and Koo, R.C.H., 2017b, Influence of debris flow solid fraction on rigid barrier impact: *Canadian Geotechnical Journal*, v. 54, no.10, p. 1421-1434.
- Sovilla, B., Faug, T., Kohler, A., Baroudi, D., Fischer, J., and Thibert, E., 2016, Gravitational wet avalanche pressure on pylon-like structures: *Cold Regions Science and Technology*, v. 126, p. 66-75.
- Sun, H.W., Lam, T.T.M. and Tsui, H.M., 2005, Design basis for standardized modules of landslide debris-resisting barriers. GEO Report No. 174. Geotechnical Engineering Office, HKSAR.
- Swiss Federal Road Authority, 2008, *Effects of rockfall protection galleries*. Federal Roads Office. Switzerland.
- Takahashi, T., 2014, *Debris Flow: Mechanics, Prediction and Countermeasures* (2nd edition). London, UK, Taylor & Francis Group.
- Thurber Consultants Ltd., 1984, *Debris torrents: a review of mitigation measures: report to ministry of transportation & highways*, British Columbia, Canada.
- VanDine, D.F., 1996, *Debris flow control structures for forest engineering*. (Ministry of Forests Research Program, Working Paper 22/1996). Vancouver, Canada: Government of the Province of British Columbia.
- Vagnon, F. and Segalini, A., 2016, Debris flow impact estimation on a rigid barrier: *Natural Hazards Earth System Sciences*, v. 16, no. 7, p. 1691-1697.
- Volkwein, A., 2014, *Flexible Debris Flow Barriers: Design and Application*, Swiss Federal Institute for Forest, Snow and Landscape Research, WSL Berichte 18, p. 32.
- Wendeler C., 2008, *Murgangrückhalt in Wildbächen - Grundlagen zu Planung und Berechnung von flexiblen Barrieren*, [Dissertation]. ETH Nr. 17916, Schweiz.
- Wendeler, C., McArdell, B.W., Rickenmann, D., Volkwein, A., Roth, A. and Denk, M., 2006a, Field testing and numerical modeling of flexible debris flow barriers. In *Proceedings of the sixth international conference of physical modelling in geotechnics* (eds. C.W.W. Ng, Y.H. Wang and L.M. Zhang), Boca Raton, FL, USA: CRC Press, p. 4-6.
- Wendeler, C., Volkwein, A., Denk, M., Roth, A. and Wartmann, S., 2007, Field measurements used for numerical modelling of flexible debris flow barriers. In *Proceedings of fourth international conference on debris flow hazards mitigation: mechanics, prediction, and assessment* (eds. C. L. Chen and J. J. Major), Rotterdam, the Netherlands: Millpress, p. 681-687.
- White, D.J., Take, W.A. & Bolton, M.D., 2003, Soil deformation measurement using particle image velocimetry (PIV) and photogrammetry: *Géotechnique*, v. 53, no.7, p. 619-63.
- Zhang, S., 1993, A comprehensive approach to the observation and prevention of debris flows in China: *Natural Hazards*, v. 7, no. 1, p. 1-23.
- Zhou, G.G.D. & Ng, C.W.W., 2010, Dimensional analysis of natural debris flow. *Canadian Geotechnical Journal*, v. 47, no. 7, p. 719-729.