

# Predictive Study of Velocimetry in the Coronary Artery after Iodinated Contrast Agent Injection

Nora Hocine, Julie Colnot, Hélène Masset, Didier Franck

# ▶ To cite this version:

Nora Hocine, Julie Colnot, Hélène Masset, Didier Franck. Predictive Study of Velocimetry in the Coronary Artery after Iodinated Contrast Agent Injection. International Journal of Medical Physics, Clinical Engineering and Radiation Oncology, 2017, 06 (01), pp.93-104. 10.4236/ijmpcero.2017.61009. hal-02948854

# HAL Id: hal-02948854 https://hal.science/hal-02948854

Submitted on 25 Sep 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

# Predictive study of velocimetry in the coronary artery after iodinated contrast agent injection

Nora Hocine<sup>1\*</sup>, Julie Colnot<sup>2</sup>; Hélène Masset<sup>2</sup> and Didier Franck<sup>1</sup>

<sup>1</sup>Institut de Radioprotection et de Sûreté Nucléaire (IRSN), BP 17, Fontenay-aux-Roses - FRANCE

<sup>2</sup>Henri Mondor University Hospitals, Créteil, FRANCE

\*Corresponding author: nora.hocine@irsn.fr

This study aims to determine the retention time of iodinated contrast agents (ICA) in the coronary artery. The mechanical aspect of ICA displacement was studied in order to better understand the effect of these products on the inner wall of the artery of patients with coronary artery stenosis, undergoing repeated imaging examinations with iodinated contrast agents. ICA flow and ICA and blood flow in the artery were modelled. The fluid was regarded to be viscous, incompressible and Newtonian. Blood flow was presumed to be unidirectional, laminar and unstationary. Iodine flow rate and retention time were calculated using the Runge-Kutta 4th order method programmed in C++ and MatLab R2013a language. The results showed that for coronary artery CT-scans, ICA retention time is 1 minute 40 seconds and for coronary arteriography it is between 2.4 and 3.6 seconds. The values calculated were compared to theoretical values and to clinical observations. The results enabled us to validate our model.

#### INTRODUCTION

Monitoring of patients with coronary artery stenosis or having had angioplasty, involves repeated imaging examinations with iodinated contrast agent (ICA) injection. These agents are used to enhance image contrast and to see the diseased arteries, those containing iodine, a heavy chemical element (Z=53) more clearly [1]. This element confers contrast agents their opacifying properties, justifying their use in medical imaging [2].

The impact of the use of iodinated contrast agents on the coronary artery is not well understood to date. The increase in the dose in the coronary artery with ICA has been demonstrated [3]. Work by Hocine *et al*, (in press) [4] showed a correlation between the increase in the amount of energy deposited in the coronary artery lumen and the increase in iodine concentration in the contrast agent.

In order to better understand the potential effect of iodine on the inner wall of the coronary artery, it seemed necessary to study the mechanical aspect of ICA displacement in the artery, their diffusion once injected into the patient and retention time in the coronary artery of ICA. This study will be used to determine artery inner wall exposure time to ICA. Iodine flow rate and retention time were calculated using the Runge-Kutta 4th order method programmed in C++ and MatLab R2013a language, and the results from our model are discussed below.

#### EQUIPMENT AND METHODS

To calculate flow, it was necessary to model the blood, a complex fluid made up of particles, but also of cells in suspension (red blood cells, white blood cells and platelet) and, the coronary artery with dimensions

defined by its length (L) and its inner diameter (d<sub>i</sub>):  $L^*d=170^*3 \text{ mm}^2$ . Blood was regarded as a Newtonian fluid, meaning it has constant viscosity and induces shear stress. The mean viscosity of blood is considered to be 3 milliPascals (mPa.s) or 3 centipoise (cP) and blood density 1070 kg/m3 [5]. Each iodinated contrast agent has an iodine concentration and viscosity [6]. The concentration maximum is 400 mg of iodine per mL and viscosity is between 6 and 12 cP [6]. The geometry of healthy coronary arteries and the

The geometry of healthy coronary arteries and the characteristics of the fluid flowing through them lead us to believe there is a laminar flow pattern with a low Reynolds number.

In an initial approach, flow is modelled in the artery as laminar flow of an incompressible viscous fluid in a duct with rigid wall, with no forks or curves and of constant radius. It is a straightforward model of blood flow in an artery (without artery lumen narrowing).

For the pulsatile flow pattern [7] caused by contractions of the heart, the pressure between the two ends of the artery was modelled by a periodic function. Heart contractions impose a pulsatile pressure gradient in the artery with maximum pressure during the diastole (heart relaxation phase), and minimum pressure during systole (heart contraction phase). A systole and a diastole make up the cardiac cycle and therefore the periodic flow phase.

The pulsatile movements of the blood in the artery caused by heart muscle contraction and relaxation leading to ejection of the blood in the arteries were modelled. Blood flow is considered to be unidirectional, laminar, unstationary and the fluid is considered to be viscous, incompressible and Newtonian. Pressure rate and gradient vary over time whereas the shape of the conduct (Figure 1) remains unchanged over time.

R is the radius of the conduct, L being its length. We presumed that R is constant over the conduct's length.  $P_0$  represents pressure at one end of the artery, and  $P_L$  that at the other end. The two vectors

<sup>\*</sup>Corresponding author: nora.hocine@irsn.fr

(1)

are orthonormal with a cylindrical base on which the equations are projected. Blood flow is modelled by the following parameters and equations:

$$\vec{v} = v(r,t)\vec{u}_{x}$$

$$P(x,t) = P_{0}(t) + \left[\frac{P_{L}(t) - P_{0}(t)}{L}\right] x \quad (2)$$

$$\vec{v}(r = R) = \vec{0} \quad (3)$$

$$P_L(t) = 0$$
  $\omega = \frac{2\pi}{T}$ 

heart rate and T the cardiac phase. The pressure gradient is expressed as follows:

$$\frac{P_L - P_0}{L} = \alpha + \operatorname{Re}(A\exp(i\omega t))$$
<sup>(7)</sup>

Where Re is the real part.



Figure 1: Rigid conduct modelling the artery

The rate r of a fluid particle is parallel to the axis of the conduct and only depends on its distance from the centre of the conduct and on time (equation 1). Pressure varies linearly according to the position in the artery (equation 2). Finally, the properties of the viscous fluids set the condition at the following limits: the viscous fluid has zero rate in the artery's fixed walls (equation 3). Blood flow is governed by the following equations: Navier Stokes equation (equation 4) in parallel flow and the incompressibility equation (equation 5).

$$\rho \frac{\partial \vec{v}}{\partial t} = -gra\vec{d}P + \eta \Delta \vec{v} \quad {}_{(4)}$$

$$div \ \vec{v} = 0 \tag{5}$$

where  $\rho$  is the density of the fluid expressed in Kg/m<sup>3</sup>,  $\eta$  is its dynamic viscosity expressed in centipoise (cP) or in Pascal.second (Pas.s).

The fluid is considered to be incompressible and described by equation 5.

Equation 6 below gives the expressions for the pressures modelled at the ends of the artery:

$$P_0 = \beta + \gamma \sin(\omega t) \quad ^{(6)}$$

The model is linear, and the rate therefore takes the following form:

$$v(r,t) = a(r) + \operatorname{Re}(u(r).\exp(i\omega t))^{(8)}$$

Where a and u are independent of time, they vary according to radius, u is a complex function.

The Runge-Kutta 4th order method programmed in C++ language in Linux Debian with the compiler's eMacs produced the values for a (r)

and u(r) for various values of the radius of the conduct, ranging from 0 to R, the artery radius.

The Matlab R2013a software was used to calculate the rate r (r, t) in the artery section according to time.

The Gnuplot graphing software was used to represent the stationary solution in 3D.

The values for a (r) and u (r) were entered into Matlab R2013a again to product r (r, t) for the rate in the artery section according to different times.

To calculate iodine retention time in the artery, it was necessary to determine the final iodinated blood volume after its dilution.

Iodinated agents are highly viscous products. Viscosity may vary between 6 and 12 cP [6] and according to the molecule properties and their concentration.

When the blood is mixed with iodine, its viscosity increases and may reach 9 cP. However if the iodinated medium is very highly diluted, viscosity remains similar to the viscosity of the blood. Iodinated blood viscosity and final volume depend on the dilution ratio.

We considered that the viscosity of the blood and contrast agent mixture could be determined by the following relation:

 $V = V_1 + V_2$ 

 $\eta$  is the viscosity of the mixture

 $\eta_1$  and  $\eta_2$  is the viscosity of the blood and iodine: nV - nV

$$\eta = \frac{\eta_1 V_1 - \eta_2 V_2}{V} \quad : \quad (9)$$

V is the mixture volume

Where:

## RESULTS AND DISCUSSION

#### Rate profiles and calculations

Modelling and programming in C++ language produced 2D and 3D blood flow rate profiles for a heart rate of 80 beats per minute.

Figure 2 shows the resulting 3D profiles for the blood flow stationary rate solution a(r). In Figure 5 we can see the rate profiles for the unstationary part resulting on a cardiac cycle. Figure 6 shows the rate profiles resulting for the full rate solution and for the pure blood.

Temporal and spatial means were calculated in order to determine the mean rate of a fluid particle crossing the coronary artery. Figure 3 shows the mean rate of a fluid particle over a cardiac cycle. In Figure 3 we note that the blood flow rate varies between 1.32 m/s and 0.058 m/s. Mean blood flow rate with this model is 0.68 m/s. This value is in keeping with that of the reference mean coronary flow rate of 250 ml/min [8], equivalent to a mean blood flow rate of 0.59 m/s. Therefore the relative deviation with the reference value is 15%.

This blood flow model for coronary artery flows therefore appears to be satisfactory.

The Reynolds number for the blood flow is:

$$R = \frac{\rho v L}{\eta} = 727.6$$



Figure 2: Blood stationary flow rate profiles in 3D



Figure 3: Change in mean rate according to time over a given period



Figure 4: Graph showing the mean rate of the viscous fluid over a given period



Fig. 5: Rate profiles resulting with Matlab resolution for the sinusoidal (pure blood) solution

N.HOCINE



Fig. 6: Rate profiles resulting for the full rate solution for the pure blood (6 profiles in one cycle)

This value is below 2000. It characterises the transition between the laminar and turbulent flow [9] in a rigid, cylindrical conduct. This result confirms that flow can be modelled by

This result confirms that flow can be modelled by laminar approximation and does not create turbulence in the artery.

The Womersley number for the resulting blood flow is:



This number is used to determine the type of forces dominating flow, whether they are inertial or viscous.

A Womersley number of less than 1 is characteristic of flow with which inertial forces are insignificant compared to the viscous forces.

The value obtained is greater than 1, indicating inertial flow.

Fig. 7: Flow rate profiles for a blood and iodinated contrast agent mixture

Figure 4 above shows the mean iodinated fluid flow rate over a cardiac phase. This figure shows the presence of reflux which is characterised by a fleeting inversion of the blood flow during the systole. We can see in Figure 4 that the main part of the flow takes place during the diastole. This observation is in keeping with the flow characteristics observed and described in literature on coronary artery blood flow [10]. Figure 7 shows flow profiles calculated by the computer model developed in this study for a bolus or single dose of weakly diluted contrast agent with high viscosity.

Where the contrast agent with high viboosity. Where the contrast agent remains very highly concentrated when flowing through the artery, as during injection for a coronary arteriography, the fluid flowing through the arteries has very high viscosity which is estimated at between 7 and 9 cP. The value of 9 cP is the mean viscosity of contrast agents on the market [2].

Our calculation shows that the mean flow rate of a fluid particle in the artery is 0.29 m/s, with a maximum flow rate of 0.67 m/s and minimum flow rate of 0.08 m/s in the opposite direction.

The Reynolds number for the blood flow is: R = 133.0. The Reynolds number is lower than for pure blood or weakly iodinated blood flow. In the same conditions, viscous flow is therefore slower and has less tendency to present turbulence.

Pulsatile blood flow is characterised by a Womersley number of: W = 3.39. In this case viscous forces play a predominant role in fluid flow.

This study makes us realise that viscosity slows fluid flow in the artery and therefore has an effect on iodinated contrast agent retention time. Therefore, the type of iodinated contrast agent used, route of injection and volume of the product injected can considerably alter the time it takes for the iodinated contrast agent to diffuse in the patient's body, and especially in coronary arteries.

#### **Contrast agent retention time**

## Coronary artery CT-scan

Administration of a volume of 80 cm<sup>3</sup> iodinated contrast agent in radial infusion (artery or arm) with a flow rate of 4 cm<sup>3</sup> per second means images can be acquired in around 10s. Bearing in mind that the contrast agent arrives in the arterial blood highly diluted, the viscosity of the blood and iodine mixture is estimated at around 4 cP, value very similar to that of the blood (around 3cP) and circulating blood volume is around 480 cm<sup>3</sup>. According to our model, the contrast agent remains in the artery for less than 2 minutes. For weakly iodinated blood flow, iodinated contrast agent retention time in the artery is estimated at 1 minute and 40 seconds.

#### Coronary arteriography

Using our model for coronary arteriography during which the contrast agent is injected directly in the artery, shows that for administration of a 5 mL bolus, travel time in the coronary arteries is estimated at between 2.41s and 3.61s. These values were calculated with the hypotheses taken for our model.

Iodinated agent retention time in the artery differs for each patient. The time interval determined allows for a good estimation of contrast agent retention in the coronary arteries. These values were correlated with clinical observations in our radiology department.

## **Model limits**

The results presented above were correlated with theoretical values. Our model has some limits however as discussed below. Certain hypotheses were put forward to simplify the complex parameters and to create the model.

The shear stress applied to our fluid, the blood, has an effect on its viscosity and clustering of cells it contains. Higher stress decreases its viscosity. In our model, the variations in blood viscosity with shear stress were set aside.

The dilution ability of iodinated contrast agents (ICA) with blood is still little known and there is also little information on the effect of ICA on the viscosity of the mixture. A linear relationship between the viscosity of the mixture and its dilution was assumed in order to simplify consideration of viscosity variations during arterial injection of the iodinated contrast agent.

Coronary artery geometry varies among patients and adapts to patient movement and blood flow changes. Artery walls are deformable and made up of various layers of cells which contract and relax in time with heart contractions. We used a straightforward shape for our model.

Vascular tone and the interaction with endothelial cells increase arterial resistance to blood flow and reduce blood flow rate [11]. Blood fluid-artery wall interactions were not discussed.

For modelling pulsatile blood flow in the artery, a heart rate of 80 beats per minute was used as it is the mean heart rate for a healthy adult at rest.

In our model, flow was considered to be parallel. Rate is parallel to the axis of the conduct over its length, when in actual fact, rough patches on the walls, curves and narrowing of the arteries, along with wall movements, cannot ensure this type of flow. Narrowing of the artery lumen can cause significant turbulence which may have an effect on fluid flow in the conduct [12].

Our model does not take changes in diseased coronary arteries into account. They play an important role in blood flow, their roughness and thickening leading to narrowing of the lumen, with a potential effect on blood flow and blood flow rate in the artery.

It would be useful to study the effect of lumen surface condition and diameter on fluid viscosity and on blood flow rate, which may also affect the retention time of the iodinated contrast agents administered.

In this study we created a straightforward model of a complex physiological system with several variable parameters. Fluid/structure interaction and turbulent blood flow caused by uneven walls are difficult to model. These entities are taken as nonlinear terms in the equations on fluid progression. Also, given the anatomical differences between patients, a personalised study would be useful and more realistic, taking the various properties of the blood and deformable walls into account, and it would be a way of observing values closest to actual values.

However, the values used with our model for calculating the retention time of iodinated contrast

agent in the coronary artery for the tests carried out in our hospital are very consistent.

## CONCLUSIONS

Modelling blood flow in coronary arteries was used to estimate iodinated contrast agent retention time in the coronary artery. For coronary artery CTscans, ICA retention time is 1 minute 40 seconds and for coronary arteriography it is between 2.4 and 3.6 seconds.

The resulting values were compared with theoretical values and with those observed during exploratory tests, and the result is fairly satisfactory and enabled us to validate our model.

The results of this study could be used to better understand the impact of the use of ICA and to better anticipate any effects from their use. These agents, which are sometimes poorly tolerated, may affect certain parameters, blood properties and therefore patients whose arteries are already severely damaged from heavy treatments. Also, the high energy deposited by ionising radiation in the arteries into which these agents are injected, could also carry additional risks. These should be taken into account to ensure that patient exposure to radiation is as low as possible.

#### REFERENCES

- 1. Diagnostics of Vascular Diseases: Principles and technology. Edition: Peter Lanzer and Martin Lipton, 1997.
- Solacroup, Boyer, Le Marec, Schouman Claeys, Bases Physiques des rayons X : Produits de contraste en radiologie, CERF 2001.
- http://www.imagemed.org/cerf/cnr/edicerf/BASES/pdc.pdf
- Joubert, A; Biston MC; Boudou, C, Irradiation in presence of iodinated contrast agent results in radiosensitization of endothelial cells: consequences for computed tomography therapy, Int. J. radiatiion oncology biol. Phys., 62: 1486– 1496, 2005.
- 4. Hocine N, Meignan M and Masset H. Monte Carlo simulations used to calculate the energy deposited in the coronary artery lumen as a function of iodine concentration and photon energy (In press).
- Quemada D. Hydrodynamique sanguine : Hémorhéologie et écoulement du sang dans les petits vaisseaux, Journal de Physique, 37 (C1) 9-22, 1976.
- 6. Caractéristiques des produits de contraste, ANSM, Agence Nationale de Sécurité du Médicament, 2013.
- Mestel J, Bio Fluid Mechanics: Pulsatile flow in a long straight artery, Imperial College London, 2009.
- 8. Précis d'anesthésie cardiaque, Edition Chassot P.G, 2011
- 9. Saudrais E. Mécanique des fluides, CPGE PSI, 2012-2013.
- Ku D.N. Blood flow in arteries, The Annual Review of Fluid Mechanics, 29:399-434, 1997.
- Hermann J, Kaski JC, and Lerman A, Coronary microvascular dysfunction in the clinical setting: from mystery to reality, European Heart Journal 33: 2771-2781, 2012.
- Wei L. Numerical study of steady and pulsatile flow through stenosed tubes [Ph.D. thesis] Singapore: Department of Mechanical Engineering, National University of Singapore; 2004.