



HAL
open science

Facility level measurement of off-shore oil & gas installations from a small airborne platform: Method development for quantification and source identification of methane emissions

James France, Prudence Bateson, Pamela Dominutti, Grant Allen, Stephen Andrews, Max Coleman, Tom Lachlan-Cope, Rebecca Fisher, Langwen Huang, Anna E Jones, et al.

► To cite this version:

James France, Prudence Bateson, Pamela Dominutti, Grant Allen, Stephen Andrews, et al.. Facility level measurement of off-shore oil & gas installations from a small airborne platform: Method development for quantification and source identification of methane emissions. Atmospheric Measurement Techniques, In press, 10.5194/amt-2020-165 . hal-02958277

HAL Id: hal-02958277

<https://hal.science/hal-02958277>

Submitted on 5 Oct 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Facility level measurement of off-shore oil & gas installations from a small airborne platform: Method development for quantification and source identification of methane emissions

5 James France^{1,2}, Prudence Bateson³, Pamela Dominutti⁴, Grant Allen³, Stephen Andrews⁴, Stephane Bauguitte⁵, Max Coleman², Tom Lachlan-Cope¹, Rebecca Fisher², Langwen Huang^{3&9}, Anna E Jones¹, James Lee⁶, David Lowry², Joseph Pitt^{3&8}, Ruth Purvis⁶, John Pyle⁷, Jacob Shaw³, Nicola Warwick⁷, Alexandra Weiss¹, Shona Wilde⁴, Jonathan Witherstone¹, Stuart Young⁴.

10 ¹ British Antarctic Survey, Natural Environment Research Council, Cambridge CB3 0ET, UK

² Department of Earth Sciences, Royal Holloway, University of London, Egham TW20 0EX, UK

³ Department of Earth and Environmental Science, University of Manchester, Manchester, M13 9L, UK

⁴ Wolfson Atmospheric Chemistry Laboratories, Department of Chemistry, University of York, Heslington, YO10 5DD, UK

⁵ FAAM Airborne Laboratory, National Centre for Atmospheric Science, Cranfield, Bedfordshire, MK43 0AL, UK

15 ⁶ National Centre for Atmospheric Science, Innovation Way, University of York, York, UK

⁷ National Centre for Atmospheric Science, Department of Chemistry, University of Cambridge, Cambridge, UK

⁸ School of Marine and Atmospheric Sciences, Stony Brook University, Stony Brook, NY 11974, USA

⁹ Departement Mathematik, ETH Zurich, Sälimstrasse 101, 8092 Zürich, Switzerland

Correspondence to: James L France (james.france@rhul.ac.uk)

20 **Abstract.**

Emissions of methane (CH₄) from offshore oil and gas installations are poorly ground-truthed and quantification relies heavily on the use of emission factors and activity data. As part of the United Nations Climate and Clean Air Coalition (UN CCAC) objective to study and reduce short-lived climate pollutants (SLCP) a Twin Otter aircraft was used to survey CH₄ emissions from UK and Dutch offshore oil and gas installations. The aims of the surveys were to i) identify installations that are significant CH₄ emitters, ii) separate installation emissions from other emissions using carbon-isotopic fingerprinting and other chemical proxies, iii) estimate CH₄ emission rates, and iv) improve flux estimation (and sampling) methodologies for rapid quantification of major gas leaks.

In this paper, we detail the instrument and aircraft set up for two campaigns flown in the springs of 2018 and 2019 over the southern North Sea and describe the developments made in both planning and sampling methodology in order to maximise the quality and value of the data collected. We present example data collected from both campaigns to demonstrate the challenges encountered during offshore surveys, focussing on the complex meteorology of the marine boundary layer, and sampling discrete plumes from an airborne platform. The uncertainties of CH₄ flux calculations from measurements under varying boundary layer conditions are considered, as well as recommendations for attribution of sources through either spot sampling for VOCs / $\delta^{13}\text{C}_{\text{CH}_4}$ or using in-situ instrumental data to determine C₂H₆-CH₄ ratios. A series of recommendations for both planning and measurement techniques for future offshore work within the marine boundary layers are provided.



1. Overview

Methane is a potent greenhouse gas in the atmosphere, with a global warming potential 84 times that of carbon dioxide when calculated over a 20-year period (Myhre et al., 2013). Increases in atmospheric CH₄ mixing ratios are expected to have major influences on the Earth's climate, and emission mitigation could go some way toward achieving goals laid out in the UNFCCC Paris Agreement (Nisbet et al., 2019).

Offshore oil and gas fields make up ~28% of the total global oil and gas production worldwide and are expected to be significant sources of CH₄ to the atmosphere, given that 22% of global CH₄ emissions are estimated to be from the oil and gas (O&G) sector (Saunio et al., 2016). Some emissions arise from routine operations or minor engineering failures (Zavala-Araiza et al., 2017), while others stem from large unexpected leaks, (e.g. (Conley et al., 2016; Ryerson et al., 2012)). In some O&G fields, large amounts of non-recoverable CH₄ can be flared or vented due to a number of factors. Thus, the composition of O&G emissions can be influenced by several variables, including the targeted hydrocarbon product (oil or gas), extraction techniques and gas capture infrastructure. O&G installations co-emit volatile organic compounds (VOCs) such as alkanes, alkenes and aromatics in addition to CH₄. Some of these VOCs are toxic and can have direct health impacts or, together with NO_x can produce ozone, having an impact on the regional air quality (Edwards et al., 2013). VOC and δ¹³C_{CH₄} measurements can be utilised to fingerprint the main processes or likely location responsible for associated CH₄ emissions (Cardoso-Saldaña et al., 2019; Lee et al., 2018; Yacovitch et al., 2014a). A recent study has also demonstrated the cost-effectiveness of airborne measurements for leak detection and repair at O&G facilities relative to traditional ground-based methods (Schwietzke et al., 2019).

There is thus a need to develop reliable methodologies to locate emissions, pinpoint sources and design effective mitigation action in sufficient detail to allow quantification of emissions and validate against publicly reported inventory emissions. To date, a number of approaches have been trialled. Airborne measurements of both individual and clusters of facilities, along with production data, have been used to scale up to an inventory of CH₄ emissions for the U.S. Gulf of Mexico (Gorchov Negrón et al., 2020). Ship based measurements of CH₄ and associated source tracers have been made in both the Gulf of Mexico (Yacovitch et al., 2020) and in the North Sea (Riddick et al., 2019). The latter reported fluxes of CH₄ from offshore O&G installations in UK waters that were derived from observations made from small boats at ~2 m above sea level. This approach has advantages in terms of cost, but the authors recognised a number of key uncertainties in their approach associated with assumptions around boundary layer conditions and a lack of 3D information (i.e. Gaussian plume modelling and assumptions of constant wind speed). Measurements from aircraft can provide this 3D spatial information enabling better characterisation of both plume morphology and boundary layer dynamics.

Here we report a project that was designed around the use of a small-aircraft with flexible instrument payload suitable for agile deployment. Key objectives were i) to identify and quantify emissions of CH₄ from a suite of offshore gas fields within a limited geographical area, and ii) to develop methodologies that can be applied to gas fields elsewhere to assess emissions at local scales. The project was part of the United Nations Climate and Clean Air Coalition (UN CCAC) objective to characterize



70 global CH₄ emissions from oil and gas infrastructure. Targeted observations of atmospheric CH₄ and C₂H₆, plus sampling for
VOC and δ¹³C_{CH₄} analysis were made from a Twin Otter aircraft operated by the British Antarctic Survey. Two campaigns
were conducted, one in April 2018 and one in April/May 2019, with a total of 10 flights (~45 hours) over the two campaigns.

The specific aims of the surveys were:

1. CH₄ surveying of facilities with a range of expected (from inventories) CH₄ emissions.
2. Resolution of types of emission from installations (such as flaring, venting, combustion and leaks) using carbon-isotopic
75 fingerprinting and analysis of co-emitted species (including VOCs).
3. Estimation of total CH₄ emissions for the target region.
4. Improvement of flux estimation (and sampling) methodologies for rapid quantification of major gas emissions.

Here, we provide an overview of measurement platform configuration and sampling strategy during these campaigns, including
instrument comparisons for hydrocarbon plume detection, spot sampling strategies for VOCs and δ¹³C_{CH₄}, and flight planning
80 to cope with complex boundary layer meteorology to allow estimation of emission fluxes. Analysis methods to determine
diagnostic hydrocarbon plume characteristics such as C₂H₆-CH₄ ratios and δ¹³C source attribution are also discussed. A sister
publication will present the estimated facility-level emissions in detail and discuss the results in a regional context.

2. Experimental

A DHC6 Twin Otter research aircraft, operated by the British Antarctic Survey, was equipped with instrumentation to measure
85 atmospheric boundary layer parameters, including the boundary layer structure and stability, as well as a number of targeted
chemical parameters. These included CH₄, CO₂, H₂O, C₂H₆ as well as whole air sampling for subsequent analysis of δ¹³C_{CH₄}
and a suite of VOC's. Here we describe the aircraft capability, aircraft fit, and the instruments deployed.

2.1. Aircraft capability

The maximum range of the Twin Otter aircraft during the flight campaigns was approximately 1000 km. Although the aircraft
90 is capable of flying up to 5000 m altitude, most of the flying was limited to below 2000 m; in regions with no minimum altitude
limit, the aircraft could be flown at the practical limit of 15 m (~50 ft) above sea level. The instrument fit included use of a
turbulence boom, which limited the speed to a maximum of 140 kts (~70 ms⁻¹); throughout the campaigns, the target aircraft
speed for surveying was 60 ms⁻¹. The aircraft was limited to a minimum safe separation distance of 200 m from any O&G
production platforms.

95 The total weight of the aircraft on take-off is limited to 14,000 lbs (6,350 kg). Allowing for fuel and crew, this left 2,086 kg
for the instrumentation. The total power available on the aircraft is 150 A at 28 V and inverters were used to provide 220 V to
those instruments that required it.



Altitude and air speed were determined by static and dynamic pressure from the aircraft static ports and heated Pitot tube, logged using Honeywell HPA sensors at 5 Hz. A radar altimeter recorded the flight height at around 10 Hz. An OXTS Inertial measurement system coupled to a Trimble R7 GPS was used to determine the aircraft position and altitude. This system gives all three components of aircraft position, altitude and velocity at a rate of 50 Hz.

The chemistry inlets on the Twin Otter are similar to those fitted to the FAAM BAE 146 large atmospheric research aircraft (e.g. O'Shea et al., (2013)) and were fitted with the inlet facing to the rear (Fig. A1). A single line (1/4" Synflex tubing) was taken from the inlet to a high capacity pump with the instruments branching from this line. This approach was taken to minimise the delay between air entering the inlet and reaching the instruments, which, with this configuration, was ~5 seconds.

The aircraft was fitted out during the week before each of the two flight campaigns allowing significant changes to be made between 2018 and 2019 based on instrument performance and data from 2018 (Fig. 1).

2.2. Boundary layer physics instrumentation

A fast response temperature sensor and a nine hole NOAA BAT 'Best Air Turbulence' probe (Garman et al., 2006) was mounted on a boom on the front of the aircraft (see photo, Fig. A2). This instrumental set-up was chosen to reduce flow distortion effects by the aircraft. These fast response measurements of wind and temperature fluctuations were made with a frequency of 50 Hz. Garman et al. (2006) investigated the uncertainty of the wind measurements by testing a BAT probe in a wind tunnel. They assessed that the precision of the vertical wind measurements due to instrument noise was approximately $\pm 0.03 \text{ ms}^{-1}$. Garman (2008) showed that an additional uncertainty in the wind data occurs when a constant up-wash correction value is used, as proposed by the model of Crawford (1996). We use the Crawford model which increases the uncertainty in the vertical wind component, w , to approximately $\pm 0.05 \text{ ms}^{-1}$. We assume for the two horizontal wind components, u and v , similar high uncertainties due to aircraft movement. A detailed description of the Twin Otter turbulence instrumentation and associated data processing can be found in Weiss et al. (2011).

Ambient air temperature was observed with Goodrich Rosemount Probes, mounted on the nose of the aircraft. A non-de-iced model 102E4AL and a de-iced model 102AU1AG logged the temperature at 0.7 Hz. Atmospheric humidity was measured with a Buck 1011C cooled mirror hygrometer. The 1011C Aircraft Hygrometer is a chilled mirror optical dew point system. The manufacturer stated the reading accuracy of $\pm 0.1 \text{ }^\circ\text{C}$ in a temperature range of -40 to $+50 \text{ }^\circ\text{C}$. Chamber pressure and mirror temperature were recorded at 1 Hz.

2.3. *In situ* atmospheric chemistry instrumentation

A Los Gatos Research (LGR) Ultraportable Greenhouse Gas Analyser (uGGA) was installed to measure CH_4 , CO_2 and H_2O . Expected manufacturer precision for the CH_4 measurement was $< 2 \text{ ppb}$ averaged over 5 s and $< 0.6 \text{ ppb}$ over 100 s. The response time of the LGR uGGA itself (i.e. the flush time through the measurement cell) was 10 s. To achieve higher temporal frequency data, a fast Picarro G2301-f was installed that provided measurements of CH_4 , CO_2 and H_2O at $\sim 10 \text{ Hz}$, with $1-\sigma$ precision at 10 Hz of $< 3 \text{ ppb}$ for CH_4 . A third greenhouse gas analyser, a LGR Ultraportable $\text{CH}_4/\text{C}_2\text{H}_6$ Analyser (uMEA) was



130 used to measure CH₄ and C₂H₆. The 1- σ precision of the uMEA, as stated by the manufacturer, was < 2 ppb for CH₄ and < 30
ppb for C₂H₆ at 1 s, however in-house laboratory measurements suggest C₂H₆ 1- σ precision at 1 s is ~17 ppb for this unit.
During the 2019 airborne campaign, atmospheric C₂H₆ was monitored by a Tuneable Infrared Laser Direct Absorption
Spectrometer (TILDAS, Aerodyne Research, Inc) (Yacovitch et al., 2014b). This instrument utilises a continuous wave laser
operating in the mid-infrared region (at $\lambda = 3.3 \mu\text{m}$). Further description of the TILDAS instrument set-up and performance is
135 available in the Appendices.

2.4. Calibration of *in situ* instrumentation

2.4.1. CH₄ and CO₂ calibration

In-situ CH₄ and CO₂ instruments were calibrated in-flight using a manually operated calibration deck, shown in schematic
form in Fig. 2. The calibration gases consisted of a suite of WMO referenced standards with a “High”, “Low” and “Target”
140 designation. The “High” CH₄ concentration was ~2600 ppb, the “Low” ~1850 ppb and the “Target” ~2000 ppb concentration.
CO₂ concentrations were “High” ~468.5 ppm, the “Low” ~413.9 ppm and the “Target” ~423.6 ppm. The absolute values of
the cylinders varied between years as they were re-filled and re-certified to the NOAA WMO-CH₄-X2004A and WMO-CO₂-
X2007 scales. The calibration deck is designed so that upon the calibration valve opening, the calibration gas flow rate is
sufficient to overflow the inlet. A similar approach to in-flight calibration is also applied on the NOAA WP-3D aircraft
145 (Warneke et al., 2016). Full details of the calibration procedure is recorded in the Appendices. CH₄ uncertainty (1 σ) at 1 Hz is
calculated as 1.24 ppb for the Picarro G2301-f and 1.77 ppb for the uGGA, giving performance comparable with similar
instrumentation on the FAAM aircraft (O’Shea et al., 2014). The excellent agreement between measured and expected values
of CH₄ for the target cylinder (for the Picarro and uGGA) gives us confidence in being able to operate to high levels of accuracy
with a very limited period of instrument fitting and testing. CO₂ uncertainty (1 σ) at 1 Hz is calculated as 0.20 ppm for the
150 Picarro G2301-f and 0.35 ppm for the uGGA. More details on the calibration and associated uncertainties are shown in the
Appendices.

2.4.2. C₂H₆ calibration

The calibration cylinders installed on the Twin Otter during both campaigns did not contain a sufficient range of C₂H₆
concentrations to enable calibrations to be performed. This represents a limitation on the accuracy and traceability of the C₂H₆
155 measurements during these campaigns and will be addressed for future studies using the BAS Twin Otter. The uMEA was
calibrated in the laboratory post campaign for the 2018 campaign, and pre-and post-campaign in the laboratory for the 2019
season. Corrections for C₂H₆ and CH₄ measurement drift as a function of cavity temperature were determined experimentally
by analysing two calibration cylinders alternately over the course of several hours as the cavity temperature increased. These
corrections were then applied to the uMEA C₂H₆ and CH₄ measurements obtained from both 2018 and 2019 flight campaigns.



160 The TILDAS (deployed in 2019) was corrected for water vapour using the TDLWintel software (Nelson et al., 2004) to account
for changes in humidity during the flight (as discussed in Pitt et al., (2016)). The instrument has a quoted precision of 50 ppt
for an averaging time of 10 s. The raw measured data were calibrated pre- and post-flight using two cylinders of known
concentration, whose mole fractions spanned the measurement range observed during flights for C₂H₆. By assuming a linear
relationship, the calibrated mole fraction corresponding to each measured TILDAS mole fraction was given by interpolating
165 the scale between the pre- and post-flight calibration reference points.

Previous studies have reported the sensitivity of TILDAS systems to aircraft cabin pressure (e.g. Pitt et al., (2016) and
Gvakharia et al., (2018)). This sensitivity means that the C₂H₆ mole fractions measured during the flight contain a systematic
altitude-dependent bias. However, as cabin pressure only affects the spectroscopic baseline, the zero-offset of the
measurements is affected, but not the instrument gain factor. Therefore, as long as each plume measurement is referenced to a
170 measured background at the same altitude, this cabin pressure sensitivity does not significantly impact the calculated C₂H₆
mole fraction enhancements. As stated above, future deployments will mitigate this issue by employing in-flight calibration
cylinders that are certified for C₂H₆. The potential to use a fast, frequent calibration for baseline correction as described by
Gvakharia et al., (2018) will also be investigated, although this has payload implications as it requires an extra calibration
cylinder.

175 2.5. Spot Sampling

On a rapid aircraft fit, manually triggered spot sampling provides a cost-effective and simple method for analysis which cannot
be performed mid-flight or require specialist laboratory facilities to gain useful levels of precision. Two discrete air-sampling
systems were used during these flights to enable post-flight analysis for VOCs and $\delta^{13}\text{C}_{\text{CH}_4}$.

2.5.1. Son of Whole Air Sampler (SWAS)

180 The Son of Whole Air Sampler (SWAS) is a new, updated version of the parent WAS system fitted to the FAAM BAE 146
large atmospheric research aircraft (e.g. as used in O'Shea et al., (2014)), which it is designed to supersede. The system
comprises a multitude of inert Silonite-coated (Entech) stainless steel canisters, grouped together modularly in cases with up
to 16 canisters per case. On-board the Twin Otter, 2 cases can be fitted allowing up to 32 canisters to be carried per flight. The
theory of operation is to capture discrete air samples from outside of the aircraft and compress the sample either into 1.4 L or
185 2 L canisters at low pressure (40 psi) via pneumatically-actuated bellows valves (PBV, Swagelok BNVS4-C). Full details of
the operation of SWAS are included in the Appendices. For the 2019 campaign, SWAS was updated with the addition of 2 L
flow-through canisters making narrow plumes easier to capture due to reduced sample line lag and fill times.

SWAS canisters sampling was manually triggered during the flights according to in-situ observations made by fast response
instrumentation such as CO₂, C₂H₆ and CH₄, with the aim of capturing specific oil and gas plumes. The samples were analysed
190 at the University of York for VOCs post-flight using a dual-channel gas chromatograph with flame ionisation detectors
(Hopkins et al., 2003). Firstly, 500 mL aliquots of air are withdrawn from the sample canister and dried using a condensation



finger held at $-30\text{ }^{\circ}\text{C}$ then pre-concentrated onto a multi-bed carbon adsorbent trap consisting of Carboxen 1000 and Carbotrap B (Supelco), and transferred to the GC columns (Al_2O_3 , NaSO_4 deactivated and open tubular PLOT) in a stream of helium. Chromatogram peak identification was made by reference to a calibration gas standard (NPL30, D600145 - 2018) containing
195 known amounts of 30 VOCs ranging from C2-C9. Compounds of interest include C_2H_6 , propane, butanes, pentanes, benzene and toluene; a full list is shown in Table A1.

2.5.2. Flexfoil Bag Sampling

Spot sampling for $\delta^{13}\text{C}_{\text{CH}_4}$ by collecting whole air samples into Flexfoil bags (SKC Ltd) has been in use on both the FAAM BAE 146 research aircraft (e.g. (Fisher et al., 2017)) and during ground based mobile studies (e.g. (Lowry et al., 2020) and
200 provides a relatively cost-effective and rapid methodology for sample collection. The method does have some limitations, however, as the Flexfoil sample bags are only stable for a number of compounds (including CH_4) and is not a true whole air sample. Samples captured in both Flexfoil bags and SWAS were measured at Royal Holloway using CF-IRMS (continuous flow isotope ratio mass spectrometry) (Fisher et al., 2006) and each measurement has a $\delta^{13}\text{C}_{\text{CH}_4}$ uncertainty of $\sim 0.05\text{ }^{\circ}\text{‰}$. Each sample is also measured for CH_4 mole fraction using cavity ring-down spectroscopy to allow direct comparison to in-flight
205 data (Fig A3). Alternative, continuous in-flight $\delta^{13}\text{C}_{\text{CH}_4}$ instrumentation currently cannot replicate the precision of laboratory sampling, and the few seconds of enhanced CH_4 that would be encountered during flight is not sufficient for averaging of continuous $\delta^{13}\text{C}_{\text{CH}_4}$ data to gain a meaningful source $\delta^{13}\text{C}_{\text{CH}_4}$ signature (e.g. (Rella et al., 2015)).

3 Overall approach to flight planning

The majority of flights were conducted during good operating conditions i.e. - daytime, no precipitation, clear or broken cloud,
210 winds $< 10\text{ms}^{-1}$ and visibility to allow flying at minimum safe altitude around the task area. Two approaches were trialled to assess CH_4 emissions from offshore gas installations: (1) regional survey, and (2) specific plume sampling. The flight modes are demonstrated in Fig. 3, with the dark grey pattern showing a flight plan for regional measurements and the orange and white patterns demonstrating specific plume sampling flight patterns. Flight plans to sample specific installations were designed to capture a full range of expected emissions using the UK National Atmospheric Emissions Inventory (NAEI) as a
215 guide.

Regional survey intentions were two-fold: firstly, to offer an identification process for emitters of interest that could specifically be targeted for plume sampling modes, and secondly, to build a picture of aggregate bulk emissions for multiple upwind platforms. This method has been successfully employed during a Gulf of Mexico airborne study (Gorchov Negron et al., 2020). However, in this instance, regional surveys were poor for identifying plumes (being too far downwind of platforms or not intercepting thin filament layers containing CH_4 enhancements) and attempts to aggregate bulk emissions were hindered by the often encountered complex boundary layer structure over the area, which controlled dispersion of CH_4 emissions from



rigs. From the regional flight data derived in 2018, and considering the work in other offshore studies in this area (e.g. Cain et al., (2017)), the regional flight mode was determined to be of limited scientific value in the context of this project and this flight pattern was not used during the 2019 campaign.

Plume sampling flights were conducted in both 2018 and 2019. These flights involved the use of a box pattern to create both upwind and downwind transects either side of the infrastructure of interest. Upwind transects provided an understanding of other methanogenic sources (such as other installations, ships or long range transport of air masses from on-shore sources) that could interfere with observed CH₄ plumes downwind, and were conducted to be confident that plumes were solely originating from the targeted infrastructure. Vertically stacked downwind transects were conducted to better capture the vertical extent of the plume in a 2-dimensional Lagrangian plane for CH₄ flux quantification using mass balance analysis (e.g. O'Shea et al., (2014)). The vertically stacked transects in profile, as planned from the 2019 field deployment, are demonstrated in Fig. 3. The separation between vertically stacked transects was usually 200 ft (60 m) with a minimum absolute height of 150 ft (45 m) above sea surface up to approximately 850 ft (260 m) to capture the entire extent of a downwind plume. Plume dispersion was dependent on meteorology and emission type (venting, fugitive, or combustive emissions) and as such, maximal plume heights varied between individual infrastructure. Upwind transects were flown at a median height between the minimum and maximum stacked runs.

4. Assessing and addressing issues encountered during flights

A number of issues were encountered during the flights that influenced the measurements made. An initial presentation of these issues is given here, with recommendations for improvements given in Section 6 below.

4.1. Complex marine boundary layers

Boundary layer structure proved to be a decisive influence on observed CH₄ mixing ratios. Figure 4 shows the measured profiles of CH₄ (left hand panel) and potential temperature (right hand panel) during an off-shore flight in April 2018 along with the corresponding synoptic chart. Potential temperature was calculated as described in Stull (1988). The potential temperature profile demonstrates that the boundary layer structure on this day (and many other days) was partly stable stratified, showing mostly an increase in potential temperature with height, and the boundary layer showed complex layering. The prevailing meteorological situation at that time, illustrated by the synoptic chart in Figure 4, was of a persistent anticyclonic ridge, stretching from the south-west over the British Isles and Western Europe, with associated low wind speeds and poorly defined air flow over the southern North Sea sector. The observed layering was partly also caused by residual boundary layers from previous days and nights which had not dispersed. The structure of the boundary layer in Fig. 4 clearly had an important influence on the vertical profile of CH₄, which varied and shows a complex profile with height. Due to the complexity of the



boundary layer structure, it was concluded that it would be inappropriate to use a particle dispersion model such as NAME (Jones et al., 2007) to derive a bulk regional emission estimate.

255 The impact of the residual layers of CH₄ enhancement make in-flight decision very challenging for two main reasons: 1. The difficulty of determining which enhancements are from installations and require further investigation, especially if flying at some distance downwind from a potential source or on a regional survey pattern. 2. Emissions being actively released can become trapped in vertically thin filaments, which can be easily missed when flying stacked legs, depending on flight altitude. In contrast, on days with a well-mixed boundary layer the CH₄ profile stays relatively constant with height, and shows increase
260 only in the surface layer near CH₄ sources. Fig. 5 shows an example of composite CH₄ and potential temperature profiles flown within an hour of each other, in a well-mixed boundary layer during a flight in May 2019; the synoptic situation on that day was consistent with a slow-moving cyclonic south-easterly air flow. It can clearly be seen how the potential temperature and CH₄ profiles stay almost constant with height above 200 m, and only show structure near CH₄ sources. The potential temperature profile indicates neutral stratification of the boundary layer.

265 **4.2. Instrument response times**

The role of the continuous in-flight measurements is to provide the backbone of the dataset and ensure that, at a bare minimum, the flights are able to identify areas of CH₄ enhancement and inform on the likely sources of the CH₄ enhancement, hence the decision to run redundancy measurements of CH₄ utilising an LGR uGGA. Figure 6 shows a typical suite of instrument response to a CH₄ plume and it is clear that the cell turnover time of the uGGA is not sufficient to capture the fine detail of
270 the plume. Whilst the uGGA and uMEA are capable of determining whole infrastructure mass balance and average infrastructure ethane-methane ratios, the refined understanding of the true plume is lost in these slower response instruments. This is important as the combined Picarro G2301-f and TILDAS data can detect several sources from the same installation (Fig. 6), because of their rapid measurement cell turnover. This information can be used to infer either cold venting (CH₄ & C₂H₆) or combustion from flares or generators (CO₂, CH₄ and C₂H₆) which could then be used to determine CH₄ emission
275 factors from identified flares (Gvakharia et al., 2017).

There are a number of other implications that arise from slow measurement response. For example, in-flight spot sampling requires guidance from fast response instruments that can indicate the optimum timing to collect samples that span the plume, and thereby capture the representative chemical nature of the plume. Further, in-flight calibrations must be matched to the
280 slowest response instrument to ensure stabilisation of the measurement of calibration gases across all instruments. Use of slower-response instruments thus induces additional, unwanted loss of measurement time and excessive use of calibration gases and the benefits of instrument redundancy should be carefully considered.



4.3. Spot sampling improvements between 2018 and 2019 campaigns

In-flight spot sample collection was carried out during both the 2018 and 2019 campaigns. Such sampling is challenging, and
285 requires fast response instruments to be viewable to the operator to give the best chance of collecting samples at appropriate
times that span the plume. For 2019, a number of simple adaptations were introduced that significantly increased the success
of capturing plumes (Fig. A3). The improvements included modified flight planning, with an increased number of passes
through discovered plumes. This approach resulted in increased fuel consumption per plume, but contributed to the higher
success rate of plume capture. The comprehensive update to the SWAS system, which included continuous sample through-
290 flow allowed more precise spot sampling to be achieved.

5. Creation of data products

5.1. Methane fluxes

A methane flux can be calculated from the CH₄ mixing ratio data using mass balance techniques (e.g. (O'Shea et al., 2014; Pitt
et al., 2019) in which a vertical 2D plane is defined at a fixed distance downwind of the infrastructure of interest, and sampling
295 is conducted across the stacked transects at this distance if a plume is identified in the downwind plane. Fluxes were derived
using Eq. (1):

$$Flux = (X_{plume} - X_{background}) \times n_{air} \times V \times \Delta x \quad (1)$$

300 where *Flux* is the bulk net flux passing through the plane per metre altitude (mol m⁻¹ s⁻¹), *n_{air}* is the molar density of air (mol
m⁻³), *X_{plume}* is the average CH₄ mole fraction measured within the plume, and *X_{background}* is the CH₄ mole fraction of the
background. *V* is the wind component perpendicular to the flight track and Δx is the plume width perpendicular to upwind-
downwind.

305 The CH₄ and CO₂ measurements from the 10 Hz response instruments were used to provide the highest accuracy in (1) lateral
plume width and (2) number of unique plumes identified from each individual platform. Slower response instruments would
allow for flux calculations but would not be able to identify individual plumes from the same platform. This could be useful
to distinguish, for example, multiple plumes from different emission processes that are spatially distinct within the same
platform (e.g., a fugitive source vs. a flare). A background mixing ratio was selected to best represent the conditions observed
310 during the flight at the specific time of survey. An average of 30 s of data either side of the plume on each run was used, if this
was deemed appropriate with a clean upwind sampling leg. When the upwind sampling was contaminated, more caution should
be taken when selecting an appropriate background so that the background value is not distorted by extraneous far-field
sources.



315 For this analysis, a flux across each individual vertical run downwind of a plume was calculated before scaling in the vertical
component. The flux was then integrated across potential minimum and maximum plume depths. Figure 7 (upper panel)
represents a reduced vertical resolution of the plume where transects at intermediate altitudes through the plume were not
conducted. In this case, the minimal plume depth is the narrow span captured by observation in the 45.9 – 51.9 m altitude
window. The maximal plume depth is taken as the height difference between the maximal and minimal altitude transects that
320 do not demonstrate CH₄ enhancements so are outside of the plume; this value has to be used as the maximum due to incomplete
sampling of the void area seen in the upper panel of Fig. 7. In cases where the base and top of the plume were not sampled
(e.g. during 2018 sampling), the lower limit was selected as the sea surface and the upper limit of the plume was selected as
the atmospheric marine boundary layer. The greatest uncertainty in bulk flux arises when the vertical resolution is not fully
captured. Between the 2018 and 2019 portions of the campaign, the flux uncertainty related to plume depth was reduced by a
325 factor of 10 (as seen in Table 1) by completing a rigorous set of stacked transects at multiple heights throughout the plume.

5.2. Ethane-Methane ratios (C₂:C₁) as a source tracer

It has already been well established that continuous C₂H₆ measurements can be an excellent diagnostic tool for ascribing
enhancements of co-located CH₄ and C₂H₆ to natural gas emissions in both urban areas (e.g. (Plant et al., 2019)), semi-rural
areas (e.g. Lowry et al., 2020)) and during large scale evaluations of oil and gas fields from aerial studies in the USA (e.g.
330 (Peischl et al., 2018)), Canada (Johnson et al., 2017), and the Netherlands (Yacovitch et al., 2018). During this work, two
methods were used to establish C₂H₆-CH₄ ratios (hereafter, described as C₂:C₁). In 2018 a Los Gatos ultraportable CH₄/C₂H₆
analyser (uMEA) was used. The benefits of such instrumentation are in its simplicity of operation and that few considerations
are required for corrections or variable lags as both species are measured at the same rate and within the same optical cavity.
C₂:C₁ can therefore be readily determined as the gradient of a linear regression between the C₂H₆ and CH₄ measurements.
335 However, the low sensitivity to C₂H₆ (standard deviation of ~10 ppb in C₂H₆ over 10 s of background flying) only allowed
emissions from two platforms to be characterised for C₂:C₁ ratios during the whole of the 2018 flying, and none during 2019.

In 2019 the addition of the TILDAS 1 Hz C₂H₆ instrument allowed for better precision of C₂H₆ (< 1 ppb) with a faster flush
time in the measurement cell. The C₂H₆ data is time matched with the 1 Hz Picarro CH₄ data set to allow C₂:C₁ derivation.
340 As the instruments do not have the exact same flow rate and different cell residence times, the C₂:C₁ ratios were determined
using the integral of each CH₄ and C₂H₆ enhancement using Gaussian peak fitting. A comparison between the 2018 flight,
2019 flight and published data derived from the same geographical area, is shown in Table 2. Although both instruments have
been operated for this work without in-flight calibration or engineering solutions to address cabin pressure sensitivity issues
(Gvakharia et al., 2018) due to weight and time constraints, the agreement between years and with published expected values
345 is highly reassuring. The added value in high precision C₂:C₁ demonstrates that C₂H₆ is not just a tracer for matching emissions
to natural gas; it can give information as to proportions of emissions from mixed sources (as previously used in Peischl et al.,



(2018)) or can be used to identify a likely emission point in a process chain depending upon enrichment or depletion of C_2H_6 relative to CH_4 . The inclusion of a continuous instrument with a sub-ppb level of detection for C_2H_6 is considered vital for future work with thermogenic sources of CH_4 to allow more precise source attribution of emissions where no spot sampling
350 has occurred.

5.3. $\delta^{13}C_{CH_4}$ for CH_4 source attribution

The principal method of $\delta^{13}C_{CH_4}$ source characterisation utilises the principles outlined in Keeling (1961) and Pataki et al., (2003), and has been well utilised since to create $\delta^{13}C_{CH_4}$ databases for a plethora of known CH_4 sources (e.g. (Sherwood et al., 2017)). In order for a Keeling plot to give useful results to determine a $\delta^{13}C_{CH_4}$ source signature of a CH_4 emission, the
355 emission must have been successfully captured multiple times and ideally with a range of CH_4 mixing ratios (which could be achieved by passes at different distances or heights downwind of a point source). This sampling process takes time (especially on an aircraft), where the emission plume is only intercepted once per transect and time in the plume is limited so that only one spot sample can be taken whilst “in-plume”. Beyond the time limitations, sampling of a range of CH_4 mixing ratios from emissions and appropriate background samples is not straightforward. Background sampling must capture the air into which
360 emissions are released, but during flights the meteorological conditions often resulted in significant variation of CH_4 mixing ratio and $\delta^{13}C_{CH_4}$ with altitude, in addition to horizontal variations. Where repeat transects were conducted at different altitudes, this made selection of appropriate background samples for Keeling plots challenging, since the background CH_4 mixing ratio and $\delta^{13}C$ varied over the different altitudes. This becomes particularly detrimental to Keeling plot validity where the range in sampled emission mixing ratios is small, since uncertainty in the background samples then becomes more important.

365
In Fig. 8, a sensitivity analysis is presented from one of the flights investigating the effect of reducing the number of samples on the uncertainty in the $\delta^{13}C_{CH_4}$ source signature determined for a plume. In this case nine samples were collected, but over eight downwind transects and one upwind transect of a cluster of installations, which is not feasible to repeat for sampling large numbers of installations. As shown in Fig. 8, the uncertainty in the $\delta^{13}C_{CH_4}$ source signatures increases only slightly with
370 reduction in number of sampling points, with the exception of one $n = 3$ run where the source signature is poorly defined. A minimum of three data points can be therefore sufficient for classifying a source of CH_4 emissions (such as thermogenic, microbial or pyrogenic sources), providing that the background and point samples are captured with a large enough range of CH_4 concentration, and providing that there is no mixing of sources. This will typically require collection of more than three samples, given some may miss the targeted plumes or potentially be lost during storage/processing as aforementioned.
375 Although a two-point Keeling plot is technically possible, it is impossible to gauge the quality of the regression to be sure that only a single source has been captured.



6. Conclusions

Given the restrictions and time constraints on the science flights, important lessons for offshore oil and gas airborne measurement campaigns have been learned for rapid instrument re-fitting and agile deployment of a small aircraft for future
380 campaigns. A key finding from this study is that offshore meteorological conditions define the ability of the flights to produce valuable data, and suitable meteorology with a well-mixed (neutral) boundary layer is critical to deriving a regional emission estimate through regional modelling. Flying in conditions with multiple residual boundary layers makes interpretation difficult and pin-pointing emissions especially challenging as emission plumes can easily be missed when they are trapped in thin filaments, dramatically increasing the uncertainties of measurement-based emission flux calculations. Although not possible
385 for this work given aircraft scheduling, it is recommended that offshore observations are scheduled with a long window of opportunity to ensure optimal flying conditions. Predictions of the likelihood of a residual boundary layer over a coastal area could be achieved through high spatial resolution forecast models such as the UK Met Office forecast model (Milan et al., 2020). Information on the temperature structure over the previous few days using all the assimilated information, such as tephigrams and synoptic charts, would help determine the likelihood of residual boundary layers versus a simpler stratified,
390 well mixed layer. For methods using alternative platforms such as ships or drones, co-incidental measurements of vertical profiles must be made to capture the true nature of the emission plume in the current meteorology.

Unlike some of the larger aircraft, payload restrictions and power limitations demand challenging decisions for instrument selection. We recommend deploying at least one instrument measuring CH_4 (and CO_2) at 10 Hz, allowing several plumes
395 emitted from a single installation to be resolved (Fig. 6). Priority should next be given to a C_2H_6 measurement capable of sub ppb limit of detection at 1 Hz (or higher) in order to give certainty to the source of the CH_4 emission. Using $\text{C}_2:\text{C}_1$ appears to be the simplest method for source attribution, and is robust for distinguishing natural gas emissions, where the gas has an C_2H_6 component (Lowry et al., 2020; Plant et al., 2019). Spot sampling is challenging, payload heavy and time consuming as several passes are needed to collect enough samples (especially for $\delta^{13}\text{C}_{\text{CH}_4}$ source attribution). However, results can be very
400 informative such as the ability to distinguish a gas leak geological reservoir from depth or near surface (Lee et al., 2018). The improvements to SWAS, allowing for continuous through flow, has increased the success rate of peak sampling, but still relies on accurate user triggering.


For mass balance flux calculations, an instantaneous plume and the surrounding background variation in the species of interest,
405 alongside local meteorology, must be fully resolved during the observation stage. This includes instruments with appropriate response times to fully capture the plume and identify any internal structure that may suggest a mixed source. An upwind leg must be conducted to ensure the plume and background is not contaminated by extraneous far-field sources and the plume must be significantly distinct from this background for meaningful flux calculations. The plume must be laterally and vertically resolved in the 2D plane as much as possible at a fixed distance downwind of the source. Straight and level runs must extend




410 either side of the plume and the vertical resolution must include multiple stacked transects with an identification of the top and
bottom of the plume (where feasible) to reduce uncertainty in the plume bulk net flux. Full understanding of the meteorology
during data collection with meteorological measurement instrumentation and an entire profile to determine the marine
boundary layer characteristics from the top to the surface, including determination of inversion heights, must be conducted
during the flight day when appropriate radiosonde soundings are not available. The observed impact of complex boundary
415 layer dynamics on plume dispersion also highlights an important limitation of ship-based plume measurements, which are
unable to resolve the vertical structure of the plume and therefore rely on the assumption of idealised models of plume
dispersion.



420 7. Figures and Tables



VP-FAZ



- Escape Hatch
- Connector Panel
- Life raft
- Smoke Hoods
- 1 x 50A outlet
- 2 x 50A outlets
- 3 x 50A outlets

- Notes:
- 1) No Wing Instrumentation.
 - 2) Total science kit fitted weight estimated at 800 lbs.
 - 3) Aiming to keep roof hatch accessible for predominantly overwater flying.

Russ Ladkin 28-Mar-2018





Figure 1. Instrument schematics for the Twin Otter aircraft as deployed in 2018 and 2019, detailing changes in layout and instrumentation between the two campaigns. The top panel is the 2018 fit and lower panel 2019 fit.



All tubing $\frac{1}{4}$ " OD, 4.32mm ID Synflex 1300


Russ Ladkin 2-Jul-2018

Figure 2. Layout of plumbing of the calibration system (and inlet system) for 2018 campaign.




430


Figure 3: [top panel] flight patterns showing the regional and plume capture styles of flight deployed between 2018 and 2019, alongside infrastructure of interest (such as drilling rigs, gas distribution platforms or production platforms). [bottom panel] a 2019 plume sampling survey showing idealised stacked transects in the 2D plane downwind of infrastructure of interest.



435 **Figure 4. Example of CH₄ and potential temperature profiles showing the large amount of structure arising from residual boundary**
layers. The increase of the potential temperature with height shows stable stratification of the boundary layer. The synoptic chart
over the eastern North Atlantic and north West Europe shows contoured sea level pressure (hPa), 2m temperature (°C, right-hand
side colour scale) and wind for 20/04/2018 12:00 UT, and reveals relatively low wind speeds and poorly defined air flow over the
southern North Sea sector, allowing the build-up of residual boundary layers. Synoptic chart image produced by the UK National
440 **Centre for Atmospheric Science (NCAS) using Weather Research and Forecasting model WFR-ARW version 3.7.1, with a 20 km**
grid spacing, 51 vertical levels initialised using the NOAA Global Forecast System. NCAS Weather Research Catalogue
(sci.ncas.ac.uk/nwr/pages/home)




445 **Figure 5. Example of CH₄ and potential temperature profiles in a well-mixed boundary layer under neutral conditions. These are composite profiles flown within an hour over water. The potential temperature and CH₄ profiles stay relatively constant above 200 m. The synoptic chart for 03/05/2019 12:00 UT shows a cyclonic south-easterly air flow over the southern North Sea sector originating from the Benelux.**




450

Figure 6. A cross-section of CH_4 , CO_2 and C_2H_6 measurement response during one plume sample as recorded by Picarro G2301-f in Pink and Green (10 Hz as dashed lines and downsampled to 1 Hz as solid lines), TILDAS 1 Hz in cyan and Los Gatos uGGA 1 Hz in brown. The difference of the uGGA and Picarro at 1 Hz arises from the slower uGGA response time due to the slower cell turnover. The blue shaded area shows enhancement in C_2H_6 and CH_4 , indicating cold venting, the orange shaded area shows enhancement in C_2H_6 , CH_4 and a small amount of CO_2 potentially indicating a co-located combustion source.

455



460 **Figure 7. Plumes measured from separate installations to demonstrate the differences in strategies between 2018 and 2019. [upper panel] Plume sampled downwind with poorer vertical spatial resolution in the 2D plane during the 2018 portion of the campaign. CH₄ measured values are much higher due to platform activities during the survey time. [lower panel] Plume sampled downwind in 2019 with intermediate transects enabling higher vertical spatial resolution. Note the colour scale across each plot signifies different measured CH₄; the scales on the upper and lower plots are different.**



465 **Figure 8.** $\delta^{13}\text{C}_{\text{CH}_4}$ source signature data source signature data derived from data collected around one installation and assumes a single source of excess methane. The coloured bars represent the uncertainty in the intercept for the regression with varying numbers of sample points removed from the dataset to represent the data if fewer in-plume samples had been collected.

<i>Survey Year</i>	CH₄ flux lower bound (kT yr ⁻¹)	CH₄ flux upper bound (kT yr ⁻¹)
2018	1.83	17.9
2019	0.67	1.04

470 **Table 1.** A comparison of flux lower and upper bounds for two individual example plumes across each year of survey as scaled by the vertical resolution available. The plumes themselves are not comparable, but the method changes demonstrate the increased certainty in the final results.



	Instrument(s)	Method	C2:C1	Uncertainty
<i>2018 flight</i>	Los Gatos ultraportable CH ₄ /C ₂ H ₆	Linear regression	0.029	± 0.014
<i>2019 flight</i>	TILDAS C ₂ H ₆ & Picarro G2301-f CH ₄	Plume area integration	0.029	± 0.003
<i>Published well data</i>			0.031	± 0.009

Table 2. Reported data for C2:C1 for a single installation surveyed during both 2018 and 2019 surveys. Well data from UK oil and gas authority report: <https://dataogauthority.blob.core.windows.net/external/DataReleases/ShellExxonMobil/GeochemSNS.zip> alongside measured C2:C1 for CH₄ enhancements measured during flights in the same geographic area.

475



Author Contribution

480 The manuscript was written and figures prepared by JLF, PB and PD with assistance from AEJ, MC, JP, SB and JTS. Experimental design and flight planning was performed by GA, JP, JDL, TLC and DL. Aircraft set-up and in-flight measurements performed by JP, PB, PD, SJA, SY, AIW, TLC, JLF, SW, JW and SB. Laboratory measurements made by REF, RP, SW and SB. Data Processing and calibrations performed by JLF, LH, PB, JTS, PD and MC and SB. Modelling work by NW, JAP, PB and LH.

485 Code / Data Availability

The data for this work will be available via request at the British Antarctic Survey Polar Data Centre.

Competing interests

The authors declare that they have no conflict of interest

Acknowledgements

490

This work was funded under the Climate and Clean Air Coalition (CCAC) Oil and Gas Methane Science Studies (MSS), hosted by the United Nations Environment Programme. Funding was provided by the Environmental Defense Fund, Oil and Gas Climate Initiative, European Commission, and CCAC.

References

495

Cain, M., Warwick, N. J., Fisher, R. E., Lowry, D., Lanoisellé, M., Nisbet, E. G., France, J., Pitt, J., O'Shea, S., Bower, K. N., Allen, G., Illingworth, S., Manning, A. J., Bauguitte, S., Pisco, I., and Pyle, J. A.: A cautionary tale: A study of a methane enhancement over the North Sea, *Journal of Geophysical Research: Atmospheres*, 122, 7630-7645, 2017.

500

Cardoso-Saldaña, F. J., Kimura, Y., Stanley, P., McGaughey, G., Herndon, S. C., Roscioli, J. R., Yacovitch, T. I., and Allen, D. T.: Use of Light Alkane Fingerprints in Attributing Emissions from Oil and Gas Production, *Environmental Science & Technology*, 53, 5483-5492, 2019.

505

Conley, S., Faloon, I., Mehrotra, S., Suard, M., Lenschow, D. H., Sweeney, C., Herndon, S., Schwietzke, S., Pétron, G., Pifer, J., Kort, E. A., and Schnell, R.: Application of Gauss's theorem to quantify localized surface emissions from airborne measurements of wind and trace gases, *Atmos. Meas. Tech.*, 10, 3345-3358, 2017.

Conley, S., Franco, G., Faloon, I., Blake, D. R., Peischl, J., and Ryerson, T. B.: Methane emissions from the 2015 Aliso Canyon blowout in Los Angeles, CA, *Science*, 351, 1317-1320, 2016.



- 510 Crawford, T. L., Dobosy, R. J., and Dumas, E. J.: Aircraft wind measurement considering lift-induced upwash, *Boundary-Layer Meteorology*, 80, 79-94, 1996.
- 515 Edwards, P. M., Young, C. J., Aikin, K., deGouw, J., Dubé, W. P., Geiger, F., Gilman, J., Helmig, D., Holloway, J. S., Kercher, J., Lerner, B., Martin, R., McLaren, R., Parrish, D. D., Peischl, J., Roberts, J. M., Ryerson, T. B., Thornton, J., Warneke, C., Williams, E. J., and Brown, S. S.: Ozone photochemistry in an oil and natural gas extraction region during winter: simulations of a snow-free season in the Uintah Basin, Utah, *Atmos. Chem. Phys.*, 13, 8955-8971, 2013.
- 520 Fisher, R., Lowry, D., Wilkin, O., Sriskantharajah, S., and Nisbet, E. G.: High-precision, automated stable isotope analysis of atmospheric methane and carbon dioxide using continuous-flow isotope-ratio mass spectrometry, *Rapid Communications in Mass Spectrometry*, 20, 200-208, 2006.
- 525 Fisher, R. E., France, J. L., Lowry, D., Lanoisellé, M., Brownlow, R., Pyle, J. A., Cain, M., Warwick, N., Skiba, U. M., Drewer, J., Dinsmore, K. J., Leeson, S. R., Bauguitte, S. J.-B., Wellpott, A., O'Shea, S. J., Allen, G., Gallagher, M. W., Pitt, J., Percival, C. J., Bower, K., George, C., Hayman, G. D., Aalto, T., Lohila, A., Aurela, M., Laurila, T., Crill, P. M., McCalley, C. K., and Nisbet, E. G.: Measurement of the ^{13}C isotopic signature of methane emissions from northern European wetlands, *Global Biogeochemical Cycles*, 31, 605-623, 2017.
- 530 Garman, K. E., Hill, K. A., Wyss, P., Carlsen, M., Zimmerman, J. R., Stirm, B. H., Carney, T. Q., Santini, R., and Shepson, P. B.: An Airborne and Wind Tunnel Evaluation of a Wind Turbulence Measurement System for Aircraft-Based Flux Measurements, *Journal of Atmospheric and Oceanic Technology*, 23, 1696-1708, 2006.
- 535 Garman, K. E., Wyss, P., Carlsen, M., Zimmerman, J. R., Stirm, B. H., Carney, T. Q., Santini, R., and Shepson, P. B.: The Contribution of Variability of Lift-induced Upwash to the Uncertainty in Vertical Winds Determined from an Aircraft Platform, *Boundary-Layer Meteorology*, 126, 461-476, 2008.
- Gorchov Negron, A. M., Kort, E. A., Conley, S. A., and Smith, M. L.: Airborne Assessment of Methane Emissions from Offshore Platforms in the U.S. Gulf of Mexico, *Environmental Science & Technology*, 54, 5112-5120, 2020.
- 540 Gvakharia, A., Kort, E. A., Brandt, A., Peischl, J., Ryerson, T. B., Schwarz, J. P., Smith, M. L., and Sweeney, C.: Methane, Black Carbon, and Ethane Emissions from Natural Gas Flares in the Bakken Shale, North Dakota, *Environmental Science & Technology*, 51, 5317-5325, 2017.
- 545 Gvakharia, A., Kort, E. A., Smith, M. L., and Conley, S.: Testing and evaluation of a new airborne system for continuous N_2O , CO_2 , CO , and H_2O measurements: the Frequent Calibration High-performance Airborne Observation System (FCHAOS), *Atmos. Meas. Tech.*, 11, 6059-6074, 2018.
- 550 Hopkins, J. R., Lewis, A. C., and Read, K. A.: A two-column method for long-term monitoring of non-methane hydrocarbons (NMHCs) and oxygenated volatile organic compounds (o-VOCs), *Journal of Environmental Monitoring*, 5, 8-13, 2003.
- Jones, A., Thomson, D., Hort, M., and Devenish, B.: The U.K. Met Office's Next-Generation Atmospheric Dispersion Model, NAME III, Boston, MA2007, 580-589.
- 555 Keeling, C. D.: The concentration and isotopic abundances of carbon dioxide in rural and marine air, *Geochimica et Cosmochimica Acta*, 24, 277-298, 1961.
- Lee, J. D., Mobbs, S. D., Wellpott, A., Allen, G., Bauguitte, S. J. B., Burton, R. R., Camilli, R., Coe, H., Fisher, R. E., France, J. L., Gallagher, M., Hopkins, J. R., Lanoiselle, M., Lewis, A. C., Lowry, D., Nisbet, E. G., Purvis, R. M.,



- 560 O'Shea, S., Pyle, J. A., and Ryerson, T. B.: Flow rate and source reservoir identification from airborne chemical sampling of the uncontrolled Elgin platform gas release, *Atmos. Meas. Tech.*, 11, 1725-1739, 2018.
- Lowry, D., Fisher, R. E., France, J. L., Coleman, M., Lanoisellé, M., Zazzeri, G., Nisbet, E. G., Shaw, J. T., Allen, G., Pitt, J., and Ward, R. S.: Environmental baseline monitoring for shale gas development in the UK: Identification and
565 geochemical characterisation of local source emissions of methane to atmosphere, *Science of The Total Environment*, 708, 134600, 2020.
- Milan, M., Macpherson, B., Tubbs, R., Dow, G., Inverarity, G., Mittermaier, M., Halloran, G., Kelly, G., Li, D., Maycock, A., Payne, T., Piccolo, C., Stewart, L., and Wlasak, M.: Hourly 4D-Var in the Met Office UKV operational
570 forecast model, *Quarterly Journal of the Royal Meteorological Society*, doi: 10.1002/qj.3737, 2020. 1-21, 2020.
- Myhre, G., Shindell, D., Bréon, F.-M., Collins, W., Fuglestedt, J., Huang, J., Koch, D., Lamarque, J.-F., Lee, D., Mendoza, B., Nakajima, T., Robock, A., Stephens, G., Takemura, T., and Zhang, H.: Anthropogenic and Natural Radiative Forcing. In: *Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change*, Stocker, T. F., Qin, D., Plattner, G.-K., Tignor, M., Allen, S. K., Boschung, J., Nauels, A., Xia, Y., Bex, V., and Midgley, P. M. (Eds.), Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA, 2013.
575
- Nelson, D. D., McManus, B., Urbanski, S., Herndon, S., and Zahniser, M. S.: High precision measurements of atmospheric nitrous oxide and methane using thermoelectrically cooled mid-infrared quantum cascade lasers and detectors, *Spectrochimica Acta Part A: Molecular and Biomolecular Spectroscopy*, 60, 3325-3335, 2004.
580
- Nisbet, E. G., Manning, M. R., Dlugokencky, E. J., Fisher, R. E., Lowry, D., Michel, S. E., Myhre, C. L., Platt, S. M., Allen, G., Bousquet, P., Brownlow, R., Cain, M., France, J. L., Hermansen, O., Hossaini, R., Jones, A. E., Levin, I.,
585 Manning, A. C., Myhre, G., Pyle, J. A., Vaughn, B. H., Warwick, N. J., and White, J. W. C.: Very Strong Atmospheric Methane Growth in the 4 Years 2014–2017: Implications for the Paris Agreement, *Global Biogeochemical Cycles*, 33, 318-342, 2019.
- O'Shea, S. J., Allen, G., Gallagher, M. W., Bower, K., Illingworth, S. M., Muller, J. B. A., Jones, B. T., Percival, C. J., Bauguitte, S. J. B., Cain, M., Warwick, N., Quiquet, A., Skiba, U., Drewer, J., Dinsmore, K., Nisbet, E. G., Lowry, D.,
590 Fisher, R. E., France, J. L., Aurela, M., Lohila, A., Hayman, G., George, C., Clark, D. B., Manning, A. J., Friend, A. D., and Pyle, J.: Methane and carbon dioxide fluxes and their regional scalability for the European Arctic wetlands during the MAMM project in summer 2012, *Atmos. Chem. Phys.*, 14, 13159-13174, 2014.
- O'Shea, S. J., Bauguitte, S. J. B., Gallagher, M. W., Lowry, D., and Percival, C. J.: Development of a cavity-enhanced absorption spectrometer for airborne measurements of CH₄ and CO₂, *Atmos. Meas. Tech.*, 6, 1095-1109, 2013.
595
- Pataki, D. E., Ehleringer, J. R., Flanagan, L. B., Yakir, D., Bowling, D. R., Still, C. J., Buchmann, N., Kaplan, J. O.,
600 and Berry, J. A.: The application and interpretation of Keeling plots in terrestrial carbon cycle research, *Global Biogeochemical Cycles*, 17, 2003.
- Peischl, J., Eilerman, S. J., Neuman, J. A., Aikin, K. C., de Gouw, J., Gilman, J. B., Herndon, S. C., Nadkarni, R., Trainer, M., Warneke, C., and Ryerson, T. B.: Quantifying Methane and Ethane Emissions to the Atmosphere From Central and Western U.S. Oil and Natural Gas Production Regions, *Journal of Geophysical Research: Atmospheres*, 123, 7725-7740,
605 2018.



610 Pitt, J. R., Allen, G., Bauguitte, S. J. B., Gallagher, M. W., Lee, J. D., Drysdale, W., Nelson, B., Manning, A. J., and
Palmer, P. I.: Assessing London CO₂, CH₄ and CO emissions using aircraft measurements and dispersion modelling,
Atmos. Chem. Phys., 19, 8931-8945, 2019.

615 Pitt, J. R., Le Breton, M., Allen, G., Percival, C. J., Gallagher, M. W., Bauguitte, S. J. B., O'Shea, S. J., Muller, J. B.
A., Zahniser, M. S., Pyle, J., and Palmer, P. I.: The development and evaluation of airborne in situ N₂O and CH₄ sampling
using a quantum cascade laser absorption spectrometer (QCLAS), Atmos. Meas. Tech., 9, 63-77, 2016.

Plant, G., Kort, E. A., Floerchinger, C., Gvakharia, A., Vimont, I., and Sweeney, C.: Large Fugitive Methane
Emissions From Urban Centers Along the U.S. East Coast, Geophysical Research Letters, 46, 8500-8507, 2019.

620 Rella, C. W., Hoffnagle, J., He, Y., and Tajima, S.: Local- and regional-scale measurements of CH₄, δ¹³CCH₄, and
C₂H₆ in the Uintah Basin using a mobile stable isotope analyzer, Atmos. Meas. Tech., 8, 4539-4559, 2015.

625 Riddick, S. N., Mauzerall, D. L., Celia, M., Harris, N. R. P., Allen, G., Pitt, J., Staunton-Sykes, J., Forster, G. L.,
Kang, M., Lowry, D., Nisbet, E. G., and Manning, A. J.: Methane emissions from oil and gas platforms in the North Sea,
Atmos. Chem. Phys., 19, 9787-9796, 2019.

630 Ryerson, T. B., Camilli, R., Kessler, J. D., Kujawinski, E. B., Reddy, C. M., Valentine, D. L., Atlas, E., Blake, D.
R., de Gouw, J., Meinardi, S., Parrish, D. D., Peischl, J., Seewald, J. S., and Warneke, C.: Chemical data quantify Deepwater
Horizon hydrocarbon flow rate and environmental distribution, Proceedings of the National Academy of Sciences, 109,
20246-20253, 2012.

635 Saunio, M., Bousquet, P., Poulter, B., Peregón, A., Ciais, P., Canadell, J. G., Dlugokencky, E. J., Etiope, G.,
Bastviken, D., Houweling, S., Janssens-Maenhout, G., Tubiello, F. N., Castaldi, S., Jackson, R. B., Alexe, M., Arora, V. K.,
Beerling, D. J., Bergamaschi, P., Blake, D. R., Brailsford, G., Brovkin, V., Bruhwiler, L., Crevoisier, C., Crill, P., Covey, K.,
Curry, C., Frankenberg, C., Gedney, N., Höglund-Isaksson, L., Ishizawa, M., Ito, A., Joos, F., Kim, H. S., Kleinen, T.,
640 Krummel, P., Lamarque, J. F., Langenfelds, R., Locatelli, R., Machida, T., Maksyutov, S., McDonald, K. C., Marshall, J.,
Melton, J. R., Morino, I., Naik, V., O'Doherty, S., Parmentier, F. J. W., Patra, P. K., Peng, C., Peng, S., Peters, G. P., Pison,
I., Prigent, C., Prinn, R., Ramonet, M., Riley, W. J., Saito, M., Santini, M., Schroeder, R., Simpson, I. J., Spahni, R., Steele,
P., Takizawa, A., Thornton, B. F., Tian, H., Tohjima, Y., Viovy, N., Voulgarakis, A., van Weele, M., van der Werf, G. R.,
Weiss, R., Wiedinmyer, C., Wilton, D. J., Wiltshire, A., Worthy, D., Wunch, D., Xu, X., Yoshida, Y., Zhang, B., Zhang, Z.,
and Zhu, Q.: The global methane budget 2000–2012, Earth Syst. Sci. Data, 8, 697-751, 2016.

645 Schwietzke, S., Harrison, M., Lauderdale, T., Branson, K., Conley, S., George, F. C., Jordan, D., Jersey, G. R.,
Zhang, C., Mairs, H. L., Pétron, G., and Schnell, R. C.: Aerially guided leak detection and repair: A pilot field study for
evaluating the potential of methane emission detection and cost-effectiveness, Journal of the Air & Waste Management
Association, 69, 71-88, 2019.

Sherwood, O. A., Schwietzke, S., Arling, V. A., and Etiope, G.: Global Inventory of Gas Geochemistry Data from
Fossil Fuel, Microbial and Burning Sources, version 2017, Earth Syst. Sci. Data, 9, 639-656, 2017.

650 Warneke, C., Trainer, M., de Gouw, J. A., Parrish, D. D., Fahey, D. W., Ravishankara, A. R., Middlebrook, A. M.,
Brock, C. A., Roberts, J. M., Brown, S. S., Neuman, J. A., Lerner, B. M., Lack, D., Law, D., Hübler, G., Pollack, I., Sjostedt,
S., Ryerson, T. B., Gilman, J. B., Liao, J., Holloway, J., Peischl, J., Nowak, J. B., Aikin, K., Min, K. E., Washenfelder, R.
A., Graus, M. G., Richardson, M., Markovic, M. Z., Wagner, N. L., Welti, A., Veres, P. R., Edwards, P., Schwarz, J. P.,
Gordon, T., Dube, W. P., McKeen, S., Brioude, J., Ahmadov, R., Bougiatioti, A., Lin, J. J., Nenes, A., Wolfe, G. M.,
655 Hanisco, T. F., Lee, B. H., Lopez-Hilfiker, F. D., Thornton, J. A., Keutsch, F. N., Kaiser, J., Mao, J., and Hatch, C.:
Instrumentation and Measurement Strategy for the NOAA SENEX Aircraft Campaign as Part of the Southeast Atmosphere
Study 2013, Atmos Meas Tech, 9, 3063-3093, 2016.



660 Weiss, A. I., King, J., Lachlan-Cope, T., and Ladkin, R.: On the effective aerodynamic and scalar roughness length of Weddell Sea ice, *Journal of Geophysical Research: Atmospheres*, 116, 2011.

Yacovitch, T. I., Daube, C., and Herndon, S. C.: Methane Emissions from Offshore Oil and Gas Platforms in the Gulf of Mexico, *Environmental Science & Technology*, 54, 3530-3538, 2020.

665 Yacovitch, T. I., Herndon, S. C., Roscioli, J. R., Floerchinger, C., McGovern, R. M., Agnese, M., Pétron, G., Kofler, J., Sweeney, C., Karion, A., and Conley, S. A.: Demonstration of an ethane spectrometer for methane source identification, *Environ. Sci. Technol.*, 48, 8028, 2014a.

670 Yacovitch, T. I., Herndon, S. C., Roscioli, J. R., Floerchinger, C., McGovern, R. M., Agnese, M., Pétron, G., Kofler, J., Sweeney, C., Karion, A., Conley, S. A., Kort, E. A., Nähle, L., Fischer, M., Hildebrandt, L., Koeth, J., McManus, J. B., Nelson, D. D., Zahniser, M. S., and Kolb, C. E.: Demonstration of an Ethane Spectrometer for Methane Source Identification, *Environmental Science & Technology*, 48, 8028-8034, 2014b.

675 Zavala-Araiza, D., Alvarez, R. A., Lyon, D. R., Allen, D. T., Marchese, A. J., Zimmerle, D. J., and Hamburg, S. P.: Super-emitters in natural gas infrastructure are caused by abnormal process conditions, *Nat. Commun.*, 8, 14012, 2017.



Appendices

A1. TILDAS data processing and performance

680 The TILDAS data was processed as follows. Rapid tuning sweeps of the laser frequency (2996.8 to 2998.0 cm^{-1}) by varying
the applied current result in the collection of thousands of spectra per second, which are co-averaged. The resulting averaged
spectrum is processed at a rate of 1 Hz using a nonlinear least-squares fitting algorithm to determine mixing ratios within the
operating software, TDLWintel (© Aerodyne). Averaging of these spectra, and the path length of 76 m achieved using a
Herriott multipass cell, provide the sensitivity required for trace gas measurement. Continuously circulated fluid from the
685 Oasis chiller unit is used as a heat sink for the thermodynamically cooled components and a flow interlock cuts power to the
relevant components if the coolant flow stops. Other optical components of the instrument include a 15x Schwarzschild
objective in front of each laser, a germanium etalon for measuring the laser tuning rate, a reference gas cell containing air at
25 Torr, and numerous mirrors for adjusting the laser beam alignment. During the airborne campaign the instrument was
operated remotely via an Ethernet connection. The TILDAS C_2H_6 instrument accuracy has been tested against two standards
690 containing C_2H_6 in mixing ratios of 39.79 ± 0.14 ppb and 2.08 ± 0.02 ppb (high concentration standard and target gas,
respectively). As the TILDAS technique relies on highly precise alignment of the focussing and beam-alignment optics before
and after the multipass measurement cell it is particularly prone to motion that applies torque to the optical bench. To remove
measurement artefacts associated with this sensitivity all data collected for roll angles greater than 20 degrees has been flagged.
The presence of the TILDAS in the 2019 campaign ruled out using the multiple circular pass method around a potential
695 emission source as developed by Scientific Aviation for installation emission flux measurements (Conley et al., 2017) as there
was a risk of invalidating data due to the roll angle of the plane if circling tightly around an installation.

A2. CO_2 and CH_4 Calibration

The three cylinders were sampled periodically in-flight to determine the instrument gain factor (slope) and zero-offset for each
700 analyser. These parameters were linearly interpolated between calibrations and used to rescale the raw measured data (for
further details see Pitt et al., 2016). The uncertainties associated with instrument drift and any instrument non-linearity were
assessed by sampling the "target" cylinder mid-way between high-low calibrations. The raw target cylinder measurements
were rescaled as per the sample data; the mean offset of these target measurements from the WMO-traceable cylinder value
(and associated standard deviations) are given for the LGR uGGA and Picarro instrument and are plotted in Figure A4.
705 The typical duration of calibration cylinder measurements during the 2018 campaign was 45s. The Picarro G2301-f analyser
had a high flow rate of ~ 5 SLPM resulting in rapid flushing of both the inlet tubing and sample cavity. The measured value
for each calibration was taken as the average over 15 s prior to the calibration end, as this allowed sufficient time for the
measured value to reach equilibrium. The uGGA and uMEA both had much lower flow rates of ~ 0.5 SLPM, resulting in a
much longer equilibration time. Consequently, the calibration duration was not of sufficient length for the uGGA and uMEA



710 measurements to reach equilibrium and their calibration routine was compromised. For these instruments each calibration run
was fitted to an offset exponential function in an attempt to predict the mixing ratio at which equilibration would have occurred,
given an infinite amount of calibrating time. In order to improve the data quality and to reduce the post processing time, the
calibration periods were run for 75 seconds per cylinder during the 2019 campaign to ensure that all instruments reached
equilibrium. Target cylinders were run approximately every 1 hour of flight.

715 **A3. SWAS Operation**

Each sample is compressed into the canisters using a modified metal bellows pump (Senior Aerospace 28823-7) capable of
150 SLPM open flow but filling the canisters at ~50 SLPM measured average integrated for ~6 and 9 seconds for the 1.4 L
and 2 L canisters, respectively. Canister fill pressure is controlled electronically using a back-pressure controller (Alicat,
PCR3), BPC. The BPC can maintain flow at any set point pressure (in general 40 psi), including the final fill pressure setpoint.
720 This allows the 2 L flow through canisters to be filled, even before the operator activates the sampling, enabling air masses to
be sampled through which the aircraft has already flown seconds earlier.

Bespoke software was created to allow control of the SWAS system wirelessly from any position in the aircraft using the
Ethernet network. Bespoke software was also created for the analysis of the canisters once in the laboratory. The SWAS flown
725 on the 1st campaign (V1) was a prototype and was updated to the current final version (V2) to fulfil the requirements of the
FAAM BAE146 and to address potential issues experienced with the prototype. V2 uses the same canisters and valves as V1
but differs slightly in the size of each case and the plumbing of gas lines. In V2, the canister and valve geometry was optimised
to allow an elbow compression fitting between the valve and the canisters to be eliminated, with the valve mounted directly to
the canister. This reduces the risk of leaks by 66%. The geometry also allowed the reduction in size by 1U rack unit, allowing
730 more canisters to be fitted in the same space, improved control electronics and sample logging to ensure canister fill times
were captured accurately and stored securely. V2 also saw the addition of 2L flow-through canister cases to complement the
1.4L to-vacuum canister cases. These allowed sample air to be flushed through the canister at a user defined pressure and
makes capturing narrow plumes easier due to reduced sample line lag and fill time.


735




Figure A1. Photo of the rear-facing chemistry inlets on the BAS Twin Otter aircraft.



Figure A2. Photo of the BAS Twin Otter showing the turbulence boom protruding from the front of the aircraft superstructure.



740



745 **Figure A3.** Examples from a 2018 flight (top panel) and a 2019 flight (lower panel) with attempted capture of CH₄ plumes in spot samples (both SWAS and Flexfoil bags). Note the improved ability to sample at the correct period to capture short-lived enhancement in both SWAS and Flexfoil samples compared for 2019 to 2018 thanks to flight planning and SWAS development improvements.




Figure A4. Target gas data from flights during 2018 for the Picarro G2301-f and Los Gatos uGGA instruments for both CO₂ and CH₄.



Volatile organic compounds identified and quantified
from SWAS samples

compound	detection limit (ppt)
ethane	4
ethene	4
propane	6
propene	2
iso-butane	1
n-butane	1
acetylene	1
trans-2-butene	2
but-1-ene	2
cis-2-butene	2
cyclopentane	2
iso-butene	2
iso-pentane	1
n-pentane	1
1,3-butadiene	2
trans-2-pentene	2
pent-1-ene	2
2,3-methylpentanes	2
n-hexane	2
isoprene	1
n-heptane	2
benzene	1
2,2,4-trimethylpentane	2
n-octane	2
toluene	1
ethylbenzene	2
m+p- xylenes	2
o-xylene	2

Table A1. Summary of VOC's measured from SWAS samples at York University.