

# The oxidation state of iron in Mid-Ocean Ridge basalt glasses by Raman spectroscopy

Charles Le Losq, Andrew J Berry, Mark A Kendrick, Daniel R. Neuville, Hugh St. C O'Neill

# ▶ To cite this version:

Charles Le Losq, Andrew J Berry, Mark A Kendrick, Daniel R. Neuville, Hugh St. C O'Neill. The oxidation state of iron in Mid-Ocean Ridge basalt glasses by Raman spectroscopy. The American Mineralogist, 2019, 104 (7), pp.1032-1042. 10.2138/am-2019-6887. hal-02989700

HAL Id: hal-02989700

https://hal.science/hal-02989700

Submitted on 12 Nov 2020

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## The oxidation state of iron in Mid-Ocean Ridge basalt glasses determined by Raman

2 spectroscopy

3

1

- 4 Charles Le Losq<sup>1</sup>, Andrew J. Berry<sup>1</sup>, Mark A. Kendrick<sup>1</sup>, Daniel R. Neuville<sup>2</sup>, Hugh St. C.
- 5 O'Neill<sup>1</sup>

6

- <sup>1</sup>Research School of Earth Sciences, Australian National University, Canberra, ACT 2601,
- 8 Australia.
- <sup>2</sup>Géomatériaux, Institut de Physique du Globe de Paris, CNRS, USPC, Paris 75005, France.

1011

#### Abstract

1213

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

30

31

32

Synthetic Mid-Ocean Ridge Basalt (MORB) glasses, for which Fe<sup>3+</sup>/Fe<sup>TOT</sup> had been determined previously by Mössbauer spectroscopy and found to vary from 0 to 1, were used to test methods for determining Fe<sup>3+</sup>/Fe<sup>TOT</sup> by Raman spectroscopy. Six numerical data reduction methods were tested, based on conventional approaches and supervised and unsupervised machine learning algorithms. For the set of glass standards, with fixed composition, the precision of all methods is  $\leq \pm 0.04$ . This suggests that Raman spectroscopy may be a readily available method for determining the oxidation state of Fe in natural volcanic glasses with good precision and high spatial resolution. Raman spectra were recorded for 42 natural MORB glasses from a wide range of locations. There is a strong correlation between the Raman spectra and composition, despite relatively limited variability, such that the methods calibrated using the glass standards are not directly applicable to the natural samples. This compositional effect can be corrected by using a compositional term when linking spectral variations to the glass Fe<sup>3+</sup>/Fe<sup>TOT</sup>. The resulting Fe<sup>3+</sup>/Fe<sup>TOT</sup> value determined by Raman spectroscopy was of  $0.090 \pm 0.067$  (n=42). This value agrees with the latest Fe K-edge XANES and wet-chemistry estimates of  $0.10 \pm 0.02$ . The larger uncertainty of the Raman determination reflects the sensitivity of Raman spectroscopy to small changes in glass composition and hence structure. This sensitivity allows Raman spectroscopy to be used to determine the major element composition of natural MORB glasses within 1 mol% through the use of a neural network. This suggests that Raman spectrometers may be used to determine the composition of samples in situ at difficult to access locations that are incompatible with X-ray spectrometry (e.g. Mid-Ocean Ridges or Mars).

#### 1. Introduction

Mid-Ocean Ridge Basalts (MORB), derived from partial melting of the upper mantle, are of critical importance for understanding the geochemistry of the mantle and the formation of the oceanic crust (e.g. Langmuir et al., 1992; Asimow et al., 2004; Gale et al., 2013; O'Neill et al., 2018). MORB glasses, formed by rapid cooling at the rim of pillow lavas enable the composition (Jenner and O'Neill, 2012; O'Neill and Jenner, 2012), including volatile content (Kendrick et al., 2013), and oxidation state (Christie et al., 1986; Bézos and Humler, 2005; Cottrell and Kelley, 2011, 2013; Berry et al., 2018; Zhang et al., 2018) of the melts to be determined. This, in turn, allows the intensive and extensive thermodynamic conditions of the mantle source to be calculated (e.g. Asimow et al., 2004). In particular, the iron oxidation state of Fe in MORB, expressed as Fe<sup>3+</sup>/Fe<sup>TOT</sup> with Fe<sup>TOT</sup> = Fe<sup>2+</sup> + Fe<sup>3+</sup>, is important because it affects estimations of temperature, mineral assemblages, and the speciation of volatile elements, at both the surface and magmatic source.

The latest average  $Fe^{3+}/Fe^{TOT}$  values of natural MORB glasses from global sources have been determined to be  $0.10 \pm 0.02$  (Berry et al., 2018) or  $0.14 \pm 0.01$  (Zhang et al., 2018) by Fe K-edge XANES spectroscopy, and  $0.11 \pm 0.02$  by wet-chemistry (corrected for plagioclase phenocrysts, Bézos and Humler, 2005). Wet chemistry is a destructive method that lacks spatial resolution and is unsuitable for inhomogeneous glasses or small samples such as melt inclusions (e.g. see Bézos and Humler, 2005). Fe K-edge XANES spectroscopy has excellent precision and micron spatial resolution in two dimensions, but requires standards that are compositionally matched and for which  $Fe^{3+}/Fe^{TOT}$  is determined by another technique, such as  $^{57}$ Fe Mössbauer spectroscopy (e.g. Berry et al., 2008). There are also questions concerning possible photo-oxidation during analysis of hydrous glasses (e.g. Cottrell et al., in press). A considerable drawback is that it also requires access to a synchrotron light source.

Raman spectroscopy is an alternative technique for determining Fe<sup>3+</sup>/Fe<sup>TOT</sup> that is easily accessible for most investigators, is non-destructive, has micron-scale spatial resolution, requires minimal sample preparation, is easy to perform, and spectra can be acquired within minutes. Previous studies have shown how Raman spectroscopy can be used for quantifying the concentration of H<sub>2</sub>O (Thomas, 2000; Zajacz et al., 2005; Behrens et al., 2006; Thomas et al., 2008; Mercier et al., 2009, 2010; Le Losq et al., 2012) and CO<sub>2</sub> (Morizet et al., 2013) in glasses, with applications to pumices and melt inclusions (Shea et al., 2014; Métrich et al.,

2016). The potential of Raman spectroscopy to determine Fe<sup>3+</sup>/Fe<sup>TOT</sup> in glasses has been demonstrated previously using various data treatment protocols (Magnien et al., 2004, 2006, 2008; Roskosz et al., 2008; Di Muro et al., 2009; Di Genova et al., 2016). The simplest method requires correlating changes in Fe<sup>3+</sup>/Fe<sup>TOT</sup> with changes in the intensity of the Raman spectra at given Raman shift (Magnien et al., 2006; Roskosz et al., 2008). A more complex method involves peak fitting the Raman signals assigned to stretching of tetrahedral SiO<sub>4</sub> and AlO<sub>4</sub> units in order to extract the Fe<sup>3+</sup>-O signal, which can be related to Fe<sup>3+</sup>/Fe<sup>TOT</sup> (Di Muro et al., 2009; Welsch et al., 2017). Recently, Di Genova et al. (2016) proposed another approach based on interpolation between two endmember spectra (*e.g.*, one from a glass with oxidized iron and one from a glass with the same composition but reduced iron). Those different studies focused on demonstrating the ability of Raman spectroscopy to quantify Fe<sup>3+</sup>/Fe<sup>TOT</sup> in glasses of known composition. To date, no systematic use of Raman spectroscopy has been attempted to tackle a problem such as the quantification of Fe<sup>3+</sup>/Fe<sup>TOT</sup> in MORB glasses.

The existing methods for quantifying Fe<sup>3+</sup>/Fe<sup>TOT</sup> of glasses from Raman spectra rely on either simple treatments (e.g. the intensity of one or several peaks, mixing end-member spectra) or peak fitting. To our knowledge, machine learning algorithms, which remove subjectivity in the data reduction protocol, have not been used for determining Fe<sup>3+</sup>/Fe<sup>TOT</sup> of glasses. Here we compare existing data reduction methods (conventional methods), based on spectral intensity variations and mixing of spectra, with new supervised and unsupervised machine learning approaches. We avoided the peak fitting procedure (e.g. Di Muro et al., 2009) because it is complex to perform and equivocal of interpretation (Welsch et al., 2017), and thus may not be suited to a routine protocol. Conventional methods and supervised machine learning require the Fe<sup>3+</sup>/Fe<sup>TOT</sup> values of the glass standards to be known. Unsupervised machine learning methods, however, do not require prior knowledge of Fe<sup>3+</sup>/Fe<sup>TOT</sup> of the standards, such that they offer an independent way of determining Fe<sup>3+</sup>/Fe<sup>TOT</sup> for comparison with the results of other techniques. Those methods were assessed for a set of 13 synthetic glasses with a typical but simplified MORB composition and known Fe<sup>3+</sup>/Fe<sup>TOT</sup> (Berry et al., 2018). Following the proof of concept, the methods were used to determine Fe<sup>3+</sup>/Fe<sup>TOT</sup> of a representative set of 42 natural MORB glasses from the Atlantic, Indian and Pacific oceans, with known major and trace elements compositions (Melson et al., 2002; Jenner and O'Neill, 2012; Kendrick et al., 2013) and Fe K-edge XANES Fe<sup>3+</sup>/Fe<sup>TOT</sup> values (Berry et al., 2018).

#### 2. Material and Methods

# 106 2.1 Starting Glasses

The MORB standards were prepared from mixtures of reagent grade  $SiO_2$  (52.0 wt%),  $Al_2O_3$  (16.1 wt%),  $CaCO_3 = CaO$  (12.4 wt%),  $Fe_2O_3 = FeO$  (10.0 wt%), MgO (8.2 wt%) and  $TiO_2$  (1.3 wt%) that were equilibrated at 1400 °C and values of  $log fO_2$  between 0 and -11 (-4.7 and 6.3 in log units relative to the quartz-fayalite-magnetite, QFM, buffer) for ~ 24 h before quenching in water. A sample was also prepared at  $log fO_2 = 4.8$  (QFM + 11.2) using a piston-cylinder apparatus. The  $Fe^{3+}/Fe^{TOT}$  ratio of each glass was determined by Mössbauer spectroscopy, and found to vary from ~ 0 to 1 (Table 1). For further details see Berry et al. (2018).

Samples of natural MORB glass were obtained from the Department of Mineral Sciences, Smithsonian Institution, as polished chips mounted in epoxy resin and are listed by MNNH catalogue numbers in Supplementary Table 1. The sample details and major element composition are given in Melson et al. (2002), their trace element composition in Jenner and O'Neill (2012), and their Fe<sup>3+</sup>/Fe<sup>TOT</sup> values determined by Fe K-edge XANES spectroscopy in Berry et al. (2018). From the set analysed by Berry et al. (2018), the Raman spectra of five glasses (NMNH No. 111235-85, 115083-41, 113828-5, 111241-1, 111237-67) were contaminated by contributions from crystals (see supplementary code) and were not considered during the data reduction. Five samples previously studied by Kendrick et al. (2013) from Juan de Fuca (Alv 2262-8 and Alv 2269-2), the East Pacific Rise Clipperton (CL DR01) and Mid-Atlantic Ridge MAPCO (CH98 DR08 and CH98 DR11) were also analysed.

## 2.2 Raman Spectra Acquisition

Raman spectra of glasses were recorded using a Renishaw InVia spectrometer, equipped with a Peltier-cooled detector, a 2400 l/mm grating and a confocal system. Samples were excited using a 532 nm laser line focused  $\sim 3~\mu m$  below the surface using a x100 Leica objective. The laser power on the sample was  $\sim 1.2~mW$ . The spatial resolution was  $< 1~\mu m$ , and the spectral resolution  $\sim 1.2~cm^{-1}$ . Five spectra were recorded from different points for each

sample. They are treated separately during the data reduction process. The acquisition time varied between 120 and 180 s. For water-bearing natural MORB samples, oxidation of Fe by the laser has been reported at high laser power (Di Genova et al., 2017). The combination of a laser power less than 5 mW (Di Genova et al., 2017) with a relatively short counting time of 120 s, and the analysis of five different spots, was used to prevent Fe oxidation during spectral acquisition. We checked this by recording Raman maps for six samples, by acquiring 120 spectra with an acquisition time of 1 s over an area of 10 µm by 12 µm. During the acquisition of these maps, the sample was continuously moved, such that the beam spent less than 1 s at a given location. The individual spectra were noisy, but their average produced a spectrum with a signal to noise ratio similar to that of a spectrum acquired in 120 s at a single point. No difference was observed between spectra obtained in these two ways, indicating that no variation of Fe<sup>3+</sup>/Fe<sup>TOT</sup> was induced the during acquisition.

#### 2.3 Data pre-processing

The spectra (Fig. 1) were pre-processed in Python using the Rampy library (Le Losq, 2018). The data were corrected for temperature and excitation line effects following Galeener and Sen (1978). We focus the data reduction methods on the 800-1300 cm<sup>-1</sup> region of the spectra, which contains signals from Si-O, Al-O and Fe<sup>3+</sup>-O stretching in the glass structure (Brawer and White, 1975, 1977; Virgo et al., 1980; Mysen et al., 1982; Virgo et al., 1982). This region also avoided signals due to nanolites (< 800 cm<sup>-1</sup>), which were observed in the spectra of some of the natural glasses (see supplementary materials). We chose to fit a linear baseline to subtract the background (Fig. 2A), with the aim of having only Si-O, Al-O and Fe<sup>3+</sup>-O stretching signals in the background-corrected spectra that will be used for Fe<sup>3+</sup>/Fe<sup>TOT</sup> determination. The low and high frequency anchors of the linear baseline were determined using a grid-search algorithm as those resulting in the lowest root mean square error (RMSE) between the Mössbauer Fe<sup>3+</sup>/Fe<sup>TOT</sup> values and those predicted by the *intensity* and *mixing* methods described in sections 2.4.1 and 2.4.2. This resulted in the subtraction of a linear baseline interpolated between the intensities at 850 and 1140 cm<sup>-1</sup> (Fig. 2A). The baseline corrected spectra were smoothed using a Whittaker function to maximize the signal to noise ratio (Eilers, 2003; see supplementary code for an example), and then the intensity normalised to vary between 0 and 1 (Fig 2B). The spectra resulting from this arbitrary baseline correction can not be used to infer the glass structure. However, the correction provides a simple method for isolating variations in the Raman signals related to changes in Fe oxidation state (Fig 2B). Furthermore, the arbitrary baseline correction was found to be beneficial because it avoids the introduction of random errors associated with variations in the real spectral background when the sample signal is low (e.g. near 1250 cm<sup>-1</sup>).

#### 2.4 Determining the oxidation state of iron by Raman spectroscopy

In this study, six different methods were evaluated to determine the oxidation state of Fe in the suite of MORB glass standards (Table 1) from the background subtracted 850-1140 cm<sup>-1</sup> region of the Raman spectra (Fig. 2B). The idea is to relate, for a set of glass standards with fixed major element composition, changes in the Raman spectra to changes in Fe<sup>3+</sup>/Fe<sup>TOT</sup>. The six methods investigated are described below.

## 2.4.1 Intensity method

The intensity of the Raman spectra between 850 and 1140 cm<sup>-1</sup> varies systematically with Fe<sup>3+</sup>/Fe<sup>TOT</sup> in the glass standards (Figs. 1, 2B). In particular, the intensity at 930 cm<sup>-1</sup> varies strongly with Fe<sup>3+</sup>/Fe<sup>TOT</sup>. This feature has contributions from Fe<sup>3+</sup>-O (Virgo et al., 1982; Magnien et al., 2006; Di Muro et al., 2009), and thus should be ideal for determining Fe<sup>3+</sup>/Fe<sup>TOT</sup>. Two methods were tested to quantify the intensity at 930 cm<sup>-1</sup>: direct measurement at fixed frequency (the average of values between 929 and 931 cm<sup>-1</sup>) and by peak fitting the 850-1140 cm<sup>-1</sup> spectral envelop with arbitrary Gaussian components. Direct measurements of the intensity at 930 cm<sup>-1</sup> (hereafter abbreviated I<sub>930</sub>) provided the better precision and this approach was used.

#### 2.4.2 Mixing method

The *Mixing* method is based on the bilinear model that describes the matrix dataset  $D_{n,m}$ , of dimension n spectra times m features (i.e. Raman shifts), as:

$$199 D_{n,m} = F_{n,k} \cdot S_{k,m} + \varepsilon_{n,m} , (1)$$

where  $F_{n,k}$  is the matrix of component fractions,  $S_{k,m}$  the matrix of partial spectral components (endmember spectra), k the number of components and  $\varepsilon_{n,m}$  a noise term. In the present case, k = 2 (reduced and oxidised endmembers), as verified by a principal component analysis of the 13 standards, which revealed that two components account for more than 99.8% of the variance in the data. Using the notation  $S_{OX}$  and  $S_{RED}$  to designate the oxidised  $(Fe^{3+}/Fe^{TOT} = 1)$  and reduced  $(Fe^{3+}/Fe^{TOT} = 0)$  Raman spectral components, and  $F_{OX}$  as the fraction of  $S_{OX}$ , eq. (1) can be re-arrange as:

209 
$$D_{n,m} = F_{OX} \cdot S_{OX} + (1 - F_{OX}) \cdot S_{RED}$$
. (2)

We used least absolute regression (LAD) to determine  $F_{\rm OX}$ , because LAD is more robust than least squares with respect to outliers or non-Gaussian distributions (Tarantola, 2005). The optimised  $F_{\rm OX}$  values can then be related to the glass Fe<sup>3+</sup>/Fe<sup>TOT</sup> values (Di Genova et al., 2016).

2.4.3 Alternative Least Square Multivariate Curve Resolution (ALS MCR)

Solving eq. (1) usually requires either  $F_{n,k}$  or  $S_{k,m}$ . For example,  $F_{n,k}$  are obtained from  $S_{k,m}$  in the *Mixing* method (sec. 2.4.2). However, several techniques allow both  $F_{n,k}$  and  $S_{k,m}$  to be estimated from  $D_{n,m}$ , as for example independent component analysis (e.g. Hyvärinen et al., 2001), non-negative matrix factorisation (e.g. Lin, 2007), and iterative optimisation (e.g. Zakaznova-Herzog et al., 2007). For the present dataset of spectra, several conditions need to be satisfied: (i)  $F_{n,k} \in [0,1]$ ; (ii)  $F_{n,1} = 1 - F_{n,2}$ ; and (iii)  $S_{k,m} \in \mathbb{R}^+$ . Of the available methods, self-modelling curve resolution (Jiang et al., 2004; de Juan and Tauler, 2006), also known as multivariate curve resolution, can help solve the present problem. As they do not require prior knowledge of neither  $F_{n,k}$  nor  $S_{k,m}$ , those methods belong to the class of unsupervised machine learning algorithms.

In this study, the Alternative Least Square Multivariate Curve Resolution (ALS MCR) method was used to iteratively optimise  $F_{n,k}$  and  $S_{k,m}$ . The PyMCR python library was used, starting the algorithm with estimations of  $S_{k,m}$  obtained from mean spectra from our spectral dataset. The algorithm was allowed to perform 50 iterations. After convergence, usually achieved in only a few iterations, optimised  $F_{n,k}$  and  $S_{k,m}$  matrices are available for the investigated dataset. The spectral endmembers stored in the optimised  $S_{k,m}$  matrix (i.e. optimised  $F_{OX}$  and  $F_{RED}$ ) can then be used with the *Mixing* method for new samples.

236

234

235

- 237 Convergence of the ALS MCR algorithm is inherently dependent on the starting conditions
- 238 (e.g. Valderrama et al., 2016). The effects of the range of  $Fe^{3+}/Fe^{TOT}$  values included in  $D_{n,m}$ ,
- 239 and the starting  $S_{k,m}$  components, were tested using iterative protocols. The  $\mathrm{Fe^{3+}/Fe^{TOT}}$
- dataset range can be represented by two variables: (i)  $\Delta \operatorname{Fe}^{3+}/\operatorname{Fe}^{\mathrm{TOT}}$  of  $D_{n,m}$ , which represents
- 241 the difference of Fe<sup>3+</sup>/Fe<sup>TOT</sup> between the most reduced and the most oxidized samples in the
- dataset; and (ii) mean  $Fe^{3+}/Fe^{TOT}$  of  $D_{n,m}$ , which is the mean value of  $Fe^{3+}/Fe^{TOT}$  of the
- 243 dataset.
- Similarly, variations in the initial  $S_{k,m}$  components are represented using two parameters: (i)
- 245  $\Delta \text{ Fe}^{3+}/\text{Fe}^{\text{TOT}}$  of  $S_{k,m}$  represents the difference of  $\text{Fe}^{3+}/\text{Fe}^{\text{TOT}}$  between the two initial  $S_{k,m}$
- components; and (ii) mean  $Fe^{3+}/Fe^{TOT}$  of  $S_{k,m}$ , which is the average value of the  $Fe^{3+}/Fe^{TOT}$  of
- 247 the two initial  $S_{k,m}$  components.
- 248 To determine how the root-mean-square deviations between the estimated and nominal
- 249 Fe<sup>3+</sup>/Fe<sup>TOT</sup> values of the standard vary with  $\Delta$  Fe<sup>3+</sup>/Fe<sup>TOT</sup> and mean Fe<sup>3+</sup>/Fe<sup>TOT</sup> of  $D_{n.m}$ , and
- 250  $\Delta \text{ Fe}^{3+}/\text{Fe}^{\text{TOT}}$  and mean  $\text{Fe}^{3+}/\text{Fe}^{\text{TOT}}$  of  $S_{k,m}$ , these values were varied by iteration, such that
- different subsets of  $D_{n,m}$  and  $S_{k,m}$  were generated. These subsets were provided to the ALS
- 252 MCR algorithm to calculate optimised  $S_{k,m}$  and  $D_{n,m}$  matrices. These optimised matrices
- 253 were then used to determine  $Fe^{3+}/Fe^{TOT}$  for the entire  $D_{n,m}$  and  $S_{k,m}$  datasets.

254

255

#### 2.4.4 Neural Networks, Kernel Ridge and Support Vector regressions

- 257 The three other techniques that were investigated used the supervised machine learning
- 258 regression algorithms Neural Networks, Kernel Ridge, and Support Vector from the Scikit
- Learn library (Pedregosa et al., 2011). An interface for using these algorithms for Raman data
- 260 was implemented in the Rampy library (Le Losq, 2018) through the class *mlregressor* (see
- the Jupyter notebook in the supplementary materials as well as the *rampy.mlregressor* help).
- The machine learning algorithms require the data to be divided into two subsets: a *training*
- 263 subset to train the different algorithms, and a testing subset that are treated as unknowns to
- 264 evaluate the predictive error of the algorithms. The train-test split was performed by

randomly sorting the dataset according to their  $Fe^{3+}/Fe^{TOT}$  values (function *chemical\_splitting* from the rampy library). The testing data subset was ~ 38 % of the total dataset.

The Neural Network technique uses a network of activation units, which are Rectifier functions [y = max(0,x)] (Glorot et al., 2011) in the present study, to map the relationship between the Raman spectra and Fe<sup>3+</sup>/Fe<sup>TOT</sup> values of the glasses (see description in Bengio, 2009 and references therein). The activation units have adjustable parameters, called weights and bias, that are optimised by least square regression. This method makes no assumptions about the linearity of variations in the Raman spectra with Fe<sup>3+</sup>/Fe<sup>TOT</sup>. The network was optimised by testing different architectures to minimize the training and testing errors, and to keep those two values as close as possible to each other. A simple architecture with three activation units in a single hidden layer provided the most robust fits. Adding more activations units or layers did not decrease the error metrics of the network, and hence this simple architecture was used. The Limited-memory Broyden-Fletcher-Goldfarb-Shanno (lbfgs) solver was chosen, as it performs better than others for the present small dataset. Bagging, which consists of training multiple networks and returning the average of their outputs (Breiman and Breiman, 1996), was performed to avoid over-fitting and to promote the ability of the network to predict new values. A total of 100 networks were trained, and the results represent the average output of these 100 networks.

The *Kernel Ridge* and *Support Vector* techniques regress the data after their projection in a high-dimensionality space. This projection was done using a non-linear radial basis kernel function, such that the Raman intensity can non-linearly depend on  $Fe^{3+}/Fe^{TOT}$ . The difference between the *Kernel Ridge* and *Support Vector* regressions lies in the use of different loss functions: *Kernel Ridge* regression uses a penalized ( $I_2$  normalisation) residual of the sum of squares, whereas *Support Vector* regression uses a  $\varepsilon$ -insensitive loss function ( $\varepsilon$  is a deviation term in the loss function, i.e. the predictions are allowed to be as far from the calibration data as  $\varepsilon$ ). More information on these algorithms is available in Murphy (2012), Smola and Schölkopf (2004) and Vapnik (1999). The hyper-parameters of the *Kernel Ridge* and *Support Vector* algorithms were automatically tuned by performing a random 5-fold cross-validation on the training dataset.

A Jupyter notebook running under the Python language, together with all the spectra, are provided as supplementary materials to enable the results of this study, and the figures, to be reproduced.

## **3. Results**

## 3.1 Raman spectra of MORB glass standards

The Raman spectra of the MORB glass standards exhibit peaks and shoulders at ~ 505, 570, 660, 735, 804, 930 and 1005 cm<sup>-1</sup> (A to G markers in Fig. 1), with intensities that depend on Fe<sup>3+</sup>/Fe<sup>TOT</sup>. The intensity of the A, B, C and D Raman signals decreases with decreasing Fe<sup>3+</sup>/Fe<sup>TOT</sup> (Fig. 1, Table 1), whereas that of E and G increases (Figs. 1, 2B). The intensity of F relative to that of G decreases with decreasing Fe<sup>3+</sup>/Fe<sup>TOT</sup> (Fig. 2B).

The changes in the Raman spectra of the glasses following changes in Fe<sup>3+</sup>/Fe<sup>TOT</sup> reflect changes in (i) the Fe<sup>3+</sup> contribution to the Raman signals, and (ii) the overall glass structure as Fe<sup>3+</sup> and Fe<sup>2+</sup> have different roles. The signals in the 810-1300 cm<sup>-1</sup> region of the Raman spectra of MORB glasses can be assigned to symmetric and asymmetric stretching of  $Q^n$  $SiO_4$ -AlO<sub>4</sub> units, where n is the number of bridging oxygens (Brawer and White, 1975, 1977; Furukawa and White, 1980; Furukawa et al., 1981; Mysen et al., 1982; McMillan, 1984; Mysen, 1990; Le Losq and Neuville, 2013; Le Losq et al., 2014). The intensity at F is assigned to the combination of signals from Fe<sup>3+</sup>-O stretching in the glass network (Virgo et al., 1982; Wang et al., 1995; Magnien et al., 2004, 2006, 2008; Di Muro et al., 2009; Cochain et al., 2012) and Si-O stretching in  $Q^2$  units (McMillan, 1984; Mysen et al., 1982; Virgo et al., 1980). This assignment agrees with (i) the decrease in the relative intensity of F with Fe reduction (Figs. 1, 2B) and (ii) the presence of F as a shoulder in the most reduced spectra (Figs. 1, 2B). The peak near 1005 cm<sup>-1</sup> mainly comprises contributions from Si-O and Al-O stretching in  $Q^3$  units. This signal usually occurs near 1100 cm<sup>-1</sup> in Al-free silicate glasses (e.g. Mysen et al., 1982; McMillan, 1984) but shifts to lower frequencies in aluminosilicate glasses (Neuville and Mysen, 1996; Mysen et al., 2003; Le Losq and Neuville, 2013). This assignment is consistent with the composition of MORB glasses; with NBO/T values ranging

- from  $\sim 0.5$  to  $\sim 1.0$  (Mysen and Richet, 2005), they are expected to be enriched in  $Q^3$  units
- and to contain minor fractions of  $Q^2$  and  $Q^4$  (e.g. Maekawa et al., 1991).

333 3.2 Raman spectroscopy as a tool for determining  $Fe^{3+}/Fe^{TOT}$  of MORB glasses

334

335 3.2.1 The Intensity method

336

- 337 I<sub>930</sub> in the Raman spectra of the synthetic MORB glasses is linearly correlated with
- 338 Fe<sup>3+</sup>/Fe<sup>TOT</sup> (Fig. 3), with a correlation coefficient of 0.9973. It is thus possible to determine
- Fe<sup>3+</sup>/Fe<sup>TOT</sup> of a glass from the I<sub>930</sub> scaled Raman intensity using the equation:

340

341  $Fe^{3+}/Fe^{TOT} = 4.084(38) \times I_{930} - 2.779(29)$ . (3)

342

343 The root-mean-square deviation between the  $Fe^{3+}/Fe^{TOT}$  values of the standards and those calculated with eq. 3 is 0.02 (1 $\sigma$ ).

345

346 3.2.2 The Mixing method

347

- Following a protocol similar to that described by Di Genova et al. (2016), we used the
- average of the five spectra recorded for the most oxidized and reduced glasses ( $\log fO_2 = 4.8$
- and -11.0, Table 1) as endmembers. Then,  $F_{\rm OX}$  was adjusted by least absolute regression to
- obtain mixed spectra that matched the observed ones (Fig. 4A). The correlation between F<sub>OX</sub>
- and  $Fe^{3+}/Fe^{TOT}$  is shown in Figure 4B; the correlation coefficient is 0.9974.  $F_{OX}$  is linearly
- proportional to Fe<sup>3+</sup>/Fe<sup>TOT</sup>. This result differs from the finding of Di Genova et al. (2016),
- 354 who reported non-linear variations of  $F_{\rm OX}$  with  ${\rm Fe}^{3+}/{\rm Fe}^{{\rm TOT}}$  for rhyolite and basalt glasses.
- 355 This may be due to the fact that these authors did not use endmember spectra with Fe<sup>3+</sup>/Fe<sup>TOT</sup>
- of 0 and 1, but of intermediate values. In the present case,  $F_{OX}$  and  $Fe^{3+}/Fe^{TOT}$  are related by:

357

358 
$$Fe^{3+}/Fe^{TOT} = 1.02(1) \times F_{OX} - 0.003(4)$$
. (4)

359

360  $F_{\text{OX}}$  directly gives Fe<sup>3+</sup>/Fe<sup>TOT</sup> of MORB glasses to within 0.03 (1 $\sigma$ ).

361

362 3.2.3 The ALS MCR method

For a set of glasses with unknown but varying  $Fe^{3+}/Fe^{TOT}$  values, *ALS MCR* can determine the endmember spectra (i.e. spectra corresponding to  $Fe^{3+}/Fe^{TOT} = 0$  and 1), and hence,

366 Fe<sup>3+</sup>/Fe<sup>TOT</sup> for any MORB glass by linear combination fitting.

367

368 Figure 5 presents the results obtained from tests performed to evaluate the sensitivity of ALS 369 MCR to the starting conditions (see sec. 2.4.3). The best results were obtained when the dataset covered the widest possible range of  $Fe^{3+}/Fe^{TOT}$  values, i.e. when  $\Delta Fe^{3+}/Fe^{TOT}$  of 370  $D_{n.m} \rightarrow 1$  and mean Fe<sup>3+</sup>/Fe<sup>TOT</sup> of  $D_{n,m} \rightarrow \sim 0.4$  - 0.5 (Fig. 5A). Fe<sup>3+</sup>/Fe<sup>TOT</sup> root-mean-square 371 deviations < 0.06 were achieved using datasets with  $\Delta$  Fe<sup>3+</sup>/Fe<sup>TOT</sup> of D  $\geq$  0.75 and mean 372  $\text{Fe}^{3+}/\text{Fe}^{\text{TOT}}$  of D  $\in$  [0.35,0.55]. The choice of the initial  $S_{k,m}$  seems less critical, but still 373 affects the accuracy of the ALS MCR method (Fig. 5B). Fe<sup>3+</sup>/Fe<sup>TOT</sup> root-mean-square 374 deviations < 0.03 were obtained for initial  $S_{k,m}$  with mean  $\text{Fe}^{3+}/\text{Fe}^{\text{TOT}} \in [0.4,0.6]$  and  $\Delta$ 375

377

376  $\operatorname{Fe}^{3+}/\operatorname{Fe}^{\mathrm{TOT}} \in [0.1, 0.6].$ 

378 The *ALS MCR* method was tested further by optimising  $S_{k,m}$  using the full dataset  $D_{n,m}$ . 379 From Figure 5B, initial S components with  $\Delta \text{ Fe}^{3+}/\text{Fe}^{\text{TOT}}$  and mean  $\text{Fe}^{3+}/\text{Fe}^{\text{TOT}}$  of  $\sim 0.5$  and

380 0.4, respectively, should provide best results. Thus, the mean spectra at  $Fe^{3+}/Fe^{TOT} = 0.66$  and

381 0.25 were selected as initial  $S_{k,m}$  components. Selecting mean spectra with  $Fe^{3+}/Fe^{TOT} = 0$ 

and 1 does not significantly change the results, but the present choice allows the effects of

differences in the initial and optimised  $S_{k,m}$  components to be illustrated, as shown in Figure

6A. The optimised  $S_{k,m}$  spectra are clearly different from their initial values, demonstrating

the ability of ALS MCR to identify the true  $S_{k,m}$  endmembers. The optimised  $S_{k,m}$  produce

good fits to the observed spectra (Fig. 6B). The fraction of the oxidised endmember,  $C_{OX}$ , is

387 linearly related to the  $Fe^{3+}/Fe^{TOT}$  of the glass by (Fig. 6C):

388

383

384

385

386

389 
$$Fe^{3+}/Fe^{TOT} = 1.07(1) \times C_{OX} - 0.035(5)$$
. (5)

390

Contrary to  $F_{\rm OX}$ ,  $C_{\rm OX}$  is not directly equal to  ${\rm Fe^{3+}/Fe^{TOT}}$ . This is because of small differences between the optimised  $S_{k,m}$  endmembers and the mean Raman spectra at  ${\rm Fe^{3+}/Fe^{TOT}} = 0$  and 1 (residuals shown in Fig. 6A). These differences introduce a bias, such that using  $C_{\rm OX}$  as a direct estimate of  ${\rm Fe^{3+}/Fe^{TOT}}$  leads to slightly (~ 0.02) under- and over-estimations of Fe<sup>3+</sup>/Fe<sup>TOT</sup>, depending on the glass  ${\rm Fe^{3+}/Fe^{TOT}}$ . Because of that, the root-mean-square

deviation between the Raman-determined and standard Fe<sup>3+</sup>/Fe<sup>TOT</sup> values is  $\pm$  0.04 when assuming  $F_{\rm OX} = C_{\rm OX}$ . Slightly better results were obtained using eq. 5, which allows Fe<sup>3+</sup>/Fe<sup>TOT</sup> of the glasses to be determined within  $\pm$  0.03 (Table 1).

## 3.2.4 Neural Networks, Kernel Ridge and Support Vector regression methods

The *Neural Network*, *Kernel Ridge*, and *Support Vector* methods performed very well on both the training and testing datasets (Fig. 7), with root-mean-square deviations between the measured and predicted  $Fe^{3+}/Fe^{TOT}$  values of ~ 0.01-0.03 (Table 1). For all methods, the root-mean-square deviations for the training dataset were slightly lower than that for the testing dataset, indicating that machine-learning algorithms tend to slightly over-fit the training dataset. Over-fitting is not desirable because it indicates that the *generalisation* ability of the algorithms (i.e. their ability to predict values for new samples) may not be optimal. However, in the present case, the difference between the training and testing standard deviations is small ( $\leq 0.02$ ), and the over-fitting is considered to be negligible. Therefore, these algorithms can be used to predict  $Fe^{3+}/Fe^{TOT}$  of MORB glasses with an error  $\leq \pm 0.03$  ( $1\sigma$ ).

#### 3.2.5 Is there a better method?

The root-mean-square deviations between the  $Fe^{3+}/Fe^{TOT}$  values determined by Mössbauer and Raman spectroscopy are < 0.04 for all six methods. The *Intensity* and *Mixing* methods are as accurate and precise as those using machine learning (*ALS MCR*, *Neural Network*, *Kernel Ridge* and *Support Vector*; Table 1).

The choice of method depends on the aims of the study and the dataset. If a single data reduction method was to be chosen, the simplicity of the *Intensity* and *Mixing* methods makes these appealing. In the case the  $Fe^{3+}/Fe^{TOT}$  of the standards are unknown, the *ALS MCR* method may allow  $S_{k,m}$  components to be extracted and the  $Fe^{3+}/Fe^{TOT}$  to be determined, if the dataset covers a large range of  $Fe^{3+}/Fe^{TOT}$  values (Fig. 5). The *Intensity*, *Mixing* and *ALS MCR* methods all rely on linear variations between Raman signals and  $Fe^{3+}/Fe^{TOT}$  of the glasses. In contrast, the *Neural Network*, *Kernel Ridge*, and *Support Vector* methods do not assume linear variations and do not require the mathematical form of the variations to be known.

Ultimately, we recommend the use of multiple data reduction methods, as undertaken here, to test the consistency of results. This is desirable because each data reduction protocol may be differently sensitive to how differences in composition affect the Raman spectra (Fig. 2B). Therefore, following a Bayesian approach, the average of the results from all the methods should be more robust than any single estimate (e.g. Perrone, 1993). In the present case, such an approach is easy to implement because all the methods presented in this study are simple to setup and cheap in terms of computing resources. For the present dataset, averaging the results of the six models to obtain an estimate of the Fe<sup>3+</sup>/Fe<sup>TOT</sup> from the Raman spectra of the glasses resulted in a root-mean-square deviation of 0.02 (1σ).

## 3.2.6 Application to natural MORB glasses

The baseline subtracted and normalised Raman spectra of natural MORB glasses are shown in Figure 8A (see supplementary Jupyter Notebook for full spectra). While their spectra are similar to that of the glass standard with  $Fe^{3+}/Fe^{TOT} = 0.106$ , non-negligible differences are apparent (8A).  $I_{930}$  varies between 0.64 and 0.76, and is correlated with the concentration of MgO and CaO in the glass (Pearson correlation coefficient = 0.76, Fig. 8B). For the glass standards, a difference of ~ 0.2 in  $I_{930}$  corresponds to a difference in  $Fe^{3+}/Fe^{TOT}$  of ~ 0.2 (Fig. 3). For these spectra, the methods described give an average  $Fe^{3+}/Fe^{TOT}$  of 0.16 with a large standard deviation of 0.12.

It is possible to refine this estimate by including a compositional term in the expressions relating Raman features to  $Fe^{3+}/Fe^{TOT}$ . We focused on the *Intensity method* and expressed I<sub>930</sub> as:

455 
$$I_{930} = (K0 + K1 \times Fe^{3+}/Fe^{TOT}) + K2 \times X,$$
 (6)

where X is a parameter reflecting the chemistry of the samples, and K0, K1 and K2 constants. X could be chosen as either [MgO+CaO] or the number of non-bridging oxygen per tetrahedral units (NBO/T) in the glass. Increasing [MgO + CaO] favours the formation of non-bridging oxygens and thus depolymerised  $Q^2$  units in basaltic glasses, which give signals near 950 cm<sup>-1</sup> (e.g. Mysen et al., 1982). This is consistent with the positive trend observed between  $I_{930}$  and [MgO + CaO] (Fig. 8B). However, while NBO/T parameterises the general effect of variations in the fractions of network formers (e.g. Si, Al) and network modifiers (e.g. Na, K, Ca, Mg) on the glass structure, it does not consider the effect of the ionic properties of network modifiers on the distribution of  $Q^n$  units, which contribute to the Raman intensity between 850 and 1140 cm<sup>-1</sup>. For example, at a constant NBO/T of 0.5, the fractions of  $Q^4$  and  $Q^2$  increase at the expense of that of  $Q^3$  in alkali silicate glasses as the ionic field strength ( $Z/r^2$ , where Z is the electric charge and r the ionic radius) of the alkali metal cation increases (Maekawa et al., 1991). The ionic field strength of metal cations also influences many other structural properties of silicate glasses and melts, including the fraction of highly-coordinated Al, excess NBO, and Si-Al disorder (see Le Losq et al., 2019 for a review). As a result, to capture changes in the Raman spectra due to variations in the sample chemistry, we used the mean ionic field strength (IFS) of network modifiers (M), IFS(M), as the X parameter in eq. (6):

476 
$$IFS(M) = 2x_{Na_2O} \times IFS(Na^+) + 2x_{K_2O} \times IFS(K^+) + x_{CaO} \times IFS(Ca^{2+}) + x_{MgO} \times IFS(Ca^{2+}) + x_{MgO}$$

 $IFS(Mg^{2+}) + x_{FeO} \times IFS(Fe^{2+}),$  (7)

where  $x_{M_{2/2}^{Z+}O}$  are the mol fractions of the oxide components  $M_{2/z}^{Z+}O$ , and IFS is the ionic field strength of the cation  $M^{Z+}$ , calculated as  $Z/r^2$ . The r values were taken from Shannon (1976), with coordination numbers (CN) of 6 for all M cations. For simplicity, we do not consider variations in CN although they will vary with glass composition (Le Losq et al., 2019 and references therein), but probably this effect is negligible due to limited range of compositional variability of MORB. We also consider FeO as equal to total Fe because the Fe<sup>3+</sup>/Fe<sup>TOT</sup> ratio of natural MORB is always low (~0.1) and constant (e.g. Berry et al., 2018; Zhang et al., 2018), such that any influence of Fe on the glass structure will come from variations in  $x_{EeO}$ .

The correlation between  $I_{930}$  and IFS(M) is linear for natural MORB glasses (Fig. 9). The ordinate at the origin of this trend corresponds to  $K0 + K1 \times Fe^{3+}/Fe^{TOT}$ , and its slope to K2. K1 is directly given by the linear trend between  $Fe^{3+}/Fe^{TOT}$  and  $I_{930}$  (Fig. 3), and is equal to 0.2435(23), while K2 equals 0.00624(29). It then is trivial to determine K0 as 0.111(27). Using these parameters, it is possible to plot iso-redox curves of IFS(M) versus  $I_{930}$ , as shown in Fig. 9. A visual inspection indicates that the natural samples have a mean  $Fe^{3+}/Fe^{TOT}$  value

~ 0.1, although there is significant scatter. Manipulating eq. (7) to extract Fe<sup>3+</sup>/Fe<sup>TOT</sup> values for natural MORB from K0, K1, K2 and I<sub>930</sub> yields a mean Fe<sup>3+</sup>/Fe<sup>TOT</sup> of 0.090(67).

## 4. Discussion

Both conventional methods (*Intensity*, *Mixing*) and machine learning algorithms (*ALS MCR*, *Kernel Ridge*, *Support Vector* and *Neural Network*) allow Fe<sup>3+</sup>/Fe<sup>TOT</sup> to be determined from the Raman spectra of glasses, with fixed major element composition, with uncertainties < 0.04 (Table 1). The combination of all six methods gives a precision of 0.02. The *Intensity* and *Mixing* methods are simple and provide accurate results. The machine learning methods performed well despite being trained with a limited set of samples. The *ALS MCR* method may be useful if the Fe<sup>3+</sup>/Fe<sup>TOT</sup> values of the glass standards are unknown, or if endmember spectra are not available. *Kernel Ridge*, *Support Vector* and *Neural Network* regression algorithms relate Fe<sup>3+</sup>/Fe<sup>TOT</sup> of the glasses to variations in their Raman spectra without any assumptions about the form of the variations. Pooling the results from multiple data reduction protocols is recommended for maximizing the robustness of Fe<sup>3+</sup>/Fe<sup>TOT</sup> determinations for glasses with fixed composition.

The determination of  $Fe^{3+}/Fe^{TOT}$  in natural MORB glasses requires a correction for the effect of composition on the Raman spectra (Figs. 8B, 9, eq. 7). The corrected mean value of  $Fe^{3+}/Fe^{TOT} = 0.090(67)$  is in agreement with the latest XANES and wet chemistry measurements (Bézos and Humler, 2005; Berry et al., 2018; Zhang et al., 2018). In particular, this estimate is in close agreement with the XANES estimate of 0.10(1) reported by Berry et al. (2018) for the same set of samples, which suggests an average  $fO_2$  for MORB of 0.1 above the quart-fayalite-magnetite redox buffer.

Raman spectroscopy can thus provide reasonable estimates of Fe<sup>3+</sup>/Fe<sup>TOT</sup> in glasses, as long as the effect of glass chemistry is considered. However, the present results do not achieve the precision of Fe K-edge XANES, Mössbauer spectroscopy or wet chemistry for natural samples with variable chemical composition. While eq. (6) is valid for MORB glasses, it is probably not suitable for determining Fe<sup>3+</sup>/Fe<sup>TOT</sup> in other compositions. However, with a set of appropriate standards, Raman spectroscopy could be used to quantify Fe<sup>3+</sup>/Fe<sup>TOT</sup> in any composition through the use of a chemical correction similar to that of eq. (6).

#### 5. Implications

530

531

532

533

534

535

536

537

538

539

540

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

529

Machine learning techniques do not seem to be advantageous relative to conventional approaches for quantifying Fe<sup>3+</sup>/Fe<sup>TOT</sup> in glasses with fixed standard composition by Raman spectroscopy. However, their ease of implementation and flexibility (the problem can be linear or not) make them preferable to other user-defined techniques when the functional form of the problem is unknown. In particular, the sensitivity of Raman spectra to glass structure can be used to determine glass composition. Di Genova et al. (2015; 2016) proposed use of the mixing method to determine the composition of natural glasses from their Raman spectra. This required a post-analysis step in the data treatment as the mixing ratio of endmember spectra varied non-linearly with glass composition. In the present case, we trained a neural network to directly link the corrected 850-1140 cm<sup>-1</sup> Raman signals (Fig. 8A) to the measured concentrations of major elements in the natural MORB glasses (supplementary materials), without any additional data manipulation. The results from one of the trained neural networks are shown in Figure 10. The network was able to predict the chemistry of MORB glasses with maximum errors of ~ 1 mol%. This result suggests that Raman spectroscopy may be developed as a chemical probe. It also demonstrates the usefulness of neural networks for such calculations, as the algorithm directly provides the glass composition without intermediate data analysis steps, as required by the method of Di Genova et al. (2015; 2016). The approach could allow Raman spectroscopy to be used in situ to analyse erupting basalts forming pillow lavas with glassy rims at ocean ridges, using submersibles equipped with Raman spectrometers already developed for deep sea water analysis (e.g. Brewer et al., 2004; White et al., 2005; Du et al., 2015), or for using Raman spectrometers as chemical probes during missions on planets or moons with dense atmospheres. The fact that all data processing performed in this study uses Python, a programming language that can be easily used in embedded systems would facilitate uptake. The present approach should be easy to implement in any system operating a portable Raman spectrometer.

557

558

## Acknowledgement

559560

561

562

The Department of Mineral Sciences, Smithsonian Institution, of thanked for providing the samples of MORB glass. H.O.N thanks the Australian Research Council for the award of a Laureate Fellowship (FL130100066). C.L.L. thanks Guil Malmann for helpful discussions.

582

583

584

585

586

587

600 601

- Asimow, P.D., Dixon, J.E., Langmuir, C.H., 2004. A hydrous melting and fractionation model for mid-ocean ridge basalts: Application to the Mid-Atlantic Ridge near the Azores. Geochem. Geophys. Geosystems 5. https://doi.org/10.1029/2003GC000568
- Behrens, H., Roux, J., Neuville, D., Siemann, M., 2006. Quantification of dissolved H<sub>2</sub> O in silicate glasses using confocal microRaman spectroscopy. Chem. Geol. 229, 96–112.
- Bengio, Y., 2009. Learning Deep Architectures for AI. Found. Trends® Mach. Learn. 2, 1– 127. https://doi.org/10.1561/2200000006
- Berry, A.J., Danyushevsky, L.V., O'Neill, H.S.C., Newville, M., Sutton, S.R., 2008.
   Oxidation state of iron in komatiitic melt inclusions indicates hot Archaean mantle.
   Nature 455, 960–963. https://doi.org/10.1038/nature07377
- Berry, A.J., Stewart, G.A., O'Neill, H.S.C., Mallmann, G., Mosselmans, J.F.W., 2018. A reassessment of the oxidation state of iron in MORB glasses. Earth Planet. Sci. Lett. 483, 114–123. https://doi.org/10.1016/j.epsl.2017.11.032
- Bézos, A., Humler, E., 2005. The Fe<sup>3+</sup>/ΣFe ratios of MORB glasses and their implications for mantle melting. Geochim. Cosmochim. Acta 69, 711–725.
   https://doi.org/10.1016/j.gca.2004.07.026
  - Brawer, S.A., White, W.B., 1977. Raman spectroscopic investigation of the structure of silicate glasses (II). Soda-alkaline earth-alumina ternary and quaternary glasses. J. Non-Cryst. Solids 23, 261–278. https://doi.org/10.1016/0022-3093(77)90009-6
  - Brawer, S.A., White, W.B., 1975. Raman spectroscopic investigation of the structure of silicate glasses. I. The binary alkali silicates. J. Chem. Phys. 63, 2421–2432. https://doi.org/10.1063/1.431671
- Breiman, L., Breiman, L., 1996. Bagging Predictors, in: Machine Learning. pp. 123–140.
- Brewer, P.G., Malby, G., Pasteris, J.D., White, S.N., Peltzer, E.T., Wopenka, B., Freeman, J.,
  Brown, M.O., 2004. Development of a laser Raman spectrometer for deep-ocean
  science. Deep Sea Res. Part Oceanogr. Res. Pap. 51, 739–753.
  https://doi.org/10.1016/j.dsr.2003.11.005
- Christie, D.M., Carmichael, I.S.E., Langmuir, C.H., 1986. Oxidation states of mid-ocean
   ridge basalt glasses. Earth Planet. Sci. Lett. 79, 397–411.
   https://doi.org/10.1016/0012-821X(86)90195-0
- Cochain, B., Neuville, D.R., Henderson, G.S., McCammon, C.A., Pinet, O., Richet, P., 2012.
   Effects of the iron content and redox state on the structure of sodium borosilicate
   glasses: A Raman, Mössbauer and boron K-Edge XANES spectroscopy study. J. Am.
   Ceram. Soc. 95, 962–971.
  - Cottrell, E., Kelley, K.A., 2013. Redox heterogeneity in mid-ocean ridge basalts as a function of mantle source. Science 340, 1314–1317. https://doi.org/10.1126/science.1233299
- 602 Cottrell, E., Kelley, K.A., 2011. The oxidation state of Fe in MORB glasses and the oxygen 603 fugacity of the upper mantle. Earth Planet. Sci. Lett. 305, 270–282. 604 https://doi.org/10.1016/j.epsl.2011.03.014
- Cottrell, E., Lanzirotti, A., Mysen, B.O., Birner, S., Kelley, K.A., Botcharnikov, R.E., Davis,
   F.A., Newville, M., in press. A Mössbauer-based XANES calibration for hydrous
   basalt glasses reveals radiation-induced oxidation of Fe. Am. Mineral.
   https://doi.org/10.2138/am-2018-6268
- de Juan, A., Tauler, R., 2006. Multivariate Curve Resolution (MCR) from 2000: Progress in
  Concepts and Applications. Crit. Rev. Anal. Chem. 36, 163–176.
  https://doi.org/10.1080/10408340600970005

- Di Genova, D., Hess, K.-U., Chevrel, M.O., Dingwell, D.B., 2016. Models for the estimation of Fe<sup>3+</sup>/Fe<sup>tot</sup> ratio in terrestrial and extraterrestrial alkali- and iron-rich silicate glasses using Raman spectroscopy. Am. Mineral. 101, 943–952.
- Di Genova, Danilo, Kolzenburg, S., Vona, A., Chevrel, M.O., Hess, K.-U., Neuville, D.R., Ertel-Ingrisch, W., Romano, C., Dingwell, D.B., 2016. Raman spectra of Martian glass analogues: A tool to approximate their chemical composition. J. Geophys. Res. Planets 121, 2016JE005010. https://doi.org/10.1002/2016JE005010
- Di Genova, D., Morgavi, D., Hess, K.-U., Neuville, D.R., Borovkov, N., Perugini, D.,
   Dingwell, D.B., 2015. Approximate chemical analysis of volcanic glasses using
   Raman spectroscopy. J. Raman Spectrosc. 46, 1235–1244.
   https://doi.org/10.1002/jrs.4751
- Di Genova, D., Sicola, S., Romano, C., Vona, A., Fanara, S., Spina, L., 2017. Effect of iron and nanolites on Raman spectra of volcanic glasses: A reassessment of existing strategies to estimate the water content. Chem. Geol. 475, 76–86. https://doi.org/10.1016/j.chemgeo.2017.10.035
- Di Muro, A., Métrich, N., Mercier, M., Giordano, D., Massare, D., Montagnac, G., 2009.
   Micro-Raman determination of iron redox state in dry natural glasses: Application to peralkaline rhyolites and basalts. Chem. Geol. 259, 78–88.
   https://doi.org/10.1016/j.chemgeo.2008.08.013
- Du, Z., Li, Y., Chen, J., Guo, J., Zheng, R., 2015. Feasibility investigation on deep ocean compact autonomous Raman spectrometer developed for in-situ detection of acid radical ions. Chin. J. Oceanol. Limnol. 33, 545–550. https://doi.org/10.1007/s00343-015-4096-8
- 635 Eilers, P.H.C., 2003. A perfect smoother. Anal. Chem. 75, 3631–3636. 636 https://doi.org/10.1021/ac034173t
- Furukawa, T., Fox, K.E., White, W.B., 1981. Raman spectroscopic investigation of the structure of silicate glasses. III. Raman intensities and structural units in sodium silicate glasses. J. Chem. Phys. 75, 3226–3237. https://doi.org/10.1063/1.442472
- Furukawa, T., White, W.B., 1980. Vibrational spectra and glass structure. J. Non-Cryst.
   Solids 38, 87–92.
- Gale, A., Dalton, C.A., Langmuir, C.H., Su, Y., Schilling, J.-G., 2013. The mean composition
   of ocean ridge basalts. Geochem. Geophys. Geosystems 14, 489–518.
   https://doi.org/10.1029/2012GC004334
- Galeener, F.L., Sen, P.N., 1978. Theory of the first-order vibrational spectra of disordered
   solids. Phys. Rev. B 17, 1928–1933.
- Glorot, X., Bordes, A., Bengio, Y., 2011. Deep sparse rectifier neural networks, in:
  International Conference on Artificial Intelligence and Statistics. pp. 315–323.
- 649 Hyvärinen, A., Karhunen, J., Oja, E., 2001. Independent component analysis. John Wiley & Sons, Inc.
- Jenner, F.E., O'Neill, H.S.C., 2012. Analysis of 60 elements in 616 ocean floor basaltic glasses: TECHNICAL BRIEF. Geochem. Geophys. Geosystems 13, n/a-n/a. https://doi.org/10.1029/2011GC004009
- Jiang, J.-H., Liang, Y., Ozaki, Y., 2004. Principles and methodologies in self-modeling curve
   resolution. Chemom. Intell. Lab. Syst. 71, 1–12.
   https://doi.org/10.1016/j.chemolab.2003.07.002
- Kendrick, M.A., Arculus, R., Burnard, P., Honda, M., 2013. Quantifying brine assimilation
   by submarine magmas: Examples from the Galápagos Spreading Centre and Lau
   Basin. Geochim. Cosmochim. Acta 123, 150–165.
- https://doi.org/10.1016/j.gca.2013.09.012

- Langmuir, C.H., Klein, E.M., Plank, T., 1992. Petrological Systematics of Mid-Ocean Ridge
   Basalts: Constraints on Melt Generation Beneath Ocean Ridges, in: Mantle Flow and
   Melt Generation at Mid-Ocean Ridges, Geophysical Monograph. American
   Geophysical Union (AGU), pp. 183–280. https://doi.org/10.1029/GM071p0183
- Le Losq, C., 2018. Rampy: a Python library for processing spectroscopic (IR, Raman, XAS...) data. Zenodo. https://doi.org/10.5281/zenodo.1168730
- Le Losq, C., Cicconi, M.R., Greaves, G.N., Neuville, D.R., 2019. Silicate Glasses, in: Handbook of Glass. Springer.
- Le Losq, C., Neuville, D.R., 2013. Effect of the Na/K mixing on the structure and the rheology of tectosilicate silica-rich melts. Chem. Geol. 346, 57–71. http://dx.doi.org/10.1016/j.chemgeo.2012.09.009
- Le Losq, C., Neuville, D.R., Florian, P., Henderson, G.S., Massiot, D., 2014. The role of Al<sup>3+</sup> on rheology and structural changes of sodium silicate and aluminosilicate glasses and melts. Geochim. Cosmochim. Acta 126, 495–517. https://doi.org/10.1016/j.gca.2013.11.010
- Le Losq, C., Neuville, D.R., Moretti, R., Roux, J., 2012. Determination of water content in silicate glasses using Raman spectrometry: Implications for the study of explosive volcanism. Am. Mineral. 97, 779–790. https://doi.org/10.2138/am.2012.3831
- Lin, C.-J., 2007. Projected Gradient Methods for Nonnegative Matrix Factorization. Neural
   Comput. 19, 2756–2779. https://doi.org/10.1162/neco.2007.19.10.2756
- Maekawa, H., Maekawa, T., Kawamura, K., Yokokawa, T., 1991. The structural groups of
   alkali silicate glasses determined from <sup>29</sup>Si MAS-NMR. J. Non-Cryst. Solids 127, 53–
   https://doi.org/10.1016/0022-3093(91)90400-Z
- Magnien, V., Neuville, D., Cormier, L., Roux, J., Hazemann, J., Deligny, D., Pascarelli, S.,
   Vickridge, I., Pinet, O., Richet, P., 2008. Kinetics and mechanisms of iron redox
   reactions in silicate melts: The effects of temperature and alkali cations. Geochim.
   Cosmochim. Acta 72, 2157–2168.
- Magnien, V., Neuville, D.R., Cormier, L., Mysen, B.O., Briois, V., Belin, S., Pinet, O.,
   Richet, P., 2004. Kinetics of iron oxidation in silicate melts: a preliminary XANES study. Chem. Geol. 213, 253–263.
- Magnien, V., Neuville, D.R., Cormier, L., Roux, J., Hazemann, J.L., Pinet, O., Richet, P., 2006. Kinetics of iron redox reactions in silicate liquids: A high-temperature X-ray absorption and Raman spectroscopy study. J. Nucl. Mater. 352, 190–195.
  - McMillan, P.F., 1984. Structural studies of silicate glasses and melts Applications and limitations of Raman spectroscopy. Am. Mineral. 69, 622–644.

- Melson, W.G., O'Hearn, T., Jarosewich, E., 2002. A data brief on the Smithsonian Abyssal
   Volcanic Glass Data File. Geochem. Geophys. Geosystems 3, 1–11.
   https://doi.org/10.1029/2001GC000249
- Mercier, M., Di Muro, A., Giordano, D., Métrich, N., Lesne, P., Pichavant, M., Scaillet, B.,
   Clocchiatti, R., Montagnac, G., 2009. Influence of glass polymerisation and oxidation
   on micro-Raman water analysis in alumino-silicate glasses. Geochim. Cosmochim.
   Acta 73, 197–217. https://doi.org/10.1016/j.gca.2008.09.030
- Mercier, M., Muro, A.D., Métrich, N., Giordano, D., Belhadj, O., Mandeville, C.W., 2010.
   Spectroscopic analysis (FTIR, Raman) of water in mafic and intermediate glasses and glass inclusions. Geochim. Cosmochim. Acta 74, 5641–5656.
   https://doi.org/10.1016/j.gca.2010.06.020
- Métrich, N., Bertagnini, A., Garaebiti, E., Vergniolle, S., Bani, P., Beaumais, A., Neuville,
   D.R., 2016. Magma transfer and degassing budget: Application to the 2009–2010
   eruptive crisis of Mt Garet (Vanuatu arc). J. Volcanol. Geotherm. Res. 322, 48–62.
   https://doi.org/10.1016/j.jvolgeores.2015.06.003

- 711 Morizet, Y., Brooker, R.A., Iacono-Marziano, G., Kjarsgaard, B.A., 2013. Quantification of 712 dissolved CO<sub>2</sub> in silicate glasses using micro-Raman spectroscopy. Am. Mineral. 98, 713 1788–1802. https://doi.org/10.2138/am.2013.4516
- Murphy, K.P., 2012. Machine Learning: A Probabilistic Perspective. The MIT Press, Cambridge, Massachusetts.
- Mysen, B.O., 1990. Role of Al in depolymerized, peralkaline aluminosilicate melts in the systems Li<sub>2</sub> O-Al<sub>2</sub> O<sub>3</sub> -SiO<sub>2</sub> , Na<sub>2</sub> O-Al<sub>2</sub> O<sub>3</sub> -SiO<sub>2</sub> , and K<sub>2</sub> O-Al<sub>2</sub> O<sub>3</sub> -SiO<sub>2</sub> . Am. Mineral. 75, 120–134.
- Mysen, B.O., Finger, L.W., Virgo, D., Seifert, F.A., 1982. Curve-fitting of Raman spectra of silicate glasses. Am. Mineral. 67, 686–695.
- Mysen, B.O., Lucier, A., Cody, G.D., 2003. The structural behavior of Al<sup>3+</sup> in peralkaline melts and glasses in the system Na<sub>2</sub> O-Al<sub>2</sub> O<sub>3</sub> -SiO<sub>2</sub>. Am. Mineral. 88, 1668–1678.
- Mysen, B.O., Richet, P., 2005. Silicate glasses and melts Properties and structure,
  Developments in geochemistry. Elsevier B.V., Amsterdam.

729

730

731

732

737

738

- Neuville, D.R., Mysen, B.O., 1996. Role of aluminium in the silicate network: In situ, hightemperature study of glasses and melts on the join SiO<sub>2</sub>-NaAlO<sub>2</sub>. Geochim. Cosmochim. Acta 60, 1727–1737.
  - O'Neill, H.S.C., Berry, A.J., Mallmann, G., 2018. The oxidation state of iron in Mid-Ocean Ridge basaltic (MORB) glasses: implications for their petrogenesis and oxygen fugacities. Earth Planet. Sci. Lett. 504, 152–162.
  - O'Neill, H.S.C., Jenner, F.E., 2012. The global pattern of trace-element distributions in ocean floor basalts. Nature 491, 698–704. https://doi.org/10.1038/nature11678
- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,
   Prettenhofer, P., Weiss, R., Dubourg, V., Vanderplas, J., Passos, A., Cournapeau, D.,
   Brucker, M., Perrot, M., Duchesnay, E., 2011. Scikit-learn: machine learning in
   python. J. Mach. Learn. Res. 12, 2825–2830.
  - Perrone, M.P., 1993. Improving regression estimation: Averaging methods for variance reduction with extensions to general convex measure optimization. Brown University Providence, RI.
- Roskosz, M., Toplis, M.J., Neuville, D.R., Mysen, B.O., 2008. Amorphous materials:
   Properties, structure, and durability: Quantification of the kinetics of iron oxidation in silicate melts using Raman spectroscopy and assessment of the role of oxygen diffusion. Am. Mineral. 93, 1749–1759. https://doi.org/10.2138/am.2008.2861
- Shannon, R.D., 1976. Revised effective ionic radii and systematic studies of interatomic
   distances in halides and chalcogenides. Acta Crystallogr. A 32, 751–767.
   https://doi.org/10.1107/S0567739476001551
- Shea, T., Hellebrand, E., Gurioli, L., Tuffen, H., 2014. Conduit- to Localized-scale Degassing during Plinian Eruptions: Insights from Major Element and Volatile (Cl and H<sub>2</sub>O)
   Analyses within Vesuvius AD 79 Pumice. J. Petrol. 55, 315–344.
   https://doi.org/10.1093/petrology/egt069
- Smola, A. J., Schölkopf, B., 2004. A tutorial on support vector regression. Stat. Comput. 14, 199–222.
- Tarantola, A., 2005. Inverse problem theory and methods for model parameter estimation.

  Society for Industrial and Applied Mathematics, Philadelphia, PA.
- 755 Thomas, R., 2000. Determination of water contents of granite melt inclusions by confocal laser Raman microprobe spectroscopy. Am. Mineral. 85, 868–872.
- 757 Thomas, R., Metrich, N., Scaillet, B., Kamenetsky, V.S., Davidson, P., 2008. Determination 758 of water in Fe-rich basalt glasses with confocal micro-Raman spectroscopy. Z. Für 759 Geol. Wiss. 36, 31–37.

- Valderrama, L., Gonçalves, R.P., Março, P.H., Rutledge, D.N., Valderrama, P., 2016.
   Independent components analysis as a means to have initial estimates for multivariate curve resolution-alternating least squares. J. Adv. Res. 7, 795–802.
   https://doi.org/10.1016/j.jare.2015.12.001
- Vapnik, V. N., 1999. The Nature of Statistical Learning Theory, Second Edition. ed.
   Springer-Verlag, New York.
- Virgo, D., Mysen, B. O., Danckwerth, P., Seifert, F., 1982. Speciation of Fe<sup>3+</sup> in 1-atm Na<sub>2</sub>O-SiO<sub>2</sub>-Fe-O Melts. Carnegie Inst. Wash. Year b. 81, 349–353.
- Virgo, D., Mysen, B.O., Kushiro, I., 1980. Anionic constitution of 1-Atmosphere silicate
   melts: implications for the structure of igneous melts. Science 208, 1371–1373.
   https://doi.org/10.1126/science.208.4450.1371
- Wang, Z., Cooney, T.F., Sharma, S.K., 1995. In situ structural investigation of iron containing silicate liquids and glasses. Geochim. Cosmochim. Acta 59, 1571–1577.
   https://doi.org/10.1016/0016-7037(95)00063-6
- Welsch, A.-M., Knipping, J.L., Behrens, H., 2017. Fe-oxidation state in alkali-trisilicate
   glasses A Raman spectroscopic study. J. Non-Cryst. Solids 471, 28–38.
   https://doi.org/10.1016/j.jnoncrysol.2017.04.033
- White, S.N., Kirkwood, W., Sherman, A., Brown, M., Henthorn, R., Salamy, K., Walz, P.,
  Peltzer, E.T., Brewer, P.G., 2005. Development and deployment of a precision underwater positioning system for in situ laser Raman spectroscopy in the deep ocean.
  Deep Sea Res. Part Oceanogr. Res. Pap. 52, 2376–2389.
  https://doi.org/10.1016/j.dsr.2005.09.002
- Zajacz, Z., Halter, W., Malfait, W.J., Bachmann, O., Bodnar, R.J., Hirschmann, M.M.,
   Mandeville, C.W., Morizet, Y., Müntener, O., Ulmer, P., Webster, J.D., 2005. A
   composition-independent quantitative determination of the water content in silicate
   glasses and silicate melt inclusions by confocal Raman spectroscopy. Contrib.
   Mineral. Petrol. 150, 631–642. https://doi.org/10.1007/s00410-005-0040-9

788

789


794

- Zakaznova-Herzog, V.P., Malfait, W.J., Herzog, F., Halter, W.E., 2007. Quantitative Raman spectroscopy: Principles and application to potassium silicate glasses. J. Non-Cryst. Solids 353, 4015–4028. https://doi.org/10.1016/j.jnoncrysol.2007.06.033
- Zhang, H.L., Cottrell, E., Solheid, P.A., Kelley, K.A., Hirschmann, M.M., 2018.
   Determination of Fe<sup>3+</sup>/ΣFe of XANES basaltic glass standards by Mössbauer
   spectroscopy and its application to the oxidation state of iron in MORB. Chem. Geol.
   479, 166–175. https://doi.org/10.1016/j.chemgeo.2018.01.006


**Table 1:** Synthesis oxygen fugacity at 1400 °C, and relative to the quartz-fayalite-magnetite (QFM) buffer, of MORB glass standards (Berry et al., 2018), together with the  $Fe^{3+}/Fe^{TOT}$  values determined by Mössbauer spectroscopy ( $\pm$  0.01), and by Raman spectroscopy using the Intensity (Int.), Mixing (Mix.), ALS MCR (A.M.), Neural Networks (N.N.), Kernel Ridge (K.R.) and Support Vector (S.V.) techniques. Root-mean-squared deviations (RMSD,  $1\sigma$ ) of the different Raman methods are indicated at the bottom; \*calculated for the training data subset;  $^{\phi}$  calculated for the testing data subset.

log fO <sub>2</sub>	ΔQFM	Fe <sup>3+</sup> /Fe <sup>TOT</sup>						
		Mössbauer	Int.	Mix.	A.M.	N.N.	K.R.	S.V.
4.8	11.2	1.000	1.01	0.99	1.01	0.97	1.00	0.97
0.00	6.38	0.773	0.75	0.73	0.75	0.77	0.77	0.75
-1.00	5.40	0.661	0.66	0.63	0.65	0.66	0.66	0.66
-2.00	4.40	0.537	0.53	0.51	0.53	0.54	0.54	0.54
-3.07	3.32	0.414	0.43	0.42	0.43	0.43	0.42	0.44
-4.00	2.39	0.250	0.26	0.25	0.27	0.23	0.27	0.28
-5.00	1.39	0.167	0.16	0.15	0.16	0.14	0.16	0.17
-6.00	0.39	0.103	0.11	0.10	0.11	0.09	0.10	0.10
-7.00	-0.61	0.039	0.01	0.01	0.01	0.05	0.04	0.05
-8.00	-1.61	0.024	0.04	0.04	0.05	0.04	0.03	0.02
-9.00	-2.61	0.017	0.02	0.00	0.01	0.03	0.02	0.01
-10.00	-3.61	0.000	0.00	0.00	-0.01	0.02	0.01	-0.01
-11.00	-4.61	0.000	0.01	0.03	0.01	0.01	0.00	0.01
		RMSD:	0.02	0.03	0.03	0.01*	0.01*	0.02*
		KINISD.	0.02	0.03	0.03	$0.04^{\phi}$	$0.02^{\phi}$	$0.03^{\phi}$


**Figure 1**: Raman spectra of synthetic MORB basaltic glasses; the colors indicate Fe<sup>3+</sup>/Fe<sup>TOT</sup>. Each spectrum corresponds to the mean of five spectra acquired for each sample. The dashed lines labelled A-G mark the position of peaks and shoulders (see text).




**Figure 2**: A) Example of the treatment of the 800-1300 cm<sup>-1</sup> sections of the Raman spectra that was performed prior to any calculation. The linear cut-off baseline (red dotted line) joins the sample signals at 850 and 1140 cm<sup>-1</sup>. Any intensity below this baseline is removed from the data. B) Intensity from 850-1140 cm<sup>-1</sup> after baseline subtraction. This background subtracted region of the spectra was normalised between 0 and 1.



**Figure 3**: Normalised intensity at 930 cm<sup>-1</sup> in the Raman spectra of the glasses as a function of the oxidation state of Fe. The line is a linear fit to the data. If not visible, errors are smaller than the symbols.





**Figure 4:** A) Comparison of the mean spectrum at  $Fe^{3+}/Fe^{TOT} = 0.41$  (black line) and of fit (dotted red line) as a linear combination of the oxidised ( $S_{OX}$ ) and reduced ( $S_{RED}$ ) spectra (*Mixing* method); residuals between the data and fit are shown in the bottom panel. B) Fraction of the oxidised endmember spectrum,  $F_{OX}$ , as a function of the oxidation state of Fe in the glasses. The line is a linear fit to the data. If not visible, errors are smaller than the symbols.




Mössbauer  $Fe^{3+}/Fe^{TOT}$ 

**Figure 5**: Results of the tests performed with the *ALS MCR* algorithm, using variable subsets of (A)  $D_{n,m}$  and (B) initial  $S_{k,m}$  spectra. In (A), the root-mean-square deviations between the predicted and measured  $Fe^{3+}/Fe^{TOT}$  for the entire dataset, RMSD  $Fe^{3+}/Fe^{TOT}$ , is represented as a function of the mean and range of the  $Fe^{3+}/Fe^{TOT}$  values of the subset of data. In (B), it is represented as a function the mean and difference of  $Fe^{3+}/Fe^{TOT}$  of the two initial S spectra. Black points show where calculations were made; lines and colors were obtained by triangular interpolation.












Figure 6: Results of the ALS MCR algorithm using the entire  $D_{n,m}$  dataset, with initial (init.)  $S_{k,m}$  spectra at  $Fe^{3+}/Fe^{TOT} =$ 0.66 and 0.25. A) Init. and optimised (opt.) reduced oxidised  $(S_{\rm OX})$ and  $(S_{\text{RED}})$ endmember spectra; residuals between the optimised  $S_{OX}$  and  $S_{RED}$  components and the means of spectra recorded for samples with  $Fe^{3+}/Fe^{TOT} = 0$  and 1 are shown in the bottom panel. B) Comparison of the mean spectrum at  $Fe^{3+}/Fe^{TOT} = 0.41$  (black line) and its fit (dotted red line) obtained by mixing the  $S_{\rm OX}$  and  $S_{\rm RED}$  endmembers; residual shown in the bottom panel. C) The fraction of the oxidised end-member,  $C_{OX}$ , against the Fe3+/FeTOT values determined by Mössbauer spectroscopy for the MORB glass standards. The line is a linear fit to the data. If not visible, errors are smaller than the symbols.




**Figure 7**: Raman Fe<sup>3+</sup>/Fe<sup>TOT</sup> against Mössbauer Fe<sup>3+</sup>/Fe<sup>TOT</sup> values for the MORB glass standards. Raman values were obtained from the A) *Kernel Ridge*, B) *Support Vector*, and C) *Neural Network* algorithms. See Table 1 for root-mean-square deviations of each dataset. If not visible, errors are smaller than the symbols.




914



**Figure 9:**  $I_{930}$  as a function of the mean ionic field strength of modifier cations, IFS(M) for natural MORB glasses (open symbols) and MORB standards (solid symbols). Dotted lines represent the values of the model (eq. 7, see text) that links  $I_{930}$  to IFS(M) and  $Fe^{3+}/Fe^{TOT}$  in MORB glasses. The colors reflect the  $Fe^{3+}/Fe^{TOT}$  ratio (see colorbar).





928