

On the dispersion relation for compressible Navier-Stokes Equations

Saad Benjelloun, Jean-Michel Ghidaglia

▶ To cite this version:

Saad Benjelloun, Jean-Michel Ghidaglia. On the dispersion relation for compressible Navier-Stokes Equations. 2021. hal-02994555v2

HAL Id: hal-02994555 https://hal.science/hal-02994555v2

Preprint submitted on 12 May 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

On the dispersion relation for compressible Navier-Stokes Equations

Saad Benjelloun^{*} and Jean-Michel Ghidaglia^{*,§} ^{*} Mohammed VI Polytechnic University (UM6P), Modeling Simulation & Data Analytics, Benguerir, Morocco. [§]Université Paris-Saclay, ENS Paris-Saclay, CNRS, Centre Borelli, 91190, Gif-sur-Yvette, France.

May 12, 2021

1 Introduction

In this paper we revisit the classical sound dispersion and attenuation theory due to Stokes [5], 1845, and Kirchhoff [3], 1868, for the propagation of sound in non-ideal fluids. In particular we reformulate the analysis due to Fletcher [2], 1974, showing conditions for which the sound propagates at the isothermal speed of sound. Also we presents asymptotic developments making precise the physical conditions under which the different dispersion and attenuation formulas apply.

The more complex case of two-fluid flow is addressed by Benjelloun and Ghidaglia [1] to which the reader is referred. In [1], it is shown that analytical expressions for the speed of sound depend heavily on the chosen model. These sound speed expressions are compared with experimental values. The consequences for CFD models are also discussed.

2 Dispersion relations for a single conductive and viscous fluid

In Table 1 below we first give the main notations that are used in this paper.

Symbol	Quantity	Symbol	Quantity
ρ	Density	Т	Temperature
μ	Dynamic viscosity	λ	Thermal conductivity
С	Adiabatic speed of sound	c_T	Isothermal speed of sound
C_v	Isochoric heat capacity	C_p	Isobaric heat capacity
γ	Ratio C_p/C_v	Г	Grüneisen parameter
Pr	Prandtl number $\mu C_p / \lambda$	Kn	Knudsen number (13)

Table 1: Notations for a single fluid model (see (6) and (3)).

Considering the 1D compressible Navier-Stokes system for a divariant fluid:

$$\begin{cases} \frac{\partial\rho}{\partial t} + u\frac{\partial\rho}{\partial x} + \rho\frac{\partial u}{\partial x} = 0, \\ \frac{\partial u}{\partial t} + u\frac{\partial u}{\partial x} + \frac{1}{\rho}\frac{\partial p}{\partial x} = \frac{1}{\rho}\frac{\partial}{\partial x}\left(\frac{4\mu}{3}\frac{\partial u}{\partial x}\right), \\ \frac{\partial s}{\partial t} + u\frac{\partial s}{\partial x} = \frac{4\mu}{3\rho T}\left(\frac{\partial u}{\partial x}\right)^2 + \frac{1}{\rho T}\frac{\partial}{\partial x}\left(\lambda\frac{\partial T}{\partial x}\right), \end{cases}$$
(1)

where the dynamic viscosity μ , the thermal conductivity λ and the pressure p are known function of the density and the temperature. The linearization of (1) around a constant solution $\rho_0, u_0 = 0, T_0$ reads:

$$\begin{cases} \frac{\partial \rho}{\partial t} + \rho_0 \frac{\partial u}{\partial x} = 0, \\ \frac{\partial u}{\partial t} + \frac{1}{\rho_0} \frac{\partial p}{\partial x} = \frac{4\mu_0}{3\rho_0} \frac{\partial^2 u}{\partial x^2}, \\ \frac{\partial s}{\partial t} = \frac{\lambda_0}{\rho_0 T_0} \frac{\partial^2 T}{\partial x^2} = \frac{\lambda_0 \Gamma_0}{\rho_0^2} \frac{\partial^2 \rho}{\partial x^2} + \frac{\lambda_0}{\rho_0 C_{v,0}} \frac{\partial^2 s}{\partial x^2}, \\ p = c_0^2 \rho + \rho_0 \Gamma_0 T_0 s, \end{cases}$$
(2)

where (for the signification see Table 1):

$$\Gamma \equiv \frac{1}{\rho} \frac{\partial p}{\partial e} \Big|_{\rho}, \quad c^2 \equiv \frac{\partial p}{\partial \rho} \Big|_{s}, \quad C_v \equiv T \frac{\partial s}{\partial T} \Big|_{\rho} = \frac{\partial e}{\partial T} \Big|_{\rho}.$$
(3)

Remark 1 In general the linearization should be made around a constant solution ρ_0 , u_0 , T_0 , but using the Galilean invariance of Navier-Stokes equations we can assume, as we did, that $u_0 = 0$. Hence in the results found, all the speed of sound in this paper should be shifted by u_0 .

The second equality in the s evolution equation in (2) follows from the two thermodynamic identities (57) given in Appendix 4 [8].

The linear differential system (2) is of the form:

$$\frac{\partial W}{\partial t} + A \frac{\partial W}{\partial x} = B \frac{\partial^2 W}{\partial x^2},$$

where $W = {}^{t}(\rho, u, s)$ and A and B are the 3×3 matrices:

$$A = \begin{pmatrix} 0 & \rho_0 & 0 \\ \frac{c_0^2}{\rho_0} & 0 & \Gamma_0 T_0 \\ 0 & 0 & 0 \end{pmatrix}, \quad B = \begin{pmatrix} 0 & 0 & 0 \\ 0 & \frac{4\mu_0}{3\rho_0} & 0 \\ \frac{\lambda_0\Gamma_0}{\rho_0^2} & 0 & \frac{\lambda_0}{\rho_0 C_{\nu,0}} \end{pmatrix}.$$

We look for non-vanishing plane-wave solutions of the form:

$$W = W_0 \exp i(k x - \omega t) = W_0 \exp ik \left(x - \frac{\omega}{k}t\right), \tag{4}$$

with $k \in \mathbb{R}$, and $\omega = \omega_R + i\omega_I \in \mathbb{C}$. Hence ω_R/k represents the speed of propagation of the plane-wave and the dispersion relation corresponds to the vanishing of the characteristic polynomial of the 3×3 matrix:

$$-i\omega I + ikA + k^2B$$

The dispersion relation reads, dropping the 0 subscript, as:

$$\left(\frac{\omega}{k}\right)^{3} + \frac{ik}{\rho} \left(\frac{4\mu}{3} + \frac{\lambda}{C_{v}}\right) \left(\frac{\omega}{k}\right)^{2} - \left(c^{2} + \frac{4k^{2}\lambda\mu}{3\rho^{2}C_{v}}\right) \left(\frac{\omega}{k}\right) + \frac{ik\lambda}{\rho} \left(\frac{c^{2}}{C_{v}} - \Gamma^{2}T\right) = 0.$$
(5)

3 On the speed of sound in single fluid

Following L. Landau and E. Lifchitz [4] a sound wave is an oscillatory motion with small amplitude in a single compressible fluid. Then these Authors

derive the classical linear wave equation where the speed of sound is the usual thermodynamic coefficient which holds this name. Extending this definition to the mixture of two non miscible fluids leads us to consider waves in such a medium. According to Whitham [7], there is no single precise definition of what exactly constitutes a wave. Nevertheless this Author proposes to distinguish between hyperbolic waves, see Definition 1, and dispersive waves. The later being plane-waves where frequency ω is a defined real function of the wave number k and the function $\omega(k)$ is determined by the particular system under consideration. In this case, the speed of the wave is its phase speed, that is $\omega(k)/k$, see (4), and the waves are usually said "dispersive" if this phase speed is not a constant but varies with k.

Dispersion relation Considering the classical compressible Navier-Stokes equation in 1*D*, as written in (1), we have shown that small disturbances around a constant state of rest will propagates as the superposition of plane waves of the form 4 ($k \in \mathbb{R}, \omega \in \mathbb{C}$) provided ω and k satisfy equation (5), which is termed as the dispersion relation. Setting (the notations are given in Table 1):

$$a = \frac{2 k \mu}{3 \rho} \equiv a_1 k \quad \text{and} \quad c_T^2 \equiv \frac{\partial p}{\partial \rho} \Big|_T,$$
 (6)

where a is Stokes' attenuation as in Stokes [5], the dispersion relation (5) can be written as:

$$\left(\frac{\omega}{k}\right)^3 + 2ika_1\left(1 + \frac{3\gamma}{4Pr}\right)\left(\frac{\omega}{k}\right)^2 - \left(c^2 + \frac{3\gamma}{Pr}a_1^2k^2\right)\left(\frac{\omega}{k}\right) - i\frac{3c^2ka_1}{2Pr} = 0,$$
(7)

thanks also to the identity $c_T^2 = c^2 - \Gamma^2 C_v T = c^2 / \gamma$, see (56) in Section 4.

3.1 Euler's equation, the hyperbolic case

For $\mu = 0$ and $\lambda = 0$ (or $a_1 = 0$, $Pr = \infty$), we recover the speeds of propagation $\omega/k \in \{0, \pm c\}$ for the inviscid Euler equation, with c the adiabatic speed of sound for the fluid. This system is hyperbolic and non dispersive. Hyperbolicity can be defined as follows.

Considering a linear differential system of the form:

$$\frac{\partial W}{\partial t} + A \frac{\partial W}{\partial x} = 0, \qquad (8)$$

where A is a $N \times N$ constant matrix and N is the number of differential equations occurring in the model, we recall the following.

Definition 1 The model (8) is said to be hyperbolic if there exists a basis (r_1, \ldots, r_N) of \mathbb{R}^N made with eigenvectors of A:

$$A r_k = \lambda_k r_k, \quad k = 1, \dots, N, \qquad (9)$$

where $\lambda_k \in \mathbb{R}$ are the associated eigenvalues.

Dimensional analysis shows that the dimension of the λ_k is m/s *i.e.* they are velocities. Looking for non-vanishing plane-wave solutions, (4), leads to the simple dispersion relation:

$$\frac{\omega}{k} \in \{\lambda_1, \dots, \lambda_N\},\tag{10}$$

i.e. all these models are non dispersive equations since ω/k is constant.

3.2 Stokes' model: the non-conductive case

In the case of an non-conductive $(\lambda = 0, Pr = \infty)$ viscous flow $(\mu \neq 0)$, we recover Stokes' attenuation and dispersion relations as in Stokes [5]:

$$\left(\frac{\omega}{k}\right)^3 + \frac{4\,i\,k\,\mu}{3\,\rho} \left(\frac{\omega}{k}\right)^2 - c^2\,\left(\frac{\omega}{k}\right) = 0\,,\tag{11}$$

$$\Rightarrow \frac{\omega}{k} \in \left\{ 0, -i\frac{2\,k\,\mu}{3\rho} \pm \sqrt{c^2 - \frac{4\,k^2\mu^2}{9\,\rho^2}} \right\}. \tag{12}$$

Let us consider a plane wave (4). Here 1/k represents a characteristic length for the wave. In the context of continuum mechanics (by opposition with rarefied flows) in which the Navier-Stokes equations are valid, the Knudsen number, Kn, built with this characteristic length should be not greater than the critical Knudsen number $\text{Kn}_c = 10^{-2}$, that is:

$$K_n \equiv \frac{k\,\mu}{\rho\,c} \le \operatorname{Kn}_c = 10^{-2}\,. \tag{13}$$

Hence:

$$\sqrt{c^2 - \frac{4k^2\mu^2}{9\rho^2}} = c\sqrt{1 - \frac{4(K_n)^2}{9}} \approx c\left(1 - \frac{2(K_n)^2}{9}\right) \\
= c\left(1 - \frac{2k^2\mu^2}{9\rho^2c^2}\right) = c - \frac{2k^2\mu^2}{9\rho^2c}.$$
(14)

According to (4), the disturbances are linear combination of functions of the form:

$$W = W_0 \exp{-\frac{2k^2 \mu t}{3\rho}} \exp{ik (x \pm c(k) t)}, \qquad (15)$$

$$W = W_0 \exp{-\frac{2k^2 \mu t}{3\rho}} \exp{ikx}.$$
 (16)

The waves (15) are dispersive since their velocities $\pm c(k)$, where:

$$c(k) \equiv \sqrt{c^2 - \frac{4k^2\mu^2}{9\rho^2}} = \sqrt{c^2 - k^2 a_1^2} \approx c - \frac{2k^2\mu^2}{9\rho^2 c}, \qquad (17)$$

depends on k. Moreover the waves are exponentially damped with time (and propagation in space), with the characteristic Stokes attenuation a_1 .

Property	Air	Freon	Water	Honey	Mercury
$ ho~({ m Kg}/~m^3$)	1.225	1570	997	1400	13500
μ (Pa.s)	1.8110^{-5}	$2,610^{-4}$	8.910^{-4}	10	1.510^{-3}
c (m. s^{-1})	340	716	1480	2030	1450
$\lambda ~({\rm W/m~K})$	2.610^{-2}	10	0.6	0.5	8.3
$\frac{\mu}{\rho c}(m)$	4.310^{-7}	2.310^{-10}	610^{-10}	4.710^{-6}	7.610^{-11}

Table 2: Typical properties at standard conditions for a selection of materials.

Remark 2 For ideal gases or gases near the ideal state, the Knudsen number defined in (13) relates to the molecular free path Λ , as we have

$$K_n = \Lambda k \sim \frac{k\mu}{\rho c}.$$

This is due to the relation $\mu = \rho \Lambda \sqrt{\frac{k_b T}{2\pi m}}$, a consequence of the Maxwell-Boltzman distribution, with m the molecular weight of the gaz, and the relation $c = \sqrt{\frac{\gamma k_b T}{m}}$. Here we extend the definition (13) to all fluids. Expression (13) gives and evaluation of $k \times 4.3 \ 10^{-7}$ for air and $k \times 6 \ 10^{-10}$ for water at 25°C. For ultrasound at 20MHz, the order of magnitude for k is 10^{-2} to 10^{-3} for air and water at standard conditions and Kn is hence very small even for high frequency sounds. See Table 2 for an estimation of $\frac{\mu}{\rho c}$ in formula (13) for other materials.

3.3 The non viscous case

For $\mu = 0$ and $\lambda \neq 0$ the dispersion relation (5) reads:

$$\left(\frac{\omega}{k}\right)^3 + \frac{i\,k\,\lambda}{\rho\,C_v}\left(\frac{\omega}{k}\right)^2 - c^2\left(\frac{\omega}{k}\right) - \frac{i\,k\,\lambda\,c^2}{\gamma\,\rho\,C_v} = 0\,. \tag{18}$$

In Vekstein [6] this dispersion relation is given in the case of perfect gas. Introducing here a Knudsen number based on thermal diffusivity:

$$Kn_{th} \equiv \frac{k\,\lambda}{\rho\,C_p\,c}\,,\tag{19}$$

we can rewrite (18) as:

$$\left(\frac{\omega}{k}\right)^3 + i\gamma c \,Kn_{th} \left(\frac{\omega}{k}\right)^2 - c^2 \left(\frac{\omega}{k}\right) - i \,c^3 \,Kn_{th} = 0\,. \tag{20}$$

Here again, since we are in the context of fluid dynamics, the Knudsen number is small. For example (19) gives a value of $k \times 6.6 \, 10^{-8}$ for air and $k \times 9.6 \, 10^{-11}$ for water at 25°C. The techniques used in the Sections 3.4.1 and 3.4.2 lead immediately to the following asymptotics:

$$\frac{\omega_I^{\pm}}{k} = -\frac{(\gamma - 1) k \lambda}{2 \rho \gamma C_v} + \mathcal{O}\left(\frac{k^2 \lambda^2}{\rho^2 C_v^2 c}\right), \quad \frac{\omega_R^{\pm}}{k} = \pm c + \mathcal{O}\left(\frac{k^2 \lambda^2}{\rho^2 C_v^2 c}\right), \quad (21)$$

$$\frac{\omega_I^0}{k} = -\frac{k\,\lambda}{\rho\,\gamma\,C_v} + \mathcal{O}\left(\frac{k^2\,\lambda^2}{\rho^2\,C_v^2\,c}\right)\,,\quad \frac{\omega_R^0}{k} = \mathcal{O}\left(\frac{k^2\,\lambda^2}{\rho^2\,C_v^2\,c}\right)\,,\tag{22}$$

and (21) generalizes Vekstein [6] to the case of arbitrary divariant fluids. Hence, we see that in this case the speed of propagation, at order zero in $Kn_{th}.c$, is given by the adiabatic speed of sound c and that the attenuation is the same as the one predicted by Stokes-Kirchhoff theory [3], with vanishing viscosity:

$$\frac{(\gamma-1)\,k\,\lambda}{2\,\rho\,\gamma\,C_v} = \frac{(\gamma-1)\,k\,\lambda}{2\,\rho\,C_p} = \frac{(\gamma-1)c}{2}Kn_{th} = \frac{k\,\lambda}{2\,\rho\,C_p}(\frac{c^2}{c_T^2}-1).$$

Regarding the speed dispersion given by the expressions for ω_R/k , we notice that it is second order w.r.t. Kn_{th}.

3.4 On the general case

In this Section our goal is to study the dispersion relation (5) that we have rewritten (see (7)) as $P\left(\frac{\omega}{k}\right) = 0$, where (we refer to (6) and Table 1 for the notation):

$$P(X) \equiv X^3 + 2ika_1\left(1 + \frac{3\gamma}{4Pr}\right)X^2 - \left(c^2 + \frac{3\gamma}{Pr}a_1^2k^2\right)X - i\frac{3ka_1c^2}{2Pr}.$$
 (23)

Introducing the two second-degree polynomials Q and Q_T :

$$Q(X) \equiv X^{2} + 2 i k a_{1} X - c^{2}, \qquad (24)$$

$$Q_T(X) \equiv X^2 + 2\,i\,k\,a_1\,X - \frac{c^2}{\gamma}\,, \tag{25}$$

we see that (note that these two polynomials are independent of Pr):

$$P(X) = X Q(X) + i k a_1 \frac{3\gamma}{2 Pr} Q_T(X).$$
(26)

3.4.1 Asymptotic for large Prandtl number

When the Prandtl number Pr is infinite, that is the case of an non conductive $(\lambda = 0)$ viscous flow $(\mu \neq 0)$, we have P(X) = X Q(X) and we recover (11). Since the 3 roots of P in this case are distinct, one can see easily¹ that for large Prandtl number (*i.e.* for $\lambda \ll C_p \mu$), that is the case where viscous effects are much more preponderant w.r.t. thermal ones, the 3 roots of P depends smoothly on 1/Pr and can be expanded as:

$$X_{Pr}^{(\ell)} = X_0^{(\ell)} - i \, k \, a_1 \, \frac{3 \, \gamma}{2 \, Pr} \frac{Q_T(X_0^{(\ell)})}{Q(X_0^{(\ell)}) + X_0^{(\ell)} \, Q'(X_0^{(\ell)})} + \mathcal{O}\left(\frac{1}{Pr^2}\right) \,, \qquad (27)$$

where the $X_0^{(\ell)}$ are the 3 roots of XQ(X). According to (12), c(k) is defined in (17), these roots are:

$$X_0^{(-1)} = -ik a_1 - c(k), \quad X_0^{(0)} = 0, \quad X_0^{(+1)} = -ik a_1 + c(k), \quad (28)$$

and after some computations we deduce from (27) the following result.

 $^{^1\}mathrm{Using}$ the Implicit Function Theorem as we do hereafter in the proof of Proposition 3.

Proposition 1 For large Prandtl number, the three roots of P satisfy:

$$X_{Pr}^{(\mp)} = -ik \, a_1 \mp c(k) \mp \frac{3(\gamma - 1) \, k \, a_1 \, (k \, a_1 \pm ic(k))}{4 \, c(k)} \frac{1}{Pr} + \mathcal{O}\left(\frac{1}{Pr^2}\right) \,, \quad (29)$$

$$X_{Pr}^{(0)} = -i\frac{5\kappa a_1}{2Pr} + \mathcal{O}\left(\frac{1}{Pr^2}\right) . \quad (30)$$

3.4.2 Asymptotic for small Prandtl number

Let us now address the case where the Prandtl number is small (*i.e.* for $C_p \mu \ll \lambda$), that is the case where thermal effects are much more preponderant w.r.t. viscous ones.

At the limit Pr = 0, the dispersion relation $P\left(\frac{\omega}{k}\right) = 0$ reads $Q_T\left(\frac{\omega}{k}\right) = 0$ but Q_T has only two roots while P has three. We are going to prove that for $Pr \ll 1$ the two roots of P will be on curves starting from the two roots of Q_T (as in (27)) and the third one is large $\mathcal{O}\left(\frac{1}{Pr}\right)$, see Propositions 2 and 3. Indeed denoting by $\xi_{Pr}^{(\ell)}$, $\ell = -1$, 0 and 1, the three roots of P, and if $\xi_{Pr}^{(-1)}$ (resp. $\xi_{Pr}^{(+1)}$) is close to $\xi^{(-1)}$ (resp. $\xi^{(+1)}$) where $\xi^{(\ell)}$ are the roots of Q_T that is:

$$\xi^{(\ell)} \equiv -ik \, a_1 + \ell \, c_T(k) \,, \quad c_T(k) \equiv \sqrt{c_T^2 - k^2 \, a_1^2} \,, \quad \ell = \pm 1 \,, \tag{31}$$

we are going to prove the following result.

Proposition 2 We have the following asymptotic behavior:

$$\lim_{Pr \to 0} \xi_{Pr}^{(\mp)} = -ik \, a_1 \mp \, c_T(k) \,, \tag{32}$$

$$\xi_{Pr}^{(0)} \sim i \frac{3 k a_1 \gamma}{2 P r}, \ as \ Pr \to 0.$$
 (33)

This result follows readily from a simple observation.

Lemma 1 The three roots $\xi_{Pr}^{(\ell)}$ of P satisfy the identity:

$$\xi_{Pr}^{(-1)} \,\xi_{Pr}^{(0)} \,\xi_{Pr}^{(+1)} = -i \frac{3 \,k \,a_1 \,c^2}{2 \,Pr} \,. \tag{34}$$

This relation is obvious since according to (26), $P(0) = i k a_1 \frac{3\gamma}{2Pr} Q_T(0)$ and then Proposition 2 follows.

Here again, in the spirit of Proposition 1, we can refine Proposition 2 and prove the following result.

Proposition 3 For small Prandtl number, the three roots of P satisfy:

$$\xi_{Pr}^{(\mp)} = -ik \, a_1 \mp c_T(k) \pm \frac{(\gamma - 1) \, c^2 \, (k \, a_1 \mp i \, c_T(k))}{3 \, \gamma^2 \, k \, a_1 \, c_T(k)} Pr + \mathcal{O}(Pr^2) \,, \qquad (35)$$

$$\xi_{Pr}^{(0)} = i \frac{3 \, k \, a_1 \, \gamma}{2 \, Pr} + \mathcal{O}(Pr) \,. \tag{36}$$

Proof The $\xi_{Pr}^{(\ell)}$ are the solutions of P(X) = 0 or equivalently:

$$F(X, Pr) \equiv Pr X Q(X) + i \frac{3 k a_1 \gamma}{2} Q_T(X) = 0.$$
 (37)

The function F is smooth and $\frac{\partial F}{\partial X}(X,0) = i \frac{3ka_1\gamma}{2} Q'_T(X)$. For each $\ell = \pm 1$, $F(\xi^{(\ell)},0) = i \frac{3ka_1\gamma}{2} Q_T(\xi^{(\ell)}) = 0$ and since the roots $\xi^{(\ell)}$ of Q_T are simple: $\frac{\partial F}{\partial X}(\xi^{(\ell)},0) \neq 0$. Hence by the Implicit Function Theorem, for small Pr, there exists two smooth curves such that $F(\xi^{(\ell)}_{Pr},Pr) = 0$ and $\xi^{(\ell)}_0 = \xi^{(\ell)}$. Then (35) follows immediately from the first order Taylor expansion of F with respect to X and Pr at the point $(\xi^{(\ell)},0)$.

Concerning (36), we simply use (35) together with the identity (34).

3.4.3 Asymptotic for the speed of sound

The general dispersion relation (7) can be explicitly solved using Cardano formula since it is a third order polynomial equation in ω/k for fixed k. In general this dispersion relation has 3 solutions (ω, k) with $k \in \mathbb{R}$ and $\omega \in \mathbb{C}$. Writing $\omega = \omega_R + i \omega_I$, real and imaginary parts, we see that (4) reads:

$$W = W_0 \exp(\omega_I t) \exp ik \left(x - \frac{\omega_R}{k} t\right).$$
(38)

If we stick to the definition by Whitham [7] of dispersive waves, the phase speed of the wave is ω_R/k while ω_I corresponds to attenuation (for negative values) or amplification otherwise. For large or small values of the Prandtl number, Pr, according to Propositions 1 and 3 in Sections 3.4.1 and 3.4.2, we have the following results for the 3 roots, $(\omega/k)^{\pm}$ and $(\omega/k)^0$, of (7).

• In the case where viscous effects are much more preponderant w.r.t. thermal ones, *i.e.* for $\lambda \ll C_p \mu$, or equivalently $Pr \gg 1$,

$$\frac{\omega_I^{\pm}}{k} = -k a_1 \left(1 + \frac{3(\gamma - 1)}{4Pr} \right) + \mathcal{O}\left(\frac{1}{Pr^2} \right) , \qquad (39)$$

$$\frac{\omega_R^{\pm}}{k} = \pm c(k) \pm \frac{3(\gamma - 1)k^2 a_1^2}{4c(k)} \frac{1}{Pr} + \mathcal{O}\left(\frac{1}{Pr^2}\right), \qquad (40)$$

$$\frac{\omega_I^0}{k} = -\frac{3ka_1}{2}\frac{1}{Pr} + \mathcal{O}\left(\frac{1}{Pr^2}\right), \qquad (41)$$

$$\frac{\omega_R^0}{k} = \mathcal{O}\left(\frac{1}{Pr^2}\right) \,. \tag{42}$$

• In the case where thermal effects are much more preponderant w.r.t. viscous one, *i.e.* for $C_p \mu \ll \lambda$, or equivalently $Pr \ll 1$,

$$\frac{\omega_I^{\pm}}{k} = -k a_1 - \frac{(\gamma - 1) c^2}{3 \gamma^2 k a_1} Pr + \mathcal{O}\left(Pr^2\right) , \qquad (43)$$

$$\frac{\omega_R^{\pm}}{k} = \pm c_T(k) \mp \frac{(\gamma - 1)c^2}{3\gamma^2 c_T(k)} Pr + \mathcal{O}\left(Pr^2\right) , \qquad (44)$$

$$\frac{\omega_I^0}{k} = \frac{3 \, k \, a_1 \gamma}{2 \, Pr} + \mathcal{O}\left(Pr\right) \,, \tag{45}$$

$$\frac{\omega_R^0}{k} = \mathcal{O}\left(Pr\right) \,. \tag{46}$$

As far as dispersive waves are concerned, the two expansions of interest are (39) and (43). It transpires from these two relations that the speed of sound for large Prandt number is at first order the adiabatic speed of sound of the fluid $\sqrt{\frac{\partial p}{\partial \rho}}|_s$ while for small Prandtl number the speed of sound is at first order the isothermal speed of sound of the fluid $\sqrt{\frac{\partial p}{\partial \rho}}|_T$. This generalizes the classical analysis in Fletcher [2]. Actually, (40) and (44) give more information, recalling that the Knudsen number depends linearly on k: $Kn = k \mu / \rho c$:

$$\frac{\omega_R^+}{c\,k} = 1 - \frac{2\,(Kn)^2}{9} + \frac{\gamma - 1}{2\,\gamma} \frac{Kn}{Pr} + \frac{2\,(\gamma - 1)}{9\,\gamma} \frac{Kn^2}{Pr} + \mathcal{O}\left(\frac{(Kn)^4}{Pr} + \frac{1}{Pr^2}\right), \text{ as } Pr \to \infty, \quad (47)$$

$$\frac{\omega_R^+}{c_T k} = 1 - \frac{2 (Kn)^2}{9} + \frac{\gamma - 1}{3 \gamma} Pr - \frac{2 (\gamma - 1)}{27} Kn^2 Pr + \mathcal{O}\left((Kn)^4 + Pr^2\right), \text{ as } Pr \to 0.$$
(48)

4 Appendix: Some classical thermodynamic identities used in this article

The dispersion relations derived in this paper involves some thermodynamic coefficients that depends on the equations of state. All the coefficients are well referenced in literature but the notations are not universal and furthermore in many references, they are expressed in the case of perfect gas for example in this case the Grüneisen coefficient Γ is equal to $\gamma - 1$ where γ is the ratio of the heat capacity at constant pressure to the heat capacity at constant volume, and this instills sometimes confusion in the obtained results.

Considering a divariant substance, we have used the following thermodynamic relations (see [8]) in this paper:

$$de = C_v dT + \frac{\gamma \Gamma p - (\gamma - 1) \rho c^2}{\gamma \Gamma \rho^2} d\rho, \qquad (49)$$

$$dh = \gamma C_v dT + \frac{\Gamma - \gamma + 1}{\Gamma \rho} dp, \quad h = e + \frac{p}{\rho}, \quad (50)$$

$$dp = c^2 d\rho + \rho \Gamma T ds = \frac{c^2}{\gamma} d\rho + \rho \Gamma C_v dT.$$
(51)

Indeed, starting from

$$de = C_v \, dT + \left(\beta + \frac{p}{\rho^2}\right) d\rho \,, \tag{52}$$

$$dh = \gamma C_v dT + \left(\alpha + \frac{1}{\rho}\right) dp, \quad h = e + \frac{p}{\rho}, \tag{53}$$

$$dp = c^2 d\rho + \rho \Gamma T \ ds = c_T^2 d\rho + \epsilon \, dT \,, \tag{54}$$

where α , β , ... can be seen as partial derivatives *e.g.* $\epsilon \equiv \frac{\partial p}{\partial T}\Big|_{\rho}$ when the pressure *p* for this divariant substance is seen as a function of the two independent thermodynamic variables ρ and *T*. We have already identified some of the coefficients in order to be consistent with Table 1, (6) and (3). Using these two variables, it is elementary to prove the following result.

Proposition 4 It follows from Gibbs relation:

$$T ds = de - \frac{p}{\rho^2} d\rho, \qquad (55)$$

that

$$\epsilon = \Gamma \rho C_v, \quad \alpha = -\frac{\gamma - 1}{\Gamma \rho}, \quad c_T^2 = \frac{c^2}{\gamma}, \quad \beta = -\frac{(\gamma - 1)c^2}{\gamma \Gamma \rho},$$
$$\Gamma^2 C_v T = \frac{\gamma - 1}{\gamma}c^2. \quad (56)$$

Hence the identities (49) to (51). Combining these identities, we find:

$$dp = c^2 d\rho + \rho \Gamma T ds, \quad dT = \frac{\Gamma T}{\rho} d\rho + \frac{T}{C_v} ds, \quad (57)$$

which we need to derive (2).

References

- [1] Benjelloun S., Ghidaglia J.-M., On the sound speed in two-fluid mixtures and the implications for CFD model validation, Submitted, $2020.\rangle$
- Fletcher, N. H., Adiabatic Assumption for Wave Propagation, American Journal of Physics, 42,487-489, 1974.https://doi:10.1119/1.1987757
- [3] Kirchhoff, G., Ueber den Einfluss der Wärmeleitung in einem Gase auf die Schallbewegung. Ann. Phys., 210: 177-193. 1868.
- [4] Landau L.D., Lifshitz E.M., Course of Theoretical Physics, Volume 6: Fluid Mechanics, Second Edition, PERGAMON PRESS, 1987.
- [5] Stokes G.G., On the theories of the internal friction in fluids in motion, and of the equilibrium and motion of elastic solids, Transactions of the Cambridge Philosophical Society, vol.8, 22, pp. 287-342, 1845
- [6] Vekstein G., Physics of continuous media: Problems and solutions in electromagnetism, fluid mechanics and MHD, 2nd Edition, CRC Press, Boca Raton, FL, USA, 2013.
- [7] Whitham G.B., Linear and nonlinear waves, John Wiley & Sons, New-York, 1974. https://doi.org/10.1016/0021-9991(84)90103-7
- S. Benjelloun, Thermodynamic identities and thermodynamic consistency of Equations of State. MSDA-Report 02, 2021, hal-03216379v2, arXiv:2105.04845.

Contents

1	Intr	oduction	1				
2	Dis	persion relations for a single conductive and viscous fluid	2				
3	3 On the speed of sound in single fluid						
	3.1	Euler's equation, the hyperbolic case	4				
	3.2	Stokes' model: the non-conductive case	5				
	3.3	The non viscous case	7				
	3.4	On the general case	8				
		3.4.1 Asymptotic for large Prandtl number	8				
		3.4.2 Asymptotic for small Prandtl number	9				
		3.4.3 Asymptotic for the speed of sound	10				

4 Appendix: Some classical thermodynamic identities used in this article 12