



**HAL**  
open science

## An Adaptive Large Neighborhood Search for an Appointment Scheduling Problem in Health Care

Eduardo Lopez Aguilar, Yannick Kergosien, Vincent Boyer, Jean-Charles Billaut

► **To cite this version:**

Eduardo Lopez Aguilar, Yannick Kergosien, Vincent Boyer, Jean-Charles Billaut. An Adaptive Large Neighborhood Search for an Appointment Scheduling Problem in Health Care. 18ème congrès de la Société Française de Recherche Opérationnelle et d'Aide à la Décision, 2017, Metz, France. hal-03018397

**HAL Id: hal-03018397**

**<https://hal.science/hal-03018397v1>**

Submitted on 17 Feb 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# An Adaptive Large Neighborhood Search for an Appointment Scheduling Problem in Health Care

Eduardo López Aguilar<sup>1,2</sup>, Yannick Kergosien<sup>1</sup>, Vincent Boyer<sup>2</sup>, Jean-Charles Billaut<sup>1</sup>

<sup>1</sup> Université François-Rabelais Tours, CNRS, LI EA 63000, OC ERL CNRS 6305,  
64 avenue Jean Portalis, 37200 Tours, France  
{eduardo.lopezaguilar}@etu.univ-tours.fr

{yannick.kergosien, jean-charles.billaut}@univ-tours.fr

<sup>2</sup> Graduate Program in Systems Engineering  
Universidad Autónoma de Nuevo León, Monterrey, México  
{eduardo.lopezag, vincent.boyer}@uanl.edu.mx

**Mots-clés :** *Appointment scheduling, health care, metaheuristic, ALNS*

## 1 Content

The appointment scheduling problem is one of the most studied problems in the context of health care services. The scheduling decisions in hospitals are one of the most important tasks performed by the planners, these decisions will impact the resource utilization (rooms, doctors, nurses, etc) and the service quality. Our study is in collaboration with the Assistance Publique - Hôpitaux de Paris (APHP) unit and is focused on the outpatients department of hospitals, where the patients have their appointments in a given day and leave the place in the same day, unlike the inpatients who need to spend some days in the hospital.

The current procedure in the hospital is divided in two main decisions : the day-patient schedule, where the planner determines the visit day of each patient ; and the daily schedule, where the hour and resources required for each appointment is defined. This study is focused on the daily schedule only. The set of patients is known in advance as well as the Clinic Pathway (CP, see [3]) of each patient. The CP represents the set of care activities that the patient must attend in order to diagnose and/or treat a disease. Each activity requires resources like materials, rooms, or human resources. The objective of the problem is to schedule all activities of the day in order to minimize the total waiting time of the patients.

Some recent literature review can be found in appointment scheduling problems in health care [1] and [5]. In most studies, only one type of resource or only one activity are considered. The problem is similar to the *resource constrained multi-project scheduling problem (RCMPSP)* that is a generalization of the single project version proposed in [2].

## 2 Problem description

The problem is defined by three sets of parameters  $(P, A, R)$ , where  $P$  is the set of patients in a given day that must be treated and/or diagnosed,  $A$  is the set of activities that the hospital can perform, and  $R$  is the set of all available resources in the hospital.

Each patient  $p \in P$  has a time window  $[a_p, b_p]$  which represents her/his preference of availability, and the CP that she/he must follow. The CP is defined by a set of activities  $i \in \Lambda_p \subset A$ , an associated set  $\Pi_p$  that are the precedences between activities within the CP, and for some pairs of activities  $(i, j) \in \Pi_p$  a minimum and maximum time lag is defined. Note that some activities can have no precedence with others activities in a CP.

Each activity  $a \in A$  is defined by a vector  $\hat{n}_a = \{n_a^1, n_a^2, \dots, n_a^T\}$  where every element represents a requirement of different types of resources, and the estimated treatment (or consultation) time  $t_a$ . Finally, every resource  $r \in R$  is defined by its type  $t \in T$ , and a time window that represents its availability  $[\alpha_r, \beta_r]$ .

The decision variables are the time schedule of each activity and their assignment to the resources. The goal is to find a schedule of all activities respecting all the constraints (preferences of patients, resource availabilities, time lags between activities, precedence constraints, cumulative resources, etc.). The objective function is to minimize the total waiting time of all patients, and the over utilization of the resources.

### 3 Solution method

First, we formulate the problem as a mixed integer linear programming and use CPLEX solver to solve it. Since only small instances can be solved with the solver due the complexity of the problem, we propose an Adaptive Large Neighborhood Search (ALNS[4]) metaheuristic. The initial solution follows an active scheduling generation, which means that every activity is scheduled as soon as possible and without generating infeasibilities. In this procedure, the assigned activities cannot be rescheduled. The destructive operators consists in removing all activities of several patients from the schedule by using some selection rules like random rule or biggest waiting time rule. The repairing operators aim to reschedule all activities that have been removed, using a best insertion procedure and several priority rules. The selection of destroy and repair operators is based on an adaptive score adjustment procedure.

The test instances was generated assuming that all the patient can be served in a given day and the results obtained with the MILP formulation and the ALNS algorithm will be presented and discussed at the conference.

### Références

- [1] Amir Ahmadi-Javid, Zahra Jalali, and Kenneth J Klassen. Outpatient appointment systems in healthcare : A review of optimization studies. *European Journal of Operational Research*, 2016.
- [2] Jacek Blazewicz, Jan Karel Lenstra, and AHG Rinnooy Kan. Scheduling subject to resource constraints : classification and complexity. *Discrete Applied Mathematics*, 5(1) :11–24, 1983.
- [3] Richard J Coffey, Janet S Richards, Carl S Remmert, Sarah S LeRoy, Rhonda R Schoville, and Phyllis J Baldwin. An introduction to critical paths. *Quality Management in Healthcare*, 14(1) :46–55, 2005.
- [4] Stefan Ropke and David Pisinger. An adaptive large neighborhood search heuristic for the pickup and delivery problem with time windows. *Transportation science*, 40(4) :455–472, 2006.
- [5] A Teixeira and MJF De Oliveira. Operations research on hospital admission systems : a first overview of the 2005-2014 decade. In *Journal of Physics : Conference Series*, volume 616, page 012009. IOP Publishing, 2015.