



HAL
open science

Atmospheric Plasma DC Source in the Micro Scale Elaborated by Micro-Nanotechnologies

Ronan Michaud, Sylvain Iséni, Arnaud Stolz, Philippe Lefauchaux, Remi
Dussart

► **To cite this version:**

Ronan Michaud, Sylvain Iséni, Arnaud Stolz, Philippe Lefauchaux, Remi Dussart. Atmospheric Plasma DC Source in the Micro Scale Elaborated by Micro-Nanotechnologies. XXV Europhysics Conference on Atomic and Molecular Physics of Ionized Gases (ESCAMPIG XXII), Jul 2022, Paris, France. hal-03049315

HAL Id: hal-03049315

<https://hal.science/hal-03049315>

Submitted on 11 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Atmospheric plasma DC source in the micro scale elaborated by micro-nanotechnologies

Ronan Michaud^(*), Sylvain Iséni, Arnaud Stolz, Philippe Lefaucheu
and Rémi Dussart

GREMI, UMR7344 CNRS/Univ. Orléans, 45067 Orléans, France

(*) ronan.michaud@univ-orleans.fr

Plasma micro reactors are in their whole elaborated in clean room by MEMS fabrication techniques. They are usually made on silicon platform and constituted by SiO₂ dielectric grown by thermal oxidation and nickel coated by PVD process. Electrical and optical characterizations are the main diagnostics used to determine the properties of the discharge and the robustness of the device. SEM images are also made before and after plasma operation. These DC microdischarges can operate continuously during more than 24 hours in stable regime from 100 Torr up to the atmospheric pressure. In these conditions, a high density of reactive species is produced and can be used for gas, liquid or surface treatment.

Micro hollow cathode discharges (MHCD) operating in DC were first introduced in the mid-90s [1]. Due to their dimensions and their large surface to volume ratio, the produced micro plasma remains cold and can operate at atmospheric pressure in a stable and normal discharge regime as long as the cathode area is not limited [2]. These properties have opened a large number of possible application like destruction of volatile organic compounds, surface analysis of treatment and even UV and VUV radiation sources [3].

Silicon processing, developed for microelectronic devices, offers many opportunities to design new, original and efficient devices to produce high-density microplasmas. We present here a Si-based microstructure realized by MEMS fabrication techniques to create from one to more than a thousand microdischarges on a 2x2 cm chip. These plasmas can be ignited in different gases such as helium or argon from 100 Torr up to the atmospheric pressure [4].




Fig. 1: Images of a micro discharge in single hole configuration operated in argon and helium at atmospheric pressure with a maximum current of 0,8mA. (Micro reactor configuration : single hole, diameter 150 μm, depth 55 μm)

The electrical and optical properties of a discharge in a single hole configuration was investigated and compared to simulations using a fluid model. The results show that the microdischarge seems to have the same behaviour as a classic glow discharge and, depending on the geometry and the parameters, the characteristics of the plasma can be tuned. For example, the position of the discharge for the same electrical parameters in argon and helium is shown in Fig. 1. In argon, the discharge is located in a ring-shape near the edge of the hole while, in helium, the discharge is more homogenous over the cathode surface area. Finally, as introduced by Eden et al. [5], a study using the semi-conductor properties of silicon to elaborate photodetector was investigated.

References

- [1] Schoenbach K H, Verhappen R, Tessnow T, Peterkin F E and Byszewski W W 1996 Microhollow cathode discharges *Applied Physics Letters* **68** 13–5
- [2] Dufour T, Dussart R, Lefauchaux P, Ranson P, Overzet L J, Mandra M, Lee J-B and Goeckner M 2008 Effect of limiting the cathode surface on direct current microhollow cathode discharge in helium *Applied Physics Letters* **93** 071508
- [3] Foest R, Schmidt M and Becker K 2006 Microplasmas, an emerging field of low-temperature plasma science and technology *International Journal of Mass Spectrometry* **248** 87–102
- [4] Michaud R, Felix V, Stolz A, Aubry O, Lefauchaux P, Dzikowski S, Schulz-von der Gathen V, Overzet L J and Dussart R 2018 Direct current microhollow cathode discharges on silicon devices operating in argon and helium *Plasma Sources Sci. Technol.* **27** 025005
- [5] Eden J G and Park S-J 2004 Microdischarge photodetectors. Patent US6828730 B2