

Correlation between mechanical and structural properties as a function of temperature within the TeO2–TiO2–ZnO ternary system

J. de Clermont-Gallerande, Maggy Colas, F. Celarie, Y. Gueguen, M. Bergler,

D. de Ligny, T. Hayakawa, P. Thomas

▶ To cite this version:

J. de Clermont-Gallerande, Maggy Colas, F. Celarie, Y. Gueguen, M. Bergler, et al.. Correlation between mechanical and structural properties as a function of temperature within the TeO2–TiO2–ZnO ternary system. Journal of Non-Crystalline Solids, 2020, 528, pp.119716. 10.1016/j.jnoncrysol.2019.119716. hal-03063712

HAL Id: hal-03063712 https://hal.science/hal-03063712v1

Submitted on 14 Dec 2020

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Correlation between mechanical and structural properties as a 1

function of temperature within the TeO₂-TiO₂-ZnO ternary 2

3 system.

4 J. de Clermont-Gallerande¹; M. Dutreilh-Colas¹; F. Célarié²; Y. Gueguen²; M. Bergler³; D. de Ligny³; T.

- Hayakawa⁴; P. Thomas¹
- ¹Institut de recherche sur les céramiques (IRCER), UMR 7315 CNRS / Université de Limoges, Centre Européen de la
- Céramique, 12, rue Atlantis, 87068 Limoges, France
- 5 6 7 8 9 ² Institut de Physique de Rennes (IPR), UMR6251 CNRS, Universite de Rennes, 263 Avenue Général Leclerc, 35700 Rennes, France
- 10 ³ Institute of Glass and Ceramics, DMSE, University of Erlangen-Nuremberg, DE 91058 Erlangen, Germany
- 11 ⁴Field of Advanced Ceramics, Department of Life Science and Applied Chemistry / Frontier Research Institute of Materials
- 12 Science (FRIMS), Nagoya Institute of Technology, Gokiso, Showa, Nagoya 466-8555, Japan

Abstract 13

14

15 In situ Raman spectroscopy, Resonance Frequency and Damping Analysis (RFDA) setup 16 and Associated Raman Brillouin Calorimeter (ARABICA) setup experiments as a function of temperature were conducted on the (100-x)TeO₂-5TiO₂-xZnO (x=15; 17.5; 20; 22.5; 25) glass 17 18 system. Structural and mechanical properties showed non-conventional properties evolution as 19 a function of ZnO content which are managed by the modification of ZnO polyhedra. Before glass transition temperature (Tg), the evolution of the Boson peak (BP) frequencies and the 20 21 elastic properties are in accordance with the idea of the relaxation of the strains inside the glass; 22 after Tg, their evolution shows the transition toward a viscous liquid. BP and mechanical 23 properties study evidences that as nano-heterogeneous domains size increases at a faster rate, 24 the mechanical properties will decrease at a slower rate. This point will be helpful for choosing 25 appropriate composition for optical fiber shaping. 26 27

Introduction 28

29 Tellurite glasses have interested researchers in the field of photonic application for many 30 years. Indeed, they are good candidates for optical fibers thanks to their high linear refractive 31 index, high dielectric constant, wide infrared transmittance, and their high third order non-linear 32 optical values (1-4).

33 Ab-initio studies showed that the pure TeO₂ glasses have the highest non-linear optical 34 properties among tellurite glasses (5) (fifty times more than fused silica glasses (4,6)), but 35 extreme quenching conditions are needed to obtain glass (7). Consequently, modifier oxides are required. Different systems have been studied in their abilities to form glasses (glassy 36 37 domains) and their structural, linear and non-linear optical properties for many years in IRCER 38 laboratory (8–14). Among them, adding TiO₂ is well known to increase the glass forming ability 39 resulting in homogeneous glasses with only slight changes in the structure of pure TeO₂ glass 40 (8, 15, 16).

41 Adding ZnO in tellurite glasses significantly increases the glass forming domain (up to 42 40mol% ZnO) (17). Binary TeO₂-ZnO glasses are useful media for ultra-low loss optical fibers 43 (1 dB/km) in the wavelength range of 3.4-4 μ m (18). Different studies have been done on TeO₂-

ZnO glasses based on Raman spectroscopy data (19-23), and neutron and X-ray diffraction 44

45 (24). The different studies showed that adding ZnO to the original TeO_2 glass matrix results in 46 (i) a structural transformation of TeO_4 into TeO_3 units and so a linear decrease of the optical 47 properties (*ii*) a band gap decrease as the glasses turn more transparent upon adding ZnO (25). 48 The goal of the present study is to highlight a correlation between the evolution of the 49 mechanical properties and the structure of (100-x)TeO₂-5TiO₂-xZnO (x=15, 17.5, 20, 22.5, 25 50 (TTZ) glasses as a function of temperature especially around the glass transition temperature (Tg). In this study, the medium-range structure of TTZ glasses is studied using in-situ Raman 51 52 spectroscopy and mechanical properties by Resonance Frequency and Damping Analysis 53 (RFDA) and Brillouin experiments (26). By looking at the properties of the glass as a function 54 of temperature, it might be possible to have an idea of their ability to fiber shaping...

1. Experimental 55

56 **1.1. Sample preparation**

57 The relevant amount of the different initial powders (commercial: α -TeO₂: Toldini 99,9%, TiO₂: Aldrich 99%, ZnO : Alfa Aesar 99,99%) within the ternary system (100-x)TeO₂-5TiO₂-58 xZnO %mol, with x= 15; 17.5; 20; 22.5 and 25 (respectively named TTZ15, TTZ17.5, TTZ20, 59 TTZ22.5 and TTZ25) were ground in a mortar then melted in a platinum crucible at 850°C 60 before being quenched on a brass mold preheated at 150°C. The glass domain is smaller than 61 the one found in (25) due to the amount of powder used (13g) to synthesize the samples for 62 63 mechanical experiment. The obtained glasses were then annealed at 30°C below the glass transition temperature (taken from (25,27)) for 12 hours in order to release stresses resulting 64 65 from the melt-quenching method. The final concentrations of the samples have been controlled by EDS experiments which evidence a deviation less than 2% from the theoretical composition. 66

As many experiments have been done, the size and synthesis conditions of the samples have 67 68 been adapted to the needs of each measure. All the relevant information are summarized in the 69 Table 1.

Experiment	Initial mass (g)	Melting time (h)	Ground or polished	Form of the sample	Sample size (mm)
Raman spectroscopy	2	1	Ground	Powder	N/A
RFDA	13	5	Polished	Parallelepiped	l=30
					L=15
					e=3
ARABICA*	2	1	Polished		D=3
	2	1		Cynnder	h=1
Table 1 : Information on the different experimental procedures for each experiment. *Associated Raman,					

70 71

72

Brillouin Calorimetry. D: diameter; h: height of a cylinder; l: length of a parallelepiped; L: width of a

parallelepiped; e: thickness of a parallelepiped.

73 Raman spectra were recorded in the 10-1000cm⁻¹ spectral range, using a T64000 HORIBA Jobin-Yvon spectrometer operating in the triple subtractive configuration at 514.5 nm. Samples 74 75 were heat using a LINKAM TMS600 device (5°C/minute).

76 All Raman spectra were normalized (total area normalization) and baseline corrected (linear 77 correction).

78 The normalized spectra were then decomposed using the Focus program (28) based on 79 previous studies (10,25,29), with 10 oscillators: 9 Gaussian functions and 1 log-normal 80 function. As the spectra are recorded at different temperature, all functions were independently corrected from the Bose-Einstein factor. Due to the width and overlapping of the bands of the
normalized Raman spectra (figure 1) all Gaussian functions were width at half maximum
(FWHM) and frequency fixed, and only the intensity was left free. As the log-normal function
is well defined, all fitting parameters were left totally free (frequency, FWHM and intensity).

- The TTZ glass Raman spectra's frequencies range can be divided in two different parts: the low wavenumber region with the Boson peak (BP), the high wavenumber region (300-800 cm⁻)
- low wavenumber region with the Boson peak (BP), the high wavenumber region (300-800 cm⁻
 with the deformation of bridges (Zn-O-Zn or Zn-O-Te and asymmetric and symmetric Te-O-
- Te) and the elongation vibrations of Te-O bonds for TeO₃ and TeO₄ polyhedra (figure 2).



- 89
- 90

91

92 The mechanical properties have been obtained by Resonance Frequency and Damping
93 Analysis (RFDA). Details on this technique can be found in the ASTM international base (26).
94 Sample have been heat until the loss of the signal (10°C/minute).

Brillouin measurements have been done on the ARABICA platform (Associated Raman
Brillouin Calorimetry) (30). Samples have been heated at 10°C/min until 420°C. Time
accumulation from Brillouin signal is 30 seconds (spectrum each 5°C).

98 2. Results and discussion

99 **2.1. Raman spectroscopy**

100 Vibrational studies of TeO_2 -ZnO glasses have been extensively done (19–21) at room 101 temperature. It has been reported (20) that adding ZnO in the glasses has different

Figure 1 : Raman bands attribution of a typical TTZ sample (Example of the TTZ15 sample)

- 102 consequences. By Raman spectroscopy, a shift of the band corresponding to the vibration of 103 the TeO₄ polyhedra toward higher frequencies and a shift of the band corresponding to the 104 vibration of the non-bridging oxygen in TeO₃ and TeO₄ polyhedra to higher values 105 accompanied by a progressive increase in intensity are observed. A decrease of the intensity of 106 the band corresponding to the vibration of the Te-O-Te bridges and a shift to lower frequencies 107 is also noted.
- 108 According to *Bürger et al.* (20), it has been evidenced that the introduction of zinc oxide in 109 TeO₂ glasses will induce Non Bridging Oxygens (NBO) species. The length of one of the Te-110 O bond of the TeO₄ units gradually increase, leading into TeO₃₊₁ units and then TeO₃ units with 111 an increase in zinc oxide content.
- 112 *Kozukharov et al.* reported that ZnO is introduced as ZnO_6 octahedra either within tellurite 113 chains or between them (23). At low content of ZnO, a part of the TeO₄ trigonal bipyramids 114 (tbps) becomes asymmetric, producing TeO₃₊₁ units observed in the Zn₂Te₃O₈ crystalline 115 phase. For higher concentration of ZnO, the TeO₃₊₁ units loose one oxygen to become TeO₃ 116 trigonal pyramids (tp) found in ZnTeO₃ crystalline phase (23).
- 117 *Thorbahn et al.* (24), evidenced by Raman spectroscopy and EXAFS experiments for binary 118 TeO₂-ZnO glasses that Zn coordination number decreases from 6 ± 1.6 to 4 ± 0.6 with a Zn-O 119 bond length that remained constant with increasing ZnO content. It was also reported that rather 120 than the ZnO₆ configuration discussed above, ZnO is present in the form of ZnO₄ tetrahedra for 121 high ZnO content (24).
- In a previous study in IRCER laboratory, *Ghribi et al.* have studied the TeO₂-TiO₂-ZnO and the TeO₂-GeO₂-ZnO system at room temperature (25,29). They concluded that adding ZnO in glassy matrix will in a first step lead to breaking Te-O-Te bridges, including network depolymerization, and in a second step, with more ZnO content, to the formation of Te-O-Zn and Zn-O-Zn bridges.
- As the role of ZnO in still unclear, we proposed here a structural investigation of the ternary system TTZ on a wide ZnO range content (15-25 mol%) from RT up to crystallization temperature. However, the crystallization of the samples won't be discuss in this paper.
- Nevertheless, as parent crystallized phases give good indications of the unit, which can be
 evidence in glasses, an overview of crystallized phases in the TeO₂-ZnO binary system is
 proposed.
- 133Two stable crystalline phases respectively $ZnTeO_3$ for 50% mol TeO_2 50% mol ZnO and134 $Zn_2Te_3O_8$ for 60% mol TeO_2 -40% mol ZnO (31,32) can be found (33).
- 135 The $Zn_2Te_3O_8$ structure is composed of chain-like structure with Te_3O_8 groups made with 136 one TeO₄ and two TeO₃₊₁ units with ZnO_{5+1} in octahedra-like structures between the chains.
- 137 Whereas, the ZnTeO₃ has Zn substituting Te to form new Zn-O-Te chains.
- 138 Pure ZnO crystal is made of chains of tetrahedra units.
- 139 By comparing each crystallized phases, it can be hypothesized that at low concentration of 140 ZnO, the zinc polyhedra could be between the tellurite chains in a pseudo-octahedral form (looking like the Zn₂Te₃O₈ crystalline phase). And as ZnO content increases, the TeO₄ and 141 142 TeO_{3+1} polyhedra will decrease for an increase in TeO_3 polyhedra, the ZnO_{5+1} polyhedra will 143 also go toward a ZnO₄₊₁ and will substitute the tellurium oxide inside the chains to form Te-O-144 Zn bridges as shown in the ZnTeO₃ crystalline phase. It is possible that in glasses with high 145 concentration in zinc oxide, the ZnO will be tetrahedra-formed inside the chains (as shown in 146 the pure ZnO crystal). The crystallization of the samples have been presented elsewhere (33).

For an in-depth understanding of the vibration modes of the Raman spectroscopy of $Zn_2Te_3O_8$ and $ZnTeO_3$ crystalline phases, computational studies by using LADY software (34) were done, and a theoretical Raman spectra was calculated for each phases.





Figure 2 : Simulated Raman spectra of the Zn₂Te₃O₈ and ZnTeO₃ crystalline phases

By comparing the Raman spectra of the two crystalline phases (figure 2), the evolution of the Raman spectra as a function of the concentration can be explained. An increase of ZnO content causes : (*i*) an increase of the Zn-O-Zn/Zn-O-Te bonds ($300-400 \text{ cm}^{-1}$), (*ii*) a decrease of the Te -O-Te bridges ($400-550 \text{ cm}^{-1}$), (*iii*) a decrease of TeO₄ polyhedra and an increase of TeO₃ polyhedra ($550-800 \text{ cm}^{-1}$) is expected.

As the Boson peak (BP) is a manifestation of the excess of Vibrationnal Density of States (VDoS), phonon scattering is caused by intrinsic density fluctuations domains in the structure (within which short and medium range order is maintained and beyond which the material is isotropic). The BP, which is characteristic of the glassy state, will give important information allowing the correlation of the mechanical and structural approaches. This paper will focus on its evolution.



163 164

Figure 3: BP intensity as a function of Tg/T. Inset: zoom of the variations around Tg



166 167 168

<u>Figure 4: a)</u> ω_{BP} as a function of Tg/T. Inset: zoom of the variations around Tg b) ω_{BP} as a function of ZnO content at 30°C (RT). c) Average slope of data extracted from figure 4-a) after Tg

Most of the graphs will be presented in a non-conventional way, namely abscissa and ordinate will be normalized by the value of the parameter under study at Tg_{DSC} (obtained from DSC measurements,) to facilitate the comparison between samples.

Figure 3 represents the evolution of the Boson peak (BP) intensity. A decrease of the BP intensity before Tg is first observed and then followed by an increase up to crystallization temperature.

175 Figure 4a, b, c summarized the Boson peak wavenumber evolution. Figure 4a illustrates the 176 general evolution of the Boson peak wavenumber of each sample as a function of temperature. 177 A slight shift to lower wavenumber up to Tg, and after this temperature, a strong difference of 178 the wavenumber evolution is observed. Figure 4b shows the Boson peak wavenumber as a 179 function of the composition at Room temperature (RT). A decrease of the wavenumber with an 180 increase of the ZnO concentration is observed until TTZ20 and a strong increase of this intensity 181 is noted for further concentrations. To illustrate the evolution of the Boson peak wavenumber 182 after Tg, Figure 4c represents the evolution of the slope of the curve shown in Figure 4a; this slope represents the rate at which the wavenumber of the Boson peak is decreasing after Tg. A 183 slight decrease of the value between TTZ15, TTZ20 and TTZ25 can be noted and an abnormal 184 185 behavior compared to the previous three samples was observed for TTZ17.5 and TTZ22.5 186 samples.

187 As a glass is considered composed of small domains with organized structure. Those 188 domains (thereafter named blobs), are randomly arranged inside the glass, explaining its non-189 existent long order structuration.

190 When the BP intensity decreases, heterogeneity between blobs decreases (35,36). The 191 present evolution means that with an increase in temperature, there is a rearrangement at short 192 and intermediate distance of the glass to reach an energy minima at each temperature. After the 193 glass transition temperature, the transition toward a viscous liquid will increase the 194 heterogeneity of the glass. After the crystallization temperature, there is a decrease of intensity 195 of the Boson peak due to the disappearance of the glass phase.

196 Duval et al. (37) and Elliott et al. (38) independently proposed a relationship between the 197 size of the blobs ξ , the BP frequencies ω_{BP} and the mean sound velocities V_{av} (see equation 3) 198 calculated from the mechanical properties of the glasses. The evolution of ω_{BP} then gives a first 199 understanding of the evolution of the size of the blobs as a function of the temperature.

200

$$V_{av}/\omega_{\rm BP}$$

 $\xi = V_{av}/\omega_{\rm BP}$ (1) In the present study, before Tg, a classical trend as a function of temperature is observed, as 201 202 glass is relaxing the size of the blobs increases, and after Tg, the samples goes toward a state of 203 a viscous liquid, increasing the size even further (figure 4a).

204 Figure 4b evidences that at RT, ω_{BP} decreases up to TTZ20 and then increases meaning that 205 blobs size firstly increases and then decreases.

206 ω_{BP} fluctuations clearly evidences a change in the structural behavior of the glass.

207 2.2. Mechanical approach

209 The temperature dependence of the elastic moduli and the shear moduli are illustrated figure 210 8. As explained by Mezeix et al. (39) for silica glasses, a good description of the comportment 211 of glasses at temperatures before Tg is obtained by using the model proposed by Wachtman et al. (40) (equation 2) and after Tg, this temperature dependence can be modeled by a power law 212 213 equation proposed by Rouxel et al. (41) (equation 3).

214

215

208

$$G = G_{0K} - BT \cdot \exp(\frac{-T_0}{T}) \tag{2}$$

 $G = G_{Tg} \left(\frac{Tg}{T}\right)^{\alpha}$

The obtained parameters of both simulated curves are reported on respectively table 2 216 217 (Wachtman parameters) and table 3 (Rouxel parameters). The intersection of both calculated curves gives the value Tg. As this temperature is dependent of the thermal history of the sample, 218

(3)

- this temperature will be denoted mechanical Tg: Tg_{RFDA}. This Tg_{RFDA} will be used to normalize
- the data.



221 222

Figure 5: Example of the shear modulus simulations as a function of temperature for the TTZ25 sample.

Sample	Е			G		
Wachtman parameters	E _{0K}	В	T_0	G _{0K}	В	T_0
TTZ15	52.45	0.023	531	21.30	0.011	588
TTZ17.5	47.43	0.019	494	19.87	0.010	574
TTZ20	51.34	0.018	353	20.87	0.009	503
TTZ22.5	55.39	0.021	481	22.08	0.011	723
TTZ25	54.25	0.029	700	21.89	0.011	634

Table 2 : Wachtman equation simulation parameters for E and G curves

Sample	E			G		
Rouxel parameters	E _{Tg}	Tg(E)	α	G _{Tg}	Tg(G)	α
TTZ15	48.38	593	1.26	30.06	383	1.01
TTZ17.5	27.43	691	4.31	39.10	527	4.65
TTZ20	30.33	722	2.79	24.20	514	1.45
TTZ22.5	51.27	639	4.11	30.46	570	3.72
TTZ25	29.82	717	3.66	26.09	547	2.25

224

Table 3 : Rouxel equation simulation parameters for E and G curves

The B parameter of the Watchman equation is quite constant for both E and G data, which means that the evolution of the properties are equivalent up to Tg. On the opposite, the evolution of the simulated alpha coefficient from the Rouxel equation evidences huge variations which means that after Tg, Young and shear modulus have special trend which has to be studied.







Figure 8: a) Evolution of the Poisson ratio as a function of temperature, b) Evolution of the Poisson ratio as a function of the glass composition at RT

238

As a function of temperature, for each sample, a slight decrease of E and G before Tg_{RFDA} is observed which is exacerbated after (figure 6a and 7a). The Poisson ratio, which is calculated using G and E, presents also strong variations around Tg (figure 8a). This evolution will be further discussed in the discussion part.

The evolution of the E, G and v values (figure 6b, 7b, 8b respectively) at room temperature and as a function of the concentration show an equivalent variation: a decrease of their values from TTZ15 to TTZ17.5 and then an increase from TTZ17.5 to TTZ25 is observed. Those results are consistent with the results previously published by *Ghribi et al.* (33), using ultrasonic echography experiments.

248 As Poisson ratio gives an information on the average connectivity of the glass (42), an 249 increase of the connectivity of the network before TTZ17.5 and a decrease of the connectivity after is observed. Those results are consistent with the proposed theory: at low concentration of 250 251 ZnO, Zinc oxide polyhedra are localized between the tellurite chains, linking them together by 252 weak bonding, increasing by consequence the connectivity of the network but decreasing E and 253 G values. At higher concentration, zinc atom substitutes Te atom within the chains, so it does 254 not link the chains as it did at lower concentration. This in turn will decrease the connectivity 255 of the network and increase once more E and G values compared to the lower concentration of zinc oxide. 256

The alpha coefficient (extracted from the Power law equation), which expresses the softening rate and which is correlated to the liquid fragility index (39), was calculated by measuring the slope of the curve obtained after plotting $\log(G/G(Tg))$ versus $f(\log(Tg/T))$ for temperatures higher than Tg (figure 9a). The same way is used for $\log (E/E(Tg))=f(\log Tg/T))$ (figure 9b).

262 The α coefficient evolution as a function of the concentration (figure 10) shows that the two 263 glasses with the highest α value are the TTZ17.5 and TTZ22.5 samples. The other three glasses 264 have a linear increase of the α coefficient value.

An higher value of α coefficient means a higher rate of decreasing mechanical properties, so the linear increase in the α coefficient value between TTZ15, TTZ20 and TTZ22.5 glasses means that the more ZnO content inside the glass, the faster the mechanical properties will decrease after Tg. The α coefficient for the two glasses TTZ17.5 and TTZ22.5 shows that the mechanical properties of these two glasses decrease at a faster rate. 270 Comparing the evolution of the TTZ17.5 glass to the previous conclusion on the structural 271 properties, another hypothesis can be added: when the Zinc oxide is between the tellurite chains, 272 the bonds between the Zinc oxide and the tellurium oxide are weak, and become even weaker 273 after the glass transition temperature (decreasing at the same time the mechanical properties 274 faster (higher α coefficient value)).

The evolution of the TTZ22.5 glass sample is still under study and other experiments are

being done to understand the strange behavior of this sample compared to other compositions.



Figure 9: a) $G/G(T_g)=f(T_g/T)$; b) $E/E(T_g)=f(T_g/T)$; Insets: zoom of the variations around T_g



279 280

277 278

Figure 10 : Alpha coefficient as a function of the ZnO concentration

281 2.2.2. ARABICA experiment

In the Brillouin spectra, due to the backscattering geometry used in the experimental setup only longitudinal mode are observed. The position of the Brillouin band strongly depends on the temperature (figure 11). A slight shift of the Brillouin position to lower energy before the glass transition temperature (Tg_{DSC}) is observed. Around 20°C before the glass transition temperature, a sharper decrease of the Brillouin shift is observed followed by a second slope break. The variation just before the glass transition temperature will be further discussed in the discussion part.





Figure 11:	TTZ glasses	Brillouin	position as a	function o	f tempe	rature
-	~			,		

As the Brillouin shift is proportional to the longitudinal velocity of the glasses, so proportional to the mechanical properties of each samples (equation 4). It is then possible to compare the mechanical properties obtained by RFDA experiments to the results from the Brillouin shift.

295 $V_L(Brillouin) = \frac{\lambda.(Brillouin shift)}{2n}$

With λ the wavelength of the measurement (488nm in this work) and n the linear refractive index at the same wavelength.



<u>Figure 12: Variation of the longitudinal velocities calculated from the Brillouin and RFDA experiments as a</u>
 <u>function of the concentration in zinc oxide at room temperature.</u>

Thanks to the figure 12, which compare the variation of the longitudinal velocities obtained by Brillouin experiment and RFDA experiment as a function of the ZnO content, a good agreement of the variation is found between the two different techniques, with a decrease of the longitudinal velocities between TTZ15 and TTZ17.5 followed by an increase thereafter.

(4)



Figure 13: a) Brillouin peak energy normalized with the Brillouin peak energy at the glass transition temperature as a function of Tg/T. Inset: zoom of the variations around Tg b) Variation of the slope in the second regime after the glass transition temperature

309 By normalizing the Brillouin shift in the same way as for the mechanical properties to extract 310 the alpha coefficient of the power law equation, it is possible to compare the evolution of the 311 mechanical properties and the variation of the Brillouin energy by calculating the slopes in the 312 second part of the graphic in figure 13a.

313 Hence, by comparing the values of slope calculated showed in figure 13b to the one from 314 the α coefficient (figure 10), it is shown that the evolution as a function of the concentration has 315 the same linear evolution between the three samples TTZ15, TTZ20 and TTZ25 with two 316 anomalies being TTZ17.5 and TTZ22.5.

The results of the Brillouin experiment are in a good agreement with the mechanical properties as a function of the concentration but also as a function of temperature, with a slight decrease of the Brillouin shift as the mechanical properties decrease, and so even after Tg.

320

2.3. Discussion

305 306

307

308

321

Sample	Tg _{Raman} (°C)	Tg _{RFD}	$_{A}(^{\circ}C)$	Tg _{Brillouin} (°C)	Tg _{DSC} (°C)
	(±10°C)	Tg(E)	Tg(G)	(±10°C)	(±5°C)
		$(\pm 5^{\circ}C)$	$(\pm 5^{\circ}C)$		
TTZ15	310	339	336	336	335
TTZ17.5	313	353	354	339	337
TTZ20	321	354	347	341	339
TTZ22.5	324	372	372	340	341
TTZ25	331	355	351	345	343

322 323

 Table 4 : Glass temperature measured by the different experiments (The values of Tg_{DSC} shown in table 3 were measured thanks to the ARABICA setup at the same time as the Brillouin shift measures).

A first interesting comment can be done on the difference between the values of Tg obtained as a function of the technique used. Using the same method as for RFDA data to extract a mechanical Tg, Raman data have been fitted with linear functions before and after the slope break observed on data, the value of Tg is extracted at the intersection of the two fitted parts. Comparing Tg_{Raman} and Tg_{RFDA} to Tg_{DSC}, it can be seen that Tg_{Raman} is lower and Tg_{RFDA} is higher. This difference partly come from the difference of sample's size, the difference of the heating rate (5°C/min for Raman spectroscopy and 10°C/min for the RFDA and ARABICA measurements). Moreover Raman data are obtained in a semi-dynamic way (Stop of the heating
 ramp during acquisition time) and not a dynamic one like RFDA and ARABICA data recording.

Now, looking at Brillouin and RFDA experiments (in particular the Poisson coefficient)
 more in details, some interesting facts can be noted:

In Brillouin experiment (figure 11), Brillouin shift evolution exhibits an intermediate slope break between the glassy state and the liquid one: This intermediate domain is characteristic of relaxation events suggesting that the heating rate of 10° C/min used for the experiment was too fast, creating strains inside the glass. The intercept between the intermediate and the liquid part is equivalent to the Tg_{DSC} and was used to define the Tg_{Brillouin} (results shown on table 4).

By comparing the Brillouin data to the Raman data it can be noticed in Figure 14 that the Tg_{Raman} corresponds to the intercept of the linear extrapolation between the glassy state and the liquid one of the Brillouin shift (relaxation temperature (T_R) values in table 5). This also corresponds to the strong variation around Tg found on the Poisson ratio curve (figure 9), where the variation in Poisson ratio starts to fluctuate (values in table 5). This means that the relaxation of the sample due to the high heating rate will strongly affect the connectivity of the network before the glass transition temperature, due to a rearrangement of the glassy network.



348

349 350

Figure 14 : Example of how the relaxation temperature and the glass transition temperature are obtained (TTZ15 glass)

351

Sample	T _R Brillouin (°C)	T _R RFDA (°C)
TTZ15	303	305
TTZ17.5	307	306
TTZ20	312	309
TTZ22.5	307	301
TTZ25	322	316

352

Table 5 : Relaxation temperatures for each samples in RFDA and Brillouin experiments

To go further, as explained before, *Duval et al.* (37) and *Elliott et al.* (38) independently found a relationship that links the size of density fluctuations domains ξ with the position of the Boson peak frequency ω_{BP} and the sound velocities inside the glasses.

356

$$=\frac{V_{av}}{\omega_{BP}}$$
(3)

357 With V_{av} the average between the transversal velocity (V_T) and the longitudinal velocity 358 (V_L). It is possible to calculate the two required velocities with the two equation below

ξ

$$V_T = \sqrt{\frac{G}{\rho}} \qquad V_L = \sqrt{\frac{K + \frac{4G}{3}}{\rho}} \qquad K = \frac{1}{3} \cdot \frac{E}{1 - 2\nu}$$
(4)

387 With K the Bulk modulus. V_{av} is then calculated with the equation below.

$$V_{av} = \left(\frac{1}{3V_l^3} + \frac{2}{3V_t^3}\right)^{-1/3}$$
(5)

388

389 Figure 15a represents the evolution of the size of the domains as a function of temperature. 390 Before the glass transition temperature, a slight increase of this parameter is evidenced, with a 391 steeper increase after the glass transition temperature. This evolution is in accordance to the 392 previous evolution of the Boson Peak, and correspond to the relaxation of the glass before Tg 393 and then the transition toward a viscous liquid after Tg.

394 As a function of the concentration (Figure 15b), two different evolutions can be seen: a sharp decrease of the size of the blobs between TTZ15 and TTZ17.5 and hereafter data are almost 395 396 constant. This means that drastic changes of the structure after TTZ17.5 are observed, which 397 can be explained by the change of the Zn atom coordination number as a function of ZnO 398 content.

399 The discrepancy between the evolution of the size of the blobs as a function of the 400 concentration and the evolution of the Boson peak wavenumber comes from the evolution of 401 the sound velocities, and by this bias the evolution of the mechanical properties. This also 402 means that having the Boson peak wavenumber evolution isn't enough to understand exactly 403 how the size of the blobs evolve, even if it can give a rough understanding of this evolution as 404 shown as a function of temperature.



405 406

Figure 15: Evolution of the size of the blobs as a function of **a**) temperature; **b**) the concentration in ZnO (at 407 RT)

3. Conclusion 408

409 Correlation between structural properties of glasses to different kind of macroscopic physic 410 one has been one of the most important field of research on glasses for years. In this study, 411 some interesting facts have been pointed out.

412 By comparing RFDA experiments and Raman spectroscopy, it has been possible to 413 understand the structural properties of a glass having a complex structure with two entities that 414 have a coordination number which change as a function of the TeO2 and ZnO content. (i) As usual Raman spectroscopy gave informations on the change of the Te-O polyedra inside the 415

- 416 glass, (ii) RFDA experiment gave an understanding on the strength of the different bonds as a
- 417 function of the concentration, and (*iii*) from both Raman and RFDA experiments by calculating
- the blobs size, the structural evolution of the glass at intermediate-distance has been evidenced.
 Lastly, the behavior of the samples after the glass transition temperature has been evidenced

420 and links to the particular behavior of Zinc polyhedra were noted. Indeed, the variation of the

421 alpha coefficient of the mechanical properties studied by RFDA experiment, the variation of

- 422 the slope after Tg of the Brillouin experiment and the variation of the slope of the shift in
- 423 wavenumber of the Boson peak recorded in Raman spectroscopy, some anomalies stood out
- 424 exactly at the same ZnO content : 17.5% ZnO and 22.5% ZnO.
- 425 Concerning mechanical properties, a higher slope value after the glass transition means that426 the decrease of the mechanical properties is faster
- In Raman spectroscopy, a shift toward lower wavenumber means that the blobs size
 increases. So a higher slope value after the glass transition means that the blobs size increases
 at a higher rate.

From the two previous point, it can be porposed that: when the blobs size increase at a faster rate, the mechanical properties will decrease at a slower rate. Thanks to this hypothesis, it will

- 431 rate, the mechanical properties will decrease at a slower rate. Thanks to this hypothesis, it will 432 be easier to predict how the mechanical properties will evolve at temperature close and higher
- 433 than Tg which will be helpful for optical fiber shaping.

434 4. Acknowledgement

The authors thank Dr. J. Cornette for valued assistance with Raman experiments and O.
Noguera for his help on Raman spectra simulation. J. de CLERMONT-GALLERANDE also
gratefully acknowledges the financial support from Conseil Régional du Limousin and the
PICS.

439 Bibliography

- R. A. H. El-Mallawany, *Tellurite glasses handbook: physical properties and data*, 2nd ed.
 Boca Raton, FL: Taylor & Francis, 2011.
- 442 [2] A. P. Mirgorodsky, M. Soulis, P. Thomas, T. Merle-Méjean, and M. Smirnov, "*Ab initio* 443 study of the nonlinear optical susceptibility of Te O 2 -based glasses," *Phys. Rev. B*, vol. 444 73, no. 13, Apr. 2006.
- J. S. Wang, E. M. Vogel, and E. Snitzer, "Tellurite glass: a new candidate for fiber devices," *Opt. Mater.*, vol. 3, no. 3, pp. 187–203, Aug. 1994.
- 447 [4] S.-H. Kim, T. Yoko, and S. Sakka, "Linear and Nonlinear Optical Properties of TeO₂
 448 Glass," *J. Am. Ceram. Soc.*, vol. 76, no. 10, pp. 2486–2490, Oct. 1993.
- M. Soulis *et al.*, "Local molecular orbitals and hyper-susceptibility of TeO₂ glass," *J. Non-Cryst. Solids*, vol. 354, no. 2–9, pp. 199–202, Jan. 2008.
- 451 [6] J.-R. Duclère *et al.*, "Third order nonlinear optical properties of a paratellurite single 452 crystal," *J. Appl. Phys.*, vol. 123, no. 18, p. 183105, May 2018.
- P. T. Sarjeant and R. Roy, "New Glassy and Polymorphic Oxide Phases Using Rapid
 Quenching Techniques," *J. Am. Ceram. Soc.*, vol. 50, no. 10, pp. 500–503, Oct. 1967.
- M. Udovic *et al.*, "Thermal characteristics, Raman spectra and structural properties of new tellurite glasses within the Bi2O3–TiO2–TeO2 system," *J. Solid State Chem.*, vol. 179, no. 10, pp. 3252–3259, Oct. 2006.
- 458 [9] M. Udovic *et al.*, "Formation domain and characterization of new glasses within the Tl2O– 459 TiO2–TeO2 system," *Mater. Res. Bull.*, vol. 44, no. 2, pp. 248–253, Feb. 2009.

- 460 [10] D. Linda *et al.*, "New glasses within the Tl2O–Ag2O–TeO2 system: Thermal
 461 characteristics, Raman spectra and structural properties," *Mater. Res. Bull.*, vol. 45, no.
 462 12, pp. 1816–1824, Dec. 2010.
- [11] O. Noguera, T. Merle-Méjean, A. P. Mirgorodsky, P. Thomas, and J.-C. ChamparnaudMesjard, "Dynamics and crystal chemistry of tellurites. II. Composition- and temperaturedependence of the Raman spectra of x(Tl2O)+(1-x) Te2O glasses: evidence for a phase
 separation?," *J. Phys. Chem. Solids*, vol. 65, no. 5, pp. 981–993, May 2004.
- 467 [12] M. Dutreilh-Colas, P. Charton, P. Thomas, P. Armand, P. Marchet, and J. C.
 468 Champarnaud-Mesjard, "The TeO 2 -rich part of the TeO 2 –Ga 2 O 3 system: equilibrium
 469 and non-equilibrium phase diagram," *J Mater Chem*, vol. 12, no. 9, pp. 2803–2806, 2002.
- 470 [13] S. Blanchandin, P. Thomas, P. Marchet, J. C. Champarnaud-Mesjard, and B. Frit, "New
 471 heavy metal oxide glasses: investigations within the TeO₂-Nb₂O₅-Bi₂O₃ system," *J.*472 *Alloys Compd.*, vol. 347, no. 1–2, pp. 206–212, Dec. 2002.
- [14] B. Jeansannetas *et al.*, "Glass Structure and Optical Nonlinearities in Thallium(I)
 Tellurium(IV) Oxide Glasses," *J. Solid State Chem.*, vol. 146, no. 2, pp. 329–335, Sep.
 1999.
- 476 [15] M. Soulis, A. P. Mirgorodsky, T. Merle-Méjean, O. Masson, P. Thomas, and M. Udovic,
 477 "The role of modifier's cation valence in structural properties of TeO₂-based glasses," *J.*478 *Non-Cryst. Solids*, vol. 354, no. 2–9, pp. 143–149, Jan. 2008.
- [16] M. R. Zaki, D. Hamani, M. Dutreilh-Colas, J.-R. Duclère, O. Masson, and P. Thomas,
 "Synthesis, thermal, structural and linear optical properties of new glasses within the
 TeO₂-TiO₂-WO₃ system," *J. Non-Cryst. Solids*, vol. 484, pp. 139–148, Mar. 2018.
- 482 [17] S. kareem Ahmmad, M. A. Samee, A. Edukondalu, and S. Rahman, "Physical and optical
 483 properties of zinc arsenic tellurite glasses," *Results Phys.*, vol. 2, pp. 175–181, 2012.
- 484 [18] L. G. Van Uitert and S. H. Wemple, "ZnCl₂ glass: A potential ultralow-loss optical fiber 485 material," *Appl. Phys. Lett.*, vol. 33, no. 1, pp. 57–59, Jul. 1978.
- [19] T. Sekiya, N. Mochida, and A. Ohtsuka, "Raman spectra of MO-TeO₂ (M = Mg, Sr, Ba and Zn) glasses," *J. Non-Cryst. Solids*, vol. 168, no. 1–2, pp. 106–114, Feb. 1994.
- 488 [20] H. Bürger, K. Kneipp, H. Hobert, W. Vogel, V. Kozhukharov, and S. Neov, "Glass
 489 formation, properties and structure of glasses in the TeO₂-ZnO system," *J. Non-Cryst.*490 Solids, vol. 151, no. 1–2, pp. 134–142, Dec. 1992.
- 491 [21] C. Duverger, M. Bouazaoui, and S. Turrell, "Raman spectroscopic investigations of the
 492 effect of the doping metal on the structure of binary tellurium-oxide glasses," *J. Non-*493 *Cryst. Solids*, vol. 220, no. 2–3, pp. 169–177, Nov. 1997.
- 494 [22] U. Hoppe, E. Yousef, C. Rüssel, J. Neuefeind, and A. C. Hannon, "Structure of zinc and
 495 niobium tellurite glasses by neutron and x-ray diffraction," *J. Phys. Condens. Matter*, vol.
 496 16, no. 9, p. 1645, 2004.
- 497 [23] V. Kozhukharov, H. Bürger, S. Neov, and B. Sidzhimov, "Atomic arrangement of a zinc-tellurite glass," *Polyhedron*, vol. 5, no. 3, pp. 771–777, Jan. 1986.
- 499 [24] J. G. Thorbahn and J. W. Zwanziger, "Compositional dependence of the stress-optic
 500 response in zinc tellurite glasses," *J. Non-Cryst. Solids*, vol. 381, pp. 48–53, Dec. 2013.
- 501 [25] N. Ghribi *et al.*, "Thermal, optical and structural properties of glasses within the 502 TeO2TiO2ZnO system," *J. Alloys Compd.*, vol. 622, pp. 333–340, Feb. 2015.
- 503 [26] ASTM International, "Standard Test Method for Dynamic Young's Modulus, Shear
 504 Modulus and Poisson's Ratio by Impulse Excitation of Vibration." ASTM E1876- 01,
 505 2006.
- I. Kabalci, N. Ö. Körpe, T. Duran, and M. Özdemir, "Optical properties and crystallization kinetics of (TeO₂)(ZnO)(TiO₂) glasses: Optical properties and crystallization kinetics of (TeO₂)(ZnO)(TiO₂) glasses," *Phys. Status Solidi C*, vol. 8, no. 9, pp. 2629–2632, Sep. 2011.

- 510 [28] D. de Sousa Menses, *FOCUS version 1.0, software utility for the creation of optical* 511 *function.*.
- 512 [29] N. Ghribi *et al.*, "Structural, mechanical and optical investigations in the TeO2-rich part
 513 of the TeO2–GeO2–ZnO ternary glass system," *Solid State Sci.*, vol. 40, pp. 20–30, Feb.
 514 2015.
- [30] A. Veber, M. R. Cicconi, H. Reinfelder, and D. de Ligny, "Combined Differential scanning calorimetry, Raman and Brillouin spectroscopies: A multiscale approach for materials investigation," *Anal. Chim. Acta*, vol. 998, pp. 37–44, Jan. 2018.
- 518 [31] K. Hanke, "Die Kristallstruktur von $Zn_2Te_3O_8$," *Naturwissenschaften*, vol. 53, no. 11, pp. 273–273, 1966.
- [32] K. Hanke, "Zinktellurit: Kristallstruktur und Beziehungen zu einigen Seleniten,"
 Naturwissenschaften, vol. 54, no. 8, pp. 199–199, 1967.
- [33] N. Ghribi, Synthesis, structural and mechanical investigations of new tellurite materials
 for non-linear optical applications. Limoges, 2015.
- [34] M. B. Smirnov and V. Y. Kazimirov, "LADY: Software for lattice dynamics simulations,"
 JINR Commun., vol. E14, p. 159, 2001.
- [35] E. Duval *et al.*, "Inelastic light, neutron, and X-ray scattering related to the heterogeneous
 elasticity of glasses," *J. Non-Cryst. Solids*, vol. 307–310, pp. 103–108, Sep. 2002.
- 528 [36] B. Champagnon, L. Wondraczek, and T. Deschamps, "Boson peak, structural inhomogeneity, light scattering and transparency of silicate glasses," *J. Non-Cryst. Solids*, vol. 355, no. 10–12, pp. 712–714, May 2009.
- 531 [37] E. Duval, A. Boukenter, and T. Achibat, "Vibrational dynamics and the structure of 532 glasses," *J. Phys. Condens. Matter*, vol. 2, no. 51, pp. 10227–10234, Dec. 1990.
- [38] S. R. Elliott, "A Unified Model for the Low-Energy Vibrational Behaviour of Amorphous
 Solids," *Europhys. Lett. EPL*, vol. 19, no. 3, pp. 201–206, Jun. 1992.
- [39] P. Mezeix, F. Célarié, P. Houizot, Y. Gueguen, F. Muñoz, and T. Rouxel, "Elasticity and viscosity of BaO-TiO₂-SiO₂ glasses in the 0.9 to 1.2Tg temperature interval," *J. Non-Cryst. Solids*, vol. 445–446, pp. 45–52, Aug. 2016.
- [40] J. B. Wachtman, W. E. Tefft, D. G. Lam, and C. S. Apstein, "Exponential Temperature
 Dependence of Young's Modulus for Several Oxides," *Phys. Rev.*, vol. 122, no. 6, pp.
 1754–1759, Jun. 1961.
- [41] T. Rouxel, "Elastic Properties and Short-to Medium-Range Order in Glasses," J. Am. *Ceram. Soc.*, vol. 90, no. 10, pp. 3019–3039, Oct. 2007.
- 543 [42] G. N. Greaves, A. L. Greer, R. S. Lakes, and T. Rouxel, "Poisson's ratio and modern 544 materials," *Nat. Mater.*, vol. 10, no. 11, pp. 823–837, Nov. 2011.
- 545