

Graphene oxide chemically reduced and functionalized with KOH-PEI for efficient Cr(VI) adsorption and reduction in acidic medium

Yasmine Tadjenant, Nahed Dokhan, Alexandre Barras, Ahmed Addad, Roxana Jijie, Sabine Szunerits, Rabah Boukherroub

▶ To cite this version:

Yasmine Tadjenant, Nahed Dokhan, Alexandre Barras, Ahmed Addad, Roxana Jijie, et al.. Graphene oxide chemically reduced and functionalized with KOH-PEI for efficient Cr(VI) adsorption and reduction in acidic medium. Chemosphere, 2020, 258, pp.127316. 10.1016/j.chemosphere.2020.127316 . hal-03089825

HAL Id: hal-03089825 https://hal.science/hal-03089825

Submitted on 21 Jun 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Version of Record: https://www.sciencedirect.com/science/article/pii/S0045653520315095 Manuscript_739d9bb8a77c81b8795863de128b9543

1	Graphene oxide chemically reduced and functionalized with KOH-PEI for
2	efficient Cr(VI) adsorption and reduction in acidic medium
3	
4	
5	Yasmine Tadjenant, ^{1,2} Nahed Dokhan, ² Alexandre Barras, ¹ Ahmed Addad, ³ Roxana Jijie, ¹
6	Sabine Szunerits ¹ and Rabah Boukherroub ¹ *
7	
8	
9	¹ Univ. Lille, CNRS, Centrale Lille, Univ. Polytechnique Hauts-de-France, UMR 8520 -
10	IEMN, F-59000
11	Lille, France
12	² Research Unit, Materials, Processes and Environment (URMPE), University of Boumerdes,
13	Algeria
14	³ Univ. Lille, CNRS, UMR 8207 – UMET, F-59000 Lille, France
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	*To whom correspondence should be addressed: Rabah Boukherroub
25	(rabah.boukherroub@univ-lille.fr; Tel: +333 62 53 17 24)

26 Abstract

In this study, graphene oxide (GO), polyethyleneimine (PEI) and potassium hydroxide (KOH) 27 were used to synthesize reduced graphene oxide (rGO/PEI-KOH) nanocomposite. The 28 presence and grafting of PEI molecules on the reduced GO surface were assessed by X-ray 29 photoelectron spectroscopy (XPS) and Fourier transform infrared (FTIR) analyses. The 30 rGO/PEI-KOH nanocomposite was successfully applied for hexavalent chromium, Cr(VI), 31 wastewater elimination. The resulting rGO/PEI-KOH adsorbent was found to be highly 32 effective for Cr(VI) removal at low pH values and achieved a maximum capacity of 33 experimental adsorption of 398.9 mg/g, which is one of the highest sorption capacity of most 34 35 GO- and PEI-based adsorbents reported in the literature up to date. Studying the adsorption mechanism, the sorption isotherm revealed that the modified-Langmuir model was the best fit 36 37 and Cr(VI) removal follows a pseudo-second-order kinetics, with the predominance of 38 intraparticle diffusion during the first step of adsorption. XPS analysis indicated the presence of appreciable amount of Cr(III) on the adsorbent surface, which suggests that the adsorbed 39 40 Cr(VI) ions were effectively reduced to Cr(III) on the rGO/PEI-KOH adsorbent surface (~70% of the total adsorbed Cr). Cr(VI) adsorption and subsequent reduction to Cr(III) both 41 contributed to the Cr(VI) removal. The results of the present study highlight the benefits of 42 rGO/PEI-KOH like low cost, environmentally friendly, large toxic Cr(VI) ions adsorption 43 capacity and its effective reduction to less-toxic Cr(III). 44

- 48
- 49
- 50

Keywords: Reduced graphene oxide; Polyethylenimine; Cr(VI) adsorption; High adsorption capacity; Cr(VI) reduction.

1. Introduction

52 Chromium is one of the most toxic heavy metals discharged into the environment and 53 constitutes one of the main causes of environmental pollution associated with a non-negligible 54 health problem. It commonly originates from diverse industrial wastewaters, derived from 55 factories of electroplating, tanning, textile dyeing, stainless steel production, water cooling, 56 and other industries (Barnhart, 1997).

57 Chromium is usually found in trivalent (III) as well as hexavalent (VI) states. While 58 Cr(VI) is highly toxic and can lead to severe illnesses such as dermatitis, kidney failure, lung 59 cancer and even death, Cr(III) is less toxic and represents an important element for the proper 60 functioning of living organisms (Zhou et al., 2016). Therefore, Cr(VI) is viewed as a critical 61 polluting agent and is listed by the US Environmental Protection Agency as class A human 62 carcinogen (US-EPA1998). Hence, eliminating Cr(VI) from wastewater or reducing it to 63 Cr(III) prior to discharge into the environment is imperative.

Several methods have been developed for the removal of Cr(VI) from aqueous media, 64 65 including physical (washing or electrical enrichment), biological (plant enrichment), and chemical (adsorption and reduction) approaches. However, most of these methods and 66 particularly the physical and biological processes experience several limitations such as 67 complexity of operation and elevated costs, and require long periods of time, which has 68 significantly impeded their use in Cr(VI) treatment. In contrary, the chemical method is a 69 favored technique because of its flexibility, high efficiency, design and operational simplicity 70 for the elimination of Cr(VI) and thus it is attracting increasing attention (Zhou et al., 2016; 71 Wang et al., 2017). 72

In chemical methods, various adsorbents have been identified to withdraw Cr(VI) from
polluted water, such as activated carbon (Sandhya and Tonni, 2004), KOH-modified
carbonized eucalyptus sawdust (Zhang et al., 2018a), PEI-modified biomass (Deng and Ting,

2005), mesoporous carbon microspheres (Zhou et al., 2016), iron nanoparticle-decorated 76 graphene (Jabeen et al., 2011), etc. However, biosorbents have often low surface area and 77 limited mechanical resistance, causing additional potential secondary emissions in extreme 78 79 conditions. On the other hand, bare metallic nanoparticles are readily oxidizable and can easily agglomerate, while carbon-based adsorbents display a relatively low adsorption 80 capacity. Such forms of disadvantages have impeded their use for Cr(VI) elimination from 81 wastewater (Ma et al., 2012; Zhang et al., 2018b). Therefore, the development of new 82 materials with a large surface area, high removal efficiency, stability in extreme conditions 83 and easy separation procedure is very attractive. 84

Most recently, chemical methods for the synthesis of adsorbents exhibiting high 85 performance for simultaneous adsorption and reduction of Cr(VI) turns to an applicable 86 research hotspot (Ma et al., 2012; Wang et al., 2017; Zhang et al., 2018b). Graphene oxide 87 88 (GO), consisting of a monolayer of carbon atoms covalently bonded, forms one of the currently most investigated two-dimensional nanomaterial. GO displays an ultra large active 89 90 surface area and plentiful of oxygen containing functional groups (e.g., -OH, -C=O, -COOH). 91 Reduced GO (rGO), obtained from GO reduction using different means, has been investigated as an efficient adsorbent for Cr(VI) thanks to its high capacity of adsorption (He et al., 2017; 92 Pakulski et al., 2018). 93

KOH reduction of GO was firstly reported by Fan et al. (Fan et al., 2008) who noticed that
a chemically stable suspension of graphene can be easily prepared by a simple heating of
exfoliated graphite oxide at mild temperatures (50-90°C) in strongly alkaline conditions. But
no noticeable works has been reported on the Cr(VI) adsorption/reduction by GO treated with
KOH.

Polyethyleneimine (PEI) with plenty of primary and secondary amine groups present in a
macromolecular chain can partially reduce and simultaneously functionalize GO (Shao et al.,

2016). PEI-functionalized GO exhibits interesting adsorption ability for removing toxic
cations (Pakulski et al., 2018).

Compared with chemical reduction using strong and toxic agents like hydrazine and 103 104 sodium borohydride, chemical reduction with KOH or PEI is less efficient for completely eliminating the oxygen-containing functional groups on GO, but they have the advantage of 105 being environmentally friendly. Additionally, their simultaneous use may be interesting as in 106 chemical reduction processes of GO, elimination of oxygen groups is generally selective 107 108 depending on the reducing reagent used (Hayes et al., 2014; Nia et al., 2017). Hence, combining two soft reducing chemicals may represent an efficient manner to optimize 109 deoxygenation of GO sheets, while simultaneously functionalizing the resulting rGO. 110

In the present work, a strong KOH solution containing PEI as a reducing and functionalizing agent is proposed to prepare a nanocomposite material, rGO/PEI-KOH, under mild reaction conditions. The resulting rGO/PEI-KOH was investigated for Cr(VI) elimination. The rGO/PEI-KOH not only exhibited high adsorption capacity, but it was able to effectively reduce the adsorbed Cr(VI) to low toxic Cr(III) ions.

116

- 117 **2.** Experimental
- 118 **2.1. Materials**


119 Polyethylenimine (PEI, MW~25,000), potassium hydroxide (KOH), potassium dichromate 120 ($K_2Cr_2O_7$), and hydrogen chloride (HCl) were purchased from Sigma-Aldrich. Graphene 121 oxide (GO) powder was obtained from Graphenea-Spain. Milli-Q water (resistivity: 18.2 122 MQ.cm) was utilized throughout this work.

123

2.2. Preparation of rGO/PEI-KOH nanocomposite

An easy preparation technique of rGO/PEI-KOH was established in this work. In short, 20 mgof GO was added to 18 mL of water and sonicated for 1 h to form a homogeneous solution.

Then, 2 mL of PEI aqueous solution (1 mg/mL) was added. The resulting suspension was
mixed under vigorous stirring for 5 h at room temperature. Thereafter, 40 mg of KOH was
added to the mixture and stirred at 90°C for 24 h. The color of the dispersion changed from
yellow-brown to black, signifying the transformation of GO to reduced graphene oxide (rGO).
The obtained black precipitate was isolated by centrifugation (4600 rpm) and washed
copiously with water and ethanol to remove excess of PEI and KOH. Finally, the rGO/PEIKOH was obtained and dried at 80°C for overnight (Scheme 1).



- 133
- 134

Scheme 1. Schematic illustration of rGO/PEI-KOH preparation.

135

136 **2.3.** Cr(VI) removal experiments

137 A stock solution of Cr(VI) (20 mg/mL) was obtained by dissolving K₂Cr₂O₇ in Milli-Q water. The stock solution was diluted to prepare different concentrations. We varied the initial 138 concentration of Cr(VI) from 50 to 700 mg/L, the pH from 2 to 9, the dosage of adsorbent 139 140 from 0.5 to 2.5 mg/mL, and the contact time from 10 to 1440 min. 0.1 M HCl or 0.1 M NaOH aqueous solution was used to adjust the pH value. All adsorption experiments were performed 141 142 at ambient temperature. Adsorption experiments were performed by adding 2 mg of rGO/PEI-KOH into 2 mL of Cr(VI) aqueous solution. After being shaken for 24 h, the solution was 143 subjected to centrifugation at 13,500 rpm during 5 min and finally UV-vis spectrophotometry 144 145 was used to determine the residual concentration of Cr(VI) in the supernatant at the maximum absorption wavelength of 348 nm in acidic pH and at 372 nm in alkaline pH. 146

147 The effect of initial Cr(VI) amount, pH, and contact time on the efficiency of Cr(VI) 148 elimination was investigated. Afterwards, the percentage of removal R (%) and the capacity 149 of adsorption (Qe, mg/g) of Cr(VI) were calculated using equations (1) and (2), respectively:

150
$$R(\%) = \left(\frac{C_0 - C_e}{C_0}\right) \times 100$$
 (1)

$$Q_e = (C_0 - C_e)V/M \tag{2}$$

Where $C_0 \text{ (mg/L)}$ is the initial concentration of Cr(VI) ions, $C_e \text{ (mg/L)}$ is the equilibrium concentration of Cr(VI) ions, Qe (mg/g) is the capacity of adsorption, V(L) is the initial volume of Cr(VI) solution, and M (g) is the mass of the as-elaborated rGO/PEI-KOH.

155

156 **3. Results and discussion**

157 **3.1. Morphological and chemical analysis**

Figure 1 depicts the SEM images of rGO/PEI-KOH at different magnifications. It reveals 158 wrinkled flakes aspect of thin and random rGO/PEI-KOH sheets; the nanosheets are visibly 159 160 crumpled in an agglomerated phase. The presence of these many wrinkles is most likely due to the suppression of the large quantities of negatively charged functional oxygen groups 161 previously covering the GO during the thermal reaction with PEI-KOH. Indeed, the reduction 162 of GO, as suggested by the UV-Vis, FTIR and XPS analyses (discussed in the next section), 163 led to the partial reconstruction of the graphenic network; the sheets then tend to aggregate in 164 order to diminish the free energy (Huang et al., 2018). Additionally, hydrogen bonding 165 between the remaining oxygen and the amine groups of PEI might result in these crumpled 166 rGO sheets. 167




Figure 1. SEM images of rGO/PEI-KOH composite at low and high magnifications.

On the transmission electron microscopy (TEM) images of Figure 2, wrinkled graphene 170 sheets (dark areas) are visible. The images also indicate that the graphene sheets were etched 171 172 during the hydrothermal reduction-functionalization of GO; traces of nanopores can be seen in Figure 2 (Lu et al., 2012; Sun et al., 2012). The nanopores formation is not fully clarified 173 in this work as usually GO becomes porous during a process where strong radicals like 174 hydroxyl radicals (OH) are produced locally in the vicinity of rGO surface; these radicals are 175 176 known to have ability to break the C–C (sp^2) bonds in the graphene sheet, causing its porosity and could even break GO into ultra-small graphene oxide of zero dimensions (Zhao et al., 177 2017). Many oxidation processes are able to produce these highly reactive hydroxyl radicals, 178 such as photocatalysis, Fenton reactions, ozone, radiolysis, electron beam irradiation, 179 sonolysis (Wu and Shi, 2010) and high voltage electrical discharge (Sahni and Locke, 2006). 180 181 However, these strong radicals could also intervene during elaboration under hydrothermal conditions in basic media, as reported by Feng et al., (Feng et al., 2016). 182





Figure 2. TEM images of rGO/PEI-KOH sheets at low and high magnifications.

The reduction of GO was monitored by UV-vis spectrophotometry. As shown in Figure 3, 195 GO displays two bands at 235 nm due to the π - π * transition of aromatic C=C bonds, and 310 196 nm ascribed to the $n-\pi^*$ transition of C=O bonds (Fellahi et al., 2011). After PEI-KOH 197 reduction-functionalization for 24 h, the peak related to the π - π * transition initially at 235 nm 198 shifted to 258 nm; this red-shift in absorption peak takes place when the π electron 199 conjugation is restored within the sheets of graphene. Furthermore, the shoulder in the 200 201 spectrum disappears, signifying an important decrease of C=O bonds; these two features indicate the partial reduction of GO during the hydrothermal process. 202




203

Figure 3. UV–vis spectra of GO and rGO/PEI-KOH in water. The inset exhibits the digital
 photographs of GO, GO-PEI and rGO/PEI-KOH dispersion in water.

Figure 4 shows the FTIR spectra of GO, PEI and rGO/PEI-KOH FTIR. The following functional groups were established in the FTIR spectrum of GO sample: O-H stretching vibrations in COOH group and/or intercalated water (3381cm⁻¹), C=O stretching vibration

(1736 cm⁻¹), aromatic stretching vibration of C=C bonds (1623 cm⁻¹), and C-O vibrations of
epoxy and alkoxy groups at 1228 and 1056 cm⁻¹, respectively (Budimir et al., 2019).

After reduction-functionalization by PEI-KOH treatment, peak intensities associated with 212 oxygen containing groups (O-H and C-O stretching vibrations) diminished significantly, 213 which is a signature of effective GO reduction. In addition, the typical absorption features of 214 the PEI at 2898 and 2970 cm⁻¹ corresponding respectively to symmetric and asymmetric C-H 215 stretching from the -CH₂ group of PEI were visible (Budimir et al., 2019). Moreover, the band 216 217 at 1736 cm⁻¹ nearly disappeared, and a new band attributed to the stretching vibration of N-H (in the C–NH group) appeared at 1575 cm⁻¹ (Ramanathan et al., 2005; Budimir et al., 2019). 218 Other observed peaks at around 1085 and 876 cm⁻¹ are assigned to C-N bond stretching 219 vibrations and CH₂ rock + N-H[⊥] bending, respectively (York et al., 2003). These results 220 clearly confirm that the GO was effectively reduced during the hydrothermal process and the 221 222 PEI molecules were attached to the rGO sheets.



224

Figure 4. FTIR spectra of GO, PEI, and rGO/PEI-KOH.



The elemental composition of the as-elaborated PEI-KOH reduced-functionalized GO was 226 examined using X-ray photoelectron spectroscopy (XPS). Figure 5(a) depicts the XPS 227 spectra of GO and rGO/PEI-KOH. The spectrum of GO essentially comprises the C_{1s} and O_{1s} 228 peaks at ~285 and ~532 eV, respectively. The peaks in the rGO/PEI-KOH XPS wide scan 229 located at 285, 400 and 531 eV are ascribed to C_{1s}, N_{1s} and O_{1s}, respectively. The occurrence 230 231 of tiny peaks attributable to K_{2p} and K_{1s} in the XPS spectrum originates most likely from potassium adsorption. Furthermore, the intensity of the oxygen peak was greatly reduced in 232 the rGO/PEI-KOH as compared to GO, indicating an efficient reduction of GO by KOH-PEI 233 treatment. The presence of a peak at 400 eV due to N_{1s} proves the successful grafting of PEI 234 on the rGO sheets (Liu et al., 2013; Budimir et al., 2019). The atomic percentages of each 235 element (C, O and N) in GO and rGO/PEI-KOH are summarized in Table 1. 236

The core level of the C_{1s} of GO can be deconvoluted into three distinct peaks centered at 237 238 284.8, 286.8 and 288.3 eV, which correspond to unoxidized graphite carbon skeleton (C-C), hydroxyl/epoxide groups (C–O) and carboxyl groups (C=O), respectively (Figure 5b) (Li et 239 240 al., 2001; Liu et al., 2013). The reduction of GO is mainly indicated by three peaks in the C_{1s} 241 core-level spectrum (Figure 5c) showing the same functional groups, but with decreased intensities of the groups containing oxygen: the sp²-hybridized carbon atoms of graphene (C-242 Csp²) at 284.6 eV, the carbon in hydroxyl and epoxide groups (C-O) at 286.5 eV, the 243 carbonyl groups (C=O) at 287.8 eV, and the carboxyl (OH-C=O) groups at 288.9 eV (Liu et 244 al., 2013). The band at 285.3 eV is assigned to C-N of the PEI molecules (Shao et al., 2016). 245

The N_{1s} high resolution peak showed a single component after fitting due to amine groups
from PEI (Figure 5d).

248

249

 Table 1. Elemental atomic percentage determined using the XPS spectra.

Composite	C _{1s} at.%	O _{1s} at.%	N _{1s} at.%

GO	69.93	30.07	-
rGO/PEI-KOH	80.13	16.68	3.19




Figure 5. (a) XPS survey spectra of GO and rGO/PEI-KOH; core level spectra of (b) C_{1s} of
GO, (c) C_{1s} and (d) N_{1s} of rGO/PEI-KOH.


The existence of a significant amount of K was identified by the presence of imposing peaks at 292.9 and 295.7 eV in **Figure 5c**. Since the binding energy discrepancy between these two peak components is ca. 2.8 eV, and their intensity ratio is ca. 2:1, they are attributed to the spin-orbit-split doublet $K_{2p1/2}$ and $K_{2p3/2}$, respectively of potassium cations and oxides (Li et al., 2001). This suggests that potassium ions probably bind to the remaining oxygen atoms or are intercalated within rGO sheets.

Raman spectroscopy is a powerful and widely employed technique for characterizing 262 graphene based structures involving disorder and defects (Fang et al., 2013). The Raman 263 spectra of GO and rGO/PEI-KOH are depicted in Figure 6. They indicate important structural 264 changes in graphene sheets before and after treatment with PEI-KOH. It can be seen that the 265 D peaks (disorder induced symmetry A1g mode) of GO and rGO/PEI-KOH are located at 266 1360 and 1357.3 cm⁻¹, respectively, while the G bands (due to the E_{2g} mode associated with 267 the bond stretching of sp²-bonded carbon atoms in hexagonal, two-dimensional lattices) are at 268 1589.4 and 1590 cm^{-1} , respectively. 269

It is worth noting that the chemical changes in graphene-based materials are marked by 270 variations in the D and G band ratios; these variations in the relative intensities of the D and G 271 bands (D/G) reflect modifications in GO electronic conjugation state during the reduction-272 functionalization phase. Commonly, the ratio I_D/I_G serves to quantify the disorder level in 273 274 graphene and rGO; this disorder can be related to vacations, impurities, dislocation, dangling bonds at the edges of the rGO sheets and to the decrease of the average size of the sp² 275 domains, but can also be the signature of an augmentation of the C sp³ hybridization caused 276 277 by molecules grafted to the 2-D hexagonal carbon lattice. After the reductionfunctionalization of GO with PEI-KOH, the intensity ratio I_D/I_G rises from 0.79 for GO to 278 1.13 for rGO/PEI-KOH. Usually, reducing GO consists mainly in the elimination of the 279 oxygen functional groups (these later are known to induce sp³ hybridization of the carbon 280 atoms) from the graphene sheet; when the GO is reduced, sp³ hybridization diminishes, and 281 the graphene sheet is more or less restored, which is generally accompanied by a diminution 282 in the I_D/I_G ratio. This is not the case in this work as a non-negligible augmentation of I_D/I_G is 283 observed despite the fact that oxygen functionalities have been significantly eliminated as it 284 was proven by XPS and FTIR analyses. We can speculate two reasons for this increase in 285 I_D/I_G ratio: either it highlights the large presence of sp³ carbon atoms on GO due the grafting 286

of PEI molecule, a signature of the mesoporosity and/or a decrease in the average size of the
sp² domains in rGO sheets (Fang et al., 2013; Liu et al., 2013; Tong et al., 2015; Singh et al.,
2017; Pakulski et al., 2018).

Also the red-shift of the D-band (from 1360 to 1357.3 cm⁻¹) testifies the actual functionalization of reduced GO (Budimir et al., 2019). Such results confirm that PEI was effectively grafted on the rGO layer during the reduction-functionalization process; these results are well consistent with the FTIR and XPS data.



294

295

Figure 6. Raman spectra of GO and rGO/PEI-KOH.

296

The thermal behavior of the rGO/PEI-KOH was evaluated by thermogravimetric and 297 differential thermogravimetric (TG/DTG) analysis. Figure S1 exhibits the TG analysis curve 298 of the as-prepared rGO-PEI-KOH, displaying different weight losses within the temperature 299 range tested. The initial weight drop (15.4%) between ambient temperature and 150°C is 300 more possibly caused by the evaporation of adsorbed water molecules. A second weight loss 301 (7.4%), observed in the range 150-270°C, is related to the removal of oxygen-containing 302 functional groups. Finally, the weight loss (12.8%) in the 270–550°C temperature range 303 corresponds to the covalently bonded PEI molecules pyrolysis, suggesting that the rGO 304


surface was modified by PEI (Liu et al., 2013). The results confirm again the surface grafting
of PEI molecules on rGO sheets.

307

308 3.2. Cr(VI) elimination performance of the rGO/PEI-KOH composite

309 3.2.1 Effect of adsorbent dosage

The effect of adsorbent dosage on the Cr(VI) removal, for a fixed pollutant concentration of 100 mg/L, was investigated and the results are displayed in **Figure 7**. The percentage of removal increases from 87.78 to 100% by increasing the adsorbent dosage from 0.5 to 2.5 mg/mL. For adsorbent dosage from 0.5 to 1 mg/mL, the removal efficiency increases until reaching ~100%; this means that the more adsorbent in the solution, the higher the availability of exchangeable sites for metal ions (Sandhya and Tonni, 2004).



316

Figure 7. Effect of rGO/PEI-KOH dosage on the capacity of adsorption (Q_e) and removal
efficiency (R) (initial Cr(VI) concentration: 100 mg/L, pH 2, room temperature, contact time:
24 h).

On the other hand, the adsorption capacity Qe shows a clear decrease, suggesting a possible formation of microscopic agglomerates of rGO/PEI-KOH sheets that would reduce the access to all adsorption sites. Exceeding the adsorbent dosage of 1 mg/mL, the removal efficiency remains roughly at ~100%, while the adsorption capacity continues dropping; this is expected
given the presence of more adsorbent than what is necessary to remove all the pollutant.

325

326 **3.2.2 pH effect**

The adsorption tests were carried out at an initial concentration of Cr(VI) of 100 mg/L, a 327 24 h contact time, an adsorbent dosage of 1 mg/mL, in the pH range from 2 to 9 at room 328 temperature. The solution pH greatly affects the stability of Cr(VI) species and the adsorbent 329 charge, thereby affecting the adsorption efficiency. Figure 8a illustrates the predominance 330 diagram of K₂Cr₂O₇ in water at different pH values. It indicates that the prevailing forms of 331 Cr(VI) ion in solution are chromate $(CrO_4)^{2-}$, dichromate $(Cr_2O_7)^{2-}$, and hydrogen chromate 332 (HCrO₄)⁻ and predominant ions are related to the solution pH and overall concentration of 333 chromate. Cr(VI) is in the form of anionic species, like HCrO₄⁻ (pH range 2.0–7.0) and 334 CrO_4^{2-} (pH range 7.0–10.0) (Fan et al., 2012) are the dominant species. 335

Figure 8b displays the zeta potential of rGO/PEI-KOH at different pH values. The 336 337 rGO/PEI-KOH sheets are globally negatively charged even they are grafted with PEI 338 molecules, which are positively charged at low pH. Indeed, the amine groups are protonated under strong acidic conditions, which is beneficial for the Cr(VI) anions adsorption through 339 electrostatic interactions. In contrast, uncharged (-NH₂) or deprotonated (-NH⁻) groups, 340 occurring under basic conditions, will repel these anions thus inhibiting their adsorption. On 341 the other hand, the overall negative charge of the adsorbent sheets remains beneficial, and 342 even necessary, as it will supply the adsorbent with H⁺ ions necessary for the Cr(VI) 343 reduction, as we will be seen in the last section (Luo et al., 2017; Wang et al., 2017). 344

Figure 8c depicts the adsorption capacity at different pH values. We can notice the absence of Cr(VI) removal by rGO/PEI-KOH for a pH value higher or equal to 3. Indeed, upon increasing the pH from 3 to 9, the divalent CrO_4^{2-} amount rises by gradual conversion of

HCrO₄⁻; also the protonation degree of the surface is weakened under weak-acidic/basic
conditions, resulting in greater electrostatic repulsion between ions charged negatively and the
adsorbent surface (Zhou et al., 2016). Nevertheless, strong acid conditions corresponding to
pH lower or equal to 2 is beneficial for Cr(VI) elimination by rGO/PEI-KOH as it promotes
more positive amine groups and less negative Cr(VI) species.

Hence, the pH of the solution, which greatly influences the stability of Cr(VI) species and the electrostatic charge of the adsorbent, impacts significantly the adsorption efficiency. The pH being the optimal one, was used for all subsequent experiments.





Figure 8. (a) Cr(VI) species predominance diagram as a function of pH; (b) Zeta potential of
 rGO/PEI-KOH; (c) Adsorption capacity at different pH (initial Cr(VI) concentration:
 100 mg/L, adsorbent dosage: 1 mg/mL, room temperature, contact time: 24 h).

362 **3.2.3 Initial concentration effect**

The influence of the initial Cr(VI) concentration on adsorption capacity of rGO/PEI-KOH 363 is depicted in Figure 9; the Cr(VI) ions are adsorbed favorably on the rGO/PEI-KOH surface 364 at pH 2. The adsorption capacity of rGO/PEI-KOH increases rapidly with increasing the 365 initial concentration of Cr(VI) from 100 to 700 mg/L, implying that there are enough 366 adsorption sites on the adsorbent and attesting the attraction effectiveness between the 367 protonated adsorbent and the hydrochromate anion. The results revealed that the Cr(VI) 368 maximum adsorption capacity of rGO/PEI-KOH is (398.9±16.9 mg/g) at room temperature, 369 which is greater than the capacity of PEI-modified graphene (324 mg/g), as shown in the last 370 371 section.



372

Figure 9. Effect of initial Cr(VI) concentration on the adsorption capacity (black) and the
removal efficiency (red) of rGO/PEI-KOH (pH 2, adsorbent dosage: 1 mg/mL, room
temperature, contact time: 24 h).

On the other hand, the removal efficiency decreases with the increase of Cr(VI) concentration. This is most likely related to the total available adsorption sites, since they are limited for a fixed adsorbent dose and consequently we approach saturation at a higher Cr(VI) concentration.

381 3.2.4 Adsorption isotherm study

The adsorption equilibrium data give very important information needed to understand the adsorption process correctly. The understanding of adsorption isotherms is important for optimizing the adsorption process pathways and implementing adsorption systems effectively (Ayawei et al., 2017). Hence, the linear and nonlinear forms of modified-Langmuir, Temkin, Freundlich and Dubinin-Radushkevich isotherm models were used to fit experimental data; C_e (mg/L) and Q_e (mg/g) are the equilibrium Cr(VI) concentration and adsorption capacity, respectively; the initial concentration of Cr(VI) is represented by C₀ (mg/L).

The classic Langmuir adsorption isotherm was derived for the gas phase adsorption process. It supposes a homogeneous surface where the binding sites have the same energy and affinity (equivalency of the adsorption sites) and where adsorption occurs in a monolayer; also it assumes that adsorbed molecules do not interact with each other (Langmuir, 1918; Luo et al., 2017). Recently, a modified Langmuir equation has proved to me more applicable for modeling liquid adsorption data. This model is given according to the following equations (Azizian et al., 2018):

$$\frac{C_e}{Q_e} = \frac{(K_{ML}-1)C_e}{K_{ML}Q_m} + \frac{C_s}{K_{ML}Q_m}$$
(3)

$$Q_e = \frac{Q_m K_{ML} C_e}{(C_s - C_e) + K_{ML} C_e} \tag{4}$$

398

397

Where Q_m is the maximum adsorption capacity, C_s is the saturation concentration of Cr(VI) in liquid-phase (45,000 mg/L) and K_{ML} is the constant of modified Langmuir.

By linear and nonlinear fittings, the Q_m capacity and K_{ML} constant are extracted from experimental data (**Figure 10a** and **10e**) and presented in **Table 2**; Q_m obtained is close to the experimental value (398.9 ±16.9 mg/g).

The modified-Langmuir isotherm parameters as well as the regression coefficient obtained (Table 2) suggest Adsorptive Interaction Effectiveness between the protonated rGO/PEI-KOH adsorbent and the hydrochromate anion.




Figure 10. Linear fitting of (a) modified-Langmuir, (b) Temkin, (c) Freundlich, (d) DubininRadushkevich and (e) nonlinear fitting of adsorption isotherm models (pH 2, adsorbent

412 dosage: 1 mg/mL, room temperature, contact time: 24 h).

413

421

The Temkin model of isotherm takes into-account the effects of the interaction between adsorbed molecules in the adsorption process. The adsorption energy (ΔH_{ads}) in this model displays a linear decrease when surface coverage rises, due to adsorbent–adsorbate interactions (Ayawei et al., 2017; Darabi et al., 2018). The following equations give the nonlinear and linear forms of the Temkin isotherm model (Temkin, 1941):

$$Q_e = ALn(K_T C_e) \tag{5}$$

$$Q_e = A \ln K_T + A \ln C_e \tag{6}$$

$$A = \frac{RT}{b} \tag{7}$$

Where A is related to the Temkin constant b corresponding to the adsorption heat, K_T is the Temkin isotherm equilibrium binding constant, R is the gas constant and T is the temperature (Darabi et al., 2018). K_T and A are extracted from the linear and nonlinear fittings (**Figure 10b and 10e**), whose values are reported in **Table 2**. The positive sign of b indicates an exothermic process (Ferrandon et al., 1995), and its value (27.19 kJ/mol) suggests that chemisorption may be an important part of the adsorption process (Ho et al., 2002).

The isotherm of Freundlich (Freundlich, 1906) is used when adsorption occurs on surfaces that are heterogeneous, showing a non-uniform adsorption heat distribution. The expression describing this isotherm encompasses the heterogeneity of the surface and the active sites (and their energy) exponential distribution. The Freundlich sorption isotherm is given by the equations (8, 9) (Ayawei et al., 2017; Darabi et al., 2018):

$$Q_e = K_F C_e^{1/n} \tag{8}$$

434
$$lnQ_e = \frac{1}{n} lnC_e + lnK_F \tag{9}$$

Where the constant K_F is related to the relative adsorption capacity of the adsorbent and n is a 435 constant indicating the adsorption intensity (the lower the 1/n value the stronger the 436 adsorption intensity (Darabi et al., 2018)). The linear and nonlinear fittings allow obtaining 437 easily these constants (Figure 10c and 10e) whose values are summarized in Table 2. The 438 isotherm of Freundlich is extensively used in heterogeneous systems, the value of (1/n)439 ranging from 0 to 1 may be an indicator of the degree of surface heterogeneity, surface being 440 more heterogeneous as (1/n) approaches zero (Foo and Hameed, 2010). The 1/n value 441 obtained here (0.33) is closer to zero than to unity and may imply a chemisorption process 442 (Foo and Hameed, 2010). 443

The Dubinin–Radushkevich (D-H) isotherm is usually used to describe the mechanism of adsorption onto a heterogeneous surface with a Gaussian energy distribution. Generally, this isotherm is expressed as follows (Ho et al., 2002; Foo and Hameed, 2010):

447 $Q_e = Q_D \exp(-B_D \varepsilon^2) \tag{10}$

$$lnQe = lnQ_D - B_D\varepsilon^2$$

where Q_D is the maximum adsorption capacity, the activity coefficient B_D is related to mean sorption energy, ϵ^2 is Polanyi potential. By fitting (**Figure 10d** and **10e**), B_D is extracted from the slope of the fitting and Q_D from the intercept.

(11)

452 The ε is estimated using Eq.12:

453
$$\varepsilon = RT ln \left[1 + \frac{1}{c_e} \right]$$
(12)

where R, T and C_e represent the gas constant, absolute temperature and adsorbate equilibrium
 concentration, respectively.

The mean sorption energy E necessary to detach a molecule from its position in the sorption space to the infinity, which is a measure of the nature of adsorption (physical or chemical) is expressed as:

$$E = \frac{1}{\sqrt{2B_D}} \tag{13}$$

460 The E value, determined using equation (13), is 73 kJ/mol. The Q_D value (353.47 mg/g) is 461 consistent with both the Q_{max} value (446 mg/g) previously determined with the modified-462 Langmuir isotherm and the experimental one (398.9±16.9 mg/g).

The results provided in **Table 2** show that the regression coefficient R^2 in the Dubinin-463 Radushkevich (0.864) is lower than that of modified-Langmuir, Temkin and Freundlich 464 fittings, indicating that D-H data do not correlate as well as for the previous isotherms. The 465 Cr(VI) removal simulation data using the modified-Langmuir model ($R^2 = 0.997$) are better 466 than those obtained by the Freundlich ($R^2 = 0.938$) and the Temkin ($R^2 = 0.972$) models, 467 demonstrating that Cr(VI) adsorption process on rGO/PEI-KOH is best fitted by the modified-468 Langmuir model; this result indicates that Cr(VI) sorption onto rGO/PEI-KOH is not 469 exceeding a monolayer coverage on a homogeneous surface with active sites well distributed 470 throughout. 471



Table 2. Isotherm rate constants and regression coefficients for different models.

Models	Parameters	Linear	Nonlinear
Langmuir	Q _{max} (mg/g)	446.00	445.97
	K _{ML} (L/mg)	1042.10	1047.11
	R ²	0.997	0.982
Temkin	A (unitless)	91.12366	91.11
	K _T (L/mg)	0.27	0.27
	b (kJ/mol)	27.1891	27.1
	R ²	0.972	0.972
Freundlich	$K_F (mg/g) (L/mg)^{1/n}$	62.74	73.30
	n	3	3.32
	R ²	0.938	0.933
Dubinin-	$Q_{\rm m}$ (mg/g)	353.47	361.96
Radushkevich	$B (mol^2/kJ^2)$	9.38011E ⁻⁵	6.6496E ⁻⁵

 E (kJ/mol)	73	86.71
R ²	0.864	0.829

474 **3.2.5** Effects of contact time and adsorption kinetics study

Cr(VI) kinetics of adsorption on rGO/PEI-KOH are estimated with the pseudo-first and
second order models by fitting kinetic experimental data. Thereby, the influence of the contact
time on Cr(VI) adsorption was studied (Cr(VI) concentration: 100 mg/L at pH 2.0). Figure
11a reveals that the capacity of adsorption rises rapidly within the first 4 h; afterward, it
continues to raise slowly and approaches equilibrium at around 24 h. Both the kinetic models,
pseudo-first-order and second-order, are given by the following equations (Ho and Mckay,
1999; Azizian, 2004):

482 Pseudo-first-order:

$$Q_t = Q_e (1 - e^{-K_1 t}) \tag{14}$$

484 Pseudo-second-order:


485
$$Q_t = \frac{Q_e^2 K_2 t}{1 + Q_e K_2 t}$$
(15)

Where Q_e is the quantity of adsorbed pollutant at equilibrium, Q_t is the amount of adsorption at t time, and K_1 and K_2 are the pseudo-first order and pseudo-second order rate constant, respectively.

The nonlinear fitting of the kinetic data is presented in **Figure 11a** and the obtained kinetic parameters are listed in **Table 3**. The comparison of the regression coefficient (R^2) values revealed that the adsorption kinetics of Cr(VI) onto rGO/PEI-KOH are well-described with the pseudo-second-order model. In addition, the absorption capacity ($Q_{e,cal}=94.67 \text{ mg/g}$), calculated from the pseudo-second order kinetic model, is closer to that obtained experimentally ($Q_{e,exp}=99.38 \text{ mg/g}$). This result is predictable, because this model is adequate for a concentration of solute not too high as it is the case in this work (Azizian, 2004). In order to investigate the mechanism of mass transfer during the adsorption process, the Weber-Morris model for intraparticle diffusion (Ho and Mckay, 1999; El Ouardi et al., 2019) was used. Weber-Morris stated that if intra-particle diffusion is the rate-controlling factor during an adsorption process, uptake of the adsorbate varies with the square root of time (equation (16)).

$$Q_t = K_{int} t^{1/2} + C (16)$$

Where K_{int} is the intraparticle diffusion rate constant. Figure 11b shows that the plots of Q_t 502 versus t^{1/2} are multi-linear, indicating that Cr(VI) adsorption mechanism occurs in three 503 504 distinct stages. The first stage with the largest slope (K_{int1}) is due to an important diffusion of Cr(VI) anions from the solution to the intraparticle regions; the R^2 value indicates that at this 505 506 first step of the adsorption process, the intraparticular diffusion is the predominant factor. The second linear stage, with lower K_{int} and R² values, suggest that the intraparticle diffusion 507 becomes less predominant, this is probably linked both to the decrease in the Cr (VI) 508 concentration gradient between the intraparticle regions and the solution, as well as a 509 510 diminution of the available adsorption sites (intraparticle). For the final stage, with the lowest K_{int} and R^2 , the process evolution ultimately resulted in a non-predominant intraparticle 511 diffusion as the system approaches equilibrium. This is presumably due to a drop in the 512 concentration gradient (between solution and intraparticle regions) as well as the almost-513 saturation of the intraparticle adsorption sites. 514



516	Figure 11. (a) Pseudo-first-order and pseudo-second-order nonlinear fitting and (b)
517	intraparticle diffusion linear fitting for Cr (VI) adsorption onto rGO/PEI-KOH (pH: 2,
518	concentration of Cr(VI): 100 mg/L, adsorbent dosage 1 mg/mL, room temperature, time of
519	contact 24 h).
520	
521	

 Table 3. Cr(VI) kinetic adsorption parameters onto rGO/PEI-KOH.

Kinetic models	Parameters	
Pseudo-first-Order		
	$K_1(min^{-1})$	0.056
	Qe.cal(mg/g)	88.96
	\mathbb{R}^2	0.898
Pseudo-second-Order		
	K ₂ (g/mg min)	0.0009
	Qe.cal (mg/g)	94.67
	\mathbb{R}^2	0.975
Intraparticle diffusion		
	K _{int1} (mg/g min ^{1/2})	6.24
	C_1	34.25
	\mathbb{R}^2	0.991
	K _{int2} (mg/g min ^{1/2})	2.13
	C_2	58.70
	\mathbb{R}^2	0.973
	K_{int3} (mg/g min ^{1/2})	0.40
	C ₃	85.19
	\mathbb{R}^2	0.892


3.2.6 Cr(VI) adsorption-reduction mechanism

To further analyze the Cr(VI) elimination mechanism by rGO/PEI-KOH, XPS was used to 525 examine the elemental composition after the adsorption of Cr(VI). As shown in Figure 12a, 526 the peaks of Cr_{2p} appear in the solid material, confirming that Cr(VI) is adsorbed successfully 527 onto the material. The XPS spectrum of the Cr_{2p} further indicates that there are four 528 components at 577.4, 580.2, 586.9 and 590.6 eV. The peaks at 577.4 and 580.2 eV represent 529 $Cr_{2p3/2}$ orbitals, while the components at 586.9 and 590.6 eV are due to $Cr_{2p1/2}$ orbitals. The 530 577.4 and 586.9 eV peaks are ascribed to Cr(III), while 580.2 and 590.6 eV peaks are related 531 to Cr(VI) (Ma et al., 2012; Zhang et al., 2013; Nezar et al., 2019). These results clearly 532 indicate that both Cr(VI) and Cr(III) ions coexist on the rGO/PEI-KOH surface with 70.3 at% 533 of Cr(III) of the total amount of adsorbed chromium, signifying a good reduction of the 534 adsorbed pollutant. 535

Figure 12b displays the high-resolution N_{1s} XPS spectrum of rGO/PEI-KOH composite 536 537 prior to and after Cr(VI) elimination. Before adsorption, the spectrum consists of one peak corresponding to N_{1s} of the amine group. After adsorption process in acidic conditions (pH 2), 538 539 the N_{1s} can be deconvoluted into two peaks: a preponderant peak related to the amine group 540 slightly shifted to higher binding energy, and a second peak at 401.4 eV due to the protonated amine groups (-NH₃⁺). As explained above, at this pH value and K₂Cr₄O₇ concentration used, 541 the chromium predominant species is the hydrochromate anion, HCrO₄⁻, and it is worth 542 noting that at this acidic pH, the PEI molecule is known to present a maximum protonation of 543 544 amine groups, almost all these groups become positively charged (Curtis et al., 2016).


The $HCrO_4^-$ anions are electrostatically attracted to the protonated amine groups where they will be adsorbed, as illustrated by equation (17) (Wang et al., 2017):

547
$$-\mathrm{NH}_3^+ + \mathrm{HCrO}_4^- \longrightarrow \mathrm{NH}_3^+ \cdots \mathrm{HCrO}_4^-$$
 (17)



567 On the other hand, we speculate that the blue shift observed for the N_{1s} of the amine group 568 after chromium adsorption is related to this chelation.

569 Scheme 2 illustrates the adsorption/reduction process, and Table 4 depicts the values of some 570 other adsorbent capacities for Cr(VI) reported in the literature. We can clearly see that the 571 adsorption capacity of 398.9±16.9 mg/g at ambient temperature is among the highest recorded 572 values.



Scheme 2. Schematic illustration of the mechanism of Cr(VI) removal by rGO/PEI-KOH.

Table 4. The maximum adsorption capacity of Cr(VI) compared with some indicati	ve
--	----

reported works.

Adsorbent	Q _{max} (mg/g)	Reference
Mesoporous carbon microspheres	156.3	(Zhou et al., 2016)
RGO/PEI/Fe ₃ O ₄	266.6	(Wang et al., 2017)
Commercial activated carbon (CAC)	15.47	(Sandhya and Tonni,
		2004)
KOH-modified carbonized Eucalyptus	45.88	(Zhang et al., 2018a)
sawdust		
PEI-modified-biomass of Penicillium	279.2	(Deng and Ting,
chrysogenum		2005)
Iron nanoparticle decorated graphene	162	(Jabeen et al., 2011)
P(TA-TEPA)-PAM-RGO	397.5(35°C)	(Zhang et al., 2018b)
3-aminopropyltriethoxysilane-functionalized	215.2	(He et al., 2017)
graphene oxide (AS-GO)		
Magnetic β -cyclodextrin/graphene oxide	120.1	(Fan et al., 2012)
nanocomposite (MCGN)		
ED/DMF/rGO	92.15	(Zhang et al., 2013)
Amino functionalized graphene oxide	123.4	(Zhao et al., 2016)
decorated with Fe ₃ O ₄ nanoparticles (AMGO)		
Reduced graphene oxide-montmorillonite (GCM)	12.86	(Zhang et al., 2015)
Polyethyleneimine modified eggshell	160	(Liu and Huang,
membrane (PEI–ESM)		2011)
Ionic liquid modified reduced graphene oxide (IL-	232.55	(Nasrollahpour et al.,
rGO)		2017)
Sulfonated magnetic graphene oxide (SMGO)	222.22	(Alizadeh et al.,
		2017)
Graphene/MgAl-layered double hydroxides	172.55	(Yuan et al., 2013)

rGO-PEI	324.0 (25°C)	This work
rGO-PEI-KOH	398.9 (25°C)	This work
chitosan composite (TGOCS)		
Triethylenetetramine modified graphene oxide/	219.5	(Ge and Ma, 2015)
(G–MgAl-LDH)		

591

592 **4.** Conclusion

A graphene-based adsorbent was elaborated by reacting graphene oxide (GO) with 593 polyetheylenimine (PEI) and potassium hydroxide (KOH) at 90°C. Under these experimental 594 conditions, GO sheets were partially reduced while being at the same time functionalized with 595 PEI moieties. XPS, Raman, FTIR and TGA characterization proved an appreciable 596 597 deoxygenation of GO as well as the effective grafting of PEI on the rGO sheets. The asprepared rGO/PEI-KOH adsorbent exhibits an adsorption capacity of 398.9 mg/g for Cr(VI) 598 at room temperature. Compared to other works in the literature, this value is among the 599 highest reported. This adsorption is mainly attributable to the electrostatic interactions 600 between the chromium anion species and the low pH induced protonation of amine groups. 601 602 The isotherm plots suggest that during Cr(VI) sorption process rGO/PEI-KOH shows a homogeneous surface where active sites are well distributed throughout; also, the results 603 604 suggest that chemisorption may play a non-negligible role in this process. Investigating the 605 adsorption kinetics, we found that it follows pseudo-second order model, which is consistent 606 with the Cr(VI) concentration range used. In addition, by applying the Weber-Morris model, we noticed that intraparticle diffusion phenomena play a predominant role in the initial phase 607 608 of Cr (VI) adsorption. The subsequent Cr(VI) reduction to Cr(III), which attained 70.3% of the total adsorbed chromium, is related to the oxidative action of the hydrochromate anion on 609 the rGO/PEI-KOH sheet, since this later acts as electron donor (π electrons). The results of 610

this work represent an interesting way to eliminate Cr(VI), while offering the advantages of
reduced cost, high capacity of adsorption and respect for the environment. Therefore, it could
be a promising adsorbent in environmental applications.

614

615 Acknowledgment

The authors gratefully acknowledge financial support from the Centre National de la Recherche Scientifique (CNRS), the MESRS-Algeria, the University of Lille and the Hautsde-France region.

619

620 **References**

- Alizadeh, A., Abdi, G., Khodaei, M.M., Ashokkumar, M., Amirian, J., 2017. Graphene
- 622 oxide/Fe₃O₄/SO₃H nanohybrid: a new adsorbent for adsorption and reduction of Cr(VI) from

aqueous solutions. RSC Adv. 7, 14876.

- 624 Ayawei, N., Ebelegi, A.N., Wankasi, D., 2017. Modelling and interpretation of adsorption
- 625 isotherms. J. Chem. 2017, 3039817.
- Azizian, S., 2004. Kinetic models of sorption: a theoretical analysis. J. Colloid Interface Sci.
 276, 47-52.
- Azizian, S., Eris, S., Wilson, L.D., 2018. Re-evaluation of the century-old Langmuir isotherm
- 629 for modeling adsorption phenomena in solution. Chem. Phys. 513, 99-104.
- 630 Barnhart, J., 1997. Occurrences, Uses, and Properties of Chromium. Regulatory Toxicol.
- 631 Pharm. 26, S3-S7.
- Budimir, M., Jijie, R., Ye, R., Barras, A., Melinte, S., Silhanek, A., Markovic, Z., Szunerits,
- 633 S., Boukherroub, R., 2019. Efficient capture and photothermal ablation of planktonic bacteria
- and biofilms using reduced graphene oxide-polyethyleneimine flexible nanoheaters. J. Mater.
- 635 Chem. B 7, 2771-2781.

- 636 Curtis, K.A., Miller, D., Millard, P., Basu, S., Horkay, F., Chandran, P.L., 2016. Unusual salt
- and pH induced changes in polyethylenimine solutions. Plos One 11, e0158147.
- Dai, J., Ren, F., Tao, C.Y., 2012. Adsorption of Cr(VI) and speciation of Cr(VI) and Cr(III) in
- aqueous solutions using chemically modified chitosan. Int. J. Environ. Res. Public Health 9,1757-1770.
- 641 Darabi, S.F.S., Bahramifar, N., Khalilzade, M.A., 2018. Equilibrium, thermodynamic and
- 642 kinetics studies on adsorption of eosin Y and red X-GRL from aqueous solution by treated
- rice husk. J. Appl. Res. Water Wastewater 9, 392-398.
- 644 Deng, S., Ting, Y.P., 2005. Polyethylenimine-modified fungal biomass as a high-capacity
- biosorbent for Cr(VI) anions: Sorption capacity and uptake mechanisms. Environm. Sci.
- 646 Technol. 39, 8490–8496.
- El Ouardi, M., Laabd, M., Abou Oualid, H., Brahmi, Y., Abaamrane, A., Elouahli, A., Ait
- 648 Addi, A., Laknifli, A., 2019. Efficient removal of p-nitrophenol from water using
- 649 montmorillonite clay: insights into the adsorption mechanism, process optimization, and
- regeneration. Environ. Sci. Pollut. R 26, 19615-19631.
- Fan, L., Luo, C., Sun, M., Qiu, H., 2012. Synthesis of graphene oxide decorated with
- magnetic cyclodextrin for fast chromium removal. J. Mater. Chem. 22, 24577-24583.
- Fan, X., Peng, W., Li, Y., Li, X., Wang, S., Zhang, G., Zhang, F., 2008. Deoxygenation of
- exfoliated graphite oxide under alkaline conditions: A green route to graphene preparation.
- 655 Adv. Mater. 20, 4490-4493.
- 656 Fang, Y., Lv, Y., Che, R., Wu, H., Zhang, X., Gu, D., Zheng, G., Zhao, D., 2013. Two-
- dimensional mesoporous carbon nanosheets and their derived graphene nanosheets: Synthesis
- and efficient lithium ion storage. J. Am. Chem. Soc. 135, 1524-1530.

- 659 Fellahi, O., Das, M.R., Coffinier, Y., Szunerits, S., Hadjersi, T., Maamache, M.,
- 660 Boukherroub, R., 2011. Silicon nanowire arrays-induced graphene oxide reduction under UV
- irradiation. Nanoscale 3, 4662-4669.
- Feng, G., Cheng, P., Yan, W., Boronat, M., Li, X., Su, J.H., Wang, J., Li, Y., Corma, A., Xu,
- 663 R., Yu, J., 2016. Accelerated crystallization of zeolites via hydroxyl free radicals. Science
- 664 351, 1188-1191.
- Ferrandon, O., Bouabane, H., Mazet, M., 1995. Tests for the validity of different models used
 for the adsorption of sSolutes on activated carbon. J. Water Sci. 8, 183-200.
- 667 Foo, K.Y., Hameed, B.H., 2010. Insights into the modeling of adsorption isotherm systems.
- 668 Chem. Eng. J. 156, 2-10.
- Freundlich, H.M.F., 1906. Over the adsorption in solution. Z. Phys. Chem. 57, 385-470.
- 670 Ge, H.C., Ma, Z.W., 2015. Microwave preparation of triethylenetetramine modified graphene
- 671 oxide/chitosan composite for adsorption of Cr(VI). Carbohydr. Polym. 131, 280-287.
- Hayes, W.I., Joseph, P., Mughal, M.Z., Papakonstantinou, P., 2014. Production of reduced
- 673 graphene oxide via hydrothermal reduction in an aqueous sulphuric acid suspension and its
- electrochemical behaviour. J. Solid State Electrochem. 19, 361-380.
- He, C., Yang, Z.Q., Ding, J., Chen, Y.C., Tong, X.W., Li, Y., 2017. Effective removal of
- 676 Cr(VI) from aqueous solution by 3-aminopropyltriethoxysilane-functionalized graphene
- 677 oxide. Colloids Surf. A 520, 448-458.
- Ho, Y.S., Mckay, G., 1999. Comparitive sorption kinetic studies of dye and aromatic
- 679 compounds onto fly ash. J. Environ. Sci. Health. A 34, 1179-1204.
- 680 Ho, Y.S., Porter, J.F., McKay, G., 2002. Equilibrium isotherm studies for the sorption of
- divalent metal ions onto peat: copper, nickel and lead single component systems. Water, Air,
- 682 Soil Pollution 141, 1-33.

- Huang, H.H., Kanishka, K., De Silva, H., Kumara, G.R.A., Yoshimura, M., 2018. Structural
- evolution of hydrothermally derived reduced graphene oxide. Sci. Rep. 8, 6849.
- Jabeen, H., Chandra, V., Jung, S., Lee, J.W., Kim, K.S., Kim, S.B., 2011. Enhanced Cr(VI)
- removal using iron nanoparticle decorated graphene. Nanoscale 3, 3583–3585.
- Langmuir, I., 1918. The adsorption of gases on plane surface of glass, mica and platinum. J.
- 688 Am. Chem. Soc. 40, 1361-1403.
- Li, S., Kang, E.T., Neoh, k.G., Ma, Z.H., Tan, K.L., Huang, W., 2001. In situ XPS studies of
- 690 thermally deposited potassium on poly(p-phenylene vinylene) and its ring-subtituted
- 691 derivatives. Appl. Surf. Sci. 181, 201-210.
- Liu, B., Huang, Y., 2011. Polyethyleneimine modified eggshell membrane as a novel
- biosorbent for adsorption and detoxification of Cr(VI) from water. J. Mater. Chem. 21, 17413.
- Liu, H., Kuila, T., Kim, N.H., Ku, B.-C., Lee, J.H., 2013. In situ synthesis of the reduced
- graphene oxide-polyethyleneimine composite and its gas barrier properties. J. Mater. Chem. A1, 3739-3746.
- Lu, N., Wang, J., Floresca, H.C., Kim, M.J., 2012. In situ studies on the shrinkage and
- 698 expansion of graphene nanopores under electron beam irradiation at temperatures in the range
- 699 of 400-1200°C. Carbon 50, 2961-2965.
- Luo, T., Tian, X., Yang, C., Luo, W., Nie, Y., Wang, Y., 2017. Polyethylenimine-
- functionalized corn bract, an agricultural waste material, for efficient removal and recovery of
- 702 Cr(VI) from aqueous solution. J. Agr. Food Chem. 65, 7153-7158.
- Ma, H.L., Zhang, Y., Hu, Q.H., Yan, D., Yu, Z.Z., Zhai, M., 2012. Chemical reduction and
- removal of Cr(VI) from acidic aqueous solution by ethylenediamine-reduced graphene oxide.
- 705 J. Mater. Chem. 22, 5914.

- Nasrollahpour, A., Moradi, S.E., Khodaveisi, J., 2017. Effective removal of hexavalent
- chromium from aqueous solutions using ionic liquid modified graphene oxide sorbent. Chem.
- 708 Biochem. Eng. Q. 31, 325-334.
- Nezar, S., Cherifi, Y., Barras, A., Addad, A., Dogheche, E., Saoula, N., Laoufi, N.A.,
- 710 Szunerits, S., Boukherroub, R., 2019. Efficient reduction of Cr(VI) to Cr(III) under visible
- 711 light irradiation using CuS nanostructures. Arabian J. Chem. 12, 215-224.
- Nia, Z.K., Chen, J.Y., Tang, B., Yuan, B., Wang, X.G., Li, J.L., 2017. Optimizing the free
- radical content of graphene oxide by controlling its reduction. Carbon 116, 703-712.
- Pakulski, D., Czepa, W., Witomska, S., Aliprandi, A., Pawluć, P., Patroniak, V., Ciesielski,
- A., Samori, P., 2018. Graphene oxide-branched polyethylenimine foams for efficient removal
- of toxic cations from water. J. Mater. Chem. A 6, 9384-9390.
- 717 Ramanathan, T., Fisher, F.T., Ruoff, R.S., Brinson, L.C., 2005. Amino-functionalized carbon
- nanotubes for binding to polymers and biological systems. Chem. Mater. 17, 1290-1295.
- 719 Sahni, M., Locke, B.R., 2006. Quantification of hydroxyl radicals produced in aqueous phase
- pulsed electrical discharge reactors. Ind. Eng. Chem. Res. 45, 5819-5825.
- 721 Sandhya, B., Tonni, A.K., 2004. Cr(VI) removal from synthetic wastewater using coconut
- shell charcoal and commercial activated carbon modified with oxidizing agents and/or
- 723 chitosan. Chemosphere 54, 951–967.
- 724 Shao, L., Li, J., Guang, Y., Zhang, Y., Zhang, H., Che, X., Wang, Y., 2016.
- 725 PVA/polyethyleneimine-functionalized graphene composites with optimized properties.
- 726 Mater. Design 99, 235-242.
- 727 Singh, S.K., Dhavale, V.M., Boukherroub, R., Kurungot, S., Szunerits, S., 2017. N-doped
- 728 Porous Reduced Graphene Oxide as an Efficient Electrode Material for High Performance
- 729 Flexible Solid-state Supercapacitor. Appl. Mater. Today 8, 141-149.

- 730 Sun, Y., Li, C., Shi, G., 2012. Nanoporous nitrogen doped carbon modified graphene as
- relation reaction. J. Mater. Chem. 22, 12810-12816.
- 732 Temkin, M.I., 1941. Adsorption equilibrium and the kinetics of processes on
- nonhomogeneous surfaces and in the interaction between adsorbed molecules. Zh. Fiz. Chim.15, 296-332.
- 735 Tong, W., Zhang, Y., Zhang, Q., Luan, X., Duan, Y., Pan, S., Lv, F., An, Q., 2015. Achieving
- right significantly enhanced dielectric performance of reduced graphene oxide/polymer composite
- by covalent modification of graphene oxide surface. Carbon 94, 590-598.
- Wang, D., Zhang, G., Zhou, L., Wang, M., Cai, D., Wu, Z., 2017. Synthesis of a
- multifunctional graphene oxide-based magnetic nanocomposite for efficient removal of
- 740 Cr(VI). Langmuir 33, 7007–7014.
- Wu, T.N., Shi, M.C., 2010. pH-affecting sonochemical formation of hydroxyl radicals under
 20 KHz ultrasonic irradiation. Sustain. Environ. Res. 20, 245-250.
- York, S.S., Boesch, S.E., Wheeler, R.A., Frech, R., 2003. Vibrational assignments for high
- 744 molecular weight linear polyethylenimine (LPEI) based on monomeric and tetrameric model
- compounds. Macromolecules 36, 7348-7351.
- Yuan, X., Wang, Y., Wang, J., Zhou, C., Tang, Q., Rao, X., 2013. Calcined graphene/MgAl
- 747 layered double hydroxides for enhanced Cr(VI) removal. Chem. Eng. J. 221, 204-213.
- 748 Zhang, X., Zhang, L., Li, A., 2018a. Eucalyptus sawdust derived biochar generated by
- combining the hydrothermal carbonization and low concentration KOH modification for
- hexavalent chromium removal. J. Environm. Management 206, 989-998.
- 751 Zhang, Y., Ma, H.L., Peng, J., Zhai, M., Yu, Z.Z., 2013. Cr(VI) removal from aqueous
- solution using chemically reduced and functionalized graphene oxide. J. Mater. Sci. 48, 1883-1889.

- 754 Zhang, Z., Gao, T., Si, S., Liu, Q., Wu, Y., Zhou, G., 2018b. One-pot preparation of P(TA
- 755 TEPA)-PAM-RGO ternary composite for high efficient Cr(VI) removal from aqueous
- 756 solution. Chem. Eng. J. 343, 207-216.
- 757 Zhang, Z., Luo, H., Jiang, X., Jiang, Z., Yang, C., 2015. Synthesis of reduced graphene oxide-
- montmorillonite nanocomposite and its application in hexavalent chromium removal from
- 759 aqueous solutions. RSC Adv. 5, 47408-47417.
- 760 Zhao, D.L., Gao, X., Wu, C.N., Xie, R., Feng, S.J., Chen, C.L., 2016. Facile preparation of
- amino functionalized graphene oxide decorated with Fe₃O₄ nanoparticles for the adsorption of
- 762 Cr(VI). Appl. Surf. Sci. 384, 1-9.
- 763 Zhao, H., Wang, J., Zhang, D., Dai, Q., Han, Q., Du, P., Liu, C., Xie, Y., Zhang, Y., Cao, H.,
- Fan, Z., 2017. Chloro-benquinone modified on graphene oxide as metal-free catalyst: Strong
- promotion of hydroxyl radical and generation of ultra-small graphene oxide. Sci. Rep. 7,42643.
- 767 Zhou, J., Wang, Y., Wang, J., Qiao, W., Long, D., Ling, L., 2016. Effective removal of
- 768 hexavalent chromium from aqueous solutions by adsorption on mesoporous carbon
- 769 microspheres. J. Colloid Interface Sci. 462, 200-207.
- 770