

Quantifying the effect of overland flow on Escherichia coli pulses during floods: use of a tracer-based approach in an erosion-prone tropical catchment

Laurie Boithias, Olivier Ribolzi, Guillaume Lacombe, Chanthamousone Thammahacksa, Norbert Silvera, Keooudone Latsachack, Bounsamay Soulileuth, Marion Viguier, Yves Auda, Elodie Robert, et al.

▶ To cite this version:

Laurie Boithias, Olivier Ribolzi, Guillaume Lacombe, Chanthamousone Thammahacksa, Norbert Silvera, et al.. Quantifying the effect of overland flow on Escherichia coli pulses during floods: use of a tracer-based approach in an erosion-prone tropical catchment. Journal of Hydrology, 2021, 594, pp.125935. 10.1016/j.jhydrol.2020.125935 . hal-03093896

HAL Id: hal-03093896 https://hal.science/hal-03093896v1

Submitted on 17 Jan 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NoDerivatives 4.0 International License

- 1 Quantifying the effect of overland flow on
- ² Escherichia coli pulses during floods: use of a
- ³ tracer-based approach in an erosion-prone
- 4 tropical catchment
- 5
- 6 Laurie BOITHIAS^{1,*}, Olivier RIBOLZI¹, Guillaume LACOMBE², Chanthamousone THAMMAHACKSA³, Norbert
- 7 SILVERA⁴, Keooudone LATSACHACK³, Bounsamay SOULILEUTH³, Marion VIGUIER³, Yves AUDA¹, Elodie
- 8 ROBERT¹, Olivier EVRARD⁵, Sylvain HUON⁴, Thomas POMMIER⁶, Cyril ZOUITEN¹, Oloth
- 9 SENGTAHEUANGHOUNG⁷, Emma ROCHELLE-NEWALL⁴
- 10
- ¹ Géosciences Environnement Toulouse, Université de Toulouse, CNES, CNRS, IRD, UPS, France
- 12 ² CIRAD, UMR G-EAU, F-34398 Montpellier, France
- 13 G-EAU, Univ Montpellier, AgroParisTech, CIRAD, INRAE, Institut Agro, IRD, Montpellier, France
- ³ IRD, Department of Agricultural Land Management (DALaM), P.O. Box 4199, Ban Nogviengkham,
 Xaythany District, Vientiane, Lao PDR
- ⁴ Institute of Ecology and Environmental Sciences of Paris (iEES-Paris), Sorbonne Université, Univ Paris Est
 Creteil, IRD, CNRS, INRA, 4 place Jussieu, 75005 Paris, France
- ⁵ Laboratoire des Sciences du Climat et de l'Environnement (LSCE/IPSL), Unité Mixte de Recherche 8212
 (CEA/CNRS/UVSQ), Université Paris-Saclay, Gif-sur-Yvette, France
- ⁶ Laboratoire d'Ecologie Microbienne, UMR1418 INRA, UMR 5557 CNRS, UCBL, VetAgroSup, Université
 de Lyon, Villeurbanne, France
- ⁷ Department of Agricultural Land Management (DALaM), P.O. Box 4195, Ban Nogviengkham, Xaythany
 District, Vientiane, Lao PDR
- 24 * Corresponding author: <u>laurie.boithias@get.omp.eu</u>


27 Abstract

28 Bacterial pathogens in surface waters threaten human health. The health risk is especially high in 29 developing countries where sanitation systems are often lacking or deficient. Considering twelve flash-30 flood events sampled from 2011 to 2015 at the outlet of a 60-ha tropical montane headwater catchment 31 in Northern Lao PDR, and using Escherichia coli as a fecal indicator bacteria, our objective was to quantify 32 the contributions of both surface runoff and sub-surface flow to the in-stream concentration of E. coli 33 during flood events, by (1) investigating E. coli dynamics during flood events and among flood events and 34 (2) designing and comparing simple statistical and mixing models to predict *E. coli* concentration in 35 stream flow during flood events. We found that in-stream *E. coli* concentration is high regardless of the 36 contributions of both surface runoff and sub-surface flow to the flood event. However, we measured the 37 highest concentration of *E. coli* during the flood events that are predominantly driven by surface runoff. 38 This indicates that surface runoff, and causatively soil surface erosion, are the primary drivers of in-39 stream E. coli contamination. This was further confirmed by the step-wise regression applied to 40 instantaneous E. coli concentration measured in individual water samples collected during the flood 41 events, and by the three models applied to each flood event (linear model, partial least square model, 42 and mixing model). The three models showed that the percentage of surface runoff in stream flow was 43 the best predictor of the flood event mean *E. coli* concentration. The mixing model yielded a Nash-44 Sutcliffe efficiency of 0.65 and showed that on average, 89% of the in-stream concentration of E. coli 45 resulted from surface runoff, while the overall contribution of surface runoff to the stream flow was 46 41%. We also showed that stream flow turbidity and *E. coli* concentration were positively correlated, but 47 that turbidity was not a strong predictor of *E. coli* concentration during flood events. These findings will 48 help building adequate catchment-scale models to predict *E. coli* fate and transport, and mapping the 49 related risk of fecal contamination in a global changing context.

50

51 Keywords

- 52 Surface runoff; Fecal Indicator Bacteria; Storm flow; Land-use change; Surface-sub surface flow
- 53 separation; northern uplands of Lao PDR
- 54
- 55 Graphical abstract



56

58 1. Introduction

The presence of bacterial pathogens in surface waters threatens human health. Pathogenic bacteria are etiological agents of several waterborne diseases such as diarrhea, which is globally a leading cause of death among all ages (1.31 million deaths in 2015) (Troeger et al., 2017). These bacterial pathogens can be of fecal origin, e.g. from cattle or from human feces where open defecation is practiced or where sanitation systems are lacking or deficient (Exley et al., 2015; Tong et al., 2016). In developing countries, untreated surface water is often used for drinking, cooking, bathing and washing, thus exposing the population to a high health risk (Boithias et al., 2016).

66 Catchment microbial response depends on complex interactions between spatial patterns of land use, 67 soil types, antecedent conditions of soil, and rainfall characteristics (Kim et al., 2018; McKergow and 68 Davies-Colley, 2010; Pachepsky et al., 2018; Strauch et al., 2014). In the tropics, the presence in stream water of Fecal Indicator Bacteria (FIB), such as Escherichia coli (E. coli), is known to be partly driven by 69 70 surface runoff (Causse et al., 2015; Ribolzi et al., 2016a) and groundwater flow (Chuah and Ziegler, 2018). 71 However, the underlying mechanisms of FIB dynamics during storms remain to be fully documented. For 72 example, there is a need to better quantify the respective contributions of surface and sub-surface flows 73 to stream flow (e.g. using geochemical tracers) to understand and model the transfers of *E. coli* at the 74 catchment scale during a flood event (Cho et al., 2016; Kim et al., 2017) and to predict the relative 75 contributions of surface and sub-surface flows to the overall in-stream E. coli contamination (Chin, 2011). 76 E. coli is known to be transported in water as free cells or cells attached to particles of soil, manure or 77 sediment (Garcia-Armisen and Servais, 2009; Krometis et al., 2007; Soupir et al., 2010). While stream 78 flow turbidity is often higher in tropical areas, as compared to temperate areas, suspended sediments 79 are known to carry E. coli (Nguyen et al., 2016). However, the relationships between stream flow 80 turbidity, suspended sediments concentration, and E. coli concentration, and their possible hysteretic 81 patterns during flood events, have not been yet fully explored.

82 Several studies in the tropics have investigated the relationships between suspended sediments 83 concentration and turbidity in rivers and lakes (Martinez et al., 2009; Robert et al., 2017, 2016; Ziegler et 84 al., 2014), and few studies investigated the relationships between suspended sediments concentration 85 and E. coli concentration (Boithias et al., 2016; Nguyen et al., 2016). However, to our knowledge, no 86 study has yet investigated the relationships between turbidity and *E. coli* concentration. Given that in-87 stream E. coli concentration can vary rapidly during a flood event, a high-frequency sampling is required to characterize this variability. The latter is both time consuming and expensive. Therefore, a proxy-88 89 based approach is required and there is a need to verify if stream flow turbidity can be used as a proxy of 90 *E. coli* concentration during flood events.

91 In rural Southeast Asia, such as the uplands of Northern Lao PDR, livestock grazing and the lack of 92 adequate sanitation systems result in high levels of fecal contamination in surface waters during both 93 high and low flow seasons (Boithias et al., 2016; Nguyen et al., 2016; Rochelle-Newall et al., 2016). In 94 addition, Northern Lao PDR, like other mountainous regions in South-East Asia, is experiencing rapid 95 changes in land use (Ribolzi et al., 2017; Turkelboom et al., 2008). Annual crops are replaced by tree 96 plantations (e.g. teak) with limited understorey and litter coverage. This land-use change decreases soil 97 water infiltration and increases surface runoff and soil erosion (Lacombe et al., 2018; Ribolzi et al., 2017; 98 Song et al., 2020; Ziegler et al., 2004), but its impact on bacteria export has not yet been investigated.

99 Considering twelve flash-flood events sampled from 2011 to 2015 at the outlet of a 60-ha montane 100 tropical headwater catchment in Northern Lao PDR, our objective was thus to quantify the contributions 101 of both surface runoff and sub-surface flow to the in-stream concentration of *E. coli* during flood events, 102 by (1) investigating *E. coli* dynamics during flood events and among flood events and (2) designing and 103 comparing simple statistical and mixing models to predict *E. coli* concentration in stream flow during 104 flood events.

105 2. Materials and methods

106 2.1. Study design

107 In this paper, we quantify the relative roles of both surface runoff and sub-surface flow in the 108 contamination of stream water by E. coli in a tropical montane catchment. To do so, we measured fine 109 temporal-scale discharge and stream flow electrical conductivity to calculate the relative contributions of 110 surface runoff and sub-surface flow to total stream flow. For twelve flash-flood events from 2011 to 111 2015 (named with the letters A to L), we then investigated statistical relationships between surface 112 runoff, sub-surface flow, E. coli concentration, together with turbidity, total suspended sediments 113 concentration, land-use features (areal percentage of land cover and E. coli input), and flood event-114 integrated variables, i.e. total rainfall, maximum rainfall intensity, rainfall duration, soil antecedent 115 conditions, peak discharge, total volume of stream water exported during the flood event, and flow 116 coefficient. For each flood event, we applied a mixing model to calculate the relative contributions of 117 surface runoff and of sub-surface flow to the overall in-stream contamination by E. coli, by assigning to 118 each one of these two flow components a characteristic bacteria concentration based on E. coli 119 measurements in overland flow (overland flow E. coli end-member) and in groundwater (groundwater E. 120 *coli* end-member).

121 2.2. Study area: the Houay Pano catchment

The 0.6 km² Houay Pano headwater catchment is located 10 km south of Luang Prabang city in Northern Lao PDR (Fig. 1a), within the 800 000 km² Mekong basin. This experimental site (Boithias et al., 2020) is part of the critical zone observatories' network named Multiscale TROPIcal CatchmentS (M-TROPICS), which belongs to the French Research Infrastructure OZCAR (Gaillardet et al., 2018). This catchment can be considered as being representative of the montane agro-ecosystems of South-East Asia. The climate is sub-tropical humid and is characterized by a monsoon regime with a dry season from November to May, and a wet season from June to October. The mean annual (2001-2019) temperature is 23.4 °C while the

129	mean annual rainfall is 1 366 mm (CV=0.23), about 71 % (CV=0.09) of which falls during the wet season.
130	Altitude within the catchment is 435-716 m (Fig. 1b) and the slope gradient is 1-135 % (mean=52 %). The
131	Laksip village, located downstream the S4 station (Fig. 1b), includes 484 inhabitants (Census of 2015).
132	2.3. Land use and land-use change
133	Detailed land-cover surveys and mapping were conducted each year from 2011 to 2015 within the
134	catchment (Boithias et al., 2020). The annual areal percentages of fallow (Fallow), teak trees (Teak),
135	annual crops (Annual crop), and annual crops grown under young teak trees (Teak+Crop) were calculated
136	using QGIS 2.6. We assessed the monthly <i>E. coli</i> input from 2011 to 2015 within the catchment with the
137	monthly counting of human and domestic animal (swine and poultry) traffic within the catchment, with
138	the daily feces production of humans and domestic animals, and with the E. coli content in their feces
139	(Causse et al., 2015).
140	2.4. Rainfall measurements
141	Rainfall was measured by an automatic weather station (Campbell BWS200 equipped with ARG100, 0.2
142	mm capacity tipping-bucket) located within the catchment (Fig. 1b). Data was recorded at 6-min time
143	interval from 2011 to 2012, and at 1-min time interval from 2013 to 2015. Data from 2013 to 2015 was
144	then cumulated into a 6-min time series for consistency with the 2011-2012 sub-period.
145	2.5. Flow rate measurements and water quality monitoring

We measured stream water level at the S4 gauging station of the catchment outlet (Fig. 1b) within a Vnotch weir equipped with a water level recorder (OTT Thalimedes) connected to a data logger, with 1mm vertical precision at a minimum of 3-min time interval. To relate water level to discharge, a control rating curve was determined using both the velocity area method and the salt dilution method by slug injection. Samples of stream water were collected at S4 gauging station in clean, plastic bottles using an

automatic sampler (Automatic Pumping Type Sediment Sampler, ICRISAT) for the measurement of Total
 Suspended Sediments concentration ([TSS]), turbidity (Turbidity), Electrical Conductivity at 25°C (EC), and
 E. coli concentration ([*E. coli*]). The automatic sampler was triggered by the water level recorder to
 collect water after every 2-cm water level change during flood rising and every 5-cm water level change
 during flood recession.

[TSS] was measured in each sample after filtration on 0.2 μm porosity cellulose acetate filters (Sartorius)
and evaporation at 105 °C for 48 h. Turbidity was determined with a turbidity meter (EUTECH
Instruments TN-100) and EC with a conductivity meter (WTW340).

159 For nine flood events (events A, B, F-L), we measured [E. coli] with the standardized microplate method 160 (ISO 9308-3). A water sub-sample was incubated at four dilution rates (i.e. 1:2, 1:20, 1:200 and 1:2000) in 161 a 96-well microplate (MUG/EC, BIOKAR DIAGNOSTICS) for 48 h at 44 °C. Ringers' Lactate solution was 162 used for the dilutions and one plate was used per sample. The number of positive wells for each 163 microplate was noted and the Most Probable Number (MPN) per 100 mL was determined using the 164 Poisson distribution. For three flood events (events C-E), we measured [E. coli] following the membrane-165 filter method (EPA Method 1603). A small quantity of each water sample was filtered through the filter 166 membrane, which retained the bacterial cells. After filtration, this membrane was placed on a selective 167 medium (Sartorius NKS Endo nutrient pads), and incubated at 44 °C for 24 h. Shiny green E. coli colonies 168 were directly counted and expressed as Colony Forming Units (CFU) per 100 mL. Although "colony forming unit" techniques and "most probable number" techniques are known to give highly correlated 169 170 results (e.g. Cho et al., 2010; Lušić et al., 2016; Wohlsen et al., 2006), we previously ensured that the two 171 methods were consistent in the Houay Pano catchment conditions (unpublished work).

In addition, we monitored surface runoff in the different land uses of the catchment from 2011 to 2015
 using 1-m² microplots (Patin et al., 2018). We annually installed between 6 and 29 microplots to collect

surface runoff water samples during each rainfall event and to measure EC with WTW340. In 2012 and
2014, we used sub-samples of surface runoff water to measure *E. coli* concentration in surface runoff as
described previously. We calculated the mean concentration of *E. coli* in surface runoff by weighing the *E. coli* concentration exported from each land use by the annual areal percentage of each land use ([*E. coli*]_{OF-TOT}). We also measured the *E. coli* concentration in water samples taken from three piezometers
(Ribolzi et al., 2018) and calculated the mean concentration of *E. coli* in groundwater ([*E. coli*]_{GW-TOT}).

180 2.6. Electrical conductivity-based hydrograph separation

181 We used a tracer-based approach to separate storm hydrographs into 'event water' and 'pre-event 182 water'. This approach relies on a simple mixing model with two end-members and EC as a tracer. It is of 183 relatively low cost compared to e.g. isotopic tracers and was successfully tested in the study catchment 184 (Ribolzi et al., 2018). Based on previous field observations and measurements performed in the same 185 study catchment (Patin et al., 2012; Ribolzi et al., 2011; Vigiak et al., 2008), the two end-members of the 186 model (i.e. overland flow EC end-member in event water, and groundwater EC end-member in pre-event 187 water) can be interpreted in terms of hydrological processes. Event water mainly includes infiltration 188 excess that produces overland flow along hillslopes. Pre-event water relates to groundwater that feeds 189 the stream during the storm event, plus the water in the stream channel prior to the storm event, which 190 is also related to groundwater outflows. As suggested by Collins and Neal (1998), we verified the linearity 191 between EC and the concentration of a conservative tracer to control the relevance of the EC-based 192 approach in our context (Ribolzi et al., 2018). The mixing model applied to individual samples is 193 described by the following equations:

$$Q = Q_{OF} + Q_{GW}$$
 Eq. 1

$$Q \times EC = Q_{OF} \times EC_{OF} + Q_{GW} \times EC_{GW}$$
Eq. 2

where Q is the instantaneous stream water discharge at the catchment outlet (L s⁻¹), Q_{OF} is the instantaneous discharge of overland flow, i.e., event water or surface runoff (L s⁻¹), Q_{GW} is the

instantaneous discharge of groundwater, i.e., pre-event water or sub-surface flow (L s⁻¹), EC is the 196 197 instantaneous electrical conductivity measured in the stream (μ S cm⁻¹), EC_{OF} is the electrical conductivity 198 in overland flow (overland flow EC end-member; μ S cm⁻¹), approximated from electrical conductivity 199 measurements in samples of overland flow collected at the soil surface on hillslopes draining to the 200 stream, and EC_{GW} is the electrical conductivity in groundwater (groundwater EC end-member; μ S cm⁻¹), 201 approximated from the stream electrical conductivity at the beginning of the flood event, since 202 groundwater is the only supply of water to the stream during inter-storm flow periods (Ribolzi et al., 203 2005). For each individual sample, we calculated the relative contributions of Q_{OF} and of Q_{GW} to Q based 204 on Eq. 2, namely Q_{OF} % and of Q_{GW} % (in %).

We assessed the uncertainty in estimating the contributions of overland flow and groundwater flow to the total stream flow using the formulation of Genereux (1998), which assigns an uncertainty specific to each term in Eqs. 1 and 2. The accuracy of Q is considered to be within $\pm 10\%$ of the measured value, while the uncertainty of EC is approximately $\pm 5\%$ (Ribolzi et al., 2018). The uncertainties of both EC_{OF} and EC_{GW} are estimated from the coefficients of variation (CV) of overland flow and groundwater samples, respectively.

211 2.7. Flood-event variables

For each flood event, the mean concentration of *E. coli* ([*E. coli*]_{mean}) is equivalent to the average of the instantaneous *E. coli* concentrations ([*E. coli*]) measured during the event, weighted by the corresponding measurements of instantaneous discharge. We considered 13 candidate explanatory variables to predict [*E. coli*]_{mean}:

216 - Rainfall duration (R_D , in min), total rainfall (R_{TOT} , in mm), maximum rainfall intensity (RI_{MAX} , in mm 217 h^{-1});

218	- Antecedent Precipitation Index (API, in mm), as a proxy of soil moisture conditions, ca	lculated as
219	$API_n = (API_{n-1} + P_{n-1}) \times e^{-\alpha \times t}$ where API_{n-1} is the antecedent precipitation index	prior to
220	rain event n-1 (mm), P_{n-1} is the rainfall precipitated during rain event n-1 (mm), $lpha$ is th	е
221	calibration coefficient usually set at 0.5 (day ⁻¹), and t is the duration between P_n and P	_{n-1} (day)
222	(Descroix et al., 2002);	
223	- Peak discharge during flood event (Q _{MAX} , in L s ⁻¹), total volume of stream water during	flood
224	event (Q _{TOT} , in m ³), total volume of surface runoff, i.e. overland flow, during flood even	nt (Q _{OF-TOT} ,
225	in m ³) and its contribution to Q_{TOT} (Q_{OF-TOT} %, in %), and volume of sub-surface flow dur	ing flood
226	event (Q_{GW-TOT} , in m ³) and its contribution to Q_{TOT} (Q_{GW-TOT} %, in %);	
227	- Flow coefficient of the flood event (K_E , no dimension), calculated as the ratio between	\mathbf{Q}_{TOT} and
228	R _{tot} ;	
229	- Flood-event mean concentration of total suspended sediments concentration ([TSS] _{me}	$_{an}$, in g L ⁻¹),
230	calculated by weighting [TSS] by the discharge, and flood-event mean turbidity (Turbic	lity _{mean} , in
231	NTU), calculated by weighting Turbidity by time.	
232	2.8. Hysteresis	
233	Combined with EC-based hydrograph separation, the analysis of rotational direction, curvature	e, and
234	trend of hysteresis relationships can be used to interpret the relative contributions from surfa	ce water
235	and groundwater, and analyte sources (Holz, 2010; Long et al., 2017). Here, we analyzed hyste	eresis
236	patterns of EC, Turbidity, [TSS] and [E. coli] against discharge; [TSS], Turbidity and [E. coli] agai	nst Q _{OF} ;
237	Turbidity and [E. coli] against [TSS]; and [E. coli] against Turbidity. For each flood, we considered	ed straight
238	relationships when the p-value of the Pearson correlation was below 0.001. The threshold was	5
239	voluntarily chosen very demanding to distinguish straight relationships from other hysteretic p	oatterns.

240 2.9. Statistical analysis

We calculated correlations and regressions to identify explanatory variables predicting [*E. coli*] and [*E. coli*]_{mean}. Statistics were calculated with R statistical package version 3.4.3 (correlations), Minitab 18.1
(stepwise regression), and XLSTAT 20.1.1 (partial least square regression). An explanatory variable was
considered to be statistically significantly different from zero when its p-value, derived from Student's ttest, was lower than 0.05.

246

2.9.1. Modelling instantaneous *E. coli* concentration [*E. coli*]

247 We first calculated Pearson correlations between [E. coli] and the eight hydrological variables measured 248 or calculated for each sample (EC, Q, Q_{OF}, Q_{GW}, Q_{OF}%, Q_{GW}%, [TSS], and Turbidity). In addition, to select 249 the best set of explanatory variables predicting [E. coli], we derived linear regressions from the 'step-250 wise regression' selection algorithm. This selection intended to maximize the prediction $R^2 (R^2_{pred})$ 251 calculated by leave-one-out cross-validations. This performance criterion reflects the ability of the model 252 to predict observations that were not used in the model calibration. Its maximization leads to greater 253 parsimony in the number of explanatory variables (Helsel and Hirsch, 2002). We verified the required 254 homoscedasticity of the model's residuals by visual inspection. Multi-collinearity among the selected 255 explanatory variables was avoided by ensuring that the Variance Inflation Factor (VIF) never exceeded 256 the value of 8 (Helsel and Hirsch, 2002). We didn't mix instantaneous measurements with flood-event 257 variables or with variables assessed annually (Annual crop, Teak+Crop, Teak, and Fallow) or monthly (E. 258 coli input).

259

2.9.2. Modelling mean concentration of *E. coli* per flood event [*E. coli*]_{mean}

We first calculated Pearson correlations between [*E. coli*]_{mean} and the thirteen hydro-meteorological
variables measured or calculated for each flood event (Table 1) and the five land-use related variables
(Annual crop, Teak+Crop, Teak, Fallow, and *E. coli* input). In addition, we used Partial Least Square (PLS)

regression to detect dependencies between variables. PLS is able to handle datasets with a number of
variables higher than the number of observations. It is also poorly sensitive to multi-collinearity, and
handles missing data by imputation. The importance of each projected variable is estimated by the
Variable Importance in the Projection (VIP). We discarded the variables for which VIP values were below
1 (Ribolzi et al., 2016b; Wold, 1995).

268 2.10. Mixing model of flood-event mean concentration of *E. coli*

We applied a simple mixing model with two end-members to predict [*E. coli*]_{mean} and to separate the contributions of both 'event water' and 'pre-event water' to the in-stream *E. coli* concentrations. Here the two end-members of the model are *E. coli* concentration in event water (overland flow *E. coli* endmember or [*E. coli*]_{OF-TOT}) and *E. coli* concentration in pre-event water (groundwater *E. coli* end-member or [*E. coli*]_{GW-TOT}). The mixing model applied to flood-event mean variables is described by the following equations:

$$Q_{TOT} = Q_{OF-TOT} + Q_{GW-TOT}$$
 Eq. 3

$$Q_{TOT} \times [E. coli]_{mean} = Q_{OF-TOT} \times [E. coli]_{OF-TOT} + Q_{GW-TOT} \times [E. coli]_{GW-TOT}$$
Eq. 4

where Q_{TOT} is the total volume of stream water during flood event (m³), Q_{OF-TOT} is the total volume of 275 276 surface runoff, or overland flow, during flood event (m^3), Q_{GW-TOT} is the total volume of sub-surface flow, or groundwater flow, during flood event (m³), [E. coli]_{mean} is the flood-event mean concentration of E. coli 277 (MPN 100 mL⁻¹), [*E. coli*]_{OF-TOT} is the mean concentration of *E. coli* exported in overland flow (MPN 100 278 279 mL⁻¹), calculated from *E. coli* concentration measured in samples of overland flow collected at the soil 280 surface on hillslopes draining to the stream, and [E. coli]GW-TOT is the mean concentration of E. coli in groundwater (MPN 100 mL⁻¹), calculated from *E. coli* concentration measured in groundwater. This 281 282 approach was shown to yield a comparable or even higher performance when predicting in-stream 283 pathogen concentrations compared with more complex fate and transport models (Chin, 2011). We 284 applied the mixing model to the twelve flood events and compared its performance with the

- performance of the PLS model. For each flood event, we calculated the relative contributions of [*E*.
- 286 *coli*]_{OF-TOT} and of [*E. coli*]_{GW-TOT} to [*E. coli*]_{mean} based on Eq. 4, namely [*E. coli*]_{OF-TOT}% and of [*E. coli*]_{GW-TOT}%
- 287 (in %).

288 3. Results

289 3.1. *E. coli* dynamics during flood events and among flood events

The areal percentage of land use evolved from 2011 to 2015 (Fig. Sl1): annual crop decreased from 28% to 4% of the catchment area, and teak and annual crop decreased from 12% to 0%, while teak increased from 18% to 36%, and fallow increased from 29% to 46%. Areal percentage of forest was constant at 8%. The *E. coli* input into the catchment decreased from a monthly average of 2x10¹⁵ in 2011 to a monthly average of 3x10¹⁴ in 2015 (Fig. Sl2). Over the 2011-2015 period, the cumulated *E. coli* input for swine and poultry accounted for 0.01-0.38 % of the total *E. coli* input.

In the meantime, a total of 294 discharge peaks were recorded between January 1, 2011, and December 31, 2015 (Fig. 2), in response to a range of rainfall events (Fig. SI3, see interquartile ranges): 50 % of R_{TOT} ranged between 7 and 22 mm, 50 % of RI_{MAX} ranged between 24 and 60 mm h⁻¹, and 50 % of R_D ranged between 49 and 235 min. Q ranged from 0 to 1 807.6 L s⁻¹ (30 L s⁻¹ ha⁻¹), with a mean Q of 33.3 L s⁻¹.

300 We monitored twelve flood events (A to L) for stream water quality. Datasets for each of the twelve 301 flood events are complete except EC measurements lacking for event A and Turbidity measurements 302 lacking for event G, due to measurement devices' breakdown. A total of 99 stream water samples was collected: [TSS] ranged from 0.02 to 25.7 g L⁻¹ while Turbidity ranged from 191.8 to 13 480 NTU (Fig. 3). 303 *E. coli* were detected in all samples and [*E. coli*] ranged between 160 and 74 000 MPN 100 mL⁻¹ (Fig. 3). 304 305 For the twelve flood events, rainfall was followed by an increase of Q, Turbidity, [TSS] and [E. coli] (Fig. 306 3). However, the peaks of Q, Turbidity, [TSS] and [E. coli] were often asynchronous (full description is 307 given in the supplementary information). Hysteresis loops showed complex patterns mixing straight 308 lines, simple clockwise or anti-clockwise loops, figures-of-eight or multiple hysteresis loops (summary is 309 presented in Table SI1, full description is given in the supplementary information, including Figs. SI4-SI7).

310	The uncertainty bands enclosing Q_{OF} and Q_{GW} in Fig. 3 show that the hydrograph could be clearly
311	separated for each flood event. Flood event C was the only event where the stream flow was virtually
312	100% groundwater flow. Excluding flood event C, Q _{OF-TOT} % ranged between 17 and 80% (Fig. 4a). The
313	average Q _{OF-TOT} % was 41% (CV=0.59).
314	The twelve flood events corresponded to a range of storm characteristics in terms of $R_{\text{TOT}},RI_{\text{MAX}}$ and R_{D}
315	(Fig. SI3, Fig. 2). Q _{MAX} ranged from 31.7 to 967.9 L s ⁻¹ (Table 1, Fig. 3). Three flood events occurred after
316	dry periods (events B, G, and I: API<10), whereas others occurred shortly after a previous flood event
317	(events D, E, and J: API>30) or later (events A, C, F, H, K, and L: 10 <api<20) (table="" 1).="" [e.="" coli]<sub="">mean ranged</api<20)>
318	from 1 125 and 27 375 MPN 100 mL ⁻¹ .
319	Mean EC _{OF} was 55 μ S cm ⁻¹ (CV=0.7) over the 2011-2015 period (65 surface runoff water samples). Mean
320	EC_{GW} was 256 μ S cm ⁻¹ (CV=0.42) among the twelve flood events. [<i>E. coli</i>] _{OF-TOT} was 24 880, 27 292, 27 441,
321	26 987, and 26 935 MPN 100 mL ⁻¹ in 2011, 2012, 2013, 2014, and 2015, respectively (26 surface runoff
322	water samples). [<i>E. coli</i>] _{GW-TOT} was 277 MPN 100 mL ⁻¹ (6 groundwater samples).
323	3.2. Statistical analysis
324	3.2.1. Modelling instantaneous <i>E. coli</i> concentration [<i>E. coli</i>]
325	Considering all water samples collected during the flood events (Fig. SI8), [E. coli] was positively
326	correlated to Q (r=0.54, p<0.001), Q _{OF} (r=0.56, p<0.001), Q _{OF} % (r=0.51, p<0.001), [TSS] (r=0.43, p<0.001),
327	and Turbidity (r=0.43, p<0.001), and was negatively correlated to EC (r=-0.31, p=0.003), and to Q_{GW} % (r=-
328	0.51, p<0.001). Turbidity was positively correlated to [TSS] (r=0.82, p<0.001).
329	From the stepwise regression, [<i>E. coli</i>] was best predicted by [TSS] and Q _{OF} (Eq. 5):
	$[E. coli] = 4995 + 689 \cdot [TSS] + 41.49 \cdot Q$ Eq. 5

T-values and p-values of the coefficients are given in Table SI2. The R² of the model is 35.3 % and the R^{2}_{pred} is 24.42 %.

332 3.2.2. Modelling mean concentration of *E. coli* per flood event [*E. coli*]_{mean}
333 [*E. coli*]_{mean} was positively correlated to Q_{MAX} (r=0.71, p=0.009), Q_{TOT} (r=0.59, p=0.042), Q_{OF-TOT} (r=0.72,
334 p=0.012), and Q_{OF-TOT}% (r=0.93, p<0.001), and was negatively correlated to Q_{GW-TOT}% (r=-0.93, p<0.001)
335 (Fig. SI9).

From the above, we found that Q_{OF-TOT}% was the variable the most positively correlated to [*E. coli*]_{mean}.
The linear model is:

$$[E. coli]_{mean} = 332 \cdot Q_{OF-TOT} \% - 3749$$
 Eq. 6

The R² between predicted and observed [*E. coli*]_{mean} was 0.87 while the Nash-Sutcliffe efficiency (NSE) was 0.84 (Fig. 5a). Excluding event C that was driven by groundwater flow only (and for which the linear model predicted a negative value), [*E. coli*]_{mean} predicted by the linear model ranged from 1 981 to 22 825 MPN 100 mL⁻¹.

342 These latter trends are confirmed by the PLS regression (Fig. 6a), which shows that Axis 1 mostly explains 343 the variables Q_{OF-TOT}% (r=0.863), Q_{GW-TOT}% (r=-0.863), Q_{MAX} (r= 0.859), and Q_{OF-TOT} (r=0.815) whereas Axis 2 344 mostly explains the variable RI_{MAX} (r=0.563). Hence, Axis 1 corresponds to variables that are strongly 345 related to stream water whereas Axis 2 corresponds to variables describing rainfall and soil moisture 346 conditions. Accordingly, the twelve flood events were scattered along the two axes, with the flood 347 events of highest [E. coli]_{mean} in the right panel (Fig. 6b). The variables with VIP values above 1 were Q_{OF-} 348 Tot%, Q_{GW-TOT}%, Q_{MAX}, Q_{OF-TOT}, and Q_{TOT} when considering one component and Q_{OF-TOT}%, Q_{GW-TOT}%, 349 [TSS]_{mean}, Q_{MAX}, and Q_{OF-TOT} when considering two components (Fig. 6c; Table SI3). The statistical model 350 given by the PLS is given in Table SI3. The R² between predicted and observed [E. coli]_{mean} was 0.83 while 351 the NSE was 0.78 (Fig. 5b). Excluding event C that was driven by groundwater flow only (and for which

- the PLS model predicted a negative value), [*E. coli*]_{mean} predicted by the PLS model ranged from 1 067 to
 23 237 MPN 100 mL⁻¹.
- 354 [*E. coli*]_{mean} predicted by the mixing model ranged from 277 to 21 572 MPN 100 mL⁻¹. The R² between
- predicted and observed [*E. coli*]_{mean} was 0.86 while the NSE was 0.65 (Fig. 5c). Flood event C was the only
- event where the percentage of *E. coli* was 100% from groundwater flow. Excluding flood event C, [*E.*
- 357 *coli*]_{OF-TOT}% ranged from 95 to virtually 100% (Fig. 4b). The average [*E. coli*]_{OF-TOT}% was 89% (CV=0.33).

360 4. Discussion

361 4.1. High *E. coli* concentration pulses match high overland flow pulses

The analysis of the twelve monitored flood events (Table 1) shows that [E. coli]mean was high regardless of 362 the flood event characteristics: [E. coli]_{mean} ranged between 1 125 and 27 375 MPN 100 mL⁻¹. The order of 363 364 magnitude of the maximum [E. coli] is about 10⁵ MPN 100 mL⁻¹. All these values exceed the 1 000 MPN 100 mL⁻¹ threshold provided by e.g. the European Directive 2006/7/EC for bathing water quality. 365 366 Although rainfall is known to reactivate hydrological connectivity (Bracken et al., 2013), rainfall 367 characteristics such as R_{TOT}, RI_{MAX}, and R_D, did not appear as strong explanatory variables of [*E. coli*]_{mean} 368 (Fig. 6 and Fig. SI9). Variations in [E. coli] and [E. coli]_{mean} between flood events may be explained by 369 rainfall spatial distribution and the timing between rainfall events: the rainfall distribution will determine 370 which areas draining animal and human manure are activated, whereas the timing between events may 371 indicate which catchment microbial stocks have accumulated to high levels (McKergow and Davies-372 Colley, 2010). In Houay Pano catchment, variations in concentration between flood events may also be 373 explained by *E. coli* input distribution at the soil surface, as the land use is mixed (Fig. SI1). Indeed, based 374 on this twelve-event dataset and hysteresis analysis, we could not find any clear, consistent trend at the 375 outlet of the Houay Pano catchment (Table SI1) and we thus could not identify any primary bacteria 376 source.

The land use change in Houay Pano catchment was rapid and led to the simultaneous increase of teak tree plantations and of fallow areas (Ribolzi et al., 2017). Previous plot- and catchment-scale results showed higher surface runoff and suspended matter export when teak tree plantations increased (Lacombe et al., 2018; Mügler et al., 2019; Ribolzi et al., 2017; Song et al., 2020), suggesting that higher numbers of *E. coli* could be transferred to the river. However, land use characteristics such as land use variables (Annual crop, Teak+Crop, Teak, Fallow, and *E. coli* input) did not appear as strong explanatory

variables of [*E. coli*]_{mean} (Fig. 6 and Fig. S110). Growing teak trees and fallow requires less people in the
field compared to annual crops. Since field workers practice open defecation, less workers imply lower
input of *E. coli* into the catchment. The contribution of domestic animals to the overall *E. coli* input being
only 0.01-0.38 % of the total *E. coli* input, the consequence of the extension of teak tree plantation and
of fallow in Houay Pano from 2011 to 2015 (Fig. S11) is the overall decrease of the *E. coli* input into the
catchment over the same period (Fig. S12).

The highest [E. coli]mean was often associated to flood events with highest QMAX (events J and L) and 389 390 dominant surface runoff (Q_{OF-TOT}%>50: events D, and I-L), confirming the role of surface runoff, and 391 subsequent soil surface erosion, in *E. coli* transfers to the stream (Causse et al., 2015) (Table 1, Fig. 6). For flood events where sub-surface flow was dominating (Q_{OF-TOT}%<50: events B, C, and E-H), [E. coli]_{mean} 392 was in general lower, although exceeding 1 000 MPN 100 mL⁻¹. High *E. coli* concentrations even when 393 394 sub-surface flow was dominating suggest that streambanks and the streambed may release stored E. coli 395 (Chu et al., 2011; Park et al., 2017; Stocker et al., 2018) since sediment deposited at the bottom of the 396 stream may act as an E. coli reservoir (Pachepsky et al., 2017; Rochelle-Newall et al., 2015; Smith et al., 397 2008). In fact, the concentration of *E. coli* in Houay Pano streambed sediment is about 40 000 MPN g⁻¹ 398 (Ribolzi et al., 2016a), but we cannot exclude that *E. coli* is simultaneously transferred from the hillslope 399 with surface runoff, if hillslope soil surface is highly contaminated. We also found both clockwise and 400 anti-clockwise [E. coli]-[TSS] and [E. coli]-Turbidity hysteresis loops, and in some cases figure-of-eight 401 patterns (Table SI1, Fig. SI6 and Fig. SI7). This further suggests that the erosion of bacteria stores is not 402 strictly driven by soil erosion, but also by in-stream sediment resuspension (Evrard et al., 2016; Gourdin 403 et al., 2015; Huon et al., 2017). In parallel, possibly less E. coli-contaminated sub-surface flow, or return 404 flow, may dilute in the stream the E. coli concentration originating from surface runoff and thus mitigate 405 the in-stream microbial contamination.

406 4.2. Predictive models of *E. coli* concentration: performances and usefulness

407 To our knowledge, few studies have reported predictive models using independent variables to explain 408 E. coli concentration and, to the best of our knowledge, they were all developed in temperate areas 409 (Chen and Chang, 2014; Hathaway et al., 2010). The models suggested by Chen and Chang (2014) 410 included antecedent precipitation, stream temperature, and TSS concentration, and gave an R² of 0.27-411 0.61 depending on the season and the catchment. The model suggested by Hathaway et al. (2010) 412 included temperature, rainfall, and humidity, and had an R² of 0.7462. The variety of explanatory 413 variables among models reflects the variety of driving processes driving *E. coli* fate and transport among 414 catchments.

415 4.2.1. Modelling instantaneous *E. coli* concentration [*E. coli*]

416 [E. coli] was equally correlated to both [TSS] and Turbidity (r=0.43, p<0.001; Fig. SI8) while Turbidity was 417 correlated with [TSS] (r=0.82, p<0.001, Fig. SI8). The strong correlation between Turbidity and [TSS] is in 418 line with the results obtained in other studies in tropical areas, such as Ziegler et al. (2014) for rivers in 419 Thailand and Robert et al. (2017) in West African lakes and ponds. The relationships between [TSS] and 420 [E. coli] and between Turbidity and [E. coli] are qualified by hysteretic trends (Figs. SI6 and SI7, 421 respectively) during flood events. Notably, little hysteresis is observed between [TSS] and Turbidity (Fig. 422 SIG). Hysteretic trends may illustrate the uncertainty when predicting *E. coli* by a proxy such as turbidity: 423 sources of sediments may not exactly coincide with sources of E. coli. For example, these relationships 424 may not apply in large mixed-land use catchments, because of the multiple, geographically separated, E. 425 coli and turbidity sources. This may limit the usefulness of using turbidity as a proxy of E. coli near the 426 catchment outlet (McKergow and Davies-Colley, 2010). Another explanation of the hysteresis is the 427 nature and the properties of the suspended sediments, that may change during the flood event: bacteria 428 may be less prone to attach to sand-rich suspended particles (Oliver et al., 2007). Similarly, hysteresis in 429 Turbidity-[TSS] relationships may be explained by changing reflectance properties of the suspended

sediments depending on particle size, shape, mineralogy, aggregation/flocculation, dissolved lightabsorbing matter and bubbles, because of the spatial heterogeneity of rainfall and suspended sediment
sources at the catchment scale (Navratil et al., 2011; Ziegler et al., 2014). A last uncertainty source in the
relationships between [*E. coli*], [TSS], and Turbidity, is the possible exhaustion of the *E. coli* stock within
the catchment after a succession of flood events.

435 From the step-wise regression analysis, the predictive model for [E. coli] includes [TSS] and QOF as 436 explanatory variables (Eq. 5). The two explanatory variables reflect the two processes driving E. coli 437 transport within the catchment: Q_{OF} reflects the mobilization of *E. coli* with relative contributions of 438 surface and sub-surface flows along the flood event, whereas [TSS] reflects the attachment of E. coli to 439 soil particles and/or streambed resuspended sediments (Garcia-Armisen and Servais, 2009; Nguyen et 440 al., 2016). Overall, higher E. coli concentration is related to higher surface runoff and higher suspended 441 matter in the stream flow. The value of the intercept term in Eq. 5 corresponds to E. coli concentration during base flow (Boithias et al., 2016; Kim et al., 2018), i.e. when [TSS] and QOF tend to zero because 442 443 there is no surface runoff during inter-storm periods, in other words when groundwater is the only 444 supply to stream flow and EC tends to EC_{GW}.

The two variables best predicting [*E. coli*], namely [TSS] and Q_{OF}, can be assessed with proxies. [TSS]
could be interchanged with Turbidity, since [TSS] and Turbidity are correlated, as discussed above.
Similarly, EC appears strongly related to Q_{OF} (and Q) by a hyperbolic function (Fig. SI8). Using EC as a
proxy of Q has already been proposed in Alpine headwaters (Cano-Paoli et al., 2019). Both of these
proxies can be monitored *in situ* at high frequencies.

450 4.2.2. Modelling mean concentration of *E. coli* per flood event [*E. coli*]_{mean}
451 The PLS regression analysis (Table SI3) confirmed the analysis of the correlation matrix (Fig. SI9): Q_{OF-TOT}%
452 and Q_{GW-TOT}% were the best predictors of [*E. coli*]_{mean} (r= 0.93 and -0.93, respectively). Land uses that

favor higher Q_{OF-TOT}% or lower Q_{GW-TOT}%, such as erosion-prone teak trees plantations (Lacombe et al.,
2016; Ribolzi et al., 2017), or more intense rainfall events, will lead to higher in-stream concentrations of *E. coli* (Fig. 6a and Fig. SI10) and thus higher fecal contamination risk. Hence, a model based on Q_{OF-TOT}%
or Q_{GW-TOT}% appears relevant to predict [*E. coli*]_{mean}. Such a basic tool may help local and national
stakeholders to assess the fecal contamination risk by testing global change scenarios in target
catchments.

459 In this study, the mixing model of [E. coli]_{mean} based on Q_{OF-TOT}% and Q_{GW-TOT}% had a R² of 0.86 and a NSE 460 of 0.65. The NSE value is lower than the NSE values' range reported by Chin (2011) in six nested 461 catchments in Georgia, United-States. However, in our study the values of both overland flow and 462 groundwater end-members were measured in the field, conversely to Chin (2011) who numerically 463 optimized the values of the two end-members. The performance of the mixing model is lower in terms of 464 NSE than those of the PLS and the linear models (NSE = 0.78 and 0.84, respectively). However, the PLS 465 model is difficult to implement because of the large number of variables it implies, and both the linear 466 and the PLS models are constrained by their validity domains.

467 Within a catchment, the sources of *E. coli* are the *E. coli* transferred from hillslopes with surface runoff, 468 as discussed in section 4.1, and the resuspension from the streambed, whereas the sinks of E. coli are the 469 deposition of the bacterium on the streambed and its decay in the water column. Since rainfall events in the Houay Pano catchment last 0.5-5 hours, considering a decay rate of 0.3-0.6 d⁻¹ (Nguyen et al., 2016), 470 471 the removal of *E. coli* in the water column from bacteria population decay is negligible during a flood 472 event. Since the mixing model is able to accurately predict the flood-event mean concentration of E. coli 473 at the catchment outlet, the deposition of *E. coli* on the streambed is either negligible or compensated 474 by the resuspension. The percentage of *E. coli* resuspended from streambed during a flood is about 11% 475 (Ribolzi et al., 2016a), which implies that the compensated E. coli deposition, e.g. in small wetlands along 476 the main stream, is about 11% as well. Finally, since the possible sources and sinks of *E. coli* are negligible

477 compared to the bacterium transport processes during flood events, the approximation of the simple
478 model that only considers two end-members, namely the *E. coli* concentration in both surface runoff and
479 groundwater, is acceptable.

480 Hence, we could calculate the relative contributions of surface runoff and of sub-surface flow to the in-481 stream E. coli contamination. Excluding flood event C that was driven by groundwater flow, more than 482 95% of [E. coli]_{mean} resulted from overland flow, even for flood events where the percentage of overland 483 flow was small (<20%, events E and G). The average contribution of overland flow to the flood-event 484 mean concentration of *E. coli* was 89%, while the average contribution of overland flow to the flood-485 event mean stream flow was 41% (Fig. 4). In other words, the contribution of groundwater to the in-486 stream E. coli contamination was low during flood events, even though the contribution of groundwater 487 to stream water flow was greater than that of overland flow, i.e. when base flow index (BFI) was over 488 0.5. In comparison, with similar BFI values, Chin (2011) reported bacteria loads from surface runoff in the 489 range of 80–90%, with the remainder mostly originating from base flow, and negligible background loads 490 from the catchment.

492 5. Conclusion

To our knowledge, few papers have reported the statistical relationships between *E. coli* and its environmental drivers (meteorological, hydrological, and land use variables) and the present study is the first one to investigate *E. coli* dynamics during flood events in a tropical humid catchment. We conclude that:

497 Regardless of the contribution of sub-surface flow to the flood, in-stream E. coli concentration is 498 high, suggesting that the streambed E. coli store is high. However, highest concentrations of E. 499 coli are measured for the flood events that are driven by surface runoff, suggesting that surface 500 runoff, and consequently soil erosion, are the primary drivers of in-stream *E. coli* contamination; 501 The three predictive models (linear model, partial least square model, and mixing model) show 502 that the percentage of surface runoff in stream flow is the best predictor of the flood event 503 mean concentration of *E. coli*; 504 A simple mixing model based on the relative contributions of both overland flow and 505 groundwater, and on the E. coli concentration in both overland flow and groundwater, is reliable 506 to predict in-stream flood-event mean *E. coli* concentration (NSE=0.65). On average, 89% of the 507 in-stream concentration of *E. coli* is supplied by surface runoff, while the overall contribution of

508 surface runoff to the stream flow is 41%.

509 - Stream flow turbidity and *E. coli* concentration are positively correlated, but turbidity is not a
 510 strong predictor of *E. coli* concentration during flood events;

Predictive models based on turbidity and electrical conductivity may be used to provide real-time estimates of in-stream *E. coli* concentration, whereas a mixing model may provide flood-event mean information. Such simple models may help to assess the impact of global change on in-stream *E. coli* contamination. They could thus be used to assess the risk of water borne diseases such as diarrhea, in rural areas where mammals, including humans, practice open defecation, and to design early warning

systems. Applied over long periods of time, the models might be used to calculate *E. coli* input-output
load balances. Such basic modelling studies would thus help to assess the long-term impact of land-use
change on the microbial quality of surface water.

519 Future work is required to better understand the pathways of FIB at catchment scale. For example, there 520 is a need to characterize the interactions between ground and surface waters, and the role of the 521 hyporheic zone, as sources of contaminant. Furthermore, the partition between free and particle-522 attached E. coli should be quantified to better understand and predict the probability that bacteria is 523 deposited on the streambed during the flood recession stage and re-suspended in the water column 524 during the next flood rising stage. These findings are of primary importance to build adequate 525 catchment-scale models to accurately simulate *E. coli* fate and transport, and thus better assess fecal 526 contamination risk in a global changing context.

527

528 Acknowledgments

- 529 The authors sincerely thank the Lao Department of Agricultural Land Management (DALaM) for its
- 530 support, including granting the permission for field access, and the M-TROPICS Critical Zone Observatory
- 531 (https://mtropics.obs-mip.fr/), which belongs to the French Research Infrastructure OZCAR
- 532 (http://www.ozcar-ri.org/), for data access. This study was funded by the GIS-Climat
- 533 (<u>http://www.gisclimat.fr/projet/pastek.html</u>) and by the French National Research Agency (TecltEasy
- 534 project; ANR-13-AGRO-0007). LB thanks the Research Institute for Development (IRD) for her
- 535 postdoctoral grant 2016-2017 (Accueil de post-doctorants / Campagne 2015; www.ird.fr).

536

538 References

- Boithias, L., Auda, Y., Audry, S., et al., 2020. Dataset from the Multiscale TROPIcal CatchmentS critical
 zone observatory M-TROPICS II: land use, hydrology and sediment production monitoring in
 Houay Pano, northern Lao PDR. Hydrol. Process. Submitted.
- 542Boithias, L., Choisy, M., Souliyaseng, N., Jourdren, M., Quet, F., Buisson, Y., Thammahacksa, C., Silvera,543N., Latsachack, K., Sengtaheuanghoung, O., Pierret, A., Rochelle-Newall, E., Becerra, S., Ribolzi,
- 544 O., 2016. Hydrological regime and water shortage as drivers of the seasonal incidence of
 545 diarrheal diseases in a tropical montane environment. PLoS Negl. Trop. Dis. 10, e0005195.
 546 https://doi.org/10.1371/journal.pntd.0005195
- Bracken, L.J., Wainwright, J., Ali, G.A., Tetzlaff, D., Smith, M.W., Reaney, S.M., Roy, A.G., 2013. Concepts
 of hydrological connectivity: Research approaches, pathways and future agendas. Earth-Sci. Rev.
 119, 17–34. https://doi.org/10.1016/j.earscirev.2013.02.001
- Cano-Paoli, K., Chiogna, G., Bellin, A., 2019. Convenient use of electrical conductivity measurements to
 investigate hydrological processes in Alpine headwaters. Sci. Total Environ. 685, 37–49.
 https://doi.org/10.1016/j.scitotenv.2019.05.166
- Causse, J., Billen, G., Garnier, J., Henri-des-Tureaux, T., Olasa, X., Thammahacksa, C., Latsachak, K.O.,
 Soulileuth, B., Sengtaheuanghoung, O., Rochelle-Newall, E., Ribolzi, O., 2015. Field and modelling
 studies of Escherichia coli loads in tropical streams of montane agro-ecosystems. J. Hydro Environ. Res. 9, 496–507. https://doi.org/10.1016/j.jher.2015.03.003
- 557 Chen, H.J., Chang, H., 2014. Response of discharge, TSS, and E. coli to rainfall events in urban, suburban,
 558 and rural watersheds. Env. Sci Process. Impacts 16, 2313–2324.
 559 https://doi.org/10.1039/C4EM00327F
- 560 Chin, D.A., 2011. Quantifying pathogen sources in streams by hydrograph separation. J. Environ. Eng.
 561 137, 770–781.
- 562 Cho, K.H., Han, D., Park, Y., Lee, S.W., Cha, S.M., Kang, J.-H., Kim, J.H., 2010. Evaluation of the
 563 relationship between two different methods for enumeration fecal indicator bacteria: Colony564 forming unit and most probable number. J. Environ. Sci. 22, 846–850.
 565 https://doi.org/10.1016/S1001-0742(09)60187-X
- Cho, K.H., Pachepsky, Y.A., Oliver, D.M., Muirhead, R.W., Park, Y., Quilliam, R.S., Shelton, D.R., 2016.
 Modeling fate and transport of fecally-derived microorganisms at the watershed scale: State of
 the science and future opportunities. Water Res. 100, 38–56.
 https://doi.org/10.1016/j.watres.2016.04.064
- 570 Chu, Y., Salles, C., Tournoud, M.-G., Got, P., Troussellier, M., Rodier, C., Caro, A., 2011. Faecal bacterial
 571 loads during flood events in Northwestern Mediterranean coastal rivers. J. Hydrol. 405, 501–511.
 572 https://doi.org/10.1016/j.jhydrol.2011.05.047
- 573 Chuah, C.J., Ziegler, A.D., 2018. Temporal Variability of Faecal Contamination from On-Site Sanitation
 574 Systems in the Groundwater of Northern Thailand. Environ. Manage.
 575 https://doi.org/10.1007/s00267-018-1016-7
- 576 Collins, R.U., Neal, C., 1998. The hydrochemical impacts of terraced agriculture, Nepal. Sci. Total Environ. 577 212. https://doi.org/10.1016/S0048-9697(97)00342-2
- 578 Descroix, L., Nouvelot, J.-F., Vauclin, M., 2002. Evaluation of an antecedent precipitation index to model
 579 runoff yield in the western Sierra Madre (North-west Mexico). J. Hydrol. 263, 114–130.
 580 https://doi.org/10.1016/S0022-1694(02)00047-1
- Evrard, O., Laceby, J.P., Huon, S., Lefèvre, I., Sengtaheuanghoung, O., Ribolzi, O., 2016. Combining
 multiple fallout radionuclides (137Cs, 7Be, 210Pbxs) to investigate temporal sediment source
 dynamics in tropical, ephemeral riverine systems. J. Soils Sediments 16, 1130–1144.
 https://doi.org/10.1007/s11368-015-1316-y

- Exley, J.L.R., Liseka, B., Cumming, O., Ensink, J.H.J., 2015. The Sanitation Ladder, What Constitutes an
 Improved Form of Sanitation? Environ. Sci. Technol. 49, 1086–1094.
 https://doi.org/10.1021/es503945x
- 588 Gaillardet, J., Braud, I., Hankard, F., Anguetin, S., Bour, O., Dorfliger, N., de Dreuzy, J.R., Galle, S., Galy, C., 589 Gogo, S., Gourcy, L., Habets, F., Laggoun, F., Longuevergne, L., Le Borgne, T., Naaim-Bouvet, F., 590 Nord, G., Simonneaux, V., Six, D., Tallec, T., Valentin, C., Abril, G., Allemand, P., Arènes, A., Arfib, 591 B., Arnaud, L., Arnaud, N., Arnaud, P., Audry, S., Comte, V.B., Batiot, C., Battais, A., Bellot, H., 592 Bernard, E., Bertrand, C., Bessière, H., Binet, S., Bodin, J., Bodin, X., Boithias, L., Bouchez, J., 593 Boudevillain, B., Moussa, I.B., Branger, F., Braun, J.J., Brunet, P., Caceres, B., Calmels, D., 594 Cappelaere, B., Celle-Jeanton, H., Chabaux, F., Chalikakis, K., Champollion, C., Copard, Y., Cotel, 595 C., Davy, P., Deline, P., Delrieu, G., Demarty, J., Dessert, C., Dumont, M., Emblanch, C., Ezzahar, J., 596 Estèves, M., Favier, V., Faucheux, M., Filizola, N., Flammarion, P., Floury, P., Fovet, O., Fournier, 597 M., Francez, A.J., Gandois, L., Gascuel, C., Gayer, E., Genthon, C., Gérard, M.F., Gilbert, D., 598 Gouttevin, I., Grippa, M., Gruau, G., Jardani, A., Jeanneau, L., Join, J.L., Jourde, H., Karbou, F., 599 Labat, D., Lagadeuc, Y., Lajeunesse, E., Lastennet, R., Lavado, W., Lawin, E., Lebel, T., Le 600 Bouteiller, C., Legout, C., Lejeune, Y., Le Meur, E., Le Moigne, N., Lions, J., Lucas, A., Malet, J.P., 601 Marais-Sicre, C., Maréchal, J.C., Marlin, C., Martin, P., Martins, J., Martinez, J.M., Massei, N., Mauclerc, A., Mazzilli, N., Molénat, J., Moreira-Turcq, P., Mougin, E., Morin, S., Ngoupayou, J.N., 602 603 Panthou, G., Peugeot, C., Picard, G., Pierret, M.C., Porel, G., Probst, A., Probst, J.L., Rabatel, A., 604 Raclot, D., Ravanel, L., Rejiba, F., René, P., Ribolzi, O., Riotte, J., Rivière, A., Robain, H., Ruiz, L., 605 Sanchez-Perez, J.M., Santini, W., Sauvage, S., Schoeneich, P., Seidel, J.L., Sekhar, M., 606 Sengtaheuanghoung, O., Silvera, N., Steinmann, M., Soruco, A., Tallec, G., Thibert, E., Lao, D.V., 607 Vincent, C., Viville, D., Wagnon, P., Zitouna, R., 2018. OZCAR: The French Network of Critical Zone 608 Observatories. Vadose Zone J. 17, 180067. https://doi.org/10.2136/vzj2018.04.0067 609 Garcia-Armisen, T., Servais, P., 2009. Partitioning and Fate of Particle-Associated E. coli in River Waters. Water Environ. Res. 81, 21–28. https://doi.org/10.2175/106143008X304613 610 611 Genereux, D., 1998. Quantifying uncertainty in tracer-based hydrograph separations. Water Resour. Res. 612 34, 915-919. https://doi.org/10.1029/98WR00010 613 Gourdin, E., Huon, S., Evrard, O., Ribolzi, O., Bariac, T., Sengtaheuanghoung, O., Ayrault, S., 2015. Sources and export of particle-borne organic matter during a monsoon flood in a catchment of northern 614 615 Laos. Biogeosciences 12, 1073–1089. https://doi.org/10.5194/bg-12-1073-2015 616 Hathaway, J.M., Hunt, W.F., Simmons, O.D., 2010. Statistical Evaluation of Factors Affecting Indicator 617 Bacteria in Urban Storm-Water Runoff. J. Environ. Eng. 136, 1360–1368. 618 https://doi.org/10.1061/(ASCE)EE.1943-7870.0000278 Helsel, D.R., Hirsch, R.M., 2002. Chapter A3: Statistical Methods in Water Resources, in: Techniques of 619 620 Water-Resources Investigations of the United States Geological Survey. Book 4, Hydrologic 621 Analysis and Interpretation. 622 Holz, G.K., 2010. Sources and processes of contaminant loss from an intensively grazed catchment 623 inferred from patterns in discharge and concentration of thirteen analytes using high intensity 624 sampling. J. Hydrol. 383, 194–208. https://doi.org/10.1016/j.jhydrol.2009.12.036 625 Huon, S., Evrard, O., Gourdin, E., Lefèvre, I., Bariac, T., Reyss, J.-L., Henry des Tureaux, T., 626 Sengtaheuanghoung, O., Ayrault, S., Ribolzi, O., 2017. Suspended sediment source and 627 propagation during monsoon events across nested sub-catchments with contrasted land uses in 628 Laos. J. Hydrol. Reg. Stud. 9, 69–84. https://doi.org/10.1016/j.ejrh.2016.11.018 629 Kim, M., Boithias, L., Cho, K.H., Sengtaheuanghoung, O., Ribolzi, O., 2018. Modeling the Impact of Land 630 Use Change on Basin-scale Transfer of Fecal Indicator Bacteria: SWAT Model Performance. J. 631 Environ. Qual. 47, 1115–1122. https://doi.org/10.2134/jeq2017.11.0456

632 Kim, M., Boithias, L., Cho, K.H., Silvera, N., Thammahacksa, C., Latsachack, K., Rochelle-Newall, E., 633 Sengtaheuanghoung, O., Pierret, A., Pachepsky, Y.A., Ribolzi, O., 2017. Hydrological modeling of 634 Fecal Indicator Bacteria in a tropical mountain catchment. Water Res. 119, 102–113. 635 https://doi.org/10.1016/j.watres.2017.04.038 636 Krometis, L.-A.H., Characklis, G.W., Simmons, O.D., Dilts, M.J., Likirdopulos, C.A., Sobsey, M.D., 2007. 637 Intra-storm variability in microbial partitioning and microbial loading rates. Water Res. 41, 506– 638 516. https://doi.org/10.1016/j.watres.2006.09.029 639 Lacombe, G., Ribolzi, O., de Rouw, A., Pierret, A., Latsachak, K., Silvera, N., Pham Dinh, R., Orange, D., 640 Janeau, J.-L., Soulileuth, B., Robain, H., Taccoen, A., Sengphaathith, P., Mouche, E., 641 Sengtaheuanghoung, O., Tran Duc, T., Valentin, C., 2016. Contradictory hydrological impacts of 642 afforestation in the humid tropics evidenced by long-term field monitoring and simulation 643 modelling. Hydrol. Earth Syst. Sci. 20, 2691–2704. https://doi.org/10.5194/hess-20-2691-2016 644 Lacombe, G., Valentin, C., Sounyafong, P., de Rouw, A., Soulileuth, B., Silvera, N., Pierret, A., Sengtaheuanghoung, O., Ribolzi, O., 2018. Linking crop structure, throughfall, soil surface 645 646 conditions, runoff and soil detachment: 10 land uses analyzed in Northern Laos. Sci. Total 647 Environ. 616–617, 1330–1338. https://doi.org/10.1016/j.scitotenv.2017.10.185 648 Long, D.T., Voice, T.C., Xagaroraki, I., Chen, A., Wu, H., Lee, E., Oun, A., Xing, F., 2017. Patterns of c-q 649 hysteresis loops and within an integrative pollutograph for selected inorganic and organic solutes 650 and E. coli in an urban salted watershed during winter-early spring periods. Appl. Geochem. 83, 651 93–107. https://doi.org/10.1016/j.apgeochem.2017.03.002 652 Lušić, D.V., Jozić, S., Cenov, A., Glad, M., Bulić, M., Lušić, D., 2016. Escherichia coli in marine water: 653 Comparison of methods for the assessment of recreational bathing water samples. Mar. Pollut. 654 Bull. 113, 438–443. https://doi.org/10.1016/j.marpolbul.2016.10.044 655 Martinez, J.M., Guyot, J.L., Filizola, N., Sondag, F., 2009. Increase in suspended sediment discharge of the 656 Amazon River assessed by monitoring network and satellite data. Catena 79, 257–264. 657 https://doi.org/10.1016/j.catena.2009.05.011 658 McKergow, L.A., Davies-Colley, R.J., 2010. Stormflow dynamics and loads of Escherichia coli in a large 659 mixed land use catchment. Hydrol. Process. 24, 276–289. https://doi.org/10.1002/hyp.7480 660 Mügler, C., Ribolzi, O., Janeau, J.-L., Rochelle-Newall, E., Latsachack, K., Thammahacksa, C., Viguier, M., Jardé, E., Henri-Des-Tureaux, T., Sengtaheuanghoung, O., Valentin, C., 2019. Experimental and 661 662 modelling evidence of short-term effect of raindrop impact on hydraulic conductivity and 663 overland flow intensity. J. Hydrol. 570, 401–410. https://doi.org/10.1016/j.jhydrol.2018.12.046 664 Navratil, O., Esteves, M., Legout, C., Gratiot, N., Nemery, J., Willmore, S., Grangeon, T., 2011. Global 665 uncertainty analysis of suspended sediment monitoring using turbidimeter in a small 666 mountainous river catchment. J. Hydrol. 398, 246-259. 667 https://doi.org/10.1016/j.jhydrol.2010.12.025 668 Nguyen, H.T.M., Le, Q.T.P., Garnier, J., Janeau, J.-L., Rochelle-Newall, E., 2016. Seasonal variability of 669 faecal indicator bacteria numbers and die-off rates in the Red River basin, North Viet Nam. Sci. 670 Rep. 6, 21644. https://doi.org/10.1038/srep21644 671 Oliver, D.M., Clegg, C.D., Heathwaite, A.L., Haygarth, P.M., 2007. Preferential Attachment of Escherichia 672 coli to Different Particle Size Fractions of an Agricultural Grassland Soil. Water. Air. Soil Pollut. 673 185, 369-375. https://doi.org/10.1007/s11270-007-9451-8 674 Pachepsky, Y., Stocker, M., Saldaña, M.O., Shelton, D., 2017. Enrichment of stream water with fecal 675 indicator organisms during baseflow periods. Environ. Monit. Assess. 189, 51. 676 https://doi.org/10.1007/s10661-016-5763-8 Pachepsky, Y.A., Allende, A., Boithias, L., Cho, K., Jamieson, R., Hofstra, N., Molina, M., 2018. Microbial 677 678 Water Quality: Monitoring and Modeling. J. Environ. Qual. 47, 931–938. 679 https://doi.org/10.2134/jeq2018.07.0277

- Park, Y., Pachepsky, Y., Hong, E.-M., Shelton, D., Coppock, C., 2017. Release from Streambed to Water
 Column during Baseflow Periods: A Modeling Study. J. Environ. Qual. 46, 219–226.
 https://doi.org/10.2134/jeq2016.03.0114
- Patin, J., Mouche, E., Ribolzi, O., Chaplot, V., Sengtahevanghoung, O., Latsachak, K.O., Soulileuth, B.,
 Valentin, C., 2012. Analysis of runoff production at the plot scale during a long-term survey of a
 small agricultural catchment in Lao PDR. J. Hydrol. 426–427, 79–92.
- 686 https://doi.org/10.1016/j.jhydrol.2012.01.015
- Patin, J., Mouche, E., Ribolzi, O., Sengtahevanghoung, O., Latsachak, K.O., Soulileuth, B., Chaplot, V.,
 Valentin, C., 2018. Effect of land use on interrill erosion in a montane catchment of Northern
 Laos: An analysis based on a pluri-annual runoff and soil loss database. J. Hydrol. 563, 480–494.
 https://doi.org/10.1016/j.jhydrol.2018.05.044
- Ribolzi, O., Evrard, O., Huon, S., de Rouw, A., Silvera, N., Latsachack, K.O., Soulileuth, B., Lefèvre, I.,
 Pierret, A., Lacombe, G., Sengtaheuanghoung, O., Valentin, C., 2017. From shifting cultivation to
 teak plantation: effect on overland flow and sediment yield in a montane tropical catchment. Sci.
 Rep. 7, 3987. https://doi.org/10.1038/s41598-017-04385-2
- Ribolzi, O., Evrard, O., Huon, S., Rochelle-Newall, E., Henri-des-Tureaux, T., Silvera, N., Thammahacksac,
 C., Sengtaheuanghoung, O., 2016a. Use of fallout radionuclides (7Be, 210Pb) to estimate
 resuspension of Escherichia coli from streambed sediments during floods in a tropical montane
 catchment. Environ. Sci. Pollut. Res. 23, 3427–3435. https://doi.org/10.1007/s11356-015-5595-z
- Ribolzi, O., Lacombe, G., Pierret, A., Robain, H., Sounyafong, P., de Rouw, A., Soulileuth, B., Mouche, E.,
 Huon, S., Silvera, N., Latxachak, K.O., Sengtaheuanghoung, O., Valentin, C., 2018. Interacting land
 use and soil surface dynamics control groundwater outflow in a montane catchment of the lower
 Mekong basin. Agric. Ecosyst. Environ. 268, 90–102. https://doi.org/10.1016/j.agee.2018.09.005
- Ribolzi, O., Patin, J., Bresson, L.M., Latsachack, K.O., Mouche, E., Sengtaheuanghoung, O., Silvera, N.,
 Thiébaux, J.P., Valentin, C., 2011. Impact of slope gradient on soil surface features and
 infiltration on steep slopes in northern Laos. Geomorphology 127, 53–63.
- 706 https://doi.org/10.1016/j.geomorph.2010.12.004
- Ribolzi, O., Rochelle-Newall, E., Dittrich, S., Auda, Y., Newton, P.N., Rattanavong, S., Knappik, M.,
 Soulileuth, B., Sengtaheuanghoung, O., Dance, D.A.B., Pierret, A., 2016b. Land use and soil type
 determine the presence of the pathogen Burkholderia pseudomallei in tropical rivers. Environ.
 Sci. Pollut. Res. 23, 7828–7839. https://doi.org/10.1007/s11356-015-5943-z
- Ribolzi, O., Silvera, N., Xayyakummanh, K., Latchachak, K., Tasaketh, S., Vanethongkham, K., 2005. The
 use of pH to spot groundwater inflows along the stream of a cultivated catchment in the
 northern Lao PDR. Lao J. Agric. For. 10, 72–84.
- Robert, E., Grippa, M., Kergoat, L., Pinet, S., Gal, L., Cochonneau, G., Martinez, J.-M., 2016. Monitoring
 water turbidity and surface suspended sediment concentration of the Bagre Reservoir (Burkina
 Faso) using MODIS and field reflectance data. Int. J. Appl. Earth Obs. Geoinformation 52, 243–
 251. https://doi.org/10.1016/j.jag.2016.06.016
- Robert, E., Kergoat, L., Soumaguel, N., Merlet, S., Martinez, J.-M., Diawara, M., Grippa, M., 2017. Analysis
 of Suspended Particulate Matter and Its Drivers in Sahelian Ponds and Lakes by Remote Sensing
 (Landsat and MODIS): Gourma Region, Mali. Remote Sens. 9, 1272.
 https://doi.org/10.3390/rs9121272
- Rochelle-Newall, E., Nguyen, T.M.H., Le, T.P.Q., Sengtaheuanghoung, O., Ribolzi, O., 2015. A short review
 of fecal indicator bacteria in tropical aquatic ecosystems: knowledge gaps and future directions.
 Front. Microbiol. 6, 308. https://doi.org/10.3389/fmicb.2015.00308
- Rochelle-Newall, E.J., Ribolzi, O., Viguier, M., Thammahacksa, C., Silvera, N., Latsachack, K., Dinh, R.P.,
 Naporn, P., Sy, H.T., Soulileuth, B., Hmaimum, N., Sisouvanh, P., Robain, H., Janeau, J.-L.,
 Valentin, C., Boithias, L., Pierret, A., 2016. Effect of land use and hydrological processes on

728 Escherichia coli concentrations in streams of tropical, humid headwater catchments. Sci. Rep. 6, 729 32974. https://doi.org/10.1038/srep32974 730 Smith, J., Edwards, J., Hilger, H., Steck, T.R., 2008. Sediment can be a reservoir for coliform bacteria 731 released into streams. J. Gen. Appl. Microbiol. 54, 173–179. 732 https://doi.org/10.2323/jgam.54.173 733 Song, L., Boithias, L., Sengtaheuanghoung, O., Oeurng, C., Valentin, C., Souksavath, B., Sounyafong, P., de 734 Rouw, A., Soulileuth, B., Silvera, N., Lattanavongkot, B., Pierret, A., Ribolzi, O., 2020. Understory 735 Limits Surface Runoff and Soil Loss in Teak Tree Plantations of Northern Lao PDR. Water 12, 736 2327. https://doi.org/10.3390/w12092327 737 Soupir, M.L., Mostaghimi, S., Dillaha, T., 2010. Attachment of Escherichia coli and Enterococci to Particles 738 in Runoff. J. Environ. Qual. 39, 1019–1027. https://doi.org/10.2134/jeq2009.0296 739 Stocker, M.D., Penrose, M., Pachepsky, Y.A., 2018. Spatial Patterns of Concentrations in Sediment before 740 and after High-Flow Events in a First-Order Creek. J. Environ. Qual. 47, 958–966. 741 https://doi.org/10.2134/jeq2017.11.0451 Strauch, A.M., Mackenzie, R.A., Bruland, G.L., Tingley, R., Giardina, C.P., 2014. Climate Change and Land 742 743 Use Drivers of Fecal Bacteria in Tropical Hawaiian Rivers. J. Environ. Qual. 43, 1475–1483. 744 https://doi.org/10.2134/jeg2014.01.0025 Tong, Y., Yao, R., He, W., Zhou, F., Chen, C., Liu, X., Lu, Y., Zhang, W., Wang, X., Lin, Y., Zhou, M., 2016. 745 746 Impacts of sanitation upgrading to the decrease of fecal coliforms entering into the environment 747 in China. Environ. Res. 149, 57–65. https://doi.org/10.1016/j.envres.2016.05.009 748 Troeger, C., Forouzanfar, M., Rao, P.C., 65 other authors, 2017. Estimates of global, regional, and 749 national morbidity, mortality, and aetiologies of diarrhoeal diseases: a systematic analysis for the 750 Global Burden of Disease Study 2015. Lancet Infect. Dis. 17, 909–948. 751 https://doi.org/10.1016/S1473-3099(17)30276-1 752 Turkelboom, F., Poesen, J., Trébuil, G., 2008. The multiple land degradation effects caused by land-use intensification in tropical steeplands: A catchment study from northern Thailand. Catena 75, 753 754 102–116. https://doi.org/10.1016/j.catena.2008.04.012 755 Vigiak, O., Ribolzi, O., Pierret, A., Sengtaheuanghoung, O., Valentin, C., 2008. Trapping Efficiencies of 756 Cultivated and Natural Riparian Vegetation of Northern Laos. J. Environ. Qual. 37, 889–897. 757 https://doi.org/10.2134/jeq2007.0251 758 Wohlsen, T., Bates, J., Vesey, G., Robinson, W.A., Katouli, M., 2006. Evaluation of the methods for 759 enumerating coliform bacteria from water samples using precise reference standards. Lett. Appl. 760 Microbiol. 42, 350-356. https://doi.org/10.1111/j.1472-765X.2006.01854.x 761 Wold, S., 1995. PLS for Multivariate Linear Modelling. In: van de Waterbeemd H. (ed.), QSAR: 762 Chemometric Methods in Molecular Design. Vol 2. Wiley-VCH, Weinheim, Germany. pp. 195-763 218. 764 Ziegler, A.D., Benner, S.G., Tantasirin, C., Wood, S.H., Sutherland, R.A., Sidle, R.C., Jachowski, N., Nullet, 765 M.A., Xi, L.X., Snidvongs, A., Giambelluca, T.W., Fox, J.M., 2014. Turbidity-based sediment 766 monitoring in northern Thailand: Hysteresis, variability, and uncertainty. J. Hydrol. 519, 2020-767 2039. https://doi.org/10.1016/j.jhydrol.2014.09.010 768 Ziegler, A.D., Giambelluca, T.W., Tran, L.T., Vana, T.T., Nullet, M.A., Fox, J., Vien, T.D., Pinthong, J., 769 Maxwell, J., Evett, S., 2004. Hydrological consequences of landscape fragmentation in 770 mountainous northern Vietnam: evidence of accelerated overland flow generation. J. Hydrol. 771 287, 124–146. https://doi.org/10.1016/j.jhydrol.2003.09.027 772






Fig. 1. (a) Location of the S4 outlet of the Houay Pano catchment in northern Lao PDR; (b) River gauging
and sampling station S4, weather station, and altitudes. Altitudes are given in meters above sea level (m
a.s.l.).





Fig. 2. Rainfall (mm h⁻¹) and discharge (Q, in L s⁻¹) for the 2011-2015 period, and *E. coli* concentration ([*E. coli*], in MPN 100 mL⁻¹) for twelve flood events from 2011 to 2015 at the outlet of the Houay Pano catchment, northern Lao PDR. The flood events of 16-17 June 2012 (C, D, and E) and of 4 August 2015 (I and J) have been decomposed into 3 and 2 separate flood events. Details of these two flood events is shown in Fig. 3. Although [*E. coli*] measures for events C-E were expressed in CFU 100 mL⁻¹, they are reported as MPN 100 mL⁻¹ for the sake of simplicity.



- Fig. 3. Monitored flood events from 2011 to 2015 at the outlet of the Houay Pano catchment, northern Lao PDR. Rainfall: rainfall (mm); Q:
- discharge (L s⁻¹); Q_{OF}: surface runoff (L s⁻¹); Q_{GW}: sub-surface flow (L s⁻¹); [TSS]: total suspended sediments concentration (g L⁻¹); Turbidity: turbidity
- (NTU); [E. coli]: E. coli concentration (MPN 100 mL⁻¹). Measurements of turbidity were lacking for event G. Although [E. coli] measures for events
- 796 C-E were expressed in CFU 100 mL⁻¹, they are reported as MPN 100 mL⁻¹ for the sake of simplicity. Red and green bands for Q_{OF} and Q_{GW} ,
- respectively, are uncertainty bands calculated with the Genereux (1998) method. Grey bands for [*E. coli*] are uncertainty intervals given by
- 798 Poisson distribution when using the standardized microplate method.




Fig. 4. Contributions (in %) of overland flow and of groundwater flow in (a) flood-event total volume of
stream flow, and in (b) flood-event total *E. coli* number. The twelve flood events were sampled from
2011 to 2015 at the outlet of the Houay Pano catchment, northern Lao PDR. Measurements of electrical
conductivity were missing for event A. Average Q_{OF-TOT}% and average [*E. coli*]_{OF-TOT}% are the average
contribution of overland flow to the in-stream flow and the average percentage of *E. coli* resulting from
overland flow, respectively. CV: coefficient of variation.






Fig. 5. Mean *E. coli* concentration per flood event ([*E. coli*]_{mean}): comparison of models' predictions with
observed values (MPN 100 mL⁻¹). (a) Q_{OF-TOT}%-based linear model against observed [*E. coli*]_{mean}; (b) PLS
model against observed [*E. coli*]_{mean}; (c) Mixing model against observed [*E. coli*]_{mean}. R²: coefficient of
determination; NSE: Nash-Sutcliffe Efficiency. The twelve flood events were sampled from 2011 to 2015
at the outlet of the Houay Pano catchment, northern Lao PDR.







824	of sub-surface flow exported during the event; Q _{GW-TOT} %: percentage of sub-surface flow during the
825	event calculated as Q_{GW-TOT}/Q_{TOT} *100; K _E : flow coefficient calculated as Q_{TOT}/R_{TOT} ; [TSS] _{mean} : flood-event
826	mean total suspended sediments concentration; Turbidity _{mean} : flood-event mean turbidity; Fallow:
827	annual percentage of the catchment area covered by fallow; Teak: annual percentage of the catchment
828	area covered by teak trees; Annual crop: annual percentage of the catchment area covered by annual
829	crops; Teak+Crop: annual percentage of the catchment area covered by annual crops grown under young
830	teak trees; <i>E. coli</i> input: monthly <i>E. coli</i> input within the catchment.

831 List of tables

- Table 1. Hydro-meteorological characteristics of the selected flood events from 2011 to 2015 at the outlet of the Houay Pano catchment,
- 833 northern Lao PDR.

	Rainfall					Dischar	ge				Wat	er quality		
Event	Start date Time	R _D (min)	R _{тот} (mm)	RI _{MAX} (mm h ^{₋1})	API (mm)	Q _{MAX} (L s ⁻¹)	Q _{TOT} (m ³)	Q _{OF-TOT} (m ³)	Q _{OF-TOT} % (%)	K _E (%)	n (-)	[TSS] _{mean} (g L ⁻¹)	Turbidity _{mean} (NTU)	[<i>E. coli</i>] _{mean} (MPN 100 mL ⁻¹)
А	05/25/2011 16:06	24	22.5	60	15.5	69.1	305.5			2.3	8	1.0	993.6	8388
В	05/15/2012 10:18	42	33.5	75	2.8	80.3	553.4	146.7	27	2.7	10	4.9	5466.0	2672
С	06/16/2012 17:48	54	10.5	40	15.0	35.8	69.7	0.0	0	1.1	6	2.9	594.2	1682
D	06/17/2012 00:00	228	39	25	48.6	242.0	2620.8	1432.4	55	11.2	18	5.3	3252.9	16053
E	06/17/2012 03:00	306	19	25	40.6	168.4	2471.3	440.9	18	21.6	7	4.1	2578.0	2181
F	06/04/2013 16:11	82	14.6	60	12.3	47.0	215.6	103.3	48	2.5	5	2.0	5860.3	11020
G	06/16/2014 13:19	36	15.4	44	9.3	31.7	222.6	38.4	17	2.4	11	0.6		1125
Η	06/12/2015 02:06	74	13.2	34	11.1	125.8	308.9	96.4	31	4.0	12	10.1	3696.0	1748
I	08/04/2015 13:22	50	6	44	4.3	95.2	127.4	69.1	54	3.8	4	4.8	6809.8	16776
1	08/04/2015 14:49	131	34.6	46	30.9	967.9	5554.2	3796.0	68	26.7	7	9.8	7790.9	16403
К	08/11/2015 21:59	81	20.8	56	17.4	374.7	1378.9	804.9	58	11.0	9	6.0	5205.8	13112
L	08/26/2015 07:48	116	32.4	54	16.2	849.6	3903.6	3118.3	80	20.0	10	8.2	4822.8	27375

834 R_D: duration of rainfall event; R_{TOT}: cumulated rainfall of the event; RI_{MAX}: maximum rainfall intensity; API: antecedent precipitation index; Q_{MAX}: peak discharge

835 during the flood event; Q_{TOT}: total volume of stream water exported during the event; Q_{OF-TOT}: total volume of surface runoff exported during the event; Q_{OF-TOT}:

836 TOT%: percentage of surface runoff during the event calculated as QOF-TOT/QTOT*100; KE: flow coefficient calculated as QTOT/RTOT; n: sample size; [TSS]mean: flood-

837 event mean total suspended sediments concentration; Turbidity_{mean}: flood-event mean turbidity; [*E. coli*]_{mean}: flood-event mean *E. coli* concentration.

838 Measurements of EC and of Turbidity were lacking for events A and G, respectively. Although E. coli measurements for events C-E were expressed in CFU 100

 mL^{-1} , they are reported as MPN 100 mL⁻¹ for the sake of simplicity.