

A rating curve model accounting for cyclic stage-discharge shifts due to seasonal aquatic vegetation

Emeline Perret, Benjamin Renard, Jérôme Le Coz

▶ To cite this version:

Emeline Perret, Benjamin Renard, Jérôme Le Coz. A rating curve model accounting for cyclic stage-discharge shifts due to seasonal aquatic vegetation. Water Resources Research, in Press, 57 (3), pp.28. $10.1029/2020 \rm WR027745$. hal-03121201

HAL Id: hal-03121201 https://hal.science/hal-03121201

Submitted on 26 Jan 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A rating curve model accounting for cyclic stage-discharge shifts due to seasonal aquatic vegetation

E. Perret¹, B. Renard¹, J. Le Coz¹

¹INRAE, UR RiverLy, F-69625, Villeurbanne, France

Key Points:

1

2

3

4

5

6

7	A rating curve model accounting for aquatic vegetation was developed and ϵ	esti-
8	nated through Bayesian inference.	
9	nformation on the vegetation development state should be used to estimate	the
10	ating curve.	
11	Discharge prediction in presence of aquatic plants was improved using the ne	ew model
12	relative errors decrease from $\pm 50\%$ to $\pm 20\%$).	

Corresponding author: Emeline Perret, emeline.perret@inrae.fr

13 Abstract

Managing stage-discharge relations at hydrometric stations affected by aquatic vegeta-14 tion is challenging. Ratings vary continuously in time due to the plant development, which 15 makes the streamflow time series difficult to predict. To the best of our knowledge, no 16 rating curve model exists to deal with stations with a vegetated channel control, only 17 manual adjustment methods. To address this issue, a temporal rating curve model ac-18 counting for transient changes due to vegetation is developed. The model is built on ba-19 sic concepts from open-channel hydraulics and plant physiology. In the model, the flow 20 resistance varies through time as a function of the plant development (growth and de-21 cay) and of the plant ability to reconfigure. Model parameters and uncertainty are es-22 timated through Bayesian inference combining prior knowledge on the hydraulic controls 23 at the station and observational data. In addition to the traditionally-used stage-discharge 24 gaugings, the model allows the use of qualitative observations on the plant development 25 state (e.g. no plant, growth, decay). The model is tested and validated for a French hy-26 drometric station where frequent gaugings (twice a month) and written comments about 27 vegetation are available over more than 20 years. Relative errors between the simulated 28 discharges and the observed discharges mostly range between $\pm 20\%$ for the temporal 29 rating curve. In contrast, they are higher than $\pm 50\%$ with a standard model with no 30 vegetation module. This case study highlights the importance of using observations about 31 plant development to predict water discharge. We finally discuss some possible improve-32 ments and extensions of the model and recommend methods for data collection. 33

³⁴ 1 Introduction

35

1.1 Rating curve management

Establishing the streamflow time series and its uncertainty is a priority for most 36 hydrological studies and water management applications. The streamflow record is com-37 monly computed by transforming a continuous water level record into water discharge 38 using a stage-discharge relation, also known as a rating curve (World Meteorological Or-39 ganization, 2010). Rating curves are site-specific and are usually built using occasional 40 measurements of water discharge Q and stage h (i.e. gaugings), combined with informa-41 tion about hydraulic controls (section or channel controls) at the hydrometric station 42 (Rantz, 1982). The process of building a rating curve is subject to a large uncertainty 43 that needs to be quantified in order to make important water-related decisions (McMil-44 lan et al., 2017). Many methods exist to estimate rating curve uncertainty and have been 45 applied with increasing frequency (Kiang et al., 2018). 46

One of the main problems for rating curve management is to deal with rating changes 47 or "shifts" (Mansanarez et al., 2019). Indeed, stage-discharge relations are not always 48 stable and can evolve in time, which leads to non-unique h-Q relations. Rating insta-49 bilities can be caused by sudden changes (e.g. morphological evolution induced by a flood, 50 human constructions that affect the hydraulic control) and/or by transient changes (e.g. 51 vegetation growth, accumulation of debris or ice). The challenge is to detect these changes 52 and update the curve accordingly, e.g. modifying the rating curve model and/or re-estimating 53 the model parameters. Some procedures exist to deal with sudden changes and are re-54 ported in Mansanarez et al. (2019). However, these methods are not suitable for tran-55 sient changes due to aquatic vegetation. In that case, the stage-discharge relation varies 56 continuously in time according to the vegetation evolution. Water discharge therefore 57 needs to be estimated from the stage and other variables depending on time. To the best 58 of our knowledge, no rating curve models accounting for aquatic vegetation exist in the 59 literature. 60

In case of a section control, removing vegetation from the critical section (e.g. weir) is a frequent and common practice to avoid any effect of plants. This procedure is in general unrealistic in case of a channel control, because vegetation should be removed from

the entire controlling channel to totally cancel the plant effect at the station. In addi-64 tion, it is considered as ecologically unacceptable in some countries and is hence forbid-65 den or at least banned from actual practice. In case of channel controls, the rating curve 66 shifts due to vegetation are generally not managed in real time, but instead are accounted 67 for with manual and non-standardized methods, according to the station manager ex-68 pertise. As far as we know, there exist no publications reviewing how different countries 69 and hydrometric services actually manage these transient changes. For example, the French 70 hydrometric services use a method called *corTH* that does not modify the base rating 71 curve (BRC) derived with vegetation-free gaugings. Instead, it replaces the observed stage 72 by a corrected stage that, once transformed by the BRC, leads to the estimated vegetation-73 affected discharge. This method is based on the assumption that the presence of plants 74 leads to a temporary and overall translation of the stage-discharge relation. This approach 75 heavily relies on gaugings to track the effect of vegetation in time. Such manual meth-76 ods have many limitations, in particular because adjustments strongly rely on the ex-77 pertise of the station manager. This expertise is in general poorly documented, making 78 manual methods hardly reproducible. As a time-varying rating curve model that accounts 79 for the hydraulic effects of seasonal aquatic vegetation is lacking, it is difficult to pre-80 dict and keep track of actual changes in the stage-discharge relation. 81

1.2 Modelling flow/plant interactions

82

Many studies examined the flow-vegetation interactions in rivers at different scales 83 (from the leaf, branch, plant, patch to the entire section) for diverse types of plants (rigid 84 or flexible) and for diverse levels of submergence (submerged or emergent) with a focus 85 on the effect of vegetation on the flow (Nikora, 2010; Folkard, 2011; Neary et al., 2012; 86 Nepf, 2012; Luhar & Nepf, 2013; Albayrak et al., 2014). These studies indicate that aquatic 87 vegetation induces a change in roughness, which modifies the flow resistance of a chan-88 nel. Plants also act as obstacles that prevent water from flowing through the part of the 89 channel cross-section that they occupy. When plant height and density increase, flow ve-90 locity decreases and channel resistance increases (Green, 2005). 91

⁹² Depending on the spatial scale of the study, the effect of the vegetation on the flow ⁹³ is either described by the drag force or by resistance coefficients such as the Darcy-Weisbach ⁹⁴ friction factor f_v [-] and the Manning coefficient n_v [m^{-1/3}.s] (Västilä & Järvelä, 2017; ⁹⁵ Shields et al., 2017). The resistance coefficients are generally preferred for stand-scale ⁹⁶ or reach-scale studies. Although it would be better to work with dimensionless Darcy-⁹⁷ Weisbach friction factors, dimensional Manning coefficients are still widely used in prac-⁹⁸ tice and remain the most popular in hydraulic equations and in rating curve models.

Many formulae and look-up tables exist to evaluate the Manning coefficients of beds qq without aquatic vegetation. They are generally based on the grain size distribution of 100 the bed surface material and other physical characteristics of a river (Meyer-Peter & Müller, 101 1948; Limerinos, 1970; Arcement & Schneider, 1989; Coon, 1998; Hicks & Mason, 1999). 102 By contrast, few methods exist to estimate the Manning coefficient n_v related to the pres-103 ence of plants (Petryk & Bosmajian, 1975; Fathi-Maghadam & Kouwen, 1997; Järvelä, 104 2004; Whittaker et al., 2013; Västilä & Järvelä, 2014; Shields et al., 2017). In addition, 105 most of them were developed for floodplain vegetation, which does not necessarily have 106 the same properties as in-stream vegetation. Some tabulated data are available in the 107 literature (Chow, 1959; Barnes, 1967; Coon, 1998; Hicks & Mason, 1999; Fisher & Daw-108 son, 2003) but they just enable evaluating n_v at a given time for a given density and type 109 of vegetation. These classic tables cannot be used for estimating the hydraulic effects 110 of plants through time. 111

Flow resistance equations for vegetated flows were historically developed for rigid plants using the analogy of the vertical rigid cylinder showing that the drag force applied to the cylinder increases with the squared average flow velocity (Petryk & Bosma-

jian, 1975; Pasche & Rouvé, 1985). However, they were not applicable in the case of nat-115 ural rivers where the vegetation is often flexible. Models for flexible plants, or for a com-116 bination of rigid and flexible plants, were created subsequently (Järvelä, 2004; Whittaker 117 et al., 2013; Västilä & Järvelä, 2014). A distinction between models for submerged and 118 for emergent plants is also important. Indeed, depending on relative submergence, i.e. 119 the ratio between the water depth and the height of the (deflected) plant H_p , the flow 120 structure changes significantly within the reach (Vargas-Luna et al., 2015), so different 121 parameterizations for the flow resistance equation need to be made (Wu et al., 1999; Shields 122 et al., 2017; Västilä & Järvelä, 2017). In particular, the choice of a suitable flow veloc-123 ity is crucial for evaluating the drag force generated by the plants and to calculate the 124 resulting flow resistance (Västilä & Järvelä, 2017). 125

Most flow resistance equations relative to aquatic vegetation depend on the den-126 sity of the plants over the channel section, their spatial distribution and their flexibil-127 ity. Unfortunately, these equations were not developed from a practical and operational 128 viewpoint (Aberle & Järvelä, 2013). The models require thorough knowledge of the plant 129 characteristics, or measurements, that most often are not available at the stations (e.g. 130 elasticity, size, age, growth rate). The plant flexibility is often used to model the abil-131 ity of the plant to reconfigure under flow stress (Jalonen, 2015). Indeed, plants can align 132 in the flow direction and bend to reduce their frontal area impacted by the flow and thus 133 exert less resistance than if they were rigid (Kouwen & Fathi-Moghadam, 2000; de Lan-134 gre, 2008). Vegetation density is often represented in models using the ratio between a 135 characteristic reference area of vegetation, commonly defined as the frontal projected area 136 of the plants perpendicular to the flow (A_p) , and the ground area (A_b) occupied by the 137 plants (Västilä et al., 2013). For leafy plants, the density is given by the Leaf Area In-138 dex: $LAI = A_L/A_b$, where A_L is the one-sided leaf area (leaves measured flat). How-139 ever, information on the type of plant present on the riverbed is scarce at hydrometric 140 stations, and measurements of plant development are also rare (e.g. no biomass samplings, 141 no camera monitoring of the plant development, etc.). Hence, the literature models for 142 n_v are too complex to use for operational purposes in hydrometry. It is nevertheless pos-143 sible and valuable to organize measurement campaigns to estimate punctually the plant 144 density in the channel, but it is difficult to monitor it continuously. A continuous-time 145 model is therefore needed to describe plan development. 146

147

1.3 Modelling aquatic plant development in rivers

Numerous plant development models exist for terrestrial plants but fewer are available for aquatic plants (Carr et al., 1997; Adams et al., 2017). Some of them require a large number of parameters to be estimated. Others relate the growth rate to other variables, such as the water temperature, the incident radiation, the nutrients within the water and the dissolved oxygen. These measurements are rarely available at hydrometric stations (with the possible exception of water temperature).

Originally, growth and decay models for aquatic plants were developed for inves-154 tigating vegetation development in lakes or reservoirs and problems of eutrophication 155 (Asaeda et al., 2001; Hilton et al., 2006). Processes governing growth in lakes are partly 156 similar to those in rivers, with the notable difference that plants in lakes are not sub-157 ject to significant time-varying flows and drags (Hilton et al., 2006). In rivers, the light 158 intensity and the water temperature are found to be the main driving factors for plant 159 development (Carr et al., 1997). However, many models relate plant growth to water tem-160 perature only because temperature is easier to measure than irradiance (Yan & Hunt, 161 1999; Briére et al., 1999; van der Heide et al., 2006). 162

Plant development models relating growth rate to water temperature take a variety of mathematical forms: linear (Tollenaar et al., 1979), bi-linear (Olsen et al., 1993),
multi-linear (Coelho & Dale, 1980), exponential (Room, 1986) and bell-shaped (Yin et

al., 1995; Yan & Hunt, 1999). Adams et al. (2017) tested 12 different growth rate-temperature 166 models on tropical seagrass species and found that the bell-shaped model of Yan & Hunt 167 (1999), which is a simplified version of the model of Yin et al. (1995), was the most ac-168 curate. This model best fits the data presented in Adams et al. (2017) and has biologically-169 meaningful parameters, such as: the base temperature that triggers plant growth, the 170 optimal temperature inducing the maximal growth rate and the ceiling temperature that 171 marks the end of growth and the beginning of the plant decay. Following the growth rate-172 temperature model of Yin et al. (1995), Yin et al. (2003) propose a bell-shaped tempo-173 ral equation for modelling plant growth using characteristic times of the plant growth 174 cycle only. The Yin et al. (2003) model is derived from biological concepts and based 175 on the assumption that the plant development can be described according to the sea-176 sons, i.e. to the time during the year. The underlying assumption is that the season evo-177 lution reflects the evolution of key forcings such as irradiance and water temperature. 178 The bell-shaped form accounts for slow growth at the beginning of the plant develop-179 ment and close to the growth end time. This model is attractive for operational purposes 180 as it uses time directly, rather than some additional physical parameters, which are not 181 always measured at hydrometric stations. 182

1.4 Objectives

183

The main objective of this paper is to develop a temporal rating curve model for 184 channel controls built on both hydraulic and biological concepts in order to better com-185 pute discharge at hydrometric stations affected by seasonal aquatic vegetation. The model 186 is intended to be used for operational purposes and hence only relies on information that 187 can be easily retrieved at hydrometric stations. Specific objectives also include: (i) as-188 sessing the relative importance of various model components such as those related to veg-189 etation growth/decay and plant reconfiguration and (ii) highlighting useful observations 190 (e.g. gaugings and information on vegetation development) that improve the estimation 191 of the rating curve. 192

The rest of the paper is organized as follows. Section 2 presents the formulation 193 of the temporal rating curve model that accounts for the presence of seasonal aquatic 194 vegetation. Section 3 describes the Bayesian approach used to estimate the model pa-195 rameters using prior knowledge on the hydraulic controls at the station and observational 196 data (hydraulic gaugings and vegetation observations). The uncertainties of both sources 197 of information are included. In Section 5, the model performance is tested using data 198 from a French hydrometric station presented in Section 4 for which frequent measure-199 ments are available. Sensitivity tests are also carried out to assess the importance of the 200 reconfiguration effect in the model and of having observations about plant development 201 for its estimation. Finally, Section 6 discusses the results and limitations of the model 202 and presents some suggestions for improving it. 203

²⁰⁴ 2 Formulation of the rating curve model

205 2.1 Hydraulic basis

The rating curve model for channel controls is constructed considering that vegetation essentially induces channel roughness changes, which modifies the flow resistance. Vegetation dissipates flow energy through a multitude of mechanisms, such as by waving in the flow or by simply blocking the flow. At the channel cross-section scale, the resulting effect of those processes can be lumped into one single resistance coefficient (e.g. Manning coefficient).

212

The model can be used at hydrometric stations fulfilling the following conditions:

- The stage-discharge relation is governed by a channel control that can be assimilated to a wide rectangular channel; section controls (e.g. rectangular weir) are not explored because, in those cases, the stage-discharge relation does not depend on bed roughness (Rantz, 1982). The effect of vegetation, if it exists, should be taken into account in another way than with a roughness change.
- 218
 2. The in-stream vegetation is made of rigid or flexible macrophytes that are just219 submerged (i.e. the height of deflected plant equals the water depth) or not deeply
 220 submerged (i.e. the relative submergence can be slightly greater than 1 but stays
 221 close to 1). The cases of emergent plants and plants staying deep and close to the
 222 bed are excluded.

223

224

225

226

227

228

249

255

- 3. The wetted area reduction by the plants from the bank or from the bed is negligible. The channel width is not reduced by plants growing from the bank and the flow is not obstructed by a dense and permanent vegetative cover on the main channel bed.
- 4. The spatial distribution of the in-stream vegetation is quite homogeneous at the station.

The standard form of a rating curve for a given hydraulic control is a power equation (Rantz, 1982; World Meteorological Organization, 2010; Mansanarez, 2016). In case of a wide and rectangular channel control, the rating curve model is generally derived from the Manning-Strickler equation, expressed as follows (Le Coz et al., 2014):

$$\begin{cases} Q(h,\tau) = \frac{1}{n(\tau)} B \sqrt{S_0} [h(\tau) - b]^c \text{ for } h > b \\ Q(h,\tau) = 0 \text{ for } h \le b \end{cases}$$
(1)

with Q the discharge, h the stage, τ the time, n the total flow resistance coefficient, Bthe channel width, S_0 the bed slope (approximating the energy slope in the case of a uniform flow), b the offset of the control (i.e. in our case the bottom level of the channel) and c = 5/3 the exponent related to the wide rectangular channel control. This kind of standard power-law rating curve can be used for modeling a single channel control affected by aquatic vegetation provided that temporal roughness variations are assessed.

The Manning-Strickler equation has the advantage to take into account the total 240 flow resistance through the total Manning coefficient n. The total flow resistance is com-241 monly decomposed into several resistance contributions with different and additive co-242 efficients (Cowan, 1956): the resistance due to bed material, to bed irregularity, to chan-243 nel geometrical variations, to obstacles in the channel and the resistance due to vege-244 tation. The resistance component related to vegetation $(n_v(\tau))$ is the most likely to vary 245 in time and the one that has the strongest temporal effect on the total flow resistance 246 (Coon, 1998). A simplified decomposition of the total flow resistance is often adopted 247 in flow-vegetation interaction studies (Morin et al., 2000): 248

$$n^{2}(\tau) = n_{b}^{2} + n_{v}^{2}(\tau) \tag{2}$$

where n_b is the Manning coefficient of the bed without vegetation (or at least with vegetation that do not evolve over the years) and $n_v(\tau)$ is the Manning coefficient related to the presence of aquatic vegetation varying in time τ . Equation 2 comes from the linear superposition principle for Darcy-Weisbach friction factors f (Aberle & Järvelä, 2013) simply converted into Manning coefficients n as follows (Smart et al., 2002):

$$n^2 = \frac{f R_h^{1/3}}{8q}$$
(3)

where g is the gravity acceleration (9.81 m/s²) and R_h is the hydraulic radius, which can be approximated by flow depth (h - b) in the case of a wide rectangular channel.

²⁵⁸ Combining Morin's decomposition of flow resistance (Equation 2) with Equation ²⁵⁹ 1, the actual discharge can be written as a product of a base discharge Q_0 not affected by the vegetation and a correction factor reflecting the effect of vegetation on the channel roughness:

$$\begin{cases} Q(h,\tau) = Q_0(h,\tau) \left(1 + \frac{n_v^2(\tau)}{n_b^2}\right)^{-1/2} \text{ for } h > b \\ Q(h,\tau) = 0 \text{ for } h \le b \end{cases}$$
(4)

263 with:

2

264

265

273

$$Q_0(h,\tau) = \frac{B\sqrt{S_0}}{n_b} [h(\tau) - b]^c$$
(5)

2.2 Flow resistance induced by aquatic vegetation

After a literature review, the physically-based flow resistance equation of Järvelä (2004) is chosen for computing $n_v(\tau)$ because it was developed for similar conditions than those presented in Section 2.1. This equation was initially created for riparian vegetation and is suitable for modeling flow resistance related to flexible (or rigid) just-submerged or emergent plants over a channel cross-section, assuming a homogeneous spatial distribution of the plants. The Järvelä (2004) equation expresses the Darcy-Weisbach flow resistance coefficient f_v relative to vegetation as follows:

$$f_v(\tau) = 4C_{D_\chi} LAI(\tau) \left(\frac{U_c(\tau)}{U_\chi}\right)^{\chi}$$
(6)

with LAI the Leaf Area Index, $C_{D_{\chi}}$ the species-specific drag coefficient, χ the species-274 specific reconfiguration exponent also called the Vogel exponent, U_c the characteristic 275 flow velocity and U_{χ} the lowest velocity used in determining χ (in other words a veloc-276 ity that scales U_c). Equation 6 takes into account the plant density over the cross-section 277 (mainly through the LAI parameter) as well as the plant ability to reconfigure under 278 flow power using $(U_c(\tau)/U_{\chi})^{\chi}$ (i.e. plant bending and streamlining). The coefficient χ 279 was evaluated using laboratory experiments for several plant species (Järvelä, 2004; Västilä 280 & Järvelä, 2014, 2017). For a rigid plant, $\chi = 0$ and a leafy flexible plant has a χ equal 281 to around -1, typically. 282

We extend the applicability of the Järvelä (2004) equation to in-stream plants that are not deeply submerged, by assuming that the water volume flowing over the vegetated part of the cross-section is negligible. Then, the vegetation induces a drag all over the water column.

According to Järvelä (2004), Equation 6 can readily be used for engineering ap-287 plications. An operational procedure has been proposed for calculating f_v (Västilä & Järvelä, 288 2017). However in practice, continuously monitoring the evolution of $LAI(\tau)$ remains 289 a difficult task. In addition, these measurements are not common at hydrometric stations, nor is the evaluation of the type of plants present on the riverbed. Equation 6 is 291 thus too complex for our purpose and therefore needs to be simplified. The Järvelä (2004) 292 model can be seen as a combination of two functions: one describing the impact of the 293 plant development (growth, increase in density, etc.) and one characterising the effect 294 of plant reconfiguration: 295

296

$$f_{v}(\tau) = d(\tau) \times \left(\frac{U_{m}(\tau)}{U_{\chi}}\right)^{\chi}$$
(7)

where $d(\tau) = 4C_{D_{\chi}}LAI(\tau)$ is a function describing the hydraulic resistance due to the plant development cycle (growth and decay) and $(U_m(\tau)/U_{\chi})^{\chi}$ is a function characterizing the plant reconfiguration. Note that in case of just-submerged or not deeply submerged plant, the characteristic velocity U_c can be assimilated to the mean velocity U_m . The function $d(\tau)$ is seen as a proxy of the plant biomass evolution and could be modeled using an empirical temporal equation not relying on $LAI(\tau)$, as will be described in the next section. It is important to note that the plant is able to bend and/or align in the flow direction only when the mean velocity U_m exceeds a minimum velocity U_{χ} . Below this value, the reconfiguration should not be taken into account, so the reconfiguration function needs to be set to 1. This condition is formally added in the flow resistance equation:

$$f_v(\tau) = d(\tau) \times \min\left\{ \left(\frac{U_m(\tau)}{U_\chi}\right)^\chi; 1 \right\}$$
(8)

Going from f_v to n_v using Equation 3 and replacing the mean velocity U_m by the discharge Q divided by the wetted area $B[h(\tau) - b]$, the time-varying Manning coefficient related to vegetation is finally expressed as follows:

$$n_v^2(\tau) = \frac{d(\tau)[h(\tau) - b]^{1/3}}{8g} \min\left\{ \left(\frac{Q(\tau)}{U_{\chi}B[h(\tau) - b]} \right)^{\chi}; 1 \right\}$$
(9)

2.3 Model for plant development

308

312

313

326

The proxy $d(\tau)$ is assumed to evolve over time in a similar way as the biomass $w(\tau)$. Therefore, a model for plant development (biomass growth and decline) is used to estimate $d(\tau)$. Remember that $d(\tau)$ and $w(\tau)$ cannot be compared in terms of values, just in terms of temporal evolution.

We first need to introduce the shorthand notation t to represent the within-year 318 time, i.e. the time within the cycle of plant development. If the time τ is expressed in 319 years, then t is simply the fractional part of τ , varying between zero and one from an 320 arbitrary start date in the year. If possible, the start date should be chosen under the 321 guidance of experts in aquatic plants (i.e. according to the plant species and its devel-322 opment cycle). In this paper, it is fixed to January 1^{st} . The growth rate temporal model 323 of Y in et al. (2003) is chosen for modelling the plant biomass evolution w(t) within a year 324 (see Figure 1): 325

$$\frac{dw}{dt} = GR_{max} \left(\frac{t_e - t}{t_e - t_m}\right) \left(\frac{t - t_b}{t_m - t_b}\right)^{\frac{t_m - t_b}{t_e - t_m}} \tag{10}$$

with dw/dt the growth rate, t_b the time at which the plant begins to grow, t_m the time at which the growth rate is maximum, t_e the time corresponding to the end of the growth and the beginning of plant decline, and GR_{max} the maximal growth rate. The Yin et al. (2003) model has a unimodal bell-shaped form like the usual growth rate models taking water temperature as input instead of time. In the Yin et al. (2003) study, t_b is assumed equal to zero, meaning that the plant start to grow at the beginning of the year. We do not make this assumption here.

Integrating Equation 10 and assuming the maximum of biomass w_{max} is reached at $t = t_e$ leads to the following equation for w(t) (see Appendix A for details):

$$\begin{cases} w(t) = w_{max} \left(\frac{t - t_b}{t_e - t_b}\right)^{\frac{t_e - t_b}{t_e - t_m}} \left[\frac{2t_e - t_m - t}{t_e - t_m}\right] & \text{for } t_b < t < t_f \\ w(t) = 0 & \text{otherwise} \end{cases}$$
(11)

Before t_b , nothing grows and the biomass is set to zero. After $t = t_e$, the growth rate dw/dt becomes negative, which corresponds to the beginning of the biomass decline. Once the final time $t_f = 2t_e - t_m$ is reached, the biomass is fixed to 0 to avoid having negative biomass. The time t_f marks the end of the plant cycle.

The model illustrated in Figure 1 describes a kind of vegetation which completely disappears at the end of its growth cycle. Plants that live through the dormant period are not considered. Their effect on flow can be included in the constant Manning coefficient n_b in our rating curve model. Note also that Equation 11 does not account for



Figure 1: Evolution of the biomass w(t) (Equation 11) and of the growth rate dw/dt (Equation 10) with characteristic times. See text for definition of variables.

external perturbations (e.g. flood, sudden drop in water temperature, changes in nutrient loads) that can impact the plant development and change its cyclic shape. These important factors will be discussed later in the section 6.3, but for the rating curve model
we choose to keep this cyclic approach (Figure 1).

The plant development model depends on parameters t_b , t_m , t_e and w_{max} only. Keeping these parameters constant from year to year implies that the vegetation cycle is exactly the same every year. This assumption is too restrictive. Consequently, these parameters are allowed to vary from year to year in the model. The case study will explore this issue in more depth and will evaluate whether at least some of these parameters can reasonably be fixed.

355

358

360

2.4 The final rating curve model

The final rating curve model is expressed using a proxy $d(\tau)$ for time-varying plant biomass:

$$\begin{cases} Q(h,\tau) = Q_0(h,\tau) \left[1 + \frac{d(\tau)[h(\tau) - b]^{1/3}}{8gn_b^2} \min\left\{ \left(\frac{Q(h,\tau)}{U_{\chi}B[h(\tau) - b]} \right)^{\chi}; 1 \right\} \right]^{-1/2} \text{ for } h > b \\ Q(h,\tau) = 0 \text{ for } h \le b \end{cases}$$
(12)

359 with:

$$d(\tau) = d_{max} \left(\frac{t - t_b}{t_e - t_b}\right)^{\frac{t_e - t_b}{t_e - t_m}} \left[\frac{2t_e - t_m - t}{t_e - t_m}\right] = d_{max} d_0(\tau)$$
(13)

where $Q_0(h,\tau)$ is the stage-discharge relation not affected by the presence of vegetation (see Equation 5), d_{max} is the maximal proxy biomass and $d_0(\tau)$ is the dimensionless timevarying component of $d(\tau)$. In practice, the discharge time series can be estimated from Equation 12 using the stage time series $h(\tau)$ and the plant evolution $d(\tau)$ deduced from Equation 13. No explicit solution exists for Equation 12 because the discharge Q is present on both sides of the equation. Nevertheless, Equation 12 can be rewritten in a polynomial form by squaring both sides and then solved using the Newton-Raphson algorithm:

$$Q^{2} + \gamma_{1} \min\left\{\frac{Q^{\chi}}{\gamma_{2}}; 1\right\} Q^{2} - Q_{0}^{2} = 0$$
(14)

with:

369

370

371 372

373

382

$$\gamma_1 = \frac{d(\tau)[h(\tau) - b]^{\frac{1}{3}}}{8gn_b^2} \tag{15}$$

$$\gamma_2 = U^{\chi}_{\chi} B^{\chi} [h(\tau) - b]^{\chi} \tag{16}$$

For mathematical convenience, the reconfiguration coefficient χ ranges between 0 and -2 (i.e. same range as in Vogel (1994) according to Luhar & Nepf (2013)). This limitation is reasonable regarding the values found for χ in literature, i.e. varying around -1 (Västilä & Järvelä, 2014), and ensures that Equation 14 has a unique solution.

The model is generic but needs to be estimated using local information. It can be applied to any stations that comply with the conditions presented in Section 2.1, for instance using the code released with this paper (see Data availability statement).

381 3 Bayesian inference

3.1 Extending the model to return the vegetation state

The final rating curve model of Equation 12 requires computing the dimensionless 383 time series $d_0(\tau) = d(\tau)/d_{max}$, which can be interpreted as a dimensionless indicator 384 of the vegetation development state at time τ (Figure 2a): $d_0(\tau) = 0$ means that there 385 is no vegetation; $d_0(\tau) = 1$ denotes the vegetation peak; $0 < d_0(\tau) < 1$ corresponds 386 to vegetation growth (before t_e) and decline (after t_e). Extending the model to return 387 the vegetation state will allow to use vegetation observations as estimation data, by com-388 paring the observed vegetation state with the one simulated by the model through $d_0(\tau)$. 389 To do so, two steps are required in practice, as described next. 390

The first step is to convert $d_0(\tau)$ into an angle $\eta(\tau)$ of values comprised between 0 and 2π (Figure 2b). This procedure is done to distinguish more readily between the growth ($\eta < \pi$) and the decline ($\eta > \pi$) stages. Formally:

$$\begin{cases} \eta(\tau) = \pi d_0(\tau) \text{ if } t \le t_e \\ \eta(\tau) = 2\pi - \pi d_0(\tau) \text{ if } t > t_e \end{cases}$$
(17)

The second step is to extend the rating curve model of Equation 12 so that it returns this angle, in addition to discharge. Because handling circular variables such as angle η requires specific care, it is more convenient to return its sine and cosine. Consequently, the model to be estimated can be viewed as a model with two inputs (stage h and time τ) and three outputs (discharge \hat{Q} , $\cos(\hat{\eta})$ and $\sin(\hat{\eta})$), as formalized below:

$$\mathcal{M}(h,\tau;\boldsymbol{\theta}) = \begin{pmatrix} \hat{Q}(h,\tau;\boldsymbol{\theta}) \\ \cos\left(\hat{\eta}(\tau;\boldsymbol{\theta})\right) \\ \sin\left(\hat{\eta}(\tau;\boldsymbol{\theta})\right) \end{pmatrix}$$
(18)

Equation 18 makes the unknown parameters $\boldsymbol{\theta} = (B, S_0, n_b, b, c, \chi, U_{\chi}, \boldsymbol{t}_b, \boldsymbol{t}_m, \boldsymbol{t}_e, \boldsymbol{d}_{max})$ to be inferred explicit. The components of the $\boldsymbol{t}_b, \boldsymbol{t}_m, \boldsymbol{t}_e, \boldsymbol{d}_{max}$ vectors are year-specific



Figure 2: Interpretation of the dimensionless biomass proxy $d_0(\tau)$ as a position within the vegetation cycle (a) and its translation in terms of an angle η (b).

so for each year these components are estimated. The first output is obtained by applying Equation 12; the second and third outputs are obtained by first applying Equation 13 to compute $d_0(\tau)$, then by transforming it into angle $\hat{\eta}(\tau)$ through Equation 17.

406

416

3.2 Inference setup and assumptions

Let $(\tilde{\tau}_i, \tilde{h}_i, \tilde{Q}_i, \cos(\tilde{\eta}_i), \sin(\tilde{\eta}_i))_{i=1:M}$ denote the observational data used to estimate the model \mathcal{M} . Estimation data are vectors comprising all input/output variables of model \mathcal{M} . The vector can further be interpreted as a "traditional" gauging $(\tilde{h}_i, \tilde{Q}_i)$ augmented with a vegetation observation $(\tilde{\tau}_i, \cos(\tilde{\eta}_i), \sin(\tilde{\eta}_i))$. Note that the vegetation observation can be derived from a qualitative assessment of the vegetation state. Importantly, it may be uncertain, so that it can accommodate more or less vague statements as shown in Table 1.

Table 1: Correspondence between qualitative assessments of the vegetation state and the vegetation observations used for model estimation.

Statement	angle $\widetilde{\eta}_i$	$\cos(\widetilde{\eta}_i)$	$\sin(\widetilde{\eta}_i)$
1/ there is no vegetation	0 ± 0	1 ± 0	0 ± 0
2/ there are few developing plants	$\pi/4 \pm \pi/4$	0.5 ± 0.5	0.5 ± 0.5
3/ there is vegetation, and the vegetation cycle	$\pi/2 \pm \pi/2$	0 ± 1	0.5 ± 0.5
is in its growing stage			
4/ there is vegetation, and the vegetation cycle	$3\pi/2 \pm \pi/2$	0 ± 1	-0.5 ± 0.5
is in its decaying stage			

Note: depending on the statement details, these values can be reviewed and their associated uncertainty can be adjusted.

The following assumptions are made to relate estimation data to the model predictions: $\begin{pmatrix} & & & \\ & & & \\ & & & \\ & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & & \\$

$$\begin{cases} \widetilde{Q}_{i} = \hat{Q}\left(\widetilde{h}_{i}, \widetilde{\tau}_{i}; \boldsymbol{\theta}\right) + \delta_{Q,i} + \varepsilon_{Q,i} \\ \cos(\widetilde{\eta}_{i}) = \cos\left(\hat{\eta}(\widetilde{\tau}_{i}; \boldsymbol{\theta})\right) + \delta_{\cos,i} + \varepsilon_{\cos,i} \\ \sin(\widetilde{\eta}_{i}) = \sin\left(\hat{\eta}(\widetilde{\tau}_{i}; \boldsymbol{\theta})\right) + \delta_{\sin,i} + \varepsilon_{\sin,i} \end{cases}$$
(19)

⁴¹⁷ This equation states that for each output variable, the observed value is equal to ⁴¹⁸ the corresponding value simulated by the model plus an observation error $\delta_{.,i}$ plus a struc-⁴¹⁹ tural error $\varepsilon_{.,i}$. All errors are assumed to be mutually independent, and the following ⁴²⁰ probabilistic assumptions are made:

$$\begin{cases} \delta_{Q,i} \sim \mathcal{N}(0, u_{Q,i}) ; \varepsilon_{Q,i} \sim \mathcal{N}(0; \gamma_{Q,1} + \gamma_{Q,2} \dot{Q}_i) \\ \delta_{cos,i} \sim \mathcal{N}(0, u_{cos,i}) ; \varepsilon_{cos,i} \sim \mathcal{N}(0; \gamma_{cos}) \\ \delta_{sin,i} \sim \mathcal{N}(0, u_{sin,i}) ; \varepsilon_{sin,i} \sim \mathcal{N}(0; \gamma_{sin}) \end{cases}$$
(20)

For each output variable, the standard deviation $u_{.,i}$ is assumed to be known and 422 may vary between observations. This standard deviation quantifies measurement uncer-423 tainty and should ideally be specified following an uncertainty analysis of the measure-424 ment process (see Le Coz et al., 2014, for more details). Conversely, the standard devi-425 ation of structural errors is more difficult to specify before model estimation even though 426 reasonable bounds can be defined; it is therefore assumed to be unknown and is inferred 427 along with model parameters $\boldsymbol{\theta}$. Note that for the discharge output, the standard de-428 viation of structural errors is allowed to increase linearly with the simulated discharge; 429 this is made to account for the frequently-observed fact that structural uncertainty of 430 rating curves tends to increase with the simulated discharge (Mansanarez et al., 2019). 431 Conversely, the standard deviation of structural errors is assumed to be constant for the 432 sine and cosine outputs. 433

3.3 Posterior distribution

438

445

⁴³⁵ Due to the mutual independence assumption for all error terms in Equation 19, the ⁴³⁶ likelihood resulting from the assumptions discussed in the previous section can be com-⁴³⁷ puted as follows:

$$p\left(\tilde{\boldsymbol{Q}},\cos(\tilde{\boldsymbol{\eta}}),\sin(\tilde{\boldsymbol{\eta}}) \mid \boldsymbol{\theta},\boldsymbol{\gamma},\tilde{\boldsymbol{\tau}},\tilde{\boldsymbol{h}}\right) = \prod_{i=1}^{M} \phi\left(\tilde{Q}_{i};\hat{Q}\left(\tilde{h}_{i},\tilde{\tau}_{i};\boldsymbol{\theta}\right),\sqrt{u_{Q,i}^{2}+\left(\gamma_{Q,1}+\gamma_{Q,2}\hat{Q}_{i}\right)^{2}}\right) \times \prod_{i=1}^{M} \phi\left(\cos(\tilde{\eta}_{i});\cos\left(\hat{\eta}(\tilde{\tau}_{i};\boldsymbol{\theta})\right),\gamma_{\cos}\right) \times \prod_{i=1}^{M} \phi\left(\sin(\tilde{\eta}_{i});\sin\left(\hat{\eta}(\tilde{\tau}_{i};\boldsymbol{\theta})\right),\gamma_{\sin}\right)$$

$$(21)$$

where $\phi(z; m, s)$ is the probability density function (pdf) of a Gaussian distribution $\mathcal{N}(m, s)$ with mean m and standard deviation s evaluated at z. Note that the multiplicative nature of this likelihood makes the handling of missing data straightforward: corresponding terms can simply be omitted in the product of Equation 21.

Based on Bayes theorem, this likelihood can be combined with a prior pdf on unknown parameters, $p(\theta, \gamma)$, to yield the following posterior pdf:

$$p\left(\boldsymbol{\theta},\boldsymbol{\gamma} \mid \widetilde{\boldsymbol{Q}},\cos(\widetilde{\boldsymbol{\eta}}),\sin(\widetilde{\boldsymbol{\eta}}),\widetilde{\boldsymbol{\tau}},\widetilde{\boldsymbol{h}}\right) \propto p\left(\widetilde{\boldsymbol{Q}},\cos(\widetilde{\boldsymbol{\eta}}),\sin(\widetilde{\boldsymbol{\eta}}) \mid \boldsymbol{\theta},\boldsymbol{\gamma},\widetilde{\boldsymbol{\tau}},\widetilde{\boldsymbol{h}}\right) \times p\left(\boldsymbol{\theta},\boldsymbol{\gamma}\right)$$
(22)

⁴⁴⁶ Note that the specification of prior distributions is case-specific and will be further
⁴⁴⁷ discussed in the case study. Guidelines and examples related to the Bayesian method used
⁴⁴⁸ here can also be found in Le Coz et al. (2014); Lundquist et al. (2016); Horner et al. (2018);
⁴⁴⁹ Mansanarez et al. (2019).

450 **3.4 MCMC sampling**

The posterior pdf of Equation 22 is explored by means of a Markov Chain Monte Carlo (MCMC) sampler, described in Renard et al. (2006). In this paper a total of 100,000 MCMC iterations are performed. The first half is discarded as a burn-in period, and the remaining iterations are further thinned by a factor of 10; this implies that subsequent computations are based on a MCMC subsample of size 5,000, which is sufficient to achieve an acceptable accuracy while avoiding storage and computing time issues. MCMC convergence is checked by visualising all MCMC traces.

458 4 Study case

459

4.1 The Ill River at Ladhof, France

The Ladhof hydrometric station is located on the Ill River in Colmar, East France, 460 and is operated by the national hydrological service DREAL Grand-Est (station code: 461 A1350310, WGS84 coordinates: Lon=7.384773 Lat=48.102498). This station is of in-462 terest since it is affected by aquatic seasonal vegetation and has been gauged frequently. 463 A pressure gauge has recorded continuously the stage since 1958. Gaugings were made 464 either with current meters or hydroacoustic profilers (ADCP). Figure 3 gives details about 465 the station location, its surrounding environment and the type of plant present on the 466 site. 467

Around the station, floodplains are bounded by well-maintained dikes on both sides. 468 A small dam and a weir with a fish-way are present at approximately 800 m upstream 469 of the station and $3.6 \,\mathrm{km}$ downstream of the station, respectively. The weir is too dis-470 tant from the station to control the flow. For in-stream flows (h < 3 m), a rectangular 471 channel control is assumed. The main channel vegetation influence noticed by the field 472 hydrologists is within this water depth range. No vegetation from the bank blocks the 473 flow. When the flow reaches the floodplains (i.e. water depth above $3 \,\mathrm{m}$), the hydraulic 474 control becomes more complex. The flow section changes radically and can be approx-475 imated by a combination of the main channel (represented by a wide and rectangular 476 channel) and the two floodplains (represented by a single wide and rectangular channel). 477 In this study, the focus is made only on flows for stages lower than 3 m. 478

The riverbed at the station is sand-dominated and flat with no large bedforms. In-479 stream vegetation is composed of flexible and filamentous macrophytes that are, most 480 of the time, just-submerged or not deeply submerged. Plants are mainly Ranunculus. 481 As they grow, they tend to concentrate near the water surface. The height of the deflected 482 vegetation within the channel was never evaluated by the local staff, so no quantitative 483 estimation of the relative submergence range at this station is available. According to the station managers, the plant species has not changed over the years and the riverbed 485 stayed quite stable. The plant density at the station can nevertheless vary from year to 486 year, but no quantitative estimation of these variations was provided by the hydromet-487 ric service. The macrophytes always die during winter or are washed out before the end 488 of the year; no dormant vegetation is observed. Conditions are thus appropriate for ap-489 plying the temporal vegetation model. 490

491 4.2 Experimental set-up

4.2.1 Data

492

Hydraulic gaugings (measurements of h and Q) from January 1996 to August 2017 were performed with a high frequency at the station (generally one gauging every 15 days). A total of 492 measurements of h and Q were carried out under the condition h < 3 m. The measurements were sometimes associated with comments about vegetation at the time of gauging. Typical comments were: no plant, few plants, many blooming plants.



Figure 3: The Ill River at Ladhof hydrometric station: a) its location in France, b) aerial view of its surrounding environment and c) the type of aquatic vegetation (Ranunculus) present in the main channel.

A total of 293 comments are available among the 492 hydraulic gaugings. In the following, they are referred to as vegetation observations. We also have access to additional data such as water level from the French national hydrological database (http://www .hydro.eaufrance.fr/), air temperature and irradiance time series from the atmospheric Safran re-analysis over France (Vidal et al., 2010) and data collected from the station managers such as water temperature time series since 2009.

4.2.2 Estimation

504

Calculations are made over a 22-year data period, where sudden rating curve changes 505 due to morphological evolution happened. The proposed rating curve model accounts 506 for transient changes due to vegetation evolution only (i.e. deviations from the base rat-507 ing curve due to the presence of plants). Sudden changes due to bed evolution need to 508 be dealt with using another approach (Mansanarez et al., 2019). The vegetation model 509 should be used over stable periods, meaning periods where no significant changes in terms 510 of river geometry are detected, i.e. no variations of S_0 , B, n_b , b or c. If the sudden change 511 is not identified before using the vegetation model, interference with the estimation of 512 plant-related parameters could happen, namely with χ , U_{χ} , d_{max} , t_b , t_m , t_e . The dataset 513 is therefore divided into several stable periods following the method presented in Appendix 514 B. Four stable periods are identified over the 22-year period. Only bed offset b is chang-515

ing across these four periods, which reflects bed erosion and deposition at the station; the other parameters S_0 , B, n_b , c of the BRC do not change over the entire data-set period. riod.

A 15% uncertainty is set for all the discharge measurements, which is fairly high but reflects the challenging conditions of measurements at this site (low flow velocity and water depth, presence of vegetation, soft surface riverbed). Uncertainty related to the water level measurement is neglected. The vegetation observations transcribed into a position within the plant cycle (see Sections 3.1 and 3.2) are also affected with large uncertainty, since the interpretation of the station manager comments is subjective.

4.2.3 Priors

525

The prior distributions of the model parameters are given in Table 2. Our knowl-526 edge about the plant species at the station and their behaviour is limited, leading to wide 527 priors for parameters related to plant development. The prior distribution for bed slope 528 S_0 was chosen taking into account the difficulty to measure bed slopes in plains. In low-529 lands, bed slopes are quite low and it is often challenging to identify the right part of 530 the channel for the measurement to have a representative value of the bed slope at the 531 station. The same priors were given for series of parameters that need to be re-estimated 532 for each new stable period (i.e. b) as well as for vegetation parameters that evolve ev-533 ery year $(t_b, t_m, t_e \text{ and } d_{max})$. As the plant species was the same over the 22 years of 534 data, parameter χ reflecting the plant flexibility is constant over the entire period. The 535 prior for d_{max} is deliberately imprecise. It was chosen to represent values of d_{max} that 536 can lead to a coefficient of resistance related to plant development, i.e. n_v considering 537 no reconfiguration correction, twelve times higher than the coefficient of resistance re-538 lated to the bed without vegetation n_b . 539

540 5 Results

In this section, the performance of the temporal vegetation model is investigated using the data from Ladhof station. The model is evaluated in terms of parameter identification and relative errors. We also explore the interest of accounting for the plant reconfiguration effect. Using various tests derived from the Ladhof dataset, the importance of using various types of information for estimating the rating curve (i.e. gaugings and vegetation observation) is highlighted.

547

5.1 Parameters estimation

Figure 4 shows the prior and posterior distributions of the estimated parameters 548 in the form of boxplots. The convergence of MCMC samples is verified visually for all 549 the parameters. Most parameters are well-identified meaning that their posterior dis-550 tributions are more precise than their prior ones; this is the case for most BRC param-551 eters of each stable periods and for χ (i.e. posterior boxplots are three times narrower 552 for n_b , S_0 , χ and up to 16 times narrower for b). Parameters related to plant-development 553 show varying properties depending on the years. Except for a few years (e.g. 2001 and 554 2017), posterior distributions of t_e are quite precise (14 narrower than prior distribution, 555 on average). For the other three parameters $(d_{max}, t_b \text{ and } t_m)$, posterior boxplots stay 556 rather wide (between 4 and 6 times narrower than prior boxplots, on average). Data for 557 the year 2017 are only available for half of the year, which might partly explain the poor 558 identification of those plant-development parameters. Their posterior distributions are 559 nevertheless more precise than their prior ones, and would probably be even more pre-560 cise with additional information. 561

The parameters describing the timing of the vegetation cycle are always located at approximately the same time over the years (see Figure 4). It is important to recall

Parameter	Distribution
Control chann	nel
$B [\mathrm{m}]$	$\mathcal{LN}(\ln(25); 0.1)$
S_0 [-]	$\mathcal{LN}(\ln(0.001); 0.5)$
$n_b [{\rm m}^{-1/3}{\rm s}]$	$\mathcal{LN}(\ln(0.02); 0.2)$
b_i [m]	$\mathcal{N}(0.8; 0.2)$
c [-]	$\mathcal{N}(1.67; 0.025)$
Vegetation pa	rameters
χ [-]	$\mathcal{N}(-1.4; 0.2)$
$U_{\chi} [{\rm m/s}]$	= 0.1 (fixed)
$t_{b,j}$ [yr]	$\mathcal{U}(0;1)$
$t_{m,j}$ [yr]	$\mathcal{U}(0;1)$
$t_{e,j}$ [yr]	$\mathcal{U}(0;1)$
$d_{max,j}$ [-]	$\mathcal{U}(0;5)$
Structural une	certainty parameters
$\gamma_{Q,1} \; [\mathrm{m}^3/\mathrm{s}]$	$\mathcal{LN}(\ln(1);1)$
$\gamma_{Q,2}$ [-]	$\mathcal{LN}(\ln(0.5);1)$
γ_{cos} [-]	$\mathcal{U}(0;1)$
γ_{sin} [-]	$\mathcal{U}(0;1)$

Table 2: Prior distributions of the temporal vegetation model parameters for the Ill at Ladhof study case.

 $1 \leq i \leq 4$ refers to the selected stable period; $1 \leq j \leq 22$ refers to the selected year within the data period; $\mathcal{LN}(m_{log}; s_{log})$ represents a lognormal variable whose logarithm has mean equal to m_{log} and standard deviation equal to $s_{log}; \mathcal{N}(m_g; s_g)$ corresponds to a Gaussian distribution with a mean m_g and a standard deviation $s_g; \mathcal{U}(a_u; b_u)$ corresponds to a uniform distribution defined by its lower (a_u) and upper (b_u) bounds.

that the plant growth in rivers is mostly driven by two key environmental factors, which 564 are the water temperature and the light intensity (Carr et al., 1997). At Ladhof station, 565 these factors evolve similarly over the years of the entire data-set period, which may ex-566 plain why some plant-development parameters do not strongly vary over the years. As 567 a consequence, some of them could be fixed over the entire 22-year period to simplify 568 the model. This scenario will be investigated in section 5.3. Some exceptions are noticed 569 about the timing of the vegetation cycle in Figure 4, such as a delay at the beginning 570 of growth in 2016 (see t_b) and a late senescence in 2005 (see t_e). During those two years, 571 no specific anomalies in the water temperature or the irradiance time series were noted. 572

Maximal proxy biomass d_{max} is more variable from year to year than parameters 573 t_b, t_m, t_e . Remember that d_{max} is a key factor in the expression of n_v (see Equation 12). 574 A strong variation in d_{max} thus reflects a strong variation of flow resistance due to plants. 575 In 1998, the posterior distribution for d_{max} is quite close to the prior higher bound (see 576 Figure 4); this bound was set so that $n_v \approx 12 \times n_b$, which is quite strong for the sole 577 influence of in-stream plants but not unrealistic given the values found in the literature; 578 the Manning coefficient n_v can vary from around 0.025 to $0.4 \,\mathrm{m}^{-1/3}$ s (Chow, 1959; Coon, 579 1998; Wang & Zhang, 2019). In their review of flow resistance, Fisher & Dawson (2003) 580 categorize Ranunculus among the 'Submerged fine-leaved' vegetation type with reported 581 Mannings n values from 0.01 to more than 0.45 in some cases. The high values of d_{max} 582 reflecting high value of n_v may also include additional effects such as the possible reduc-583 tion in wetted area due to plants growing from banks, which were assumed negligible in 584 our case. 585

⁵⁸⁶ Correlations between t_b , t_m , t_e and d_{max} were checked for each year. Figure 5 shows ⁵⁸⁷ an example of the resulting correlation matrix for the year 2004. It looks similar for other ⁵⁸⁸ years. In general, a strong correlation between t_m and t_e is noticed; for some specific years ⁵⁸⁹ and to a lesser extent, correlations between t_b and t_m are also noted. We expect to bet-⁵⁹⁰ ter identify model parameters by reducing the number of parameters varying per year, ⁵⁹¹ for example by estimating a single t_m over the entire period of 22 years.



Figure 4: Prior and posterior distributions of the estimated parameters of the vegetation model in case of the Ladhof station over the 22 vegetation years from 1996 to 2017. White and green boxplots relate to the prior and posterior distributions, respectively. The boxes represent the 95% probability interval of the distribution with its median symbolized by a line. Black points refer to parameter values maximising the posterior pdf, also known as maximum a posteriori estimators (MAP).



Figure 5: Example of posterior scatterplot correlation matrix between parameters of the plant development model for year 2004.

592 5.2 Time series reconstruction

Using the stage record at the station and the posterior distributions of the estimated 593 parameters, it is possible to reconstruct the discharge time series $Q(\tau)$ with uncertainty 594 as well as the plant development evolution $d(\tau)$ over the period of 22 years. Figure 6 shows 595 these two time series with uncertainty. The 95% total uncertainty includes both the para-596 metric (i.e. related to estimation errors of the parameters θ in Equation 18) and struc-597 tural (i.e. related to structural errors in Equation 20) uncertainties. The "Maxpost" curves 598 correspond to the results obtained using the maximum a posteriori estimates, i.e. parameter-599 values maximising the posterior pdf. The uncertainty of $Q(\tau)$ is low and the measured 600 and simulated water discharges are close, i.e. within the 20% error range (Figure 6a). 601 For more clarity, a zoom on year 2015 is shown in Figure 6c. The effect of vegetation is 602 generally well-described by the model. For comparison, the computed discharges obtained 603 with a standard model with no vegetation module (see Q_0 in Equation 5) and their as-604 sociated uncertainty are added to Figure 6c. Total uncertainty is higher when using the 605 model with no vegetation module and observed discharges are better approximated by 606 the vegetation temporal model. The temporal vegetation model is also able to simulate 607 vegetation cycles that are strongly varying from year to year (see $d(\tau)$ in Figure 6b). It 608 is thus possible to account for variable flow resistance induced by the plants. At the Lad-609 hof station, plant cycles have different shapes and amplitudes, which shows that the anal-610 ysis of the vegetation cycle on a yearly basis is essential even for a case where water tem-611 perature and light intensity conditions are similar over the years. 612



Figure 6: Results obtained with the temporal vegetation model over the 22 years of data at the Ladhof station : a) water discharge time series $Q(\tau)$ with uncertainties, b) time evolution of the plant biomass proxy $d(\tau)$ with parametric uncertainty over the entire period of study, c) water discharge evolution $Q(\tau)$ for year 2015 obtained with the temporal vegetation model and with a standard model with no vegetation module and d) plant evolution $d(\tau)$ for year 2015. Blue lines in b) and c) represent a change in hydraulic control occurring for h > 3 m: the vegetation model is not valid above this line (see Section 4.1).

5.3 Potential for reducing the number of time-varying parameters

Figure 7 shows the effect of fixing some of the yearly-varying parameters to a constant (but still unknown) value. It compares the relative errors E_r between the gauged discharge and the discharge predicted by the temporal vegetation model (using the MAP estimates).

Relative errors obtained with a standard model with a constant Manning coeffi-618 cient (no vegetation module) are also added in Figure 7. In that case, E_r can exceed 50% 619 and vary mostly between -28% and +81%. This result highlights the importance of us-620 ing a rating curve model that accounts for the presence of plants when it is needed through 621 a time-varying Manning coefficient $n_v(t)$. When all parameters related to the plant de-622 velopment vary, E_r values mostly range between $\pm 20\%$, which is a promising result con-623 sidering the uncertainty applied to the measured water discharge (15%). Fixing either 624 t_b or t_m does not result in any noticeable increase in relative errors. By contrast, fixing 625 t_e or d_{max} leads to larger relative errors, suggesting that these parameters should be yearly-626 varying. 627

For the analyses described in the remainder of the paper, we decided to fix t_m based on the following rationale: a fixed t_m is expected to be very precisely estimated, and this might have the positive side-effect of improving the precision for parameter t_e through the correlation displayed in Figure 5. In these conditions, the model succeeds in identifying parameters and in predicting water discharge with relatively low errors ($\pm 20\%$, see Figure 7).



Figure 7: Relative discharge errors E_r for various computation configurations. Dashed lines delimit the $\pm 20\%$ range of errors.

5.4 Reconfiguration versus plant growth

In the rating curve model, it was assumed that the resistance due to aquatic plant was induced by the plant development (growth and decline) but also by the plant ability to reconfigure for high flow velocities. In this section, the relative importance of these two main effects is investigated.

When fixing the reconfiguration coefficient χ to zero, Equation 12 becomes only 639 function of plant development $d(\tau)$. The reconfiguration correction is thus not activated. 640 With $\chi = 0$, plants are assumed to be rigid and not to reconfigure under flow power. 641 To evaluate the importance of the reconfiguration correction in the rating curve model. 642 we compare the discharge obtained with the complete temporal vegetation model account-643 ing for reconfiguration $Q_{\rm R}$ with the discharge obtained with no reconfiguration correc-644 tion $Q_{\text{no-R}}$. The discharge $Q_{\text{no-R}}$ is computed using the same MAP estimators than those 645 estimated for $Q_{\rm R}$, except that χ is now fixed to 0 (i.e. the rating curve is not re-estimated). 646 For more details, please refer to Perret et al. (2020). 647

Figure 8 shows the relative discharge differences due to deactivating the reconfig-648 uration function in the estimated model. Only the data for which vegetation was present 649 were selected and plotted in Figure 8. A large difference in discharge is observed, reach-650 ing more than 70%. The reconfiguration correction is larger when the quantity of plant 651 is larger (i.e. $d(\tau)$ is high) and when the mean velocity is higher. The difference between 652 $Q_{\text{no-R}}$ and Q_{R} is negative. Indeed, by contrast to flexible plants, rigid plants cannot bend 653 or align in the flow direction to reduce their frontal areas impacted by the flow. The flow 654 is therefore impeded by their presence. Rigid plants act as strong obstacles. Discharge 655 is thus reduced in presence of rigid plants compared with flexible plants. 656

In Figure 8, measurements in presence of vegetation and for $U_m \leq 0.3 \,\mathrm{m/s}$ are barely 657 available. Nevertheless, it is possible to predict that in this area the difference between 658 $Q_{\text{no-R}}$ and Q_{R} will tend to 0 as we approach the threshold value of $U_m = U_{\chi} = 0.1 \text{ m/s}$. 659 For reminder, the critical flow velocity for which the plant is able to reconfigure U_{χ} was 660 fixed to $0.1\,\mathrm{m/s}$ for all the calculations. When $U_m~\leq~U_\chi$ the plant reconfiguration is 661 made not possible by definition in the model (i.e. the function characterizing the recon-662 figuration equals the value of 1 in Equation 9). The reconfiguration correction thus be-663 comes inactive. 664



Figure 8: Impact of the reconfiguration correction in the estimated temporal vegetation model versus the gauged mean velocity U_m and the proxy biomass d at the station of the III at Ladhof.

5.5 Sensitivity to the number and type of gaugings

665

At many hydrometric stations, gaugings are less frequent than those performed at 666 Ladhof station, and indications about vegetation are generally not available. From the 667 perspective of testing the model in more realistic conditions, the Ladhof station case is 668 subdivided into different tests varying the number and type of available information (i.e. 669 gaugings and vegetation observations) for the computation. These tests are described 670 in Table 3. They were chosen to represent diverse kinds of stations : 1/research stations, 671 where many data are available for estimating the water discharge; the original Ladhof 672 station is considered as a research station; 2/operational stations, more common than 673 research stations and used for surveillance and monitoring purposes; and 3/participa-674 tory stations, still rare nowadays, where gaugings are very rare and where most of the 675 vegetation observation comes from the goodwill of outside actors or automatic devices 676 (e.g. photographs of the river section). 677

The model performance is investigated comparing the test results in terms of parameter identification and relative errors. Figure 9 shows posterior distributions of parameters estimated for all the tests. Figure 10 shows the discharge relative errors obtained with the 283 validation data of tests O1, O2, P1 and P2. For information, discharge relative errors resulting from tests R1 and R2 at the same 283 validation points are added to Figure 10, but note that for these two cases, these points are estimation points too.

The main conclusion arising from these sensitivity tests are summarized in the following:

1. With vegetation information only, estimating time parameters related to plant development is possible (see Figure 9, test P2 and parameters t_b , t_m , t_e). However, for the other parameters the posteriors remain very similar to the priors (see Figure 9, test P2 and parameters d_{max} , B, S_0 , n_b , c, χ , b). Unless these priors are very accurate, this procedure leads to fairly large discharge errors (see Figure 10, test P2).

			Gaugings		Vegetation observations		
Test	Kind of station	Number of estimation data [*]	Number of validation data ^{\dagger}	Frequency	Number of estimation data [*]	Frequency	
R1	Research	492	0	2/month	293	1/month	
R2	Research	492	0	2/month	0	0	
O1	Operational	209	283	10/year	119	5/year	
O2	Operational	209	283	10/year	0	0	
P1	Participatory	88	283	4/year	293	1/month	
P2	Participatory	0	283	0	293	1/month	

Table 3:	Test	configurations	chosen	to	evaluate	the	temporal	vegetation	model.
		0					1	0	

*: Estimation data are those used for the estimation of the model parameters; they are different from the validation data.

Validation data are additional data used only for testing and validating our model; they are the same for tests O1, O2, P1 and P2 in order to compare their results.

2. Adding only a few gaugings per year allows a better estimation of the rating curve parameters (see Figure 9 and compare improvements from tests P2 to P1 for all parameters). While still large, discharge relative error E_r values are already smaller than when using a well-gauged rating curve that ignores vegetation (compare test P1 in Figure 10 versus test with no vegetation module in Figure 7).

692

693

694

695

696

698

- 3. At the other end of the spectrum, if plenty of gaugings are available and well-distributed 697 over the years, then this suffices to estimate the model (compare test R1 versus test R2 in Figure 9 and 10). A large amount of information is included in the wa-699 ter discharge measurements, including the resistance induced by the vegetation. 700
- 4. The operational case is more difficult to interpret as results seem to be parameter-701 dependent and year-dependent (Figure 9, compare test O1 and test O2). The use 702 of vegetation observations improves the estimation of time parameters for some 703 years but does not have any positive effect on the estimation of the BRC param-704 eters. For the operational cases, most errors are within $\pm 20\%$, with a few isolated 705 points showing larger errors (Figure 10). 706

To sum up, the model has a good performance as long as a few gaugings combined 707 with vegetation observations are available. Although vegetation observations are not es-708 sential when many gaugings are available, it does help a lot when gaugings are scarce, 709 in particular for the identification of parameters related to plant development. 710



Figure 9: Model sensitivity to the type and number of gaugings or observations. Prior and posterior distributions (95% probability intervals) of the model parameters estimated for all cases presented in Table 3. Black points represent the MAP estimators.



Figure 10: Discharge relative error as a function of observed water discharge obtained for the tests presented in Table 3.

6 Comments on model use and further developments

6.1 How to use the model?

712

722

723

724

725

726

727

733

One of the objective of this paper was to develop a rating curve model for operational use. In this part, we detail how the temporal rating curve model can be used in practice. Figure 11 formalizes its functioning. To predict discharge in vegetated flows, an operational user may use the computer implementation of the model that is freely available (see data availability statement). She/he will need to provide the following local information:

- ⁷¹⁹ 1. A data file containing two inputs (i.e. the time and the stage time series recorded ⁷²⁰ at the hydrometric station) and observations (i.e. gaugings and vegetation obser-⁷²¹ vations converted into a position into the vegetation cycle using $\cos(\tilde{\eta}_i)$ and $\sin(\tilde{\eta}_i)$).
 - 2. Prior specifications for parameters that define the channel control, namely for the channel width B, the channel slope S_0 , the base Manning coefficient n_b , and the bed level b.
 - 3. Prior specification for plant-related parameters (i.e. the reconfiguration parameter χ , the reconfiguration velocity U_{χ} , the characteristic times of the plant cycle (t_b, t_m, t_e) and the maximal proxy biomass d_{max}).

In the model configuration files, non-informative priors can be specified in case no information can be provided a priori. After launching the model runner, the user can have access to the estimated parameters and to four outputs with their parametric and to-

tal uncertainty envelopes (see Figure 11), in particular to the discharge $Q(\tau)$ and the proxy

biomass $d(\tau)$ time series.



Figure 11: Diagram of the temporal rating curve model for vegetated flows: inputs, parameters and outputs.

6.2 Data collection strategy for vegetation-influenced rating curves

Some suggestions of data collection strategies are made based on our experience 734 of modelling the Ladhof station. The first recommendation is to have information about 735 the aquatic plants present at the station, namely about their nature, morphology and 736 mechanical properties. We therefore advice the station managers to have opinions of ex-737 perts in aquatic plants in order to improve the estimation of discharge, even if it is not 738 a common practice at hydrometric station. Such information could be used to specify 739 more precise priors for model parameters that are related to plant-development (i.e. t_b , 740 t_m , t_e and d_{max}). Note that even if the plant properties are known specifically, there is 741

⁷⁴² no means to deduce the parameters χ and U_{χ} precisely. For example, Järvelä (2004) iden-⁷⁴³ tified the plant species in his study but used laboratory experiments anyway to evalu-⁷⁴⁴ at empirically these parameters. Look-up tables with χ -values exist for few floodplain ⁷⁴⁵ plants, but they are still missing for in-stream plants.

Secondly, the distribution of gaugings within the vegetation cycle (i.e. within the year) is likely to be an important factor for a good estimation of the model. Although this point was not explored in the paper, we suggest to have measurements amongst the various states of the vegetation cycle (no plants, growth, peak, decline). In this paper, the gauging measurements were performed about every two weeks and not necessarily scheduled according to the plant cycle.

Finally, this study highlights the importance of having data to characterize the plant 752 development. The plant development is associated to the proxy biomass d in our model, 753 but technically this parameter cannot be measured in the field because it is a proxy. In 754 practice, the angle η is used in the rating curve model to provide information on the state 755 of development of the plant. We thus suggest collecting information describing the po-756 sition in the plant cycle, which would be used as observational data and would yield valu-757 able information to estimate model parameters. Such information could take the form 758 of simple explicit comments about plant development relative to previous visit at the sta-759 tion, such as no / same amount of / more / less plants than before. Comments such as 760 few plants, scarce plants, lots of plants, should be avoided, because they are too vague 761 to be translated into a plant cycle position. Some specific states of the plant cycle are 762 easy to identify such as the vegetation peak, the period without vegetation and the pe-763 riods of growth and decay. We also recommend collecting quantitative information such 764 as the percentage of channel cross-section covered by vegetation, in order to directly as-765 similate information about d_0 in the model (i.e. the dimensionless proxy biomass). 766

As shown in this study, the model can be calibrated using simple observations on 767 the amount of aquatic vegetation that can be made by non biologist observers, e.g. the 768 field hydrologists in charge of streamflow measurement during their field visits. By con-769 trast, post-processing vegetation observation, i.e. transforming them into angles in the 770 development cycle, is generally more time-consuming and complex. For quantifying the 771 plant development cycle, several inexpensive monitoring techniques can be considered 772 such as direct observations (e.g. explicit comments or evaluation of the percentage of chan-773 nel cross-section covered by vegetation), image analysis from frequent (and automatic) 774 photography of the station or analysing satellite or drone images (Biggs et al., 2018). In-775 direct vegetation observations could also be deduced from other nearby hydrometric sta-776 tions, since plant cycles are probably similar as long as the climate and the type of plants 777 are the same at these other stations. Assimilating those data could be a promising de-778 velopment of our model. Thanks to the spatial coherence, these new data would help to 779 better identify the plant parameters of the model and to reduce the uncertainty of the 780 resulting discharge time series at the station. 781

782

6.3 Improvements of the rating curve model

The proposed temporal rating curve model is promising for the estimation of water discharge at hydrometric stations affected by aquatic plants. Nevertheless, the discharge relative errors are still high $(-20\% < E_r < +20\%)$ even if acceptable compared with the uncertainty of the gaugings (15%). In this section, possible improvements of the temporal model proposed in this paper are discussed.

We anticipate that incorporating some biology concepts in the model might lead to better results. Using covariates controlling variations of the plant biomass could help predict the parameters of the vegetation model $d(\tau)$. For example, from their monitoring of the seasonal growth and decay of Ranunculus between 1971 and 1976 in an unshaded section of the River Lambourn at Bagnor, England, Ham et al. (1981) found that

the spatial expansion of Ranunculus in a given year tended to be greater as the mean 793 discharge in spring of that year was greater. Therefore, cumulative discharge in the spring 794 season might be a good candidate for modelling the maximum proxy biomass d_{max} of 795 Ranunculus or similar vegetation. However, Ham et al. (1981) discuss several other influencing factors and mention other sites where high discharge may limit the spatial ex-797 pansion of Ranunculus. Also, the water temperature (T) or its cumulative form (T_c) could 798 help predict the characteristic times of the plant growth and decay. At hydrometric sta-799 tions, water temperature is arguably the most common continuously measured param-800 eter after the water level. A possible approach would be to relate t_b to the time where 801 the degree-day had accumulated sufficiently for the plant to start growing $(t_b = t | T_c =$ 802 $T_{c,\min}$]), t_m to the time where the water temperature reaches the optimal temperature 803 T_{opt} for plant growth $(t_m = t[T = T_{\text{opt}}])$, and t_e to the time where the degree-day had 804 accumulated too much, leading to the plant decay $(t_e = t[T_c = T_{c,max}])$. This method 805 might work for t_b and t_m but less likely for t_e . Indeed, it often happens that the plant 806 decline in natural rivers is driven by plant removal due to high velocities rather than by 807 natural mortality. The optimal temperature T_{opt} and the minimal cumulative degree-808 day for plant growth $T_{c,\min}$ would be estimated using the Bayesian framework in order 809 to deduce t_b and t_m . 810

Ultimately, it could be judicious to use a dynamic model rather than a temporal 811 model to predict the plant evolution at hydrometric stations. The evolution of the biomass 812 proxy $d(\tau)$ is cyclic in our model. However, it does not always follow a bell-shaped curve 813 in practice. Plant development can be sometimes subject to perturbations depending on 814 external factors. For example, a brutal variation in water temperature, change in nutri-815 ent loads, human plant removal, or a large flood can strongly impact the typical evolu-816 tion of the plant. A dynamic model that would update the biomass as a function of such 817 external drivers could increase the performance of the rating curve model. Compartment 818 models are often used to describe dynamic behaviour, e.g. reservoir models in hydrol-819 ogy or crop growth compartment models in biology (Johnson & Thornley, 1983). By anal-820 ogy, the proxy of biomass $d(\tau)$ in rivers could be seen as a stock of biomass that evolves 821 in time according to diverse external factors (Fovet et al., 2010). The production of biomass 822 would be regulated by environmental factors that favor or limit the plant growth, such 823 as the water temperature, the light intensity, the amount of nutrients, etc. The loss of 824 biomass would be modelled by detachments of biomass (due to hydraulic variations, nat-825 ural senescence, external interventions, etc.). Using such model is promising for the fu-826 ture because these external factors are expected to change according to climate projec-827 tions (e.g. increase in water temperature, eutrophication). One of the main advantages 828 of using this dynamic approach is that parameters would be estimated one time only for 829 the entire data period and not every year as for the cyclic approach. In addition, more 830 complex stations than Ladhof station could also be dealt with such a dynamic model, 831 832 such as, for example, stations where plants do not die at the end of each year.

833 834

6.4 Extension of the rating curve model to fully submerged or emergent plants

The applicability of the model is limited to specific conditions detailed in Section 2.1. It could be extended by revising those conditions. However, limiting the model complexity is important to ensure that it is applicable for operational purposes.

Importantly, the model applicability is limited to a specific range of relative submergence (close to 1), namely for just-submerged or not deeply submerged plants. To cover as many cases as possible, the model could be extended to emergent and fully submerged plants (i.e. $[h-b]/H_p \leq 1$ and $[h-b]/H_p > 1$, respectively). This would require modifying the flow resistance equation $n_v(\tau)$. Major changes in Equation 9 would be related to the plant density parametrization (because emergent and submerged plants do not have the same properties) and to the chosen characteristic velocity (because flow structure strongly changes from submerged to emergent plants).

In the case of submerged plants, the flow structure over the section would change 846 and the water volume located above the ground-plants should be accounted for. The flow 847 structure would be composed of two separate vertical layers: one for vegetation and one 848 for overflow. The mean velocity within the vegetated part of the cross-section U_v should 849 be retained as the new characteristic velocity for the computation of n_v , in replacement 850 of the depth-averaged velocity U_m used in our study. The velocity U_v is harder to es-851 852 timate than U_m , but methods such as the common two-layer approach exist (Luhar & Nepf, 2013; Västilä et al., 2016). The velocity U_v depends on the length of the submerged 853 plants, and hence on their evolution. Using U_v instead of U_m in Equation 9 will thus com-854 plicate the flow resistance model, because (i) another proxy for plant development would 855 be needed and (ii) U_m would no longer be the characteristic velocity and its simple re-856 lation with the total discharge Q (i.e. $U_m = Q/(B[h-b]))$ would not hold anymore. 857

For emergent plants, no change of parametrization for the characteristic velocity 858 U_c would be needed in the flow resistance equation (i.e. $U_c = U_m$). Indeed, the flow 859 structure would still be composed of one layer. However, the plant density parameter 860 (i.e. $d(\tau)$, which simulates the proxy biomass of the entire vegetation) should be revis-861 ited since only the submerged part of the plants needs to be accounted for. Järvelä (2004) 862 suggests that partially submerged plants generally have uniform distributions of LAI over 863 their height, and so adds the relative submergence $[h-b]/H_p$ as a correction in Equa-864 tion 6. The same type of correction could be applied to Equation 9. It would imply the 865 addition of another time-varying model $H_p(\tau)$ to be able to predict the plant height evo-866 lution in function of time. 867

In our opinion, extending the model to submerged plants should have priority because emergent plants are not often observed in main channels and are more relevant for the study of floodplain flows.

871 7 Conclusion

This study is a first attempt at deriving a rating curve model for channel controls 872 to predict water discharge time series at hydrometric stations affected by seasonal in-873 stream plants. A temporal rating curve model is developed based on the assumption that 874 vegetation induces a change in bed roughness mainly, which modifies the flow resistance. 875 In the model, the bed roughness is described using a time-varying resistance coefficient, 876 which combines the change in resistance due to plant growth and decay, and to the plant 877 ability to reconfigure with high flow velocity (i.e. streamlining and bending). A Bayesian 878 approach using prior knowledge on hydraulic controls at the station and observation data 879 (gaugings and comments about the amount of vegetation) is used for estimating the model 880 parameters and uncertainty. With such an approach, it is possible to compute the wa-881 ter discharge time series over a given time-period along with the evolution of the proxy 882 biomass, which informs about the plant resistance potential. 883

Several tests are conducted to investigate the model performance using data from 884 a station affected by aquatic vegetation. The relative discharge errors and the param-885 eter identification are analysed and discussed. The relative importance of the two main 886 effects that drive the time-varying resistance coefficient is investigated. Although plant 887 development is the main cause of flow resistance variation, the reconfiguration correc-888 tion was found to be crucial for the discharge calculation. This correction is especially 889 important when the mean velocity and the plant biomass are large. The tests also sug-890 gest that the complexity of the model can be reduced by fixing some year-to-year vary-891 ing parameters related to plant growth and decay, without reducing the model perfor-892 mance. Both gaugings and vegetation observations are valuable for a good calibration 893

of the model. Simple comments on the amount of aquatic vegetation yield valuable information for the estimation of the parameters related to the plant growth and decay, especially when hydraulic gaugings are scarce. Finally, the temporal rating curve model accounting for aquatic vegetation can reduce the relative discharge errors to acceptable levels, from a range of $\pm 50 \%$ to $\pm 20 \%$ as found in the application case.

Obviously, further tests and the development of guidelines and procedures are needed 899 to prepare the transfer of the proposed method to hydrological services. The main per-900 spectives for model development are the extension to fully submerged plants and the im-901 plementation of a dynamic model instead of the temporal approach based on a param-902 eterized shape of the growth and decay cycle from year to year. A dynamic model would 903 predict the biomass evolution based on external and environmental factors that enhance 904 or limit the plant growth. Such an approach will certainly require a deeper knowledge 905 of the plant species, distribution and dynamics at a given site. But again, a trade-off be-906 tween model complexity and performance should be sought to ensure its operational ap-907 plicability by field hydrologists. 908

³⁰⁹ Appendix A Temporal plant development model

The biomass model is obtained by integrating in time the growth rate model of Yin et al. (2003) (Equation 10):

$$w(t) = \int \frac{dw}{dt} dt = \int GR_{max} \left(\frac{t_e - t}{t_e - t_m}\right) \left(\frac{t - t_b}{t_m - t_b}\right)^p dt$$
(A1)

with $p = (t_m - t_b)/(t_e - t_m)$, dw/dt the growth rate, w(t) the biomass, t_b the time at which the plant starts to grow, t_m the time at which the growth rate is the greatest, t_e the end of the growth time and GR_{max} the maximal growth rate.

⁹¹⁶ In the following, the integration of Yin et al. (2003) model is detailed step by step:

$$\int \frac{dw}{dt}dt = \frac{GR_{max}}{t_e - t_m} \left[\int t_e \left(\frac{t - t_b}{t_m - t_b} \right)^p dt - \int t \left(\frac{t - t_b}{t_m - t_b} \right)^p dt \right]$$
(A2)

The second part of Equation A2 can be easily integrated by using the equality $t = t - t_b + t_b$:

$$\frac{1}{(t_m - t_b)^p} \int t(t - t_b)^p dt = \frac{1}{(t_m - t_b)^p} \int (t - t_b + t_b)(t - t_b)^p dt$$
$$= \frac{1}{(t_m - t_b)^p} \left(\int (t - t_b)(t - t_b)^p dt + \int t_b(t - t_b)^p dt \right)$$
$$= \frac{1}{(t_m - t_b)^p} \left[\frac{(t - t_b)^{p+2}}{p+2} + t_b \frac{(t - t_b)^{p+1}}{p+1} \right]$$
$$= \frac{1}{(t_m - t_b)^p} (t - t_b)^{p+1} \frac{pt + t + t_b}{(p+2)(p+1)} + C_0$$
(A3)

920

922

923

926

917

with C_0 a constant equal to zero since $w(t = t_b) = 0$.

Going back to the integration of the entire model, Equation A2 becomes:

$$w(t) = \frac{GR_{max}}{t_e - t_m} \left[t_e \left(\frac{t - t_b}{t_m - t_b} \right)^p \frac{(t - t_b)}{(p+1)} - \frac{(t - t_b)^{p+1}}{(t_m - t_b)^p} \frac{(pt + t + t_b)}{(p+2)(p+1)} \right]$$

$$= \frac{GR_{max}}{t_e - t_m} \left(\frac{t - t_b}{t_m - t_b} \right)^p (t - t_b) \left[\frac{(p+2)t_e - (p+1)t - t_b}{(p+2)(p+1)} \right]$$
(A4)

We now assume that the maximum of biomass w_{max} is reached at $t = t_e$. To calculate w_{max} , t is replaced by t_e in Equation A4:

$$w_{max} = \frac{GR_{max}}{t_e - t_m} \left(\frac{t_e - t_b}{t_m - t_b}\right)^p (t_e - t_b) \left[\frac{t_e - t_b}{(p+2)(p+1)}\right]$$
(A5)

⁹²⁷ The biomass model is deduced from the comparison between Equations A4 and A5, ⁹²⁸ by forming the ratio $w(t)/w_{max}$:

929

932

$$\frac{w(t)}{w_{max}} = \left(\frac{t-t_b}{t_e-t_b}\right)^p \frac{(t-t_b)}{(t_e-t_b)} \left[\frac{(p+2)t_e - (p+1)t - t_b}{t_e-t_b}\right] = \left(\frac{t-t_b}{t_e-t_b}\right)^{p+1} \left[\frac{(p+2)t_e - (p+1)t - t_b}{t_e-t_b}\right]$$
(A6)

Reminding that $p = (t_m - t_b)/(t_e - t_m)$, the final biomass model can be expressed as follows:

$$w(t) = w_{max} \left(\frac{t - t_b}{t_e - t_b}\right)^{\frac{t_e - t_b}{t_e - t_m}} \left[\frac{2t_e - t_m - t}{t_e - t_m}\right]$$
(A7)

Appendix B Identification of stable periods

This appendix details the method used for identifying stable periods where no significant changes in terms of river geometry can be detected. Over a stable period, no sudden changes (due to bed evolution) in the rating curve should be observed.

We assume that significant change in riverbed happens after a morphogenic flood 937 (Mansanarez et al., 2019). The date following the flood event marks the beginning of a 938 new stable period. For convenience, morphogenic flood is arbitrarily defined as a flood 939 exceeding the 2-year flood $(Q > Q_2)$. For the Ladhof station, the possible changes af-940 ter such a flood are overall bed erosion or deposition at the station according to station 941 managers. In other words, it might induce a change in the offset of the main channel con-942 trol b. No particular variations of channel slope S_0 , channel width B and bed roughness 943 n_b have been previously noticed over the years. Note that at the Ladhof station, the veg-944 etation disappears every winter and n_b depends on the type of sediments and bedforms 945 present on the riverbed only. Consequently, only one parameter of the BRC needs to be 946 re-estimated when a new stable period begins. Ten stable periods were identified based 947 on $Q > Q_2$ for the Ladhof station over the 22 years of data. The stage time series (Fig-948 ure B1a) show that even after floods the riverbed level does not obviously vary. The num-949 ber of stable periods can thus be further reduced. 950

Base rating curves of the ten periods were estimated using the classical power-law model and the Bayesian method presented in Le Coz et al. (2014):

$$\begin{cases} Q(h,\tau) = \frac{1}{n_b} B \sqrt{S_0} [h(\tau) - b]^c \text{ for } h > b \\ Q(h,\tau) = 0 \text{ for } h \le b \end{cases}$$
(B1)

The base rating curves are shown in Figure B1b along with the posterior distributions 954 of b in Figure B1c. The estimation of b is sometimes uncertain due to the small num-955 ber of gaugings available over the considered periods (see gaugings from period 1 for ex-956 ample). Combining visual observations of the BRC (Figure B1b) and analysis of the riverbed 957 level evolution (Figure B1c), the 22 years of data were divided into four periods. If two 958 successive BRCs overlap and if the posterior distribution of b is in the same range, we 959 assume that no changes have happened and that the two successive periods can be merged. 960 The initial 10 stable periods are hence merged into four stable periods with this com-961 parison technique. Figure B1d and Figure B1e show the characteristics of the BRCs for 962 the new four periods. 963

964 Acknowledgments

This work was funded by SCHAPI, France's national hydrological service (SRNH 2018

and 2019 contracts between INRAE and the Ministry of Ecology). Data for the Ladhof



Figure B1: Identification of stable periods at the III at Ladhof hydrometric station over the 22-year of data available: a) stage time series of the ten periods defined by $Q > Q_2$ flood events, b) base rating curves (BRC) estimated using Bayesian method for the ten periods and c) distributions of the riverbed level b, and d) BRC estimated using Bayesian method for the four resulting periods and e) distributions of b. Blue numbers refer to the number of gaugings without vegetation used for computing the BRC over the considered period. Colored rectangles in b) highlight the four final periods.

station were provided by the DREAL Alsace/Grand-Est. Data were mostly collected by
Daniel Moritz and his colleague Vincent Mossard. We gratefully thank them for their
contribution. The authors would also like to thank Juha Järvelä, Sara Puijalon and Ellis Penning for the interesting discussions we had in the earlier stages of this work. We
finally want to thank the two anonymous reviewers and Paul A. Carling, associate ed-

itor and editor for their valuable and insightful comments, which have undoubtedly improved this paper.

P74 Competing interests. The authors declare that they have no conflict of inter P75 est.

Data availability statement The data set and the data processing algorithms
 used in this study are available on request from the authors and are archived in https://
 forge.irstea.fr/projects/bam/files (folder name: Perret_VegetationPaper_WRR.zip)..

979 References

- Aberle, J., & Järvelä, J. (2013). Flow resistance of emergent rigid and flexible floodplain vegetation. *Journal of Hydraulic Research*, 51(1), 33-45.
- Adams, M.-P., Collier, C., Uthicke, S., Ow, Y.-X., Langlois, L., & O'Brien., K.
- (2017). Model fit versus biological relevance: Evaluating photosynthesis temperature models for three tropical seagrass species. Scientific reports,
 7(39930), 1-12. doi: 10.1038/srep39930
- Albayrak, I., Nikora, V., Miler, O., & O Hare, M. (2014). Flow-plant interactions at leaf, stem and shoot scales: drag, turbulence, and biomechanics. Aquatic Sciences, 76(2), 269-294. doi: 10.1007/s00027-013-0335-2
- Arcement, G.-J., & Schneider, V.-R. (1989). Guide for selecting Manning's roughness coefficients for natural channels and flood plains. U.S. Geological Survey Water Supply, Paper 2339, 1-67.
- Asaeda, T., Trung, V., Manatunge, J., & Bon, T. (2001). Modelling macrophyte nutrient phytoplankton interactions in shallow eutrophic lakes and the evalua tion of environmental impacts. *Ecological Engineering*, 16, 341-357.
- Barnes, H.-H. (1967). Roughness characteristics of natural channels: color photographs and descriptive data for 50 stream channels for which roughness coefficients have been determined. U.S. Geological Survey Water Supply, Paper 1849.
- Biggs, H., Nikora, V., Gibbins, C., Fraser, S., Green, D., Papadopoulos, K., & Hicks,
 D. (2018). Coupling Unmanned Aerial Vehicle (UAV) and hydraulic surveys to
 study the geometry and spatial distribution of aquatic macrophytes. Journal of
 Ecohydraulics, 3(1), 45-58. doi: 10.1080/24705357.2018.1466666
- Briére, J.-F., Pracros, P., Roux, A.-Y.-L., & Pierre, J. (1999). A novel rate model of temperature-dependent development for arthropods. *Environmental Entomology*, 28, 22-29.
- Carr, G.-M., Duthie, H.-C., & Taylor, W. (1997). Models of aquatic plant productivity: a review of the factors that influence growth. *Aquatic Botany*, 59, 195-215.
- 1007 Chow, V.-T. (1959). Open-channel hydraulics. McGraw-Hill, NewYork.
- Coelho, D.-T., & Dale, R.-F. (1980). An energy-crop growth variable and temper ature function for predicting maize growth and development: planting to silking.
 Agronomy journal, 72, 503-510.
- Coon, W. (1998). Estimation of roughness coefficients for natural stream channels
 with vegetated banks. U.S. Geological Survey Water Supply, Paper 244, 145.
- Cowan, W.-L. (1956). Estimating hydraulic roughness coefficients. Agricultural Engineering, 37(7), 473-475.
- de Langre, E. (2008). Effect of wind on plants. Annual Review of Fluid Mechanics,
 40, 141-168. doi: 10.1146/annurev.fluid.40.111406.102135
- Fathi-Maghadam, M., & Kouwen, N. (1997). Nonrigid, nonsubmerged, vegetative
 roughness on floodplains. Journal of Hydraulic Engineering, 123(1), 51-57. doi:
 doi:10.1061/(ASCE)0733-9429(1997)123:1(51)
- Fisher, K., & Dawson, F. H. (2003). Reducing uncertainty in river flood conveyance
 Roughness review (Tech. Rep.). London, UK: DEFRA / Environment Agency,
 Project W5A-057.
- Folkard, A.-M. (2011). Vegetated flows in their environmental context: a review.
 Proceedings of the Institution of Civil Engineers Engineering and Computational

Mechanics, 164(1), 3-24.

1025

1046

1047

1048

- Fovet, O., Belaud, G., Litrico, X., Charpentier, S., Bertrand, C., Dauta, A., &
 Hugodot, C. (2010). Modelling periphyton in irrigation canals. *Ecological Modelling*, 221, 1153-1161. doi: 10.1016/j.ecolmodel.2010.01.002
- Green, J. (2005). Comparison of blockage factors in modelling the resistance of channels containing submerged macrophytes. *Rivers Research and Applications*, 21, 671-686. doi: 10.1002/rra.854
- Ham, S. F., Wright, J. F., & Berrie, A. D. (1981). Growth and recession of aquatic
 macrophytes on an unshaded section of the River Lambourn, England, from 1971
 to 1976. Freshwater Biology, 11, 381-390.
- Hicks, D.-M., & Mason, P.-D. (1999). Roughness characteristics of New Zealand
 rivers. NIWA, Christchurch.
- Hilton, J., O'Hare, M., Bowes, M., & Jones, J. (2006). How green is my river? a new paradigm of eutrophication in rivers. *Science of the Total Environment*, 365, 66-83.
- Horner, I., Renard, B., Le Coz, J., Branger, F., McMillan, H. K., & Pierrefeu, G.
 (2018). Impact of stage measurement errors on streamflow uncertainty. Water
 Resources Research, 54 (1952-1976).
- Jalonen, J. (2015). Hydraulics of vegetated flows: estimating riparian plant drag
 with a view on laser scanning applications (PhD Thesis). Aalto University School
 of Engineering.
 - Järvelä, J. (2004). Determination of flow resistance caused by non-submerged woody vegetation. International Journal of River Basin Management, 2(1), 61-70. doi: 10.1080/15715124.2004.9635222
- Johnson, I., & Thornley, J. (1983). Vegetative crop growth model incorporating
 leaf area expansion and senescence, and applied to grass. *Plant, Cell and Environ- ment*, 6, 721-729.
- Kiang, J., Gazoorian, C., McMillan, H., Coxon, G., Le Coz, J., & Westerberg, I.
 (2018). A comparison of methods for streamflow uncertainty estimation. Water Resources Research, 54, 7149-7176. doi: https://doi.org/10.1029/2018WR0222708
- Kouwen, N., & Fathi-Moghadam, M. (2000). Friction factors for coniferous trees alons rivers. Journal of Hydraulic Engineering, 126 (10), 732-740.
- Le Coz, J., Renard, B., Bonnifait, L., Branger, F., & Le Boursicaud, R. (2014). Combining hydraulic knowledge and uncertain gaugings in the estimation of
- hydrometric rating curves: A Bayesian approach. Journal of Hydrology, 509,
 573-587. doi: https://doi.org/10.1016/j.jhydrol.2013.11.016
- Limerinos, J.-T. (1970). Determination of the Manning coefficient from measured
 bed roughness in natural channels. U.S. Geological Survey Water Supply, Paper
 1898-B.
- Luhar, M., & Nepf, H. (2013). From the blade scale to the reach scale: a characterization of aquatic vegetative drag. Advances in Water Resources, 51, 305-316. doi: 10.1016/j.advwatres.2012.02.002
- Lundquist, J. D., Roche, J. W., Forrester, H., Moore, C., Keenan, E., Perry, G., ...
 Dettinger, M. D. (2016). Yosemite hydroclimate network: Distributed stream
 and atmospheric data for the tuolumne river watershed and surroundings. Water
 Resources Research, 52, 7478-7489.
- Mansanarez, V. (2016). Non-unique stage-discharge relations: Bayesian analysis of complex rating curves and their uncertainties (PhD Thesis). Université Grenoble
 Alpes.
- Mansanarez, V., Renard, B., Le Coz, J., Lang, M., & Darienzo, M. (2019). Shift
 happens! adjusting stage-discharge rating curves to morphological changes at
- known times. Water Resources Research, 55, 2876-2899. doi: https://doi.org/
 1077 10.1029/2018WR023389
- McMillan, H., Seibert, J., Petersen-Overleir, A., Lang, M., White, P., & Snelder, T.

- (2017). How uncertainty analysis of streamflow data can reduce costs and promote
 robust decisions in water management applications. Water Resources Research,
 53, 5220-5228. doi: https://doi.org/10.1002/2016WR020328
- Meyer-Peter, E., & Müller, R. (1948). Formulas for bed-load transport. In *Proceedings of the 2nd iahr congress* (p. 39-64). Stockholm, Sweden.
- Morin, J., Leclerc, M., Secretan, Y., & Boudreau, P. (2000). Integrated twodimensional macrophytes-hydrodynamic modeling. Journal of Hydraulic Research, 38(3), 163-172. doi: doi:10.1080/00221680009498334
- Neary, V., Constantinescu, S., Bennett, S., & Diplas, P. (2012). Effects of vegetation
 on turbulence, sediment transport, and stream morphology. *Journal of Hydraulic Engineering*, 138(9), 765-776.
- Nepf, H.-M. (2012). Hydrodynamics of vegetated channels. Journal of Hydraulic Research, 50(3), 262-279.
- Nikora, V. (2010). Hydrodynamics of aquatic ecosystems: An interface between ecol ogy, biomechanics and environmental fluid mechanics. *River Research and Appli- cations*, 26, 367-384. doi: https://doi.org/10.1002/rra.1291
- ¹⁰⁹⁵ Olsen, J., McMahon, C.-R., & Hammer, G.-L. (1993). Prediction of sweet maize ¹⁰⁹⁶ phenology in subtropical environments. *Agronomy journal*, *85*, 410-415.
- Pasche, E., & Rouvé, G. (1985). Overbank flow with vegetatively roughened flood
 plains. Journal of Hydraulic Engineering, 111(9), 1262-1278.
- Perret, E., Le Coz, J., & Renard, B. (2020). Estimating time-varying stage-discharge
 relations in rivers with aquatic vegetation. In 10th Conference on Fluvial Hy draulics, IAHR-River Flow. Delft, The Netherland.
- Petryk, S., & Bosmajian, G. (1975). Analysis of flow through vegetation. Journal of Hydraulic Division, 101(7), 871-884.
- Rantz, S. E. (1982). Measurement and computation of streamflow : Volume 1. Measurement of stage and discharge. (Tech. Rep.). USGS.
- Rantz, S. E. (1982). Measurement and computation of streamflow: Volume 2. Computation of discharge. (Tech. Rep.). USGS.
- Renard, B., Garreta, V., & Lang, M. (2006). An application of Bayesian anal ysis and Markov Chain Monte Carlo methods to the estimation of a regional
- trend in annual maxima. Water Resources Research, 42 (W12422). doi: http://dx.doi.org/10.1029/2005WR004591?
- Room, P.-M. (1986). Equations relating growth and uptake of nitrogen by salvinia molesta to temperature and the availability of nitrogen. *Aquatic Botany*, 24, 43-59.
- Shields, F.-D., Coulton, K., & Nepf, H. (2017). Representation of vegetation in twodimensional hydrodynamic models. *Journal of Hydraulic Engineering*, 143(8), 1-9.
 doi: 10.1061/(ASCE)HY.1943-7900.0001320
- Smart, G. M., Maurice, M. J., & Walsh, J. M. (2002). Relatively rough flow resistance equations. *Journal of Hydraulic Engineering*, 128(6), 568-578.
- Tollenaar, M., Daynard, T.-B., & Hunter, R.-B. (1979). Effect of temperature on rate of leaf appearance and flowering date in maize. *Crop Science*, 19, 363-366.
- van der Heide, T., Roijackers, R.-M.-M., van Nes, E.-H., & Peeters, E.-T.-H.-M.-.
- 1123 (2006). A simple equation for describing the temperature dependent growth of 1124 free-floating macrophytes. *Aquatic Botany*, *84*, 171-175.
- Vargas-Luna, A., Crosato, A., & Uijttewaal, W. (2015). Effects of vegetation on flow
 and sediment transport: comparative analyses and validation of predicting models.
 Earth Surface Processes and Landforms, 40, 157-176. doi: 10.1002/esp.3633
- Västilä, K., & Järvelä, J. (2014). Modeling the flow resistance of woody vegeta tion using physically based properties of the foliage and stem. Water Resources
 Research, 50, 229-245. doi: 10.1002/2013WR013819
- Västilä, K., & Järvelä, J. (2017). Characterizing natural riparian vegetation for
 modeling of flow and suspended sediment transport. Journal of Soils and Sedi-

¹¹³³ ments, 1-17. doi: 10.1007/s11368-017-1776-3

- Västilä, K., Järvelä, J., & Aberle, J. (2013). Characteristic reference areas for estimating flow resistance of natural foliated vegetation. *Journal of Hydrology*, 492, 49-60. doi: http://dx.doi.org/10.1016/j.jhydrol.2013.04.015
- Västilä, K., Järvelä, J., & Koivusalo, H. (2016). Flow-vegetation-sediment interaction in a cohesive compound channel. *Journal of hydraulic Engineering*, 142(1).
- Vidal, J.-P., Martin, E., Franchistéguy, L., Baillon, M., & Soubeyroux, J.-M. (2010).
 A 50-year high-resolution atmospheric reanalysis over France with the Safran system. *International journal of climatology*, 30, 1627-1644. doi: 10.1002/joc.2003
- Vogel, S. (1994). Life in moving fluids the physical biology of flow (P. University,
 Ed.). Princeton University Press.
- Wang, J., & Zhang, Z. (2019). Evaluating riparian vegetation roughness computation methods integrated within hec-ras. *Journal of Hydraulic Engineering*, 145(6).
 doi: 10.1061/(ASCE)HY.1943-7900.0001597
- ¹¹⁴⁷ Whittaker, P., Wilson, C., Aberle, J., Rauch, H.-P., & Xavier, P. (2013). A drag ¹¹⁴⁸ force model to incorporate the reconfiguration of full-scale riparian trees under ¹¹⁴⁹ hydrodynamic loading. *Journal of Hydraulic Research*, 51(5), 569-580.
- World Meteorological Organization. (2010). Manual on Stream Gauging. Computation of discharge - Vol. II (Tech. Rep. No. 1044). WMO.
- Wu, F., Shen, H., & Chou, Y. (1999). Variation of roughness coefficients for unsub merged and submerged vegetation. *Journal of hydraulic Engineering*, 125(9), 934 942.
- Yan, W., & Hunt, L.-A. (1999). An equation for modelling the temperature response
 of plants using only the cardinal temperatures. Annals of Botany, 84, 607-614.
- Yin, X., Goudriaan, J., Lantinga, E.-A., Vos, J., & Spiertz, H.-J. (2003). A flexible
 sigmoid function of determinate growth. Annals of Botany, 91, 361-371. doi: 10
 .1093/aob/mcg029
- Yin, X., Kropff, M.-J., McLaren, G., & Visperas, R.-M. (1995). A nonlinear model
 for crop development as a function of temperature. Agricultural and Forest Meteo rology, *77*, 1-16.