



All-fibered high-quality low duty-cycle 40-GHz picosecond pulse source based on nonlinear compression of besselons

Anastasiia Sheveleva, Christophe Finot

► To cite this version:

Anastasiia Sheveleva, Christophe Finot. All-fibered high-quality low duty-cycle 40-GHz picosecond pulse source based on nonlinear compression of besselons. Nonlinear Photonics, Jul 2020, Washington, United States. OSA, NpTu4D.20, Proceedings OSA Advanced Photonics Congress (AP) 2020 (IPR, NP, NOMA, Networks, PVLED, PSC, SPPCom, SOF). 10.1364/NP.2020.NpTu4D.20 . hal-03140845

HAL Id: hal-03140845

<https://hal.science/hal-03140845>

Submitted on 9 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

All-fibered high-quality low duty-cycle 40-GHz picosecond pulse source based on nonlinear compression of besselons




Anastasiia SHEVELEVA and Christophe FINOT


Laboratoire Interdisciplinaire Carnot de Bourgogne, CNRS-Université Bourgogne-Franche-Comté, Dijon Cedex, France
anastasiia.sheveleva@etu.u-bourgogne.fr

INTRODUCTION

GOAL: Ultrashort pulse train generation at high repetition rates using a simple all optical setup



I. EXPERIMENTAL SETUP



WaveShaper #1


Triangular step phase generates the Besselon waveform

WaveShaper #2


Quadratic phase compensates induced chirp [2, 5]

Suppression of spectral lines allows to multiplex the repetition rate


II. BESELON PULSE GENERATION



III. NONLINEAR COMPRESSION



IV. REPETITION RATE MULTIPLEXING



CONCLUSION

- High extinction ratio ✓
- Low sidelobes ✓
- High repetition rate ✓
- Low duty cycle ✓
- Background-free pulse train
- Sub-ps pulses at (1 : 5) × 40 GHz
- All-optical setup of low complexity
- Significant improvement of the results

REFERENCES:

- C. Finot, J. Fatome, S. Pitois, and G. Millot, "All-Fibered High-Quality Low Duty-Cycle 20-GHz and 40-GHz Picosecond Pulse Sources," *IEEE Photon. Technol. Lett.* **19**, 1711-1713 (2007).
- T. Kobayashi, H. Yao, K. Amano, Y. Fukushima, A. Morimoto, and T. Sueta, "Optical pulse compression using high-frequency electrooptic phase modulation," *IEEE J. Quantum Electron.* **24**, 382-387 (1988).
- U. Andral, J. Fatome, B. Kibler, and C. Finot, "Triangular spectral phase tailoring for the generation of high-quality picosecond pulse trains," *Opt. Lett.* **44**, 4913 (2019).
- D. Grischkowsky and A. C. Balant, "Optical pulse compression based on enhanced frequency chirping," *Appl. Phys. Lett.* **41**, 1-3 (1982).
- M. A. F. Roelens, S. Frisken, J. Bolger, D. Abakounov, G. Baxter, S. Poole, and B. J. Eggleton, "Dispersion trimming in a reconfigurable wavelength selective switch," *J. Lightw. Technol.* **26**, 73-78 (2008).
- A. Sheveleva, U. Andral, B. Kibler, S. Boscolo, and C. Finot, "Temporal Optical Besselon Waves for High-Repetition Rate Picosecond Sources," *arXiv:2003.12630* (2020).