

# Glucose- and H2O2-dual responsives drug delivery particle based on the boronic acid chemistry

Julie Oniszczuk, Imane El Joukhar, Fayida Ali Said, Sabrina Belbekhouche

## ▶ To cite this version:

Julie Oniszczuk, Imane El Joukhar, Fayida Ali Said, Sabrina Belbekhouche. Glucose- and H2O2-dual responsives drug delivery particle based on the boronic acid chemistry. Materials Today: Proceedings, 2020, 602, pp.125072. 10.1016/j.matpr.2020.05.557. hal-03143196

## HAL Id: hal-03143196 https://hal.science/hal-03143196

Submitted on 9 Mar 2023

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1 2 3	Glucose- and H2O2- Dual Responsives Drug Delivery Particle Based on The Boronic Acid Chemistry
4	Julie Oniszczuk, Imane El Joukhar, Fayida Ali Said, Sabrina Belbekhouche $^{*}$
6	Institut de Chimie et des Matériaux Paris-Est, UMR 7182 CNRS-Université Paris-Est Créteil
7	Val-de-Marne, 2 rue Henri Dunant, 94320 Thiais, France
8	
9	Corresponding author:
10	* Sabrina Belbekhouche
11	Université Paris Est, ICMPE (UMR7182), CNRS, UPEC, F-94320 Thiais, France
12	Tel : +33 (0)1 49 78 11 49.s
13	Fax: +33 (0)1 49 78 12 08.
14	E-mail address: belbekhouche@icmpe.cnrs.fr
15	
16	
17	
18	
19	
20	
21	
22	
23	
24	
25	
26	
27	
28	
29	
30	
31	
32	
33	
34 35	

#### 36 Abstract.

Herein, we report on responsive systems presenting dual response to two different stimuli, namely glucose and hydrogen peroxide which are interesting for biological applications. New chemical stimulus-responsive multilayer assemblies have been designed through the layer-by-layer deposition of oppositely charged biopolymer on either flat or spherical surfaces. (diethylaminoethyl-dextran hydrochloride/alginate derivative) polyelectrolytes pair was selected for hydrogen peroxide-response and (polylysine/alginate derivative) polyelectrolyte pair for glucose-response. Concentration-dependent glucose and hydrogen peroxide responsiveness were reached via the incorporation of phenylboronic acid moieties inside the alginate chain. Wettability and quartz crystal microbalance measurements showed that the alginate derivate self-assembles though electrostatically-driven interactions with the polycation. These techniques also evidenced that the multilayer assemblies present tuneable behaviour according to the addition of glucose- and/or- hydrogen. This approach was further extended to the preparation of smart microparticles using calcium carbonate as initial substrate. The porosity of these microparticles has been advantageously used to entrap a probe. Its release could then be triggered via glucose or hydrogen peroxide. The present system may be used to targeted drug delivery to diseased tissue or as sugar-sensing device for diabetic treatment.

Keywords: particle; glucose-responsive; polysaccharides; layer-by-layer; phenylboronic acid
chemistry; hydrogen peroxide-responsive

#### 68 **1. Introduction**

69 Stimuli-responsive particles have still attracted scientific interest as for diagnosis, sensing, or 70 drug delivery. [1, 2] This undeniable success can be rationalized by the possibility to tune the 71 resulting property by changing the environnmental condition as pH or ionic strenght. This 72 allows a control and a specific release of the drug.

73 Several methods have been successfuly developed to produce particles. One may cite pH 74 induced micellization of a grafted polymer, [3] emulsion polymerization, crosslinking of 75 micelles, self-assembly and layer-by-layer (LbL) deposition of polyelectrolytes onto a 76 sacrificial template. [4, 5] Herein, we focus on the LbL process [6] as it is proved to be 77 efficient for the chemical modification of a plethora of substrates. [7, 8]

This approach allows developing particle with well-tuned property. The overall strategy 78 combines particles templating and self-assembly methods. More precisely, it lies on the 79 alternative deposition of charged polyelectrolyte to form a multilayer film on particles used as 80 templates. The polyelectrolyte excess could easily be removed by a simple washing step 81 before the deposition of the next layer. This strategy enables to easily and efficiently control 82 the size and the film thickness of the as-obtained material. Herein, we focus on calcium 83 84 carbonate microparticle cores because it presents several advantages as biocompatibility, low cost, mild decomposition and its intrinsic porosity which can be beneficial for providing high 85 drugs loading. [9-13] Moreover, the CaCO<sub>3</sub> micro-sized particles are easily obtained, for 86 instance by mixing calcium chloride and sodium carbonate.[14] 87

For promising applications in the drug-delivery field, the most fundamental requirement is the use of biocompatible and nontoxic polymer. In this aims, polysaccharides reveal to be very competitive candidates. Their hydroxyl- or amine- rich chemical structure enables to bring new interesting functionality as stimuli-responsiveness. They present also the interest of being pH-dependent charged which is interesting for LbL assembly. We can cite the alternative deposition of polysaccharides to form multilayers walls on microparticles, as dextran sulfate/protamine.[15]

95 Bringing stimuli-responsiveness to drug system may open new route to trigger the drug 96 release. Numerous studies reported on responsive particles to a broad range of external stimuli 97 such as pH, ionic strength or even temperature. [16-18] Although glucose has a crucial 98 biological function in living systems, only few groups have being working on this chemical. 99 [19, 20] For instance, cancer cells contain a very high glucose concentration in comparison to 99 normal cells [21] or we may simply think about diabetes treatment. The design of glucose-99 responsive systems is then still a challenging and interesting task. [22] The phenylboronic

acids chemistry could be successfully implied for developing glucose-responsive system. [23] 102 Indeed, this functional group is recognized to form covalent bonds with polydiols as 103 polysaccharides. [19] The complexation occurs mainly in a pH range above the pKa of the 104 boronic moieties (pKa~9). [19, 22, 24] Levy et al. have prepared glucose-sensitive capsules, 105 106 stabilized by the formation of ester bonds between mannan and phenylboronic acid moieties grafted onto a polyacid. [25] Glucose-sensitive capsules have been produced by De Geest et 107 al. by the layer-by-layer assembly of a copolymer of dimethylaminoethylacrylate and 108 acrylamidophenylboronic acid and poly(styrene sulfonate). They demonstrated glucose-109 110 induced change in the electrostatic interactions between the polyanion and the phenylboronic acid-containing polycation. [19] Belbekhouche et al. reported assemblies based on alginate 111 112 derivative containing phenylboronic acid side group and chitosan [20] or poly(vinylpyrrolidone).[26] 113

114 Furthermore, it is important to note that phenylboronic acid chemistry may also be used for developing hydrogen peroxide responsive system. This could be interesting to develop 115 116 reactive oxygen species detection systems. [27-31] Such systems are implied in several physiological processes such as apoptosis or proliferation Excess ROS production is often 117 118 correlated to diseases such as tumors and inflammatory pathologies.[32, 33] Cellular components can be damaged out of the balance due to ROS, e.g. hydrogen peroxide, 119 superoxide or even hydroxide radicals.[34] Thus, some ROS can be considered as a key to 120 cell signalling [35] for instance. 121

In this paper, the boronic acid chemistry is used to develop a new smart responsive material 122 presenting a dual response to glucose and hydrogen peroxide. Our work consists in the 123 building-up and the characterization of multilayer films on flat substrate based on either 124 ((diethylaminoethyl-dextran hydrochloride/alginate derivative) polyelectrolytes pair for 125 hydrogen peroxide-response or (polylysine/alginate derivative) polyelectrolytes pair for 126 glucose-response. This strategy is then extended to the fabrication of stimuli-responsive 127 microparticles which can be loaded with a probe and further be triggered released according 128 129 to glucose or hydrogen peroxide.

130

### 131 **2.** Experimental parts.

#### 132 **2.1. Chemicals**:

These chemicals were purchased diethylaminoethyl-dextran hydrochloride (Sigma-aldrich),
polylysine (Sigma-aldrich), alginate with mannuronic / guluronic ratio 1.4 (Cargill (Baupte,
France, Table 1), 1-ethyl-3-(3-dimethylaminopropyl) carbodiimide hydrochloride (EDC,

> 98.5%), N-hydroxysuccinimide (NHS, Sigma-aldrich, > Sigma-aldrich, 136 98%), mercaptosulfonate (Sigma-aldrich, > 89.5%), calcium chloride (CaCl<sub>2</sub>, rectapur, 99%), 137 sodium nitrate (rectapur, 99%), 4-aminophenylboronic acid hydrochloride (Alfa Aesar, 97%), 138 acetic acid (Alfa Aesar,+99%), sodium acetate (Alfa Aesar. 99%) 139 and ethylenediaminetetraacetic acid (EDTA, Sigma-Aldrich, 98%). 140

- 141
- **Table 1**: Characterization of the alginate derivative.

Samples	$\overline{Mn}$ (g.·mol <sup>-1</sup> )	$\overline{Mw}$ (g.·mol <sup>-1</sup> )	DS*
alginate	2.7.10 <sup>5</sup> (± 1.3 %)	$3.8.10^{-5} (\pm 0.4\%)$	-
alginate-g-boronic	2.5.10 <sup>5</sup> (± 1.3 %)	$6.2.10^{5} (\pm 0.4 \%)$	$0.20 \pm 0.04$

\* grafting ratio of phenylboronic acid groups (estimated from <sup>1</sup>H NMR from Pettignano et al.
[36]).

145

## 146 **2.2. Introduction of phenylboronic group on polyanionic polysaccharide**

Phenylboronic-modified alginate derivative was obtained by adding an amine-containing 147 phenylboronic groups onto the carboxylic acid groups of the alginic acid via the formation of 148 amide linkage through the EDC/NHS coupling reagent. The used EDC/NHS ratio is the 149 optimized condition for this alginate modification. More precisely, 500 mg of alginate was 150 dissolved in 100 mL of aqueous solution (potassium phosphate buffer (0.1 M, pH 7.2)) 151 overnight. Further, a mixture of 10 mg EDC and 10 mg NHS was added on the solution of 152 alginate and stirred for 45 min. A solution of 4-aminophenylboronic acid (100 mg in 1 mL of 153 methanol) was then dropwise added to the solution of alginate (mixing 1 day). A dialysis step 154 155 was implied to purify the product (6 kDa cut off). The product was obtained via freeze-drying (yield 90%). [20] 156

157

#### 158 **2.3.** Monitoring of the multilayer buildup and stimuli-response with QCM measurement

After cleaning (rinsing with water and ethanol, treatment in a UV/ozone chamber for 20 min and additional flushing with ethanol), the gold coated QCM Sensor Crystal was pretreated with sulfonated thiol (5 g.L<sup>-1</sup> in water). 1 mg.mL<sup>-1</sup> of polyelectrolytes was injected into the cell with a flow rate of 500  $\mu$ L.min<sup>-1</sup>. The following polyelectrolytes pair were used ((diethylaminoethyl-dextran hydrochloride/alginate derivative) and (polylysine/alginate derivative).

After the multilayer built-up, the glucose- or hydrogen hydroxide- response was investigatedby flushing the resulting film by solution containing this chemical at different concentration.

## 167 **2.4. Fabrication of glucose- and H<sub>2</sub>O<sub>2</sub>-responsive[ particles.**

168 CaCO<sub>3</sub> microparticles were fabricated according to Belbekhouche et al. [26] Multilayer 169 buildup was done via the LbL technique from 1 mg.mL<sup>-1</sup> of each polyelectrolytes (namely 170 diethylaminoethyl-dextran hydrochlorid, polylysine and alginate derivative). After each 171 adsorption process, the excess of polyelectrolyte was removed via two washing steps. A 172 centrifugation process (5 min, 10 000 rpm) was implied after each adsorption process. The 173 particles were washed with water two times during 5 min.

174

## 175 **2.5. Probe-loaded hybrid microcapsules.**

176 10 mg.mL<sup>-1</sup> of a suspension of microparticles were added into the solution containing a probe 177 (0.5 mg rhodamine b in 5 mL of deionized water). After 12 h, the loaded-CaCO<sub>3</sub> 178 microparticles were centrifuged and washed to remove free rhodamine derivative. The LbL 179 process was done as explained in section 2.4. The probe loading and the entrapment 180 efficiency were calculated by using equations 1 and 2.

181

probe loading = 
$$\frac{\text{amount of probe in microparticles}}{\text{amount of microparticle}} \times 100\%$$
 (1)

183

184 entrapment efficiency = 
$$\frac{\text{amount of entrapped probe}}{\text{initial amount of probe}} X 100\%$$
 (2)

185

186 The release behavior was investigated by introducing in a dialysis bag the probe-loaded 187 microcapsules and then immersing it in glucose or hydrogen peroxide solution. The probe 188 concentration was determined by absorbance measurements at 550 nm.

189

#### 190 **2.6. Methods**

Fourier transform infrared spectra were recorded on a Bruker Tensor 27 instrument equipped 191 with a Digi TectDLaTGS detector. <sup>1</sup>H NMR spectra were recorded on a Bruker Avance 300 192 NMR spectrometer. Zeta potential values of microparticles were determined on a Zetasizer 193 Nano-ZS (Malvern Instrument) equipped with a He–Ne laser ( $\lambda = 633$  nm; scattering angle, 194 195 173°). Average molar masses and molar masses distributions were determined by size exclusion chromatography (SEC) coupled online with multi-angle light scattering (MALS) 196 197 and differential refractive index (DRI) detectors. The MALS apparatus is the DAWN Heleos-II from Wyatt Technology (Ca, USA) filled with a K5 cell and a Ga–As laser ( $\lambda$ = 690 nm). 198 199 The DRI detector is a Shimadzu RID-10A (Japan). Columns [Shodex SB OHpak 804 and 806

HQ for alginate] were eluted with 0.1mol.L<sup>-1</sup> LiNO<sub>3</sub> at 0.5 mL min<sup>-1</sup>. Eluent was filtered 200 through 0.1 µm filter unit (Millipore, USA), degassed (Shimadzu DGU3, Japan). The sample 201 was injected (100 µL) with an automatic injector (Shimadzu SIL-20A). A Q-Sense E1 (Q-202 Sense, Sweden) system employing ATcut gold-coated quartz crystal sensors (Lot-Oiel, 203 France) with a nominal frequency of about 5 MHz was used. Absorbance spectra were 204 recorded with a UV-Visible spectrophotometer from Varian Cary 50 Bio. Scanning Electron 205 206 Microscopy (SEM) with line scanning of energy-dispersive X-ray spectroscopy was produced Leo Elektronenmikroskopie, Oberkoche in Germany. The non-conducting surface of the 207 calcium carbonate particles and capsules was covered with palladium before subject to 208 209 analysis.

210 211

## 212 **3. Results and discussion**

As shown in figures 1 and 2 A, our overall strategy consists in the layer-by-layer assembly of charged biopolymer, namely diethylaminoethyl-dextran hydrochloride or polylysine (polycation) and an alginate derivate (polyanion). For providing glucose- and hydrogen peroxyde sensitivity, phenylboronic acid moiety is incorporated inside the alginate. Subjected to these stimuli (figure 2B), the as-obtained multilayer is supposed to totally be removed from the substrate. Then, this strategy is transposed to spherical substrate leading to stimuliresponsive particle.

- 220
- 221
- 222
- 223



Figure 1. Biopolyelectrolytes used for the elaboration of glucose- and/or hydrogen peroxide
responsive substrate namely phenylboronic acid modified alginate as polyanion and
diethylaminoethyl-dextran hydrochloride or polylysine as polycation.

- 230 A)



**Figure 2.** A) Glucose- and/or hydrogen peroxide responsive multilayer, B) Boronic acid

*chemistry for obtaining glucose- or hydrogen peroxide response.* 

Phenylboronic acid pending group was incorporated in the alginate chain by coupling 236 aminophenylboronic acid with the carboxylic acid function of the alginic acid with a 237 condensation namely the [1-ethyl-3-(dimethylamino)propyl]carbo-diimide 238 reagent hydrochloride. [37, 38] After a purification process (dialysis and freeze drying), a white 239 chemical is obtained and labeled alg-bor (Figure 3A). The <sup>1</sup>H NMR spectra show the presence 240 of both chemical shift of the protons of the alginate chain (from 3 to 4 ppm) and phenyl 241 groups (from 6.7 to 7.2 ppm) (Figure 3A). From this technique, the presence of the aromatic 242 group is qualitatively checked and allows estimating a degree of substitution which is found 243 to be around 20%.[20] From FTIR spectra (Figure 3B), we show the presence of two peaks at 244 867 cm<sup>-1</sup> and 945 cm<sup>-1</sup> which are assigned respectively to the guluronate and mannuronate 245 residues of alginate and alg-bor samples and a band around 3300 cm<sup>-1</sup> attributed to the -OH 246 groups. The C-O stretching vibration of alcoholic hydroxyl group and C-O-C stretching 247 vibration remain unchanged, i.e. at 1143 cm<sup>-1</sup> and 1023 cm<sup>-1</sup> respectively. Moreover, a new 248 peak attributed to the C-N stretching vibration (at 1080 cm<sup>-1</sup>) appeared after the chemical 249 modification. At 1595 cm<sup>-1</sup> and 1412 cm<sup>-1</sup> peaks obtained are correlated to N-H deformation 250 and C-N stretching vibrations. The presence of the carbonyl group from the amide is observed 251 at around 1740 cm<sup>-1</sup>. 252





254

255



257

258 B)



259

*Figure 3.* A) <sup>1</sup>H NMR spectrum (D<sub>2</sub>O) of (A) alginate and (B) phenylboronic acid modified
alginate; B) FTIR spectra of alginate and phenylboronic-modified alginate derivative.

262 263

#### 264 Multilayers self-assembly on flat gold surfaces

The Lbl process is performed in an aqueous solution between obtain alginate derivative 265 (presence of carboxylate groups) and diethylaminoethyl-dextran hydrochloride or polylysine 266 (presence of ammonium group) as oppositely charged polyelectrolytes. Electrostatic 267 attractions are then implied as the driving force during the multilayer assembly. First, the gold 268 269 substrate is pretreated with a sulfonated thiol derivative leading to high density of negative surface charges. This enables to adsorb the polycation as the first layer, and then this is 270 271 followed by the adsorption of the alginate derivative (polyanion). This step is repeated to form 272 the multilayer build-up.

To demonstrate the efficiency of this method, the LbL assembly is investigated by wettabilityand then in real time by QCM experiments on a flat surface.

275 Static contact angle measurement are performed on the flat gold pretreated substrate before and after the multilayer build-up with (alg-bor/diethylaminoethyl-dextran hydrochloride)5 or 276 (alg-bor/polylysine)<sub>5</sub> to show qualitatively the elaboration of the multilayer film onto the 277 substrate. The contact angle values decreased from  $70^{\circ}\pm2^{\circ}$  to  $20^{\circ}\pm3^{\circ}$  upon the coating 278 independently of the polyelectrolytes pair. This result could be correlated to the hydrophilic 279 nature of these polysaccharides (Figure 4). Interestingly, the flushing of this modified 280 substrate with a solution of glucose or hydrogen peroxide results in a contact angle values 281 above  $70^{\circ}\pm2^{\circ}$  (i.e. removal of the multilayer from the surface). Note that flushing this 282

modified substrate with the buffer does not lead to a change in the contact angle value (i.e. remains near  $20^{\circ}\pm3^{\circ}$ ).

285



**Figure 4**. Wettability measurement on bare gold substrate  $(70^{\circ}\pm2^{\circ})$  and after the multilayer film build-up  $(20^{\circ}\pm3^{\circ})$ .

290

286

Then, the LbL assembly was monitored by QCM experiments to (i) demonstrate the stepwise 291 adsorption of polycation/ phenylboronic acid-containing alginate polyelectrolytes pair, (ii) 292 investigate the adsorption kinetics and (iii) evidence the impact of glucose or hydrogen 293 294 peroxide on the resulting multilayer film. In aqueous solution, the implied build-up procedure ensures both the presence of oppositely charged carboxylate and ammonium groups and, that 295 boronic acid function remained uncharged during the layer-by-layer buildup (pKa of 296 phenylboric acid 8.9). [39] Upon addition of the polyelectrolytes, a decrease of the frequency 297 298 signal is seen, showing that mass was being added onto the surface (Figure 5). Seven layers of the polyelectrolytes were then successfully deposited onto the quartz substrates. After 299 300 adsorption, the final frequency shift is around -150 Hz and -200 Hz for (phenylboronic acid 301 modified alginate/ polylysine)<sub>n</sub> and (b) (phenylboronic acid modified alginate/ 302 diethylaminoethyl-dextran hydrochloride) n respectively.

303



Figure 5. Evolution of the frequency shift values vs time during the successive polyelectrolytes addition, (a) (phenylboronic acid modified alginate/ polylysine)<sub>n</sub> and (b)
 (phenylboronic acid modified alginate/ diethylaminoethyl-dextran hydrochloride)<sub>n</sub> (standard deviation was always lower than 5%).

To demonstrate the glucose and/or hydrogen peroxide sensitivity, various concentrations of 310 311 these chemicals were flushed on the resulting multilayer film (Figure 6). As discussed before, the final equilibrium frequency shift values after the LbL build-up of the dextran 312 derivative/alg-bor films were -200 Hz. These values can then be used as references to show 313 either the glucose or hydrogen peroxide response of the films. Indeed, the total destabilization 314 315 of the films should involve a variation of the equilibrium frequency shift of about +200 Hz. The same hypothesis could be used if implying (phenylboronic acid modified alginate/ 316  $polylysine)_n$  as polyelectrolytes pair. 317

As observed from figure 6A and 6B, the frequency shift parameter increases upon exposing 318 the film to both glucose and  $H_2O_2$  to finally reach a stable value. The critical concentration is 319 found to be less than 100  $\mu$ M for H<sub>2</sub>O<sub>2</sub> and around 10<sup>-2</sup> M for glucose, meaning near 320 biologically relevant chemical concentrations. Our results are in accordance with the results 321 obtained by (i) Levy et al. who studied glucose-sensitive system based on mannan and 322 phenylboronic acid moieties grafted onto a polyacid, [25] (ii) De Geest et al. who fabricated 323 glucose-responsive layer-by-layer assembly of a copolymer of dimethylaminoethylacrylate 324 325 and acrylamidophenylboronic acid and poly(styrene sulfonate) and (iii) Sato et al. who designed hydrogen peroxide responsive multilayer film based on phenylboronic acid-bearing 326 327 poly (allylamine) and poly (vinyl alcohol). [40] The film decomposition upon the addition of these chemicals is then successfully demonstrated. In contrast, in a buffer solution meaning 328 329 without  $H_2O_2$  nor glucose, the frequency shifts does not change indicating that the multilayer film remained stable on the substrate. These results clearly pointed out that these films are 330

sensitive under oxidizing condition and glucose condition (explained through the suggestedmechanism in Figure 2B).

To our point of view, the as-observed mass behavior change is mainly due to the incorporation of glucose within the multilayer films through complexation with the phenyl boronic moieties. This assumption is confirmed by the fact that no significant frequency shift was seen upon flushing glucose solutions with high concentration (up to 0.1 M) over multilayer films composed by diethylaminoethyl-dextran hydrochloride and native alginate.

338 339

340



Figure 6. Effect of increasing concentrations of (A) glucose and B) hydrogen peroxide (NB:
no variation of the frequency without glucose or hydrogen peroxide)

344 345

341

Figure 7 shows how phenylboronic acid- containing alginate interacts with the diol of the glucose.[41] The result strongly suggests that there is formation of boronate ester bonds during the contact with the flushing with glucose which leads to (i) the complexation caused by the electrostatic interactions in the anionic glucose/borate complex and (ii) repulsion between the carboxylate groups of the alginate and the glucose/borate complex. The combination of these two phenomena seems to result in repulsion phenomena between the multilayers and then to the multilayer removal (Figure 8).

353



Figure 7. Equilibrium between phenylphenylboronic acids- containing alginate and diols-based glucose in aqueous solution.

359

Figure 8. Proposed mechanism of the glucose-induced disassembly of (phenylboronic acid
 modified alginate/ polylysine)<sub>n</sub>

362

363 The hydrogen peroxide response could be explained by the scheme presented in Figure 2B.

364

## 365 Multilayers self-assembly onto spherical surfaces

366 (diethylaminoethyl-dextran hydrochloride / phenylboronic acid-based alginate) and
367 (polylysine / phenylboronic acid-based alginate) polyelectrolytes pairs have been evidenced to
368 form multilayer film and to present glucose- or hydrogen peroxide responsive behavior.
369 Further, these conditions will be implied for the fabrication of smart particles (Figure 9).





Figure 9. Schematic illustration of the elaboration of the stimuli-responsive microcapsules
based on phenylboronic acid containing polyanion.

371

CaCO<sub>3</sub> particles have been used for the fabrication of responsive microparticles due to their 375 intrinsic porosity which may enable the entrapment of small molecules. They can easily 376 377 synthesize in a reproducible and size-controlled way. Furthermore, they are non-toxic. As shown in Figure 9, the CaCO<sub>3</sub> core particle was coated with the studied polyelectrolyte 378 379 bilayers. The conditions of the multilayer deposition were identical to those implied during the coating of the quartz surfaces but no precoating step with the thiol derivative was 380 required. Indeed, pristine CaCO<sub>3</sub> particles present negative surface charges allowing the direct 381 deposition of positively charged polyelectrolytes as pointed by the measured zeta-potential 382 value of -5 mV for the uncoated calcium carbonate material (Figure 10A). This parameter was 383 then measured after each adsorption step to evidence the successive deposition of each 384 polyelectrolyte on the particles surface. [42] A variation of the zeta-potential value is 385 observed i.e. between +40 and -20 mV upon successive adsorption of polycation and alg-bor, 386 respectively. As seen from SEM picture, the as-obtained microparticles present well-defined 387 388 spherical shape and micrometer size (Figure 10B).

- 389
- 390
- 391



**Figure 10.** A) Zeta potential variation according to the adsorption step during the film build up on the CaCO<sub>3</sub> microparticles (PC = polycation and MP = microparticles). B) SEM images of modified microspheres constituted by (polycation/alg-bor)<sub>n</sub> polyelectrolytes pair.

392

398

The release rate of the entrapped probe within the interior cavity of the LbL coated 399 microparticles may be highly impacted by the permeability of the material. For 400 polyelectrolytes LbL assemblies, the inter-polyelectrolyte interactions can be tuned by various 401 stimuli as pH or ionic strength. One may cite as example, particles based on 402 alginate/polylysine or DNA/spermidine which were evidenced to provide a cargo release due 403 to change in salt concentration. [43] In the present work, the release behavior of the coated 404 microparticles loaded with the rhodamine b derivative inside its cavity is supposed to be 405 406 triggered by both glucose and hydrogen concentration. Initially, the rhodamine b was loaded 407 within the porous structure of the CaCO<sub>3</sub> material prior to coat it with the multilayer film. The entrapment efficiencies efficiency of the material are is up to 60% and the probe loading is 408 409 above 4 % (determined via equations 1 and 2). Without chemical stimulus the coated microparticles stay stable meaning that the remained loaded with the probe and those even 410 411 after more than two weeks. However, when the coated microparticles are suspended in glucose- or hydrogen peroxide containing solution a release of the rhodamine derivative is 412 evidence. It deserves noting that the threshold concentrations of each of this chemical has 413 been estimated during the QCM experiment. These concentrations were used for monitoring 414 415 the rhodamine b release. A fast probe release of 85% is observed after 24 h up to this critical concentration. The probe is progressively released below this critical concentration. This 416 result is illustrated in Figure 11. 417



*Figure 11: Release of rhodamine b from* ((phenylboronic acid modified alginate/ polylysine)<sub>n</sub> 420 particles in presence of glucose solution at  $\bullet$  7.5 10<sup>-3</sup> M and  $\circ$  10<sup>-2</sup> M.

#### 

### **4. Conclusion**

Novel multilayer assemblies based on alginate derivative (chemically modified to introduce phenylboronic acid group) have been implied for the design of both glucose- and hydrogen peroxide responsive system. Herein, the implemented strategy is based on the alternative adsorption of the polycation and the phenylboronic acid-containing polyanion on the surface of CaCO<sub>3</sub> microparticles. After each deposition, the reversal of the surface charge was shown by zeta potential measurements, which is in accordance with the successful multilayer assemblies. Spherical shape was evidenced by SEM measurements. The glucose- and hydrogen peroxide sensitive character was related to these chemicals concentration in the surrounding buffer and implied due to the phenylboronic acid incorporation inside the polymer chain. The present work mainly focuses on the chemical modification and the physico-chemical aspect of the systems, a biological study will further be done. Indeed, the novel smart microparticle may further be employed for specific biological applications. One may cite diabetes disease (glucose-sensing device) or to detect oxidative stress (hydrogen peroxide-sensing system). 

#### 440 Acknowledgements

441 The authors wish to sincerely thank the UPEC and CNRS for financial support.

## 446 **References**

- Deshmukh PK, Ramani KP, Singh SS, Tekade AR, Chatap VK, Patil GB, Bari SB.
   Stimuli-sensitive layer-by-layer (LbL) self-assembly systems: targeting and biosensory applications. J Control Release 166(2013)294-306.
- 450 2. Sukhorukov G, Fery A, Möhwald H. Intelligent micro- and nanocapsules. Prog Polym
  451 Sci 30(2005)885-897.
- 452 3. Dou H, Jiang M, Peng H, Chen D, Hong Y. pH-dependent self-assembly:
  453 micellization and micelle-hollow-sphere transition of cellulose-based copolymers.
  454 Angew Chem Int Ed 42(2003)1516-1519.
- 455 4. Gittins DI, Caruso F. Tailoring the polyelectrolyte coating of metal nanoparticles. J
  456 Phys Chem B 105(2001)6846-6852.
- 457 5. Gittins DI, Caruso F. Multilayered polymer nanocapsules derived from gold
  458 nanoparticle templates. J Adv Mater 12(2000)1947-1949.
- 459 6. Borges JO, Mano JF. Molecular interactions driving the layer-by-layer assembly of
  460 multilayers. Chem Rev 114(2014)8883-8942.
- 461 7. Shimomura M, Sawadaishi T. Bottom-up strategy of materials fabrication: a new trend
  462 in nanotechnology of soft materials. Curr Opin Colloid In 6(2001)11-16.
- 8. Szarpak A, Cui D, Dubreuil F, De Geest BG, De Cock LJ, Picart C, Auzély-Velty R.
  Designing hyaluronic acid-based layer-by-layer capsules as a carrier for intracellular drug delivery. Biomacromolecules 11(2010)713-720.
- 466 9. Volodkin DV, Larionova NI, Sukhorukov GB. Protein encapsulation via porous
  467 CaCO<sub>3</sub> microparticles templating. Biomacromolecules 5(2004)1962-1972.
- Volodkin DV, Petrov AI, Prevot M, Sukhorukov GB. Matrix polyelectrolyte
  microcapsules: new system for macromolecule encapsulation. Langmuir 20(2004)
  3398-3406.
- 471 11. Sukhorukov GB, Volodkin DV, Günther AM, Petrov AI, Shenoya DB, Möhwalda H.
  472 Porous calcium carbonate microparticles as templates for encapsulation of bioactive compounds. J Mat Chem 14(2004)2073-2081.
- 474 12. Stein EW, Volodkin DV, McShane MJ, Sukhorukov GB. Real-time assessment of
  475 spatial and temporal coupled catalysis within polyelectrolyte microcapsules containing
  476 coimmobilized glucose oxidase and peroxidase. Biomacromolecules 7(2006)710-719.
- 477 13. Petrov AI, Volodkin DV, Sukhorukov GB, Protein-calcium carbonate coprecipitation:
  478 a tool for protein encapsulation. Biotechnol Prog 21(2005)918-925.
- 479 14. Zhao Q, Mao Z, Gao C, Shen J. Assembly of multilayer microcapsules on CaCO<sub>3</sub>
  480 particles from biocompatible polysaccharides. J Biomater Sci Polym Ed 17(2006)997481 1014.
- 482 15. Balabushevich NG, Tiourina OP, Volodkin DV, Larionova NI, Sukhorukov GB.
  483 Loading the multilayer dextran sulfate/protamine microsized capsules with peroxidase.
  484 Biomacromolecules 4(2003)1191-1197.
- 485 16. De Geest BG, Skirtach AG, Mamedov AA, Antipov AA, Kotov NA, De Smedt SC,
  486 Sukhorukov GB. Ultrasound-triggered release from multilayered capsules. Small
  487 3(2007)804-808.
- 488 17. Sukhishvili SA. Responsive polymer films and capsules via layer-by-layer assembly.
  489 Curr Opin Colloid In 10(2005)37-44.
- 490 18. De Geest BG, Sanders NN, Sukhorukov GB, Demeester J, De Smedt SC. Release
  491 mechanisms for polyelectrolyte capsules. Chem Soc Rev 36(2007)636-649.
- 492 19. De Geest BG, Jonas AM, Demeester J, De Smedt SC. Glucose-responsive polyelectrolyte capsules. Langmuir 22(2006)5070-5074.

- 494 20. Belbekhouche S, Charaabi S, Picton L, Le Cerf D, Carbonnier B. Glucose-sensitive
  495 polyelectrolyte microcapsules based on (alginate/chitosan) pair. Carbohydr Polym
  496 184(2018)144-153.
- 497 21. Aykin-Burns N, Ahmad IM, Zhu Y, Oberley LW, Spitz DR. Increased levels of 498 superoxide and  $H_2O_2$  mediate the differential susceptibility of cancer cells versus 499 normal cells to glucose deprivation. Biochem J 418(2009)29-37.
- Wu Q, Wang L, Yu H, Wang J, Chen Z. Organization of glucose-responsive systems
  and their properties. Chem Rev 111(2011)7855-7875.
- 502 23. Kazunori K, Hiroaki M, Teruo O, Yasuhisa S. Sensitive glucose-induced change of the
  503 lower critical solution temperature of poly[N,N-(dimethylacrylamide)-co-3504 (acrylamido)-phenylboronic acid] in physiological saline. Macromolecules 27(1994)
  505 1061-1062.
- Brooks WLA, Sumerlin BS. Synthesis and applications of boronic acid-containing
   polymers: from materials to medicine. Chem Rev 116(2016)1375-1397.
- Levy T, Déjugnat C, Sukhorukov GB. Polymer microcapsules with carbohydrate sensitive properties. Adv Funct Mater 18(2008)1586-1594.
- 510 26. Belbekhouche S, Charaabi S, Carbonnier B. Glucose-sensitive capsules based on hydrogen-bonded (polyvinylpyrrolidone / phenylboronic –modified alginate) system.
  512 Colloid Surface B 177(2019)416-424.
- 513 27. Van de Bittner GC, Dubikovskaya EA, Bertozzi CR, Chang CJ. In vivo imaging of
  514 hydrogen peroxide production in a murine tumor model with a chemoselective
  515 bioluminescent reporter. Proc Natl Acad Sci USA 107(2010)21316-21321.
- 516 28. Srikun D, Albers AE, Nam CI, Iavarone AT, Chang CJ. Organelle-targetable
  517 fluorescent probes for imaging hydrogen peroxide in living cells via SNAP-Tag
  518 protein labeling. J Am Chem Soc 132(2010)4455-4465.
- Lee D, Khaja S, Velasquez-Castano JC, Dasari M, Sun C, Petros J, Taylor WR,
  Murthy N. In vivo imaging of hydrogen peroxide with chemiluminescent nanoparticles. Nat Mater 6(2007)765-769.
- 522 30. Chang MC, Pralle A, Isacoff EY, Chang CJ. A selective, cell-permeable optical probe
  523 for hydrogen peroxide in living cells. J Am Chem Soc 126(2004)15392-15393.
- 524 31. Yu SS, Koblin RL, Zachman AL, Perrien DS, Hofmeister LH, Giorgio TD, Sung HJ.
  525 Physiologically relevant oxidative degradation of oligo(proline) cross-linked
  526 polymeric scaffolds. Biomacromolecules 12(2011)4357-4366.
- 527 32. Song CC, Ji R, Du FS, Li ZC. Oxidation-responsive poly(amino ester)s containing
  528 arylboronic ester and self-immolative motif: synthesis and degradation study.
  529 Macromolecules 46(2013)8416-8425.
- Song CC, Ji R, Du FS, Liang DH, Li ZC. Oxidation-accelerated hydrolysis of the
  ortho ester-containing acid-labile polymers. ACS Macro Lett 2(2013)273-277.
- 532 34. Geronikaki AA, Gavalas AM. Antioxidants and inflammatory disease: synthetic and natural antioxidants with anti-inflammatory activity. Comb Chem High Throughput Screen 9(2006)425-442.
- 535 35. Finkel T. Oxidant signals and oxidative stress. Curr Opin Cell Biol 15(2003)247-254.
- 536 36. Pettignano A, Grijalvo S, Häring M, Eritja R, Tanchoux N, Quignard F, Díaz Díaz D.
  537 Boronic acid-modified alginate enables direct formation of injectable, self-healing and multistimuli-responsive hydrogels. Chem Commun 53(2017)3350-3353.
- 539 37. Kitano S, Kataoka K, Koyama Y, Okano T, Sakurai Y.Glucose-responsive complex
  540 formation between poly (vinyl alcohol) and poly (N-vinyl-2-pyrrolidone) with pendent
  541 phenylboronic acid moieties. Makromol Chem Rapid Comm 12(1991)227-233.
- 542 38. Kitano S, Koyama Y, Kataoka K, Okano T, Sakurai Y. A novel drug delivery system utilizing a glucose responsive polymer complex between poly (vinyl alcohol) and poly

544		(N-vinyl-2-pyrrolidone) with a phenylboronic acid moiety. J Control Release
545 546	20	19(1992)161-170. Wastmark PR Gardinar SL Smith PD Salastiva monosassharida transport through
540 547	39.	lipid bilayers using boronic acid carriers. J Am Chem Soc 118(1996)11093-11100.
548 540	40.	Sato K, Takahashi M, Ito M, Abe E, Anzai J. H <sub>2</sub> O <sub>2</sub> -induced decomposition of layer- by layer films consisting of phenylboropic acid-bearing poly (allylamine) and poly
549 550		(vinyl alcohol). Langmuir 30(2014)9247-9250.
551	41.	Springsteen G, Wang B. A detailed examination of boronic acid–diol complexation.
552 553	42.	Belbekhouche S, Charabi S. Hamadi S, Carbonnier B. Latex nanoparticles surface
554		modified via the layer-by-layer technique for two drugs loading. Colloid Surface A
555 556	43.	Schüler C, Caruso F. Decomposable hollow biopolymer-based capsules.
557		Biomacromolecules 2(2001)921-926.
558		
559		
560		
561		
562		
563		
564		
565		
566		
567		
568		
569		
570		
571		
572		
573		
574		
575		
576		
577		
578		