

Microplastic pollution in agricultural soils and abatement measures mmodel-based assessment for Germany

Martin Henseler, Micheal Bernard Gallagher

▶ To cite this version:

Martin Henseler, Micheal Bernard Gallagher. Microplastic pollution in agricultural soils and abatement measures a model-based assessment for Germany. 2021. hal-03176598v1

HAL Id: hal-03176598 https://hal.science/hal-03176598v1

Preprint submitted on 22 Mar 2021 (v1), last revised 22 Mar 2022 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

| 1 2 | Microplastic pollution in agricultural soils and abatement measures – a model-based assessment for Germany |
|----------|--|
| 3 | |
| 4 | Martin Henseler ^{a,b,*} and Micheal B. Gallagher ^c |
| 5 | |
| 6 7 | a) EDEHN - Equipe d'Economie Le Havre Normandie, Université du Havre, Le Havre France |
| 8 | b) Partnership for Economic Policy (PEP), Nairobi, Kenya |
| 9 | c) Independent Consultant, 62 rue Casimir Delavigne, Le Havre France |
| 10 11 | *) EDEHN - Equipe d'Economie Le Havre Normandie, Université du Havre, Le Havre France, Email: <u>martinhenseler@gmx.de</u> |
| 12 | Abstract |

13 Microplastic pollution in soils is a recent challenge for environmental science and policy. Designing and implementing policies to mitigate microplastic emissions requires scientific 14 data, which is rare because analytical methods to detect and quantify microplastics in soils are 15 16 still under development. Using a normative emission model we simulate for the year 2020 a 17 microplastic concentration in agricultural soil between 40 and 50 mg/kg, which we expect to find on 2% of Germany's utilized agricultural area. On around 20% of utilized agricultural 18 19 area, we expect any microplastic pollution present from sludge or microplastic. At the region-20 al scale, we expect the difference of pollution between sites to be close to urban regions and less urban regions. We find that for sludge, thermal recycling (end-of-the-pipe treatment) 21 22 reduces the microplastic emissions more cost-efficiently and effectively than filtering the 23 microplastic emissions from the waste-water. For compost, the application of detection sys-24 tems and quality control for the biowaste collection (source of pollution) is a more costefficient abatement measure than thermal recycling. This approach is of comparable effec-25 tiveness to thermal recycling. The presented results must be updated with future research re-26 27 sults. But these model results can contribute to research on reducing microplastic pollution in 28 agricultural soils.

29 Key words: environmental assessment, normative model, abatement cost, efficiency, effec-

- 30 tiveness
- 31

32 1 Introduction

- 33 Microplastic pollution is a recent challenge for environmental science and policy.
- 34 Microplastics, commonly defined as solid plastic particles of the size between 1 and 5000µm,
- have been found in nearly all environmental systems (e.g., Gestoso et al. 2019, Horton et al.
- 36 2017, Koelmans et al. 2017). Many industrial and household sources emit different quantities
- 37 of microplastics into atmosphere or into aquatic or terrestrial ecosystems. A lack of
- 38 knowledge on the bio-physical behavior of microplastics in ecosystems and on their impacts
- 39 on living organisms is of increasing concern to society and researchers.
- 40 Insufficient empirical data on the emission quantities, on the impacts and on potential abate-
- 41 ment measures has made microplastic pollution a threatening environmental problem at a
- 42 global and European level. Society perceives microplastic as a threat and demands action for
- 43 environmental and human health protection.
- 44 In its principles of precaution and prevention, European environmental policy legislation fo-
- 45 cuses on "preserving, protecting and improving the quality of the environment" and "protect-
- 46 ing human health" (European Union 2012). Recently, these objectives were also emphasized
- 47 for soil pollution in the EU Action Plan on "Zero Pollution" (European Union 2020a) and the
- 48 European "New Soil Strategy" (European Union 2021). Both strategies are part of the Euro-
- 49 pean Green Deal (European Commission 2019) aiming at the reduction of soil pollution to
- 50 protect and improve the terrestrial ecosystem and aquatic ecosystem, retain soil productivity
- 51 and protect human health.
- 52 Environmental policy design should ideally target the source of microplastic pollution and
- 53 obligate associated costs to be paid by the polluter. However, European environmental policy
- 54 principles also require an evaluation of potential benefits and costs of action or lack of action
- and an assessment of costs in terms of proportionateness. Available scientific and technical
- 56 data are to serve as the basis for evaluation and policy design (European Union 2012). Thus,
- 57 the current lack of knowledge on the status, the processes and the impacts of microplastic
- 58 pollution, makes it difficult or impossible to legislate environmental policy against
- 59 microplastic pollution in the different ecosystems.
- 60 The potential environmental threat of microplastic pollution in terrestrial ecosystems has re-
- 61 cently gained increased attention (e.g., Hurley and Nizzetto 2018, de Souza Machado et al.
- 2018, Rillig et al. 2017, Nizzetto et al. 2016). Microplastics were found in agricultural soils
 as textile fibers originating from sewage sludge as early as 2005 (Zubris and Richards 2005,
- 64 Selonen et al. 2020).
- 65 Microplastics are suspected to have negative impacts on soils ecosystems. They can change
- 66 physical characteristics of soils (Rillig et al. 2017, Lehmann et al. 2019) and release associat-
- 67 ed toxic chemicals (e.g., additives, cf. Hahladakis et al. 2018). They can also act as vectors 68 for anyironmental contaminanta like posticidae beaux metals or artification (Shi et al. 2020)
- 68 for environmental contaminants like pesticides, heavy metals or antibiotics (Shi et al. 2020).
- Furthermore, microplastic particles can be ingested by soil organisms. At the nano-scale size,
 microplastics may even cross biological barriers (Wang et al. 2019, Ng et al. 2018, Koelmans
- 71 et al. 2017). However, scientific evidence to support these theories on the impacts in ecosys-
- 72 tems is currently lacking for in situ conditions. Thus, in the natural environment, the toxic
- 73 concentrations or transportation processes cannot be quantitatively described.
- 74 The high stability of plastic as a material means that the decomposition (degradation) of
- 75 microplastic particles under environmental conditions is extremely slow. Thus, researchers
- 76 expect an accumulation of microplastic in environmental systems (e.g., in soil and water)
- 77 (Horton et al. 2017). It is assumed that microplastics can be emitted from soils to water sys-
- 78 tems, where they can have negative impacts on aquatic ecosystems (Horton et al. 2017, Lush-

- re et al. 2017, Eerkes-Medrano et al. 2015, Bakir et al. 2014). Groundwater flow and soil ero-
- sion (wind, water) can transport microplastics, and soils with high microplastic content are
- potential sources for microplastic emissions to other environmental systems such as surface
- waters. Thus, microplastic-polluted soils as a potential source of emissions to aquatic systemsare of interest for research.
- 84 In agricultural production the land based application of sewage sludge and compost as organ-
- 85 ic fertilizers are considered as important pathways of microplastic to agricultural soils (Hur-
- 86 ley and Nizzetto 2018, Ng et al. 2018). Microplastics in sewage sludge and compost are emit-
- 87 ted by private households and different industries. Microplastics enter wastewater from 88 households and industry (a.g. cleaning products, fibers from synthetic tartiles). Sources
- households and industry (e.g., cleaning products, fibers from synthetic textiles). Sewage
 sludge, as a residue from the water treatment process, contains these microplastics (Corradini
- sludge, as a residue from the water treatment process, contains these microplastics (Corradini
 et al. 2019, Kay et al. 2018, Wijesekara et al. 2018). Microplastics in compost originate from
- 91 private households, industry and landscaping when plastic materials (e.g., food packaging,
- 92 littered plastic in landscaping clippings) are not (sufficiently) separated from the organic
- 93 waste before collection and composting. The compost producer can only remove plastic par-
- 94 ticles down to a certain size, meaning that the separation process is not efficient in removing
- 95 the smaller plastic fragments (e.g., small thin fragments of plastic film from food packaging).
- 96 Mechanical processes (e.g., shredding and mixing) degenerate the macro plastic fragment to
- 97 microplastic sized particles (Bläsing and Amelung 2018, Weithmann et al. 2018).
- 98 In Germany, a European study area with regionally intensive agricultural production, farmers 99 apply sewage sludge and compost as soil amendments to improve soil structure and as organic fertilizers to supply the soil with nutrients. At the same time, farmers provide German society with a waste disposal service. But farmers emit microplastics into agricultural soils by 102 spreading sewage sludge and compost on their fields. Microplastics can thus potentially be
- 102 spreading sewage studge and compost on their nerds. Microprastics C 103 included in the list of agricultural pollutants (Henseler et al. 2020).
- However, the lack of scientific knowledge to date does not allow for the development of policies to reduce the suspected pollution of agricultural soils with microplastics (Brodhagen et al. 2017). Gaps in research exist with regard to sources, processes, fates, sinks, exports and impacts of microplastics. (Rillig et al. 2019, Büks et al. 2020). Furthermore, microplastics exist in soils in relatively low concentrations and are difficult to separate from the soil parti-
- 109 cles. From an analytical point of view, difficulties exist in developing methods to measure
- 110 microplastics in soils and to carry out impact assessments (Möller et al. 2020, Brennholt et al. 2014)
- 111 2018, Wagner et al. 2014).
- 112 An increasing number of studies address the problem of microplastic pollution in soils. Most
- 113 of these studies are review studies and only a few studies provide original empirical findings.
- 114 While economic literature addresses the problem of the plastic crises (e.g., Batker 2020) and
- 115 plastic pollution in marine environment (Abate et al. 2020) economic studies on microplastic
- pollution in terrestrial systems are still rare and they tend to be of qualitative nature. For ex-
- 117 ample, Henseler et al. (2020) describe the microplastic pollution of agricultural soils as a new
- 118 challenge for agricultural and environmental policies and discuss if agriculture, which is
- 119 providing the service of bio-waste disposal to the society should be considered pollutant or as
- a victim of microplastic pollution (Henseler et al. 2020).
- 121 The present study contributes to the environmental economic literature by providing quantita-
- tive empirical findings on microplastics in agricultural soils. Concretely, the study addresses
- the following goals and objectives: (i) to present a normative emission model at the sector
- level on microplastic emissions from sludge and compost into agricultural soils; (ii) to simu-
- 125 late emission scenarios in order to estimate the concentration of microplastic in soils and the

127 cost-efficiency and effectiveness. Finally the results of this study can (iv) contribute to the128 discussion on microplastic pollution.

129 2 Model and data

- 130 We developed a normative emission model for Germany to estimate the quantities of
- 131 microplastic released from sewage sludge and compost and the concentration of microplastic
- accumulated in agricultural soils. The data to be used in the model and the assumptions are
- 133 derived from literature and statistics.

134 **2.1 Estimating the concentration of microplastic in sewage sludge and compost**

- 135 We use research by Bertling et al. (2018) and Kehres (2019) on microplastic concentrations
- 136 in sewage sludge and compost to estimate the released quantities of microplastic We assume
- that the estimated microplastic concentrations are representative of the average national concentrations in Germany.
- 139 **2.1.1** Concentration of microplastic in sewage sludge
- 140 A few analytical studies have been published concerning the microplastic content of sewage
- sludge. We use the mass based emission quantities published by Bertling et al. (2018) for the
- 142 whole of Germany by aggregating all sources relevant to wastewater and sewage sludge: tex-
- tiles, cosmetics, cleaning and personal care products.
- 144 Equation 1 describes the calculation of microplastics in sewage sludge from the selected
- sources for 2016, which we define as the reference year. We consider the filtration rate for
- 146 microplastics in wastewater treatment plants to be 95%. The empirical filtering rate is as-
- sumed to be between 95 and 99% (Bertling et al. 2018). Thus, we assume the "worst case"
- scenario for the effectiveness of filtration. This means that 5% of microplastics will leave the
- treatment plant with the treated waste water into aquatic systems, while 95% will remain in
- the sludge. We compute an average microplastic content in sludge of 0.6% dry weight for the
- 151 reference year 2016.
- 152 Literature cites smaller microplastic concentrations reaching from mean values of 0.05% to
- 153 0.1% dry weight (Crossmann et al. 2020) to 0.4% dry weight (Okoffo et al. 2020). We follow
- the worst-case assumption by selecting 0.6% as a higher concentration representative for
- 155 Germany.

$$MPCONC_{sludge} = \left(\frac{\sum_{source} MPEM_{source} * POP_{2016}}{Q_{sludge,2016}}\right) * FR$$
(Eq. 1)

156 With

$157 \qquad MPCONC_{sludge} = concentration of microplastics in sewage sludge as \% dry weight$

- MPEM_{source}: annual emissions of microplastics per capita in 2016 expressed as g/(head *
 year): Textile fibers from households and industry = 76.8 g/(head*year) (57.7%); Industrial cleaning = 23 g/(head*year) (17.0%), Cosmetics = 19 g/(head*year) (14.0%), Abrasives
 in pipes = 12 g/(head*year) (8.9%), cleaning products and personal care products = 4.6
- 162 g/(head*year) (3.4%) computations based on Bertling et al. (2018).
- 163 POP_{2016} : population in Germany in 2016 = 82.3 M
- 164 $Q_{sludge,2016}$: quantity of sewage sludge produced in 2016 in g
- 165 FR: filtration rate = 95%
- 166 The amount of microplastic in wastewater is determined by the emissions from various
- 167 household and industrial sources. Thus, we assume that the amount of microplastics in

wastewater and sewage sludge has changed over the period from 1983 to 2016. We use the
global development of polyester production as an index to consider the changes in the concentration of microplastics over time. Since synthetic fibres are the main source of microplastics in sludge, we use this index as the basis for all calculations of microplastic concentrations
in wastewater and sewage sludge (for further details, see Appendix).

2.1.2 Concentration of microplastic in compost

174 Few empirical studies analyze the concentration of microplastics in compost. In composts of

- different types, Weithmann et al. (2018) found particle numbers ranging from 14 to 895
- 176 items/kg dry weight in the size range of between 1 and 5mm. Bläsing and Amelung (2018)
- measured a concentration of microplastics in compost samples ranging from 2.38 mg/kg to
- 178 180 mg/kg dry weight, in the size range of between 1 and 5mm, translating into a mean value
- of 0.008% dry weight. For this study, we consider the concentration of microplastics in compost to be that determined by Kehres (2019) in different types of compost. Kehres (2019)
- determines the concentration of plastic particles which are larger than 2mm to be 0.032% dry
- weight in certified composts. Kehres (2019) estimates that there is about 10% more plastic
- 183 present when considering the size fraction range of 1 2mm (Kehres 2019, BGK 2018).
- 184 Thus, we derive a concentration of microplastic in compost to be 0.04% dry weight¹ for the
- particle size range of 1 to 5mm. Following the worst-case assumption, we select the higher
- 186 concentration of 0.04% dry weight as representative for Germany.

187 **2.1.3** Development of the concentration of microplastic in sewage sludge and compost

- Equation 2 computes the emission factors $(EF_{f,t})$ for the organic fertilizer (f) in year (t). We
- assume that only the emission factor of sewage sludge ($EF_{sludge,t}$) varies over time from 1983
- to 1990. Due to missing information on the development of the plastic content in bio-waste,

191 we assume that the emission factor for compost $(EF_{compost,t})$ is constant over time.

 $EF_{f,t} = MPCONC_f^* DEV_{f,t}$ (Eq. 2)

192 with

193 $EF_{f,t}$: Emission factor for the organic fertilizer (f) for the year (t).

- 194 $MPCONC_f$: Concentration of microplastic in the organic fertilizer, sewage sludge = 0.6% 195 dry weight matter, compost = 0.04% dry weight.
- 196 $DEV_{sludge, t} = Scaling factor applied the 2016 microplastic concentration in sewage sludge197according to Fig 1$
- $198 \qquad DEV_{compost} = 1$

2.2 Estimating the emissions of microplastic from sewage sludge and compost in agricul ture

- 201 To estimate the quantities of microplastics released from sewage sludge and compost to agri-
- 202 cultural soils, we develop a normative emission model at the sector scale. The model takes
- 203 exclusively sewage sludge and compost into account and does not consider the other sources
- of microplastics. The model (Eq. 3 to 7) simulates the emissions of microplastics as they
- should be according to current legislation, for each single year and only for sewage sludge
- and compost. The model is therefore a partial normative emission model.

¹i.e., 0.032% + 10%*0.032% = 0.035% ca. 0.04%

Equation 3 computes the quantity of microplastic emitted for the year t and from fertilizer f (sewage sludge or compost). The sector emission factor $EF_{f,t}$ expresses the concentration of microplastic in the fertilizer, with $EF_{sludge,t}$ increasing from the year 1983 to 2016 to 0.6% of dry weight in 2016 (Figure 1) and with $EF_{compost,t}$ as a constant concentration from 1990 to 2016 at 0.04% of dry weight.

$$QMP_{f,t} = QF_{f,t} * EF_{f,t}$$
(Eq. 3)

- 212 with
- 213 $QMP_{f,t}$: Quantity of microplastics emitted from fertilizer (f) in the year (t) in mg
- 214 $QF_{f,t}$: Quantity of fertilizer used(f) in year (t) in tons of dry solids
- 215 $EF_{f,t}$: Emission Factor for microplastic emissions from fertilizer (f) in year (t) in mg/t
- 216 *f:* Fertilizer used; either sewage sludge or compost
- 217 $t = (1983 \dots 2016)$: The simulated year.
- Equation 4 describes the cumulated quantities of microplastics released into the soils in the
- simulated year t by summing up the quantities of microplastics over the past years. We as-
- sume that microplastics emitted from sewage sludge and compost accumulate in the soil over

(Eq. 4)

- time. Due to the lack of information on processes, we exclude any metabolisation of
- 222 microplastics and presume no losses occur through wind and water erosion.

$$QMPS_{f,T} = \sum_{t_0}^{T} (QMP_{f,t_i})$$

- With
- 224 t_0 : The first year, for sludge = 1983, for compost = 1996
- 225 t_i : The past year, for sludge = (1984, 1985,..., 2016), for compost = 1996, 1997,..., 2016.
- 226 *T*: The last simulated year = (1984, ..., 2016):
- 227 $QMPS_{f,T} = QMPS_{f,t}$: Cumulative quantity of microplastic emitted to soils from fertilizer f 228 (sewage sludge, compost) over time in the simulated year t
- Based on normative assumptions of the maximal application of fertilizer f, we define three
- fertilization intensity scenarios: high, medium, and low (Table 1). The scenarios define the amount of fertilizer applied per area according to the given intensity (int).
- amount of fertilizer applied per area according to the given intensity (int).
- Equation 5 computes the polluted area $AMP_{f,int,t}$ fertilized with either sewage sludge or com-
- post. This scenario-driven calculation is based on the fact that the actual mean fertilization
- rates using compost and sewage sludge in Germany are unknown.

$$AMP_{f,int,t} = \frac{QF_{f,t}}{FINT_{f,int}}$$
(Eq. 5)

- 235 with
- 236 $AMP_{f,int,t}$: Area polluted with microplastic from the application of organic fertilizer (f) in 237 scenario (int) in year (t) in ha
- 238 $QF_{f,t}$: Quantity of organic fertilizer applied (f) in year (t) in kg of dry solids

- 239 *FINT*_{*f*,*int*}: *Fertilization intensity in kg/ha*
- 240 *int: Fertilization intensity scenario: high, medium, low*

Table 1: Average quantities of fertilizer dry solids applied per hectare and for different fertilization intensity scenarios

| Fertilization intensity | Sewage sludge | Compost |
|-------------------------|---------------|-------------|
| | kg/(ha * a) | kg/(ha * a) |
| High ^a | 1,600 | 10,000 |
| Medium ^b | 600 | 6,700 |
| Low ^c | 300 | 3,300 |

a) High intensity level: Sewage sludge: according to AbfKlärV2017):(5,000 kg/ha within 3 years, i.e., 1,600 kg = 5,000kg/3 years (according to AbfKlärV2017), according to DVO compost 30,000kg/ha in 3 years (according to BioAbfV 2017). B) Medium fertilization intensity = High intensity level * 0.66. c) Low fertilization intensity = High intensity level * 0.33

246 Equation 6 computes the average concentration of microplastics per polluted area

- 247 ($CAMP_{f,int,t}$) on which we expect microplastic emissions from sewage sludge and compost.
- 248 We make the simplified assumption that over time the same fields have been fertilized with

249 either sewage sludge or compost.

$$CAMP_{f,int,t} = \frac{QMPS_{f,t}}{AMP_{f,int,t}}$$
(Eq. 6)

250 *with*

CAMP_{f,int,t}: Concentration of microplastic per area for fertilizer (f), intensity (int) and year
 (t) in mg/ha

253 Equation 7 computes the average mass-based concentration of microplastics in the soil of the polluted area. We assume that microplastic is homogenously distributed in the soil due to 254 ploughing, and we define a soil depth of 30 cm as a uniform ploughing horizon all over Ger-255 256 many. We do not consider varying depths of ploughing horizons or the possible transfer of 257 microplastics into deeper soil horizons (e.g., by soil pores or organisms). Based on our assumption that farmers apply bio-solids to light sandy soils, we assume a uniform soil density 258 259 of 1.2 g/cm³ as smallest density for sandy light soils. The choosing the very small density of 1.2 g/cm³ results in an overestimation of sandy soils which have higher soil density (e.g., at 260 1.4 g/cm³), (i.e., the worst case assumption). We present the influence of the value of soil 261 262 density in a separate sensitivity analysis (see Appendix A-4.0).

$$CSMP_{f,int,t} = \frac{CAMP_{f,int,t}}{(ha * Ap * \rho_S)}$$
(Eq. 7)

263 *with*

- 264 $CSMP_{f,int,t}$: Concentration of microplastics in the soils for fertilizer (f), intensity (int) and 265 year (t) in mg/ha
- 266 *ha: One hectare equivalent in square meters* = $10,000m^2$
- 267 Ap: Ploughing horizon = 0.3m
- 268 ρ_s : Soil density = 1.200 kg/m³

269 **3 Results and discussion**

270 We use the normative emission model described by Equations (1) to (7) to estimate the quan-

tities of microplastic released into agricultural soils; to estimate the concentration of

272 microplastic accumulated in agricultural soils, and to estimate the agricultural area potentially273 polluted by microplastics.

274 **3.1** The quantities of microplastics released to agricultural soils

- First, we estimate the quantities of sewage sludge and compost applied to agricultural soils to
- derive the quantities of microplastics emitted. The input data for this estimation is based on $\frac{1}{2}$
- 277 sectoral statistical data provided by different sources 2 .

Figure 1 shows the quantities of sewage sludge and compost applied as an organic fertilizer
during the period 1983 to 2016. The annual quantities of sewage sludge applied remain lower
than one million tons (dry solids). Before 1990, the data does not include the sludge quanti-

than one million tons (dry solids). Before 1990, the data does not include the sludge quantities applied in East Germany. Based on the development of sludge quantities in western and

- eastern Germany (Gallenkemper and Dohmann 1994), it can be assumed, however, that this
- missing data from East Germany does not result in a significant underestimation of the quan-
- tities of microplastics before 1990.
- 285 The year 1995 saw a peak in the amount of sewage sludge applied and used as fertilizer on
- agricultural land, the use has dropped off continuously since then. Changes in disposal capac-
- ities and in the demand and use of sewage sludge explain this decreasing trend. The phasing-
- out of sewage sludge disposal in landfill sites expanded the capacities of thermal disposal
- 289 units (e.g., for incineration)³ and thus created an alternative option for the disposal of sludge
- 290 (Franck and Schröder 2015). The depletion of phosphorous resources increased the demand
- for sewage sludge as a raw material to recover and recycle phosphorous. Additionally, stricter
- legislation concerning the agricultural use of sewage sludge and increasing environmental
- concerns (e.g., due to the presence of pathogens and heavy metals) reduced the demand forsewage sludge as an organic fertilizer and soil amendment. Thus, legislation prohibits the use
- 294 sewage studge as an organic refunzer and son amendment. Thus, registration promotes the use 295 of sludge in critical regions (e.g., those close to surface waters or soils with already high lev-
- 296 els of pollution).
- In Germany, the agricultural use of compost has increased steadily since 1996, driven by the
- implementation of the Circular Economy legislation (The "Kreislaufwirtschaftsgesetz",
- KrWG 2012). This law initiated the systematic and wide-scale collection of biowaste from
- industry and households, and the recycling of this waste as an organic fertilizer and soil
- amendment. Since then, the improvement in infrastructures for collecting and recycling bio-
- 302 waste has resulted in four times more compost than sewage sludge being used in agriculture.

²UBA (2020), BMEL (2019), Statistisches Bundesamt und DWA-Arbeitsgruppe KEK-1.2 "Statistik" (2014, 2015).

³In May 1993 the TASI (Technische Anleitung Siedlungsabfall) prohibited the disposal of organic waste (such as sewage sludge) in landfills (TASI 1993).



Figure 1. Quantities of sewage sludge and compost dry solids applied to agricultural soils in Germany. Note: before the German reunification in 1989 data represent quantities only in West Germany, after 1989 quantities from East and West Germany are aggregated. Source: Own calculations based on UBA (2020), Bioabfälle, BMEL (2019), Statistisches Bundesamt und DWA-Arbeitsgruppe KEK-1.2 "Statistik" (2014, 2015).

303 Figure 2 shows the annual quantities of microplastic emissions from sewage sludge and com-

- $P_{f,t}$ post (QMP_{f,t}) for the period 1980 to 2016. The quantities of microplastic emitted from sewage sludge increase over time until 2010, where they remain at approximately 2,500 tons per
- 306 year between 2011 and 2016. This leveling off results from the decreasing quantities of sew-
- 307 age sludge applied to agricultural soils (Fig 2) combined with the increasing concentration of
- 308 microplastics in sludge (Fig Annexe-1). The higher concentration of microplastics in sewage
- sludge leads to annual emissions of these pollutants three to five times higher for sewagesludge than for compost. Thus, the fact that the emission factor of sewage sludge
- 311 ($EF_{sludge.2016} = 0.6\%$) is higher than the emission factor of compost ($EF_{compost.2016} = 0.04\%$)
- 312 compensates largely for the lesser amount of sewage sludge applied to land compared to
- 313 compost. Indeed, the simulated results of microplastic quantities and the subsequent results
- depend strongly on the assumptions of the microplastic concentration in sludge and compost.
- 315 We selected the high concentrations provided by the literature by following the worst-case
- 316 assumption, which could result in an overestimation of the results.
- Figure 2 presents the accumulated quantities of microplastics emitted from sewage sludge
- and compost in agricultural soils ($\overline{QMPS}_{f,t}$) over the period 1983 to 2016. The more signifi-
- cant increase in sewage sludge microplastics results from the assumption of the exponential
- 320 increase in microplastic concentration from synthetic fiber production (see Appendix A-1.0).
- **321** For the year 2016, the total quantity of microplastic originating from both sewage sludge and
- compost was estimated at 3,084 t, with 2,452 t originating from sewage sludge and 632 t from
- 323 compost. For the period 1983 to 2016, total emitted microplastics amounted to 58,997 t, with
- 48,733 t originating from sewage sludge and 10,264 t from compost. Emissions are approxi-
- 325 mately five times higher for sludge than for compost.



Figure 2. Quantities of microplastic emitted annually from sewage sludge and compost into agricultural soils in Germany. Source: Own computations based on: UBA (2020): Bioabfälle, BMEL (2019), Statistisches Bundesamt und DWA-Arbeitsgruppe KEK-1.2 "Statistik" (2014, 2015).

326 3.2 Concentration of microplastic and utilized agricultural area polluted with microplastics

- 328 We simulate two worst-case scenarios to estimate the concentration of microplastic in agri-
- cultural soils and the utilized agricultural area (UAA) with potentially polluted soils. One
- 330 simulates the highest concentration and the other simulates the largest extent of potentially
- 331 polluted area. We simulate both worst-case scenarios for the emission of microplastic by
- sewage sludge and by compost with each of three different fertilization intensities.
- 333 Concerning the highest concentration worst-case scenario, we assume that the fields received
- sludge or compost in each year of the simulation periods. Thus, microplastic emitted from
- sludge could have accumulated in these fields between 1983 and 2016 and from compost
- between 1990 and 2016. The area with the highest concentration is limited to the fertilizedarea of the first year. Only this area could have received microplastic from organic fertilizers
- 338 every year.
- 339 To determine the largest polluted UAA worst-case scenario, we use the year with the highest
- 340 quantity of sludge and compost applied to the land. The quantity determines the area, which
- 341 received, at least in one year, microplastic from the organic fertilizer. The year 1995 is estab-
- 342 lished with the largest quantity of sludge and 2016 for compost. Figure 3 plots the simulated
- 343 microplastic concentration in soils and the polluted UAA.
- 344 We simulate an accumulation of microplastic at 40 mg/kg (Point A) for the fields receiving
- an annual application of sludge (for 33 years, between 1983 and 2016), with the highest ferti-
- 346 lization intensity. We expect to find this high concentration on a potentially polluted area of 1.20% UAA (i.e. 0.22 million 1.5%
- 347 1.3% UAA (i.e., 0.22 million ha). For compost we compute a concentration of approximately 348 30 mg/kg on 0.5% UAA (i.e., 0.08 million ha) (Deint D)
- 348 30 mg/kg on 0.5% UAA (i.e., 0.08 million ha) (Point D).
- 349 Points I and L represent the maximal polluted UAA with any microplastic present after at
- least one application of sludge or compost between 1983 and 2016 at the lowest simulated
- fertilization intensity. These fields add up to 19% of UAA (3.17 M ha) for sludge and 3% of
- 352 UAA (0.5 M ha), for compost, with correspondingly marginal microplastic concentrations.

- The aggregated UAA with highest concentration from sludge or compost does not exceed 2%
- 354 UAA (~ 1.8% UAA = 1.3% UAA + 0.5% UAA). The maximum UAA with some
- microplastic pollution resulting from at least one application of sludge or compost, does not exceed in total about 20% of UAA (\sim 22% UAA = 19% UAA + 3% UAA).
- 357 In situ the concentration of microplastic in agricultural soils can be expected to be m
- In situ the concentration of microplastic in agricultural soils can be expected to be much lower than simulated in the worst-case scenarios, because the yearly application of sludge or
- er than simulated in the worst-case scenarios, because the yearly application of sludge orcompost might not have been carried out in practice. The enrichment by organic matter might
- be reached at a certain point and does not require further fertilization with sludge or compost.
- soo se reached at a certain point and does not require further refunzation with studge of compost.
- 361 The scenarios assuming medium and low fertilization intensity result in lower concentration
- than for the scenario of high fertilization intensity. The concentrations are Sludge 16 and
- 363 7 mg/kg (Point B and C) and Compost 20 and 10 mg/kg (Points E and F). The total potential-
- 364 ly polluted area adds up to about 10% of UAA (= 1.61 M ha) (Points H+K) for medium fertilization intensity 22% of UAA (= 2.56 M ha) (Points L+L) for law fartilization intensity
- 365 lization intensity 22% of UAA (= 3.56 M ha) (Points I+L) for low fertilization intensity.



Figure 3. Microplastic concentrations in agricultural soils and extent of polluted area in the simulated scenarios of high, medium and low fertilization intensity for the year 2016.

Notes: 1 % of UAA = 0.167 M ha. Scenario assumptions: annual application rates in the: (i) high fertilization intensity scenario: 1.6 t/ha for sludge and 10 t/ha for compost, (ii) medium fertilization intensity scenario: 0.6 t/ha for sludge and 6.7 t/ha for compost. (iii) low fertilization intensity scenario: 0.3 t/ha for sludge and 3.3 t/ha for compost. Application duration: sludge 1980 to 2016, for compost from 1990 to 2016. Soil density: 1.2 g/cm+3. Ploughing horizon: 0.3 m.

- 366 The simulations provide benchmark values of concentration and potentially polluted UAA for
- the whole of Germany. However, at the regional scale the concentrations and the UAA can
- 368 vary. Figures 4a to 4d present the potentially polluted UAA at regional county level in the
- reference year 2016 for low fertility intensity (Fig a and d) and high fertility intensity (Fig b
- and c). The snap-shot for the year 2016 illustrates significant regional heterogeneity of the
- 371 potentially polluted UAA.
- 372 In the high fertilization scenario with sludge, the potentially polluted soils reach 1 to 4 % of
- utilized agricultural area (UAA) in the north-western half of Germany, where farmers have
- traditionally been applying more sludge as fertilizer than in the southern regions (Aqua Con-
- sult Baltic 2015). In the southern regions, the regional governments recommend not applying

- 376 sludge as organic fertilizer (StaLa-BW 2021, UM-BW 2021, LfU 2020). Thus, in Baden-
- Württemberg (South-East) the agricultural disposal of sludge as fertilizer has been nearly
 completely abandoned and disposal has switched to thermal recycling and to export of sludge
- 379 (StaLA-BW, 2021).
- 380 In urban regions the polluted area is higher because of high supply of sludge from many in-
- habitants. The low transportation value of sewage sludge limits the transportation distance
- from waste water treatment plants to the sites of application. Consequently, the application of
- sewage sludge as a fertilizer is higher in regions close to bigger cities, such as Hamburg,
- Hannover, and in the north of the urban cluster the Ruhr Area, (Dortmund, see Figures 4a and
- b). The regional distribution of area polluted by compost follows the similar pattern, with the
- difference that compost is used as fertilizer. Polluted areas of 4 to 6 % of UAA can be found
- also around Frankfurt, Stuttgart and Munich (see, Figures 4c and d).



Fig 4a. Area potentially polluted by microplastic from sludge in share of UAA under fertilization intensity of 1.6 t/ha



Fig 4b. Area potentially polluted by microplastic from sludge in share of UAA under fertilization intensity of 0.3 t/ha

Area with MP pollution in %UAA



Fig 4c. Area potentially polluted by microplastic from compost in share of UAA under fertilization intensity of 10 t/ha



Fig 4d. Area potentially polluted by microplastic from compost in share of UAA under fertilization intensity of 3.3 t/ha

- 388 The regional analysis suggests that the regions around big cities are a hot-spot where many
- 389 sites with potentially polluted soils can be expected. These regions may require particular
- focus for environmental assessment. Furthermore, these regions could also be of interest forin situ analysis of microplastic in soils on suitable sample fields.

392 3.3 Evaluating abatement measures

- 393 The simulated model results indicate that the microplastic concentration and the polluted area
- can regionally be relatively high. Abatement measures may be required, depending on how
- future research quantifies the thresholds of damage, the thresholds of concentration or the
- thresholds of area. The definition might not only be based on negative impacts of
- 397 microplastic in the terrestrial environment. Such thresholds can also consider potentially neg-
- ative impacts caused by the emissions of microplastics from soils (e.g., transport into aquatic
- 399 systems by soil erosion).

400 **3.3.1 Scenarios of abatement measures**

- 401 To analyze the ways to reduce microplastic emissions from sewage sludge and compost, we
- 402 simulate abatement measures for sludge and compost according to environmental policy prin-
- 403 ciples. Filter systems for washing machines, and detection systems for bio-waste collection
- 404 represent measures in accordance with the "reduction at the source" principle. Thermal recy-
- 405 cling would rather represent an "end-of-the pipe" treatment.
- 406 Furthermore, filter and detection systems for households and industry follow the "polluter-
- 407 pays-principle", whereas thermal recycling (end-of-the-pipe solution) might create the costs
- 408 for farmers by halting the application of sludge and compost as fertilizer. We compute two
- 409 indicators for the reference year 2016 assessing relative cost-efficiency and effectiveness of
- 410 the simulated measures: the marginal abatement costs and the abatement effect. We compare

- the results of the scenarios with a reference, without any measure to avoid the microplastic
- emissions. To evaluate the effectiveness of the measures in the long term, we also simulate
- the evolution of microplastics in soils up to the year 2060.

414 Scenario: No-Measure

- 415 We assume that the land-based disposal of sludge and compost as organic fertilizer continues
- 416 without any abatement measure, without any extra-costs and without reduction of
- 417 microplastic emissions. For the sludge we assume that the content of microplastic remains at
- the level defined for the reference year 2016 and for the long-term simulation, we assume an
- annual increase in its use as observed as average for the last five years from 2015 to 2020.
- For sludge disposal in Germany, the scenario "No-Measure" is not realistic, because in Germany the sludge from bigger waste water treatment plants with will be mandatorily thermally
- 421 many the studge from orgger waste water treatment plants with will be man422 recycled. Thus, this scenario is counter-factual serving as comparison.
- 423 For compost the scenario "No-Measure" represents the current situation in reality. Although
- there are defined thresholds for the maximum content of non-organic items in compost (i.e.,
- 425 at 1%, Kehres 2019), there is currently no specific measure to reduce the content of
- 426 microplastic emissions to agricultural soils significantly below this threshold. For the long-
- term simulation, we assume that infrastructure for biowaste collection will improve and allow
- 428 for the collection of additional biowaste, which was not collected from all households in
- 429 2016. Thus, up to the year 2060 we assume an annual increase of 1%, which increases the
- 430 quantity of collected bio-waste by about 50% compared to the 2016 value. This value corre-
- 431 sponds to the estimate of the hidden potential of biowaste by Herrmann et al. (2017:7). We432 assume that the microplastic content in compost remains stable over this time.
- 452 assume that the interophastic content in compost remains stable over this time

433 Scenario: Thermal recycling of sludge and bio-waste (end-of-the-pipe)

- 434 For sludge in Germany this scenario is close to the reality. After 2030 most of the sludge will
- be thermally recycled from waste water treatment plants with population equivalents greater
- than 50,000. Waste water treatment plants treating smaller volumes can continue with
- 437 landbased disposal (Rokosch 2019). We simplify the scenario assumption so that the sludge
- 438 from the smaller waste water treatment plants is also thermally recycled.
- 439 For compost, we assume that the fraction of biowaste originating from households and indus-
- try is thermally recycled, as we assume that most of microplastics enter the compost from
- these sources. We assume that bio-waste from landscaping (e.g., cuttings), continues to be
- 442 recycled as compost and disposed on the land.
- Thermal recycling results in a reduction of microplastic emission by 100% for both sludge
- and compost. We assume that microplastic accumulates in the soil and does not migrate or
- decompose, thus in the long-run, the projected soil concentration remains in 2060 at the levelof 2016.
- 447 To estimate the abatement costs, we consider (i) technical costs for the thermal recycling pro-448 cess, (ii) cost for the loss of nutrients which are not available for agricultural production and
- 449 (iii) cost of CO₂ emissions.
- 450 We assume the technical cost for thermal recycling for sludge as the additional costs com-
- 451 pared to the land-based recycling as being higher than for compost. The energy demand for
- 452 incinerating sludge is higher than for bio-waste. We do not consider the costs for building the
- 453 thermal recycling plants. Considering these fixed costs will increase the cost of thermal recy-
- 454 cling.
- To derive the costs for the lost nutrients, we assume that farmers replace the lost nutrients
- 456 with mineral fertilizers and straw for substituting the organic matter. To derive the cost of

- 457 CO₂ emissions, we assume that during thermal recycling the carbon in the organic matter is
- burned completely to CO_2 . This CO_2 is released to the atmosphere as greenhouse gas, where the contributes to a label surveying We simplify any structure and contributes the surveying the second structure of the surveying the second structure of the second structu
- 459 it contributes to global warming. We simplify our assumption and consider only the emis-460 sions resulting from burning carbon. We also exclude the emission of other greenhouse gases,
- 460 sions resulting from burning carbon. We also exclude the emission of other greenhouse gases, 461 which might be emitted during incineration (nitrogen oxides, etc). We assume that in land-use
- 462 based recycling, the carbon from the organic matter in sludge and compost will be fixed in
- the soils for longer durations. Thus, we simulate carbon price to quantify the cost of these
- 464 emissions and vary them from 50 to 200 EUR/t CO₂eq.

465 Scenario: Filter systems in washing machines

- We assume that 75% of microplastic in wastewater and sewage sludge is released from the textile fibers during the washing of clothes in private households and industry. Filters applied to the washing machines in households can reduce the emission of textile fibers by up to 80%. In this scenario we assume that each washing machine in Germany is equipped by a
- 470 filter for textile fibers.
- 471 This scenario is oriented from the abatement measure foreseen in France. As the leading Eu-
- ropean country, France intends to make it compulsory for washing machine manufacturers to
- equip new machines with filters starting in January 2025 (Ministère de la Transition
- 474 écologique et solidaire 2020). This measure would be in line with the European plastic strate-
- 475 gy (European Union 2012) and would help reduce the emissions of microplastic from house-
- 476 holds. To estimate the costs for the filter systems, we derive the costs for the technical477 equipment of washing machine with filters and for replacing the filter membranes. We com-
- 477 equipment of washing machine with mers and for replacing the memoranes. We com-478 pute annual costs, based on the 10-year lifespan of a washing machine. As the abatement
- 479 measure reduces only microplastic emission from textile fibers (i.e., 75% of the total
- 480 microplastic in sludge), the total concentration of microplastic content in sludge is reduced by
- totally 45%. We assume that microplastic emissions to wastewater and sludge from other
- sources stay unchanged, although for some sources a reduction can also be expected. In some
- 483 EU countries some producers have already banned the use of plastic microbeads in personal 484 care products and detergents (e.g., in the Netherlands, France, Ireland, Sweden, UK and Ita-
- 485 ly).

486 Scenario: Detection system for bio-waste collection

- 487 The microplastic content in compost results mainly from packaging material. Detection sys-
- tems in garbage trucks, which collect the biowaste from households and industry, allow for
- the quantification of the non-organic material in the biowaste. Thus, excessively high levels
- 490 of plastic during the collection process can be detected in the bio-waste. Plastic contaminated
- bio-waste is not collected and households are informed that their biowaste does not reach the
- required quality standard. The households have to pay extra fees for its disposal. We assumethat quality control combined with a monetary penalty will improve the quality of the
- 494 biowaste and reduce the plastic content by 90%. We assume that the same system and policy
- 495 can be applied for the collection of industrial biowaste. This scenario is based on a detection
- 496 system and policy measures tested in some German communities (see Appendix A-3.5.1). To
- derive the costs, we apply the annual cost for the detection system to the total number of gar-
- bage trucks collecting biowaste in Germany. Since, statistical data on the total number of
- 499 garbage trucks could not be retrieved, we estimated the number of German garbage truck for
- 500 biowaste and varied the number in a sensitivity analysis (see Appendix A-3.5.1).
- 501 Table 2 summarizes the assumption of the scenarios for analysing the abatement measures.
- 502 Appendix A-3.5 presents the assumption and the computations and source in more detail.
- 503 Indeed, the data and the results can only provide a rough estimation because the assumptions

for the simulated systems are based on pioneering techniques. Thus, the interpretation of the results is limited to ranges and should not be considered as exact figures as marginal abatement costs are used as indicators for ordinal comparison rather than for the interpretation of absolute costs. Furthermore, the results require future updating and revision because future technological progress might change the assumptions for costs, prices and effectiveness.

| | Sludge | | Compost/Bio- Wast | | |
|--|---|--|--|---|--|
| | Thermal recy- cling | Filter System | Thermal recy- cling | Detection System | |
| Abatement Reduction rate Costs | 100% | 45% | 100% | 80% | |
| Cost of tech- nique | 2.5 EUR/(t dry matter)additional cost compared to landbased appli- cation | 35 EUR per filter and washing mash- ing, 0.8 EUR per filter mem- brane | 0.90 EUR/(t dry matter), additional cost compared to landbased appli- cation | 3965 EUR per garbage truck for biowaste collection per year | |
| Cost of Nutri- ent Losses | 144 EUR/t | | 55 EUR/t | | |
| Cost of CO2 emissions | varied for from 0 to 200 EUR/t CO2eq | | varied for from 0 to 200 EUR/t CO2eq | | |
| Projection to 2060 | | | | | |
| Quantity of sludge and compost ap- plied to soils | Reduced to zero tons in 2021 | annual applica- tion of sludge until 2060 based on the average appli- cation from 2015 to 2019 | Increase of col- lected biowaste from households by 0.5% annually until 2060 | | |

509 **Table 2: Overview on reduction rate and costs.**

510 Notes: Filter systems reduce fibers from textile washing by 80%, which accounts for 45% of the total microplastic load in waste-water. Detection systems reduce the quantity of non-organic waste disposed in the bio-waste collection bin by 80%.

512 **3.3.2** Cost-efficiency and effectiveness

513 Table 3 presents the marginal abatement cost and the abatement effect for the simulated

abatement measures. For sludge, the marginal abatement costs are significantly higher for the

515 filter system than for thermal recycling, even under extremely high assumptions for the car-

bon prices at 200 EUR/t CO₂eq. The filter system abates with 1,000 t less than the half of the

abatement reached by thermal recycling scenario with 2500 t. Reducing more microplastics

518 would require additional measures (e.g., technical standards) to abate emissions from the

cleaning of containers (17% of the total load), cosmetics and personal care products (14%)

- and cleaning products (3%).
- 521 Removing microplastics as an ingredient has already been considered by some producers of

522 personal care and cleaning products who can retain market shares by "greening" their prod-

523 ucts. Since microplastics are publicly discussed as pollutants, consumers favor products with-

524 out microplastics. In some products, microplastics can be replaced by more environmentally

525 friendly particles to achieve the abrasive or covering effects (e.g., natural crystals: salt, sand).

- 527 cost, would reduce the marginal abatement cost to only 120 EUR/kg. The costs for the filter
 528 system is still higher than the abatement cost computed for the thermal recycling at carbon
 520 prices at less than 200 EUR/t CO2eg (Table 2)
- 529 prices at less than 200 EUR/t CO2eq (Table 2).
- 530 The limited abatement effect of the filter system (i.e., reduction by 45%) and the high costs
- make the filter system less cost-efficient and less effective than thermal recycling. Thermal
- recycling of sludge has other advantages not considered here. Thermal recycling allows for
- recycling of phosphorous, which can reenter the nutrient cycle as a mineral fertilizer. Additionally, thermal recycling avoids the release of pollutants other than microplastic into the
- 535 soil and aquatic systems (e.g., antibiotics, heavy metals and pathogens).
- Thus, the results confirm the planned thermal recycling of sludge from bigger waste watertreatment plants as a cost-efficient and effective measure. However, washing machine filter
- 538 systems could still be considered as an abatement measure for households connected to waste
- 539 water treatment plants with population equivalents lower than 50,000, which will be still al-
- 540 lowed to dispose of their sludge by land (Rokosch 2019). The regional application of filter
- 541 systems would allow for an effective reduction of microplastic emission into agricultural
- 542 soils. As less cost-efficient than thermal recycling, however, the filter system would allow the
- 543 disposal of sludge according to the objectives of the European Circular Economy Strategy
- and in line with soil and environmental protection (European Union 2020b).

Table 3: Average MP abatement costs and abatement effect of the simulated abatement measures

| Abatement costs | | | | | |
|--|----------|--------|----------------------|-----------------|-------------------|
| | | Sludge | Bio-waste | used for compos | t |
| | | | Number of collection | garbage trucks | used for biowaste |
| Assumptions of fitted number of garbage trucks | | | 1,400 | 2,500 | 3,000 |
| Filter system for washing maschines | [Eur/kg] | 264 | NA | NA | NA |
| Detection system for biowaste collection Thermal recycling of sludge or biowaste, | [Eur/kg] | NA | 9 | 16 | 19 |
| carbon price = 200EUR/t CO2eq Thermal recycling, carbon price = | [Eur/kg] | 110 | 262 | 262 | 262 |
| 100EUR/t CO2eq Thermal recycling, carbon price = 50EUR/t | [Eur/kg] | 85 | 164 | 164 | 164 |
| CO2eq | [Eur/kg] | 73 | 115 | 115 | 115 |
| Thermal recycling, no carbon price | [Eur/kg] | 61 | 66 | 66 | 66 |
| Abatement effect | | | | | |
| Filter system for washing machines | [tons] | 1112 | NA | NA | NA |
| Detection system for biowaste collection Thermal recycling, carbon price = | [tons] | NA | 612 | 612 | 612 |
| 200EUR/t CO2eq | [tons] | 2450 | 680 | 680 | 680 |

547 For bio-waste, the marginal abatement cost for the garbage truck detection system is cheaper than the thermal recycling, even at zero cost emission costs (66 EUR/kg) and even with the 548 high assumption of fitting out 3,000 garbage trucks at 19 EUR/kg. The marginal abatements 549 costs from losses of nutrients are relatively high for compost (see Appendix A-3.0). Thus, the 550 abatement of emission at the source of pollution appears to be more cost-efficient than the 551 end-of-pipe solution. Fitting out more than 10,000 garbage trucks would let the abatement 552 costs be higher than the cost for the filter system. However, a number of 10,000 garbage 553 554 trucks for the bio-waste collection seems to be an extremely high given that the number of

- 555 garbage trucks (for biowaste and other waste) in Germany is estimated to be 12,000 (VAK
- 556 2021). In terms of effectiveness, the reduction of microplastics by 612 tons using the detec-557 tion system is comparable to the reduction by thermal recycling with a 680-ton reduction.

558 3.3.3 Effectiveness in the long-run

To analyse the effectiveness of the abatement measure over time, we simulate a period from 2016 to 2060. Indeed, the simulation period of more than 40 years appears to be quite long, and many changes can occur during this time in terms of environmental policies and technological progress (e.g., development of completely biodegradable (bio) plastics or of textiles with reduced fiber emissions). Thus, the *ceteris paribus* assumption for the simulation period

- 564 is important to consider.
- Figure 5 displays the evolution of the concentration over time under the worst-case assumption of the highest fertilization intensity, resulting in the highest future pollution pressure.
 This means, strong *ceteris paribus* conditions over the long term. In the No-Measure scenario, the concentration of microplastic from sludge will reach about 50 mg/kg in 2020 and
- 569 140 mg/kg in 2050; with filter systems applied in 2021, the concentration reaches 100 mg/kg
- 509 in 2050, with thermal recycling the concentration remains below 60 mg/kg in 2060. For
- 570 m 2050. With the main recycling the concentration remains below 60 mg/kg in 2000. For 571 compost without changes, the concentration will reach about 30 mg/kg in 2020 and 65 mg/kg
- 572 in 2050. With simulating the start of using detection systems or thermal recycling in 2021, the
- 573 concentration increases at a low rate and remains until 2060 at less than 40 mg/kg. The simu-
- 574 lation of the microplastic concentration in the soil over the long term illustrates that the detec-
- tion system effectively reduces the emissions of microplastic from compost into agricultural
- 576 soils.





Note: in the scenarios "Compost Thermal" and "Compost Detection" and we refer to the thermal recycling of bio-waste and the detection system applied to the collection of bio-waste.

577 **4** Conclusions

578 The new environmental problem of microplastic pollution represents a new challenge for

- 579 policy makers to follow the principles of precaution and prevention under respecting scien-
- tific evidence and appropriateness. Scientific evidence is required for the evaluation of the
- 581 microplastic pollution, which considers all economic agents and stakeholders along the pollu-
- tion chain (e.g. society and farmers) (Henseler et al. 2020). Wholistic evaluation approaches
- and interdisciplinary research is required to understand the complex of microplastic pollution,

as it is required for many problems in environmental economics (Melgar-Melgar and 2020,
Hagens 2020).

586 The normatively simulated results allow the conclusion that the current microplastic concen-587 tration from sludge or compost (2020) should not exceed concentrations between 40 and 50 mg/kg, which is computed under the worst-case assumption. The potentially polluted area 588 589 with such a high concentration should not exceed the relatively small agriculturally used area of 2%. Area polluted with some microplastic from at least one application should not exceed 590 22% (i.e., around 20%) of utilized agricultural area, which is a considerable area, however, 591 592 which also includes fields where sludge or compost have been applied only one time and where the concentration of microplastic is expected to be marginal. The computed values for 593 concentration and area can flow into the discussion between researchers and policy makers as 594 595 scientific data required for policy design. The regional analysis shows that in regions close to bigger cities, more polluted UAA should be expected where regional assessments and 596 597 measures could be required.

598 Applying detection systems for the collection of biowaste appears to be a cost-efficient and

- effective abatement measure to avoid microplastic emissions from compost, and it the strate-
- 600 gy of a circular economy to be followed (European Union 2020b). For sludge, the thermal
- 601 recycling appears to be more cost-efficient and effective than equipping washing machines
- with filters. However, for regions where land-based disposal of sludge will continue, filterssystems could be an option to reduce soil pollution. The simulated results also can provide a
- 604 starting point for information on the cost and benefit of mitigation measures.
- The results presented in this study are based on simulations with a normative model. The assumptions of the model, the scenarios and the results, need to be revised and up-dated accord-
- 607 ing to the relatively fast developing research field "microplastics". However, the presented
- 608 model-based values can contribute as scientific data on soil pollution as required by the Eu-
- ropean legislation to discuss, design and evaluate environmental policies. Preventing soil pol lution has gained recent relevance within the European Green Deal (European Union 2019)
- 611 directly addressed by the European "New Soil Strategy" (European Union 2019)
- 612 "Action Plan towards a Zero Pollution Ambition for Air, Water and Soil" (European Union
- 613 2020a). As findings for the study region Germany, the result can also be applied for the dis-
- 614 cussion on countries with comparable of usage of sludge and compost in agriculture.
- The application of normative models can be a complementary approach to methods used by
- analytical science. An interdisciplinary and iterative research approach between modelling
- and analytical science can be a fruitful way to close the knowledge gaps on microplastics.
- 618 Model simulations can help estimate concentrations, assess polluted areas and to identify sites
- 619 interesting for in-situ. The evidence from analytical science is required to calibrate and vali-
- 620 date the simulation models. Normative simulation models can be developed complementarily
- 621 to analytical science methods and be prepared to support policy decision-making on a still
- 622 unknown, but already ubiquitous pollutant: microplastics in agricultural soils.

623 **5** Literature

- 624 Abate T.G., Börger T., Aanesen M, Falk-Andersson J, Wyles KJ, Beaumont N. (2020): Valua625 tion of marine plastic pollution in the European Arctic: Applying an
- 626 integrated choice and latent variable model to contingent valuation. Ecological Economics627 169 (2020) 106521
- 628 AbfKlärV (2017). Verordnung über die Verwertung von Klärschlamm, Klärschlammgemisch
 629 und Klärschlammkompost (Klärschlammverordnung AbfKlärV), 47.

- 630 Aqua Consult Baltic (2015): "Ausarbeitung der Lösungen zur regionalen Klärschlammaufberei-
- 631 tung sowie Ausarbeitung der Kriterien zum Ende der Abfalleigenschaft von Klärschlamm"
- 632 Teil III Begründung.URL: <u>https://ec.europa.eu/growth/tools-</u>
- 633 <u>databases/tris/hr/index.cfm/search/?trisaction=search.detail&year=2017&num=154&iLang=</u>
 634 <u>DE</u> 2021-02-13
- 635 Backhaus, T., & Wagner, M. (2019). Microplastics in the Environment: Much Ado about
- 636 Nothing? A Debate. *Global Challenges*, *1900022*, 1900022.
- 637 https://doi.org/10.1002/gch2.201900022
- 638 Bakir, A., Rowland, S. J., & Thompson, R. C. (2014). Enhanced desorption of persistent organic
- 639 pollutants from microplastics under simulated physiological conditions. *Environmental Pollu-*
- 640 *tion*, 185. https://doi.org/10.1016/j.envpol.2013.10.007
- 641 Batker D (2020): Implementing ecological economics. Ecological Economics 172 (2020)642 106606
- 643 BBodSchG (2017). Gesetz zum Schutz vor schädlichen Bodenveränderungen und zurSanierung
 644 von Altlasten (Bundes-Bodenschutzgesetz BBodSchG)
- 645 BBodSchV (2017). Bundes-Bodenschutz- und Altlastenverordnung (BBodSchV)BBodSchV
- 646 Bertling, J., Bertling, R., & Hamann, L. (2018). Kunststoffe in der Umwelt : Mikro- und Makro-
- 647 plastik. Ursachen, Mengen, Umweltschicksale, Wirkungen, Lösungsansätze, Empfehlungen.
- 648 Kurzfassung der Konsortialstudie. *Fraunhofer UMSICHT*, 10–11, 16.
- 649 https://doi.org/10.24406/UMSICHT-N-497117
- 650 BGK (2017). Verwertung von Bioabfällen 2016. BGK-Statistik . Humuswirtschaft & Kompost
 651 Aktuell.(Q1 2017)
- 652 BGK (2018). Kunststoffe in Kompost und Gärprodukten. *Humuswirtschaft & Kompost Aktuell*,653 (Q4 2018).
- 654 BioAbfV (2017). Verordnung über die Verwertung von Bioabfällen auf landwirtschaftlich,
 655 forstwirtschaftlich und gärtnerisch genutzten Böden (Bioabfallverordnung BioAbfV)
- 656 BKV (2017). Vom Land ins Meer Modell zur Erfassung landbasierter Kunststoffabfälle.
- Bläsing, M., & Amelung, W. (2018). Plastics in soil: Analytical methods and possible sources. *Science of the Total Environment*, 612. https://doi.org/10.1016/j.scitotenv.2017.08.086
- 659 BMEL (2019). Statistisches Jahrbuch über Ernährung, Landwirtschaft und Forsten (2019).
- Federal Minister of Food and Agriculture (BMEL). Verbleib von Kompost und Klärschlamm.
 SJT-3060620-0000.xlsx.
- 662 Brennholt, N., Heß, M., & Reifferscheid, G. (2018). Freshwater Microplastics: Challenges for
- 663 Regulation and Management. In Wagner, M., & Lambert, S. (2018). *Freshwater*
- 664 *Microplastics The Handbook of Environmental Chemistry* 58. https://doi.org/10.1007/978-
- 665 3-319-61615-5
- 666 Brodhagen, M., Goldberger, J. R., Hayes, D. G., Inglis, D. A., Marsh, T. L., & Miles, C. (2017).
- Policy considerations for limiting unintended residual plastic in agricultural soils. *Environ- mental Science and Policy*, 69, 81–84. https://doi.org/10.1016/j.envsci.2016.12.014
- 669 Büks, F., van Schaik, N. L., Kaupenjohann, M. (2020). What do we know about how the terres-
- trial multicellular soil fauna reacts to microplastic? SOIL Discuss, in review.
- 671 https://doi.org/10.5194/soil-2020-4

- 672 Carney Almroth, B. M., Åström, L., Roslund, S., & Petersson, H. (2017). Quantifying shedding
 673 of synthetic fibers from textiles ; a source of microplastics released into the environment. *En-*674 *viron Sci Pollut Res.* https://doi.org/https://doi.org/10.1007/s11356-017-0528-7
- 675 Cesa, F. S., Turra, A., Baruque-Ramos, J. (2017). Synthetic fibers as microplastics in the marine
 676 environment: A review from textile perspective with a focus on domestic washings. Science
 677 of the Total Environment 598 (2017) 1116–1129
- 678 Corradini, F., Meza, P., Eguiluz, R., Casado, F., Huerta-Lwanga, E., & Geissen, V. (2019).
- 679 Evidence of microplastic accumulation in agricultural soils from sewage sludge disposal.
- 680 *Science of the Total Environment*, 671, 411–420.
- 681 https://doi.org/10.1016/j.scitotenv.2019.03.368

682 Crossman J, Hurley RR, Futter M, Nizzetto L. (2020): Transfer and transport of microplastics

- from biosolids to agricultural soils and the wider environment. Science of The Total Envi-
- 684 ronment, 724, 2020 https://doi.org/10.1016/j.scitotenv.2020.138334.
- 685 De Falco, F., Pia, M., Gentile, G., Di, E., Escudero, R., Villalba, R., ... Avella, M. (2017).
- Evaluation of microplastic release caused by textile washing processes of synthetic fabrics *.
 Environmental Pollution. https://doi.org/10.1016/j.envpol.2017.10.057
- 688 De Souza Machado, A. A., Kloas, W., Zarfl, C., Hempel, S., & Rillig, M. C. (2018).
- Microplastics as an emerging threat to terrestrial ecosystems. *Global Change Biology*, 24(4).
 https://doi.org/10.1111/gcb.14020
- 691 DüMV (2019). Verordnung über das Inverkehrbringen von Düngemitteln,Bodenhilfsstoffen,
 692 Kultursubstraten und Pflanzenhilfsmitteln (Düngemittelverordnung DüMV)
- 693 DüV (2017). Verordnung über die Anwendung von Düngemitteln, Bodenhilfsstoffen, Kultursub-
- 694 straten und Pflanzenhilfsmittelnnach den Grundsätzen der guten fachlichen Praxis beim Dün-
- 695 gen (Düngeverordnung DüV)
- 696 Eerkes-Medrano, D., Thompson, R. C., & Aldridge, D. C. (2015). Microplastics in freshwater
- 697 systems: A review of the emerging threats, identification of knowledge gaps and prioritisation 698 of research needs. *Water Research*, 75, 63–82. https://doi.org/10.1016/j.watres.2015.02.012
- 699 Espí, E., Salmerón, A., Fontecha, A., García, Y., & Real, A. I. (2006). Plastic films for agricul-
- tural applications. *Journal of Plastic Film and Sheeting*, 22(2), 85–102.
- 701 https://doi.org/10.1177/8756087906064220
- 702 European Commission (2018). Communication from the Commission to the European Parlia-
- ment, the Council, the European Economic and Social Committee and the Committee of the
- Regions: A European Strategy for Plastics in a Circular Economy. *COM*(2018) 28 *Final*,
- 705 *SWD*(2018)(1), 1–18. https://doi.org/10.1021/acs.est.7b02368
- Furopean Commission (2019): The European Green Deal. Communication by the European
 Commission. COM(2019) 640 final. URL: https://eur-lex.europa.eu/legal-
- 708 content/EN/TXT/?qid=1596443911913&uri=CELEX:52019DC0640#document2 [2021-02-
- 709 07]
- 710 European Parliament and the Council of the European Union. (2018). Official Journal of the
- European Union L 150: Legislation. *Official Journal of the European Union*, 2018(406), 26–
- 712 42. Retrieved from https://eur-lex.europa.eu/legal-
- 713 content/EN/TXT/PDF/?uri=OJ:L:2016:119:FULL

- 714 European Union (2012): Consolidated Version of the Treaty on the Functioning of the European
 715 Union (TFEU) URL: https://eur-lex.europa.eu/legal-
- 716 content/EN/TXT/PDF/?uri=CELEX:12012E/TXT&from=EN [2021-02-07]
- 717 European Union (2020a): EU Action Plan "Towards a Zero Pollution Ambition for air, water
- and soil –building a Healthier Planet for Healthier People". Communication by the European
- 719 Union. Ref. Ares(2020)5152184 01/10/2020 URL:
- 720 https://ec.europa.eu/environment/strategy/zero-pollution-action-plan_en#ecl-inpage-214
- 721 [2021-02-07]
- 722 European Union (2020b): Circular Economy Action Plan. For a cleaner and more competitive
- 723 Europe. URL: https://ec.europa.eu/environment/circular-
- economy/pdf/new_circular_economy_action_plan.pdf [2021-02-25]
- 725 European Union (2021): New Soil Strategy healthy soil for a healthy life. Communication by726 the European Union. Ref. Ares(2020)6391319 05/11/2020. URL:
- https://ec.europa.eu/info/law/better-regulation/have-your-say/initiatives/12634-New-EU-Soil-
- 728 Strategy-healthy-soil-for-a-healthy-life [2021-02-07]
- 729 Franck, J., & Schröder, L. (2015). Zukunftsfähigkeit kleiner Klärschlammverbrennungsanlagen.
- 730 In J. . Thomé-Kozmiensk & M. . Beckmann (Eds.), Energie aus Abfall (Vol. 12, pp. 457-
- 731 476). Verlag KarlThomé-Kozmiensky.
- 732 Gallenkemper, B., & Dohmann, M. (1994). *Klärschlamm-Entsorgung*. Economica-Verlag,733 Bonn.
- 734 Gestoso, I., Cacabelos, E., Ramalhosa, P., & Canning-Clode, J. (2019). Plasticrusts: A new
- potential threat in the Anthropocene's rocky shores. *Science of the Total Environment*, 687,
- 736 413–415. https://doi.org/10.1016/j.scitotenv.2019.06.123
- 737 Gömann, H., Kreins, P., Kunkel, R., & Wendland, F. (2005). Model based impact analysis of
- policy options aiming at reducing diffuse pollution by agriculture A case study for the river
- Ems and a sub-catchment of the Rhine. *Environmental Modelling and Software*, 20(2), 261–
- 740 271. <u>https://doi.org/10.1016/j.envsoft.2004.01.004</u>
- 741 Hagens N.J. (2020): Economics for the future Beyond the superorganism. Ecological Econom742 ics 169 (2020) 106520
- 743 Hahladakis, J. N., Velis, C. A., Weber, R., Iacovidou, E., Purnell, P. (2018). An overview of
- chemical additives present in plastics: Migration, release, fate and environmental impact dur-
- ing their use, disposal and recycling. Journal of Hazardous Materials, 344, 179-199.
- 746 https://doi.org/10.1016/j.jhazmat.2017.10.014
- 747 Henseler, M., Brandes, E., Kreins, P. (2020) Microplastics in agricultural soils: A new challenge
- not only for agro-environmental policy? Journal of Applied Business and Econonomics
- 749 22(7):38-52, DOI:10.33423/jabe.v22i7.3250
- 750 Hernandez, E., Nowack, B., & Mitrano, D. M. (2017). Mechanistic Study to Understand Micro
- 751 fi ber Release During Washing. *Environmental Science & Technology*.
- 752 https://doi.org/10.1021/acs.est.7b01750
- Herrmann, T., Weiss, V., Bannick, C. G., Ehlers, K., & Claussen, U. (2017). Bioabfallkomposteund -gärreste in der Landwirtschaft. *Position*. UBA Position paper
- 755 Horton, A. A., Walton, A., Spurgeon, D. J., Lahive, E., & Svendsen, C. (2017). Microplastics in
 756 freshwater and terrestrial environments: Evaluating the current understanding to identify the

- knowledge gaps and future research priorities. *Science of the Total Environment*, 586, 127–
 141. https://doi.org/10.1016/j.scitotenv.2017.01.190
- 759 Huber, A., Bach, M., & Frede, H. G. (2000). Pollution of surface waters with pesticides in
- Germany: Modeling non-point source inputs. *Agriculture, Ecosystems and Environment*,
 80(3), 191–204. https://doi.org/10.1016/S0167-8809(00)00145-6
- 762 Huerta Lwanga, E., Gertsen, H., Gooren, H., Peters, P., Salánki, T., Van Der Ploeg, M., ...
- 763 Geissen, V. (2016). Microplastics in the Terrestrial Ecosystem: Implications for Lumbricus
- terrestris (Oligochaeta, Lumbricidae). Environmental Science and Technology, 50(5), 2685–
- 765 2691. https://doi.org/10.1021/acs.est.5b05478
- 766 Huerta Lwanga, E., Gertsen, H., Gooren, H., Peters, P., Salánki, T., van der Ploeg, M., ...
- 767 Geissen, V. (2017). Incorporation of microplastics from litter into burrows of Lumbricus
- 768 terrestris. *Environmental Pollution*, 220, 523–531.
- 769 https://doi.org/10.1016/j.envpol.2016.09.096
- 770 Hurley, R. R., & Nizzetto, L. (2018). Fate and occurrence of micro(nano)plastics in soils:
- 771 Knowledge gaps and possible risks. *Current Opinion in Environmental Science and Health*,
- 772 *1*, 6–11. https://doi.org/10.1016/j.coesh.2017.10.006
- 773 Kawecki, D., & Nowack, B. (2019). Polymer-Specific Modeling of the Environmental Emis-
- sions of Seven Commodity Plastics As Macro- and Microplastics. *Environmental Science and Technology*, 53(16), 9664–9676. https://doi.org/10.1021/acs.est.9b02900
- 776 Kay, P., Hiscoe, R., Moberley, I., Bajic, L., & McKenna, N. (2018). Wastewater treatment
- plants as a source of microplastics in river catchments. *Environmental Science and Pollution Research*, 25(20), 20264–20267. https://doi.org/10.1007/s11356-018-2070-7
- 779 Kehres, B. (2019). Kunststoffe in Kompost und Gärprodukten Herkunft Bedeutung Vermei-780 dung. *BGK Information*. Bundesgütegemeinschaft Kompost.
- 781 Knight, L. J., Parker-Jurd, F. N. F., Al-Sid-Cheikh, M., & Thompson, R. C. (2020). Tyre wear
- particles: an abundant yet widely unreported microplastic? *Environmental Science and Pollu- tion Research*. Retrieved from https://link.springer.com/article/10.1007/s11356-020-08187-4
- 784 Koelmans, A. A., Besseling, E., Foekema, E., Kooi, M., Mintenig, S., Ossendorp, B. C., ...
- Scheffer, M. (2017). Risks of Plastic Debris: Unravelling Fact, Opinion, Perception, and Be lief. *Environmental Science and Technology*, *51*(20). https://doi.org/10.1021/acs.est.7b02219
- 787 KrWG (2012). Gesetz zur Förderung der Kreislaufwirtschaft und Sicherung der umweltverträg-
- 788 lichen Bewirtschaftung von Abfällen: Abfallhierarchie. Retrieved from https://www.gesetze-
- 789 im-internet.de/krwg/__6.html
- 790 Kuhn, T., Enders, A., Gaiser, T., Schäfer, D., Srivastava, A. K., & Britz, W. (2020). Coupling
- crop and bio-economic farm modelling to evaluate the revised fertilization regulations in
- 792 Germany. Agricultural Systems, 177(March 2019), 102687.
- 793 https://doi.org/10.1016/j.agsy.2019.102687
- 794 Kuhn, T., Schäfer, D., Holm-Müller, K., & Britz, W. (2019). On-farm compliance costs with the
- 795 EU-Nitrates Directive: A modelling approach for specialized livestock production in north-
- west Germany. *Agricultural Systems*, *173*(March), 233–243.
- 797 https://doi.org/10.1016/j.agsy.2019.02.017
- 798 Lahive, E., Walton, A., Horton, A. A., Spurgeon, D. J., & Svendsen, C. (2019). Microplastic
- particles reduce reproduction in the terrestrial worm Enchytraeus crypticus in a soil exposure.
- 800 Environmental Pollution, 255, 113174. <u>https://doi.org/10.1016/j.envpol.2019.113174</u>

- 801 Lehmann, A., Fitschen, K., & Rillig, M. C. (2019). Abiotic and biotic factors influencing the
- 802 effect of microplastic on soil aggregation. Soil Systems, 3(1), 1–8.
- 803 https://doi.org/10.3390/soilsystems3010021
- 804 LfU (Bayerisches Landesamt für Umwelt) 2020: Klärschlamm Entsorgungssituation. URL:
 805 https://www.lfu.bayern.de/abfall/klaerschlamm/index.htm
- 806 Lusher, A., Hollman, P., & Mandoza-Hill, J. J. (2017). Microplastics in fisheries and aquacul-
- 807 *ture. FAO Fisheries and Aquaculture Technical Paper* (Vol. 615).
- 808 https://doi.org/dmd.105.006999 [pii]\r10.1124/dmd.105.006999
- 809 Marahrens, Stephan; Schmidt, Simone; Frauenstein, Jörg; Mathews, Jeannette; Bussian, Bernd-
- 810 Michael; Penn-Bressel, Gertrude; Utermann, Jens; Glante, Frank; Eberhardt, Einar; Frei-
- 811 bauer, Annette; Bechthold, Michel; Tiemeyer, Bärbel; Wellbrock, Nicole; Böttch, F. (2015).
- 812 Bodenzustand in Deutschland. Umweltbundesamt. Retrieved from
- 813 www.umweltbundesamt.de/publikationen/%0Abodenzustand-in-deutschland
- 814 Melgar-Melgar, R.E, Hall, C.A.S, (2020): Why ecological economics needs to return to its roots:
- The biophysical foundation of socio-economic systems. Ecological Economics 169 (2020)106567
- 817 Ministère de la Transition écologique et solidaire. (2020). Lutte contre la pollution plastique :
- 818 Brune Poirson reçoit les fabricants de machines à laver. Communiqué de presse. 17 février
- 819 2020. Retrieved from https://www.ecologique-solidaire.gouv.fr/lutte-contre-pollution-
- 820 plastique-brune-poirson-recoit-fabricants-machines-laver
- 821 Mintenig, S. M., Int-Veen, I., Löder, M. G. J., Primpke, S., & Gerdts, G. (2017). Identification
- of microplastic in effluents of waste water treatment plants using focal plane array-based mi-
- 823 cro-Fourier-transform infrared imaging. *Water Research*, *108*, 365–372.
- 824 <u>https://doi.org/10.1016/j.watres.2016.11.015</u>
- 825 Möller, J. N., Löder, M. G. J., & Laforsch, C. (2020). Finding Microplastics in Soils: A Review
- of Analytical Methods. Environmental Science and Technology, 54(4), 2078–2090.
- 827 https://doi.org/10.1021/acs.est.9b04618
- 828 Napper, I. E., & Thompson, R. C. (2016). Release of synthetic microplastic plastic fibres from
- domestic washing machines : Effects of fabric type and washing conditions. *Marine Pollution Bulletin.* https://doi.org/10.1016/j.marpolbul.2016.09.025
- 831 Ng, E., Huerta, E., Eldridge, S. M., Johnston, P., Hu, H., Geissen, V., & Chen, D. (2018). An
- 832 overview of microplastic and nanoplastic pollution in agroecosystems. *Science of the Total*
- 833 *Environment*, 627, 1377–1388. https://doi.org/10.1016/j.scitotenv.2018.01.341
- 834 Nizzetto, L., Bussi, G., Futter, M. N., Butterfield, D., & Whitehead, P. G. (2016). A theoretical
- assessment of microplastic transport in river catchments and their retention by soils and river
- 836 sediments. Environ. Sci.: Processes Impacts, 18(8), 1050–1059.
- 837 https://doi.org/10.1039/C6EM00206D
- 838 Okoffo ED, Tscharke BJ, O'Brien JW, O'Brien S, Ribeiro F, Burrows SD, Choi PM, Wang X,
- 839 Mueller JF, Thomas KV. Release of Plastics to Australian Land from Biosolids End-Use.
- 840 Environ Sci Technol. 2020 Dec 1;54(23):15132-15141. doi: 10.1021/acs.est.0c05867. Epub
- 841 2020 Nov 17. PMID: 33200922.
- 842 Pirc, U., Vidmar, M., Mozer, A., & Kržan, A. (2016). Emissions of microplastic fibers from
- 843 microfiber fleece during domestic washing. *Environmental Science and Pollution Research*,
- 844 23(21), 22206–22211. https://doi.org/10.1007/s11356-016-7703-0

- 845 Rillig, M. C., Ingraffia, R., & de Souza Machado, A. A. (2017). Microplastic Incorporation into
- 846 Soil in Agroecosystems. *Frontiers in Plant Science*, 8(October), 8–11.
- 847 https://doi.org/10.3389/fpls.2017.01805
- 848 Rillig, M.C., Lehmann, A., Ryo, M., Bergmann, J. (2019). Shaping Up: Toward Considering the
- Shape and Form of Pollutants. Environmental Science & Technology 53(14), 7925-7926.
 https://doi.org/10.1021/acs.est.9b03520
- 951 Dodriguoz Saijo A. Lourence, I. Deche Sentez, T. A. D. de Caste, I. Durate
- 851 Rodriguez-Seijo, A., Lourenço, J., Rocha-Santos, T. A. P., da Costa, J., Duarte, A. C., Vala, H.,
 852 & Pereira, R. (2017). Histopathological and molecular effects of microplastics in Eisenia an-
- drei Bouché. *Environmental Pollution*, 220, 495–503.
- 854 https://doi.org/10.1016/j.envpol.2016.09.092
- 855 Roskosch, A., & Heidecke, P. (2018). *Klärschlammentsorgung in der Bundesrepublik Deutsch-*856 *land*.
- 857 SAPEA (2019). A Scientific Perspective on Microplastics in Nature and Society. SAPEA,
- 858 Science Advice for Policy by European Academies. Berlin.
- 859 https://doi.org/10.26356/microplastics
- 860 Sattler, C., Kächele, H., & Verch, G. (2007). Assessing the intensity of pesticide use in agricul-
- ture. Agriculture, Ecosystems and Environment, 119(3–4), 299–304.
- 862 <u>https://doi.org/10.1016/j.agee.2006.07.017</u>
- 863 Selonen, S., Dolar, A., Jemec Kokalj, A., Skalar, T., Parramon Dolcet, L., Hurley, R., & van
- 864 Gestel, C. A. M. (2020). Exploring the impacts of plastics in soil The effects of polyester
- textile fibers on soil invertebrates. Science of the Total Environment, 700.
- 866 https://doi.org/10.1016/j.scitotenv.2019.134451
- 867 Scientific Advisory Board on Fertiliser Issues at the Federal Ministry of Food and Agriculture.
- 868 (2015). Application of Organic Fertilisers and Organic Residual Materials in Agriculture.
 869 Retrieved from
- 870 https://www.bmel.de/SharedDocs/Downloads/EN/Ministry/AppOrganicFertilisersOrganicRes
- 871 idualMaterialsAgriculture.pdf?__blob=publicationFile
- 872 Shi, J., Sanganyado, E., Wang, L., Li, P., Li, X., Liu, W. (2020). Organic pollutants in sedimen-
- tary microplastics from eastern Guangdong: Spatial distribution and source identification.
- Ecotoxicology and Environmental Safety, 193. https://doi.org/10.1016/j.ecoenv.2020.110356.
- 875 Sommer, F., Dietze, V., Baum, A., Sauer, J., Gilge, S., Maschowski, C., & Gieré, R. (2018). Tire
- abrasion as a major source of microplastics in the environment. *Aerosol and Air Quality Re-*
- 877 *search*, 18(8), 2014–2028. https://doi.org/10.4209/aaqr.2018.03.0099
- 878 StaLA-BW (Statistischen Landesamt Baden-Württemberg). 2021: Landwirtschaftliche Klär-
- 879 schlammverwertung ist die Ausnahme -- Baden-Württemberg: In der Mehrzahl der Kreise
- 880 wurde der gesamte Klärschlamm verbrannt (<u>Statistischen Landesamt Baden-Württemberg</u>
- 881 (StaLaBW). Pressemitteilung 8/2021. URI: http://www.statistik-
- 882 bw.de/Presse/Pressemitteilungen/2021008
- 883 Statista (2019). Polyester fiber production globally 1975-2017. Uploaded by Garside M., Aug
- 884 15, 2019. Retrieved from https://www.statista.com/statistics/912301/polyester-fiber-
- 885 production-worldwide/
- 886 Statistisches Bundesamt and DWA-Arbeitsgruppe KEK-1.2 "Statistik." (2015). Abwasser und
- 887 Klärschlamm in Deutschland statistische Betrachtungen Teil 2: Klärschlamm, Klärgas, Re-
- chen und Sandfanggut. *Korrespondenz Abwasser, Abfall*, 62(1). Retrieved from
- 889 https://www.destatis.de/DE/Themen/Gesellschaft-

- 890 Umwelt/Umwelt/Wasserwirtschaft/Publikationen/Downloads-Wasserwirtschaft/abwasser-
- 891 klaerschlamm-5322102159004.pdf?__blob=publicationFile&v=5
- 892 Statistisches Bundesamt und DWA-Arbeitsgruppe KEK-1.2 "Statistik." (2014). Abwasser und
- 893 Klärschlamm in Deutschland statistische BetrachtungenTeil 1: Abwasserbehandlung. Kor-
- 894 *respondenz Abwasser, Abfall, 61*(12). Retrieved from
- 895 https://www.destatis.de/DE/Themen/Gesellschaft-
- 896 Umwelt/Umwelt/Wasserwirtschaft/Publikationen/Downloads-Wasserwirtschaft/abwasser-
- 897 klaerschlamm-5322102159004.pdf?__blob=publicationFile&v=5
- 898 Steinmetz, Z., Wollmann, C., Schaefer, M., Buchmann, C., David, J., Tröger, J., ... Schaumann,
- 6. E. (2016). Plastic mulching in agriculture. Trading short-term agronomic benefits for long-
- 900 term soil degradation? *Science of the Total Environment*, 550, 690–705.
- 901 https://doi.org/10.1016/j.scitotenv.2016.01.153
- 902 TASI (1993). Technische Anleitung zur Verwertung, Behandlung und sonstigen Entsorgung von
- 903 Siedlungsabfällen, 1–65. Retrieved from https://www.umwelt-
- 904 online.de/recht/abfall/ta_siedl/taa_ges.htm
- 905 UBA (2020). Bioabfälle. Data-Set: An Bioabfallbehandlungsanlagen angelieferte biologisch
- abbaubare Abfälle. Umweltbundesamt (UBA). Based on: Statistisches Bundesamt (2019):
- 907 Abfälle. Fachserie 19 Umwelt, R. 1 Abfallentsorgung, verschiedene Jahrgänge; Abfallentsor-
- 908 gung . Retrieved from https://www.umweltbundesamt.de/bild/an-
- 909 bioabfallbehandlungsanlagen-angelieferte
- 910 UM-BW (Ministerium für Umwelt, Klima und Energiewirtschaft Baden-Württemberg) (2021):
- 911 Entsorgung Klärschlämme. https://um.baden-wuerttemberg.de/de/umwelt-natur/abfall-und-
- 912 kreislaufwirtschaft/abfallstroeme/abfallarten-und-ihre-entsorgung/klaerschlaemme/
- 913 VAK (2021): Refuse collection vehicles Environment and safety details make the difference.
- 914 Verband der Arbeitsgeräte- und Kommunalfahrzeug-Industrie e.V. (VAK). URL:
- 915 https://www.vak-ev.de/en/members/refuse-collection-vehicles [2021-02-21]
- 916 Wagner, M., Scherer, C., Alvarez-Muñoz, D., Brennholt, N., Bourrain, X., Buchinger, S., ...
- 917 Georg, R. (2014). Microplastics in freshwater ecosystems : what we know and what we need
- 918 to know. *Environmental Sciences Europe 2014*, 26:12, 26(12), 1–9.
- 919 https://doi.org/10.1186/s12302-014-0012-7
- 920 Wang, J., Liu, X., Li, Y., Powell, T., Wang, X., Wang, G., & Zhang, P. (2019). Science of the
- 921 Total Environment Microplastics as contaminants in the soil environment : A mini-review.
- 922 Science of the Total Environment, 691, 848–857.
- 923 https://doi.org/10.1016/j.scitotenv.2019.07.209
- 924 Weithmann, N., Möller, J. N., Löder, M. G. J., Piehl, S., Laforsch, C., & Freitag, R. (2018).
- Organic fertilizer as a vehicle for the entry of microplastic into the environment. *Science Ad- vances*, 4(4), 1–18. https://doi.org/10.1126/sciadv.aap8060
- 927 Weller, S., Fischer, A., Willibald, G., Navé, B., & Kiese, R. (2019). N2O emissions from maize
- 928 production in South-West Germany and evaluation of N2O mitigation potential under single
- 929 and combined inhibitor application. Agriculture, Ecosystems and Environment, 269(February
- 930 2018), 215–223. https://doi.org/10.1016/j.agee.2018.10.004
- 931 Wijesekara, H., Bolan, N. S., Bradney, L., Obadamudalige, N., Seshadri, B., Kunhikrishnan, A.,
- 932 ... Vithanage, M. (2018). Trace element dynamics of biosolids-derived microbeads. *Chemo-*
- 933 *sphere*, 199, 331–339. https://doi.org/10.1016/j.chemosphere.2018.01.166

934 Zambrano, M. C., Pawlak, J. J., Daystar, J., Ankeny, M., & Cheng, J. J. (2019). Microfibers

- generated from the laundering of cotton , rayon and polyester based fabrics and their aquatic
- biodegradation Micro fi bers generated from the laundering of cotton , rayon and polyester
- 937 based fabrics and their aquatic biodegradation. *Marine Pollution Bulletin*, 142(May), 394–
- 938 407. https://doi.org/10.1016/j.marpolbul.2019.02.062
- 939 Zubris, K. A. V., & Richards, B. K. (2005). Synthetic fibers as an indicator of land application
- 940 of sludge. *Environmental Pollution*, *138*(2), 201–211.
- 941 <u>https://doi.org/10.1016/j.envpol.2005.04.013</u>
- 942

- 943 Microplastic pollution in agricultural soils and abatement measures a model-based 944 assessment for Germany
 945
 946 Appendix
- 947

948 Appendix A-1.0: Assumptions for the evolution of microplastic content in sewage sludge

949 Textile fibers are the largest source of microplastics in sewage sludge with a share of 57%. 950 Textile fibers are released into wastewater during the laundering processes in private house-951 holds and industry (Zambrano et al. 2019, Carney Almroth et al. 2017, Cesa et al. 2017, De Falco et al. 2017, Hernandez et al. 2017, Napper and Thompson 2016, Pirc et al. 2016). We 952 953 consider polyester fibers to be representative of all present textile fibers (e.g., polyester, ny-954 lon, acrylic). We assume that the global production of polyester fibers determines the use and subsequent laundering of textiles containing synthetic polymer fibers. Thus, we assume that 955 956 the increase in the production of fibers is indicative of the evolution of these emissions to 957 waste-water.

Polyester production increases exponentially from 3.4 million tons in 1975 up to

53 million tons in 2016 (Fig.1). We fit an exponential model to describe the evolution of theproduction of polyester fibre production and we define the level of the reference year 2016 to

961 represent 100% of microplastic concentration in sewage sludge. Based on this model, we de-

962 rive that in the years before 1990, the microplastic concentration accounted for less than 15%

963 of the microplastic concentration in sewage sludge found in 2016.



Figure 1. Production of polyester fibers worldwide from 1975 to 2017. The missing data is approximated using a linear interpolation. Source: Own computation based on Statista (2019)

965 Appendix A-2.0: Additional information on soil protection and fertilizer regulation

966 Regulations on the disposal of bio-waste protecting the soils from contamination by pollu-

967 tants in bio-solids (i.e., Bundes-Bodenschutzgesetz – BBodSchG, BBodSchG 2017); Bundes-

- 968 Bodenschutz- und Altlastenverordnung –BbodSchV, BBodSchV 2017). Regulations on the
- 969 disposal and recycling of sewage sludge and compost regulate the disposal practices of sew-
- 970 age sludge and compost on agricultural land and define pollutant thresholds (i.e.,
- 971 Klärschlammverordnung AbfKlärV, Bioabfallverordnung BioAbfV, BioAbfV 2017).
- 972 Regulations on *fertilizer* and product certificates define the thresholds for pollutants in ferti-
- 973 lizer (Düngemittelverordnung DüMV, DüMV 2019) and quality certificates for compost).
- 974 Regulations on fertilization specify the good agricultural practice for the application of organ-
- 975 ic fertilizers (Düngeverordnung DüV, DüV 2017).
- 976

978 Appendix A-3.0: Overview on the marginal abatement costs

979 We derive the marginal abatement costs for the different abatement measures based on in-

980 formation researched from different sources. Partially the sources are information on the

981 products provided by the producers (i.e., the filter system for washing machines and the de-

tection system collecting biowaste). Thus, this information might require updates in further
 research work according to future scientific reviews and technological progress. Table A-3.0

984 provides an overview on the abatement costs for different cost (e.g., incineration, nutrients)

and scenarios assumptions (e.g., CO2 price). Appendix A-3.1- to A-3.5 present the computa-

986 tions in more detail.

| | Scenarios | Sludge | Compost ^{a)} |
|---|---------------|--------|-----------------------|
| Thermal recycling | | | |
| Costs for incineration [EUR/kg] | | 0.44 | 1.07 |
| Losses of nutrients [EUR/kg] | | 24 | 65 |
| Costs for CO2 emissions [EUR/kg] | High price | 49 | 195 |
| | Medium price | 24 | 98 |
| | Low price | 12 | 49 |
| Marginal abatement costs [EUR/kg] | High price | 73 | 262 |
| | Medium price | 49 | 164 |
| | Low price | 37 | 115 |
| | Zero price | 24 | 65 |
| Filter System | | | |
| Cost for filter system and replacement[EUR/kg] | | 264 | |
| Detection system | | | |
| Assumption of number of garbage trucks [EUR/kg] | High number | | 19 |
| | Medium number | | 16 |
| | Low number | | 9 |

987 Table A-3.0: Overview on the marginal abatement costs

a) Note that the measures here refer to compost as the organic fertilizer, however, the processors of thermal recycling and the application of a detection system apply to bio-waste

988 Appendix A-3.1: Abatement costs – thermal recycling: incineration

One component of the costs for thermal recycling is additional costs for incineration com-989 990 pared to the land-based disposal. This value is based on data provided for the different ways of disposal for sludge. We assume these costs for sludge to be the option with the highest 991 992 costs (i.e., mono incineration). For compost we derive a lower value by assuming that compost is first dried and then incinerated. The costs for compost might be overestimated. How-993 ever, given the relatively small share of the total costs (see Table A-3.0), we expect that this 994 995 overestimation does not significantly change the magnitude of the computed marginal abate-996 ment costs. We do not consider the costs for the infrastructure or the transport for incinera-997 tion.

- 998
- 999

1000

| | Value | Source |
|--|--------|-------------------|
| Abatement costs | | |
| Thermal recycling of sludge [Eur/t] | 6.84 | Rokosch (2018:64) |
| Land-based disposal [Eur/t] | 4.32 | Rokosch (2018:64) |
| Additional costs for thermal recycling [Eur/t] | 2.52 | Own Computation |
| Sludge applied as fertilizer [M t] | 0.42 | Own Computation |
| Additional costs for thermal recycling [M EUR] | 1.07 | Own Computation |
| | | |
| Abatement | | |
| Sludge applied as fertilizer [M t] | 0.42 | Own Computation |
| Microplastic content [% dry matter] | 0,6% | Own Computation |
| Microplastic abated from sludge [tons] | 2,500 | Own Computation |
| | | |
| Marginal abatement costs | | |
| Marginal abatement costs [EUR/t] | 435.54 | Own Computation |
| Marginal abatement costs [EUR/kg] | 0.435 | Own Computation |

1002Table A-3.1.1: Computation of abatement costs for thermal recycling – incineration of1003sludge

1004Table A-3.1.2: Computation of abatement costs for thermal recycling – incineration of1005biowaste

| | Value | Source |
|---|-------|-------------------|
| Abatement costs | | |
| Thermal recycling of bio-waste [Eur/t] | 5.22 | Rokosch (2018:64) |
| Land-based disposal [Eur/t] | 4.32 | Rokosch (2018:64) |
| Additional costs for thermal recycling [Eur/t] | 0.90 | Own Computation |
| Bio-Waste from industry and households in compost [M t] | 0.80 | Own Computation |
| Additional costs for thermal recycling [M EUR] | 0.73 | Own Computation |
| | | |
| Abatement | | |
| Compost applied in agriculture [M t] | 1.7 | Own Computation |
| Microplastic content [% dry matter] | 0.04% | Own Computation |
| Microplastic abated compost [tons] | 680 | Own Computation |
| | | |
| Marginal abatement costs | | |
| Marginal abatement costs [EUR/t] | 1,070 | Own Computation |
| Marginal abatement costs [EUR/kg] | 1.07 | Own Computation |

1006 Appendix A-3.2: Abatement costs – thermal recycling: Nutrients

1007 To derive the monetary losses caused by the losses of nutrients, which are in case of thermal

1008 recycling no longer available for the agricultural sector, we assume that all nutrients are not

1009 available and need to be substituted by mineral fertilizer and by straw (for the organic mat-

1010 ter). We do not consider that phosphorus can enter the nutrition cycle again after the incinera-

tion of sludge.

| | Bio-waste (households and indus- try) | Bio-Waste (landscaping) | Sludge | Computations based on source | |
|---|--|--------------------------------|--------|---|--|
| Nutrient quantity | | | | | |
| Dry matter [M kg] | 495.9 | 522.9 | 14.7 | WBD (2008), Kehres and Reinhold (2008) | |
| N-content [M kg] | 1.80 | 1.55 | 6.72 | WBD (2008), Kehres and Reinhold (2008) | |
| NH4-N content [M kg] | 0.11 | 0.01 | 1.85 | WBD (2008), Kehres and Reinhold (2008) | |
| P2O5 content [M kg] | 12.60 | 8.98 | 54.83 | WBD (2008), Kehres and Reinhold (2008) | |
| K2O content [M kg] | 21.45 | 17.18 | 2.63 | WBD (2008), Kehres and Reinhold (2008) | |
| Organic matter [humus equivalent (t TM)-1] | 97.09 | 106.91 | 33.60 | WBD (2008), Kehres and Reinhold (2008) | |
| Quantity applied in agricul- ture in compost [M t] | 0.81 | 0.89 | 0.42 | Own computations | |
| Nutrient quantity | | | | | |
| N [Euro/kg] | 0.74 | | | LEL (2016) | |
| N [Euro/kg] | 0.74 | | | LEL (2016) | |
| P2O5 [EUR/kg] | 0.82 | 3.76 | | LEL (2016) | |
| K2O [EUR/kg] | 0.43 | 1.04 | | LEL (2016) | |
| Organic matter [EUR/kg] | 0.24 | | | Kehres and Reinhold (2008) | |
| Abatment costs | | | | | |
| N value [M Euro] | 1.33 | 1.15 | 4.97 | Own computations | |
| NH4-N value [M Euro] | 0.08 | 0.01 | 1.37 | Own computations | |
| P2O5 value [M Euro] | 10.33 | 7.36 | 44.96 | Own computations | |
| K2O value [M Euro] | 9.22 | 7.39 | 1.13 | Own computations | |
| Organic matter value [M Euro] | 23.30 | 25.66 | 8.06 | Own computations | |
| Total nutrient value [M Euro] | 44.27 | 41.56 | 60.50 | Own computation | |
| | | | | | |
| | Con | npost | Sludge | | |
| Marginal abatement costs | | | | | |
| Quantity of compost in agri- culture [M t] | 1 | .7 | 0.42 | Own computation | |
| Microplastic concentration [% dry weight] | 0 | .04 | 0.6 | | |
| Microplastic abated from compost and sludge [t] | 6 | 80 | 2,520 | Own computation | |
| Marginal abatement costs | (| 55 | 24 | Own computation | |

1013Table A-3.2.1: Computation of abatement costs for thermal recycling – costs from losses1014of nutrients from sludge and bio-waste

1017 **Appendix A-3.3: Abatement costs – thermal recycling CO2 emissions**

To derive the costs for CO2 emissions, we compute the content of carbon in bio-waste and 1018

sludge and derive the CO2 emissions which are released during the incineration. We consider 1019

these CO2 emissions from incineration as additional emissions, which are released into the 1020

atmosphere, compared to the land-use disposal, as fertilizer, which fixes the carbon in the 1021 soil.

1022

1024Table A-3.3.1: Computation of abatement costs for thermal recycling – costs for CO21025emissions from sludge and bio-waste

| | Value | Source |
|--|--------|------------------------------|
| Carbon content and CO2-emissions | | |
| C-content in sludge [% dry weight] | 43 | Schuchardt and Vorlop (2010) |
| C-content in bio-waste [% dry weight] | 25 | Schuchardt and Vorlop (2010) |
| C-content in sludge [M t] | 0.18 | Own computation |
| C-content in bio-waste [M t] | 0.20 | Own computation |
| | | |
| CO2 emissions from sludge [M t] | 0.60 | Own computation |
| CO2 emissions from bio-waste [M t] | 0.66 | Own computation |
| | | - |
| CO2 price scenarios | | |
| High CO2 price [EUR/CO2eq] | 200 | Own assumption |
| Medium CO2 price [EUR/CO2eq] | 100 | Own definition |
| Low CO2 price [EUR/CO2eq] | 50 | Own definition |
| | | |
| Emission costs under CO2 price scenarios | | |
| Costs for CO2 from sludge at High CO2 price [M EUR] | 120 | Own computation |
| Costs for CO2 from bio-waste at High CO2 price [M | 133 | Own computation |
| Costs for CO2 from sludge at medium CO2 price [M EUR] | 60 | Own computation |
| Costs for CO2 from bio-waste at medium CO2 price [M EUR] | 66 | Own computation |
| Costs for CO2 from sludge at low CO2 price [M EUR] | 30 | Own computation |
| Costs for CO2 from bio-waste at low CO2 price [M EUR] | 33 | Own computation |
| | | - |
| Abatement | | |
| Quantity sludge applied in agriculture [M t] | 0,42 | Own computation |
| Quantity compost applied in agriculture [M t] | 1,7 | Own computation |
| Concentration of microplastic in sludge [%] | 0,60 | Bertling et al. 2018 |
| Concentration of microplastic in compost [%] | 0,04 | et al. 2018 |
| Microplastic abatement from sludge [t] | 2,520 | Own computation |
| Microplastic abatement from bio-waste [t] | 680 | Own computation |
| | | 1 |
| Marginal abatement costs | | |
| Marginal Abatement Costs for CO2 from sludge at High CO2 price [M FUR] | 48.84 | Own computation |
| Marginal Abatement Costs CO2 from bio-waste at High CO2 price [EUR/kg] | 195.47 | Own computation |
| Marginal Abatement Costs CO2 from sludge at medium CO2 price [M EUR] | 24.42 | Own computation |
| Marginal Abatement Costs CO2 from bio-waste at medi- um CO2 price [M EUR] | 97.74 | Own computation |
| Marginal Abatement Costs CO2 from sludge at low CO2 price [M EUR] | 12.21 | Own computation |
| Marginal Abatement Costs CO2 from bio-waste at low CO2 price [M EUR] | 48.87 | Own computation |
| | | |

1027 We base our assumptions to simulate a filter system for reducing microplastic in sewage

sludge on the system "PlanetCare filters" which filters at a rate of 80% of textile fibres (Stef-

1029 fen 2019). We assume that such filters are installed in every private washing machine in

1030 German households and in industrial washing. For the computation of costs we consider only 1031 the private households.

| Source of microplastic in wastewater | MP before filter | Share of MP | Filter rate | MP with filter | Share with filtering |
|--|---------------------|----------------|-------------|-------------------|----------------------------|
| | g/(cap*year) | [%] | [%] | g/(cap*year) | [%] |
| Textile fibers | 77 | 57 | 80 | 15 | 11 |
| Cleaning of con- tainers | 23 | 17 | 0 | 23 | 17 |
| Cosmetics | 19 | 14 | 0 | 19 | 14 |
| Abrasive in pipes | 12 | 9 | 0 | 12 | 9 |
| Cleaning products | 5 | 3 | 0 | 5 | 3 |
| Total | 135 | 100 | 45 | 74 | 55 |

Table A-3.4.1: Computation of abatement by filter systems

1033

| Value | Source |
|-------|--|
| | |
| 40.8 | Destatis (2021) |
| 93.9 | Tenzer (2020) |
| 38.3 | Own computation |
| 2 | Own assumption |
| 104 | Own computation |
| 3.98 | Own computation |
| | |
| 35 | Steffen (2019) |
| 0.8 | Steffen (2019) |
| 20 | Steffen (2019) |
| 0.04 | Own computation |
| | |
| 1.34 | Own computation |
| 10 | Own assumption oriented to the depreciation time fo washing machines |
| 134.0 | Own computation |
| 159.3 | Own computation |
| 293.2 | Own computation |
| | |
| 0.42 | Own computation |
| 0.6 | Own computation based on Bertling et al. (2019) |
| 2,520 | Own computation |
| 45 | Own computation based on Steffen A.D. (2019) an Bertling et al (2019) |
| 1,112 | Own computation |
| 264 | Own computation |
| | Value 40.8 93.9 38.3 2 104 3.98 - 35 0.8 20 0.04 - 1.34 10 134.0 159.3 293.2 0.42 0.6 2,520 45 1,112 264 |

1035 Table A-3.4.2: Computation of the abatement costs by filter systems

1038 Appendix A-3.5: Abatement costs – detection system

1039 A-3.5.1 Estimation of share of bio-waste of total waste

- 1040 We estimate the shares of quantities based on the German city Duesseldorf for which the
- number of garbage trucks is available. We compute that 20% of the waste collected from
- 1042 households is bio-waste, 76% is non-recycling waste and 4% is recycling paper.

| | Value | Source |
|------------------------------------|---------|--------------------|
| Waste non-recycle [t] | 145,388 | AWISTA GmbH (2019) |
| Biowaste in Duesseldorf [t] | 39,104 | AWISTA GmbH (2019) |
| Paper recycling [t] | 7,339 | AWISTA GmbH (2019) |
| Waste total [t] | 191,831 | AWISTA GmbH (2019) |
| | | |
| Share of waste non-recycle [%] | 76 | Own computations |
| Share bio-waste in Duesseldorf [%] | 20 | Own computations |
| Share paper recycling [%] | 4 | Own computations |
| Share waste total [%] | 100 | Own computations |

1043 Table A-3.5.1: Computation of shares of waste

1044 -A-3.5.1 Estimation of the number of garbage trucks used for the collection of bio-waste

1045 We asked three different institutions for the information on the number of garbage trucks1046 used for bio-waste collection either for Germany (Federal Motor Transport Authority 2020,

1047 DESTATIS 2020) or at the regional level (LANUV 2020). None of these institutions could

1048 provide data on number of garbage trucks. The survey of single disposal companies or ex-

1049 perts could have provided more information. However, for this study we derived three differ-1050 ent values for the number of garbage trucks used for bio-waste collection by using three dif-

1050 ferent approaches: (i) based on average bio-waste load in Duesseldorf; (ii) based on the num-

1052 ber of garbage trucks in Germany, and (iii) estimating a value for sensitivity analysis.

- 1053 (i) Using exemplary values for the German city Duesseldorf we compute, based on the quantities of waste, the share of bio-waste of total waste at 20%. We apply this share to the num-1054 ber of garbage trucks available for Duesseldorf and compute the annual average load of one 1055 1056 garbage truck. We apply this average load to the whole quantity of bio-waste collected in Germany and estimate around 1,400 garbage trucks collecting bio-waste in Germany. (ii) 1057 Using the number of total garbage trucks estimated at 12,000 (VAK 2019) we apply the share 1058 1059 computed with (i) at 20% and obtain around 2,500 garbage trucks. (iii) As arbitrary estimator we define 3,000 garbage trucks for bio-waste collection, which would represent 25% of the 1060 total of 12,000 (VAK 2019. 1061
- 1062 We use these three derived values as data to estimate the cost for the detection system "DS
- 1063 2010" (Maier und Fabris GmbH 2021a) by applying the annual costs of 3,950 EUR/garbage
- truck (based on Maier 2011). We assume an abatement effect of 90% of reduction of plasticin bio-waste. This estimation is based on a report on application of the detection system in
- 1065 In bio-waste. This estimation is based on a report on application of the detection system in 1066 different communities or regions in Burgenlandkreis (Otto 2018), Wien Maier (2011),
- 1067 Euskirchen (Mehren 2015), Main-Tauber-Kreis (von Brandenstein 2019). For more exam-
- 1068 ples, see Maier und Fabris GmbH (2021b).
- 1069 In our costs we do not consider the reduction of costs for the improved quality of the com-
- 1070 post. Considering this reduction would decrease the abatement cost.
- 1071

Table A-3.5.2: Computation of fitted number of garbage trucks for bio-waste collection with three estimators

| | Value | Source | |
|--|--------|---|--|
| Estimator 1: Based on average bio-waste load in Duesseldorf | | | |
| Total number of garbage trucks in Duesseldorf [#] | 55 | AWISTA GmbH (2019) | |
| | | | |
| Number of garbage trucks for bio-waste derived by the share of bio-waste (20%) [#] | 11 | AWISTA GmbH (2019) | |
| Bio-waste in Duesseldorf [t] | 39,104 | AWISTA GmbH (2019) | |
| Bio-waste per garbage truck in Duesseldorf [t] | 3,488 | Own computation | |
| Bio-waste in Germany [M t] | 4.903 | Statistische Ämter des Bundes und der Länder (2019) | |
| Estimated number of garbage trucks collecting bio-waste (computed by Biowaste in Germany / Biowaste per garbage truck in Duesseldorf) [#] | 1,400 | Own computation | |
| | | | |
| Estimator 2: Based on number of Garbage trucks in Germany | | | |
| Number of garbage trucks total in Germany [#] | 12,000 | VAK (2021) | |
| Share biowaste in Duesseldorf [%] | 20 | Own computations | |
| Number of garbage trucks for biowaste derived by the share of biowaste (20%) [#] | 2,400 | Own computation | |
| | | | |
| Estimator 3: Sensitivity Analysis | | | |
| Number of garbage trucks for biowaste as sensitivity analysis | 3,000 | Own assumption | |

Table A-3.5.2: Computation of fitted number of garbage trucks for bio-waste collection with three estimators.

| | Fitted out number of gar- bage trucks | | | Source |
|---|--|--------|-------|-----------------------------|
| | Low | Medium | High | |
| Estimated number of garbage trucks collecting bio-waste | 1,400 | 2,400 | 3,000 | |
| Cost per day per garbage truck [EUR] | | 15.19 | | Maier (2011) |
| Number of working days (52weeks*5days) | | 260 | | Own assump- tion |
| Cost for detection system per year and garbage truck [EUR/year] | | 3,950 | | Own compu- tation |
| Cost for detection system per year [M EUR/year] | 5.6 | 9.7 | 11.9 | Own compu- tation |
| Microplastic from compost [t] | | 680 | | Own compu- tation |
| Reduction by detection system [%] | | 90 | | Derived from Otto (2018) |
| Microplastic abatement [t] | | 612 | | Own compu- tation |
| Marginal abatement costs [EUR/kg] | 9.11 | 15.85 | 19.43 | Own compu- tation |

1078 Appendix A-4.0: Sensitivity analysis on soil density

1079 Figure A-4.0 and Table Annex A-4.0 present the microplastic concentrations from sludge and 1080 compost in soils of different density. The results show that in the years after 2020 the concentrations differ significantly between soils of density of 1.2 g/cm+3 and 1.4 g/cm+3. The dif-1081 ference accounts for sludge for about 7 mg/kg and for compost for about 5 mg/kg. This dif-1082 1083 ference increases for consecutive years. The density of light sandy soils on which sludge and compost are applied to increase the organic matter can vary from 1.2 to 1.7 g/cm+3. Thus, in 1084 extreme cases, the simulated concentration assuming a soil density of 1.2 g/cm+3 can be 1085 1086 overestimated significant by 30 to 50%.





Notes: Sludge 1.2 g/cm+3 = microplastic from sludge in soils with density of 1.2 g/cm+3; sludge 1.4 g/cm+3 = microplastic from sludge in soils with density of 1.6 g/cm+3; sludge 1.8 g/cm+3 = microplastic from sludge in soils with density of 1.8 g/cm+3; compost 1.2 g/cm+3 = microplastic from compost in soils with density of 1.2 g/cm+3; compost 1.4 g/cm+3 = microplastic from compost in soils with density of 1.4 g/cm+3; compost 1.4 g/cm+3 = microplastic from compost in soils with density of 1.4 g/cm+3; compost 1.4 g/cm+3 = microplastic from compost in soils with density of 1.4 g/cm+3; compost 1.4 g/cm+3 = microplastic from compost in soils with density of 1.4 g/cm+3; compost 1.6 g/cm+3 = microplastic from compost in soils with density of 1.6 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.6 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; compost 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3 = microplastic from compost in soils with density of 1.8 g/cm+3; by 30 to 50% (see Table A-4.1).

| <u> </u> | Soil density: 1.2 g/cm+3 | |
|----------|-----------------------------|---------|-----------------------------|---------|-----------------------------|---------|-----------------------------|---------|
| | Sludge | Compost | Sludge | Compost | Sludge | Compost | Sludge | Compost |
| 1990 | 3.2 | 1.1 | 2.7 | 0.9 | 2.4 | 0.8 | 2.1 | 0.7 |
| 1995 | 6.2 | 6.4 | 5.3 | 5.5 | 4.7 | 4.8 | 4.2 | 4.3 |
| 2000 | 10.5 | 11.7 | 9.0 | 10.1 | 7.9 | 8.8 | 7.0 | 7.8 |
| 2005 | 16.5 | 17.1 | 14.2 | 14.6 | 12.4 | 12.8 | 11.0 | 11.4 |
| 2010 | 25.0 | 22.4 | 21.4 | 19.2 | 18.7 | 16.8 | 16.6 | 14.9 |
| 2015 | 36.8 | 27.7 | 31.5 | 23.8 | 27.6 | 20.8 | 24.5 | 18.5 |
| 2020 | 50.7 | 33.1 | 43.4 | 28.3 | 38.0 | 24.8 | 33.8 | 22.0 |
| 2025 | 64.6 | 38.4 | 55.4 | 32.9 | 48.5 | 28.8 | 43.1 | 25.6 |
| 2030 | 78.5 | 43.7 | 67.3 | 37.5 | 58.9 | 32.8 | 52.4 | 29.1 |
| 2035 | 92.5 | 49.0 | 79.3 | 42.0 | 69.4 | 36.8 | 61.7 | 32.7 |
| 2040 | 106.4 | 54.4 | 91.2 | 46.6 | 79.8 | 40.8 | 70.9 | 36.3 |
| 2045 | 120.3 | 59.7 | 103.1 | 51.2 | 90.3 | 44.8 | 80.2 | 39.8 |
| 2050 | 134.3 | 65.0 | 115.1 | 55.7 | 100.7 | 48.8 | 89.5 | 43.4 |
| 2055 | 148.2 | 70.4 | 127.0 | 60.3 | 111.1 | 52.8 | 98.8 | 46.9 |
| 2060 | 162.1 | 75.7 | 139.0 | 64.9 | 121.6 | 56.8 | 108.1 | 50.5 |

1089Table A-4.1: Concentrations simulated for selected year and different soil densities in1090mg/kg.

1093 Literature -- Appendix

- AWISTA GmbH (2019): Düsseldorf bleibt sauber. Buisness report of the AWISTA GmbH
 2018. URL: <u>https://www.awista.de/wp-</u>
 content/uploads/2019/08/Gesch%C3%A4ftsbericht-2018.pdf
- 1097 DESTATIS (2020): Anzahl Mülltransportwagen in D _ Statistisches Bundesamt, GZ 465555
 1098 _ 668635. Personal communication via email with Erxleben, C. date: 27.10.2020
- 1099 Destatis (2021): Haushalte und Familien -- Daten zur Entwicklung der Zahl der Privathaus 1100 halte nach Haushaltsgröße für die Jahre 2015 bis 2035
- Entwicklung der Zahl der Privathaushalte nach Haushaltsgröße bis 2035 (Trendvariante)
 Deutschland. Statistisches Bundesamt (Destatis). Stand 28. Februar 2017
- 1103 Federal Motor Transport Authority 2020: AW: Statisti-
- 1104 ken_Verkehr_deutscher_Lastkraftfahrzeuge // AZ: 321-130/10476-20. Personal communication via email with Schleunes E. date 12.11.2020.
- 1106https://www.destatis.de/DE/Themen/Gesellschaft-Umwelt/Bevoelkerung/Haushalte-1107Familien/Tabellen/vorausberechnung-haushalte.html [2021-02-21]
- 1108 Kehres B, Reinhold J (2008): Monetäre Bewertung der Humusreproduktion von Kompost
 1109 und Gärrückständen. H&K 2/08, 20 ff,
- LANUV (2020) WG Anzahl der landesweiten Anzahl der Mülltransportwagen für Biomüll 'Holst, Heike' (Heike.Holst@lanuv.nrw.de) 2020-11-18 1131. Personal communication via email with Holst, H. date: 18.11.2020
- 1113 LEL (2016): Düngerpreis P, Vers. 2.4 11/2. LEL Schwäbisch Gmünd.
- Maier HJ (2011): Die Kommunen sollten mehr tun für den Klimaschutz. Die Bürger sparen dabei noch Müll-Gebühren! September 2019/ UmweltJournal-Wien. Page 11. URL: https://www.maier-fabris.de/images/Umwelt-Journal-Wien-09-2019.pdf
- Maier und Fabris GmbH (2021a): Detection System " DS 2010 " (Product description). URL:
 <u>https://www.maier-fabris.de/images/Prosp-0519-2-engl.pdf</u>[2021-02-22]
- Maier und Fabris GmbH (2021b). Homepage Maier and Fabris GmbH.
 <u>URL:https://www.maier-fabris.de/pages/frame_produkt.htm</u> [021-02-22]
- Mehren L (2015): Erfahrungsbericht über den Einsatz des Detektionssystems im Landkreis
 Euskirchen. URL: <u>https://www.maier-fabris.de/images/Vortrag_Euskirchen_2015.pdf</u>
- Otto H. (2018): "Aktion Biotonne" im Burgenlandkreis: Maßnahmen zur Fremdstoffreduzie rung. Presentation. URL: <u>https://www.maier-fabris.de/images/Erfahrungsbericht-</u>
 <u>Burgenlandkreis.pdf</u>,
- Schuchardt F., Vorlop K-D (2010): Abschätzung des Aufkommens an Kohlenstoff in Bio masse-Reststoffen in Deutschland für eine Verwertung über Hydrothermale
- 1128 Carbonisierung (HTC) und Einbringung von HTC-Kohle in den Boden.
- 1129Landbauforschung vTI Agriculture and Forestry Research 4 2010 (60) 205-212. URL:1130https://d-nb.info/1009077295/34
- Statistische Ämter des Bundes und der Länder (2019): Aufkommen an Haushaltsabfällen.
 Statistikportal. URL: <u>https://www.statistikportal.de/de/aufkommen-haushaltsabfaellen</u>

Steffen A.D. (2019): This Is The First Ever Microplastics Filter For Washing Machines! www.intelligentliving.co. URL: <u>https://www.intelligentliving.co/microplastics-filter-</u> <u>washing-machines/</u> [2021-02-21]

- Tenzer F. (2020): Anteil der privaten Haushalte in Deutschland mit Waschmaschine bis 2020.
 Pulished by Tenzer, F. (10.11.2020) on www. Statista.com. URL:
 <u>https://de.statista.com/statistik/daten/studie/516859/umfrage/private-haushalte-in-</u>
 <u>deutschland-mit-waschmaschine/</u> [2021-02-21]
- 1140 VAK (2021): Refuse collection vehicles Environment and safety details make the differ 1141 ence. Verband der Arbeitsgeräte- und Kommunalfahrzeug-Industrie e.V. (VAK). URL:
 1142 <u>https://www.vak-ev.de/en/members/refuse-collection-vehicles</u> [2021-02-21]
- von Brandenstein, H (2019): Biomüll-Qualität ist deutlich gestiegen. Fränkische Nachrichten.
 Samstag15.JUNI2019/Seite17. URL: <u>https://www.maier-</u>
 fabris.de/images/FraenkischeNachrichten15062019.pdf
- WBD (2015): Application of Organic Fertilisers and Organic Residual Materials in Agricul ture Position paper of the Scientifc Advisory Board on Fertiliser Issues. Scientifc Advisory Board on Fertiliser Issues at the Federal Ministry of Food and Agriculture (WBD):
 s:24/25; Tabelle A1