

# Huawei HCIA-IoT v. 2.5 Evaluation Questions

#### Michel Bakni

#### ▶ To cite this version:

Michel Bakni. Huawei HCIA-IoT v. 2.5 Evaluation Questions. Engineering school. Huawei HCIA-IoT v. 2.5, Bidart, France. 2021, pp.77. hal-03189245v1

# HAL Id: hal-03189245 https://hal.science/hal-03189245v1

Submitted on 2 Apr 2021 (v1), last revised 10 Sep 2023 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



# Huawei HCIA-IoT v. 2.5 Evaluation Questions

March 2021 Michel BAKNI Author: Michel BAKNI Editor: Sandra HANBO Version: 1.0, 2021

DOI: 10.6084/m9.figshare.14336687

## **Copyright notice**

This work is licensed under Creative Commons Attribution 4.0 International (CC BY 4.0) You are free to:

**Share** — copy and redistribute the material in any medium or format

**Adapt** — remix, transform, and build upon the material

for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms:

**Attribution** — You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.

**No additional restrictions** — You may not apply legal terms or technological measures that legally restrict others from doing anything the license permits.

Read the text of the full license Creative Commons Attribution 4.0 International on the following link: <a href="https://creativecommons.org/licenses/by/4.0/legalcode">https://creativecommons.org/licenses/by/4.0/legalcode</a>





#### **Preface**

This document is oriented towards students preparing for the exam of Huawei Certified Information and communication technology Associate (HCIA-IoT) v. 2.5. The main idea of this booklet is to provide students with an evaluation tool for their understanding of the course content. This booklet is not an exam dump, and it should never be handled like that.

HCIA-IoT is a course prepared provided by Huawei. It focuses on the Internet of things explaining the technologies used to support it, such as 5G and NB-IoT. It also introduces Huawei products and solutions in this domain.

The structure of this document follows the chapters of the course. For each chapter, there are two groups of questions: True or false and multiple choices questions. Additionally, the booklet includes a table for abbreviations used in this course in alphabetical order.

I recommend the following steps to maximize the benefits of this document (Figure 1):

- 1. Read the targeted chapter from the course support.
- 2. Try to answer the questions associated with the targeted chapter in this document.
  - a. If you succeed (more than 90% of answers are correct), go forward for the next chapter.
  - b. If not, go backward and study the targeted chapter with more careful.




Figure 1: Flow chart explaining a proposed mechanism to address this booklet.

I had the chance to work with Huawei in France in February and March 2021. In this period, I prepared this document. Unfortunately, the spread of COVID-19 was at its highest rates. The course had to follow very strict instructions of the local authorities. However, we were able to touch physical materials and develop several labs using IoT Huawei developer kit.

**Paris** 

15-03-2021

Attention: Studying this document only is not enough to pass the official exam.

## **Contents at a Glance**

Chapter 1.	IoT development history and Overview	5		
Chapter 2.	IoT Industry Applications and Solutions	10		
Chapter 3.	IoT Security Technologies	15		
Chapter 4.	Overview of Common IoT Communications Technologies	20		
Chapter 5.	NB-IoT Communication Technologies and Solutions	25		
Chapter 6.	5G Communications Technologies and Solutions	30		
Chapter 7.	Huawei IoT Gateways (Industrial + Home)	35		
Chapter 8.	IoT Platform	40		
Chapter 9.	IoT Platform Secondary Development	45		
Chapter 10.	IoT OS	50		
Chapter 11.	Sensing Layer Development	54		
Chapter 12.	AT Commands for Communication Modules	59		
Correct Answ	Correct Answers			
Abbriviations	S	68		

## Chapter 1. IoT development history and Overview

- 1. The Trojan room coffee pot of the computer laboratory in Cambridge University is an example of an IoT solution.
- 2. ITU referred to the IoT concept at the world summit on the information society in 2005.
- 3. NB-IoT is developed for 5G technologies.
- 4. The first 3GPP standard for the 5G is Release-16.
- 5. VR glasses, body fat scales, smart locks, and smart speakers are examples of industry-related IoT products.
- 6. Smart agriculture is an example of industry-related IoT products.
- 7. IoT is an Internet where all things are interconnected.
- 8. IoT requires moving from the internet of things to the internet of people.
- 9. IoT model includes 4 layers.
- 10. In the IoT model, the platform layer collects Information and process signals.
- 11. Huawei IoT solution architecture is 1+2+1.
- 12. Huawei cloud IoT platform is open, pre-integrated and access-dependent.
- 13. Bluetooth is an example of communication protocols used by IoT applications.
- 14. Fully open smart ONT requires a bit rate up to 1 Gbit/s.
- 15. In the IoT model, device management and security maintenance are performed by the platform.
- 16. Huawei IoT Solution Architecture is 1+2+1 means: one IoT access method, two platforms, and one IoT operating system.
- 17. Huawei LiteOS features low power consumption, small size, and quick response.
- 18. NB-IoT stands for NearBand Internet of Things.
- 19. Huawei LiteOS features basic kernel size less than 20 kB.
- 20. 5G Architecture supports both NFV and SDN.

B.	Choose the correct answer, there is only of	ne correct answer for each question:
1.	Which of the following is considered the old	dest known mention of IoT:
	A. Bill Gates Book (the road ahead)	B. ITU internet reports.
	C. Trojan room coffee pot	D. Hannover messe
2.	In which release of the 3GPP the NB-IoT s	tandard was frozen?
	A. 13	B. 14
	C. 15	D. 16
3.	Which of the following chinese mobile oper commercially used?	erator(s) was(were) the first 5G network(s)
	A. China Telecom	B. China Mobile
	C. China Unicom	D. All of them
4.	In which quarter of 2019 the 5G network commercial use?	orks were employed in china for public
	A. First	B. Second
	C. Third	D. Fourth
5.	Development of IoT industry is driven by:	
	A. Consumers	B. Policies
	C. Industry	D. All of them
6.	One of the following is not a policy-driven	application of the IoT industry:
	A. Firefighting	B. Smart agriculture
	C. Parking	D. Streetlightning

7.	One of the following is consumption-driven application of the IoT industry:			
	A.	Smart speaker	B.	Public utilities
	C.	Security system integration	D.	Internet of Vehicles
8.	W	hich of the following is industry-driven appli	catio	on of the IoT industry?
	A.	Smart agriculture	B.	Smart logistics
	C.	IoV	D.	All of them
9.	Fre	om 1999 to 2013, the term "connected objects	" w	as used to describe:
	A.	Smart wearable devices	B.	Smart home utilities
	C.	Things in the radio frequency	D.	Industrial devices and
		domain		applications
10.	Но	w many layers are there in the IoT model?		
	A.	2	B.	3
	C.	4	D.	5
11.		nich of the following layer of the IoT model peraction services?	orov	ide data presentation and costumer
	A.	Application layer	B.	Platform layer
	C.	Network layer	D.	Device layer
12.	On	e of the following is not a component of the p	olatf	form layer in the IoT model:
	A.	Cloud data center	B.	Operations platform
	C.	IoT gateways	D.	Security maintenance

13.	Wł	nich of the following is a network layer techn	olog	gy in the IoT model?
	A.	GPRS	B.	NB-IoT
	C.	4G	D.	All of them
14.	On	e of the following is not an example of an Io	Гар	pplications:
	A.	Smart home	В.	Huawei LiteOS
	C.	Safe city	D.	IoV
15.		nich of the following solutions for the IoT awei?	' me	odel architecture are proposed by
	A.	1+2+1	B.	2+1+1
	C.	2+1+2	D.	1+1+2
16.	Th	e adapted Huawei IoT architecture includes:		
	A.	Two IoT platform, two access methods and one IoT operating system	B.	One IoT platform, two access methods and one IoT operating system
	C.	One IoT platform, two access methods and two IoT operating system	D.	None of them
17.		e of the following is not an example of proution:	toco	ols used in the NB-IoT end-to-end
	A.	НТТР	B.	MQTT
	C.	ICMP	D.	CoAP

18.	8. One of the following is not an example of devices used in the NB-IoT end-to-end solution:		
	A. MCUs	B. Modules	
	C. NB-IoT chipsets	D. HTTP	
19.	Which of the following connectivity is required	in a smart home using ONT technology?	
	A. 1 Mbit/s	B. 1 Gbit/s	
	C. 1 Tbit/s	D. None of them	
20.	Huawei cloud IoT platform is:		
	A. Open	B. Pre-integrated	
	C. Service-oriented	D. All of them	

## **Chapter 2.** IoT Industry Applications and Solutions

- 1. Traffic management is a common problem in modern cities.
- 2. Environmental sanitation is not included in the city management scenario.
- 3. Device management in the smart city solution includes: 2G/3G/4G, fixed and NB-IoT accesses.
- 4. Smart streetlamp services do not include charging piles.
- 5. Smart manhole cover solution can provide real-time monitoring.
- 6. Security management is a common problem in campus management.
- 7. Power consumption management is not covered in the smart campus solution.
- 8. In the campus solution, facial recognition can be used to manage visitors.
- NB-IoT is a common technology used to manage security in the smart campus solution.
- 10. AMI stands for Advanced Metering Interface.
- 11. Randomness is a character in the desired AMI solution.
- 12. V2X includes V2N, V2I, V2P, and V2V.
- 13. DRIS consists of V2X server and V2X edge.
- 14. DRIS and HUD can be integrated in an IoV solution.
- 15. DRIS stands for Driver Road Infrastructure Service.
- 16. It is not necessary in an ICT-based production system of smart manufacturing to include intelligent sensing technologies.
- 17. In 5IABCDE, E stands for Encryption.
- 18. 5IABCDE includes five emerging technologies.
- 19. Block chain is included in 5IABCDE.
- 20. AIoT stands for Advanced Internet of Things.

B.	. Check the correct answer, there is <u>only one correct answer</u> for each question:			
1.	. One of the following is not a common problem in modern cities:			
	A. Visitor management	B. Parking management		
	C. Street lamp management	D. Manhole cover management		
2.	Smart city solution includes:			
	A. 2G/3G/4G and fixed access	B. NB-IoT access		
	C. None of them	D. Both of them		
3.	One of the following is not in the application	on layer for smart firefighter solution:		
	A. Alarm handling	B. Remote muting		
	C. Traffic broadcast	D. Device self-check		
4.	One of the following is not used in the sma	rt parking solution:		
	A. NB-IoT modules	B. Huawei IoT platform		
	C. IoT agent	D. RRU+Antenna		
5.	Which of the following protocol(s) is(are) fighting solution?	used in the network layer in the smart fire		
	A. SNMP	В. НТТР		
	C. CoAP	D. All of them		
6.	Which of the following is a common proble	em in an traditional campus?		
	A. Lack of sensing	B. Visitor management		
	C. None of them	D. Both of them		

7.	In a smart campus solution, facial recognition uses one of the following:			
	A.	Video- assisted alarm acknowledgment	В.	Intelligent pre-event warning
	C.	System linkage handling	D.	Blacklist-based surveillance
8.		ne of the following is not used in the power of the solution:	cons	sumption management in the smart
	A.	Temperature/humidity sensor	B.	Geo-magnetic vehicle detector
	C.	Intelligent switch/motion sensor	D.	Smart electricity/water meter
9.	Ele	ectrical power supply system does not include	<b>:</b> :	
	A.	Power generation	B.	Power transformation
	C.	Power distribution	D.	Power storage
10.	Wł	nich of the following is(are) a character(s) of	trad	itional grid?
	A.	Simultaneity	B.	Integration
	C.	Integration	D.	All of them
11.	In	the AMI solution, one of the following is not	use	d in the field area network:
	A.	LTE	B.	Microwave
	C.	Zigbee	D.	Wireless LAN
12.	In	the AMI solution, NAN stands for:		
	A.	Node Area Network	B.	Neighborhood Area Network
	C.	NB-IoT Area Network	D.	None of them

13. One of the following is not used as a device in the smart AMI solution:		
A. Three-phase prepaid meter	B. Wireless smoke sensor	
C. Single-phase prepaid meter	D. Data concentrator unit	
14. Which of the following is not a connection name	e in IoV environment?	
A. V2V	B. V2N	
C. V2I	D. V2E	
15. One of the following is not considered as a vehi	cle device in IoV solution:	
A. T-Box	B. Rearview mirror	
C. Cabinet meter	D. Vehicle-mounted screen	
16. Which of the following is not a part of the seven	n-emerging technologies?	
A. 4G	B. 5G	
C. IoT	D. AI	
17. "B" in 5IABCDE stands for:		
A. Big data	B. Block chain	
C. 5G	D. None of them	
18. AI does not include:		
A. Speech recognition	B. Image recognition	
C. Edge computing	D. Natural language processing	
19. AIoT includes:		
A. Edge computing	B. Image recognition	
C. Block chain technologies	D. Hybrid networking	

20. Digital twin includes:

A. Physical products

B. Virtual products

C. Both of them

D. None of them

## **Chapter 3. IoT Security Technologies**

- 1. The Tesla incident is classified as a DDoS attack.
- 2. In the Tesla incident, the network layer of the IoT architecture was attacked.
- 3. DDoS stands for Distributed Denial of Service.
- 4. Data interception and tampering is not considered as a security threat.
- 5. API attacks are categorized as a pipe threat.
- 6. Pipe detection, cloud-cloud synergy and trusted device authentication are effective means to resolve security threats.
- 7. Huawei IoT security system provides security to data, access and devices.
- 8. In the Huawei IoT security system, digital signature process includes the use of RSA2048 or SHA256.
- 9. In the Huawei IoT security system, the use of digital signature includes generation of public and private keys.
- 10. In the Huawei IoT security system, the signature verification is provided by the terminal device.
- 11. During the last two decades, the attackers' capability level has increased.
- 12. Password guessing is an example of IoT attacks.
- 13. DoS, phishing and encryption are examples of network attacks.
- 14. In recent days, requirements on attackers' capabilities are low.
- 15. As requirements on attackers' capabilities are decreasing, attackers' capability level is decreasing as well.
- 16. AI-based attacks and ransomware viruses are examples of attack tools developed in the 2010s.
- 17. 3T+1M means 3 security tires and 1 management layer.
- 18. Anti-DDoS and signaling storms are part of the pipe security.
- 19. A priority-based system is an anti-DDoS tool.
- 20. The two-factor authentication can include: certificate and password.

C. None of them

<b>5.</b>	. Check the correct answer, there is <u>only one correct answer</u> for each question:				
1.	In Tesla incident, the hackers attack the:				
	A. Inter-vehicles connections	B.	In-vehicle system		
	C. Vehicle-gateway interconnection	D.	All of them		
2.	In the context of Mirai malware attack, "Zombio	es" 1	refer to:		
	A. Network cameras	B.	Digital video recorders		
	C. Intelligent routers	D.	All of them		
3.	One of the following is not categorized as applic	catio	on threat for the LPWA security:		
	A. Invalid security access control	B.	Incorrect security configurations		
	C. API attacks	D.	Sensitive information leakage		
4.	Which of the following is not a security threat to	the	e IoV system?		
	A. DDoS attacks/signaling storms	B.	API attacks		
	C. T-Box communication security threats	D.	Bluetooth vulnerabilities		
5.	Trust key attacks are LPWA security threat, they	fill	into one of the following category:		
	A. Application	B.	Platform		
	C. Network (pipe)	D.	Device		
6.	Which of the following is device security threat	?			
	A. Unencrypted transmission	В.	Checking of damaged devices		

D. Both of them

7.		ring the last two decades, as the network oblisticated, the requirements on attackers' cap		_
	A.	Raised up	B.	Stayed the same
	C.	Dropped down	D.	Become also sophisticated
8.	Wł	nich of the following tools is(are) used to atta	ck I	oT networks?
	A.	APT attacks	B.	AI-based attacks
	C.	Ransomware viruses	D.	All of them
9.	Wł	nich of the following architecture does Huawe	ei Io	T security adopt?
	A.	3T+1M	B.	1T+3M
	C.	3T+2M	D.	3T+3M
10.	Wł	nich of the following is(are) included in the Io	oT s	ecurity solution?
	A.	Data security	B.	Access security
	C.	Device security	D.	All of them
11.	On	e of the following is not included in the Huav	wei ]	IoT defense of big data security:
	A.	Machine learning	B.	Anti-DDoS
	C.	Threat response	D.	Attack detection
12.	Im	plementation of FOTA digital signature inclu	des	using of the following algorithm(s):
	A.	RSA2048	B.	SHA256
	C.	Both of them	D.	None of them

13.	The digital signature operation includes the use	of:	
	A. Two public keys	В.	Two private keys
	C. One public and one private keys	D.	Only a private key
14.	Pipe security mechanism for IoT solution include	des:	
	A. Anti-DDoS	В.	Firmware validity
	C. Both of them	D.	None of them
15.	A priority-based mechanism against anti-DDoS	inc	ludes:
	A. Congestion management	В.	Delay access mechanism
	C. Both of them	D.	None of them
16.	In the digital signature algorithm, the signature	crea	tion is done at the:
	A. Core of the network	В.	Terminal devices
	C. Gateway	D.	Cloud
17.	One of the following is not an attack tool:		
	A. Password cracking	B.	Encryption
	C. Password guessing	D.	Phishing
18.	Which of the following is not used in the two-fa	actor	authentication?
	A. Certification	B.	SMS
	C. Digital signature	D.	Password

19. In the bicycle sharing scenario, which of the following mechanism(s) is(are) used?

A. One-way authentication

B. Dual authentication

C. Both of them

D. None of them

20. In the context of bicycle sharing scenario, "DICE" stands for:

A. Device Identifier Composition

Engine

B. Digital Identifier Composition

Engine

C. Digital Identifier Center Engine

D. Digital InterconnectionComposition Engine

## **Chapter 4.** Overview of Common IoT Communications

## **Technologies**

- 1. Ethernet uses CSMA/CA to detect collisions.
- 2. FE stands for Fast Ethernet.
- 3. Micro-B is a USB port Type.
- 4. USB 4.0 bit rate can go up to 40 Gbit/s.
- 5. In M-Bus technology, the power supply capability of the bus is 10 A.
- 6. Bluetooth includes three types: BR/EDR, BLE and BLF.
- 7. Wi-Fi can use 2.4 GHz UHF or 5 GHz SHF ISM radio frequency bands.
- 8. GPRS bit rate is 9.6 kbps.
- 9. UMTS is categorized as 2.5G.
- 10. IMT-Advanced is the official name of 4G.
- 11. LTE UE category 1 supports a downlink bit rate of up to 10 Mbit/s.
- 12. 5G application scenarios are eMBB, mMTC and URLLC.
- 13. Commercial use of the 5G started in 2020.
- 14. NB-IoT is categorized as LPWA communication technology.
- 15. SigFox bit rate is 1000 bit/s.
- 16. 3G, 4G and 5G are considered high-rate and long-range technologies.
- 17. Smart meter reading scenarios can use small-packet and ultra-long-range technology such as 3G.
- 18. Wi-Fi and Bluetooth are considered high-rate and short-range technologies.
- 19. NB-IoT and LoRa are low-speed connection technologies.
- 20. Z-Wave coverage can extend to 1 km.

# B. Check the correct answer, there is only one correct answer for each question: 1. One of the following is not a wired communication technology: A. Ethernet B. LTE C. PLC D. USB 2. One of the following is not a wireless communication technology: A. Wi-Fi B. Zigbee C. LoRa D. RS-232 3. Which of the following is not considered as a cellular mobile network technology? A. UMTS B. GSM C. PLC D. LTE 4. Which of the following is(are) considered as short-range wireless communication technology(ies): A. Wi-Fi B. Zigbee C. Bluetooth D. All of them 5. LTE-Advanced Pro belongs to: A. 2G B. 3G C. 4G D. 5G

B. GPRS

D. HSPA+

6. One of the following is not a 3G technology:

A. UMTS

C. HSPA

7.	GSM data rate is in the range of:		
	A. kbit/s	B.	Mbit/s
	C. Gbit/s	D.	Tbit/s
8.	5G connection density is:		
	A. 10 <sup>4</sup> connections/km <sup>2</sup>	B.	10 <sup>5</sup> connections/km <sup>2</sup>
	C. 10 <sup>6</sup> connections/km <sup>2</sup>	D.	10 <sup>7</sup> connections/km <sup>2</sup>
9.	5G supports mobility at the speed of:		
	A. 200 km/h	B.	300 km/h
	C. 400 km/h	D.	500 km/h
10.	One of the following is not a 3G technology:		
	A. FDMA	B.	TD-SCDMA
	C. CDMA2000	D.	WCDMA
11.	AR, VR and MR are supported in the:		
	A. 3G	B.	4G
	C. 5G	D.	All of them
12.	In which of the following LPWA technology, the	ne co	overage can extends to 50 km?
	A. SigFox	B.	LoRa
	C. NB-IoT	D.	eMTC
13.	The bandwidth used for LPWA NB-IoT is:		
	A. 180 MHz	B.	180 kHz
	C. 18 MHz	D.	18 kHz

14. LPWA NB-IoT supports mobility scenarios with a speed less than:		
A. 80 km/h	B. 100 km/h	
C. 200 km/h	D. 500 km/h	
15. eMTC is developed by:		
A. Nokia	B. Ericsson	
C. Huawei	D. None of them	
16. Which of the following has the lowest typical transmission rate?		
A. SigFox	B. LoRa	
C. NB-IoT	D. eMTC	
17. Video surveillance requires:		
A. Low data rate and high	B. High data rate and high	
bandwidth	bandwidth	
C. High data rate and low bandwidth	D. Low data rate and low bandwidth	
18. Smart meter applications require:		
A. High data rate	B. High bandwidth	
C. None of them	D. Both of them	
19. Which of the following require 5G?		
A. Video surveillance	B. IoV	
C. None of them	D. Both of them	

20. Small packet and short-range technologies includes:

A. eMTC

B. LoRa

C. Z-Wave

D. SigFox

## **Chapter 5.** NB-IoT Communication Technologies and Solutions

- 1. NB-IoT and NR can coexist.
- 2. The industry recognizes NB-IoT evolution and agrees to incorporate it into the overall 5G plan.
- 3. NB-IoT bandwidth is 200 kHz.
- 4. NB-IoT downlink has 12 subcarriers each is 15kHz.
- 5. OFDMA is an evolution of OFDM that combines it with FDMA.
- 6. NB-IoT technology supports massive connections but it consumes remarkable amount of energy.
- 7. PSM stands for Power Sleeping Mode.
- 8. In NB-IoT technology, PSM consumes the most amount of energy.
- 9. NB-IoT uses retransmission over the air interface and ultra-narrow bandwidth to provide an extra gain of over 20 dB compared with GSM.
- 10. NB-IoT is based on cellular networks and coexists with other networks of this type.
- 11. NB-IoT standalone deployment is only based on LTE.
- 12. NB-IoT supports three deployment modes.
- 13. NB-IoT on the Boudica 150 chip supports full duplex channel.
- 14. DRX period can be 1.28, 2.56, 5.12 or 10.24s, and it is determined by the operator's network.
- 15. The maximum eDRX period is 2.92 hours.
- 16. An IoT device can be in the dormant state for up to 99% of the total time.
- 17. PSM maximum period is 200 hours.
- 18. Because NB-IoT uses repeated transmission, the downlink gain increased by 12 dB and the uplink gain increased by 9 dB.
- 19. NB-IoT is a wide coverage technology.
- 20. NB-IoT is not an example of LPWA communication technologies.

C. Supports IP only

A. 150 kHz

C. 120 kHz

6. At the physical layer of NB-IoT, the bandwidth is:

# B. Check the correct answer, there is only one correct answer for each question: 1. LPWA stands for: A. Long-Power Wide-Area B. Low-Power Wide-Area C. Large-Power Wide-Area D. Low-Person Wide-Area 2. Power transmission gain in the basic version of LPWA was: A. 20 dB B. 10 dB C. 5 dB D. 25 dB 3. NB-IoT and NR technologies: A. Work separately only B. Can coexist C. Interfere with each other D. None of them 4. Boudica 150 chip supports: A. Multicast B. Downlink: 21.2 kbps, uplink: 15.6 kbps D. All of them C. Positioning 5. One of the following is not true about Boudica 120, it: A. Supports paging B. Has 20 dB coverage enhancement

D. Supports single tone

B. 180 kHz

D. 200 kHz

7.	At the physical layer of NB-IoT, uplink technology is:	
	A. OFDMA	B. SC-FDMA
	C. TDMA	D. CDMA
8.	One of the following is not an NB-IoT feature:	
	A. Ultra-low cost	B. Massive connections
	C. Ultra-high power consumption	D. Ultra-wide coverage
9.	NB-IoT deployment mode(s) is(are):	
	A. Standalone	B. Guard band
	C. In-band	D. All of them
10.	Standalone deployment mode is used with:	
	A. GSM	B. UTMS
	C. LTE	D. All of them
11.	Kirin 4G chip supports:	
	A. Broadband	B. High bit rate
	C. Full duplex	D. All of them
12.	PSM consumption pattern can last up to:	
	A. 300 hours	B. 210 hours
	C. 310 hours	D. 350 hours
13.	Deep coverage solution provides gain increasing	g by:
	A. 5 dB	B. 11 dB
	C. 20 dB	D. 25 dB

14.	14. NB-IoT gain in the repeated transmission is:				
	A.	Decreased both in the uplink and downlink	В.	Increased both in the uplink and downlink	
	C.	Increased in the uplink only	D.	Increased in the downlink only	
15.	15. Which of the following technologies has the highest maximum coupling loss?				
	A.	LTE	B.	GPRS	
	C.	NB-IoT	D.	GSM	
16.	NB	3-IoT increases battery life to be:			
	A.	5 years	B.	7 years	
	C.	10 years	D.	12 years	
17. Which of the following is the number of connection per cells supported by NB-IoT?					
	A.	5000	B.	50 000	
	C.	100 000	D.	150 000	
18.	On	e of the following is not true about NB-IoT:			
	A.	Evolution is based on the live network	B.	Operator-level reliability	
	C.	High security	D.	Local roaming	
19.	NB	3-IoT solution architecture includes:			
	A.	3 layers	B.	4 layers	
	C.	5 layers	D.	None of them	

20. Which of the following solution can include NB-IoT?

A. Smart parking

B. Shared bikes

C. Smart streetlamp

D. All of them

## Chapter 6. 5G Communications Technologies and Solutions

- 1. NR stands for New Reality.
- 2. Massive MIMO supports 64 transceiver antennas and 64 for receivers.
- 3. Release 15 is the first 3GGP standard dedicated for 5G.
- 4. In 5G, E2E latency is 10 ms.
- 5. Compared to the 4G technology, latency in 5G is 30 to 50 times less.
- 6. The throughput of 5G can go up to 10 Mbps.
- 7. Compared to the 4G technology, throughput in 5G is 100 times higher.
- 8. 5G can support a number of connections per km<sup>2</sup> up to 1 million.
- 9. Compared to the 4G technology, 5G supports 1000 times the number of connections.
- 10. 4G and 5G supports slicing.
- 11. IMT-Advanced is another name for 5G.
- 12. SDN stands for Software-Driven Networking.
- 13. NSA can coexist with SA.
- 14. eNB stands for evolved NodeB.
- 15. 5G New Radio can be full duplex or half duplex.
- 16. 5G New Radio supports Massive MIMO.
- 17. Sub-3 GHz means lower than 3000 MHz and C-band covers 3000 6000 MHz.
- 18. 5G New Radio extends to the visible light band.
- 19. In 5G, URLLC scenarios need to provide ultra-high reliability and ultra-low latency services.
- 20. VR, AR and MR are examples of eMBB scenarios.

C. 10 msec

# B. Check the correct answer, there is only one correct answer for each question: 1. 3GPP process of the 5G standardization started in: A. Release 14 B. Release 15 C. Release 16 D. Release 17 2. Which of the following standard(s) can benefit from the 5G? A. WiMax B. WCDMA C. LTE D. All of them 3. One of the following is not true about the 5G, it provides: A. Global unified standardization B. Global roaming C. Massive connections D. Bit rate up to 1Tbit/s 4. Compared to LTE, the throughput of the 5G is: A. 10 times greater B. 100 times greater C. 1000 times greater D. None of them 5. Compared to LTE, the number of connections of 5G is: A. The same B. 10 times greater C. 100 times greater D. 1000 times greater 6. In 5G, the latency is around: A. 0.1 msec B. 1 msec

D. 100 msec

7.	How many connections per km <sup>2</sup> can a 5G network support?			
	A. $10^3$		B.	$10^{4}$
	C. 10 <sup>5</sup>		D.	$10^{6}$
8.	In terms of spectral efficiency, and compared to IMT-advanced, IMT-2020 can provide			C-advanced, IMT-2020 can provide:
	A. The same efficience	су	B.	Less efficiency
	C. 3 Times more		D.	10 Times more
9.	Which of the following	g is not true about 5G? it	•	
	A. Uses low and bands	nigh frequency	В.	Creates one physical network for hundreds of industries
	C. Has an impression efficiency	oved spectral	D.	Has massive energy consumption
10. eNB stands for:				
	A. enhanced NodeB		B.	evolved NodeB
	C. enhanced Narrow	Band	D.	evolved Narrow Band
11. Which of the following service(s) is(are) provided by the 5G core network?				
	A. Control and user p	plane separation	В.	Mobile edge computing
	C. Network slicing		D.	All of them
12.	. Which of the following	g technology(ies) is(are)	supp	orted by the 5G New Radio?
	A. Half duplex		В.	CDMA
	C. Both of them		D.	None of them

13.	13. Which of the following multiplexing technologies does massive MIMO use?			
	A.	Spatial	B.	Time
	C.	Code	D.	Frequency
14.	On	e of the following is not true about the 5G fre	eque	ncy bands:
	A.	C-band is mainly used for capacity expansion	В.	5G can use bands above 6 GHz
	C.	28 GHz band can be used for industrial purposes	D.	Visible light bands are supported
15.	On	e of the following is not true about the sub-6	GH	z, it is used for:
	A.	Higher bit rate	B.	Coverage
	C.	Mobility	D.	Connectivity
16. Which of the following is not true about 5G full spectrum?				
	A.	Sub-6 GHz low frequency bands serve as the core spectrum	В.	High frequency bands are supplementary
	C.	Sub-6 GHz is used for higher rate	D.	C-band is mainly used for capacity expansion
17.	eM	IBB stands for:		
	A.	Enhanced Mobile BroadBand	B.	Evolved Mobile BroadBand
	C.	Electronic Mobile BroadBand	D.	Enhanced Mobile BaseBand
18. Which one of the following is not a reality-based technology?			chnology?	
	A.	Virtual Reality	B.	Augmented Reality
	C.	Supported Reality	D.	Mixed Reality

- 19. URLLC scenarios require:
  - A. Ultra-low reliability and ultra-low latency
  - C. Ultra-low reliability and ultrahigh latency
- B. Ultra-high reliability and ultralow latency
- D. Ultra-high reliability and ultrahigh latency
- 20. Which of the following 5G application scenario(s) is(are) defined by ITU?
  - A. eMBB

B. mMTC

C. URLLC

D. All of them

## **Chapter 7.** Huawei IoT Gateways (Industrial + Home)

- 1. Industrial-grade design requirements include the need of the gateway to be dustproof and waterproof.
- 2. Enterprise routers temperature range is  $-40^{\circ}$ C to  $+70^{\circ}$ C.
- 3. Industrial IoT gateway sets in-between the network and the cloud.
- 4. Industrial IoT gateway includes extensive interfaces and protocols.
- 5. Industrial IoT gateway uses edge computing to reduce latency.
- 6. Edge computing reference architecture covers 4 domains: application, data, cloud and device.
- 7. The reliability of the star topology is high.
- 8. Huawei RF networking technology is based on the bus topology.
- 9. Bus topology is simple and easy to expand.
- 10. Ring topology is easy to expand.
- 11. The topology of the future home network will be star.
- 12. A smart home network runs over a baseband connection.
- 13. AP stands for Access Point.
- 14. Huawei HiLink allows two connection modes: direct hardware and cloud-based.
- 15. STB stands for Set Tree Box.
- 16. Smart home devices can use PLC.
- 17. Security surveillance is one application of the smart home scenario.
- 18. Huawei HiLink ecosystem connection includes modules, SDK and routers.
- 19. HiLink SDK is used to connect the smart home application to the cloud.
- 20. Wi-Fi, ZigBee, Z-Wave and Bluetooth are examples of wireless communication technologies supported by the smart home gateway.

## B. Check the correct answer, there is <u>only one correct answer</u> for each question:

1.	Which of the following is not true about industrial-grade routers? they are:		
	A. Designed to work in temperature: -40°C to +70°C	B. Dustproof	
	C. Waterproof	D. Weak against electromagnetic interference	
2.	Industrial IoT gateways sit in-between:		
	A. Network and terminal devices	B. Network and application	
	C. Application and terminal devices	D. None of them	
3.	Which of the following is(are) a core-benefit of	f edge computing?	
	A. Real-time services	B. Data aggregation	
	C. Processing at the edge	D. All of them	
4.	One of the following is not distributed in the net	twork by edge computing technologies:	
	A. Computing	B. Storage	
	C. Coverage	D. Security	
5.	How many domains are considered in the edge	computing architecture?	
	A. 3	B. 4	
	C. 5	D. 6	
6.	One of the following is not true about star topol	logy, it is/has:	
	A. Easy control	B. Low cost	
	C. Simple structure	D. Short latency	

7.	Which of the following is true about the star topology?				
	A. Low cost	B.	High reliability		
	C. High network latency	D.	Poor resource sharing capability		
8.	Which of the following is not true about the ring	g top	pology?		
	A. Closed	B.	Difficult to extend		
	C. High reliability	D.	Difficult to locate faulty nodes		
9.	Which of the following is not true about the bus	top	ology?		
	A. Complex structure	B.	Easy to expand		
	C. Difficult to locate faulty nodes	D.	Small number of cables are linked		
10.	Which of the following is not true about the mea	sh to	ppology?		
	A. Rapid deployment	B.	Resilient to damage		
	C. Has a control center	D.	No preset infrastructure		
11.	Which of the following topologies is adopted by	Hu	awei RF technology?		
	A. Mesh	B.	Bus		
	C. Star	D.	Ring		
12.	Nowadays, home network topology is:				
	A. Star	B.	Mesh		
	C. Ring	D.	Bus		

13.	13. Which of the following is not true about future IoT home networks? it:			
	A.	Requires accessing broadband connection	В.	Uses fiber optics
	C.	Has a mesh topology	D.	Has a low-processing ability
14.	Wh	nich of the following is not a device used in the	he Io	oT home network?
	A.	STB	B.	Smart gateway
	C.	NodeB	D.	Wi-Fi repeater
15.		nich of the following technology(ies) can be home network?	use	d to extend Wi-Fi coverage in the
	A.	PLC	B.	Wireless repeater
	C.	Ethernet AP	D.	All of them
16.	In t	the smart ONT solution, which of the following	ıg te	chnology is not used inside homes?
	A.	USB dongle	B.	ZigBee
	C.	Z-Wave	D.	LTE
17.	In	the Huawei smart home solution, the plug-in	dow	vnload service is provided by:
	A.	The smart terminal devices	B.	The open platform
	C.	The smart gateway	D.	Control and management applications
18.	Wh	nich of the following is not true about Huawe	i Hi	Link platform? it is:
	A.	Open	B.	Simple to use
	C.	Jointly constructed	D.	Expensive

19. Which of the following is(are) part(s) of the Huawei HiLink access?		
A. HiLink module	B. HiLink SDK	
C. HiLink router	D. All of them	
20. How many connection modes are su	pported in the Huawei HiLink solution?	
A. 2	B. 3	
C. 4	D. 5	

### Chapter 8. IoT Platform

#### A. Mark the following <u>True or False</u>?

- 1. An IoT platform requires device access decoupling, security and reliability.
- 2. Decimal data are accepted format in Huawei cloud IoT platform.
- 3. Huawei cloud IoT platform uses LwM2M and MQTT to access devices.
- 4. Huawei cloud IoT platform is multi-network access, this means devices can connect to the platform directly, through gateways or edge devices.
- 5. Devices that use property protocols based on TCP/UDP can connect to the IoT platform by using CIGs deployed on the cloud.
- 6. HTTP is an asynchronous protocol.
- 7. HTTP is a heavyweight protocol with many headers and rules, thus, it is not suitable for restricted networks.
- 8. CoAP is based on HTTP.
- 9. CIG stands for Carrier Interworking Gateway.
- 10. Device management includes device registration and activation.
- 11. IoT platform has three ways to deliver commands: Immediate, delayed and synchronic deliveries.
- 12. In time-based triggers, actions can be set based on specific events.
- 13. In the IoT platform, firmware and software upgrades for devices are achieved through FOTA and SOTA respectively.
- 14. In the IoT platform, hardware upgrade is called "Hardware-Over-The-Air".
- 15. Huawei cloud uses Identity and Access Management for application registration authentication.
- 16. Multi-temperature data management maximizes processing efficiency.
- 17. Multi-temperature management classifies data into two levels: hot and cold.
- 18. Huawei cloud IoT is access agnostic.
- 19. The IoT platform has its own security strategies, it includs one for each of the following: device, networking, service, access, data storage and access security.
- 20. The IoT platform cloud-based architecture is flexible but not scalable.

A. X

C. X+1

# B. Check the correct answer, there is only one correct answer for each question: 1. One of the following is not a requirement for IoT platform: A. Device access decoupling B. Coverage C. Security D. Reliability 2. How many sublayers are there in the functional architecture of the Huawei IoT platform? A. 2 B. 3 C. 4 D. 5 3. Which of the following is(are) an accepted data format(s) for Huawei IoT platform? A. JSON only B. Binary only C. None of them D. Both of them 4. One of the following is not a category of an IoT device access service: A. Device connectivity B. Data forwarding C. IoT Edge D. Application integration 5. One of the following is not true about the IoT device access in the Huawei platform, it supports: A. Multiple access modes B. Multi-network access C. Multi-protocol access D. Multiplexing modes 6. If the HTTP client first message has the sequence field set to X, the ACK field in the server response will be set to:

B. X-1

D. None of them

7.	Which of the following is not true about HTTP? it is:				
	A. Stateless	В.	Asynchronous		
	C. Heavy weight	D.	Not suitable for restricted network		
8.	If MQTT is used, how many message(s) is(are) the server before sending the first publish message		_		
	A. 1	B.	2		
	C. 3	D.	4		
9.	CoAP stands for:				
	A. Constrained Access Point	В.	Constrained Application Protocol		
	C. Coverage Application Protocol	D.	None of them		
10	Which of the following is not a typical IoT prot	tocol	?		
	A. CoAP	В.	НТТР		
	C. MQTT	D.	FBB		
11.	Devices that do not use TCP/IP protocol stack:				
	A. Can not connect the IoT platform	В.	Use a gateway with an integrated IoT device SDK		
	C. Use a gateway with an integrated IoT device tiny SDK	D.	None of them		
12	IoT device SDK does not support:				
	A. C	В.	R		
	C. Java	D.	C#		

13. Which of the following is(are) used by the IoT platform to deliver commands?		
A. Delayed delivery	B. Synchronous delivery	
C. None of them	D. Both of them	
14. Which of the following is(are) supported trigge	er(s) in the IoT platform?	
A. Time-based	B. Event-based	
C. Data-based	D. All of them	
15. Which of the following is true about the IoT pla	atform? it supports:	
A. Hardware upgrade only	B. Hardware and software upgrades	
C. Firmware upgrade only	D. Software and firmware upgrades	
16. One of the following is not true about IoT data:	:	
A. Huge volume	B. High quality	
C. Low value density	D. High time sensitivity	
17. How many data categorizations are included in	the Multi-temperature management?	
A. 2	B. 3	
C. 4	D. 5	
18. Which of the following is the correct sequence	for managing warm data?	
A. Cleansing, storage, analysis, visualization	B. Storage, cleansing, analysis, visualization	
C. Analysis, storage, cleansing, visualization	D. Visualization, analysis, storage, cleansing	

19. One of the following is not a common IoT data problem:
A. Duplicate data
B. High-quality data
C. Format differences
D. Noise interference
20. Which of the following is(are) character(s) of Huawei cloud IoT platform?
A. Access agnostic
B. Scalable
C. None of them
D. Both of them

### **Chapter 9.** IoT Platform Secondary Development

#### A. Mark the following **True or False**?

- Product development includes product management, model developing and online debugging.
- 2. The codec is also called "profile".
- 3. The profile describes what a device is, what it can do and how to control it.
- 4. Only data that is matched with the product model is saved on the IoT platform.
- 5. The codec decodes binary data reported by application into JSON format that can be read by the devices.
- 6. NB-IoT devices have high requirements on power consumption, that is why their application layer data uses JSON format.
- 7. Graphical codec development is recommended.
- 8. GET action is used to create a resource on the server.
- 9. PUT action is used to update resources on the server.
- 10. In an API message, path parameter includes the path part in the URL.
- 11. In an API message, the body parameter is used after the question mark (?) in the URL.
- 12. Application access authentication is achieved by exchanging messages with the platform's IAM.
- 13. The status code in the response message of the querying device is 203.
- 14. Creating a device requires registering it in the cloud first and then binding it.
- 15. All developments on the device side can be achieved using MQTT and CoAP/LwM2M.
- 16. IoTDA stands for Internet of Things Data Analytics.
- 17. Authentication for devices using LwM2M over CoAP is not possible.
- 18. Authentication for devices is possible using Native MQTT or MQTTS.
- 19. When deleting a device successfully, the returned code is 204.
- 20. Querying device messages is achieved using the PUT method.

### B. Check the correct answer, there is <u>only one correct answer</u> for each question:

1.	. Which of the following is not true about the product model?		t model?
	A. It is also called "profile"	В.	It defines the properties of a device
	C. It is created using codes	D.	It defines what can a device do
2.	A product model includes:		
	A. Product details	В.	Service capabilities
	C. None of them	D.	Both of them
3.	Which of the following is not done by the code	c?	
	A. Encodes binary data into JSON format	В.	Decodes data in JSON format into binary data
	C. None of them	D.	Both of them
4.	Which of the following is not true about codec	deve	elopment? it is:
	A. Graphical	В.	Written using C++
	C. Offline	D.	Script-based
5.	Which of the following can not be performed by	y ap	plication-side API?
	A. View the application access address on the console	B.	Report binary data
	C. Create and manage products	D.	Deliver commands, properties and messages

6.	One of the following is not an API action:		
	A. ADD	B. GET	
	C. PUT	D. DELETE	
7.	Which of the following is not a parameter used	in the API messages?	
	A. Path	B. Data	
	C. Header	D. Query	
8.	Which of the following methods is used by the	application access authentication?	
	A. POST	B. GET	
	C. PUT	D. DELETE	
9.	What is the status code in the response of the ap	oplication access authentication?	
	A. 200	B. 201	
	C. 202	D. 203	
10	PUT Method is used to:		
	A. Application access authentication	B. Querying device messages	
	C. Create a device	D. Modify device information	
11.	Which of the following device development me IoT?	ethod is not supported by Huawei c	loud
	A. Certified sensor	B. Certified module	
	C. Certified MCU	D. LiteOS	

	Which of the following device development methods is supported by Huawei cloud IoT?			
	Α. (	Certified sensor	B.	Certified module
	C. (	Certified MCU	D.	LiteOS
13.	Con	nmon development on the device side requir	es tl	he use of:
		Certified MCU and communications module	B.	MCU/single-chip microcomputer only
		MCU/single-chip microcomputer and communications module	D.	Certified MCU only
14.	Imn	nediate delivery of MQTT device messages i	is ac	chieved using:
	<b>A.</b> ]	IoT device	B.	IoT platform
	<b>C</b> . ]	IoT application	D.	All of them
15.	Whi	ich of the following is true about device prop	perty	y reporting in JSON format?
	<b>A</b> . ]	It requires a codec	B.	It does not require a codec
	<b>C</b> . ]	It is not possible	D.	None of them
16.	Whi	ich of the following protocol(s) can be used	for a	authentication for devices?
	<b>A.</b> ]	Native MQTT	B.	LwM2M over CoAP
	<b>C</b> . 1	MQTTS	D.	All of them
17.	Whe	en deleting a device successfully, the returne	ed co	ode is:
	A. 7	201	B.	202
	C. 2	203	D.	204

18. In which of the following API operation(s) a token is returned? A. Application access authentication B. Device creating C. None of the them D. Both of them 19. IAM service is only used when: A. Creating a device B. Authenticating application access C. Deleting a device D. None of them 20. Which of the following device development method is used if the device includes an SDK Tiny? B. Gateway A. Certified MCU C. Common D. LiteOS

### Chapter 10. IoT OS

#### A. Mark the following <u>True or False</u>?

- 1. OS is a computer program that manages hardware, software and firmware resources.
- 2. DOS and windows are examples of programming language handlers.
- 3. Peripherals hardware includes external memory, input devices and output devices.
- 4. Internal memory includes RAM, REM and ROM.
- 5. CPU stands for Central Programming Unit.
- 6. Punched tapes are an example of the manual operation system.
- 7. Multi-job batch processing OS developed to time-sharing OS.
- 8. Time-sharing OS is an operating system that implements a specific function within a defined time frame.
- 9. In single-job batch processing OS programs are loaded into the memory and executed individually.
- 10. Network OS developed after distributed OS.
- 11. IoT OS can operate in networks where the number of connections might grow up to reach a limit of 10 billions.
- 12. Open source Huawei LiteOS entered the IoT field in 2015.
- 13. High requirements on performance and power consumption for videos are two challenges facing the IoT OS.
- 14. Smart terminals need to meet three standards: smart connections, smart networking and smart management.
- 15. Huawei LiteOS includes multiple kernels and one middleware.

# B. Check the correct answer, there is only one correct answer for each question: The OS manages and controls all resources of: A. Software and hardware B. Software only C. Hardware only D. Firmware 2. CPU includes: A. Input devices B. Output devices C. None of them D. Both of them 3. One of the following is not a peripherals hardware in the microcomputer system: A. CD-ROM B. Keyboard C. Printer D. ROM 4. ALU is included within: A. CPU B. RAM C. ROM D. CD-ROM 5. DOS is a(n): A. Central processing unit B. Operating system D. Main memory C. Output device

B. Time-sharing OS

D. Real-time OS

6. One of the following is not an operating system type:

A. Patch OS

C. Complex OS

7.	Time-sharing OS developed to:	
	A. Real-Time OS	B. Network OS
	C. Distributed OS	D. Multi-job OS
8.	IoT OS should be able to handle connections up	p to:
	A. 1 billions	B. 10 billions
	C. 100 billions	D. None of them
9.	Which of the following hardware technology(ie	es) is(are) supported by the IoT OS?
	A. DSP	B. MIPS
	C. FPGA	D. All of them
10.	Which of the following is not a challenge to the	e IoT terminal development?
	A. Multi-sensor coordination that is complex to manage	B. High requirements on performance
	C. Power consumption for videos	D. Various IoT platform
11.	How many kernel(s) does Huawei LiteOS inclu	ides?
	A. 1	B. 2
	C. 3	D. 4
12.	Which of the following is true about security in	the Huawei LiteOS? it is implemented:
	A. In the kernel layer	B. In the middleware layer
	C. Across model's layers	D. In the open API layer only

13. H	13. Huawei LiteOS became open to consumers on:		
A	2010	B.	2011
C	2012	D.	2013
14. In	which year Huawei LiteOS entered the IoT fi	eld?	,
A	2014	B.	2015
C	2017	D.	2018
15. W	Thich of the following solution(s) implement H	luaw	vei LiteOS?
A	Smart home	B.	Smart water meter
C	Smart parking	D.	All of them

### **Chapter 11. Sensing Layer Development**

#### A. Mark the following <u>True or False</u>?

- 1. All programs process computer data through a simple set of instructions.
- 2. To implement multiple functions, a register is used.
- 3. MOV is a common ARM instruction, it is used to transfer data from memory to register.
- 4. There are two types of instruction sets in today's typical architecture: RISC and CISC.
- 5. Standard MPUs have a system clock speed of 3 GHz.
- 6. RAM stores data running in the program, it will disappear after the power goes off.
- 7. ROM data is lost after the power is off.
- 8. An interface connects an internal device to an MCU.
- 9. ADC stands for Analog-to-Digital Converter
- 10. An interrupt is the process where the CPU stops to execute a new program.
- 11. In terms of basic sensing functions, there are 5 types of sensing elements.
- 12. RTD stands for Resistance Temperature Detector.
- 13. A photoelectric sensor converts electrical signals into optical signals.
- 14. Huawei LiteOS provides one single memory management algorithm: the static memory allocation.
- 15. An interrupt can be deleted.
- 16. The message queue provides an asynchronous processing mechanism.
- 17. An event is not associated with a task.
- 18. A semaphore is used only to enable tasks to access system resources synchronously.
- 19. A mutex is a special binary queue.
- 20. The system clock is also referred to as time scale or tick.

A. Vision sense

C. Taste sense

В.	. Check the correct answer, there is <u>only one correct answer</u> for each question:				
1.	Which of the following elements is used to record previous results and subsequent instructions?				
	A. Multiplexer	B. Register			
	C. Mux	D. None of them			
2.	LDR ARM instructions is used to:				
	A. Addition	B. Subtraction			
	C. Data transfer from memory to register	D. Exclusive OR			
3.	Standard MPUs have a system clock speed of	of:			
	A. 3 MHz	B. 300 MHz			
	C. 3 GHz	D. 300 GHz			
4.	Standard MCUs have a system clock speed to	hat ranges between 10 and 100:			
	A. kHz	B. MHz			
	C. GHz	D. None of them			
5.	The system bus in the MCU architecture inc	ludes:			
	A. Control bus	B. Address bus			
	C. Data bus	D. All of them			
6.	Under which of the following senses the che	emical sensor is classified?			

B. Auditory sense

D. Olfactory sense

7.	. In terms of basic sensing functions, which of the following is not a type of senses?					
	A. Color	B. Taste				
	C. Touch	D. Magnet				
8.	How many classes are used to classify temperat	ure sensors?				
	A. 2	B. 3				
	C. 4	D. 5				
9.	Which of the following is not a type of heart rat	e sensor?				
	A. Piezoelectric	B. Photoelectric				
	C. Piezoresistive	D. Photoresistive				
10.	The process where the CPU stops to execute a n	new program is called:				
	A. Task	B. Allocation				
	C. Interrupt	D. None of them				
11.	A task can be:					
	A. Created	B. Deleted				
	C. Delayed	D. All of them				
12.	12. One of the following is not a disadvantage of the dynamic memory use:					
	A. High performance overheads	B. Fragments in the memory pool				
	C. Memory is wasted if there are many small blocks	D. Large blocks are cost-effective				

13. An interrupt can be:	
A. Deleted	B. Delayed
C. None of them	D. All of them
14. Which of the following is not an inter-task of	communication?
A. Queue	B. Stack
C. Semaphore	D. Mutex
15. Which of the following is not true about ever	ents?
A. It is a synchronization inter-task communication	B. It involves data transmission
C. Events are independent from each other.	D. An event is not associated with a task
16. When the number of tasks accessing the semaphore:	same resource reaches the maximum, the
A. Blocks other tasks from accessing the resource	B. Release all resources
C. Execute all the tasks	D. All of them
17. How many statuses does the mutex have?	
A. 2	B. 3
C. 4	D. 5
18. A mutex is locked when:	
A. Two tasks are competing on it	B. A task owns it
C. None of them	D. Both of them

19. Huawei LiteOS provides:

A. Hardware timers B. Software timers

C. Firmware timers D. All of them

20. Which of the following is true about Huawei LiteOS kernel features?

A. Low power consumption B. Strong performance

C. Ultra-small kernel of less than D. All of them

6 kB

### **Chapter 12. AT Commands for Communication Modules**

#### A. Mark the following **True or False**?

- 1. AT commands are sent from DTE to DCE.
- 2. After a TE sends an AT command to an MT, the MT sends backs the response.
- 3. AT commands stands for ATtraction commands.
- 4. PUT command is a category of AT commands.
- 5. Execution commands can be written with or without parameters.
- 6. Set command is used to display valid parameter values set by other AT commands.
- 7.  $AT+\langle x\rangle=P1$  is the syntax of a read command.
- 8. Execution command is used to instruct a module to execute a specific function.
- 9.  $AT+\langle x\rangle=?$  is the syntax of a read command.
- 10. AT+<x>=<...> is not a valid syntax of the AT commands.

## B. Check the correct answer, there is <u>only one correct answer</u> for each question:

1.	AT commands stands for:		
	A. ATtention commands	B.	Adapter Terminal commands
	C. Adapter Technical commands	D.	ATtraction commands
2.	AT commands are:		
	A. Sent from terminal equipment	B.	Sent to a terminal equipment
	C. Sent from a mobile terminal	D.	All of them
3.	AT commands are used within:		
	A. NB-IoT networks only	B.	Wi-Fi networks only
	C. NB-IoT and Wi-Fi networks	D.	Bluetooth networks only
4.	How many categories are there for AT comman	ds?	
	A. 2	B.	3
	C. 4	D.	5
5.	AT command type "=XX" is used to:		
	A. Display valid parameter values set by other AT commands	В.	Set the attributes carried in the AT command
	C. Query attributes set by other AT commands	D.	Instruct a module to execute a specific function
6.	Read command is referred to as:		
	A. "=XX"	B.	"=?"
	C. "?"	D.	Null

7.	AT execution command is used to:		
	A. Display valid parameter values set by other AT commands	B.	Set the attributes carried in the AT command
	C. Query attributes set by other AT commands	D.	Instruct a module to execute a specific function
8.	Which of the following AT commands can be u	sed	with and without parameters?
	A. Set	В.	Test
	C. Read	D.	Execution
9.	For which of the following command set the syn	ntax	"AT+ <x>=?" is used?</x>
	A. Set	B.	Test
	C. Read	D.	Execution
10.	"AT+CGSN" is an example for a:		
	A. Set command	В.	Test command
	C. Execution command with parameters	D.	Execution command without parameters

### **Correct Answers**

### Chapter 1. IoT development history and Overview

### A. True or False questions

1. False	2. True	3. False	4. True	5. False
6. True	7. True	8. False	9. True	10. False
11. True	12. False	13. False	14. True	15. True

16. False 17. True 18. False 19. False 20. True

#### **B.** Multiple choices questions

1. C	2. A	3. D	4. D	5. D
6. B	7. A	8. D	9. C	10. C
11. A	12. C	13. D	14. B	15. A
16. B	17. C	18. D	19. B	20. D

## **Chapter 2. IoT Industry Applications and Solutions**

#### A. True or False questions

1. True	2. False	3. True	4. False	5. True
6. True	7. False	8. True	9. False	10. False
11. False	12. True	13. True	14. True	15. False
16 False	17 False	18 False	19 True	20 False

1. A	2. D	3. C	4. D	5. A
6. D	7. D	8. B	9. D	10. D
11. C	12. B	13. B	14. D	15. C
16. A	17. B	18. C	19. C	20. C

### **Chapter 3. IoT Security Technologies**

#### A. True or False questions

1.	False	2.	False	3.	True	4.	False	5.	False

### **B.** Multiple choices questions

1. B	2. D	3. C	4. A	5. D
6. B	7. C	8. D	9. A	10. D
11. B	12. C	13. C	14. A	15. C

18. C

19. B

20. A

## **Chapter 4. Overview of common IoT communication Technologies**

17. B

#### A. True or False questions

16. B

1. False	2. True	3. True	4. True	5. False
6. False	7. True	8. False	9. False	10. True
11. True	12. True	13. False	14. True	15. False
16. False	17. False	18. True	19. True	20. False

1. B	2. D	3. C	4. D	5. C
6. B	7. A	8. C	9. D	10. A
11. C	12. A	13. B	14. A	15. B
16. A	17. B	18. C	19. B	20. C

### **Chapter 5. NB-IoT Communication Technologies and Solutions**

### A. True or False questions

1.	True	2.	True	3.	False	4.	True	5.	True
6.	False	7.	False	8.	False	9.	True	10	. True

### **B.** Multiple choices questions

1. B	2. A	3. B	4. D	5. C
6. B	7. B	8. C	9. D	10. A
11. D	12. C	13. B	14. B	15. C
16. C	17. B	18. D	19. B	20. D

### Chapter 6. 5G Communications Technologies and Solutions

### A. True or False questions

1. False	2. True	3. True	4. False	5. True
6. False	7. True	8. True	9. False	10. False
11. False	12. False	13. True	14. True	15. False
16. True	17. True	18. False	19. True	20. True

1. B	2. D	3. D	4. B	5. C
6. B	7. D	8. C	9. D	10. B
11. D	12. D	13. A	14. D	15. A
16. C	17. A	18. C	19. B	20. D

### **Chapter 7. Huawei IoT Gateways (Industrial + Home)**

#### A. True or False questions

1.	True	2.	False	3.	False	4.	True	5.	True

#### **B.** Multiple choices questions

1. D	2. A	3. D	4. C	5. B
6. B	7. D	8. C	9. A	10. C

11. A	12. A	13. D	14. C	15. D

<sup>16.</sup> D 17. B 18. D 19. D 20. A

### **Chapter 8. IoT Platform**

#### A. True or False questions

1.	True	2.	False	3.	True	4.	False	5.	True

6.	False	7.	True	8.	True	9.	False	10. True
----	-------	----	------	----	------	----	-------	----------

1. C	2. D	3. D	4. C	5. D

### **Chapter 9. IoT Platform Secondary Development**

### A. True or False questions

1. True 2. Paise 3. True 4. True 3. Pai	1. True	True 2. False	3. True	4. True	5. False
---	---------	---------------	---------	---------	----------

#### **B.** Multiple choices questions

#### Chapter 10. IoT OS

#### A. True or False questions

1.	False	2.	False	3.	True	4.	False	5.	False

1. A	2. C	3. D	4. A	5. B
6. C	7. A	8. C	9. D	10. D

### **Chapter 11.** Sensing Layer Development

### A. True or False questions

1. True 2. False 3. False 4. True 5.	True
--------------------------------------	------

#### **B.** Multiple choices questions

#### **Chapter 12.** AT Commands for Communication Modules

#### A. True or False questions

1.	True	2.	True	3.	False	4.	False	5.	True

### **B.** Multiple choices questions

6. C 7. D 8. D 9. B 10. D

# **Abbriviations**

Abbreviation	Full name
	#
3GPP	3rd Generation Partnership Project
	${f A}$
AGC	Automated Guided Cart
AGV	Automated Guided Vehicle
AES	Advanced Encryption Standard
ADC	Analog-to-Digital Converter
ADSL	Asymmetric Digital Subscriber Line
AI	Artificial Intelligence
AIoT	Artificial Intelligence and Internet of Things
ALU	Arithmetic and Logic Unit
AMI	Advanced Metering Infrastructure
AP	Access Point
API	Application Programming Interface
APT	Advanced Persistent Threat
AR	Augmented Reality
AT command	ATtention command
	В
BLE	Bluetooth Low Energy
BR	Basic Rate
BRAS	Broadband Remote Access Server
BSC	Base Station Controller
BSS	Basic Service Set
BSD	Berkeley Software Distribution
BSS	Business Support System
BTS	Base Transceiver Station
	C
CA	Certificate Authority

CAN Controller Area Network **CDMA Code-Division Multiple Access** CIG Cloud Interworking Gateway **CISC** Complex Instruction Set Computer CoAP **Constrained Application Protocol** CPE **Customer-Premises Equipment CPU** Central Processing Unit **CRM** Customer Relationship Management Carrier Sense Multiple Access with Collision Detection CSMA/CD DAC Digital-to-Analog Converter DC Data Center DCE Data Circuit Equipment **DDoS** Distributed Denial-of-service DICE Device Identifier Composition Engine DIS **Data Ingestion Service DMS** Distributed Message Service DOS Disk Operation System **DRIS** Digital Road Infrastructure Solution DRX Discontinuous Reception **DSL** Digital Subscriber Line **DSP** Digital Signal Processor DTE **Data Terminal Equipment DTLS Datagram Transport Layer Security**  $\mathbf{E}$ 

End-To-End

ECC Edge Computing Consortium

ECU Electronic Control Unit

EDR Enhanced Data Rate

E2E

eDRX extended Discontinuous Reception

EIA Electronic Industries Association

eMBB enhanced Mobile BroadBand

eMTC Enhanced Machine Type Communication

eNB evolved NodeB

Electronic Power Control

EPC Evolved Packet Core

EPP Enhanced Parallel Port

ESS Extended Service Set

ETSI European Telecommunications Standards Institute

E-UTRAN Evolved Universal Terrestrial Radio Access Network

F

FAN Field Area Network

FBB Fixed BroadBand

FDMA Frequency Division Multiple Access

FE Fast Ethernet

FOTA Firmware-On-The-Air

FPGA Field-Programmable Gate Array

FSK Frequency Shift Keying

FTTB Fiber-To-The-Building

FTTH Fiber-To-The-Home

FTTN Fiber-To-The-Neighborhood

FTTx Fiber-To-The-x

FWA Fixed Wireless Access

G

GDPR General Data Protection Regulation

GE Gigabit Ethernet

GFW Great FireWall

GMSC Gateway Mobile service Switching Center

gNB next generation NodeB

GPRS General Packet Radio Service

GPS Global Positioning System

GSM Global System for Mobile Communications

JVM

H

HUD Head-Up Display HTTP HyperText Transfer Protocol HTTPS HyperText Transfer Protocol Secure Ι IAM Identity and Access Management **ICT** Information and Communication Technology **IEEE** Institute of Electrical and Electronics Engineers **IEF** Intelligent EdgeFabric **IETF** Internet Engineering Task Force IDE **Integrated Development Environment IMEI International Mobile Equipment Identity IMSI** International Mobile Subscriber Identity Internet Interconnected networks IoT Internet of Things **IoTDA Internet of Things Device Access** IoV Internet of Vehicles ΙP Internet Protocol IPv4 Internet Protocol version 4 IPv6 Internet Protocol version 6 **ISM** Industrial, Scientific and Medical ISO International Organization for Standardization **ITS Intelligent Transportation System** ITU International Telecommunication Union Union - Radiocommunication International Telecommunication ITU-R Sector In-Vehicle Infotainment IVI Input/Output I/O J

Java Virtual Machine

 $\mathbf{L}$ 

LAN Local Area Network

LiFi Light Fidelity

LoRa Long Range

LPWA Low-Power Wide-Area

LTE Long Term Evolution

LwIP Lightweight Internet Protocol

LwM2M Lightweight Machine-To-Machine

 $\mathbf{M}$ 

M2M Machine-To-Machine

MAC Media Access Controller

MBus Meter Bus

MCU Microcontroller Unit

MCL Maximum Coupling Loss

MDM Metering Data Management

MEC Mobile Edge Computing

MIMO Multi-Input Multi-Output

MIPS Microprocessor without Interlocked Pipelined Stages

M-MIMO Massive Multi-Input Multi-Output

mMTC Massive Machine-Type Communications

MQTT Message Queuing Telemetry Transport

MPU MicroProcessor Unit

MR Mixed Reality

MRS MapReduce Service

MSA Multi-Streaming Aggregation

MSC Mobile service Switching Center

MT Mobile Terminal

MU-MIMO Multi-User Multi-Input Multi-Output

N

NAN Neighbourhood Area Network

NB-IoT NarrowBand Internet of Things

NB-OFDM Narrowband Orthogonal Frequency Division Multiplexing

NFC Near-Field Communication

NFV Network Function Virtualization

NGC Next Generation Core

NR New Radio

NMS Network Management System

NSA Non-StandAlone

0

O2O Online-To-Offline

OBD On-Board Diagnostics

OBS OBject storage Service

OEM Original Equipment Manufacturer

OFDMA Orthogonal Frequency Division Multiple Access

OICT Operational, Information, and Communications Technologies

OLT Optical Line Terminal

ONT Optical Network Terminals

OS Operating System

OSGi Open Services Gateway initiative

OSI Open Systems Interconnection

OSS Operations Support System

OTA Over-The-Air

OTN Optical Transmission Network

OTT Over-The-Top

O&M Operations & Management

P

PAN Personal Area Network

PCB Printed Circuit Board

PDC Personal Digital Cellular

PLC Power Line Communication

PKI Public Key Infrastructure

PMU Power Monitoring Unit

PSM Power Saving Mode

PTW Paging Time Window

Q

QoS Quality of Service

R

RAM Random Access Memory

RF Radio Frequency

RFID Radio-Frequency IDentification

RISC Reduced Instruction Set Computer

ROM Read-Only Memory

RR Round-Robin

RRU Remote Radio Unit

RSU Road-Side Unit

RTD Resistance Temperature Detector

RTOS Real Time Operating System

RTU Remote Terminal Unit

S

SA StandAlone

SC-FDMA Single-Carrier Frequency-Division Multiple Access

SDK Software Development Kit

SDMA Space Division Multiple Access

SDN Software-Defined Networking

SHA Secure Hash Algorithm

SHF Super High Frequency

SIM Subscriber Identity Module

SMS Short Message Service

SNMP Simple Network Management Protocol

SOAP Simple Object Access Protocol

SoC System-on-a-Chip

SOTA Software On The Air

SRAM Static Random Access Memory

STB	Set Top Box
	T
TA	Terminal Adapter
TCP	Transmission Control Protocol
TCM	Trusted Cryptography Module
TDMA	Time Division Multiple Access
TE	Terminal Equipment
TLS	Transport Layer Security
TLSF	Two-Level Segregated Fit
TPM	Trusted Platform Module
TTM	Time-To-Market
	U
UART	Universal Asynchronous Receiver-Transmitter
UBI	Usage-Based Insurance
UDP	User Datagram Protocol
UE	User Equipment
UHD	Ultra-High Definition
UHF	Ultra-High Frequency
UMTS	Universal Mobile Telecommunications System
UNB	Ultra-Narrow Band
URLLC	Ultra-Reliable Low-Latency Communication
USB	Universal Serial Bus
	${f v}$
V2I	Vehicle-To-Infrastructure
V2N	Vehicle-To-Network
V2P	Vehicle-To-Pedestrian
V2V	Vehicle-To-Vehicle
V2X	Vehicle-To-Everything
VM	Virtual Machine
VR	Virtual Reality
VRP	Versatile Routing Platform

 $\mathbf{W}$ 

WAN Wide Area Network

WLAN Wireless Local Area Network

 $\mathbf{X}$ 

XG X Generation

# **About the Author**



Michel Bakni received the B.S. degree in telecommunication and electronics from Tishreen University, Lattakia, in 2013 and the M.S. degree from UTBM, France, in 2017, in mobile and distributed networks. In 2021, He received a Ph.D. degree in electronics from the doctoral school of the University of Bordeaux (UBx). His research interests include networking, wireless sensor networks, and energy consumption optimization.