

Indoor use of essential oil-based cleaning products: Emission rate and indoor air quality impact assessment based on a realistic application methodology

S. Angulo Milhem, Marie Verriele, M. Nicolas, Frederic Thevenet

▶ To cite this version:

S. Angulo Milhem, Marie Verriele, M. Nicolas, Frederic Thevenet. Indoor use of essential oil-based cleaning products: Emission rate and indoor air quality impact assessment based on a realistic application methodology. Atmospheric Environment, 2021, 246, pp.118060. 10.1016/j.atmosenv.2020.118060. hal-03203304

HAL Id: hal-03203304 https://hal.science/hal-03203304

Submitted on 13 Feb 2023 $\,$

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1	Indoor use of essential oil-based cleaning products: Emission rate						
2	and indoor air quality impact assessment based on a realistic						
3	application methodology						
4							
5	S. Angulo Milhem ^{a, b} , M. Verriele ^a , M. Nicolas ^b , F. Thevenet ^{a*}						
6							
7	^a IMT Lille Douai, Université de Lille, SAGE, F-59000 Lille, France						
8	^b Centre Scientifique et Technique du Bâtiment (CSTB), F-38000 Grenoble, France						
9							
10	shadia.angulo@imt-lille-douai.fr						
11	marie.verriele@imt-lille-douai.fr						
12	melanie.nicolas@cstb.fr						
13	frederic.thevenet@imt-lille-douai.fr						
14							
15							
16	*CORRESPONDING AUTHOR						
17	F. Thevenet						
18	941 Rue Charles Bourseul, 59500 Douai.						
19	Tel.: 03.27.71.26.12						
20	Fax: 03.27.71.26.14						
21	E-mail: frederic.thevenet@imt-lille-douai.fr						
22							

23 ABSTRACT

24 Cleaning is performed to increase hygiene, esthetics and material preservation. Despite its 25 benefits, cleaning also poses risks, potentially contributing to nearly 20 % of indoor pollution. As 26 indoor air quality has become a major human health concern, "natural-scented" cleaning 27 products, formulated with essential oils, have become market leaders among household products. 28 However, these consumer products have benefitted from skillful marketing strategies based on 29 the ambiguity of the words "green" and "natural". The characterization of the emission processes 30 studied through 1-m³ chamber experiments under a realistic scenario suggests variable maximum 31 total terpene concentrations from 150 to 300 ppb. The estimated emission rate profiles confirm 32 that the liquid-to-gas transfer of terpenes is driven by (i) the formulation of the product matrix 33 inducing specific chemical affinities, (ii) the liquid content of individual terpenes, and (iii) the 34 intrinsic volatility of terpenes. A unique formaldehyde emission kinetics profile was observed, 35 suggesting the presence of a unique emission source: formaldehyde-releasers. Consequently, the 36 use of essential-oil-based cleaning products might generate a long-term increase in the indoor 37 formaldehyde concentration, and the maximum levels might be sustained for several hours after 38 cleaning. Thus, essential-oil-based cleaners should be seriously considered as versatile and 39 significant sources of fragrance molecules and formaldehyde.

40

41 **KEYWORDS:** cleaning products; emission rates; indoor air quality; terpenes

42

ABBREVIATIONS: TerVOCs Terpenic volatile organic compounds; AER Air exchange rate;
 OVOCs Oxygenated volatile organic compounds; VP Vapor pressure; PROBAS Danish
 Product Register Database; BNPC National Database for Products and Compositions

47 **1 INTRODUCTION**

48 Major efforts have been focused on addressing indoor air problems since daily activities 49 mostly occur in confined environments. Indoors, people are exposed to a wide variety of 50 chemical, biological and physical pollutants that (i) infiltrate from outdoor air, (ii) are released 51 from building materials and furnishing, and (iii) are generated by occupants and their indoor 52 activities (Missia et al., 2012; Weschler, 2001). The scientific community has focused on 53 chemical pollutants, principally volatile organic compounds (VOCs), defined as organic 54 molecules with boiling points ranging from 50 to 100 °C on the low end and from 240 to 260 °C 55 on the high end (Brown et al., 1994; World Health Organisation, 2010). Among indoor sources 56 of pollutants, the main origins of chemical contaminants are linked to occupant activities, such as 57 interior renovation or decoration, smoking, cooking, or housekeeping (Kirchner et al., 2001).

Among the thousands of cleaning products available and marketed, people are tempted to 58 59 use scented products because a pleasant odor is associated with a cleaner environment. 60 Therefore, despite all the benefits of cleaning activities, such as increased hygiene, esthetics, and 61 material preservation, the chemical and physical pollutant exposure risks posed by such activities 62 remain unclear. Previous studies (Nazaroff and Weschler, 2004; Wolkoff et al., 1998) have 63 shown that atmospheric VOC emissions per capita from general purpose cleaners and air 64 fresheners contribute the most to indoor VOC pollution, with values ranging from 200 to 230 mg per day. The intake fraction is defined as the pollutant mass inhaled per unit of pollutant mass 65 66 emitted (Lai et al., 2000). A typical intake fraction from indoor emissions is on the order of 10^{-3} and 10⁻¹, while that from outdoor emissions is on the order of 10⁻⁶ and 10⁻³. These data highlight 67 68 the fact that the proportion of emissions inhaled is higher when emissions occur indoors rather than outdoors (Nazaroff and Weschler, 2004). 69

70 Unexpectedly, the largest indoor sources of terpene VOCs are not usually the recognized, 71 regulated and controlled sources. Indeed, the composition of VOCs emitted from household 72 products has been associated with health hazards to indoor occupants (Dimitroulopoulou et al., 73 2015; Nazaroff and Weschler, 2004; Steinemann, 2009, 2016; Trantallidi et al., 2015; Wolkoff et 74 al., 1998). Nevertheless, limited information is available about the composition, quantification 75 and emission dynamics associated with housekeeping activities in confined environments. 76 Available scientific data are, in most cases, incomparable due to wide variations and 77 heterogeneity in the experimental methodologies used for the evaluation of primary and 78 secondary pollutant emissions from fragranced household products (Angulo et al., 2020). These 79 variations are related to two key parameters: (i) the application protocol (quantity, mode of 80 operation) and (ii) the test environment (air exchange rate (AER), temperature, chamber size, and relative humidity (RH)) (BEUC, 2005; Chesnais and Marchais, 2014; Colombo et al., 1991; 81 82 Delmas et al., 2016; Höllbacher et al., 2017; Nicolas and Chiappini, 2013; Norgaard et al., 2014; 83 Sarwar et al., 2004; Singer et al., 2006a, 2006b; Solal et al., 2014; Uhde and Schulz, 2015). 84 Therefore, comparing the results from one investigation to those of another may be difficult and 85 inaccurate.

Fragranced household products can be formulated with (i) synthetic fragrances, (ii) pure essential oils and (iii) mixtures of synthetic fragrances and essential oils to reduce production costs. Essential oils are used in "naturally" formulated cleaning products either to provide them with a pleasant odor, to hide odors from other chemicals in the formulation, or to enhance their antibacterial performance (Rastogi, 2002; Steinemann, 2009). Essential oils are extracted from plants by water vapor distillation, dry distillation or mechanical extraction, which does not involve temperature changes (Delmas et al., 2016). They usually contain more than 100 different 93 chemicals that compose their characteristic smell, and most of these chemicals are terpenes: 94 monoterpenes, sesquiterpenes, terpene alcohols and terpenoids (denoted TerVOCs) (Babu et al., 95 2002; Lassen et al., 2008; Zuzarte and Salgueiro, 2015). The characteristic smell of an essential 96 oil often originates from its major chemical components; therefore, the typical "scent" of an 97 essential oil directly depends on its chemical composition. In contrast, fragrance mixtures 98 combine differently sourced compounds (synthetic, natural-like or extracted) to replicate a 99 "natural" scent (Teixeira et al., 2013; Zuzarte and Salgueiro, 2015).

100 Although diverse sanitation benefits of essential oil-based cleaning products have been 101 recognized, several risks associated with their use in indoor environments are still questioned. *Is* 102 *there a potential exposure risk to consumers posed by TerVOCs emitted from household* 103 *products*?

104 This study is developed within the framework of the ESSENTIEL research project, 105 aiming to characterize the impact of essential oil-based products on indoor air quality (IAQ) 106 through investigation of their realistic emissions and indoor fate. The objectives of this 107 investigation are to evaluate the correlation between the fragrance chemicals contained in 108 cleaning products and their volatile fraction through determination of the gas-transferred 109 concentration by micro-chamber testing and to characterize and assess their emissions in a 1 m³ 110 experimental chamber reflecting a realistic application scenario. The proposed experimental 111 approach and the results provided in this study are required (i) to propose harmonized and 112 realistic test protocols and (ii) to define risk scenarios and evaluate the human exposure to 113 TerVOCs associated with the use of essential oil-based cleaning products.

114

116

117 2 MATERIAL AND METHODS

118 2.1 Cleaning product benchmarking

119 To frame the approach of the present study, it is necessary to define the type of cleaning 120 products considered. Essential oil-based cleaning products are defined in this work as naturally 121 scented and certified organic products used in a nonpermanent way in indoor environments for 122 housekeeping purposes. For their selection, a benchmark analysis was performed among cleaners 123 certified as ecological products by different European labels. A total of 108 essential oil-based 124 products were identified from the European market. Among them, 6 representative cleaning 125 products were selected in the framework of this work and classified by category, i.e., intended 126 use: (i) 2 kitchen degreasers, (ii) 2 general (multiuse) cleaners, (iii) 1 surface cleaner, and (iv) 1 127 glass cleaner. This selection considered (i) diverse intended uses to assess the effect of different 128 solvent formulations, (ii) a variety of application modes and (iii) a diversity of essential oils used 129 as natural fragrances in the formulation of the cleaning products. The selected cleaning products 130 were purchased from environmentally friendly and ecologically conscious retail stores in France.

Importantly, the solvent matrix composition could vary from one product to another in terms of the organic content (% ethanol) or the presence of texturing agents (gums). The contents of the fragrance chemicals and their volatile fractions were characterized for the six selected cleaning products, whereas only three products were considered for the 1 m³ emission test. Table 1 details the characteristics of the six selected products.

					C	haracteriz	zation		
						performed			
Product	Product category	Diffusion mode	Natural fragrance ¹	General product formulation ²	Liquid composition	Performance Performance <t< th=""><th>Realistic emissions (1 m³ test chamber)</th></t<>	Realistic emissions (1 m ³ test chamber)		
KC – 1	Kitchen	Trigger spray	Lemon oil	< 5 % surfactant (anionic and nonanionic), citrus oil, citric acid, water, methylisothiazolone, 5-chloro-2-methyl-4-isothiazolin-3-one, nitrilotriacetic acid trisodium salt monohydrate	x	X			
KC – 2	cleaner		Eucalyptus oil	< 5 % surfactant (nonanionic), essential oils (including eucalyptus oil ²), water, alcohol ² , preservatives, acid correctors	х	X	Х		
MC – 1	Multiuse	Liquid	Citrus oil	< 5 % surfactant (anionic and nonanionic), water, alcohol, citrus oil ² , citric acid	x	Х	Х		
MC – 2 cleaner		Liquid	Lemon oil	< 5 % surfactant (anionic and nonanionic), water, alcohol, lemon oil ² , lactic acid, fatty acids, sodium citrate, glyceryl caprylate	x	х			
SC – 1	Surface cleaner	Trigger spray	Lavender oil	70 % ethanol ² , < 1 % lavender oil ² , < 1 % sage oil ² , water	х	x	x		
GC - 1	Glass cleaner	Trigger spray	Eucalyptus oil	> 30 % water, 5 – 15 % alcohol ² , < 5 % surfactant (anionic and nonanionic), citric acid, essential oils ² (including eucalyptus oil), amphoteric surfactants	x	х			

1: Certified organically grown

139 2: Based on information given by the manufacturer

141 2.2 Characterization of the liquid composition

Several extraction parameters were optimized to maximize the extraction of terpenes: (i) the organic extraction solvent, (ii) the mass ratio of the cleaning product to the solvent, (iii) the contact time between the solvent and the cleaning product, and (iv) the number of consecutive extractions. The extraction procedure and the analytical methods and parameters are detailed in a supplementary information sile (SI file).

147

148 **2.3 Determination of the gas-transferred concentration by micro-chamber testing**

149

150 2.3.1 Micro-chamber description

151 The liquid-to-gas phase transfer capacity of each terpene identified in the cleaning products is 152 defined as the gas-transferred concentration and was determined by using a stainless steel 153 cylindrical micro-chamber with a 44 mL volume (M-CTE-120 Markes International®). The 154 device was equipped with restrictors allowing the selection of a low-flow range and a high-flow 155 range of 10 – 70 mL/min and 50 – 500 mL/min, respectively. In this work, the low-flow range 156 was used and set at 50 mL/min. The dry air generation is ensured by an air compressor combined 157 with membrane for humidity removal. Before entering the micro chamber, the dry air is purified 158 by an activated carbon filter in order to remove particles and trace pollutants. The top of the 159 chamber acts as a door and is sealed with a silicon gasket for leak control. After optimization, the 160 temperature and air flow were set at 40 °C and 50 mL/min, respectively. Dry air flow enters each 161 micro-chamber through the lid and is preheated to the micro-chamber temperature of 40 °C. A 162 total volume of 50 \pm 1 μ L of each selected fragranced cleaner was introduced into the micro-163 chamber. Blank measurements were performed to determine the background levels of VOCs in 164 the chamber outlet before running each set of experiments. Note that the mean concentration of 165 blank measurements in the micro-chamber did not exceed the quantification limits for the 166 background concentrations of the individual target VOCs. The detailed characteristics of the 167 micro-chamber are presented in Fig. 1a.

168



Fig. 1. (a) Schematic of the M-CTE-120 micro-chamber from Markes International®. (b)
Schematic of the 1 m³ emission chamber VCE1000 Classic from Vötsch.

171

172 2.3.2 Analytical strategy

The TerVOCs emitted from the investigated products inside each micro-chamber were monitored using an off-line device for their identification and quantification. Subsequently, two consecutive Tenax TA[®] cartridges collected volatilized compounds at the device outlet for 15 minutes. The total sampled volume was 0.6 L. Afterward, these samples were desorbed at 280 °C under a helium flow of 50 mL/min using a PerkinElmer[®] thermal desorber (model: Turbo Matrix 350). Then, the desorbed compounds were thermally transferred via the helium flow and refocused on a Carbotrap B/C trap at 5 °C with an outlet split flow of 70 mL/min. The gas 180 chromatographic analyses were performed using a 7890A instrument from Agilent Technologies 181 equipped with a Restek 10189 chromatographic column (60 m x 320 μ m, 1 μ m film thickness) 182 connected to two different detectors: (i) an FID and (ii) an MS (5975B inert MSD) from Agilent 183 Technologies. The typical detection limit of this instrument for hydrocarbon VOCs with the 184 abovementioned sampling conditions is 0.5 μ g/m³. Calibration for the identified and quantified 185 TerVOCs was achieved by individual liquid doping of the high-purity certified standards from 186 Sigma-Aldrich[®] on Tenax TA® absorbent tubes.

187

188 2.4 Emission chamber test: simulation of a realistic scenario – correlation method for a
 189 realistically sized room

190

191 2.4.1 Emission chamber parameters

The experiments reported in this paper were conducted in an experimental chamber with a 1 m^3 192 193 volume (Vötsch VCE1000 Classic) that complied with the ISO 16000-9 (2006) standards. The 194 chamber was operated at a controlled temperature, humidity and air exchange rate (AER) of $23 \pm$ 1 °C, 50 ± 5 % and 0.3 h⁻¹ ± 0.05, respectively. The humidity and temperature were set according 195 to ISO 16000-9. The established AER corresponds to the 25th percentile reported in French 196 197 dwellings by the Indoor Air Quality Observatory (OQAI) (Kirchner et al., 2001; Lucas et al., 198 2009). Detailed characteristics of the experimental chamber are presented in Fig. 1b. Before 199 loading the test chamber with the selected product, blank measurements were performed to 200 determine background levels of TerVOCs and oxygenated volatile organic compounds (OVOCs). Note that the mean concentration determined from blank measurements in the 201

202 experimental chamber did not exceed the standardized background concentrations of individual203 VOCs.

204

205 2.4.2 Definition of a realistic scenario for the use of essential oil-based household products

The assessment of TerVOC emissions in the experimental test chamber has been primarily focused on *surface cleaning scenarios*. The product application procedure must be based on the typical consumer use pattern to mimic realistic application in the evaluation of cleaning product emissions. The key parameters required to define a specific and standardized product application procedure are (i) the quantity of product to apply and (ii) the surface to clean. These parameters were estimated from the loading factor and the final application yield of the cleaning product after wiping, called *product yield* is this study.

213

214 *Loading factor*

215 The loading factor is defined as the ratio between the emissive surface area, i.e., the cleaned area, 216 and the chamber volume. This is the key parameter to transfer the real application scenario at 217 scale 1:1 to the 1m3 test chamber. It has to be keot constant between both chamber volume as 218 reported in Table 2. Conventionally, a reference room is used to extrapolate measured VOC 219 concentrations in test chambers with small volumes when assessing human exposure. The 220 reference room considered for the study is the IRINA experimental room characterized by a floor 221 area of 12 m², a ceiling height of 2.5 m and a volume of 40 m³. (Harb et al., 2016) In regard to the product application for surface cleaning, a typical table area of 2 m² was considered in the 222 reference room. It results in a loading factor of $0.05 \text{ m}^2/\text{m}^3$. For the correlation between the 1 m³ 223 emission test chamber and the 40 m³ reference room, the loading factor must be identical (Table 224

225 2). Based on this consideration, the *surface cleaning scenario* was defined and the surface to 226 clean was determined for the 1 m³ emission test chamber as reported in Table 2, along with the 227 corresponding masses of cleaning products. Table 2.

Table 2. Application parameters for the surface cleaning scenario: reference values from the 40

m3 room for the product yield and loading factor and subsequent quantities of products to be

230 applied in both chambers 40 m^3 and 1m^3 .

Application parameters to mimic a 2 m^2 surface cleaning in a 40 m^3 room to the 1 m^3 test chamber						
		(40 m ³)	$1 m^3$			
		REFERENCE ROOM	TEST CHAMBER			
SURFACE TO CLEAN		2 m ²	$0.05 m^2$			
LOADING FACTOR		0.05	0.05			
(m ² /m ³)		0.05	0.05			
	SC – 1	8.7 (g.n	1-2)			
PRODUCT YIELD	MC -1	7.2 (g.n	1-2)			
	KC - 2	12.0 (g.r	n ⁻²)			
	SC – 1 18.0 g		3.2 g			
MASS APPLIED	MC -1	15.0 g	4.4 g			
	KC - 2	24.0 g	2.7 g			

231

232 <u>Product yield</u>

The product yield is defined as the effective mass of product remaining on a 1 m² surface; it includes the total mass applied balanced by the losses induced by wiping. This parameter was estimated for each selected cleaning product. First, the average amount of cleaning product required to clean 1 m² of surface was determined from the cleaning of a 1 m² surface by 10 different operators. Subsequently, the average mass of each product dispersed by a single spray from each trigger spray mechanism was determined for a set of 15 successive sprays performed by the same operator. Then the mass of product lost on wipes is determined by weighing. This
procedure allows the estimation of the effective mass of product remaining on a 1 m² surface.
The mass of product required for the *surface cleaning scenario* in the 1 m³ emission test chamber
is determined from this product yield by proportionality.

For each experiment, the calculated mass of product was evenly drizzled or sprayed on a 0.05 m² stainless steel surface placed at the center of the 1 m³ experimental chamber. Once the simulation of the cleaning activity was completed, the experimental chamber remained closed during the emission monitoring. For each cleaning product, a set of three experiments was performed to evaluate the repeatability of the experimental protocol. Additionally, during the experiment, t = 0 corresponded to the time when the application of the cleaning product was completed inside the chamber.

250 2.4.3 Sampling and analytical parameters

Regarding the analytical methodology, the temporal dynamics of the TerVOC and OVOC concentrations inside the experimental chamber were monitored using off-line devices that allowed their quantification with high temporal resolution. Several preliminary tests were performed to optimize the experiment duration depending on the cleaning product. On the basis of these preliminary results, the duration of a typical emission experiment was 5 hours.

256 Off-line sampling was performed according to ISO 16000-3 and 16000-6 by using (i) 257 Tenax TA[®] cartridges for terpene compounds and (ii) 2,4-dinitrophenylhydrazine (DNPH)-258 impregnated silica cartridges (Sep-Pak DNPH-Silica Plus Short Cartridges, Waters) for carbonyl 259 compounds. Sampling was performed using a pump (KNF[®]) connected to a mass flow controller 260 with specific flow rates and durations optimized for each cleaning product tested, as described in 261 Table 3.

Evaluation of emissions from cleaning products						
	Sampling device	Terpenes (TerVOCs): Tenax TA [®] adsorbent Carbonyl Compounds (OVOCs): DNPH cartridges				
Du	ration of experiment* (h)	5 h				
Sampling	TerVOCs	0.150 L/min				
flow*	Carbonyl compounds	0.800 L/min				
Sampling du	ration (min) and time interval (h)*	 From 0 to 1 hour; continuous sampling for 15 minutes; total of 4 samples From 1 – 5 hour; continuous sampling for 60 minutes; total of 4 samples 				

262 **Table 3.** Experimental protocol and optimized parameters for the off-line sampling systems.

263 *Experimental parameters that were optimized

264

265 The analytical protocol to quantify TerVOCs was the same as that reported in section 2.3 266 for the gas-transferred concentration determination. In contrast, derivatized carbonyl compounds 267 (OVOCs) were extracted from DNPH cartridges with 3 mL of acetonitrile and analyzed with a 268 Thermo Dionex Ultimate U3000 liquid chromatograph. Compounds were eluted on an Acclaim 269 RSLC Carbonyl column (2.1 x 150 mm) and detected by RS variable-wavelength UV 270 absorption. The acquisition was performed at 365 nm wavelength. Calibration for the carbonyl 271 compounds was achieved using high-purity certified standard solutions (Aldehyde/Ketone-272 DNPH Stock Standard-13). Under these conditions, the detection limit for the carbonyl 273 compounds was 0.01 ppb.

274

275 **3 RESULTS AND DISCUSSION**

276

277 3.1 Chemical composition: terpene (TerVOC) content of natural, certified organic cleaning
278 products

279 The terpene contents of the six selected cleaning products are listed in Table 4. Note that of the 280 identified compounds, the predominant terpenes are written in bold. The most frequently 281 identified terpenes were limonene, linalool, and α -terpineol, which were present in all the 282 evaluated cleaning products. To date, five studies have assessed the presence of fragrance 283 chemicals in cleaning product formulations on the European market. Among the 121 cleaning 284 products evaluated, limonene and linalool have been reported with the highest occurrence rates: 285 84.2 % and 60.8 %, respectively (Nicolas and Chiappini, 2013; Pors and Fuhlendorff, 2003; 286 Rastogi, 2002; Rastogi et al., 2001; Uhde and Schulz, 2015). Worldwide, the most commonly 287 used essential oils in household product formulations are citrus oil, lavender oil, pine oil, 288 eucalyptus oil, tea tree oil and rose oil. In contrast, several terpene derivatives, such as camphor 289 and bergamol, detected in SC-1 and KC-2, have been more rarely reported (Ezendam et al., 290 2009; Huang et al., 2011; Jo et al., 2008; Kwon et al., 2007).

291 **Table 4.** Liquid composition (expressed in μg of terpene per g of product: $\mu g/g$) of the six

selected cleaning products and their occurrence rate in the literature. NB: the mass concentration

293 of the predominant TerVOCs in each cleaning product is written in bold.

	Occurrence rate (%)						
	in the literature						
Identified Terpenes	MC -1	MC -2	SC - 1	KC - 1	KC – 2	GC - 1	[121 cleaning products] (Nicolas and Chiappini, 2013: Rastori, 2002;
Diffusion mode	Liquid	Liquid	Spray	Spray	Spray	Spray	Rastogi et al., 2001; Uhde and Schulz, 2015)
α-Pinene	24.2 ± 6.2	23.3 ± 4.8	37.6 ± 5.0	-	35.6 ± 3.8	-	36 %
Limonene	852.9 ± 32.9	472.0 ± 8.2	25.5 ± 0.7	6.3 ± 0.5	173.3 ± 36.1	2.2 ± 0.3	84 %
Linalool	10.2 ± 0.6	6.0 ± 0.9	390.0 ± 5.0	6.5 ± 0.5	4.3 ± 0.7	1.5 ± 0.3	61 %

Eucalyptol	424.1 ± 37.0	-	213.4 ± 4.7	-	2230.8 ± 71.4	18.0 ± 1.5	38 %
Cymene	158.7 ± 23.9	8.5 ± 0.2	-	-	76.2 ± 11.5	-	26 %
Bergamol	-	-	279.0 ± 2.0	-	-	-	NS
Camphor	-	-	256.8 ± 2.5	-	19.3 ± 2.5	-	NS
β-Pinene	69.9 ± 3.6	146.2 ± 5.0	21.8 ± 0.4	3.4 ± 0.4	3.1 ± 1.4	-	40 %
γ-Terpinene	15.9 ± 2.6	61.4 ± 5.7	2.6 ± 0.2	-	7.5 ± 0.5	-	20 %
α-Terpineol	29.7 ± 7.4	2.9 ± 0.8	16.4 ± 0.5	10.0 ± 0.3	18.2 ± 0.8	12.8 ± 2.0	NS
Menthol	-	-	-	1.0 ± 0.3	570.9 ± 25.2	3.3 ± 0.7	NS
Other TerVOCs	121.5 ± 15.8	79.1 ± 7.4	247.9 + 6.9	10.3 ± 0.6	77.2 ± 18.5	1.30 ± 0.3	-
TOTAL TerVOCs	1682.8± 131.3	776.0 ± 28.1	1453.7 ± 22.6	37.6 ± 2.5	3180.7 ± 200.5	39.1±4.5	

294

295 3.1.1 Total TerVOC mass concentration

296 Regarding the total terpene content in household products, the mass concentrations varied 297 widely, ranging from 37.6 \pm 2.5 to 3180.7 \pm 200.5 μ g/g (of product). Nevertheless, these 298 concentrations accounted for only 0.01 % to 0.17 % w/w of the total composition of the selected 299 products, as shown in Table 4. Sarwar et al. (2004) reported the quantification of TerVOCs in 300 four different types of cleaning products used as floor cleaners and general purpose cleaners. The 301 main detected terpenes were α -pinene, β -pinene, β -carene, limonene and α -terpinene, with 302 individual mass concentrations ranging from 0.2 % w/w to 2.0 % w/w. The proportions of 303 fragrance chemicals in industrial formulations of cleaning products do not exceed 5.0 % w/w 304 (Ezendam et al., 2009; Rastogi, 2002; Steinemann, 2009; Steinemann et al., 2011).

305

306 3.1.2 Individual mass concentration of TerVOCs

307 Among the selected cleaning products, a total of 27 terpenes were detected: (i) 14 monoterpenes, 308 (ii) 8 terpene alcohols, (iii) 4 terpene derivatives, and (iv) 1 sesquiterpene. Per product, the 309 diversity of odorous chemicals varied from 6 to 20 different species. Furthermore, all tested products, except for KC - 1, showed a correlation between the predominant terpene detected and 310 311 the essential oil indicated by the manufacturer. KC - 1 was reportedly formulated with lemon oil; 312 however, the major terpene was a-terpineol instead of limonene. In terms of the product 313 categories, limonene was the predominant terpene contained in the multiuse cleaners, both 314 fragranced with citrus oils. In the kitchen cleaners tested, the main detected terpene differed: 315 eucalyptol in KC – 2 and α -terpineol in KC – 1. Concerning the mass concentration of terpenes, 316 the predominant species in the selected products were limonene, linalool, eucalyptol, and α -317 terpineol, detected at concentrations ranging from $10.0 \pm 0.3 \,\mu$ g/g to $2230.8 \pm 71.4 \,\mu$ g/g.

318 The chemical composition of a cleaning product might vary widely depending on its 319 usage purpose and diffusion mode. For instance, when a cleaning product emphasizes a 320 disinfecting property, complementary chemicals are added to its formulation to suppress or 321 inhibit microbial activity. In so-called "green" cleaning product formulations, specific essential 322 oils might be added to increase the concentration of terpenes with antibacterial and antiseptic 323 activity, such as eucalyptol and geraniol. Therefore, no correlation was evidenced between the 324 diffusion mode of the selected cleaning products and their total terpene mass concentration. This 325 finding is suggested to result from the intrinsic industrial formulations designed to achieve a 326 particular performance.

Finally, the contrasting terpene contents bring up questions about the intrinsic emission potential of the cleaning products. The diversity in the constituent volatility affects the emission dynamics associated with the cleaning activity. *Does a high terpene content necessarily imply high emission levels? What is the effective amount of terpenes eventually transferred to the gas phase? What is the impact of the cleaning product matrix on the gas phase transfer? How long is the user impacted by the emissions?*

To provide key elements needed to answer these questions, a screening of their ability to be transferred from the liquid to the gas phase, defined in this paper as the gas-transferred concentration, was performed to identify the emission potential of each cleaning product.

336

337 3.2 Gas-transferred concentration vs. liquid composition

338 3.2.1 Total gas-transferred concentration

339 The total gas-transferred concentration of terpenes corresponds to the sum of the concentrations, 340 subsequently expressed in $\mu g/m^3$, of terpenes collected at the outlet of the micro-chamber setup. 341 This concentration can be used to assess the ability of a given cleaning product to release 342 terpenes to the gas phase. Comparison of the six selected products revealed very different total 343 gas-transferred concentrations, ranging from 125 ± 15 to $85\ 225 \pm 5\ 500\ \mu g/m^3$. The glass 344 cleaner GC - 1 was the least emissive product, with a total gas-transferred concentration of 125 345 \pm 15 µg/m³, while the gas-transferred concentrations of the surface cleaner SC – 1 and the 346 kitchen cleaner KC – 2 were higher by 2 orders of magnitude. These two products transferred 347 analogous total terpene concentrations to the gas phase, considering the standard deviation: $85\ 000 \pm 5\ 500\ \mu\text{g/m}^3$ and $81\ 000 \pm 12\ 000\ \mu\text{g/m}^3$, respectively. 348

349 Fig. 2 shows the correlation between the total terpene mass concentrations in the liquid 350 phase of the selected products (µg/g of product) and the total gas-transferred concentrations of TerVOCs ($\mu g/m^3$) for the same products. For the multiuse cleaners (MC - 1 and MC - 2), the 351 352 volatile concentrations reached equivalent levels of 27 000 μ g/m³, but their total terpene mass 353 concentrations in the liquid phase differed by a concentration ratio of 2:1. The pattern between 354 the surface cleaner SC - 1 and the kitchen cleaner KC - 2 was similar, with gas-transferred concentrations that both reached approximately $80\,000 \,\mu g/m^3$, considering the standard 355 356 deviation, but a terpene content of the surface cleaner SC - 1 that was half that of the kitchen 357 cleaner KC – 2 ($3200 \pm 270 \mu g/g$). In contrast, the two household products SC – 1 and MC – 1 358 had equivalent terpene mass contents but gas-transferred concentrations that differed by a factor 359 of 3. Consequently, no direct correlation was evidenced between the total terpene mass content 360 and the total gas-transferred concentration among the six selected products. Therefore, the 361 amount of terpenes emitted by a given product cannot be estimated from its liquid terpene 362 content, and emission tests are required.



Fig. 2. Total TerVOC gas-transferred concentration from micro-chamber testing ($\mu g/m^3$) as a function of the total terpene mass concentration in the liquid form ($\mu g/g$) for the six selected cleaning products (T = 40 °C, dry air flow = 50 mL/min, micro-chamber volume = 44 mL).

366

367 3.2.2 Individual gas-transferred concentrations

368 Only 19 terpene molecules from the 27 TerVOCs contained in the cleaning products were 369 identified in the gas phase during the micro-chamber evaluation, and the number of emitted 370 terpenes varied from 1 to 14 per cleaning product. Table 5 lists the (i) volatile/liquid fraction 371 concentration ratio (V/L) of each cleaning product and (ii) various physical and chemical 372 properties of the individual terpene molecules. For discussion purposes, in this paper, the V/L 373 concentration ratio is defined as the ratio of an individual gas-transferred concentration to its 374 mass fraction in the liquid phase for each identified terpene. Higher is the V/L value, greater is 375 the ability of the considered molecule to be transferred from the liquid to the gas phase.

376

Table 5. Comparison of the total TerVOC gas-transferred concentrations (T = 40 °C, dry air flow = 50 mL/min, micro-chamber volume = 44 mL) with the total TerVOC mass fractions in the liquid form for each cleaning product, individually. NB: The physical and chemical properties of identified terpenes (VP, boiling point and molar mass) from the literature are detailed.

	RATIO – Gas-transferred concentration/Mass fraction (V/L) -						Vapor pressure	
TERPENES			(thi	(VP) from the	Boiling point			
	MC - 1	MC -2	SC - 1	GC – 1	KC - 1	KC - 2	literature (Pa)*	(°C)
α-Pinene	1.15	1.39	-	-	-	1.27	529- 599,	156
Limonene	1.15	1.02	0.68	-	3.99	1.51	189-213	176

Linalool	-	0.47	0.97	-	-	1.17	20-27	198
Eucalyptol	1.27	-	1.13	2.17	-	0.80	230-260	176
Cymene	0.58	0.99	-	-	-	1.73	192-195	177
Bergamol	-	-	1.15	-	-	-	NS	220
Camphor	-	-	1.25	-	-	1.02	28	209
β-Pinene	0.49	1.02	0.53	-	2.83	1.12	391-400	166
γ-Terpinene	0.17	1.19	0.64	-	-	1.99	103-145	183
α-Terpineol	-	-	1.31	-	-	-	**	175
Menthol	-	-	-	-	-	1.49	11-18	212

382 NS: Not specified in the literature; *: (Harb et al., 2016; ISO 16000-9, 2006; López and Gómez, 2000; Lucas et al.,

383 2009; Rastogi et al., 2001; Teixeira et al., 2013 ; Espinoza et al., 1999; Hoskovec et al., 2005; Štejfa et at., 2014);

384 **Vapor pressure near 0 Pa

Among the physical and chemical properties of TerVOCs, the saturation vapor pressure (VP) of a pure molecule (expressed in Pa) is an inherent property required for the investigation of vapor-liquid equilibrium and a key parameter for emission assessment. It is defined as the pressure exerted by a vapor in equilibrium with its pure condensed phase at a given temperature in a closed system. VPs have been experimentally determined in the literature for most TerVOCs, and the corresponding values are given in Table 5. The reported VPs of terpenes are highly varied, ranging from 0.3 Pa for α -terpineol to 599 Pa for α -pinene.

As shown in Table 5, α -pinene had a V/L ratio higher than 1, ranging from 1.15 to 1.39 among the cleaning products in which this molecule was detected. This suggests a significant ability of α -pinene to be transferred to the gas phase independent of the solvent matrix composition and could be related to its high VP of 599 Pa, the highest among all identified terpenes. In contrast, for the other compounds, the relation between the VP and V/L ratio was not predictable. Unique behaviors were observed for different terpenes: (i) the V/L ratio of linalool, with low volatility (VP values below 30 Pa), differed greatly depending on the cleaning product,

399 ranging from 0.47 for MC – 2 to 1.17 for KC – 2, while (ii) V/L ratio of β -pinene, with chemical 400 and physical properties analogous to those of α -pinene, widely varied from 0.49 for MC – 1 and 401 2.83 for KC - 1. Thus, for most terpene species, the transfer to the gas phase is not exclusively 402 driven by the intrinsic properties of the pure molecule but more by the solvent properties. The 403 proportion of organic solvent and the presence of texturing agents in the aqueous media of a 404 cleaning product play key roles in flavor release (Jouquand et al., 2008). Interactions between 405 flavor compounds and a matrix have been extensively studied in the field of food sciences 406 (Guichard, 2002). The determination of the gas-liquid partition coefficient under equilibrated 407 conditions specific to each VOC/matrix pair could be used to explain the various observed 408 behaviors (Ettre et al., 1993).

409 Consequently, terpene emissions from essential oil-based household cleaning products 410 cannot be directly predicted from the liquid composition of the product. Instead, the 411 concentrations of TerVOC species released from such products could be governed by three main 412 factors: (i) the inherent volatility of the TerVOCs, (ii) the chemical affinities between the 413 TerVOCs and other compounds in the formulations and (iii) the mass concentrations of terpenes 414 in the liquid phase. In the micro-chamber tests, the major compounds emitted and transferred to 415 the gas phase were identified, but this experimental approach is not a substitute for emission 416 testing using experimental chambers of conventional size. Moreover, micro-chamber tests are 417 not conducted under realistic conditions of temperature, humidity and air velocity, but under 418 conditions which potentially enhance the transfer from the product to the gas phase. Next, 419 primary emissions were investigated from a representative cleaning product for each of the three 420 product categories of the six selected products.

422 **3.3** Emission of TerVOCs under realistic application conditions: $1 m^3$ emission test chamber

423 To assess the primary emissions associated with the application of essential oil-based products, 424 one representative product from each category was selected. This selection was based on the previously discussed results regarding the correlation between the gas-transferred concentration 425 426 and the liquid content of TerVOCs. The cleaning product in each category attesting the highest 427 ratio between its gas-transferred and liquid concentrations (V/L) was selected: (i) the surface 428 cleaner SC - 1, (ii) the multiuse cleaner MC - 1, and (iii) the kitchen cleaner KC - 2. Regarding 429 the diversity of the species emitted, 19 out of the 23 TerVOCs contained in the three liquid 430 cleaners were identified in the gas phase. Fig. 3b shows the contributions of the top three emitted 431 terpenes to the total TerVOC concentration after the separate application of the selected cleaners.



Fig. 3. (a) Temporal evolution of the total TerVOC concentration during cleaning with SC – 1 (black symbols), MC – 2 (dark gray symbols) and KC – 2 (light gray symbols) (T = 23 °C, RH = 50 %, air renewal rate = 0.3 h⁻¹, chamber volume = 1 m³). (b) Peak concentration of total TerVOCs and the contributions of the 3 predominant terpenes after the application of SC – 1, MC – 1 and KC – 2.

438

439 3.3.1 Emission Profile of total TerVOCs

The temporal profiles of the total TerVOC concentrations in SC - 1, KC - 2 and MC - 1, 440 reported in Fig. 3a, are characterized by the three typical phases of transient emission: (i) a 441 442 sudden increase in the total TerVOC concentration, reflecting the rapid transfer of terpenes from 443 the applied cleaning product layer to the gas phase until a peak concentration is reached (< 30 444 minutes); (ii) a long decrease, corresponding to the gradual depletion of the VOC source and 445 removal of VOCs from the experimental chamber; and (iii) a final decrease exclusively 446 associated with the evacuation of the gas phase terpenes by air exchange and possible deposition 447 on the inner walls of the experimental chamber. Note that in any of the three phases, possible 448 losses of terpenes from deposition on the chamber walls must be considered. As observed in Fig. 449 3a, SC – 1 and MC – 1 had similar, considering their respective standard deviations, peak total 450 TerVOC concentrations of approximately 300 ppb within a half-hour after application. The 451 maximum emitted concentration of TerVOCs KC-2 (160 ppb) was lower than those of the other 452 two cleaning products but was reached at an analogous time. However, considering the total terpene composition in the liquid phase (section 2.1), KC - 2 was characterized by the highest 453 454 mass concentration of TerVOCs (3200 \pm 200 μ g/g) among the three cleaners. These results 455 confirm the absence of correlation between the liquid content of terpenes and the resulting 456 concentrations of terpenes in the 1 m³ emission test chamber. Based on the investigated products, 457 the temporal emission dynamics of essential oil-based cleaning products cannot be directly 458 predicted from their liquid composition.

In comparison with other indoor terpene sources, primary emissions from a wood-basedbuilding product evaluated by Harb et al. (2018) produced a peak concentration of total

461 TerVOCs of 31 ppb under realistic conditions. Brown (1999) identified similar emitted 462 concentrations from a 16-mm pine softwood particleboard. Thus, the contribution to the indoor 463 total concentration of TerVOCs made by cleaning activities may transiently exceed that made by 464 wood-based materials. However, emissions from cleaning products are characterized by temporal dynamics different from those of indoor material emissions; the former emissions mostly act as 465 466 punctual or transient sources of pollutants. Thus, the cumulative exposure to TerVOCs from 467 cleaning products is directly related to cleaning frequency and human factors. This behavior 468 contrasts with wood-based materials, which mostly act as long-term and continuous emission 469 sources.

- 470 3.3.2 Individual emission profiles of TerVOC
- 471





The individual emissions of 9 monoterpenes, 7 terpene alcohols, 1 oxygenated terpene, and 1 sesquiterpene were quantified. SC – 1 was characterized by the largest diversity of terpenes, since it emitted a total of 16 different terpene molecules. Fig. 4 shows the individual profiles of the predominantly emitted terpene species. The individual profiles were characterized by the same three phases observed in the emission profiles of the total TerVOCs (Fig. 3a). Nonetheless, some differences can be observed among the tested products.

478 The predominant terpenes released from *surface cleaner* SC - 1 were linalool, eucalyptol 479 and cymene, which had peak concentrations of 85 ± 10 ppb, 50 ± 5 ppb and 55 ± 5 ppb, 480 respectively. Their cumulative concentration accounted for 47.6 % of the peak total TerVOC 481 concentration. Interestingly, regarding the emission kinetics, despite these compounds showing 482 contrasting physical and chemical properties (Table 5), their peak concentrations were reached at 483 equivalent emission times, i.e., nearly 25 minutes after the cleaning activity was completed (Fig. 484 4a). This observation suggests that determinants other than the physical and chemical properties 485 of individual TerVOCs are involved in the emission of TerVOCs during cleaning. For instance, in the liquid composition of SC - 1, a significant concentration of ethanol of 70 % w/w was 486

487 detected. In general, in their formulations, surface cleaners contain water and various water-488 miscible solvents, i.e., alcohols and glycols, which are included to (i) enhance the "fast-dry 489 effect" and (ii) dissolve grease on the surface being cleaned (Magnano et al., 2009; Missia et al., 490 2012; Steinemann et al., 2011; Wolkoff et al., 1998). The ethanol in surface cleaner SC – 1 was 491 probably included for those purposes and may have accelerated the emission kinetics of 492 TerVOCs due to the fast drying rate.

493 The major terpenes emitted from kitchen cleaner KC - 2 were eucalyptol, menthol, and 494 limonene, as reported in Fig. 4b. Their respective peak concentrations were 110 ± 10 ppb, 38 ± 5 495 ppb, and 7 \pm 1 ppb, contributing to 96 % w/w of the total TerVOC peak concentration. 496 Analogous times (15 minutes) were observed for the peak concentrations of eucalyptol and 497 limonene (Fig. 4b). Noticeably, the emission profile of eucalyptol was characterized by a sharp 498 increase in its concentration and a subsequent clearly identifiable maximum concentration ca. 15 499 minutes. The emission kinetics of eucalyptol contrasts with those of menthol, which had a peak 500 concentration at 30 minutes after the cleaning product was applied. The lower VP of menthol of 501 approximately 18 Pa may explain this different behavior.

502 In the case of the *multiuse cleaner* MC - 1, limonene, eucalyptol and cymene were the 503 main terpenes identified in the gas phase. As shown in Fig. 4c, limonene and eucalyptol had peak 504 concentrations of approximately 145 ppb. However, despite their similar VPs, several differences can be noted in the emission profiles of these terpenes. Limonene and eucalyptol were 505 506 characterized by a sharp increase up to their peak concentrations within 8 minutes, and 90 507 minutes after the cleaning activity was completed, their gas phase concentrations still accounted 508 for more than 60 % of their peak concentrations. This behavior suggests that after the intense 509 emission within the first minutes post cleaning, their emissions may continue over a long time 510 scale. This phenomenon can be evaluated through the determination of individual TerVOC 511 emission rates as a function of time. In contrast, cymene presents a concentration profile 512 characterized by a broad emission peak corresponding to a low peak concentration but possibly 513 emission over a longer time scale.

514 Comparing the emission dynamics of eucalyptol (commonly released from all cleaners), 515 rapid emission kinetics were observed for MC - 1, from which the maximum emitted 516 concentration of eucalyptol was reached within the first 8 minutes after its application. The peak 517 eucalyptol concentration (140 ppb) emitted from this product (MC - 1) was higher than that from 518 the other tested products; however, the liquid form contained only $424 \mu g/g$ eucalyptol. In 519 contrast, slower eucalyptol emission dynamics were observed from KC - 2, with the peak 520 concentration occurring nearly 23 minutes after the application of the kitchen cleaner. KC - 2521 contained the highest concentration (2230 µg/g) of eucalyptol in its liquid phase, but its 522 maximum emitted eucalyptol concentration was only 110 ppb. These observations suggest that 523 the liquid concentration of individual terpene molecules is not the only key factor driving the 524 transfer from the liquid to the gas phase. To assess the emission of individual TerVOCs from 525 each cleaner, the mass emission rate was calculated from the concentration profiles and assessed 526 in the next section.

527

528 3.4 Estimation of TerVOC mass emission rates from monitored concentration profiles

In this study, the emission rate of a cleaning product is defined as the mass of volatile compound emitted per gram of applied product per unit time for a given duration t from the beginning of the emission. The estimated mass emission rate from a source is of major importance since (i) it provides key information to understand and describe the emission from an indoor source of pollutants; (ii) it is a representative parameter that can be extrapolated to realistic cases, allowing
the prediction of pollutant emissions in other scenarios; and (iii) it is required for the evaluation
of human exposure and indoor quality control technologies.

Indoor pollutant concentrations are governed by various processes, including ventilation, pollutant emission, and pollutant transformation, such as uptake or chemical interaction. The same phenomena could be observed in an emission test chamber. Therefore, it is necessary to address the fate of pollutants considering the contribution of each process separately. In a typical indoor environment, the variation in the concentration of an individual VOC is driven by the mass conservation equation shown in Eq. 1.



542

543 In controlled environments, such as the emission chamber used for our experiments, 544 several processes included in Eq. 1 can be ruled out because of the design and operation of the 545 chamber. First, the concentration of one of the main oxidants in the experimental chamber was 546 continuously monitored during experiments; the ozone level remained lower than the detection 547 limit of the ozone analyzer (0.4 ppb) during all experiments, suggesting that the contribution of 548 ozone-induced homogeneous and heterogeneous reactions can be neglected. Harb et al. (2016) 549 and Haghighat and De Bellis (1998) evidenced that stainless steel is the most common chamber 550 material in reviewed publications due to its inert properties. The use of stainless steel prevents 551 the reaction of deposited TerVOCs with the inner material surface of the chamber. This is 552 supported by the fact that no terpenes other than those monitored in the liquid composition and 553 no carbonyls other than those reported in the literature were detected in the gas phase in the experimental chamber. Therefore, surface reactivity on stainless steel was disregarded.
Additionally, desorption is endothermic. Moreover, in a temperature-controlled environment, the
sorption of TerVOCs is suggested to be irreversible, and desorption is considered negligible.

Thus, in the emission experiments with the cleaning products, the TerVOC concentrations in the emission test chamber were predominantly controlled by (i) the air exchange, (ii) the emission rate from the TerVOC sources, and (iii) the loss due to sorption to the inner walls of the chamber (k_D). Therefore, *Eq. 2* describes the resulting pollutant concentration [X] in the experimental chamber. Determining the TerVOC emission rates from their monitored concentration profiles requires knowledge of the contributions of their respective AERs and deposition rates.

$$\frac{d[X]}{dt} = -\frac{d[X]_{out}}{dt} + \frac{d[X]_E}{dt} - \frac{d[X]_{Dep}}{dt}$$
Concentration
profile
$$-\frac{d[X]_{out}}{dt} + \frac{d[X]_E}{dt} - \frac{d[X]_{Dep}}{dt}$$
Deposition on
surfaces
$$Eq. 2$$

565

564

566 *3.4.1 Air exchange*

Air exchange removes species *X* via the air renewal system of the emission test chamber and is characterized by k_{AER} , expressed in h⁻¹. The air exchange can be calculated considering the ventilation flow and the volume of the chamber or experimentally determined using a relevant tracer gas. Based on the inlet ventilation flow of our emission test chamber, k_{AER} was fixed at 0.3 h⁻¹ in all sets of experiments.

$$\left(-\frac{d[X]_{out}}{dt}_{\text{Air Exchange}}\right) = -k_{AER} \times [X]$$
Eq. 3

573

574 *3.4.2 Emission rate*

588

575 The emission rate of species X is determined from its release from the mass of applied product 576 per unit of time. For cleaning products, the mass emission rate is determined using Eq. 4, where 577 m_p is the mass of cleaner applied over the surface depending on the cleaning purpose, i.e., floor 578 or surface cleaning, and $V_{chamber}$ corresponds to the volume of the experimental chamber.

579
$$\frac{d[X]_E}{dt} = \frac{\tau(t) \times V_{chamber}}{m_p}$$
Eq. 4

580 *3.4.3 Deposition on the inner surfaces of the emission test chamber*

This phenomenon corresponds to the sorption of gas-phase TerVOCs to the surface of the stainless steel chamber. The nonreactive sorption of TerVOCs on indoor materials can be characterized by the deposition rate k_D expressed in h⁻¹ and is driven by the concentration of the gas-phase species X, as reported in *Eq. 5*. Note that k_D depends on the nature of the material and the VOC and was assessed for each set of experiments to provide a comprehensive evaluation of the fate of emitted TerVOCs and its impact on the resulting TerVOC concentrations in the gas phase.

$$\left(-\frac{d[X]_{Dep}}{dt}_{\text{Deposition on surfaces}}\right) = -k_D \times [X]$$
Eq. 5

As finite sources of TerVOCs, fragrance molecules in cleaning products may become depleted. Thereafter, the drivers of the TerVOC concentrations in the experimental chamber are only (i) the air renewal at a known decay rate (k_{AER}) and (ii) the deposition on walls at a decay rate (k_D). This situation is described in *Eq.* 6, the linearized form of Eq. 2. The air renewal rate was set to 0.3 h⁻¹ in our emission test chamber and was therefore easy to account for. The method 594 to determine k_D is illustrated with the temporal profile of linalool emitted from the surface cleaner SC - 1 in Fig. 5a. After 1 hour of emission, the peak in linalool emission has past, and 595 596 the experimental data inside the box (Fig. 5a) correspond to a decaying linalool concentration 597 due to air exchange and possible sorption on the emission chamber walls. Based on Eq. 6, this 598 portion of the data series is plotted in Fig. 5b as ln ([linalool]) as a function of time (h). The 599 linear relationship indicates pseudo-first-order decay. The slope of the straight line in Fig. 5b is 600 the sum of kAER and kD. Since kAER is a known experimental constant, the deposition rate of 601 linalool under our experimental conditions can be determined as k_D (linalool) = 0.16 h⁻¹.



Fig. 5. (a) Temporal evolution of the linalool concentration (ppb) during cleaning using the surface cleaner SC – 1 (T = 23 °C, RH = 50 %, air renewal rate = 0.3 h⁻¹, chamber volume = 1 m^{3}); the data series in the box corresponds to linalool decay after depletion of its source. (b) Plot of ln ([*linalool*]) as a function of time (h); NB: in b), only the data series within the box in (a) is plotted.

608 The deposition rates (k_D) of the 6 predominant released TerVOCs were experimentally 609 determined during the application of the surface cleaner SC – 1, the kitchen cleaner KC – 2, and

610	the multiuse cleaner MC – 2 (Table 6) and ranged from 0.12 to 0.52 h ⁻¹ . These values clearly
611	show that the deposition rates of TerVOCs on the chamber walls have to be determined to
612	interpret the concentration profiles since they impact the resulting concentrations by the same
613	order of magnitude as the AER $(0.3 h^{-1})$.

614

615 **Table 6.** Comparison of the deposition rate coefficient k_D (h⁻¹) of the predominant terpenes from

616 the three selected cleaning products: (i) the surface cleaner SC – 1, (ii) the kitchen cleaner KC –

Deposition rate $k_D(h^{-1})$								
TERPENE		Cleaning Product						
IERFEINE	SC - 1	KC – 2	MC – 1					
α-Pinene	0.52	0.46	0.26					
Limonene	0.12	0.11	0.24					
 Linalool	0.16	ND	ND					
Eucalyptol	0.19	0.38	0.30					
 Cymene	Ø	0.22	0.31					
 Bergamol	0.12	Ø	Ø					
 Camphor	0.12	ND	Ø					
 Menthol	Ø	0.08	Ø					

617 2, and (iii) the multiuse cleaner MC - 1.

618 Ø = This terpene was not identified in a cleaning product in its liquid form.

ND: This terpene was not a predominantly emitted terpene from a cleaning product; therefore, it was not detected inthe gas phase.

According to Table 6, the k_D values for the same species may differ from one applied product to another. For instance, the k_D of α -pinene was 0.52, 0.46, and 0.26 h⁻¹ for SC – 1, KC – 2, and MC – 1, respectively. These differences are suggested to be associated with the cleaning product formulations. Among cleaning product constituents, water can be present in formulations at mass percentages ranging from 95 % and 50 %. Subsequently, during cleaning, the RH of the confined environment increases. Springs et al. (2011) evidenced that the number of moles of terpenes taken up per unit of surface area tends to decrease with increasing RH, suggesting competitive interactions with water molecules for uptake surfaces. Consequently, the deposition rate (k_D) of fragrance molecules on indoor materials could be impacted by two main factors: (i) competition for uptake among terpenes and cleaning constituents and (ii) the increase in RH related to the water content of the cleaner. Consequently, the k_D value for a given terpene might differ depending on the cleaning product formulation.

633

639

634 *3.4.4 Determination of the mass emission profiles from the concentration profiles*

The mass conservation equation under our experimental conditions during cleaning is described by *Eq. 7*, where [X] is the concentration of species X, m_p is the mass of applied cleaning product, V_{chamber} corresponds to the volume of the chamber (m³), and k_{AER} and k_D are the decay rates (h⁻¹) of species X related to air renewal and deposition.

$$\frac{d[X]}{dt}_{\text{Concentration}} = \frac{\tau(t) \times V_{chamber}}{m_p} - \frac{(k_D + k_{AER}) \times [X]}{(k_D + k_{AER})} + \frac{(k_D + k_{AER}) \times [X]}{(k_D + k_{AER})}$$

Based on *Eq.* 7, the emission rate of a given TerVOC can be retrieved from its concentration profile corrected by the air renewal rate and by the depletion rate. Fig. 6 shows the temporal evolution (a) of linalool emitted during cleaning using the surface cleaner SC – 1 and (b) of eucalyptol released during cleaning using the kitchen cleaner KC – 2. The concentrations of linalool and eucalyptol directly monitored in the 1 m³ emission test chamber are plotted as black squares in Fig. 6a and b. First, the raw profile was corrected by the air renewal rate, resulting in linalool and eucalyptol concentration profiles that would have been recorded if no air 647 exchange occurred in the emission test chamber (light gray squares in Fig. 6). Then, these 648 profiles were corrected by the specific deposition rate of each terpene, producing final profiles 649 that correspond to the concentrations if no linalool and eucalyptol had been removed from the 650 gas phase in the chamber, neither by sorption on the chamber walls nor by air exchange (dark 651 gray circles in Fig. 6). The resulting profiles reflect only the linalool and eucalyptol emissions 652 from SC - 1 and KC - 2, respectively. Therefore, the times when these terpenes reach steady 653 state indicates the end of their emission from their respective cleaners. Moreover, this final 654 profile can be used to calculate the emission rate of linalool and eucalyptol according to Eq. 8. 655 The same calculations were performed for all terpenes detected in the gas phase during the use of 656 the three cleaners.



Fig. 6. (a) Temporal evolution of the (i) monitored concentration (ppb), (ii) air exchangecorrected concentration (ppb), and (iii) air exchange + deposition-corrected concentration (ppb) of linalool during cleaning using the surface cleaner SC – 1. (b) Temporal evolution of the (i) monitored concentration (ppb), (ii) air exchange-corrected concentration (ppb), and (iii) air exchange + deposition-corrected concentration (ppb) of eucalyptol during cleaning using the

663 kitchen cleaner KC – 2 (T = 23 °C, RH = 50 %, air renewal rate = 0.3 h⁻¹, chamber volume = 1 664 m³).

665

a)

666 3.4.5 Emission rate profiles of individual TerVOCs

Based on *Eq.* 8, the temporal evolution of the mass emission rate was calculated for each cleaner and for each TerVOC emitted. Fig. 7 presents the temporal evolution of the mass emission rates of the three predominant TerVOCs monitored during the use of (a) SC - 1, (b) KC - 2 and (c) MC - 1. The temporal profiles of the emission rates allow the determination of (i) the time required to reach the maximum emission rate, (ii) the value of the maximum emission rate, and (iii) the time at which the emission source is depleted.



b)



Fig. 7. Temporal evolution of the mass emission rates of the three predominant terpenes detected in the gas phase during the use of (a) the surface cleaner SC – 1, (b) the kitchen cleaner KC – 2 and (c) the multiuse cleaner MC – 1 applied in the 1 m³ emission test chamber (T = 23 °C, RH = 50 %, air renewal rate = 0.3 h⁻¹, chamber volume = 1 m³).

Based on Fig. 7, irrespective of the cleaning product, the time required for a given terpene to reach the maximum emission rate was similar for all monitored terpenes: within 8 minutes after cleaning was completed. However, the magnitude of the peak emission rate of the predominant terpene released clearly differed from one cleaning product to another: (i) 710 ± 15 μ g/h linalool from SC – 1, (ii) 1550 ± 90 μ g/h eucalyptol from MC – 1, and (iii) 5 000 ± 120 μ g/h eucalyptol from KC – 2.

Noticeably, the emission of eucalyptol and menthol from KC - 2 was exhausted within 50 minutes and after 30 minutes for limonene. Of the three selected categories, this product category had the highest emission rates. However, SC - 1 and MC - 1 showed shorter emission durations than KC - 2. Their total TerVOC emissions were exhausted within only 24 minutes, as shown in Fig. 7a and b.

Regarding the emission of individual terpenes, eucalyptol was only terpene emitted from all three tested cleaners. However, its peak emission rate varied widely, reaching $620 \pm 20 \,\mu$ g/h, $4\,900 \pm 110 \,\mu$ g/h and $1460 \pm 30 \,\mu$ g/h for the surface cleaner (SC – 1), the kitchen cleaner (KC – 687 2) and the multiuse cleaner (MC – 1), respectively. Similar emission rate variability was 688 observed for the limonene emitted from two products: $240 \pm 30 \mu g/h$ and $1100 \pm 80 \mu g/h$ for KC 689 – 2 and MC – 1, respectively.

The assessment of the emission rates confirms that in addition to the liquid TerVOC content in the cleaner, the emission dynamics are also driven by (i) the solvent matrix in which the fragrance molecules are contained due to chemical affinities that might be generated among species, delaying the emission kinetics, and (ii) the volatility of individual terpene molecules.

694

695 3.5 Emission of OVOCs from natural cleaning products under realistic application conditions: 696 1 m³ emission test chamber

697 Carbonyl compounds were monitored during each set of emission experiments. Three targeted 698 oxygenated VOCs emitted from the application of SC - 1, KC - 2 and MC - 1 were identified 699 and quantified: formaldehyde, acetaldehyde and acetone. Their individual maximum emitted 700 concentrations varied from one cleaning product to another, ranging from (i) 6 ± 1 to 18 ± 3 ppb 701 formaldehyde, (ii) 22 ± 3 to 210 ± 20 ppb acetaldehyde, and (iii) 18 ± 4 to 108 ± 15 ppb acetone. 702 Among the identified OVOCs, formaldehyde was classified in 2016 by the European 703 Commission as carcinogenic (Group 1) and genotoxic (International Agency for Research on 704 Cancer, 1979). Additionally, the long-term exposure limit was established at 9 ppb by the World 705 Health Organisation (2010). Thus, in the framework of this study, formaldehyde is of particular 706 interest because of its toxicity.

^{708 3.5.1} Formaldehyde emission profiles from the use of natural cleaning products

709 Fig. 8a presents the temporal evolution of the concentration of formaldehyde emitted by cleaning 710 with SC - 1, KC - 2 and MC - 1. Unlike the terpene emission profiles, the temporal evolution of 711 the formaldehyde concentration in Fig. 8 is characterized by two phases: (i) a marked increase 712 confirming the rapid transfer of formaldehyde from the product to the gas phase during the first 50 minutes of emission and (ii) either a slow increase for SC - 1 and MC - 1 or steady state for 713 714 KC – 2. In contrast to the terpene concentration profiles, the emission profiles of formaldehyde 715 do not follow a typical transient emission process. As observed in Fig. 8a, the maximum emitted 716 concentration of formaldehyde was 9 and 16 ppb for the surface cleaner (SC - 1) and for the 717 multiuse cleaner (MC - 1), respectively. These values were observed 3.5 hours after the cleaning 718 was finished. For the kitchen cleaner KC - 2, the concentration of formaldehyde reached 6 ppb at 719 0.8 hours and then remained constant for at least 3.5 hours after the product application. These 720 observations suggest that even after 3.5 h, the emission source of formaldehyde was not 721 exhausted, reflecting delayed emission kinetics that may not solely be related to a primary 722 release from the cleaning product itself. In agreement with our findings, (CSTB, 2006); Solal et 723 al. (2014) assessed the emissions of formaldehyde from 35 consumer products in different 724 categories applied under realistic conditions in the experimental house MARIA. Among the 725 evaluated products, the uses of (i) 2 vacuum fresheners, (ii) 2 carpet cleaners, (iii) 3 toilet 726 cleaners, (iv) 4 glass cleaners and (v) 2 furniture polishes were associated with increases in the 727 formaldehyde concentration in the experimental house. The observed concentrations were 728 described by the same two phases shown in Fig. 8a: (i) a sharp increase in the HCHO 729 concentration confirming the rapid transfer of formaldehyde from the product to the gas phase 730 and (ii) a slower increase or steady state. The maximum concentrations that arise from the emission were 6 to 16 ppb, depending on the category of product applied. These values wereobserved at 120 minutes after the cleaning was completed.

733



Fig. 8. (a) Temporal evolution of the concentration of formaldehyde (ppb) from the use of three cleaning products: (i) surface cleaner (SC-1), (ii) kitchen cleaner (KC-1) and (iii) multiuse cleaner (MC-1) (T = 23 °C, RH = 50 %, AER = 0.3 h⁻¹). (b) Temporal evolution of the *air exchange-corrected* concentration of formaldehyde (ppb) as a function of time during cleaning with the three cleaners: (i) SC – 1, (ii) KC – 2, and (iii) MC – 1 (T = 23 °C, RH = 50 %, AER = 0.3 h⁻¹).

740

To confirm these observations, the emission profile was corrected by the air exchange in the experimental chamber, i.e., k_{AER} of 0.3 h⁻¹. The corrected profile is presented in Fig. 8b, which depicts the temporal evolution of the concentration of formaldehyde that would have been monitored if no air exchange occurred in the emission test chamber. The concentration variation resulted from only the transfer of formaldehyde to the gas phase and the possible sorption on the inner walls of the experimental chamber. However, the mass emission rate of formaldehyde 747 cannot be calculated by the estimation method in section 3.4 since the emission source could not 748 be assumed to be exhausted and the deposition rate (k_D) could not be determined. As shown in 749 Fig. 8b, the corrected profile of formaldehyde emission from SC - 1, MC - 1 and KC - 2 was 750 characterized by two main phases: (i) a primary increase in the concentration, suggesting a 751 release linked to a primary emission of formaldehyde potentially contained in the cleaning 752 product, and (ii) a linear increase in the concentration of formaldehyde. The slope of the linear 753 relationship of the corrected formaldehyde concentration varied depending on the cleaning 754 product. Therefore, the temporal evolution of the corrected formaldehyde concentration, 755 presented in Fig. 8b, did not correspond to a transient emission profile but suggested the 756 presence of formaldehyde releasers in the cleaning product formulation, in which case, the 757 concentration of formaldehyde might be associated with secondary emission sources.

758 The specific concentration dynamics associated with the emission of formaldehyde are 759 suggested to be related to two mechanisms: (i) direct (or primary) emission of formaldehyde 760 contained in the cleaning product and (ii) emission of formaldehyde from formaldehyde-761 releasing molecules present in the cleaning product formulations (Pastor-Nieto et al., 2017). 762 Formaldehyde releasers are defined as chemical compounds that decompose to release 763 formaldehyde when dissolved in aqueous solvents (De Groot et al., 2009; Flyvholm and 764 Andersen, 1993; Kajimura et al., 2008). This process is characterized by an in situ degradation of 765 non-formaldehyde-containing components, i.e., the self-oxidation of ethoxylated alcohols. 766 Generally, these chemicals are used in consumer products as preservatives, antiseptics, and/or for 767 enhancing their disinfectant performance. The concentration of formaldehyde or formaldehyde-768 releasing compounds added in product formulations might depend on their use purpose and 769 manufacturer preferences. According to the National Database for Products and Compositions in France (BNPC), formaldehyde releasers are included in the formulations of 78 % of household
products as preservative agents, corresponding to a mass concentration ranging from 0.2 % to 0.3
% w/w (Affset, 2009).

773 De Groot et al. (2009) assessed formaldehyde and formaldehyde releasers contained in 774 consumer products in various categories by reviewing the Danish Product Register Database 775 (PROBAS). His findings reveal that the most important product categories containing 776 formaldehyde or formaldehyde releaser are (i) biocides or pesticides; (ii) paints, lacquers and 777 varnishes; and (iii) cleaning and washing agents. In the cleaning and washing agents, 9 different 778 formaldehyde-releasing compounds were identified. Among these chemicals, Bronopol® (2-779 brono-2-nitropropane-1,3-diol) was the most frequently used formaldehyde releaser, being 780 detected in 124 out of 275 cleaning products or washing agents. However, the authors indicated 781 that a total of 19 out of the 42 detected formaldehyde-releasing compounds were not found in 782 *PROBAS.* Similarly, the BNPC in France reported the presence of formaldehyde releasers in 236 783 out of 692 cleaning products on the European market (Affset, 2009). Additionally, the BNPC 784 published and identified a list of 24 compounds confirmed as formaldehyde releasers, including 785 Bronopol[®] and Methenamine as the most frequently used among household products. Kajimura 786 et al. (2008) investigated the formation of HCHO from a common formaldehyde-releasing compound known as Bronopol[®] from a homemade cosmetic product prepared with 0.1 % w/v of 787 788 this molecule. This study aimed to correlate the presence of Bronopol® and the respective 789 formation of formaldehyde by headspace analysis. Their results verified an increase in 790 formaldehyde concentration over time, reaching 20 ppm after 10 days, and this level was 791 observed to be constant over 50 days. Note that this concentration cannot be compared to our 792 results because of differences in the experimental protocol and approach.

793 Regarding the three cleaning products evaluated in this study, the presence of Bronopol[®] 794 was listed by manufacturers for only the multiuse cleaner MC - 1. Its presence may explain the 795 unique formaldehyde emission profile observed for that product. However, according to 796 European legislation for the cleaning product industry, numerous formaldehyde releasers are not 797 required to be included in the product ingredient list. With this lack of information, the 798 correlation between the formaldehyde emission profile observed for the tested cleaning products 799 and the presence of formaldehyde releasers in their composition is suggested but has not been 800 confirmed.

Therefore, the use of natural cleaning products might generate a continuously increasing indoor formaldehyde concentration, in which the maximum emitted levels might remain in the confined environment for several hours after the cleaning is completed. Additionally, formaldehyde releasers included in consumer products represent a hidden source of formaldehyde, of which consumers might not even be aware, extending its impact on IAQ by several tens of ppb for several hours after household activity is completed.

807

3.6 Wrap-up of the terpene emissions from cleaning products: from their liquid composition to their mass emission rates

In this work, the TerVOC emissions from the use of 3 cleaners were investigated by comparing different scales, including their liquid composition, their gas-transferred concentration and their emission under realistic use patterns. This innovative methodology allowed the investigation of the emission of fragrance molecules at different scales to evaluate the impact on IAQ through an integrated approach, achieving an accurate assessment of the mass emission rates. These 815 estimated mass emission rates could be further implemented for the estimation of human816 exposure to these chemicals and to the definition of risk scenarios.

Fig. 9 shows the relative abundances expressed as percentages of the predominant TerVOCs and as their respective absolute scales for (i) the mass concentration detected in the liquid form ($\mu g/g$ of product), (ii) the volatile fraction (gas-transferred concentration) associated with the micro-chamber testing ($\mu g/m^3$), and (iii) the maximum emission rates per individual terpene (ppb/h per g of product) associated with the use of (a) the surface cleaner SC – 1, (b) the kitchen cleaner KC – 2, and (c) the multiuse cleaner MC – 1.





Fig. 9. Comparison of the relative abundances in the mass concentration ($\mu g/g$) in the liquid phase, the volatile concentration ($\mu g/m^3$) (T = 40 °C, dry air flow = 50 mL/min, microchamber volume = 44 mL) and the maximum emission rate per gram of cleaning product (T = 23 °C, RH = 50 %, air renewal rate = 0.3 h⁻¹, chamber volume = 1 m³) for (a) the surface cleaner SC – 1, (b) the kitchen cleaner KC – 2, and (c) the multiuse cleaner MC – 1.

(c)

824 In terms of the absolute values, written in bold in Fig. 9, no correlation was found 825 between them. As mentioned in section 3.2, the maximum emission rate of terpene molecules 826 from the use of essential-oil-based cleaning products cannot be directly predicted from their 827 content in the liquid form or from micro-chamber testing. Micro-chamber results can be used to 828 describe key general trends of the predominant emitted terpenes but should not be considered for 829 realistic emission assessment. Moreover, the relative distributions between terpenes for the liquid 830 content and for the maximum emission rate are much closer rather than one for the gas-831 transferred concentration. That can be explained by the fact that micro-chamber experiments were conducted at a temperature of 40 °C, enhancing the transfer from the liquid to the gas 832 833 phase.

835 In regard to the behavior of specific compounds, such as eucalyptol and limonene, two species with similar VPs (260 and 219 Pa, respectively), substantial differences were observed. 836 837 In all the investigated cleaning products, eucalyptol evidence higher proportions in the maximum 838 mass emission rate if compared to its relative abundance in the liquid form. This observation 839 confirms the ability of eucalyptol to be transferred from the liquid to the gas phase, irrespective 840 of the solvent matrix of the cleaner. In contrast, for a given cleaning product, limonene had (i) a 841 lower relative abundance at the maximum mass emission rate than in the liquid phase and (ii) a 842 higher relative abundance in the volatile fraction than in the liquid form. These observations 843 suggest that the emission of limonene might be more impacted by the solvent matrix in the 844 cleaning product than by its volatility (VP = 219 Pa), and therefore, its mass transfer might be 845 delayed due to chemical affinities to other compounds.

846

847

7 4. CONCLUSIONS AND PERSPECTIVES

848 This study has shown that the largest contributors of terpenes to indoor air are not only 849 recognized, regulated and controlled sources, namely, building materials, but also "green" 850 household products, which should be seriously considered as versatile and high-impact sources. 851 These fragrance chemicals classified as allergens responsible for skin irritation, allergic rhinitis, 852 and asthma are primarily associated with the use of cleaning products (Wolkoff and Nielsen, 853 2017). Essential-oil-based household products might release concentrations of several tens to 854 hundreds of ppb TerVOCs, exceeding the exposure limits established by the European Union and 855 the United States (Dimitroulopoulou et al., 2015; Kirchner et al., 2001; World Health 856 Organisation, 2010). Regarding formaldehyde emissions from the investigated cleaning products, 857 this study has confirmed that these products could represent a hidden source of formaldehyde in confined environments. Indeed, consumers might increase the formaldehyde concentration
indoors by several ppb without being aware of it due to the presence of non-regulated
formaldehyde-releasing compounds contained in these types of products.

Several key factors were confirmed to drive the mass transfer from the liquid to the gas phase of terpene molecules contained in essential-oil-based cleaning products: (i) the mass concentration of individual terpenes in the liquid phase, since a correlation between the major contained and the predominantly emitted terpenes was observed for all the tested cleaning products; (ii) the solvent matrix included in the cleaning formulation, which may generate chemical affinities between terpenes and the cleaner constituents, impacting the emission dynamics; and (iii) the volatility of the individual terpene molecules.

Micro-chamber testing cannot replace standard emission test chambers but is a complementary tool that allows evaluation of the gas-transferred concentrations and rapid screening of the potentially released TerVOCs from essential-oil-based household products prior to a detailed product emissions characterization. Micro-chamber experiments need to be accompanied by an evaluation of the effective emissions under realistic conditions in a test chamber to accurately estimate the human exposure to cleaning product constituents under recommend application scenarios.

While this study aimed to implement realistic scenarios, the 1 m³ chamber imposes limitations regarding the application process. Due to space limitations, real consumer use patterns while performing a cleaning activity could not be completely reproduced. Without being wiped, trigger spray products were directly sprayed in the chamber and dispersed by droplets onto the surface, and liquid cleaning products were drizzled on the surface placed at the center of the chamber. Therefore, further assessments of TerVOC emissions from essential-oil-based
cleaning products under real consumer use patterns in a full-scale room are highly recommended.

883 ACKNOWLEDGEMENTS

The authors acknowledge Agence de l'Environnement et de la Maîtrise de l'Energie (ADEME) for the provided financial support of research project ESSENTIEL within the framework of the CORTEA research program. In particular, Isabelle AUGEVEN-BOUR and Souad BOUALLALA are acknowledged for their positive, benevolent and constructive care of the project. Shadia ANGULO MILHEM thanks IMT Lille Douai and CSTB for the provided PhD grant.

Above all, the authors are grateful to each other for the pleasure of working together on theESSENTIEL research project.

892

893 FUNDING

This work was financially supported by l'Agence de l'Environnement et de la Maîtrise de l'Energie (ADEME), IMT Lille Douai and the Centre Scientifique et Technique du Bâtiment (CSTB).

897

898 DECLARATIONS OF INTEREST

899 The authors declare that they have no conflicts of interest.

901 **REFERENCES**

- 902 AFFSET, 2009. Formaldéhyde Rélation Entre Composition et Émission. Rapport ANSES, France, pp.
 903 150-200.
- Babu K.G.D., Singh B., Joshi V.P., Singh V., 2002. Essential oil composition of Damask rose (Rosa
 damascena Mill.) distilled under different pressures and temperatures. Flavour and Fragrance
 Journal 17, 136-140.
- BEUC, 2005. Emission of Chemicals by Air Fresheners. Final Report. ICRT International Consumer
 Research & Testing, Belgium.
- Brown S.K., 1999. Chamber assessment of formaldehyde and VOC emissions from wood-based panels.
 Indoor Air 9, 209-215.
- Brown S.K., Sim M.R., Abramson M.J., Gray C.N., 1994. Concentrations of volatile organic compounds
 in indoor air A review. Indoor Air 4, 123-134.
- 913 Chesnais E., Marchais M., 2014. Sprays assainissants et désodorisants. Notre Intérieur Dégradé 530, 50914 53.
- Colombo A., De Bortoli M., Knöppel H., Schauenburg H., Vissers H., 1991. Small chamber tests and
 headspace analysis of volatile organic compounds emitted from household products. Indoor Air 1,
 13-21.
- 918 CSTB, 2006. Caractérisation des Émissions de COV et Formaldéhyde par Différents Types de Produits.
 919 Rapp. Sci. CSTB SB-06-044.
- De Groot A.C., Flyvholm M.A., Lensen G., Menne T., Coenraads P.J., 2009. Formaldehyde-releasers:
 relationship to formaldehyde contact allergy. Contact allergy to formaldehyde and inventory of
 formaldehyde-releasers. Contact Dermatitis 61, 63-85.
- Delmas C., Weiler A.S., Ortega S., Duong O., Dazy A., Ott M., Schneider C., Moritz R., Leclerc N.,
 Rivière E., De Blay F., 2016. Mesure de la concentration aérienne de COV terpéniques (dont le
 limonène) selon plusieurs procédures lors de pulvérisations d'un mélange d'huiles essentielles.
 Revue Française d'Allergologie 56, 357-363.
- Dimitroulopoulou C., Trantallidi M., Carrer P., Efthimiou G.C., Bartzis J.G., 2015. EPHECT II: exposure
 assessment to household consumer products. Science of the Total Environment 536, 890-902.
- Espinosa Díaz M.A., Guetachew T., Landy P., Jose J., Voilley A., 1999. Experimental and estimated
 saturated vapour pressures of aroma compounds. Fluid Phase Equilibria 157, 257-270.
- Ettre L.S., Welter C., Kolb B., 1993. Determination of gas-liquid partition coefficients by automatic
 equilibrium headspace-gas chromatography utilizing the phase ratio variation method.
 Chromatographia 35, 73-84.

- Ezendam J., Te Biesebeek J.D., Wijnhoven S.W.P., 2009. The Presence of Fragrance Allergens in
 Scented Consumer Product. Letter Report 340301002/2009. National Institute of Public Health
 and the Environment, Netherland.
- Flyvholm M.A., Andersen P., 1993. Identification of formaldehyde releasers and occurrence of
 formaldehyde and formaldehyde releasers in registered chemical products. American Journal of
 Industrial Medicine 24, 533-552.
- Guichard E., 2002. Interactions between flavor compounds and food ingredients and their influence onflavor perception. Food Reviews International 18, 49-70.
- Haghighat F., De Bellis L., 1998. Material emission rates: literature review, and the impact of indoor air
 temperature and relative humidity. Building and Environment 33, 261-277.
- Harb P., Locoge N., Thevenet F., 2018. Emissions and treatment of VOCs emitted from wood-based
 construction materials: impact on indoor air quality. Chemical Engineering Journal 354, 641-652.
- Harb P., Sivachandiran L., Gaudion V., Thevenet F., Locoge N., 2016. The 40m³ Innovative experimental
 Room for INdoor Air studies (IRINA): development and validations. Chemical Engineering
 Journal 306, 568-578.
- Höllbacher E., Ters T., Rieder-Gradinger C., Srebotnik E., 2017. Emissions of indoor air pollutants from
 six user scenarios in a model room. Atmospheric Environment 150, 389-394.
- Hoskovec M., Grygarová D., Cvačka J., Streinz L., Zima J., Verevkin S.P., Koutek B., 2005. Determining
 the vapour pressures of plant volatiles from gas chromatographic retention data. Journal of
 Chromatography A 1083, 161-172.
- Huang Y., Ho S.S.H., Ho K.F., Lee S.C., Gao Y., Cheng Y., Chan C.S., 2011. Characterization of
 biogenic volatile organic compounds (BVOCs) in cleaning reagents and air fresheners in Hong
 Kong. Atmospheric Environment 45, 6191-6196.
- International Agency for Research on Cancer, 1979. IARC Monographs on the Evaluation of the
 Carcinogenic Risk of Chemicals to Humans. International Agency for Research on Cancer, Lyon,
 France.
- ISO 16000-9, 2006. Indoor Air Part 9: Determination of the Emission of Volatile Organic Compounds
 from Building Products and Furnishing Emission Test Chamber Method. BSI, London, UK.
- Jo W.K., Lee J.H., Kim M.K., 2008. Head-space, small-chamber and in-vehicle tests for volatile organic
 compounds (VOCs) emitted from air fresheners for the Korean market. Chemosphere 70, 1827 1834.
- Jouquand C., Aguni Y., Malhiac C., Grisel M., 2008. Influence of chemical composition of
 polysaccharides on aroma retention. Food Hydrocolloids 22, 1097-1104.

- Kajimura K., Tagami T., Yamamoto T., Iwagami S., 2008. The release of formaldehyde upon
 decomposition of 2-Bromo-2-nitropropan-1, 3-diol (Bronopol). Journal of Health Science 54,
 488-492.
- Kirchner S., Buchmann A., Cochet C., Dassonville C., Derbez M., Leers Y., Lucas J.P., Mandin C.,
 Ouattara M., Ramalho O., Riberon J., 2001. Qualité d'Air Intérieur, Qualité de Vie. 10 ans de
 Recherche Pour Mieux Respirer. CSTB, Paris, France.
- Kwon K.D., Jo W.K., Lim H.J., Jeong W.S., 2007. Characterization of emissions composition for selected
 household products available in Korea. Journal of Hazardous Materials 148, 192-198.
- Lai A.C., Thatcher T.L., Nazaroff W.W., 2000. Inhalation transfer factors for air pollution health risk
 assessment. Journal of the Air and Waste Management Association 50, 1688-1699.
- Lassen C., Havelund S., Mikkelsen S., 2008. Health Assessment of Chemical Substances in Essential Oils
 and Fragrance Oils. Survey No. 92. Danish Environmental Protection Agency (DEPA), Denmark.
- López E.F., Gómez E.F., 2000. Comparison of solvents for determination of monoterpenes in wine using
 liquid-liquid extraction. Chromatographia 52, 798-802.
- Lucas J.P., Ramalho O., Kirchner S., Ribéron J., Intérieurs P., 2009. Etat de la Ventilation Dans le Parc
 de Logements Français. CSTB DESE/SB-2009-037, Paris, France.
- Magnano M., Silvani S., Vincenzi C., Nino M., Tosti A., 2009. Contact allergens and irritants in
 household washing and cleaning products. Contact Dermatitis 61, 337-341.
- Missia D., Kopanidis T., Bartzis J., Ventura G., De Oliveira Fernandes E., Carrer P., Wolkoff P., Stranger
 M., Goelen E., 2012. Literature Review on Product Composition, Emitted Compounds and
 Emissions Rates and Health End Points from Consumer Products. Final Report European Project
- 988 EPHECT. Executive Agency for Health and Consumers-EAHC, European Union.
- Nazaroff W.W., Weschler C.J., 2004. Cleaning products and air fresheners: exposure to primary and
 secondary air pollutants. Atmospheric Environment 38, 2841-2865.
- Nicolas M., Chiappini L., 2013. Household Products Using and Indoor Air Quality: Emissions, Reactivity
 and By-products. Final Report ADOQ Project. Centre Scientifique et Technique du Bâtiment
 (CSTB), INERIS, Paris, France
- 994 Nicolas M., Karr G., Real E., Maupetit F. Avril 2019. Impact des produits d'entretien sur la qualité de
 995 l'air intérieur. PEPS Définition d'un protocole d'essais simple et harmonisé pour l'évaluation
- 996 des émissions en composés volatils. Report ADEME. 20 162p. www.ademe.fr/mediatheque
- 997 Norgaard A.W., Kofoed-Sorensen V., Mandin C., Ventura G., Mabilia R., Perreca E., Cattaneo A.,
- 998 Spinazze A., Mihucz V.G., Szigeti T., De Kluizenaar Y., Cornelissen H.J., Trantallidi M., Carrer
 999 P., Sakellaris I., Bartzis J., Wolkoff P., 2014. Ozone-initiated terpene reaction products in five

- European offices: replacement of a floor cleaning agent. Environmental Science and Technology48, 13331-13339.
- Pastor-Nieto M.A., Alcántara-Nicolás F., Melgar-Molero V., Pérez-Mesonero R., Vergara-Sánchez A.,
 Martín-Fuentes A., González-Muñoz P., De Eusebio-Murillo E., 2017. Preservatives in personal
 hygiene and cosmetic products, topical medications, and household cleaners in Spain. Actas
 Dermo-Sifiliográficas 108, 758-770.
- Pors J., Fuhlendorff R., 2003. Mapping of Chemical Substances in Air Fresheners and Other Fragrance
 Liberating Products. Survey No. 30. Danish Environmental Protection Agency (DEPA),
 Denmark.
- Rastogi S.C., 2002. Contents of Selected Fragrance Materials in Cleaning Products and Other Consumer
 Products. Survey No. 8. Danish Environmental Protection Agency (DEPA), Denmark.
- 1011 Rastogi S.C., Heydorn S., Johansen J.D., Basketter D.A., 2001. Fragrance chemicals in domestic and
 1012 occupational products. Contact Dermatitis 45, 221-225.
- Sarwar G., Olson D.A., Corsi R.L., Weschler C.J., 2004. Indoor fine particles: the role of terpene
 emissions from consumer products. Journal of the Air and Waste Management Association 54,
 367-377.
- Singer B.C., Coleman B.K., Destaillats H., Hodgson A.T., Lunden M.M., Weschler C.J., Nazaroff W.W.,
 2006a. Indoor secondary pollutants from cleaning product and air freshener use in the presence of
 ozone. Atmospheric Environment 40, 6696-6710.
- Singer B.C., Destaillats H., Hodgson A.T., Nazaroff W.W., 2006b. Cleaning products and air fresheners:
 emissions and resulting concentrations of glycol ethers and terpenoids. Indoor Air 16, 179-191.
- Solal C., Rousselle C., Mandin C., Manel J., Maupetit F., 2014. VOCs and Formaldehyde Emissions from
 Cleaning Products and Air Fresheners, Proceedings of the 11th International Conference on
 Indoor Air Quality and Climate. Technical University of Denmark (DTU), Copenhagen,
 Denmark, Paper ID: 183.
- Springs M., Wells J.R., Morrison G.C., 2011. Reaction rates of ozone and terpenes adsorbed to model
 indoor surfaces. Indoor Air 21, 319-327.
- Steinemann A., 2016. Fragranced consumer products: exposures and effects from emissions. Air Quality,
 Atmosphere and Health 9, 861-866.
- Steinemann A.C., 2009. Fragranced consumer products and undisclosed ingredients. Environmental
 Impact Assessment Review 29, 32-38.
- 1031 Steinemann A.C., MacGregor I.C., Gordon S.M., Gallagher L.G., Davis A.L., Ribeiro D.S., Wallace
- 1032 L.A., 2011. Fragranced consumer products: chemicals emitted, ingredients unlisted.
- 1033 Environmental Impact Assessment Review 31, 328-333.

- 1034 Štejfa V., Fulem M., Růžička K., Červinka C., 2014. Thermodynamic study of selected monoterpenes II.
 1035 The Journal of Chemical Thermodynamics 79, 272-279.
- 1036 Teixeira B., Marques A., Ramos C., Neng N.R., Nogueira J.M.F., Saraiva J.A., Nunes M.L., 2013.
- 1037 Chemical composition and antibacterial and antioxidant properties of commercial essential oils.1038 Industrial Crops and Products 43, 587-595.
- Trantallidi M., Dimitroulopoulou C., Wolkoff P., Kephalopoulos S., Carrer P., 2015. EPHECT III: health
 risk assessment of exposure to household consumer products. Science of the Total Environment
 536, 903-913.
- 1042 Uhde E., Schulz N., 2015. Impact of room fragrance products on indoor air quality. Atmospheric
 1043 Environment 106, 492-502.
- 1044 Weschler C.J., 2001. Reactions among indoor pollutants. The Scientific World Journal 1, 443-457.
- Wolkoff P., Nielsen G.D., 2017. Effects by inhalation of abundant fragrances in indoor air An overview.
 Environment International 101, 96-107.
- Wolkoff P., Schneider T., Kildesø J., Degerth R., Jaroszewski M., Schunk H., 1998. Risk in cleaning:
 chemical and physical exposure. Science of the Total Environment 215, 135-156.
- World Health Organisation, 2010. WHO Guidelines for Indoor Air Quality. Final Report, 2010. WHO
 European Centre for Environment and Health, Copenhagen Ø, Denmark.
- Zuzarte M., Salgueiro L., 2015. Essential Oils Chemistry, in: De Sousa, D.P. (Ed.), Bioactive Essential
 Oils and Cancer. Springer International Publishing, Cham, pp. 19–61.

