

Origin of the synergistic effect between TiO2 crystalline phases in the Ni/TiO2-catalyzed CO2 methanation reaction

Davina Messou, Vincent Bernardin, Frédéric Meunier, Marta Borges Ordoño, Atsushi Urakawa, Bruno Machado, Vincent Collière, Régis Philippe, Philippe Serp, Carole Le Berre

▶ To cite this version:

Davina Messou, Vincent Bernardin, Frédéric Meunier, Marta Borges Ordoño, Atsushi Urakawa, et al.. Origin of the synergistic effect between TiO2 crystalline phases in the Ni/TiO2-catalyzed CO2 methanation reaction. Journal of Catalysis, 2021, 398, pp.14-28. 10.1016/j.jcat.2021.04.004 . hal-03216533

HAL Id: hal-03216533 https://hal.science/hal-03216533

Submitted on 4 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Origin of the synergistic effect between TiO ₂ crystalline phases in the Ni/TiO ₂ -
2	catalyzed CO ₂ methanation reaction
3	
4	Davina Messou, ^a Vincent Bernardin, ^b Frédéric Meunier, ^c Marta Borges Ordoño, ^d Atsushi
5	Urakawa, ^{d,e} Bruno F. Machado, ^f Vincent Collière, ^a Régis Philippe, ^b Philippe Serp, ^{*,a} and
6	<i>Carole Le Berre^{*,a}</i>
7	
8	^a LCC-CNRS, INPT, 205 route de Narbonne, 31077 Toulouse Cedex 4, France
9	^b Catalysis Polymers Processes and Materials (CP2M), Université de Lyon, UMR 5128
10	CNRS, CPE Lyon, Université Claude Bernard Lyon 1, France
11	^c Univ. Lyon, Université Claude Bernard Lyon 1, CNRS, IRCELYON, 2 Av. Albert Einstein,
12	69626 Villeurbanne, France.
13	^d Institute of Chemical Research of Catalonia (ICIQ), Av. Paisos Catalans 16, 43007
14	Tarragona, Spain
15	^e Catalysis Engineering, Department of Chemical Engineering, Delft University of
16	Technology, Van der Maasweg 9, 2629 HZ Delft, The Netherlands
17	^f Laboratory of Separation and Reaction Engineering - Laboratory of Catalysis and Materials
18	(LSRE-LCM), Chemical Engineering Department, Faculty of Engineering, University of
19	Porto, Rua Dr. Roberto Frias s/n, 4200-465 Porto, Portugal
20	

Abstract. The catalytic performances of TiO₂-supported Ni catalysts for the methanation of 1 CO₂ have been investigated using different crystalline phases of TiO₂ (rutile and anatase). The 2 catalytic activity of Ni depends appreciably on the nature of the support. The rate for CO₂ 3 hydrogenation decreases in the order of 10Ni/TiO_{2-rutile} >> 10Ni/TiO_{2-anatase}. The use of a 4 mixture of catalysts containing 70% 10Ni/TiO2-anatase + 30% 10Ni/TiO2-rutile allows for a 5 significant increase of the reaction rate related to 100% 10Ni/TiO2-rutile. Importantly, it has been 6 7 demonstrated that the two catalysts do not need to be in direct contact for the synergetic effect to occur. DRIFTS operando analysis during the methanation reaction shows that adsorbed CO 8 accumulates on Ni/TiO_{2-anatase} and not on Ni/TiO_{2-rutile}, and that the role of the Ni/TiO_{2-rutile} is 9 10 to assist the hydrogenation of this adsorbed CO on the Ni/TiO2-anatase. Increased CO2 methanation is also observed by adding Ni-free TiO2-anatase to 10Ni/TiO2-rutile, indicating that 11 COx hydrogenation can also occur on bare TiO2-anatase if activated hydrogen can be supplied by 12 another source. H₂-TPD analyses and catalytic tests performed after dilution of the catalysts 13 have shown that hydrogen spillover (mediated by surface or gas-phase species) is at the origin 14 15 of the synergy observed between the two catalysts for the Sabatier reaction.

16

17 Key words: CO₂ methanation, nickel, titania, spillover, rutile, anatase

18

19 **1. Introduction**

The reduction of greenhouse gas emissions, and particularly those of CO_2 , which is the main contributor to global warming, is one of the major challenges of the beginning of this century. In addition to reducing the emissions of this gas, two major strategies have been proposed to reduce the amount of CO_2 present in the atmosphere: its capture and storage [1-3] and its chemical transformation [4-6]. The chemical transformation of CO_2 is particularly promising as increasing amounts of low-cost and relatively pure CO₂ are available from current plants [7].
In this context, CO₂ methanation (Sabatier reaction) is particularly attractive [8-11]. CO₂ can
be combined with hydrogen (produced by water electrolysis using renewable electricity) to
produce methane (power-to-gas), which can be directly injected into existing natural gas
pipelines [12-14]. Therefore, CO₂ methanation makes it possible to combine an environmental
benefit with an economic opportunity.

The Sabatier reaction is an exothermic reaction that has been studied using catalytic systems
based on Group VIII metals (Ru, Rh, Co, Ni) supported on various oxides (TiO₂, SiO₂, Al₂O₃,
CeO₂, ZrO₂) [9, 11]. Nickel remains the metal of choice, due to its selectivity, activity, low
price and abundance [15-18]. Haldor Topsøe uses Ni-based catalysts supported on alumina for
its own methanation processes (TREMPTM process) [19], and continuous efforts are pursued to
develop active, selective and stable Ni-based catalysts able to operate under mild reaction
conditions [18, 20-25].

14 The role of TiO_2 has been recognized in many reactions, as it enhances the catalytic activity 15 due to specific metal-support interactions [26, 27]. TiO₂ exists in three main crystalline forms, *i.e.* anatase (TiO_{2-anatase}), rutile (TiO_{2-rutile}) and brookite. Each phase exhibits different physical 16 and chemical properties, such as thermal stability, density and band gap as well as surface 17 structure [27, 28]. Several works have been conducted to investigate the influence of the support 18 in methanation catalysts: TiO2 vs Al2O3 or SiO2 supports, but also TiO2-anatase vs TiO2-rutile vs 19 TiO_{2-P25} (a commercial mixture of rutile and anatase phases) [29-34]. On cobalt-based catalysts, 20 the activity of a Co/TiO_{2-rutile} catalyst is remarkably higher than that of Co/TiO_{2-anatase}; and while 21 CH4 is selectively produced on Co/TiO2-rutile, CO is the main product on Co/TiO2-anatase. From 22 an in situ DRIFT study, it was proposed that the high activity of Co/TiO2-rutile is related to the 23 formation of strongly adsorbed CO species on this catalyst [29]. On Ru/TiO₂ catalysts, Prairie 24 et al. have shown that: i) the high Ru dispersion is believed to contribute to the enhanced activity 25

for CO2 methanation, and ii) a synergy exists for mixtures of Ru/TiO2-anatase and Ru/TiO2-rutile 1 2 [30]. From a FTIR study, these authors have evidenced that Ru/TiO_{2-anatase} is a better catalyst for CO production, while Ru/TiO2-rutile is more efficient in CO hydrogenation (the rate 3 determining step of methanation). The resulting ranking is as follows: $Ru/TiO_{2-P25} > Ru/TiO_2$ 4 (mechanical mixture of anatase and rutile to simulate P25) > Ru/TiO_{2-rutile} >> Ru/TiO_{2-anatase}. 5 6 Continuing with ruthenium, Sassove *et al.* have used different catalyst preparation methods, 7 using different TiO₂ crystalline phases and ratios [31, 32]. Phase mixing was also performed at different stages of the catalyst preparation *i.e.*, before RuO₂ deposition, and before or after 8 calcination at 450 °C. These studies have shown that the interaction between the RuO₂ particles 9 10 and the anatase and rutile TiO₂ phases during the calcination step dictates the performance of the Ru/TiO₂ methanation catalyst. The positive effect of support mixing, correlated with RuO₂ 11 migration and stabilization from TiO_{2-anatase} over TiO_{2-rutile}, was noticed only in the case where 12 the mixing was done before the calcination step. Regarding nickel-based catalysts, Bao et al. 13 have shown that the TOF on Ni/TiO2-rutile is almost two orders of magnitude higher than that on 14 Ni/TiO_{2-anatase} for CO₂ methanation, independently of Ni loading and particle size [33]. In situ 15 IR and temperature-programmed surface reaction experiments have revealed that TiO2-rutile 16 significantly enhances the CO dissociation and hydrogenation ability of Ni. To the best of our 17 18 knowledge, a possible synergy between the anatase and rutile phase of TiO_2 for CO_2 methanation has not yet been demonstrated in the case of nickel, although high catalytic 19 activities have been reported for Ni/TiO_{2-P25} catalysts [20]. 20

In this study, we have focused our attention on the interaction between nickel and TiO_{2-rutile} and TiO_{2-anatase} phases by studying the performances of Ni catalysts supported on TiO_{2-rutile}, TiO_{2anatase} and TiO_{2-P25}. We confirmed the better performances of Ni/TiO_{2-rutile} compared to Ni/TiO₂₋ anatase, and revealed for the first time a synergy between the two phases in the Ni/TiO_{2-P25} catalyst or in physical mixtures of Ni/TiO_{2-rutile} and Ni/TiO_{2-anatase}. Catalyst characterizations, as well as catalytic experiments performed with pure catalysts in two separated and successive
 fixed-beds, demonstrate that hydrogen spillover is at the origin of the synergistic effect, but also
 of the different reactivity of Ni/TiO_{2-rutile} and Ni/TiO_{2-anatase} catalysts.

4

5 **2. Methods**

Catalyst synthesis. The commercial TiO₂ supports with different structures used are TiO_{2-rutile}
(99.5 %, Janssen Chimica), TiO_{2-anatase} (99.8 %, Aldrich) and TiO_{2-P25} (Safic-Alcan). In some
experiments, TiO_{2-rutile} and TiO_{2-anatase} were physically mixed in the corresponding proportions
to those of TiO_{2-P25}.

The Ni catalysts were prepared by using an impregnation method. Ni(NO₃)₂, 6H₂O (99.9% 10 Strem Chemical) was dissolved in water, where TiO₂ (rutile, anatase or P25) was then added. 11 The mixture was stirred during 4 h. The water was evaporated to obtain the catalyst, which was 12 dried at 120 °C overnight, and calcined under air at 500 °C during 6 h. The desired quantity of 13 14 Ni(NO₃)₂, 6H₂O to reach a 10 % w/w was used. According to Inductively Coupled Plasma (ICP) analyses, the amount of nickel deposited on each support is similar. The as-prepared 15 catalysts were denoted as 10Ni/TiO2-rutile, 10Ni/TiO2-anatase or 10Ni/TiO2-P25 (with 10 16 17 representing the Ni percentage on the support).

Catalyst characterization. The structural and textural properties of the catalysts were evaluated using different characterization techniques. The specific surface area, pore volume and pore size distribution of the samples were obtained from the isothermal adsorption/desorption of nitrogen at -196 °C on a Quantachrome autosorb instrument with N₂ automatic injection. The specific surface area was determined from the linear part of the Brunauer-Emmett-Teller (BET) plot. The pore volume was measured on the isotherm at $P/P_0 = 0.97$. The pore size distribution was obtained by BJH treatment applied to the desorption branch of the isotherm. All samples were pretreated under vacuum at 90 °C for 1 h to remove adsorbed water, then at 250 °C during
 10 h for all other physisorbed species.

The amount of surface metal was quantified by chemisorption. Hydrogen was used to 3 determine the dispersion of the metal particles for each catalyst. In a first step, the sample (200 4 mg) was reduced using hydrogen (30 mL·min⁻¹) at 400 °C (10 °C·min⁻¹) during 4 h. Argon was 5 6 introduced at the same temperature for 2 h, and then maintained while the reactor cooled to room temperature. At this stage of the analysis, pulses of H₂ were injected on the catalyst, and 7 the amount of residual gas was measured using a TCD detector (Quantachrome autosorb 8 instrument). The metallic dispersion D_{Ni}(%) of the catalysts was calculated from the amount of 9 irreversibly adsorbed hydrogen (HC): $D(\%) = HC/N_T * 100$ (N_T is the total quantity of metallic 10 atom in the sample). 11

Temperature-Programmed Reduction (TPR) experiments were performed with a Micromeritics chemisorb 2700. Firstly, the catalyst (100 mg) was heated to 200 °C (10 °C·min⁻¹) ¹) for 1 h. After the reactor cooled to room temperature, an argon flow (30 mL·min⁻¹) swept the sample for 30 minutes. In a second step, the catalyst was reduced under a gaseous mixture of 16 10% H₂/Ar (30 mL·min⁻¹) with a heating ramp of 10 °C·min⁻¹ to 850 °C. The amount of hydrogen consumed was monitored using a TCD. Peaks of hydrogen consumption were obtained as a function of the temperature.

The distribution, shape, and size of the metal particles were obtained using a JEOL JEM 1011 transmission electron microscope (TEM). The average particle size was determined by measuring at least 100 particles for each sample analyzed and using the following formula: Ni particle size = $\Sigma n_i d_i^3 / \Sigma n_i d_i^2$ (d_i = diameter of n_i particles). The high-resolution analyses were conducted on a JEOL JEM 2100F equipped with a field emission gun (FEG) operating at 200 kV with a point resolution of 2.3 Å and a JEOL JEM-ARM200F Cold FEG operating at 200 kV with a point resolution of > 1.9 Å. The crystalline structure of the samples was determined 1 on a D8 Advance Bruker Diffractometer (XRD) using Cu K α radiation ($\lambda = 0.15418$ nm) as X-2 ray source. The surface of a sample, to a depth of 1 to 10 nm, was observed by X-ray 3 Photoelectron Spectroscopy (XPS) using a Thermo Scientific K-alpha spectrometer equipped 4 with an aluminum monochromatic source (Al K α , hv = 1486.6 eV). Data were processed using 5 the Thermo Avantage© software.

6 DRIFTS spectra were collected using a Harrick cell (powder, ca. 30 mg) fitted in a Nicolet 7 8700 FT-IR (MCT detector). Gas-phase CH₄ and CO₂ were quantified after the DRIFTS using a quartz 10-cm pathlength IR gas-cell fitted in a Bruker FT-IR. The CO signal was very low 8 (and not visible for Ni/Rutile) and was not quantified. The band area of adsorbed CO was 9 calculated and compared for three catalysts. The DRIFTS analysis provides quantitative 10 11 comparison within 10% as long as evolution of the same sample (or same mixture of samples) are compared with each other (hence in each case the optical pathway remains the same). In our 12 case, it is also coherent to compare mechanical mixtures of similar materials, since scattering 13 14 and absorption coefficient should be similar.

In order to understand the behavior and the synergetic effect between the anatase and rutile phases, space-resolved gas sampling was performed using a fused silica capillary (I.D. = 150 μm) inserted in the catalyst bed that moved along the axial direction; data was collected for each position (9 positions in total) along the catalyst using a mass spectrometer (OmniStar, Pferiffer Vacuum). The custom-built reactor was made of ¼" quartz tube with an I.D. of 4 mm. For each experiment, 100 mg of catalyst was used with a particle size between 125 and 200 μm.

H₂-TPD-MS (Altamira Instruments AMI-300 device) was used to elucidate the nature of the
hydrogen adsorbed species during the desorption step. First, the catalyst (or support) (100 mg)
was purged with helium at 120 °C for 1 h in order to clean the surface of the sample. The sample
was then reduced *in situ* at 400 °C (10 °C·min⁻¹) for 4 h using a 1/4 mixture of He/H₂ and then

cooled to room temperature under the same atmosphere. The sample was then swept with
helium at a flow rate of 30 mL·min⁻¹ for 1 h to remove physisorbed and/or weakly bound
species. TPD was performed by heating the sample from 50 to 700 °C with a heating ramp of
10 °C·min⁻¹ in helium and the TPD spectra were recorded.

Catalytic tests. The catalytic tests for the methanation of CO₂ were performed using a 5 6 continuous-flow stainless steel fixed bed reactor (height = 300 mm, e.d. = 9.52 mm, i.d. = 7.97 mm) under a total pressure of 6.1 bar. 200 mg of catalyst with a particle size in the 100-200 µm range were mixed with 1800 mg of SiC (Alfa Aesar). Before the catalytic test, the catalyst was 8 reduced in situ at 400 °C for 4 h under a 1/4 mixture of N₂/H₂, at atmospheric pressure. Then, 9 10 experiments were performed at a constant WHSV (Weigh Hourly Space Velocity) of 2750 NmL_{CO2}·h⁻¹·g⁻¹. under a N₂/H₂/CO₂ gas mixture of 1/4/1 at 340 °C and 6.1 bar. Some tests were 11 also conducted at 260 °C and 6.1 bar, or at 340 °C and 1 bar. Some tests were also performed 12 by dilution of the catalyst in TiO₂ support instead of pure SiC. In typical dilution tests, 200 mg 13 of catalyst were diluted in 1000 mg of TiO₂ support and 800 mg of SiC. 14

The composition of the reactant/product mixture was analyzed using an on-line gas chromatograph (500 Clarius) equipped with two TCD: one with argon as gas vector to quantify H_2 , CH_4 , and CO, and another with helium to quantify CO₂. The GC is equipped with two Shincarbon columns (1/8, 2.0 mm, 80/100), and recorded the formation of methane and conversion of H_2 and CO₂ every 8 min.

The different response coefficients determined from the GC calibration allowed us to calculate
the molar fractions (X) of the different molecules considered during the methanation reaction,
as follows:

23
$$X_{a} = \left(\frac{Area \ of \ a \ signal}{Area \ of \ N_{2} \ signal}\right) \times \frac{1}{k_{a}}$$

- 1 With $a = CO_2$, CH₄, H₂, CO and k = response coefficient.
- 2 The conversion rates of the reagents were then calculated as follows:

3
$$CO_2 \ conversion = \left(1 - \frac{X_{CO_2}}{X_{CO_2} + X_{CH_4} + X_{CO}}\right)$$
 $H_2 \ conversion = \left(1 - \frac{H_2 \ outlet \ flow}{H_2 \ inlet \ flow}\right)$

4 With
$$H_2$$
 outlet flow = Dry flow outlet $\times X_{H_2}$

5 With Dry Flow, the gas flow without water formed during the reaction.

6
$$Dry \ flow \ outlet = \left(\frac{CO_2 \ inlet \ flow}{X_{CO_2} + X_{CH_4} + X_{CO}}\right)$$
 $CH_4 \ yield = \left(\frac{CH_4 \ outlet \ flow}{CO_2 \ inlet \ flow}\right)$

- 7 With CH_4 outlet flow = Dry flow outlet $\times X_{CH_4}$
- 8 *CO* yield = CO_2 conversion CH_4 yield

9
$$CH_4 \ selectivity = \left(\frac{\% CH_4 \ yield}{\% CO_2 \ conversion}\right)$$
 $CO \ selectivity = \left(\frac{CO \ yield}{CO_2 \ conversion}\right)$

10

Possible thermodynamic, heat transfers and mass transfer limitations have been checked (see 11 SI 1 and SI 2). When not specified, all the results are due to an intrinsic kinetic effect and thus 12 reflect a catalytic effect. In order to remove any effect of a different level of conversion between 13 experiments, the quantitative comparison of catalysts has been achieved through a robust 14 kinetic comparison on the basis of estimated inlet CO₂ consumption rates $(r_{co_2}^i)$ at the reactor 15 16 inlet. This goal was achieved thanks to a non-isothermal and non-isobaric unidimensional pseudo-homogeneous plug-flow reactor model combined with the regression of a limited set of 17 kinetic parameters of the kinetic model from Champon et al.[36] More details on this approach 18 are available in the SI 3. The CO₂ consumption rates at the inlet $(r_{CO_2}^i)$, can then be used to 19 calculate corresponding TOF_i at the reactor inlet. These TOF_i, which refer to the number of 20 reacted molecules per surface active Ni per unit of time at the reactor inlet, have been calculated 21

considering dispersion data (TEM mean particle size after testing) obtained from a universal
 mathematical relation [35].

Catalyst stability was evaluated considering a deactivation parameter (DP) based on the
evolution of the inlet reaction rate of CO₂ hydrogenation with time on stream (TOS) defined as
follows:

6
$$DP = \frac{(r_{CO_2}^i)_{TOS=20h} - (r_{CO_2}^i)_{TOS=1h}}{(r_{CO_2}^i)_{TOS=1h}}$$

Because of possible differences in catalyst activity and active specie dispersion, a Turn Over
Number (TON, expressed in mol_{CO2 converted} per mol_{Ni surf.}) is always given simultaneously to
reflect the corresponding work of the catalyst.

- 10
- 11

12 **3. Results**

13 3.1. Catalyst characterization

The specific surface area, pore volume, average pore diameter, Ni loading (ICP), Ni mean 14 particle size and dispersion of the investigated samples are shown in Table 1. The BET area of 15 commercial TiO₂ supports follows the sequence TiO_{2-P25} (57 m² g⁻¹) > TiO_{2-anatase} (10 m² g⁻¹) > 16 TiO_{2-rutile} (4 m² g⁻¹). As already reported for similar catalysts [20], the addition of nickel by 17 impregnation induces a decrease of the specific surface area for the TiO_{2-P25}-based catalyst. 18 Figure 1 shows the H₂-TPR profiles of the calcined Ni/TiO₂ samples, which correspond to the 19 reduction of NiO. The catalysts can be classified according to their reducibility in the following 20 order: 10Ni/TiO_{2-rutile} ~ 10Ni/TiO_{2-anatase} > 10Ni/TiO_{2-P25}. For 10Ni/TiO_{2-rutile} and 10Ni/TiO₂₋ 21 anatase catalysts, the H₂-TPR profile presents a main reduction peak at 420 and 440 °C, 22

respectively. An easier reduction of NiO to Ni⁰ for Ni/TiO_{2-rutile} compared to Ni/TiO_{2-anatase} has 1 been previously reported [37]. The 10Ni/TiO_{2-P25} catalyst profile is relatively broad (stepwise 2 Ni reduction) and the lower reducibility suggests a stronger interaction between Ni and the 3 support, arising presumably from a smaller Ni particle size. Previous H₂-TPR experiments on 4 Ni/TiO_{2-anatase} and Ni/TiO_{2-rutile} have also proposed a stepwise reduction of Ni [33]. Finally, if 5 the discussion on the TPR profiles of Ni/TiO₂ catalysts are generally limited to the reduction of 6 NiO species presenting different type of interaction with the support, some works [38, 39] also 7 reported that the NiO phase reduction can be accompanied by a partial reduction of Ti^{4+} to Ti^{3+} , 8 resulting in the formation of O_{ν} - Ti³⁺ site (where O_{ν} denotes oxygen vacancy). It is not possible 9 to exclude the occurrence of such a phenomenon in our case. 10

The Ni particle size was obtained from both XRD and TEM analyses (Table 1). The TEM and
XRD analyses confirmed a smaller Ni particle size on the TiO_{2-P25} support.

13



14

15 Figure 1. H₂-TPR profiles for the 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile} and 10Ni/TiO_{2-P25} catalysts.

In XRD, the characteristic NiO peak is identified at $2\theta = 43.55^{\circ}$ (Figure 2). Although it has been shown that the anatase-rutile transformation of the TiO₂ support is facilitated by the metallic ions formed during the reduction [40]; such phenomenon was not significant in the present study. The amount of anatase phase in TiO_{2-P25} (78 %) was determined from the equation proposed by Spurr and Myer [41]:

% anatase =
$$(1 + 1.26 * (\frac{lr}{la}))^{-1}$$

7 where Ia ($2\theta = 25.4^{\circ}$) and Ir ($2\theta = 27.6^{\circ}$) are the XRD peak intensities of the anatase and rutile

8 crystal components, respectively.



9

6

Figure 2. XRD diffractograms for the 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile} and 10Ni/TiO_{2-P25}

12

11

catalysts.

13 The images obtained by conventional TEM (Figure 3a-c) allowed us to compare the 14 morphology of the catalysts and to determine the corresponding Ni particle size distribution

(Figure S1). STEM-HAADF images (Figure 3d-f) and EDX mapping (Figure 3g-i) demonstrate 1 the presence of Ni particles on the three catalysts. The Ni particles are larger on TiO_{2-rutile} and 2 TiO_{2-anatase} supports. Nickel is relatively well dispersed, especially on the 10Ni/TiO_{2-P25} 3 catalyst, presumably due to the significantly higher surface area of this support. Although TEM 4 studies have revealed that Ni particles show a non-wetting morphology when grown on TiO₂₋ 5 anatase and a wetting morphology when grown on the rutile (101) surface [42], in our case 6 HRTEM observations (Figure S2) were not conclusive regarding such a phenomenon, even if 7 it appears that the Ni particles on TiO_{2-rutile} were more facetted than the ones on TiO_{2-anatase} 8 (Figures 3a,b and Figure S3). 9



10

Figure 3. TEM images of a) 10Ni/TiO_{2-anatase}, b) 10Ni/TiO_{2-rutile} and c) 10Ni/TiO_{2-P25}; STEMHAADF images of d) 10Ni/TiO_{2-anatase}, e) 10Ni/TiO_{2-rutile} and f) 10Ni/TiO_{2-P25}; and EDX
mapping of g) 10Ni/TiO_{2-anatase}, h) 10Ni/TiO_{2-rutile} and i) 10Ni/TiO_{2-P25}. Scale bar (a-c): 100nm;
(d-i): 200 nm.

The dispersion values of the catalysts obtained by hydrogen chemisorption are very low (0.1-1 1%). Similar results have already been reported, and have been rationalized by the fact that 2 hydrogen adsorption on Ni/TiO₂ is an activated process [43]. In all cases, the dispersion values 3 calculated from the average particle sizes determined by TEM differ from the chemisorption 4 experimental values. However, the trends remain the same. The H₂ adsorption capacity on the 5 various catalysts decreases according to the following order: $TiO_{2-P25} > TiO_{2-rutile} \approx TiO_{2-anatase}$. 6 Since CO adsorption at low temperature (< 200 °C) may result in [Ni(CO)4] formation [44], Ni 7 corrosion and Ni deposition in the setup and lines, CO chemisorption was not performed. 8 XPS analyses were performed just after reducing the samples at 400 °C. The deconvolutions of 9

10 the Ni $2p_{3/2}$ region of the three catalysts are presented on Figure 4. The chemical states of Ni 11 considered are the following [45-48]:

- Ni⁰ particles: 1 peak at 852.6 eV and 2 satellite peaks (856.3 eV and 858.7 eV)

- NiO: 1 peak at 853.7 eV and 4 satellite peaks (855.4 eV, 860.9 eV, 864.0 eV, and
866.3 eV)

15 - Ni(OH)₂: 1 peak at 855.6 eV and 5 satellite peaks (855.7 eV, 857.7 eV, 860.5 eV,
16 861.5 eV and 866.5 eV).

Nickel is present as Ni⁰, NiO and Ni(OH)₂ on the three catalysts. The superposition of the bands 17 does not show any significant differences between the different catalysts at the level of the 18 binding energies. Table 2 groups relevant results obtained after deconvolution of the XPS 19 spectra. The atomic percentage and binding energies associated with all the corresponding 20 peaks are given in Table S8. The relative atomic percentage of Ni⁰ follows the order 10Ni/TiO₂-21 $a_{natase} > 10 \text{Ni}/\text{TiO}_{2-rutile} > 10 \text{Ni}/\text{TiO}_{2-P25}$. The lower amount of Ni⁰ on 10 Ni/TiO_{2-P25} is in 22 accordance with the TPR results, and should be due to the smaller particle size measured for 23 this catalyst. Indeed, small Ni⁰ particles interact strongly with the support, and react with 24 oxygen at a faster rate than with large particles [49]. 25

Table 1. Specific surface area, pore volume, average pore diameter, Ni loading (ICP), Ni mean particle size and dispersion of the investigated samples.

Sample	BET surface area (m ² g ⁻¹)	Pore volume $(cm^3 g^{-1})$	Average pore diameter (nm)	%Ni	Ni particle size (nm) ^a	Ni particle size (nm) ^b	Ni particle size (nm) ^c	$D_{\mathrm{Ni}}(\%)^d$
TiO _{2-anatase}	10	0.12	15	-	-	-	-	-
TiO _{2-rutile}	4	0.05	15	-	-	-	-	-
TiO _{2-P25}	57	0.31	17	-	-	-	-	-
10Ni/TiO ₂ - anatase	10	0.14	17	11.0	31	24	27	4.4
10Ni/TiO2-rutile	4	0.05	16	10.1	33	27	29	4.1
10Ni/TiO _{2-P25}	47	0.37	15	10.1	22	17	20	6.1

^a The Ni crystal size after reduction, from TEM.
^b The Ni crystal size after reduction, from XRD.
^c The Ni crystal size after catalysis (340°C, time-on-stream (TOS) = 25 h), from TEM.
^d Dispersion of Ni, calculated from the average particle sizes determined by TEM.

Regarding the difference between $10Ni/TiO_{2-anatase}$ (36 % Ni⁰) and $10Ni/TiO_{2-rutile}$ (25.5 % Ni⁰), it might be related to the different Ni/Ti surface atomic ratios in these samples. The $10Ni/TiO_{2-}$ *rutile* catalyst shows a significantly higher ratio (0.81) than $10Ni/TiO_{2-anatase}$ (0.31), which should result from the lower surface area of the TiO_{2-rutile} support. Another explanation for the higher Ni/Ti surface atomic ratio observed on $10Ni/TiO_{2-rutile}$ could arise from the fact that Ni particles on TiO_{2-anatase} are wrapped by a thin TiO_x overlayer [33, 50].



Figure 4. Deconvolutions of Ni $2p_{3/2}$ peak of the catalysts, after *ex-situ* reduction under H₂ at 500 °C a) 10Ni/TiO_{2-*anatase*}, b) 10Ni/TiO_{2-*rutile*}, and c) 10Ni/TiO_{2-*P25*}. d) Superposition of the Ni $2p_{3/2}$ bands of the three samples.

However, our HRTEM observations and STEM-EDX analyses (Figures S4), as well as the catalytic results (see below) do not support this possibility on any of the three supports. This is understandable if we consider that for Ni/TiO₂ catalysts, strong metal support interactions are

significant when a high calcination temperature is used, typically around 800 °C [51, 52]. The low Ni/Ti surface atomic ratio measured for 10Ni/TiO_{2-P25} should be related to the much higher specific surface area of this catalyst. No significant changes in the Ni⁰ binding energy were noticed for the three catalysts, precluding significant differences in charge transfer between these samples, which could affect selectivity in the Sabatier reaction [53, 54]. This is expected if we consider the large Ni particle size; but we cannot exclude that some differences exist in the interfacial region between the metal and the support. Titanium is in the Ti⁴⁺ form, and the Ti³⁺ form characteristic of reduced TiO₂ [55] was not detected (Figure S5) under these conditions. From HRTEM observations, STEM-EDX analyses (Figures S4) and these XPS data, we can thus exclude the mobility of TiO_{2-x} over the nickel surface.

Table 2. Atomic relative percentage of Ni species, Ni⁰ and Ti binding energy and Ni/Ti at. ratios of the catalysts determined by XPS analyses after *ex situ* reduction under H₂ at 400 °C.

Catalyst	Ni ⁰ (%)	Ni(OH) ₂ (%)	NiO (%)	Ni ⁰ B.E. (eV)	Ti B.E. (eV)	Ni/Ti
10Ni/TiO _{2-anatase}	36.0	42.0	22.0	852.6	459.1	0.31
10Ni/TiO2-rutile	25.5	35.6	38.9	852.5	459.2	0.81
10Ni/TiO _{2-P25}	19.7	50.6	29.6	852.6	459.3	0.14

Based on the above analyses, we can conclude that the main difference between the three catalysts arise mainly from the higher BET surface area of TiO_{2-P25} , which allows a better nickel dispersion on that support. The smaller Ni particles present on TiO_{2-P25} are more difficult to reduce than those supported on $TiO_{2-anatase}$ or $TiO_{2-rutile}$. The higher dispersion of Ni on $10Ni/TiO_{2-P25}$ should result in a higher catalytic activity for CO₂ methanation, as demonstrated by Wei *et al.* [20].

3.2. Evaluation of the catalytic behavior

The catalytic performances of the obtained Ni/TiO₂ catalysts towards the reaction of CO₂ methanation were studied under different configurations: i) pure catalysts in single fixed-bed reactor configuration; ii) mixture of catalysts in single fixed-bed reactor configuration, and iii) pure catalysts in two separated and successive fixed-beds. Reproducibility tests were regularly performed on the 10Ni/TiO_{2-P25} catalyst, showing experiment error in the range \pm 5%.

Pure catalysts in single fixed-bed reactor configuration. Figure 5 shows the CO₂ consumption rates at the inlet of the reactor ($r_{co_2}^i$) and CH₄ selectivity of 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-P25}, and 10Ni/TiO_{2-rutile} at 260 °C. Table 3 summarizes the values of CO₂ conversion, CH₄ selectivity, CO₂ consumption rate and initial TOF at 260 and 340 °C. At 260 °C, the conversion values were all below 10%, far from the thermodynamic equilibrium composition. Thus, any thermodynamic limitation can be excluded at 260°C (see SI 1-2 for further details). The reaction rate at the inlet of the reactor $r_{co_2}^i$ of the three catalysts follows the order: $10Ni/TiO_{2-P25} >$ 10Ni/TiO_{2-rutile} >> 10Ni/TiO_{2-anatase} (k_{CO2meth} kinetics constants are given in SI.2, Table S7). These results confirm the findings of Bao et al. for Ni/TiO₂ catalysts; i.e. Ni/TiO₂-rutile is much more active than Ni/TiO_{2-anatase} for CO₂ methanation [33]. Since the 10Ni/TiO_{2-P25} catalyst presents a smaller mean Ni particle size compared to 10Ni/TiO2-rutile and 10Ni/TiO2-anatase catalysts (Table 1), the TOF_i led to the following order $10Ni/TiO_{2-rutile} \approx 10Ni/TiO_{2-P25} >>$ 10Ni/TiO_{2-anatase}. Additionally, as the Ni particle size is significantly smaller on TiO_{2-P25} than on TiO_{2-rutile}, no obvious structure sensitivity is apparent in the particle size range investigated. Considering that: i) the Ni particle size is similar on 10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} catalysts, ii) no TiO_x overlayer is present on these particles, and iii) the nature of the metal/support interaction is not significantly different for these catalysts (except maybe at the interface), it is reasonable to propose that all catalysts should contain mainly interfacial actives sites, *i.e.* those located at the gas/particle/support interface [56].



Figure 5. Comparison of: a) CO₂ consumption rates at the inlet of the reactor; and b) CH₄ selectivity of 10Ni catalyst on 10Ni/TiO_{2-*anatase*} (blue diamonds), 10Ni/TiO_{2-*rutile*} (red circles) and 10Ni/TiO_{2-*P25*} (black triangles) at 260 °C.

Table 3. CO_2 conversion, CH_4 selectivity, CO_2 consumption rate and initial TOF (TOF_i) of Ni catalysts on different supports obtained at 260 °C and 340 °C.

Catalyst	$\mathrm{CO}_2 \operatorname{conv.} (\%)^{\mathrm{a}}$	CH ₄ selec.(%) ^a	$\mathbf{r_{co_2}^i} \; (\mathrm{mmol_{CO2}} \; \mathrm{g_{cat}}^{-1} \; \mathrm{h}^{-1})$	TOF _i (h ⁻
10Ni/TiO _{2-anatase}	4.5 (42.6)	66.4 (79)	5.8	71
10Ni/TiO _{2-rutile}	8.8 (78.4)	99.5 (98.3)	11.7	166
10Ni/TiO _{2-P25}	11.0 (95.6)	99.9 (99.5)	15.1	146

^a The values between brackets are the value obtained at 340 °C.

As far as selectivity is concerned, it follows the order: 10Ni/TiO_{2-P25} ≈ 10Ni/TiO_{2-rutile} >
10Ni/TiO_{2-anatase}. In the case of 10Ni/TiO_{2-anatase}, higher amounts of CO are produced. It has
also been shown that the binding strengths of key reaction intermediates at the metal/oxide
interface determine the reaction pathways and selectivity in CO₂ hydrogenation reactions [57,
58]. The presence of Ni single atoms or very small nanoparticles or clusters that bind CO too
weakly, could also facilitate an easy desorption [54, 59, 60].

7 The stability of the catalyst is also an important property for CO₂ methanation because of possible Ni sintering and coke deposition under the exothermic reaction conditions, which can 8 9 lead to fast deactivation. The catalyst stability was investigated for the three catalysts using 10 deactivation parameter (DP) representing the relative loss in reaction rate at the inlet of the reactor and a corresponding TON. These evaluations were done at 260 °C and 340 °C under a 11 constant GHSV of 16500 NmL/h/g_{cata} for a time on stream of 20 h. For the experiments at 260 12 °C (Figure S6), no detectable deactivation occurs during 20 h for 10Ni/TiO_{2-rutile} and 10Ni/TiO₂₋ 13 P25 and a slight one for 10Ni/TiO2-anatase with a DP around 7 %. Final TON values of 1340, 2750 14 15 and 2214 are reached for a TOS of 20 h at 260 °C for 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile} and 16 10Ni/TiO_{2-P25} respectively. The same experiments run at 340°C (Figure S6) indicate again that no detectable deactivation was observed for 10Ni/TiO2-rutile and 10Ni/TiO2-P25 and a pronounced 17 one is observed for 10Ni/anatase (DP = -62%). Nonetheless, the high conversion level 18 encountered with 10Ni/TiO_{2-P25} at this temperature is too close to the thermodynamic 19 equilibrium to draw any robust conclusion on the catalyst stability at this temperature for this 20 catalyst. One can just reasonably expect that it is due to its similarity with the rutile catalyst. 21

The final TON values reached during these experiments are logically higher than the former ones and are of 12 710, 27 250 and 22 370 for 10Ni/TiO_{2-*anatase*}, 10Ni/TiO_{2-*rutile*} and 10Ni/TiO₂₋ *p*₂₅ respectively. Deactivation of Ni/TiO₂ catalysts during CO₂ methanation has been ascribed either to coke formation through either CH₄ decomposition, or *via* CO disproportionation [24], or to nickel oxidation [61]. It is interesting to notice that this deactivation is more likely on the
catalyst prepared on the anatase phase, which also produces more CO available for
disproportionation.

4 Mixtures of catalysts in single fixed-bed reactor configuration. In order to obtain more information on the influence of the TiO₂ phase on the catalytic performances, calcined 5 6 10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} catalysts were physically mixed at different weight ratio. 7 Table 4 shows the CO₂ conversion, CH₄ selectivity, CO₂ consumption rate and inlet TOF_i of these catalyst mixtures. Figure S7 shows the evolution with ToS of CO₂ consumption rate and 8 CH₄ selectivity. The use of 10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} catalyst mixtures (presenting 9 10 similar particle sizes) improves the CO₂ consumption rate, and a synergistic effect is evidenced (k_{CO2meth} kinetics constants are given in SI.2, Table S7). Interestingly, the synergistic effect was 11 noticed even if the catalysts were mixed after the calcination step, which differs from the work 12 of Sassoye et al. [31,32]. Figure 6 shows the inlet CO₂ consumption rate and the corresponding 13 14 TOF_i for the mixed series from pure 10Ni/TiO_{2-anatase} to pure 10Ni/TiO_{2-rutile} catalyst, as a function of the anatase content in the supports. A synergy is clearly observed for a % of 15 10Ni/TiO_{2-anatase} between 40 and 80%, as the catalyst mixtures are more active than the 16 corresponding calculated weighted rates based on single-phase rates. The highest TOF_i was 17 18 obtained for a ratio 70/30, close to the 72/28 ratio of TiO_{2-P25} . It is worth noting that the TOF_i of the 70/30 mixture (211 h⁻¹, Table 4) is markedly higher than that of 10Ni/TiO_{2-P25} (146 h⁻¹). 19



Figure 6. a) CO₂ consumption rate at the inlet of the reactor; and b) TOF_i at 260 °C for the
mixed series from pure 10Ni/TiO_{2-anatase} to pure 10Ni/TiO_{2-rutile} catalyst, as a function of the
anatase content. The full lines indicate the calculated weighted average of 10Ni/TiO_{2-anatase} and
10Ni/TiO_{2-rutile} individual performances. The red diamond corresponds to the 10Ni/TiO_{2-P25}
catalyst.

Table 4. CO_2 conversion, CH_4 selectivity, CO_2 consumption rate (sum of methanation reaction rate and RWGS reaction rate) at the inlet of the reactor, initial TOF, and specific activity of $10Ni/TiO_{2-anatase} + 10Ni/TiO_{2-rutile}$ at different ratio and 260 °C (average values after 20 h).

10Ni/TiO _{2-anatase} /10Ni/TiO _{2-rutile}	CO ₂ conv. CH ₄ selec.		r ⁱ co ₂	TOFi
(weight %)	(%)	(%)	(mmolCO2 g _{cat} ⁻¹ h ⁻¹)	(h ⁻¹)
100/0	4.5	66.4	5.8	71
80/20	6.1	87.9	7.9	101
70/30	11.9	97.8	16.3	211
60/40	9.1	92.7	12.2	159
40/60	8.7	94.7	11.6	155
20/80	6.5	94.7	8.5	117
0/100	8.8	97.2	11.7	166

Pure catalysts in two separated and successive fixed-beds. We performed a series of 1 2 experiments with two successive beds of 10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} (Figure S8 shows the two reactor configurations with the two separated beds). In the first configuration (C1), the 3 gas flow passes first through a bed of 10Ni/TiO_{2-rutile}, and then through a separate bed of 4 10Ni/TiO_{2-anatase}. In the second configuration (C2), the gas flow passes first through a bed of 5 6 10Ni/TiO_{2-anatase}, and then through a separated bed of 10Ni/TiO_{2-rutile}. It is important to note that 7 in these two configurations the two beds are not in physical contact since they are separated using quartz wool. The results of this series of experiments are summarized in Table 5. 8

9

10 **Table 5.** CO₂ conversion and CH₄ selectivity of two successive beds of 10Ni/TiO_{2-rutile} (20%)

and 10Ni/TiO_{2-anatase} (80%) and vice versa at 260 °C. Conversion and selectivity reported here

12 are average values for 20 h of TOS.

Configuration	$CO_2 \operatorname{conv.}(\%)$	CH ₄ selec. (%)
C1 first 10Ni/TiO _{2-rutile} then 10Ni/TiO _{2-anatase}	11 (5.6) ^a	84.4 (78.6) ^a
C2 first 10Ni/TiO _{2-anatase} then 10Ni/TiO _{2-rutile}	3.5 (5.4) ^a	97.9 (77.1) ^a

13 ^a Expected values (without the synergy) obtained by the simulation of the two successive beds using regressed

14 kinetic parameters of pure 10Ni/TiO₂-rutile and pure 10Ni/TiO₂-anatase are given between brackets.

15

This series of experiments is important since it clearly demonstrated that a physical contact between the two catalysts is not necessary to obtain the synergistic effect in the case of the configuration C1. Our results contrast significantly with previous studies showing an influence of the TiO₂ crystallographic phase on CO₂ methanation, since: i) from XPS analyses, activity does not seem to be linked to a different electronic interaction between Ni and TiO₂ as previously discussed [33], except maybe at the interface where should be located the active sites; and ii) the hypothesis of metal migration [31] is excluded from this latter experiment
 series.

3 *3.3. Space resolved-gas-sampling analyses.*

The following conditions were used for space-resolved gas sampling during CO₂ methanation: 4 $P_{total} = 1$ bar, T = 340 °C; CO₂/H₂/He = 1/4/10; WHSV = 1200 NmL_{CO2} h⁻¹ g⁻¹.Under these 5 conditions, CO₂, CH₄, and CO were quantified using an FTIR spectrometer to follow the gas 6 7 phase composition under different reactor configurations: i) 10Ni/TiO_{2-anatase}; ii) 10Ni/TiO₂₋ rutile; iii) 10Ni/TiO_{2-anatase} (80%) +10Ni/TiO_{2-rutile} (20%) catalyst mixture; iv) two beds 8 configuration - first 10Ni/TiO_{2-anatase} (80%) then 10Ni/TiO_{2-rutile} (20%); and v) two beds 9 configuration - first 10Ni/TiO_{2-rutile} (20%) then 10Ni/TiO_{2-anatase} (80%). The catalytic results 10 (conversion and selectivity) obtained at atmospheric pressure in these experiments as well as in 11 the methanation reactor are presented on Table S9 and Table S10, respectively. The space-12 resolved gas sampling was performed using a capillary inserted in the catalyst bed (Figure S9) 13 14 that moved along the axial direction; data were collected for each position along the catalyst 15 using MS. The quantitative results obtained are summarized on Figure 7. This series of experiments shows that 10Ni/TiO2-rutile promotes the formation of CH4 (Figure 7b), while 16 10Ni/TiO2-anatase promotes the RWGS reaction with formation of CO, together with CH4 (Figure 17 7a). When the 2-bed configuration is used, it is observed that: i) in the configuration 10Ni/TiO₂-18 rutile first, CO₂ methanation occurs first, and then on 10Ni/TiO_{2-anatase} RWGS comparably more 19 accelerated; and ii) in the configuration 10Ni/TiO2-anatase first, first CO2 methanation and RWGS 20 take place, the evolved CO on Ni/TiO_{2-anatase} does not further react on the Ni/TiO_{2-rutile} catalyst 21 that only produces more CH₄ and water. Due to the rather low activity at the atmospheric 22 pressure of this space-resolved gas sampling study, the differences between the two sequential-23 bed configurations are not large. Nevertheless, the selectivity trends defined by the support 24

structure and also the advantage of the close vicinity of the anatase TiO_2 and rutile TiO_2 supported Ni catalysts on methanation activity is evident (Figure 7c vs. Figures 7d and 7e).



Figure 7. Space-resolved gas sampling for: a) 10Ni/TiO_{2-anatase}; b) 10Ni/TiO_{2-rutile}; c) catalyst
mixture 10Ni/TiO_{2-anatase} (80%) +10Ni/TiO_{2-rutile} (20 %); d) 2 beds – 20% 10Ni/TiO_{2-rutile} and
80% 10Ni/TiO_{2-anatase}; and e) 2 beds – 80% 10Ni/TiO_{2-anatase} and 20% 10Ni/TiO_{2-rutile}. (blue:
CO₂; orange: CH₄; and brown: CO (the contribution from CO₂ has been subtracted)). MS
profiles (a.u.) along the catalyst bed were converted into concentration profiles (in vol. %) by
using the inlet and outlet gas concentrations measured by FTIR.

1 3.4 Surface species analysis by DRIFTS operando

For surface species analysis by DRIFTS operando during CO₂ methanation, the following 2 conditions were used: $P_{total} = 1$ bar, T = 280-340 °C; $CO_2/H_2 = 1/4$; WHSV = 336 NmL_{CO2} h⁻¹ 3 g⁻¹. These experiments were performed after reducing the catalyst under H₂ at 400 °C for 1 h. 4 Under these conditions, 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile} and the catalyst mixture 80% 5 10Ni/TiO_{2-anatase} + 20% 10Ni/TiO_{2-rutile} were studied. First, the relative rates were measured at 6 7 280 °C, and under these conditions, a synergistic effect was also observed, as compared to weighted activities (Figure S10). A series of experiments was also performed at different 8 9 temperatures to calculate the apparent activation energy (SI.2, Table S7). The calculated 10 activation energies were 80 (10Ni/TiO_{2-anatase}), 105 (10Ni/TiO_{2-rutile}), 133 (10Ni/TiO_{2-P25}) and 85.5 kJ.mol⁻¹ (catalyst mixture). Figure 8a shows the spectra for the 10Ni/TiO_{2-rutile} catalyst at 11 various temperatures between 50 and 280 °C taken in the DRIFTS cell under a CO₂+H₂ feed. 12 Only the large band of $CO_2(g)$ at 2360 cm⁻¹ is visible for all the temperatures, whereas the 13 CH₄(g) band at 3050 cm⁻¹ starts to appear at 260 °C. There are no visible surface species on 14 15 10Ni/TiO_{2-rutile}. If, at 280 °C, H₂ is removed from the gas mixture, two large bands at 1875 and 2024 cm⁻¹ appear, characteristic of multi-bonded and linear CO on Ni, respectively. These 16 bands disappeared when H₂ was added again to the gas mixture, meaning that nickel carbonyl 17 18 species are reversibly formed when H₂ is removed (Figure S11). DRIFTS spectra were also recorded at various temperatures with 10Ni/TiO_{2-anatase} (Figure 8b). In that case, carbonyls 19 adsorbed on Ni are visible under a CO₂+H₂ feed, exhibiting two characteristic bands at 1842 20 cm⁻¹ for multi-bonded nickel carbonyl and 2070 cm⁻¹ for linear nickel carbonyl species. 21 Surprisingly, the CO adsorbed on Ni with the mixture of H₂/CO₂ is slowly removed when H₂ 22 23 is not present in the gas mixture (Figure S12). Ni-CO species are still present 5 min after removing H₂, and they only disappear after 4 h. 24



Figure 8 DRIFTS spectra recorded under 2% CO₂ + 8% H₂ (1 bar) for: a) 10Ni/TiO_{2-rutile} at
various temperatures; b) 10Ni/TiO_{2-anatase} at various temperatures; and c) 10Ni/TiO_{2-rutile},
10Ni/TiO_{2-anatase} and the catalyst mixture 80% 10Ni/TiO_{2-anatase} + 20% 10Ni/TiO_{2-rutile} at 280°C.
(WHSV = 336 NmL_{CO2} h⁻¹ g⁻¹).

This contrasts with the data collected over the 10Ni/TiO_{2-rutile} catalyst, possibly due to 1 2 differences in CO₂ adsorption or dissociation rates or CO desorption rate (and the gradual oxidation of Ni particles by CO₂ in the absence of H₂). There is no visible formation of formate 3 or carbonate species on nickel. These results contrast with those obtained by Bao et al. at much 4 lower temperature (i.e. 75 °C) [33], who observed the formation of hydrogenocarbonate species 5 on both Ni/TiO_{2-rutile} and Ni/TiO_{2-anatase} catalysts. The higher temperatures used here likely led 6 7 to lower surface coverage of these weakly bound species. The study by Bao et al. was also conducted at atmospheric pressure, but using a catalyst reduced 4 h at 500°C and at a higher 8 WHSV (2400 NmL_{CO2} g⁻¹ h⁻¹). The fact that such adsorbed species were not observed in this 9 10 study could thus be related to: i) a low surface coverage; or ii) the reduction conditions. For this latter possibility, Panagiotopoulou et al. have recently shown that during CO₂ methanation 11 formate species appeared after prolonged catalyst reduction [62]. The same operando DRIFTS 12 experiments were performed with the mixture of catalysts. Figure 8c shows a comparison of 13 the three catalysts. A quantitative analysis of the sample spectra at 280 °C (Figure 8.c) is only 14 valid if the materials exhibit similar scattering and absorption coefficient, leading to similar 15 optical pathlengths. This can be assumed to be true in the present case, since a mixture of the 16 same loading of Ni supported on two titania polymorphs are considered. For the catalyst 17 18 mixture 80% 10Ni/TiO_{2-anatase} + 20% 10Ni/TiO_{2-rutile}, CO adsorbed on metallic Ni is still visible, but the band area of adsorbed CO has a calculated value of 0.79 for the mixture, when a value 19 of 1.25 (= 0.8 * 1.56) would be expected for an 80% dilution of the signal obtained on the pure 20 10Ni/TiO2-anatase. This important observation corroborates the fact that the 10Ni/TiO2-rutile 21 assisted the hydrogenation of the CO(ads) on the 10Ni/TiO_{2-anatase}. This result enables to unravel 22 the origin of one of the synergetic effects between 10Ni/TiO_{2-rutile} and 10Ni/TiO_{2-anatase}. 23

24

1 3.5 H₂-TPD experiments and catalytic tests to assess hydrogen spillover

2 The results from catalyst characterization, catalytic study, operando DRIFTS and MS study can
3 be summarized as follows:

10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} present similar Ni particle size before and after
 catalysis, and from XPS analyses, similar metal support interactions (except maybe at
 the interface where should be located the active sites);

for pure catalysts, the activity, selectivity and stability for CO₂ methanation are higher
on Ni/TiO_{2-rutile} than those on 10Ni/TiO_{2-anatase};

9 - when a mixture of these two catalysts is used, a synergistic effect is observed, since the
10 measured rate of the mixture is higher than the corresponding calculated weighted rate;
11 - the two catalysts do not need to be in physical contact for the synergistic effect to occur
12 (configuration C1);

during the methanation reaction, adsorbed CO is accumulating on Ni/TiO_{2-anatase}, and
 one role of the Ni/TiO_{2-rutile} could be to assist the hydrogenation of this adsorbed CO.

15

Taken together, these results suggest that: i) these catalysts could contain mainly interfacial 16 actives sites; ii) Ni/TiO_{2-anatase} is a more selective but less active RWGS reaction catalyst 17 compared to Ni/TiO2-rutile (hypothesis independently checked, see Figure S12), which is a 18 necessary step for methanation; iii) methanation of CO, generally recognized as the rate-19 20 determining step of the reaction [30, 63-66], should be faster on Ni/TiO_{2-rutile} [33], iv) hydrogen spillover, which occurs fast and at relatively large distances on reducible supports, by surface 21 species but also by gas-phase radicals [67-69], could be involved in the process, by assisting 22 23 the CO₂ hydrogenation steps on Ni/TiO_{2-anatase}; and v) the optimal anatase/rutile ratio can arise from the balance of the reaction rates for the H-spillover and CO₂ methanation. 24

Concerning hydrogen spillover, it is worth mentioning that it has already been proposed as the 1 2 explanation of the synergy between Pd/γ -Al₂O₃ and Rh/ γ -Al₂O₃ catalysts in CO₂ methanation [70]. In that study, the authors have shown that although Pd/ γ -Al₂O₃ is inactive at 200 °C, the 3 activity of mechanical mixtures of the two catalysts was up to 50 % higher than that of the pure 4 Rh/y-Al₂O₃ catalyst. While Pd/y-Al₂O₃ alone could not hydrogenate the Pd-CO adsorbed 5 species, the presence of Rh/y-Al₂O₃ significantly increased the reactivity of Pd-CO species, 6 7 which was proposed to account for the observed synergistic effect, via hydrogen spillover. Synergies associated to H-spillover were also reported for mechanical mixtures of Rh/y-Al₂O₃ 8 (methanation catalyst) and Ni/C (spillover catalyst) [71], for Ni-Ru/SiO₂-La₂O₃ catalysts (Ni: 9 10 methanation catalyst, and Ru: spillover catalyst) [72], or for Co-Pt/SiO₂ catalysts [73, 74]. In this latter case, it was shown that the H-spillover (from Pt to Co) significantly enhance the 11 reduction of Co. This effect could be also important in our case since: i) it is known that Ni 12 deactivation can occur due to coke formation [75] or formation of Ni-hydroxide by reaction 13 with water [63], and ii) the deactivation observed for pure Ni/TiO_{2-anatase} is suppressed when 14 using the catalyst mixture (see Figure S7). Another implication of H-spillover in CO₂ 15 methanation on Ru/CeO₂ [76] and Ni/MgO [77] catalysts is related to H-assisted H₂O removal. 16 H2-TPD of the three catalysts, 10Ni/TiO2-anatase, 10Ni/TiO2-rutile and the physical mixture, were 17 performed after hydrogen reduction at 400 °C in order to quantify the spillover of hydrogen. 18 The total amounts of H₂ adsorbed on these three catalysts were 29.6, 50.3 and 32.9 µmol.g⁻¹ for 19 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile} and the mixture, respectively. Concerning the supports (Figure 20 9), higher amounts of H₂ were observed for the TiO_{2-rutile} (4 m² g⁻¹) than for TiO_{2-anatase} (10 m²) 21 g^{-1}). The heterolytic H₂ dissociation (leading to a hydride and a hydroxyl) on TiO_{2-rutile} has been 22 reported to proceed much more easily ($E_a = 8.5$ kcal mol⁻¹) than on TiO_{2-anatase} ($E_a = 24$ kcal 23 mol⁻¹) [78]. For TiO_{2-rutile}, the hydride produced by the H₂ heterolytic activation can transfer 24 from Ti to O with activation energy of 22.8 kcal mol⁻¹, yielding the homolytic products. For the 25

catalysts, higher amounts of H₂ were observed for the 10Ni/TiO_{2-rutile} compared to 10Ni/TiO₂₋ 1 anatase. Theoretical calculations have shown that although H₂ desorption is difficult on a 2 stoichiometric TiO₂ surface, it becomes easier (and favored upon H₂O desorption) with an 3 increase in Ov, which are generated by H₂O desorption [79]. Two main desorption peaks are 4 observed at ~190 and ~300 °C. The presence of these two peaks in Ni/TiO₂ catalysts has already 5 been reported [80]. The peak at lower temperature (190 °C) can be attributed to hydrogen 6 chemisorbed at the surface of the Ni particles [20], and to reverse hydrogen spillover. The 7 presence of a peak at higher temperatures has been discussed in several studies dealing with 8 hydrogen spillover on TiO₂ supports, it is ascribed to H-spillover associated with the support 9 10 [81, 82]. The desorption of hydrogen adsorbed at interfacial sites located at the metal-support interface has also be invoked [83]. These analyses point to a higher H-spillover on 10Ni/TiO₂. 11 rutile than on 10Ni/TiO2-anatase. On Ru/TiO2 catalysts, the opposite situation was observed [53], 12 which highlights the importance of the intimate interaction between the metal and the support 13 on the jump of the hydride from the metal to the support. 14

15



17 Figure 9. H₂-TPD profiles over TiO_{2-anatase}, 10Ni/TiO_{2-anatase}, TiO_{2-rutile} and 10Ni/TiO_{2-rutile}.



Figure 10. Comparison of: a) CO₂ consumption rates at the inlet of the reactor; and b) CH₄
selectivity at 260 °C of 10Ni/TiO_{2-P25} diluted with 1.8 g of SiC (black triangles), diluted in TiO₂₋ *rutile* (red circles) - 0.2g 10Ni/TiO_{2-P25} + 1g TiO_{2-rutile} (+ 0.8 g SiC), and diluted in TiO_{2-anatase}
(blue diamonds) - 0.2g 10Ni/TiO_{2-P25} + 1g TiO_{2-anatase} (+ 0.8 g SiC).

Since spillover is often postulated when a dilution of the catalyst leads to an activity increase, 1 2 we performed two experiments starting from the 10Ni/TiO_{2-P25} catalyst, measuring the CO₂ consumption rate evolution upon dilution of the catalyst with either TiO2-rutile or TiO2-anatase (in 3 addition to SiC). The increase of the rate with higher degrees of dilution can be understood if 4 one admits that the reaction also involves the support (because of spillover hydrogen) in 5 addition to reactivity occurring on the sites of the Ni/TiO₂ particles. The results of these 6 experiments performed at 260 °C in order to better quantify differences are shown on Figure 7 10 and Table S11. 8

For both tests performed with diluted catalysts, the rate increases, confirming hydrogen 9 spillover. The rate increase is significantly higher when the dilution is performed with the TiO₂-10 anatase support, with a calculated TOF = 0.0197 s^{-1} , which is one of the highest reported for Ni-11 catalyzed CO₂ methanation at this temperature and GHSV (see Table S12 for comparison with 12 reference catalysts). We independently verified that an increase in CO₂ consumption rates was 13 also observed after dilution of the 10Ni/TiO2-rutile catalyst in pure TiO2-anatase support (Figure 14 15 S14 and Table S13). These data suggest that CO₂ is also hydrogenated on the Ni-free TiO₂. anatase and much less on the Ni-free TiO_{2-rutile}. On TiO_{2-anatase}, however, the reaction seems to be 16 slightly less selective (Table S11) since small amounts of CO are produced. 17

These results can be rationalized by: i) an easier spillover hydrogen species diffusion on TiO₂. 18 anatase than on TiO_{2-rutile} and/or ii) the higher specific surface area of TiO_{2-anatase} (10 m² g⁻¹) 19 compared to TiO_{2-rutile} (4 m² g⁻¹). To evaluate the impact of the support surface area we also 20 performed a dilution test with the 10Ni/TiO_{2-P25} catalyst and only 0.4 g of TiO_{2-anatase} to be at 21 isosurface with 1 g of TiO_{2-rutile} (Table S11). In that case the CO₂ consumption rate increases 22 compared to pure 10Ni/TiO_{2-P25} (15.0 mmol_{CO2} g_{cat}⁻¹ h⁻¹) is not so high. Indeed, the rate is 25.0 23 mmol_{CO2} g_{cat}⁻¹ h⁻¹ (0.4 g of TiO_{2-anatase}) instead of 45.4 mmol_{CO2} g_{cat}⁻¹ h⁻¹ (1 g of TiO_{2-anatase}), which 24 is still higher than with 1 g of TiO_{2-rutile} (21.3 mmol_{CO2} g_{cat}^{-1} h⁻¹). 25

If the bare supports are considered, the mechanism for hydrogen atom diffusion has been 1 2 investigated by DFT [84-86]. Three competing processes have been taken into account, namely, migration of H on the surface, diffusion of H into the bulk, and hydrogen desorption. On both 3 supports, diffusion of H into the bulk is both kinetically and thermodynamically favorable. 4 Activation barriers for bulk migration of 102 and 67 kJ mol⁻¹ have been reported for TiO_{2-rutile} 5 and TiO_{2-anatase}, respectively. This latter result corroborates our experimental findings. We can 6 thus propose that Ni-initiated hydrogen spillover on Ni/TiO₂ creates active sites on the TiO₂ 7 bare support for CO₂ hydrogenation. The generation thanks to H-spillover of active 8 hydrogenation sites on TiO₂ (Ov created by partial reduction of TiO₂) has already been reported 9 during the Ag/TiO₂ catalyzed hydrodeoxygenation of guaiacol [87] and the Fe/TiO₂ catalyzed 10 ammonia synthesis [88]. 11

It thus appears that the origin of the synergetic effect between TiO_2 crystalline phases in the Ni/TiO₂ catalyzed CO₂ methanation reaction comes from hydrogen activation. The Ni/TiO₂*rutile* catalyst is much more active for CO₂ reduction to methane than Ni/TiO₂-*anatase* for a CO₂/H₂ ratio of 1/4 and 1/1. On the other hand, Ni/TiO₂-*anatase* is more selective for the RWGS reaction catalyst, and the diffusion of H-species is easier on the TiO₂-*anatase* support than on TiO₂-*rutile*. Thus, in a catalyst mixture, the H-species resulting from the spillover on the Ni/TiO₂-*rutile* catalyst should have the tendency to accumulate on the TiO₂-*anatase* support (Scheme 1).

The contact between the two supports is actually not necessary since gas phase hydrogen spillover can occur [66-68, 89-91]. Even if thermodynamically the gas phase H spillover concentration should be very low [92], it should permit a fast formation of H species adsorbed on the support. Additionally, the water present in the gas phase could be involved in the transport process maybe *via* the reactor walls or the quartz wool used to separate the catalyst beds [93].



Scheme 1. Hydrogen spillover and H diffusion in a Ni/TiO_{2-rutile} - Ni/TiO_{2-anatase} catalyst
mixture.

1

5 When these H species have reached the TiO_{2-anatase} support, the CO₂ hydrogenation is greatly 6 improved on the Ni/TiO_{2-anatase} catalyst, the methane being formed even from the support alone, 7 and catalyst deactivation is reduced. The part of CH₄ formed directly on the TiO₂ support is however relatively low. Thus, we compare the CO₂ conversion at 260 °C for the 10Ni/TiO_{2-rutile} 8 9 catalyst (200 mg), the 10Ni/TiO_{2-rutile} catalyst (60 mg, corresponding to 30% in weight) mixed with 140 mg of TiO_{2-anatase} (corresponding to 70% in weight), and the Ni/TiO_{2-rutile} catalyst (60 10 mg, corresponding to 30% in weight) mixed with 140 mg of Ni/TiO_{2-anatase} (corresponding to 11 12 70% in weight). The results, presented on Table S13, clearly show that the conversion improvement linked to the Ni on Ni/TiO_{2-anatase} is much higher than the one linked to the TiO₂₋ 13 anatase support itself. The precise role of the H species is still unclear, but it is worth mentioning 14 that TiO₂ reduction by hydrogen spillover has been reported [94-96]. Additionally, it was 15 reported that on Rh catalyst supported on CeO₂ (another reducible support), the fraction of CO 16 that undergoes dissociation increases significantly as the CeO₂ surface is reduced [97]. The fact 17 that the TOF of the catalyst mixture is significantly higher than that of the Ni/TiO_{2-P25} catalyst 18 could be related to the lower specific surface area of the supports used in the mixture compared 19

to TiO_{2-P25}, and to Ni particle proximity, which should be higher for the mixture of catalysts. 1 2 These two characteristics should favor the hydrogen spillover. Finally, considering the fact that Ni particles in Ni/TiO_{2-anatase} and Ni/TiO_{2-rutile} catalysts present similar sizes without TiO_x 3 overlayers, and similar electronic interaction with the supports, we can propose that these 4 catalysts should contain mainly interfacial actives sites [98]. The importance of the metal-5 6 support interface in Ni-catalyzed CO_2 hydrogenation has been discussed [57,77,99,100]. For CO2 methanation, the role of the active sites located at the Ni-support interface has been studied 7 by DFT and operando DRIFT analyses, and different implications related to the reaction 8 mechanism have been proposed. 9

10 On Ni/ZrO₂ catalysts, hydrogen species generated by hydrogen spillover could contribute to the formation of O_v on the ZrO₂ surface, which enhance CO₂ adsorption and activation [99]. It was 11 also proposed that the interaction of the Ni-ZrO₂ interface with adsorbed CO was strong enough 12 to facilitate its further hydrogenation to CH₄ [57]. For the Sabatier reaction on Ni/MgO 13 catalysts, it was shown by DFT that the presence of the MgO support is beneficial for the OH 14 15 removal from intermediate species, and consequently for H₂O formation during CO₂ 16 methanation, due to hydrogen-spillover and the strong OH adsorption on the MgO support [77]. On Ni/CeO₂ catalysts [101], it was recently proposed that, as in the case of Ni/ZrO₂ catalysts 17 18 [99], H-spillover from Ni to CeO_2 can lead to a partial reduction of CeO_2 and generation of O_v at the metal-support interface region. A linear correlation between the CO₂ methanation 19 20 reaction rate and the number of O_v was reported. This suggests the involvement of surface O_v in CO₂ adsorption and activation [102]. A similar phenomenon could occur on TiO₂, another 21 reducible oxide. Such a phenomenon could be at the origin of the difference of reactivity 22 23 between 10Ni/TiO_{2-anatase} and 10Ni/TiO_{2-rutile} catalysts. Indeed, it was shown by DFT that the O_v formation energy is much lower on TiO_{2-rutile} rutile than on TiO_{2-anatase} [103]. Thus, the 24

higher H-spillover on 10Ni/TiO_{2-rutile} than on 10Ni/TiO_{2-anatase} could result in a higher
 concentration of O_v on the 10Ni/TiO_{2-rutile} catalyst, and consequently a higher activity.

Finally, as far as Ni/TiO₂ catalyst stability is concerned, it is worth mentioning that it has been
reported that highly active hydrogen species resulting from spillover that diffuse on Ni catalyst
surface lead to the hydrogenation of the coke precursor species adsorbed on the catalyst
[104,105], and to the reduction of nickel oxide [106]. Such phenomena could explain why the
use of mixture of TiO₂ phases allows limiting catalyst deactivation (Fig. S6b for 10Ni/TiO₂. *P25*).

9

10 4. Conclusion

Nickel catalysts (10% w/w) were prepared on TiO_{2-rutile}, TiO_{2-anatase} and TiO_{2-P25}. The catalysts 11 prepared on TiO_{2-rutile} and TiO_{2-anatase} present a similar Ni particle size (~ 30 nm) before and 12 after CO₂ methanation, as well as similar metal-support interactions. The 10Ni/TiO_{2-P25} presents 13 14 smaller particle size (~ 20 nm). The CO_2 consumption rate measured at the inlet of the reactor of 10Ni/TiO_{2-anatase}, 10Ni/TiO_{2-rutile}, 10Ni/TiO_{2-P25} and a physical mixture of 30% 10Ni/TiO₂₋ 15 $r_{utile} + 70\% 10 \text{Ni}/\text{TiO}_{2-anatase}$ show that a synergistic effect operates when a mixture of the crystal 16 17 phases of TiO₂ is used as a support in the Ni/TiO₂-catalyzed methanation reaction. The synergy observed using a mixture of catalysts could also occur even if the two catalysts are not in 18 physical contact. H₂-TPD analyses and methanation tests performed with diluted catalysts have 19 shown that hydrogen spillover is more pronounced on the Ni/TiO_{2-rutile} catalyst. DRIFTS 20 operando analyses have shown that adsorbed CO is accumulating on Ni/TiO_{2-anatase} but not on 21 Ni/TiO_{2-rutile}. The synergy between the two catalysts can be rationalized as follows: i) the 22 Ni/TiO_{2-rutile} catalyst is active and selective for CO₂ methanation and also for hydrogen 23 activation; ii) the Ni/TiO_{2-anatase} is poorly active for the CO₂ methanation and RWGS, and the 24

TiO_{2-anatase} support is more efficient than TiO_{2-rutile} for diffusion of H species; iii) when the two 1 2 catalysts are used together, the H species diffuse from Ni/TiO2-rutile to Ni/TiO2-anatase; iv) the Henriched Ni/TiO_{2-anatase} catalyst becomes very active for CO₂ methanation. The optimal TiO₂₋ 3 anatase/TiO_{2-rutile} ratio (between 0.4 and 0.8) is achieved through a control of the balance of the 4 spillover, CO₂ methanation and deactivation rates. Finally, the higher TOF obtained with 5 catalyst mixtures compared to Ni/TiO_{2-P25} suggests that interfacial sites, presumably involving 6 7 O_v, should be involved in this reaction. Our results that confirm the essential role of the support for Ni-based CO₂ methanation catalysts [107], can also be put into perspective to propose an 8 explanation of the support effect (rutile vs anatase) observed on Co/TiO2 catalysts for Fischer-9 10 Tropsch synthesis, for which a similar synergistic effect has been observed without being clearly explained [108, 109]. DFT calculations are in course to reveal the mechanism of the 11 hydrogenation at the interfacial active sites and on the bare TiO_{2-anatase} support, and to clarify 12 13 the possible role(s) of the H species resulting from spillover (H-assisted hydrogenation steps, H-assisted water desorption or H-assisted Ni reduction). 14

15 Notes

16 The authors declare no competing financial interest.

17

18 Acknowledgements.

This work was financially supported by "Région Occitanie" through a laboratory and company contract "HYDROMET: Renewable CO₂ hydrogenation for methane production" (N°15065590). B.F.M. acknowledges the exploratory project under the Fundação para a Ciência e a Tecnologia (FCT, Portugal) Investigator Programme (ref. IF/00301/2015) with financial support from FCT/MCTES, through national funds (PIDDAC).

1 References:

2	[1]	D. Y. C. Leung, G. Caramanna, M. M. Maroto-Valer, An overview of current status of
3		carbon dioxide capture and storage technologies, Renew. Sus. Energ. Rev., 39 (2014)
4		426-443.
5	[2]	M. Bui, C. S. Adjiman, A. Bardow, E. J. Anthony, A. Boston, S. Brown, P. S. Fennell,
6		S. Fuss, A. Galindo, L. A. Hackett, et al. Carbon capture and storage (CCS): the way
7		forward, Energy Environ. Sci., 11 (2018) 1062-1176.
8	[3]	J. G. Vitillo, B. Smit, L. Gagliardi, Introduction: Carbon Capture and Separation,
9		Chem. Rev., 117 (2017) 9521-9523.
10	[4]	M. Mikkelsen, M. Jørgensen, F. C. Krebs, The teraton challenge. A review of fixation
11		and transformation of carbon dioxide, Energy Environ. Sci., 3 (2010) 43-81.
12	[5]	T. Sakakura, JC. Choi, H. Yasuda, Transformation of Carbon Dioxide, Chem. Rev.,
13		107 (2007) 2365-2387.
14	[6]	J. Artz, T. E. Müller, K. Thenert, J. Kleinekorte, R. Meys, A. Sternberg, A. Bardow,
15		W. Leitner, Sustainable Conversion of Carbon Dioxide: An Integrated Review of
16		Catalysis and Life Cycle Assessment, Chem. Rev., 118 (2018) 434-504.
17	[7]	G. Centi, S. Perathoner, Opportunities and prospects in the chemical recycling of
18		carbon dioxide to fuels, Catal. Today, 148 (2009) 191-205.
19	[8]	K. Ghaib, K. Nitz, FZ. Ben-Fares, Chemical Methanation of CO ₂ : A Review,
20		ChemBioEng Rev., 3 (2016) 266-275.
21	[9]	P. Frontera, A. Macario, M. Ferraro, P. Antonucci, Supported Catalysts for CO ₂
22		Methanation: A Review, Catalysts, 7 (2017) 59.
23	[10]	W. Wei, G. Jinlong, Methanation of carbon dioxide: an overview, Front. Chem. Sci.
24		Eng., 5 (2011) 2-10.

1	[11]	A. Solis-Garcia, J. C. Fierro-Gonzalez, Mechanistic Insights into the CO ₂ Methanation
2		Catalyzed by Supported Metals: A Review, J. NanosciNanotechnol., 19 (2019)
3		3110-3123.
4	[12]	M. Bailera, P. Lisbona, L. M. Romeo, S. Espatolero, Power to Gas projects review:
5		Lab, pilot and demo plants for storing renewable energy and CO ₂ , Renew. Sus. Energ.
6		Rev., 69 (2017) 292-312.
7	[13]	K. Ghaib, FZ. Ben-Fares, Power-to-Methane: A state-of-the-art review, Renew. Sus.
8		Energ. Rev., 81 (2018) 433-446.
9	[14]	M. Thema, F. Bauer, M. Sterner, Power-to-Gas: Electrolysis and methanation status
10		review, Renew. Sus. Energ. Rev., 112 (2019) 775-787.
11	[15]	X. Guo, A. Traitangwong, M. Hu, C. Zuo, V. Meeyoo, Z. Peng, C. Li, Carbon Dioxide
12		Methanation over Nickel-Based Catalysts Supported on Various Mesoporous Material,
13		Energ. Fuels, 32 (2018) 3681-3689.
14	[16]	J. Martínez, E. Hernández, S. Alfaro, R. López Medina, G. Valverde Aguilar, E.
15		Albiter, M. A. Valenzuela, High Selectivity and Stability of Nickel Catalysts for CO ₂
16		Methanation: Support Effects, Catalysts, 9 (2018) 24.
17	[17]	K. Stangeland, D. Kalai, H. Li, Z. Yu, CO ₂ Methanation: The Effect of Catalysts and
18		Reaction Conditions, Energy Procedia, 105 (2017) 2022-2027.
19	[18]	I. Sreedhar, Y. Varun, S. A. Singh, A. Venugopal, B. M. Reddy, Developmental trends
20		in CO ₂ methanation using various catalysts, Catal. Sci. Technol., 9 (2019) 4478-4504.
21	[19]	J. H. Jensen, J. M. Poulsen, N. U. Andersen, From coal to clean energy,
22		Nitrogen+Syngas, (2011) 310.
23	[20]	J. Liu, C. Li, F. Wang, S. He, H. Chen, Y. Zhao, M. Wei, D. G. Evans, X. Duan,
24		Enhanced low-temperature activity of CO ₂ methanation over highly-dispersed Ni/TiO ₂
25		catalyst, Catal. Sci. Technol., 3 (2013) 2627-2633.

1	[21]	Y. Wang, Y. Xu, Q. Liu, J. Sun, S. Ji, Zj. Wang, Enhanced low-temperature activity
2		for CO ₂ methanation over NiMgAl/SiC composite catalysts, J. Chem. Technol.
3		Biotechnol., 94 (2019) 3780-3786.
4	[22]	S. Tada, T. Shimizu, H. Kameyama, T. Haneda, R. Kikuchi, Ni/CeO2 catalysts with
5		high CO ₂ methanation activity and high CH ₄ selectivity at low temperatures, Int. J.
6		Hydrogen Energ., 37 (2012) 5527-5531.
7	[23]	L. Bian, L. Zhang, R. Xia, Z. Li, Enhanced low-temperature CO ₂ methanation activity
8		on plasma-prepared Ni-based catalyst, J. Nat. Gas Sci. Eng., 27 (2015) 1189-1194.
9	[24]	W. L. Vrijburg, E. Moioli, W. Chen, M. Zhang, B. J. P. Terlingen, B. Zijlstra, I. A. W.
10		Filot, A. Züttel, E. A. Pidko, E. J. M. Hensen, Efficient Base-Metal NiMn/TiO ₂
11		Catalyst for CO ₂ Methanation, ACS Catal., 9 (2019) 7823-7839.
12	[25]	X. Guo, H. He, A. Traitangwong, M. Gong, V. Meeyoo, P. Li, C. Li, Z. Peng, S.
13		Zhang, Ceria Imparts Superior Low Temperature Activity to Nickel Catalysts for CO2
14		Methanation, Catal. Sci. Technol., 9 (2019) 5636-5650.
15	[26]	S. Bagheri, N. Muhd Julkapli, S. Bee Abd Hamid, Titanium Dioxide as a Catalyst
16		Support in Heterogeneous Catalysis, Sci. World J., (2014) 727496.
17	[27]	K. Bourikas, C. Kordulis, A. Lycourghiotis, Titanium Dioxide (Anatase and Rutile):
18		Surface Chemistry, Liquid-Solid Interface Chemistry, and Scientific Synthesis of
19		Supported Catalysts, Chem. Rev., 114 (2014) 9754-9823.
20	[28]	U. Diebold, The Surface Science of Titanium Dioxide, Surf. Sci. Rep., 48 (2003) 53-
21		229.
22	[29]	W. Li, G. Zhang, X. Jiang, Y. Liu, J. Zhu, F. Ding, Z. Liu, X. Guo, C. Song, CO ₂
23		Hydrogenation on Unpromoted and M-Promoted Co/TiO ₂ Catalysts (M = Zr, K, Cs):
24		Effects of Crystal Phase of Supports and Metal – Support Interaction on Tuning
25		Product Distribution, ACS Catal., 9 (2019) 2739-2751.

1	[30]	M. R. Prairie, A. Renken, J. G. Highfield, K. Ravindranathan Thampi, M. Grätzel, A
2		fourier transform infrared spectroscopic study of CO2 methanation on supported
3		ruthenium, J. Catal., 129 (1991) 130-144.
4	[31]	A. Kim, C. Sanchez, G. Patriarche, O. Ersen, S. Moldovan, A. Wisnet, C. Sassoye, D.
5		P. Debecker, Selective CO ₂ methanation on Ru/TiO ₂ catalysts: unravelling the
6		decisive role of the TiO ₂ support crystal structure, Catal. Sci. Technol., 6 (2016) 8117-
7		8128.
8	[32]	A. Kim, D. P. Debecker, F. Devred, V. Dubois, C. Sanchez, C. Sassoye, CO ₂
9		methanation on Ru/TiO ₂ catalysts: On the effect of mixing anatase and rutile TiO_2
10		supports, Appl. Catal. B., 220 (2018) 615-625.
11	[33]	Y. Lin, Y. Zhu, X. Pan, X. Bao, Modulating the methanation activity of Ni by the
12		crystal phase of TiO ₂ , Catal. Sci. Technol., 7 (2017) 2813-2818.
13	[34]	S. Chai, Y. Men, J. Wang, S. Liu, Q. Song, W. An, G. Kolb, Boosting CO ₂
14		Methanation Activity on Ru/TiO2 Catalysts by Exposing (001) Facets of Anatase
15		TiO ₂ , J. CO ₂ Util., 33 (2019) 242-252.
16	[35]	A. Borodzinski, M. Bonarowska, Relation between Crystallite Size and Dispersion on
17		Supported Metal Catalysts, Langmuir, 13 (1997) 5613-5620.
18	[36]	A. Champon, A. Bengaouer, S. Chaise, S. Thomas, AC. Roger, Carbon dioxide
19		methanation kinetic model on a commercial Ni/Al2O3 catalyst, J. CO ₂ Util., 34 (2019)
20		256-265.
21	[37]	K. J. A. Raj, M. G. Prakash, R. Mahalakshmy, T. Elangovan, B. Viswanathan, Liquid
22		Phase Hydrogenation of Nitrobenzene over Nickel Supported on Titania, Chin. J.
23		Catal., 33 (2012) 1299–1305.

1	[38]	M. Xu, S. He, H. Chen, G. Cui, L. Zheng, B. Wang, M. Wei, TiO _{2-x} -modified Ni
2		nanocatalyst with tunable metal-support interaction for water-gas shift reaction, ACS
3		Catal., 7 (2017) 7600-7609.
4	[39]	A. Shukla, R. Kumar Singha, T. Sasaki, S. Adak, S. Bhandari, V. V. D. N. Prasad, A.
5		Bordoloi, R. Bal, Room temperature selective reduction of nitroarenes to azoxy
6		compounds over Ni-TiO ₂ catalyst, Mol. Catal. 490 (2020) 110943.
7	[40]	G. Sankar, K. R. Kannan, C. N. R. Rao, Anatase-Rutile Transformation in Fe/TiO ₂ ,
8		Th/TiO ₂ and Cu/TiO ₂ Catalysts and its Possible Role in Metal-Support Interaction,
9		Catal. Lett., 8 (1991) 27-36.
10	[41]	R. A. Spurr, H. Myers, Quantitative Analysis of Anatase-Rutile Mixtures with an X-
11		Ray Diffractometer, Anal. Chem., 29 (1957) 760-762.
12	[42]	P. Li, J. Liu, N. Nag, P. A. Crozier, Dynamic Nucleation and Growth of Ni
13		Nanoparticles on High-Surface Area Titania, Surf. Sci., 600 (2006) 693-702.
14	[43]	SW. Ho, CY. Chu, SG. Chen, Effect of Thermal Treatment on the Nickel State
15		and CO Hydrogenation Activity of Titania-Supported Nickel Catalysts, J. Catal., 178
16		(1998) 34-48.
17	[44]	F.C. Meunier, On the contamination with nickel and nickel tetracarbonyl during FT-IR
18		investigation of catalysts under CO-containing gases, J. Catal., 372 (2019) 388-388.
19	[45]	M. C. Biesinger, B. P. Payne, L. W. M. Lau, A. Gerson, R. S. C. Smart, X-ray
20		Photoelectron Spectroscopic Chemical State Quantification of Mixed Nickel Metal,
21		Oxide and Hydroxide Systems, Surf. Interface Anal., 41 (2009) 324-332.
22	[46]	M. C. Biesinger, B. P. Payne, A. P. Grosvenor, L. W. M. Lau, A. R. Gerson, R. S. C.
23		Smart, Resolving Surface Chemical States in XPS Analysis of First Row Transition
24		Metals, Oxides and Hydroxides: Cr, Mn, Fe, Co and Ni, Appl. Surf. Sci., 257 (2011)
25		2717-2730.

1	[47]	L. Soriano, I. Preda, A. Gutiérrez, S. Palacín, M. Abbate, A. Vollmer, Surface Effects
2		in the Ni 2p X-Ray Photoemission Spectra of NiO, Phys. Rev. B, 75 (2007) 233417.
3	[48]	B. Zhao, XK. Ke, JH. Bao, CL. Wang, L. Dong, YW. Chen, HL. Chen,
4		Synthesis of Flower-Like NiO and Effects of Morphology on Its Catalytic Properties,
5		J. Phys. Chem. C, 113, (2009) 14440-14447.
6	[49]	V. Vonk, N. Khorshidi, A. Stierle, Structure and Oxidation Behavior of Nickel
7		Nanoparticles Supported by YSZ(111), J. Phys. Chem. C, 121 (2017) 2798-2806.
8	[50]	J. Li, Y. Lin, X. Pan, D. Miao, D. Ding, Y. Cui, J. Dong, X. Bao, Enhanced CO ₂
9		Methanation Activity of Ni/Anatase Catalyst by Tuning Strong Metal – Support
10		Interactions, ACS Catal. 9 (2019) 6342-6348.
11	[51]	V. Nichele, M. Signoretto, F. Menegazzo, I. Rossetti, G. Cruciani, Hydrogen
12		production by ethanol steam reforming: Effect of the Synthesis Parameters on the
13		Activity of Ni/TiO ₂ Catalysts, Int. J. Hydrogen Energ., 39 (2014) 4252-4258.
14	[52]	I. Rossetti, J. Lasso, E. Finocchio, G. Ramis, V. Nichele, M. Signoretto, A. Di
15		Michele, TiO ₂ -Supported Catalysts for the Steam Reforming of Ethanol, Appl. Catal.
16		A, 477 (2014) 42-53.
17	[53]	X. Li, J. Lin, L. Li, Y. Huang, X. Pan, S. E. Collins, Y. Ren, Y. Su, L.i Kang, X. Liu,
18		Y. Zhou, H. Wang, A. Wang, B. Qiao, X. Wang, Tao Zhang, Controlling CO ₂
19		Hydrogenation Selectivity by Metal-Supported Electron Transfer, Angew. Chem. Int.
20		Ed. 59 (2020) 19983-19989.
21	[54]	C. Rivera-Cárcamo, C. Scarfiello, A. B. García, Y. Tison, H. Martinez, W. Baaziz, O.
22		Ersen, C. Le Berre, P. Serp, Stabilization of Metal Single Atoms on Carbon and TiO ₂
23		Supports for CO ₂ Hydrogenation: The Importance of Regulating Charge Transfer,
24		Adv. Mater. Interfaces, (2020) doi.org/10.1002/admi.202001777.

1	[55]	M. J. Jackman, A. G. Thomas, C. Muryn, Photoelectron Spectroscopy Study of
2		Stoichiometric and Reduced Anatase TiO ₂ (101) Surfaces: The Effect of Subsurface
3		Defects on Water Adsorption at Near-Ambient Pressures, J. Phys. Chem. C, 119
4		(2015) 13682-13690.
5	[56]	I. Ro, J. Resasco, P. Christopher, Approaches for Understanding and Controlling
6		Interfacial Effects in Oxide-Supported Metal Catalysts, ACS Catal., 8 (2018) 7368-
7		7387.
8	[57]	B. Yan, B. Zhao, S. Kattel, Q. Wu, S. Yao, D. Su, J. G. Chen, Tuning CO ₂
9		Hydrogenation Selectivity via Metal-Oxide Interfacial Sites, J. Catal. 374 (2019) 60-
10		71.
11	[58]	S. Kattel, P. Liu, J. G. Chen, Tuning Selectivity of CO ₂ Hydrogenation Reactions at the
12		Metal/Oxide Interface, J. Am. Chem. Soc., 139 (2017) 9739-9754.
13	[59]	C. Vogt, E. Groeneveld, G. Kamsma, M. Nachtegaal, L. Lu, C. J. Kiely, P. H. Berben,
14		F. Meirer, B. M. Weckhuysen, Unravelling Structure Sensitivity in CO ₂ Hydrogenation
15		over Nickel, Nat. Catal., 1 (2018) 127-134.
16	[60]	MM. Millet, G. Algara-Siller, S. Wrabetz, A. Mazheika, F. Girgsdies, D. Teschner, F.
17		Seitz, A. Tarasov, S. V. Levchenko, R. Schlögl, E. Frei, Ni Single Atom Catalysts for
18		CO2 Activation, J. Am. Chem. Soc., 141 (2019)) 2451-2461.
19	[61]	C. Mebrahtu, S. Perathoner, G. Giorgianni, S. Chen, G. Centi, F. Krebs, R. Palkovits,
20		S. Abate, Deactivation Mechanism of Hydrotalcite-Derived Ni-AlOx Catalysts during
21		Low-Temperature CO2 Methanation via Ni-Hydroxide Formation and the Role of Fe in
22		Limiting this Effect, Catal. Sci. Technol., 9 (2019) 4023-4035.
23	[62]	A. Kokka, T. Ramantani, A. Petala, P. Panagiotopoulou, Effect of the Nature of the
24		Support, Operating and Pretreatment Conditions on the Catalytic Performance of

1		Supported Ni Catalysts for the Selective Methanation of CO, Catal. Today, (2019)
2		doi:https://doi.org/10.1016/j.cattod.2019.04.015.
3	[63]	A. Karelovic, P. Ruiz, Mechanistic Study of Low Temperature CO ₂ Methanation over
4		Rh/TiO ₂ Catalysts, J. Catal., 301 (2013) 141-153.
5	[64]	X. Wang, Y. Hong, H.Shi, J. Szanyi, Kinetic Modeling and Transient DRIFTS-MS
6		Studies of CO ₂ Methanation over Ru/Al ₂ O ₃ catalysts, J. Catal. 343 (2016) 185-195.
7	[65]	R. A. Hubble, J. Y. Lim, J. S. Dennis, Kinetic Studies of CO ₂ Methanation over a
8		Ni/g-Al ₂ O ₃ Catalyst, Faraday Discuss., 192 (2016) 529-544.
9	[66]	A. Westermann, B. Azambre, M.C. Bacariza, I. Graça, M.F. Ribeiro, J.M. Lopes, C.
10		Henriques, Insight into CO2 Methanation Mechanism over NiUSY Zeolites: An
11		Operando IR Study, Appl. Catal. B, 174-175 (2015) 120-125.
12	[67]	E. Baumgarten, G. Meyer, Hydrogen Spillover Through the Gas Phase. Some Kinetic
13		Aspects. React. Kinet., Catal. Lett., 71 (2000) 325-333.
14	[68]	E.; Baumgarten, R. Krupp, Hydrogenation of Hexene1 by Gas Phase Spillover
15		Hydrogen. Influence of Substances Added in the Reaction Chamber, Without Contact
16		to the Catalyst, React. Kinet. Catal. Lett., 70 (2000) 35-41.
17	[69]	R. Prins, Hydrogen Spillover. Facts and Fiction, Chem. Rev., 112 (2012) 2714-2738.
18	[70]	A. Karelovic, P. Ruiz, Improving the Hydrogenation Function of Pd/γ -Al ₂ O ₃ Catalyst
19		by Rh/γ -Al ₂ O ₃ Addition in CO ₂ Methanation at Low Temperature, ACS Catal., 3
20		(2013) 2799-2812.
21	[71]	C. Swalusa, M. Jacquemin, C. Poleunis, P. Bertrand, P. Ruiz CO ₂ Methanation on
22		Rh/γ -Al ₂ O ₃ Catalyst at Low Temperature: "In Situ" Supply of Hydrogen by
23		Ni/Activated Carbon Catalyst, Appl. Catal. B, 125 (2012) 41-50.
24	[72]	T. Inui, Highly Effective Conversion of Carbon Dioxide to Valuable Compounds on
25		Composite Catalysts, Catal. Today, 29 (1996) 329-337.

1	[73]	S. K. Beaumont, S. Alayoglu, C. Specht, N. Kruse, G. A. Somorjai, Nanoscale
2		Demonstration of Hydrogen Atom Spillover and Surface Diffusion Across Silica
3		Using the Kinetics of CO ₂ Methanation Catalyzed on Spatially Separate Pt and Co
4		Nanoparticles, Nano Lett., 14 (2014) 4792-4796.
5	[74]	S. K. Beaumont, S. Alayoglu, C. Specht, W. D. Michalak, V. V. Pushkarev, J. Guo, N.
6		Kruse, G. A. Somorjai, Combining in Situ NEXAFS Spectroscopy and CO ₂
7		Methanation Kinetics To Study Pt and Co Nanoparticle Catalysts Reveals Key
8		Insights into the Role of Platinum in Promoted Cobalt Catalysis, J. Am. Chem. Soc.,
9		136 (2014) 9898-9901.
10	[75]	Z Yan, Q. Liu, L. Liang, J. Ouyang, Surface hydroxyls mediated CO2 methanation at
11		ambient pressure over attapulgite-loaded Ni-TiO2 composite catalysts with high
12		activity and reuse ability, J. CO ₂ Utilization, 47 (2021) 101489.
13	[76]	Y. Guo, S. Mei, K. Yuan, DJ. Wang, HC. Liu, CH. Yan, YW. Zhang, Low-
14		Temperature CO ₂ Methanation over CeO ₂ -Supported Ru Single Atoms, Nanoclusters,
15		and Nanoparticles Competitively Tuned by Strong Metal-Support Interactions and H-
16		Spillover Effect, ACS Catal., 8 (2018) 6203-6215.
17	[77]	J. Huang, X. Li, X. Wang, X. Fang, H. Wang, X. Xu, New Insights into CO ₂
18		Methanation Mechanisms on Ni/MgO Catalysts by DFT Calculations: Elucidating Ni
19		and MgO Roles and Support Effects, J. CO ₂ Util., 33 (2019) 55-63.
20	[78]	G Hu, Z. Wu, De. Jiang, First Principles Insight into H ₂ Activation and Hydride
21		Species on TiO ₂ Surfaces, J. Phys. Chem. C, 122 (2018) 20323-20328.
22	[79]	R.n Wang, H. Fan, The mechanism of H ₂ and H ₂ O desorption from bridging hydroxyls
23		of a TiO ₂ (110) surface, Catal. Sci. Technol., 7 (2017) 251-264.

1	[80]	W. Lin, H. Cheng, L. He, Y. Yu, F. Zhao, High Performance of Ir-Promoted Ni/TiO ₂
2		Catalyst toward the Selective Hydrogenation of Cinnamaldehyde, J. Catal., 303 (2013)
3		110-116.
4	[81]	P. Panagiotopoulou, D. I. Kondarides, Effects of Alkali Additives on the
5		Physicochemical Characteristics and Chemisorptive Properties of Pt/TiO ₂ Catalysts, J.
6		Catal., 260 (2008) 141-149.
7	[82]	P. Panagiotopoulou, D. I. Kondarides, Effects of Promotion of TiO ₂ with Alkaline
8		Earth Metals on the Chemisorptive Properties and Water-Gas Shift Activity of
9		Supported Platinum Catalysts, App. Catal. B, 101 (2011) 738-746.
10	[83]	Z. He, M. Hu, X. Wang, Highly Effective Hydrodeoxygenation of Guaiacol on
11		Pt/TiO ₂ : Promoter Effects, Catal. Today, 302 (2018) 136-145.
12	[84]	XL. Yin, M. Calatayud, H. Qiu, Y. Wang, A. Birkner, C. Minot, C. Wöll, Diffusion
13		versus Desorption: Complex Behavior of H Atoms on an Oxide Surface,
14		ChemPhysChem, 9 (2008) 253-256.
15	[85]	M. M. Islam, M. Calatayud, G. Pacchioni, Hydrogen Adsorption and Diffusion on the
16		Anatase TiO ₂ (101) Surface: A First-Principles Investigation, J. Phys. Chem. C, 115
17		(2011) 6809.
18	[86]	SC. Li, Z. Zhang, D. Sheppard, B. D. Kay, J. M. White, Y. Du, I. Lyubinetsky, G.
19		Henkelman, Z. Dohnálek, Intrinsic Diffusion of Hydrogen on Rutile TiO ₂ (110), J. Am.
20		Chem. Soc., 130 (2008) 9080-9088.
21	[87]	K. Liu, P. Yan, H. Jiang, Z. Xia, Z. Xu, S. Bai, Z. C. Zhang, Silver Initiated Hydrogen
22		Spillover on Anatase TiO ₂ Creates Active Sites for Selective Hydrodeoxygenation of
23		Guaiacol, J. Catal., 369 (2019) 396-404.

1	[88]	C.g Mao, J. Wang, Y. Zou, G. Qi, J. Yi, Y. Loh, T. Zhang, M. Xia, J. Xu, F. Deng, M.
2		Ghoussoub, N. P. Kherani, L. Wang, H. Shang, M. Li, J. Li, X. Liu, Z. Ai, G. A. Ozin,
3		J. Zhao, L. Zhang, J. Am. Chem. Soc., 142 (2020), 17403-17412.
4	[89]	E. Baumgarten, R. Krupp, Gas Phase Hydrogen Spillover and Oxygen Content, React.
5		Kinet. Catal. Lett., 70 (2000) 27-33.
6	[90]	I. A. Razzhivina, G. A. Badun, M. G. Chernysheva, A. V. Garshev, V. P. Shevchenko,
7		K. V. Shevchenko, I. Y. Nagaev, N. E. Shchepina, Hydrogen Spillover through a Gas
8		Phase, Mendeleev Commun, 26 (2016) 59-60.
9	[91]	E. Baumgarten, L. Maschke, Hydrogen Spillover through the Gas Phase: Reaction
10		with Graphite and Activated Carbon, Appl. Catal. A, 202 (2000) 171-177.
11	[92]	M. S. Spencer, R. Burch, S. E. Golunski, Comments on "Hydrogen Spillover through
12		Gas Phase Transport of Hydrogen Atoms", J. Catal., 126 (1990) 311-313.
13	[93]	S. S. Han, H. Kim, N. Park, Effect of Shuttling Catalyst on the Migration of Hydrogen
14		Adatoms: A Strategy for the Facile Hydrogenation of Graphene, J. Phys. Chem. C,
15		115 (2011) 24696-24701.
16	[94]	Y. Zhu, D. Liu, M. Meng, H ₂ Spillover Enhanced Hydrogenation Capability of TiO ₂
17		Used for Photocatalytic Splitting of Water: a Traditional Phenomenon for New
18		Applications, Chem. Commun., 50 (2014) 6049-6051.
19	[95]	D. Panayotov, E. Ivanova, M. Mihaylov, K. Chakarova, T. Spassov, K. Hadjiivanov,
20		Hydrogen Spillover on Rh/TiO ₂ : the FTIR Study of Donated Electrons, co-Adsorbed
21		CO and H/D Exchange, Phys. Chem. Chem. Phys., 17 (2015) 20563-20573.
22	[96]	W Wan X Nie M I Janik C Song X Guo Adsorption Dissociation and
22	[20]	Spillover of Hydrogen over Au/TiO2 Catalysts: The Effects of Cluster Size and
20		Metal Surger Interaction from DET. J. Divers. Cham. C. 122 (2010) 17005 1701(
24		Nietal–Support Interaction from DF1, J. Phys. Chem. C, 122 (2018) 1/895-1/916.

1	[97]	E. S. Putna, R. J. Gorte, J. M. Vohs, G. W. Grahamy, Evidence for Enhanced
2		Dissociation of CO on Rh/Ceria, J. Catal., 178 (1998) 598-603.
3	[98]	R. Burch, A. R. Flambard, Strong Metal-Support Interactions in Nickel-Titania
4		Catalysts: The Importance of Interfacial Phenomena, J. Catal., 78 (1982) 389-405.
5	[99]	X. Jia, X. Zhang, N. Rui, X. Hu, Cj. Liu, Structural Effect of Ni/ZrO ₂ Catalyst on
6		CO ₂ Methanation with Enhanced Activity, Appl. Catal. B, 244 (2019) 159-169.
7	[100]	S. D. Senanayake, P. J. Ramírez, I. Waluyo, S. Kundu, K. Mudiyanselage, Z. Liu, Z.
8		Liu, S. Axnanda, D. J. Stacchiola, J. Evans, J. A. Rodriguez, Hydrogenation of CO ₂ to
9		Methanol on CeOx/Cu(111) and ZnO/Cu(111) Catalysts: Role of the Metal–Oxide
10		Interface and Importance of Ce ³⁺ Sites, J. Phys. Chem. C, 120 (2016) 1778-1784.
11	[101]	Sh. Lin, Z. Hao, J. Shen, X. Chang, S. Huang, M. Li, X. Ma, Enhancing the CO ₂
12		methanation activity of Ni/CeO2 via activation treatment-determined metal-support
13		interaction, J. Energy Chem. 59 (2021) 334-342.
14	[102]	W. Li, H. Wang, X. Jiang, J. Zhu, Z. Liu, X. Guo, C. Song, A short review of recent
15		advances in CO ₂ hydrogenation to hydrocarbons over heterogeneous catalysts, RSC
16		Adv., 8 (2018) 7651-7669.
17	[103]	Y. Hinuma, T. Toyao, T. Kamachi, Z. Maeno, S. Takakusagi, S. Furukawa, I.
18		Takigawa, Ki. Shimizu, Density functional theory calculations of oxygen vacancy
19		formation and subsequent molecular adsorption on oxide surfaces, J. Phys. Chem. C,
20		122 (2018) 29435-29444.
21	[104]	J. Kapicka, N. I. Jaeger, G. Schulz-Ekloff, Evidence for a hydrogen spillover effect in
22		the deposition of coke on a nickel-faujasite catalyst during syngas conversion, Appl.
23		Catal. A: General, 84 (1992) 47-55.

1	[105]	Cj. Liu, J. Ye, J. Jiang, Y. Pan, Progresses in the preparation of coke resistant Ni-
2		based catalyst for steam and CO ₂ reforming of methane, ChemCatChem, 3 (2011)
3		529-541.
4	[106]	G. E. Batley, A. Ekstrom, D. A. Johnson, Studies of topochemical heterogeneous
5		catalysis: 3. Catalysis of the reduction of metal oxides by hydrogen, J. Catal, 34
6		(1974) 368-375.
7	[107]	L. Shen, J. Xu, M. Zhu, YF. Han, Essential Role of the Support for Nickel-Based
8		CO ₂ Methanation Catalysts, ACS Catal., 10 (2020) 14581–14591.
9	[108]	I. T. Chashechnikova, V. M. Vorotyntsev, A. V. Gette, G. I. Golodets, Effect of
10		Rutile/Anatase Ratio on Catalytic Properties of Co-TiO2 Catalysts for Fischer-
11		Tropsch Synthesis, React. Kinet. Catal. Lett., 40 (1989) 47-51.
12	[109]	K. Shimura, T. Miyazawa, T. Hanaoka, S. Hirata Fischer–Tropsch Synthesis over
13		TiO ₂ Supported Cobalt Catalyst: Effect of TiO ₂ Crystal Phase and Metal Ion Loading,
14		Appl. Catal. A, 460-461 (2013) 8-14.