

# Viscoelastic properties in cancer: from cells to spheroids

Yara Abidine, Arianna Giannetti, Jean Revilloud, Valérie M Laurent, Claude Verdier

# ▶ To cite this version:

Yara Abidine, Arianna Giannetti, Jean Revilloud, Valérie M Laurent, Claude Verdier. Viscoelastic properties in cancer: from cells to spheroids. Cells, 2021, 10. hal-03249960v1

# HAL Id: hal-03249960 https://hal.science/hal-03249960v1

Submitted on 4 Jun 2021 (v1), last revised 5 Jul 2021 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Article

# Viscoelastic properties in cancer: from cells to spheroids

Yara Abidine 1,†,‡, Arianna Giannetti 1,‡, Jean Revilloud , Valérie M. Laurent and Claude Verdier 1,0 \*

- <sup>1</sup> Univ. Grenoble Alpes, CNRS, LIPhy, F-38000 Grenoble, France
- \* Correspondence: claude.verdier@univ-grenoble-alpes.fr; Tel.: +33-4-7663-5980 (C.V.)
- † Current address: Clinical Microbiology department, Virology group, Umeå University, Sweden
- † These authors contributed equally to this work.
- Abstract: AFM-based rheology methods enable the investigation of the viscoelastic properties of
- 2 cancer cells. Such properties are known to be essential for cell functions, especially for malignant
- 3 cells. Here, we investigate the relevance of these methods to characterize the viscoelasticity
- 4 of bladder cancer cells of various invasiveness on soft substrates, and we find that rheology
- 5 parameters are a signature of malignancy. We further investigate the viscoelastic moduli of
- 6 spheroids composed of cancer cells and characterize the effect of the collagen microenvironment.
- 7 Collagen is found to act as a proxy than can modify the global spheroid rheology, leading to an
- 8 increase of moduli vs. frequency, predicted by a double power law model. Together, our results
- shed new light on how cancer cells and tissues adapt their viscoelastic properties depending on
- their malignancy and the microenvironment. This could be an attractive way to control their
- properties in the future, especially since spheroids constitute realistic in vivo tumor models.
- 12 Keywords: cancer cells; spheroids; AFM; viscoelastic; rheology; microenvironment

# 3 1. Introduction

14

20

21

23

33

37

Cell mechanical properties are essential in various processes like cell migration, embryogenesis, wound healing, the immune response, i.e. physiological processes but also in various pathological cases, in particular during cancer metastasis. Understanding how cell deformability can control the way cancer cells migrate or extravasate through blood vessels is essential. While it is well known that the elastic properties play a central role in such processes [1,2], the viscoelastic nature of the cell system is significant and has to be taken into account [3–5]. The many filaments (actin, microtubules and intermediate filaments) of the cell provide a rigid structure to the cell, thus an elastic response, and the surrounding fluid adds viscosity so that the overall properties become viscoelastic, similar to a physical gel, that can remodel constantly. This is indeed what is happening as the cell migrates, and F-actin filaments polymerize at the front to push the membrane forward, while the other actin monomers are recycled [6]. Several other studies have proposed a different behavior for the cell cytoplasm, where the fluid flow can affect the mechanical response and give rise to a poroelastic behavior [7,8]. It is therefore important to obtain experimental data regarding cell behavior under various mechanical solicitations such as constant force, prescribed deformation or rate of deformation. For this reason, new methods have been proposed to determine such properties, either locally using AFM [9,10], magnetocytometry [11], particle tracking measurements [12], or using global measurements thanks to microfluidics [13], micropipettes [14], optical tweezers [15] or optical coherence elastography [16].

While the mechanical properties of cancer at the cell scale has been extensively studied, less is known about the tissue level; therefore we aimed to understand how cellular properties combine and whether similar ones are retained at a higher scale. As could be expected, several features are preserved as classical tissues follow nonlinear elastic behaviors with a substantial role of the deformation rate [17]. Tissues are usually made of cells surrounded by the extra cellular matrix (ECM) inside a fluid and the

Citation: Abidine, Y.; Giannetti, A.; Revilloud, J.; Laurent, V.M.; Verdier, C. Viscoelastic properties in cancer: from cells to spheroids. *Cells* **2021**, *1*, 0. https://doi.org/

Received: june, 2021 Accepted: Published:

**Publisher's Note:** MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Copyright: © 2021 by the authors. Submitted to *Cells* for possible open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

concentrations of the different components depend on tissue type. Cell suspensions have been described [18,19] using mixture models and exhibit a behavior close to that of yield stress fluids, when the cell concentration is around 50% or more. On the other end, with a large collagen content [20] and a small amount of cells (around 10%), the behavior becomes viscoelastic but the effect of cells on the ECM is critical, since cells are able to remodel the collagen network.

To investigate other biological tissues – in particular solid tumours – spheroids have been developed over the years [21] and are considered to be good models. They are made of cells closely packed together, surrounded by ECM in culture medium. Spheroids can grow and make their own ECM, and cell adhesion molecules (cadherins in particular) can form to bind cells within the spheroid afterwards. Generally tumours grow, but this depends on the environment. Indeed, several earlier studies have focused on the role of compressive stresses exerted from the outside onto the tumour [22,23], this effect being to limit growth. Less results are devoted to the understanding of the mechanical behavior of such spheroids, but recent models have focused on the flow of the interstitial liquid within the spheroid [21] and reveal that poroelastic active models can describe the spheroid [24]. These effects have also been observed on other tissues like cartilage or tendons revealing notable high–frequency poroelastic responses [25,26], that can be used to differentiate physiological and pathological tissues. Although these systems are different, possible correlations can be made.

In this work, we choose to use AFM as an interesting device to probe both single cancer cells and spheroids made of the same cells. We developed a microrheology method based on initial indentation followed by oscillations at various frequencies [5,27], to probe the viscoelastic properties of cells and spheroids. The method is presented in § 3 together with modeling tools, and is used further on different cells in different environments (§ 4). Then we adapt it to spheroids and obtain similar data (§ 5), but we note that some differences do exist: viscoelastic properties of both cells and spheroids depend on the microenvironment (substrate or collagen within the spheroid.) Therefore we discuss these results (§ 6) and try to determine the key features that are relevant in both cases (cells or spheroids), and how the differences obtained can be explained, based on complementary confocal microscopy experiments.

#### 2. Materials and methods

#### 2.1. Cancer cells

Three epithelial bladder cancer cell lines with increasing malignancy were used: RT112 (luminal molecular subtype, Leibniz Institute DSMZ, Braunschweig, Germany), T24 and J82 (American Type Culture Collection, Manassas, VA). RT112 is a moderately differentiated cell line that exhibits low invasiveness, while T24 and J82 are both poorly differentiated and very malignant cells, with J82 being the more invasive type. The choice of such bladder cell lines came from earlier studies by the authors [28–31] and the classification method was described previously [27]. These cells were cultured in RPMI 1640 (Gibco, Saint-Aubin, France) supplemented with 10% fetal bovine serum (FBS, Life Technologies SAS, Villebon-sur-Yvette, France) and 1% penicillin-streptomycin (Life 81 Technologies SAS). One day before measurements, cells were seeded at low density on polyacrylamide gels coated with 20 mg/mL fibronectin (PromoCell, Heidelberg, Germany) overnight at 37°C in a humidified 5% CO<sub>2</sub> atmosphere. These cells are considered to adhere firmly on such gels. AFM measurements were carried out on isolated cells at 37°C. These cells were stably transfected with a plasmid expressing LifeAct-GFP to stain F-actin according to previous work [32].

# 2.2. Polyacrylamide gels

Polyacrylamide gels of different rigidities were prepared prior to seeding of the cells using a previous protocol [27]. Briefly, acrylamide, N-hydroxethyl-acrylamide and N,N-methylene-bisacrylamide (Sigma-Aldrich) in different amounts were mixed to

reach controlled rigidities of 5, 8 and 28 kPa, as measured by AFM. Functionalization was achieved using fibronectin (20 mg/mL). Gels were kept under humid conditions before cells were seeded.

# 2.3. Spheroids preparation

100

102

106

107

108

111

114

115

116

118

122

123

125

127

128

129

132

136

138

140

Spheroids can be made of various cells inside an extracellular matrix and are reported to be good candidates for modelling tumors. This is why the same T24 cells as above were selected to prepare them. As before, T24 cells were cultured in RPMI 1640 medium supplemented with 10% FBS and 1% penicillin-streptomycin. 96-well plates were filled with a 1.5% sterile agarose solution (Abnova, Fischer Scientific, Illkirch, France) which solidified quickly at room temperature. Then 10,000 cells were added into the well. Finally, type I rat tail collagen (Corning, Bedford, MA, USA) at 0.01 or 0.03 mg/mL concentration (4°C and pH  $\sim 7.4$ ) was added to the medium. The 96–well plate was centrifugated for 10 min at 200 g. Cells remained at the bottom of the well and were followed in time. After 3 days, spheroids usually presented a spherical compact shape. Experiments were conducted then, with spheroid diameter D ranging between 270 and 400  $\mu$ m. Spheroids were detached with a  $100\mu$ L-pipette (chopped nozzle) and deposited into Petri dishes (TPP, to fit within the AFM setup) in culture medium. Up to three spheroids could be measured at the same time. After sedimentation and proper adhesion to the Petri dish bottom, the AFM cantilever was lowered to come into contact with the top of the spheroid and measurements were carried out as explained below (§ 3.2).

# 2.4. Confocal microscopy of spheroids

Confocal imaging of spheroids containing 0.01 mg/mL collagen was carried out using a confocal Leica TCS SP8 (LIPhy platform). Cells with F–actin GFP labelling were imaged in the green channel (argon laser, 488 nm) and collagen was imaged using the reflectance technique in the red channel (HeNe laser, 633 nm) [20,33]. The spheroids were prepared as described earlier, and let to sediment in a Petri dish (with a 170  $\mu$ m–glass coverslip bound to the bottom). Images were taken (X40 Leica oil–objective) from the bottom to the median part, as it is difficult to penetrate deeper than 200  $\mu$ m. Z–stacks were acquired using steps of 0.35  $\mu$ m. Then images were processed using the Fiji software.

#### 2.5. Statistical analysis

Statistical analysis was measured using a two-sample unpaired Student's t-test. Statistical significance was reached for \* p<0.05 and \*\* p<0.01 while p>0.05 was considered non-significant. Means are presented with the SEM (standard error of the mean).

# 3. Microheology using AFM

## 3.1. Principles of viscoelasticity

The main idea behind viscoelasticity comes from the combined properties of soft systems under applied deformations or forces. When the system is elastic, stresses (i.e. forces per unit surface, in Pa) are proportional to deformations, whereas a viscous material will flow under applied force, with stresses proportional to the rate of deformation. In order to capture both viscous and elastic responses, one can apply a sinusoidal shear deformation  $\delta = \delta_0 \sin(\omega t)$ , where  $\delta_0$  is the amplitude of the deformation, and  $\omega = 2\pi f$  is the angular frequency (f is the frequency in Hz). At small enough deformations  $\delta_0$ , one can assume – and this needs to be checked – that the shear stress response is also periodic in time  $\tau(t) = \tau_0 \sin(\omega t + \phi)$  at the same angular frequency, where  $\tau_0$  is the stress amplitude and where  $\phi$  is a phase shift. Thus one can extract the components of stress in phase  $(\phi = 0)$  and phase opposition  $(\phi = \pi/2)$ , i.e. the moduli G' (elastic) and G'' (viscous or loss) which appear as the coefficients in front of  $\sin(\omega t)$  and  $\cos(\omega t)$  terms. It is found that  $G' = \tau_0 \cos\phi/\delta_0$  and  $G'' = \tau_0 \sin\phi/\delta_0$ . The resulting complex

 $G^* = \frac{\sigma^*}{\delta^*} = G' + iG''$  is called the complex shear modulus and the loss angle  $\phi$  is defined by  $tan\phi = \frac{G''}{G'}$ , as the ratio of viscous to elastic stresses. Given these basic principles, let us now consider a real experiment based on the use of an Atomic Force Microscope (AFM).

#### 3.2. Oscillations using an AFM

146

157

164

160

171

173

174

175

178

180

181

182

184

185

AFM experiments were carried our using a Nanowizard II AFM (JPK Instruments) 147 mounted on a Zeiss microscope (Observer D1). AFM is based on the use of a tip placed 148 on a cantilever that can be set in contact with a surface to investigate the forces due to the interactions between the tip and the substrate. The laser reflected by the cantilever onto a photodiode gives the tip displacement and therefore the force thanks to proper 151 calibration. Calibration was performed here for the sensibility parameter (s  $\sim$  30–80 nm/Volt) then using the thermal fluctuation method [34] to finally obtain the cantilever stiffness (k in N/m). In this study, we used soft cantilevers (MLCT, lever C, Bruker, Billerica, CA) with stiffness on the order  $k \sim 0.01$  N/m for cells, whereas for spheroids 155 stiffer cantilevers (Nanosensors, TL-NCL model) were favored, with  $k \sim 30$  N/m. The basic idea is to perform an initial indentation  $\delta_0$  then to superimpose small sinusoidal deformations  $\delta$  at a given frequency f. For cells, we start from the Sneddon relationship [35] for pyramidal tips, where the applied force  $F_0$  is related to the indentation  $\delta_0$  by:  $F_0 = \frac{3}{4} \frac{E \tan \theta \, \delta_0^2}{1 - \nu^2}$ , where *E* is the elastic Young modulus,  $\nu$  is the Poisson ratio ( $\nu \sim 0.5$ ), and  $\theta$  is the half–pyramid angle. This relationship is then linearized (assuming  $\delta \ll \delta_0$ ), to obtain:

$$G^*(\omega) = G' + i G'' = \frac{1 - \nu}{3 \tan \theta \delta_0} \left\{ \frac{F^*(\omega)}{\delta^*(\omega)} - i \omega b(0) \right\}$$
 (1)

The final calibration regards the hydrodynamic drag created by oscillations of the cantilever in a fluid: the drag is proportional to viscosity and velocity but also depends on geometry. Here the geometry of the cantilever is different each time, so the best way to calibrate it is to oscillate far from the substrate (given distance h) then come closer to it (h  $\sim$  0). The drag force is a pure imaginary number  $F^*/\delta^* = i\omega b(h)$ , where b(h) is to be found. Using the method suggested by Alcaraz et al. [36], we found that b(0)=6.95  $10^{-6}$  N.s/m for the MLCT cantilevers that we used in a typical culture medium.

In the case of spheroids, another method was proposed using large tipless cantilevers [37] indenting the spherical aggregate. The previous formula is then adapted from Hertz:  $F_0 = \frac{4}{3} \frac{E \sqrt{R} \, \delta_0^{3/2}}{1 - \nu^2}$  and one finds, after linearization:

$$G^{*}(\omega) = G' + i G'' = \frac{1 - \nu}{4 (R\delta_{0})^{1/2}} \left\{ \frac{F^{*}(\omega)}{\delta^{*}(\omega)} - i \omega b(0) \right\}$$
 (2)

where *R* is the spheroid radius, and the other parameters remain unchanged. In that case the hydrodynamic drag calibration gave  $b(0)=3.45 \ 10^{-5} \ N.s/m$ .

Therefore, using this method, it is possible to obtain the viscoelastic data (G',G") over a large range of frequency ranging from 1 Hz to 1 kHz.

#### 3.3. Substrate effects

Investigating cells in a complex environment demands to evaluate the mechanical properties of the surrounding media or tissues. Typically values of soft tissues (excluding bones) range from 50 Pa to 20 kPa. Therefore, our studies focused on such media. When using AFM on cells plated on a soft/rigid substrate, it is important to account for its rigidity. Indeed, the cell apparent modulus is overestimated on a rigid substrate but can be estimated for different cantilever geometries [38,39]. On the other hand, less is known on soft substrates where the apparent modulus can be underestimated as shown recently [27,40,41]. This is precisely what has been done prior to this study. The details of the calculations can be found in our previous work [27]. Corrections make use of an

equivalent medium made of the glass substrate covered by a thick gel on top of which cells are deposited. This medium is described by a simple apparent modulus [42], and equation (1) is modified as shown previously [27] to obtain the corrected moduli (G', G'').

#### 3.4. Rheological model

190

191

193

195

197

202

214

216

218

222

Different authors have tried to model viscoelastic data. Previous studies report that polymers or complex materials [43,44] exhibiting wide relaxation spectra have power law dependence, i.e. moduli G' and G'' vary with a certain power of the frequency (f). For example, it was reported that cells have moduli (G',G'') varying with the same small exponents  $\sim 0.1-0.3$ , and behave as Newtonian fluids at higher frequencies [10]. Nevertheless a single exponent is usually not enough to cover the whole frequency range, therefore it is better to define different frequency domains with different exponents [5,27,45]. This is what is done here. Assuming that both moduli exhibit two different behaviors according to the frequency range, as shown in Figure 1, a double power–law behavior can be assumed, of the following form:

$$G' = G_0 \left( \frac{f}{f_0} \right)^a + G_1 \left( \frac{f}{f_0} \right)^b, \quad G'' = G_2 \left( \frac{f}{f_0} \right)^c + G_3 \left( \frac{f}{f_0} \right)^d$$
 (3)


Note that we used  $f_0 = 1$  Hz and f is expressed in Hz. By making this dimensionless reduction, we can get rid of complex units. Indeed  $G_0$ ,  $G_1$ ,  $G_2$ ,  $G_3$  are simply expressed in Pascals (Pa), whereas exponents a, b, c, d are dimensionless. We note further that:

- A plateau for G' is sometimes obtained at low frequencies (see Figure 3A below) so that a = 0, and  $G_0$  is the so–called elastic plateau modulus [5].
- A single power law for G' can be enough to describe the data (see Figure 3B for instance), then  $G_1 = 0$ .
- Note that for low frequencies, when the second term is negligible,  $G' \sim G_0 \left(\frac{f}{f_0}\right)^a$  and  $G'' \sim G_2 \left(\frac{f}{f_0}\right)^c$  so that  $G_0 \sim G'(1Hz)$  and similarly  $G_2 \sim G''(1Hz)$
- We also recover most of the cases studied before, in particular Alcaraz *et al.*[10] found  $G_1 = 0$ , a = c and d = 1 for single cells.

# 4. Results on live cancer cells

#### 4.1. Cell viscoelastic properties

The viscoelastic properties of the three different cell lines with increasing invasiveness (RT112 < T24 < J82) were measured using AFM as described in § 3.2. The measurements were located above the cell nucleus with a maximum indentation of the AFM tip of 500 nm. Cells were adherent on gel substrates of different rigidities and the contribution of the substrate to the viscoelastic properties was corrected as described in § 3.3 ensuring that only the microrheology of the cells is characterized. This correction is essential as it allows the comparison between different cell lines. Figure 1 shows the elastic modulus G' (black) and the loss modulus G'' (red) of cells that were adherent on a soft gel of 8 kPa (which is similar to the stiffness of the endothelial monolayer [27]). First, one can observe that the viscoelastic properties follow a common behavior with G' and G'' increasing with frequency with the ratio of G''/G' when the invasiveness increases, suggesting an effect of the invasiveness on the microrheology of cancer cells. Moreover, the elastic modulus of the less invasive cells RT112 reveals a plateau modulus at the lower frequencies (Figure 1A), which is not present for T24 and J82 (Figure 1B-C), indicating that invasiveness has the effect of making cells less elastic.



**Figure 1.** Viscoelastic moduli of RT112, T24 and J82 cells on a **8kPa substrate**. The elastic modulus G' (black) and the loss modulus G'' (red) are shown as a function of frequency f. These measurements were done above the cell nucleus. The lines correspond to the model in Eq. (3), using (A)  $G_0$ =1567 Pa, a=0.05,  $G_1$ =0.005 Pa, b=2.4,  $G_2$ =321 Pa, c=0.07,  $G_3$ =29.4 Pa, d=1.05, (B)  $G_0$ =1060 Pa, a=0.20,  $G_1$ =0.24 Pa, b=1.7,  $G_2$ =351 Pa, c=0.08,  $G_3$ =84 Pa, d=0.8 and (C)  $G_0$ =682 Pa, a=0.14,  $G_1$ =0.04 Pa, b=2,  $G_2$ =205 Pa, c=0.01,  $G_3$ =40 Pa, d=0.92. N = 5, error bars represent the mean  $\pm$  SEM (standard error of the mean).

Quantitative parameters of cancer cell microrheology were then found using the model in Equation (3) and summarized in Figure 2 and Figure S1 (supplementary material). First, the elastic modulus  $G_0$  decreases significantly between RT112 and J82 (Figure 2A) while the slope a of G' increases (Figure 2B). At high frequency,  $G_1$  of RT112 increases significantly as compared to T24 and J82 (Figure S1A) while the slope b of G' decreases (Figure 2C). These results indicate that the less invasive cells are more elastic. In addition, the loss modulus G'' exhibits a similar dependency on the cancer cell invasiveness. Indeed, the slope c (Figure 2D, 8kPa) of the more invasive cells J82 is lower than RT112 and T24 and close to zero, revealing that the loss modulus follows a single power law.


These results demonstrate that the cell microrheology parameters can provide the signature of malignancy, with more invasive cell lines being less elastic and more deformable, which gives them the advantage to rapidly change their shape and migrate through endothelial barriers.

## 4.2. Comparison on various substrates

While the use of 8 kPa soft gels is biologically relevant in the context of metastasis, when cancer cells are in contact with the endothelium monolayer (having a similar rigidity [27]), it is also important to investigate the effect of the substrate rigidity on the viscoleastic properties. This is relevant to understand how cancer cells modify their micro–structure depending on the substrate. Here, we use polyacrylamide gels with calibrated stiffnesses of 5–8–28 kPa. The viscoelastic moduli were measured above the cell nucleus and corrected for the effect of the substrate, as mentioned above, and the microrheological parameters were determined using Equation (3) and are summarized in Figure 2.

These results reveal that invasive cells are sensitive to the substrate rigidity. Indeed, the rheology parameters of T24 and J82 exhibit significant changes with gel rigidity increase. In particular,  $G_0$  increases while a and b (exponents at low and high frequencies respectively) decrease when the substrate becomes more rigid (Figure 2A-B-C). This suggests that the cells become more rigid when the substrate is stiffer. Interestingly, the less invasive cell line RT112 does not show a similar behavior, indicating that the more invasive cells are more sensitive to the substrate rigidity. However, the effect of the substrate is less pronounced on the loss modulus. Indeed, the model reveals that the exponent c of G'' (low frequencies) increases significantly for RT112 and J82 with the gel rigidity (Figure 2D).

Taken together, these results reveal that the mechanosensitivity of cancer cells to the substrate depends on their invasiveness.



**Figure 2.** Parameters  $G_0$  (A), exponent a (B), exponent b (C), exponent c (D) for RT112, T24 and J82 cancer cells on different gels (E=5–8–28 kPa). The parameters were extracted from fitting averaged G' and G'' for each condition with Eq. (3). Three different adjustments were performed and the means of the fitted parameters were obtained. Errors bars represent the mean  $\pm$  SEM (standard error of the mean). Asterisks represent a significant difference using student t-test: ns=not significant, \*p<0.05 and \*\*p<0.01. For each cell line, the statistical asterisk is versus the condition 5kPa. A bar is added under the asterisk when a statistical difference is found between RT112–T24 and T24–J82 on 8 kPa gels.

In summary, we have shown here that the microrheology of cancer cells is dependent on both (i) the invasiveness of the cells and (ii) the substrate rigidity. These findings shed light on the adaptative power of the more invasive cell lines that can deform and pass through barriers but can also change their mechanical properties depending on the type of substrate.

## 5. Results on spheroids

267

269

272

273


274

275

276

#### 5.1. Spheroid viscoelastic properties

Experimental data on such spheroids are interesting and already reveal features associated with cell mechanical properties as well as spheroid content. Figure 3 shows two sets of measurements conducted on T24 spheroids: without collagen (diameter of 320  $\mu$ m) in Figure 3A and with collagen at 0.03 mg/mL concentration (diameter of 410  $\mu$ m) in Figure 3B.




**Figure 3.** (A) Viscoelastic properties (G', G'') of T24 spheroid with **no collagen**. D  $\sim$  320  $\mu$ m. Initial number of cells=10,000. The lines correspond to the model in Eq.(3), using  $G_0$ =2100 Pa, a=0,  $G_1$ =4.8 Pa, b=1.02,  $G_2$ =530 Pa, c=-0.15,  $G_3$ =4.4 Pa, d=1.2. (B) Viscoelastic properties (G', G'') of T24 spheroid containing collagen at **0.03 mg/mL**. D  $\sim$  410  $\mu$ m. Initial number of cells=10,000. The same model gives  $G_0$ =358 Pa, a=0.30,  $G_1$ =0 Pa, b=0,  $G_2$ =161 Pa, c=0.35,  $G_3$ =0.026 Pa, d=1.92.

There is indeed a difference with respect to the low frequency behavior with a plateau modulus for G' and G'' in the case without collagen (Figure 3A) whereas interestingly, when collagen is added (Figure 3B), moduli G' and G'' exhibit power law behavior with no plateau at low frequencies. Modelling of this behavior has been carried out using Equation (3).

### 5.2. Role of collagen

The role of collagen has been further characterized using spheroids cultured at three different concentrations of collagen: 0 - 0.01 mg/mL and 0.03 mg/mL. The spheroids all have a similar number of initial cells (10,000 cells) and have diameters ranging between 300  $\mu$ m and 410  $\mu$ m. The viscoelastic properties (G', G'') were acquired as described previously and fitted using the model in Eq.(3). The fitting parameters are summarized in Figure 4 and Table 1. First, one can observe that the exponent a of G' (at low frequency) increases with the collagen concentration (Figure 4B). In particular, a is null when there is no collagen. Collagen also has an effect on G' at the high frequencies, where both  $G_1$  and b decrease for the highest concentration of collagen (Figure 4A-B), suggesting that the spheroid modifies its elastic properties when collagen is added in the microenvironment. Finally, we also show the effect of collagen on the loss modulus G'', where both exponents c and d (low and high frequencies) increase when collagen is present (Figure 4B).


In summary, these results demonstrate that the collagen changes the viscoelastic properties of the spheroid, in particular the low frequency plateau modulus disappears and gives rise to a small frequency–dependence, typical of a soft glassy rheological system [44].



**Figure 4.** Role of collagen (concentration: 0-0.01-0.03 mg/mL) on parameters  $G_0$ ,  $G_1$  (A) and exponents a, b, c, d (B). The values of all parameters are reported in Table 1. For each collagen concentration, all spheroids with a size ranging from  $300~\mu m$  to  $410~\mu m$  were considered. The parameters were then extracted by fitting the averaged G' and G'' with the model in Eq. (3). For each condition, three fits were performed to obtain means of the parameters. The error bars represent the standard error of the mean (SEM).

**Table 1.** Values of the fitting parameters of  $G_0$ , a,  $G_1$ , b,  $G_2$ , c,  $G_3$ , d for different collagen concentrations (0, 0.01 and 0.03 mg/mL).

| parameters                 | c=0    | c=0.01 mg/mL | c=0.03 mg/mL |
|----------------------------|--------|--------------|--------------|
| <i>G</i> <sub>0</sub> (Pa) | 1492   | 423          | 1946         |
| а                          | 0      | 0.2          | 0.3          |
| <i>G</i> <sub>1</sub> (Pa) | 14     | 0.004        | 0            |
| b                          | 1      | 1.3          | 0            |
| $G_2$ (Pa)                 | 364    | 197          | 1152         |
| С                          | 0.0005 | 0.22         | 0.17         |
| <i>G</i> <sub>3</sub> (Pa) | 3.6    | 0.6          | 2.8          |
| d                          | 1.34   | 1.69         | 1.75         |



**Figure 5.** Confocal image of T24 spheroid with 0.01mg/mL collagen concentration (GFP cells in green, collagen in red). D  $\sim$  350  $\mu$ m.

304

308

309

311

313

315

316

317

320

322

324

326

328

330

332

333

337

341

345

349

350

351

353

Finally, we further verified the effect of collagen on the spheroids by confocal microscopy, where it is possible to visualize both labeled cells (using transfection with LifeAct GFP) and the collagen (reflectance technique [20] at 650 nm). This is shown in Figure 5, where cells are visible and collagen appears in between cells. Therefore, the microstructure of the spheroid relies on the ability of cells to bind to the extracellular matrix and construct a particular network. In the first case, there is no collagen to be seen (data not shown) but when using collagen, this provides a network to build on, and this affects dramatically the mechanical properties as seen above in Figure 3.

## 6. Discussion and conclusion

The importance of mechanical properties of cells and tissues in relation with different physiological or pathological conditions is of utmost importance [46]. Here we propose to determine cell and spheroids properties using dynamic rheology thanks to AFM. The technique has already been applied successfully for cells [5,10,27]. However, less is known about the rheology of tissues, in particular only a few biological systems were tested for viscoelasticity so far [26,47–49], and there was no data available for spheroids, as proposed in this new study. AFM was found to be a powerful tool for measuring elastic and loss moduli (G', G'') and revealed important new features. To analyze the data, a new model was used in Eq.(3), based on the fact that the usual power law behaviors fail to describe single cell or spheroid properties [27,45,50]. Indeed it is common to use a single power law exponent describing the elastic modulus G' in the low frequency regime [10,51]. But the loss modulus G'' has a different behavior at low and high frequencies with respective small and high slopes. This can also be the case for the storage modulus G'.

The investigation of the microrheology of single cancer cells revealed that dynamic mechanical properties are clearly dependent on *cell type* (i.e. invasiveness) and *substrate stiffness* (Figures 1–2). New fitting parameters using the new model suggest that possible differences between invasive or non–invasive cells can be clearly identified through the new parameters  $G_0$  and a, to name just these two (see Figure 2). With respect to different substrates, cancer cells also revealed their ability to behave differently, in relation with their cytoskeleton [27,52]. The above parameters  $G_0$  and a, as well as c and d, were also used successfully to exhibit this microrheology evolution when the substrate stiffness increased from 5 to 28 kPa (see Figure 2). Finally, invasive cancer cells were found to be more mechanosensitive with respect to an increase of substrate stiffness.

When treating the case of spheroids, which are known to be good tumor models [21,24,37,53], interesting data was found, regarding the role of collagen or the ECM [54]. Indeed it is known that collagen can be synthesized by cells or can be recruited from the extracellular matrix. Using small amounts of collagen (here ranging from 0 to 0.03 mg/mL), it was found that cells re–arrange efficiently in order to form a more compact structure (see Figure 5) using collagen as a proxy [24,55]. This resulted in various behaviors due to the viscoelastic nature of collagen [20,56]. Indeed, collagen has enhanced viscous properties at low frequency and exhibits very small moduli (typically a few tens or hundreds of Pa). This effect modified quite significantly the low-frequency behavior of the spheroids as shown by comparing Figure 3A and Figure 3B. Initial slopes  $\sim 0.3-0.35$  were found for G' and G'' in Figure 3B, and this was quite different from the case without collagen (Figure 3A). In the presence of collagen, the spheroid behavior becomes that of a glassy system, probably because cells rearrange constantly in a disordered way to try to find a stable configuration, that could occur if adhesion proteins are expressed and enhance elastic effects at longer times (as compared to the ones used in this study). Finally, the analysis of rheological parameters (Figure 4) showed that  $G_0$  and a are quite relevant, as with single cells, but we further noticed that  $G_1$ , b, cand d can also predict such changes. Altogether these parameters may be quite essential for investigating the microstructural evolution of spheroids in time, when considering the main interactive components such as cells, ECM, fluid and adhesion proteins [20].

365

The final question relies on the ability to describe a macroscopic system (i.e. tissue level) with a constitutive equation taking into account all the components. Obviously the signature of single cells with (G', G'') varying like power law models is persistent at the macroscopic level (spheroid), and this could be a starting point for future modeling. This is an interesting question raised by homogeneisation of poroelastic media containing inclusions/cells embedded in a matrix [57]. Such studies could be very useful since both microscopic and macroscopic properties have been measured in this study. Additionally the active behavior of cells [24] could be considered. But this requires further investigations.

Therefore these results confirm the interest of AFM rheology to investigate cells and tissues; it provides mechanical parameters (or cues) to test biological samples in the time or frequency domains, possibly leading to therapeutical investigations.

Author Contributions: "Conceptualization, C.V.; methodology, Y.A., A.G., J.R., V.M.L., C.V.; experiments, Y.A., A.G., J.R.; data analysis, Y.A., A.G.; writing—review and editing, Y.A., A.G., C.V. All authors have read and agreed to the published version of the manuscript."

Funding: "This research used the LIPhy AFM Platform, funded by the Nanoscience fiundation, Grenoble, France. Authors are members of the LabEx Tec21 (Investissements d'Avenir: grant agreement No. ANR-11-LABX-0030)."

Data Availability Statement: Data is available from the authors upon request.

Acknowledgments: The authors are thankful to A. Duperray for fruitful discussions, and for providing cancer cell lines. They also thank A. Popov for her help with the spheroids preparation.

Conflicts of Interest: "The authors declare no conflict of interest."

#### References

- 1. Lekka, M.; Laidler, P.; Gil, D.; Lekki, J.; Stachura, Z.; Hrynkiewicz, A.Z. Elasticity of normal and cancerous human bladder cells studied by scanning force microscopy. *Eur. Biophys. J.* **1999**, *28*, 312–316.
- Cross, S.E.; Jin, Y.S.; Rao, J.; Gimzewski, J.K. Nanomechanical analysis of cells from cancer patients. *Nat. Nanotechnol.* 2007, 2, 780–783.
- 3. Verdier, C.; Étienne, J.; Duperray, A.; Preziosi, L. Review: Rheological properties of biological materials. *C. R. Acad. Sci. Phys.* **2009**, *10*, 790–811.
- 4. Rother, J.; Nöding, H.; Mey, I.; Janshoff, A. Atomic force microscopy-based microrheology reveals significant differences in the viscoelastic response between malign and benign cell lines. *Open Biology* **2014**, *4*, 140046.
- 5. Abidine, Y.; Laurent, V.M.; Michel, R.; Duperray, A.; Verdier, C. Local mechanical properties of bladder cancer cells measured by AFM as a signature of metastatic potential. *Eur. Phys. J. Plus* **2015**, *130*, 202.
- 6. Pollard, T.D.; Borisy, G.G. Cellular motility driven by assembly and disassembly of actin filaments. Cell 2003, 112, 453–465.
- 7. Biot, M.A. General theory of three-dimensional consolidation. J. Appl. Phys. 1941, 12, 155–164.
- 8. Moeendarbary, E.; Valon, L.; Fritzsche, M.; Harris, A.R.; Moulding, D.A.; Thrasher, A.J.; Stride, E.; Mahadevan, L.; Charras, G.T. The cytoplasm of living cells behaves as a poroelastic material. *Nat. Mater.* **2013**, *12*, 253–261.
- 9. Abidine, Y.; Laurent, V.M.; Michel, R.; Duperray, A.; Palade, L.; Verdier, C. Physical properties of polyacrylamide gels probed by AFM and rheology. *Europhys. Letters* **2015**, *109*, 38003.
- 10. Alcaraz, J.; Buscemi, L.; Grabulosa, M.; Trepat, X.; Fabry, B.; Farré, R.; Navajas, D. Microrheology of human lung epithelial cells measured by atomic force microscopy. *Biophys. J.* **2003**, *84*, 2071–2079.
- 11. Laurent, V.M.; Planus, E.; Fodil, R.; Isabey, D. Mechanical assessment by magnetocytometry of the cytosolic and cortical cytoskeletal compartments in adherent epithelial cells. *Biorheology* **2003**, *40*, 235–240.
- 12. Yamada, S.; Wirtz, D.; Kuo, S.C. Mechanics of living cells measured by laser tracking microrheology. Biophys. J. 2000, 78, 1736–1747.
- 13. Guillou, L.; Dahl, J.B.; Lin, J.M.G.; Barakat, A.I.; Husson, J.; Muller, S.J.; Kumar, S. Measuring Cell Viscoelastic Properties Using a Microfluidic Extensional Flow Device. *Biophys. J.* **2016**, *111*, 2039–2050.
- 14. Evans, E.; Yeung, A. Apparent viscosity and cortical tension of blood granulocytes determined by micropipet aspiration. *Biophys. J.* **1989**, *56*, 151–160.
- 15. Hénon, S.; Lenormand, G.; Richert, A.; Gallet, F. A new determination of the shear modulus of the human erythrocyte membrane using optical tweezers. *Biophys. J.* **1999**, *76*, 1145–1151.
- 16. Leartprapun, N.; Iyer, R.R.; Untracht, G.R.; Mulligan, J.A.; Adie, S.G. Photonic force optical coherence elastography for three-dimensional mechanical microscopy. *Nat. Comm.* **2018**, 9.
- 17. Fung, Y.C. Biomechanics. Mechanical properties of living tissues; Springer-Verlag: New York, 1993.


- 18. Iordan, A.; Duperray, A.; Verdier, C. Fractal approach to the rheology of concentrated cell suspensions. *Phys. Rev. E* **2008**, 77, 011911.
- 19. Preziosi, L.; Ambrosi, D.; Verdier, C. An Elasto-visco-plastic Model of Cell Aggregates. J. Theor. Biol. 2010, 262, 35–47.
- 20. Iordan, A.; Duperray, A.; Gérard, A.; Grichine, A.; Verdier, C. Breakdown of cell-collagen networks through collagen remodeling. *Biorheology* **2010**, *47*, 277–295.
- 21. Delarue, M.; Montel, F.; Caen, O.; Elgeti, J.; Siaugue, J.M.; Vignjevic, D.; Prost, J.; Joanny, J.F.; Cappello, G. Mechanical Control of Cell flow in Multicellular Spheroids. *Phys. Rev. Letters* **2013**, *110*.
- 22. Helmlinger, G.; Netti, P.A.; Lichtenbeld, H.C.; Melder, R.J.; Jain, R.K. Solid stress inhibits the growth of multicellular tumor spheroids. *Nat. Biotechnol.* **1997**, *15*, 778–783.
- 23. Delarue, M.; Montel, F.; Vignjevic, D.; Prost, J.; Joanny, J.F.; Cappello, G. Compressive stress inhibits proliferation in tumor spheroids through a volume limitation. *Biophys. J.* **2014**, *107*, 1821–1828.
- 24. Dolega, M.; Zurlo, G.; Goff, M.L.; Greda, M.; Verdier, C.; Joanny, J.F.; Cappello, G.; Recho, P. Mechanical behavior of multi-cellular spheroids under osmotic compression. *J. Mech. Phys. Solids* **2021**, *147*, 104205.
- 25. Nia, H.; Bozchalooi, I.; Li, Y.; Han, L.; Hung, H.H.; Frank, E.; Youcef-Toumi, K.; Ortiz, C.; Grodzinsky, A. High-Bandwidth AFM-Based Rheology Reveals that Cartilage is Most Sensitive to High Loading Rates at Early Stages of Impairment. *Biophys. J.* **2013**, *104*, 1529–1537.
- 26. Connizzo, B.K.; Grodzinsky, A.J. Tendon exhibits complex poroelastic behavior at the nanoscale as revealed by high-frequency AFM-based rheology. *J. Biomech.* **2017**, *54*, 11–18.
- 27. Abidine, Y.; Constantinescu, A.; Laurent, V.M.; Rajan, V.S.; Michel, R.; Laplaud, V.; Duperray, A.; C. Verdier. Mechanosensitivity of cancer cells in contact with soft substrates using AFM. *Biophys. J.* **2018**, *114*, 1165–1175.
- 28. Chotard-Ghodsnia, R.; Haddad, O.; Leyrat, A.; Drochon, A.; Verdier, C.; Duperray, A. Morphological analysis of tumor cell/endothelial cell interactions under shear flow. *J. Biomech.* **2007**, *40*, 335–344.
- 29. Haddad, O.; Chotard-Ghodsnia, R.; Verdier, C.; Duperray, A. Tumor cell/endothelial cell tight contact upregulates endothelial adhesion molecule expression mediated by NFkB: differential role of the shear stress. *Exp. Cell Res.* **2010**, *316*, 615–626.
- 30. Laurent, V.M.; Duperray, A.; Sundar, V.R.; Verdier, C. Atomic Force Microscopy Reveals a Role for Endothelial Cell ICAM-1 Expression in Bladder Cancer Cell Adherence. *PLOS One* **2014**, *9*, e98034.
- 31. Rajan, V.S.; Laurent, V.M.; Verdier, C.; Duperray, A. Unraveling the Receptor-Ligand Interactions between Bladder Cancer Cells and the Endothelium Using AFM. *Biophys. J.* **2017**, *112*, 1246–1257.
- 32. Riedl, J.; Crevenna, A.H.; Kessenbrock, K.; Yu, J.H.; Neukirchen, D.; Bista, M.; Bradke, F.; Jenne, D.; Holak, T.A.; Werb, Z.; Sixt, M.; Wedlich-Soldner, R. Lifeact: a versatile marker to visualize F-actin. *Nat. Methods* **2008**, *5*, 605–607.
- 33. Friedl, P.; Borgmann, S.; Bröcker, E.B. Amoeboid leukocyte crawling through extracellular matrix: lessons from the Dictyostelium paradigm of cell movement. *J. Leukoc. Biol.* **2001**, *70*, 491–509.
- 34. Butt, H.J.; Jaschke, M. Calculation of thermal noise in atomic force microscopy. Nanotechnology 1995, 6, 1–7.
- 35. Sneddon, I.N. The relation between load and penetration in the axisymmetric Boussinesq problem for a punch of arbitrary profile. *Int. J. Engng* **1965**, *3*, 47–57.
- 36. Alcaraz, J.; Buscemi, L.; de Morales, M.P.; Colchero, J.; Baro, A.; Navajas, D. Correction of Microrheological Measurements of Soft Samples with Atomic Force Microscopy for the Hydrodynamic Drag on the Cantilever. *Langmuir* **2002**, *18*, 716–721.
- 37. Giannetti, A.; Revilloud, J.; Verdier, C. Mechanical properties of 3D tumor spheroids measured by AFM. *Comput. Meth. Biomech. Biomed. Eng.* **2020**, 23, S125–127.
- 38. Dimitriadis, E.K.; Horkay, F.; Maresca, J.; Kachar, B.; Chadwick, R.S. Determination of elastic moduli of thin layers of soft material using the atomic force microscope. *Biophys. J.* **2002**, *82*, 2798–2810.
- 39. Santos, J.A.C.; Rebêlo, L.M.; Araujo, A.C.; Barrosa, E.B.; de Sousa, J.S. Thickness-corrected model for nanoindentation of thin films with conical indenters. *Soft Matter* **2012**, *8*, 4441–4448.
- 40. Vichare, S.; Sen, S.; Inamdar, M.M. Cellular mechanoadaptation to substrate mechanical properties: contributions of substrate stiffness and thickness to cell stiffness measurements using AFM. *Soft Matter* **2014**, *10*, 1174–1181.
- 41. Rheinlaender, J.; Dimitracopoulos, A.; Wallmeyer, B.; Kronenberg, N.M.; Chalut, K.J.; Gather, M.C.; Betz, T.; Charras, G.; Franze, K. Cortical cell stiffness is independent of substrate mechanics. *Nat. Mater.* **2020**, pp. 1–7.
- 42. Korsunsky, A.M.; Constantinescu, A. Work of indentation approach to the analysis of hardness and modulus of thin coatings. *Mat. Sci. Eng.: Part A* **2006**, 423, 28–35.
- 43. Palade, L.I.; Vernay, V.; Attané, P. A modified fractional model to describe the entire viscoelastic behavior of polybutadienes from flow to glassy regime. *Rheol. Acta* **1996**, *35*, 265–273.
- 44. Sollich, P.; Lequeux, F.; Hébraud, P.; Cates, M.E. Rheology of Soft Glassy Materials. Phys. Rev. Letters 1997, 78, 2020–2023.
- 45. Stamenovic, D.; Rosenblatt, N.; Montoya-Zavala, M.; Matthews, B.D.; Hu, S.; Suki, B.; Wang, N.; Ingber, D.E. Rheological behavior of living cells is timescale-dependent. *Biophys. J.* **2007**, *93*, L39–L41.
- 46. Denis Wirtz, K.K.; Searson, P.C. The physics of cancer: the role of physical interactions and mechanical forces in metastasis. *Nat. Rev. Cancer* **2011**, *11*, 512–522.
- 47. Nia, H.; Han, L.; Li, Y.; Ortiz, C.; Grodzinsky, A. Poroelasticity of Cartilage at the Nanoscale. Biophys. J. 2011, 101, 2304–2313.
- 48. Chiron, S.; Tomczak, C.; Duperray, A.; Laine, J.; Bonne, G.; Eder, A.; Hansen, A.; Eschenhagen, T.; Verdier, C.; Coirault, C. Complex Interactions between Human Myoblasts and the Surrounding 3D Fibrin-Based Matrix. *PLOS One* **2012**, *7*, e36173.

- 49. Connizzo, B.K.; Naveh, G.R.S. In situ AFM-based nanoscale rheology reveals regional non-uniformity in viscoporoelastic mechanical behavior of the murine periodontal ligament. *J. Biomech.* **2020**, *111*, 109996.
- 50. de Sousa, J.S.; Freire, R.S.; Sousa, F.D.; Radmacher, M.; Silva, A.F.B.; Ramos, M.V.; Monteiro-Moreira, A.C.O.; Mesquita, F.P.; Moraes, M.E.A.; Montenegro, R.C.; Oliveira, C.L.N. Double power-law viscoelastic relaxation of living cells encodes motility trends. *Sci. Rep.* **2020**, *10*, 4749.
- 51. Lenormand, G.; Bursac, P.; Butler, J.P.; Fredberg, J.J. Out-of-equilibrium dynamics in the cytoskeleton of the living cell. *Phys. Rev. E* **2007**, *76*, 041901.
- 52. Solon, J.; Levental, I.; Sengupta, K.; Georges, P.C.; Janmey, P.A. Fibroblast adaptation and stiffness matching to soft elastic substrates. *Biophys. J.* **2007**, *93*, 4453–4461.
- 53. Dolega, M.E.; Delarue, M.; Ingremeau, F.; Prost, J.; Delon, A.; Cappello, G. Cell-like pressure sensors reveal increase of mechanical stress towards the core of multicellular spheroids under compression. *Nat. Comm.* **2017**, *8*, 14056.
- 54. Elosegui-Artola, A. The extracellular matrix viscoelasticity as a regulator of cell and tissue dynamics. *Curr. Opin. Cell Biol.* **2021**, 72, 10–18.
- 55. Dolega, M.E.; Monnier, S.; Brunel, B.; Joanny, J.F.; Recho, P.; Cappello, G. Extracellular matrix in multicellular aggregates acts as a pressure sensor controlling cell proliferation and motility. *eLife* **2021**, *10*.
- 56. Vader, D.; Kabla, A.; Weitz, D.; Mahadevan, L. Strain-induced alignment in collagen gels. PLOS One 2009, 4, e5902.
- 57. Royer, P.; Recho, P.; Verdier, C. On the quasi-static effective behaviour of poroelastic media containing elastic inclusions. *Mech. Res. Commun.* **2019**, *96*, 19–23.

# **Supplementary materials**

# Viscoelastic properties of cancer systems: from cells to spheroids

Yara Abidine, Arianna Giannetti, Jean Revilloud, Valerie M. Laurent and Claude Verdier



**Figure S1.** Parameters  $G_1$  (A),  $G_2$  (B),  $G_3$  (C) and exponent d (D) for RT112, T24 and J82 cancer cells on different gels (E= 5-8-28 kPa). These parameters are a complement of the fitted parameters shown in Figure 2. The parameters were extracted from fitting G' and G'' with Eq. (3). Three different adjustments were performed, and the means of the parameters were obtained. Error bars represent the mean and SEM (standard error of the mean). Asterisks denote a significant difference by student t-test: ns=not significant, \*p<0.05, \*\*p<0.01 relative to condition 5 kPa. A bar is added under the asterisk when a difference is found between RT112-T24 and T24-J82 on 8 kPa gels.