

Fabrication of 3D printed antimicrobial polycaprolactone scaffolds for tissue engineering applications

Socrates Radhakrishnan, Sakthivel Nagarajan, Habib Belaid, Cynthia Farha, Igor Iatsunskyi, Emerson Coy, Laurence Soussan, Vincent Huon, Jonathan Barés, Catherine Teyssier, et al.

▶ To cite this version:

Socrates Radhakrishnan, Sakthivel Nagarajan, Habib Belaid, Cynthia Farha, Igor Iatsunskyi, et al.. Fabrication of 3D printed antimicrobial polycaprolactone scaffolds for tissue engineering applications. Materials Science and Engineering: C, 2021, 118, pp.111525. 10.1016/j.msec.2020.111525. hal-03258024

HAL Id: hal-03258024

https://hal.science/hal-03258024

Submitted on 11 Jun 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- 1 Fabrication of 3D printed antimicrobial polycaprolactone scaffolds for tissue
- 2 engineering applications

- 4 Socrates Radhakrishnan^{1,2μ}, Sakthivel Nagarajan^{2μ}, Habib Belaid^{2,3}, Cynthia Farha²,
- 5 Igor Iatsunskyi⁴, Emerson Coy⁴, Laurence Soussan², Vincent Huon⁵, Jonathan Bares⁵,
- 6 Catherine Teyssier³, Sébastien Balme², Philippe Miele^{2,6}, David Cornu², Narayana
- 7 Kalkura¹, Vincent Cavaillès³ and Mikhael Bechelany^{2*}

8

- 9 1. Crystal Growth Centre, Anna University, Chennai, India, 600025.
- 2. Institut Européen des Membranes, IEM UMR 5635, Univ Montpellier, CNRS, ENSCM,
- 11 Montpellier, France
- 3. IRCM, Institut de Recherche en Cancérologie de Montpellier, INSERM U1194, Université
- Montpellier, Montpellier F-34298, France
- 4. NanoBioMedical Centre, Adam Mickiewicz University, 3 Wszechnicy Piastowskiej str.,
- 15 61-614, Poznan, Poland
- 5. LMGC, Laboratoire de Mécanique et Génie Civil, Université Montpellier, CNRS,
- 17 Montpellier, France
- 6. Institut Universitaire de France (IUF), 1 rue Descartes, Paris F-73231, France


19

- 20 ^μ Authors contributed equally
- *Corresponding author: mikhael.bechelany@umontpellier.fr, Phone: +33467149167, Fax:
- 22 +33467149119

23

24

1 GRAPHICAL ABSTRACT



2

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

ABSTRACT

Synthetic polymers are widely employed for bone tissue engineering due to their tunable physical properties and biocompatibility. Inherently, most of these polymers display poor antimicrobial properties. Infection at the site of implantation is a major cause for failure or delay in bone healing process and the development of antimicrobial polymers is highly desired. In this study, silver nanoparticles (AgNps) were synthesized in polycaprolactone (PCL) solution by in-situ reduction which was further extruded into PCL/AgNp filaments. Customized 3D structures were then fabricated using the PCL/AgNp filaments through 3D printing technique. As demonstrated by scanning electron microscopy, the 3D printed scaffolds exhibited interconnected porous structures which are crucial for cell infiltration. Furthermore, X-ray photoelectron spectroscopy analysis revealed the reduction of silver ion. Transmission electron microscopy along with energy-dispersive X-ray spectroscopy analysis revealed the formation of silver nanoparticles throughout the PCL matrix. *In vitro* enzymatic degradation studies showed that the PCL/AgNps scaffolds displayed 80% degradation in 20 days. The scaffolds were cyto-compatible, as assessed by using MG63 cells and their antibacterial activity was demonstrated on Escherichia coli. Due to their interconnected structure, mechanical and antibacterial properties, these cyto-compatible multifunctional 3D printed PCL/AgNps scaffolds are highly suitable for bone tissue engineering.

2223

Keywords:

- 2 polycaprolactone, silver nanoparticles, nanocomposites, cytocompatibility, antimicrobial,
- 3 multifunctional properties

Highlights:

- 6 We report the development of antimicrobial polycaprolactone scaffold by 3D printing
- 7 The silver nanoparticles (AgNps) were obtained by in-situ reduction in PCL solution
- 8 AgNps reinforcement improved the stiffness of the 3D printed scaffolds
- 9 3D printed scaffold exhibited multifunctional property
- 10 Fabricated 3D scaffold showed cytocompatibility and antimicrobial properties

INTRODUCTION

Fused deposition modelling (FDM) is one of the simple and cost effective techniques employed in 3D printing of polymers for bone tissue engineering¹⁻². Various thermoplastic polymers such as poly-ε-capro-lactone (PCL)³, poly(L-lactic acid) (PLLA)⁴ and poly-vinylalcohol (PVA)⁵, have been used in 3D printing. Among them, PCL was widely used for the fabrication of bone scaffolds because of its FDA (Food and Drug Administration) approval, biocompatibility and biodegradation properties⁶. The low melting point (60°C) of PCL is advantageous for 3D printing⁷. In addition, PCL exhibits good mechanical properties with high flexibility and great elongation at break⁸, interesting for the preparation of scaffolds for craniofacial bone repair and cranial defects⁹. However, optimization of 3D printed PCL scaffolds by including other multifunctional properties such as antimicrobial activity and mechanical performance, without compromising their biocompatibility, is crucial to employ the scaffold for biomedical application.

About 2 to 5% of orthopaedic implants are complicated by infection¹⁰ and this can raise up to 30% in the case of open fractures¹¹. Implant related infections are associated with significant morbidity and sometimes death. These complications lead to implant removal, surgical debridement of infected tissue and long-term antibiotic administration¹²⁻¹³. Loading of antibiotics or metallic component is an issue to impart antibacterial property to the scaffolds. For instance, Visscher *et al.* developed 3D printed PCL scaffolds containing macro- and micro-pores (obtained using porogen) and coated with antibiotic (®Cefazoline). These scaffolds were active against *S. aureus*¹⁴. This design is very potential, however the

alarming levels of antibiotic resistance bacteria implies the necessity for developing potential

2 alternate to this approach.

expression, DNA damages and apoptosis²⁰.

3 Silver, copper and zinc as metallic components are shown to exhibit antibacterial properties¹⁵.

Among them, silver has been widely used in research and clinics as a broad spectrum antibacterial agent and apart from antibacterial application, silver nanoparticles-polymer composite has been used as catalytic agent¹⁶, super capacitors¹⁷, electromagnetic interference (EMI) shielding¹⁸, fuel cells¹⁹ etc., Mechanism of the antibacterial activity of silver nanoparticles (AgNps) is unclear. However, a recent investigation by Qing et *al.* provides possible explanations: (i) Anchoring of AgNps on bacterial membrane leads to membrane rupture and cellular content leakage that result in the bacterial cell death, (ii) Small size nanoparticles infiltrate the membrane and interact with the biomolecules which result in the

dysfunction of bacterial cell, and (iii) AgNps are likely to catalyze O₂ reduction into reactive

oxygen species (ROS) whose accumulation leads to down regulation of antioxidant enzyme

Silver ions and its metallic nanoparticles can be directly incorporated into inorganic materials or mixed with synthetic and biopolymeric materials for the fabrication of antibacterial 3D printed structures²¹ ²². For example, Muwaffak *et al.* developed 3D printed antimicrobial wound dressing material by incorporating ionic silver, copper and zinc oxide onto the PCL polymer. Silver and copper based PCL material displayed better bactericidal property than the zinc based material. However, this study is very limited and the influence of ionic silver on biocompatibility was not analyzed.²³ AgNps were mixed with other synthetic polymers such as polyetheretherketone (PEEK) and 3D printed using FDM technique. The obtained scaffolds showed good antimicrobial properties²⁴. Silver incorporation in tricalcium phosphate (as inorganic matrix) based 3D printed scaffolds facilitated differentiation of mesenchymal stem cells into osteoblasts²⁵. PCL scaffolds were also synthesized with impregnated or surface coated silver nanoparticles in order to increase antibacterial activity²⁶⁻²⁸. The scaffolds fabricated through solvent casting and electrospinning technique display poor control over the architecture and the uncontrollable pore size in comparison to the 3D printing approach.

In this work, silver ions were *in situ* reduced into silver nanoparticles and encapsulated into the PCL matrix. The PCL composite (PCL/AgNps) was thermally extruded into PCL/AgNps filaments used for the fabrication of customized scaffolds by the FDM technique. After validation of *in situ* reduction, the enzymatic degradation of the scaffolds

- 1 was elaborately analyzed. The antibacterial activity of the PCL and PCL/AgNps scaffolds
- 2 was analyzed. Furthermore, scaffold cytocompatibility was evaluated using hFOB cells in
- 3 order to assess their potential use for bone tissue engineering applications.

5

6

Materials and Methods

Materials

- 7 Polycaprolactone (PCL, Mw~ 50000 Da) pellets were obtained from polymorph
- 8 (UK). N,N-Dimethylformamide (DMF; 99.8%; CAS number 68-12-2; Sigma),
- 9 Tetrahydrofuran (THF; 99%; CAS number 109-99-9; Sigma), silver nitrate (AgNO₃; CAS
- 10 number 7761-88-8, Sigma), Lipase cepacia (40.7 units/mg, CAS number 9001-62-1; Sigma),
- 11 MEM α (Minimum Essential Medium α) (A10490-01; Gibco), MTT (3-(4,5-Dimethylthiazol-
- 12 2-yl)-2,5-Diphenyltetrazolium Bromide) (98%; CAS number 298- 93 -1), fetal bovine serum
- 13 (FBS) (CVFSVF00-01; Eurobio), 1% (V/V), penicillin/streptomycin (15140-122; Gibco),
- 14 0.05% Trypsin-EDTA (25300-054; Gibco), Dimethyl sulfoxide (DMSO) (23486.297; BDH
- Prolab), ethanol (96% vol; CAS number 64-17-5), phosphate buffered saline (PBS, P44717;
- Sigma), Lysogeny broth (LB) Miller culture medium (L3522; Sigma), microbiologic agar
- 17 (A1296-1KG; Sigma), Bacteriopeptone (211677-500g; BD Biosciences), Yeast extract
- 18 (9112001; Biokar diagnostics), Sodium Chloride (NaCl; 99%; CAS number 7647-14-5;
- 19 Sigma), Potassium dihydrogen phosphate (KH₂PO₄; CAS number 7778-77-0), di-Sodium
- 20 hydrogen phosphate dodecahydrate (Na₂HPO₄.12H₂O; CAS number: 10039-32-4; Sigma)
- 21 and agar (CAS number 9002-18-0; Sigma) were obtained and used without further
- 22 purification. hFOB osteoblastic cell line obtained from ATCC was used for cytocompatibility
- 23 analysis. Non-pathogenic Gram-negative Escherichia coli bacterium (K12 DSM 423, from
- 24 DSMZ, Germany) was used for the antibacterial study.

25 26

Preparation of PCL/AgNps composite and extrusion of composite filaments

- 27 PCL solution (10% w/v) was prepared by dissolving it in solvent mixture (7:3 volume
- ratio of THF and DMF respectively) at 90°C. Silver nitrate with 2 different percentages (1%
- and 3% w/v) was added into the PCL solution and the temperature of the solution was
- maintained at 90°C. Resultant solution was refluxed for 3 hours to facilitate the reduction of
- 31 silver nitrate into silver nanoparticles. Brown polymer suspension was obtained which are
- 32 cooled and precipitated using 300 mL of ethanol and dried at room temperature. PCL/AgNp
- composites prepared using 1% and 3% silver nitrate are denoted as C1Ag2 and C3Ag2. PCL,
- C1Ag2 and C3Ag2 were extruded into filament by Noztek pro extruder at 120 °C.

Fabrication of 3D printed PCL/AgNp scaffold

PCL/AgNp scaffolds were fabricated using FDM technique. Scaffolds structure was customized using DesignSpark Mechanical® 2.0 software. The extruded filament was cast into 3D printed matrix by using FDM based 3D printer (PRUSA i3) and the settings are reported in the Table 1. Furthermore the scaffold made from the filaments of PCL, C1Ag2 and C3Ag2 are denoted as PCL, 1Ag2 and 3Ag2.

Table 1 Printer settings employed for printing PCL and PCL/AgNp scaffolds

Nozzle Diameter	0.4 mm
Extrusion width	0.45 mm
Layer height	0.05 mm
Fill density	25%
Fill pattern	Cubic
Extruder temperature	140°C
Bed Temperature	25°C
Speed of print moves	20-30 mm/s

Physical and chemical characterizations of the polymer and scaffolds

Surface morphology of the scaffold was observed using HITACHI S4800 scanning electron microscopy system and the samples were sputter-coated for 30s using platinum/palladium for SEM analysis. Here, Image J software was employed to calculate the mean filament diameter by taking average at 20 points and the pore size by taking average of 8 pores, which is denoted as mean \pm standard deviation. The Fourier transform infrared (FTIR) spectrum of the scaffold was recorded in the frequency range of $4000-600~\text{cm}^{-1}$ by NEXUS instrument in an attenuated total reflection (ATR) mode. X-Ray diffraction (XRD) analysis was performed by PANalytica Xpert powder XRD system using Cu Ka radiation, 20 range of $10-80^{\circ}$. X-ray photoelectron spectroscopy (XPS) analysis was performed using KRATOS- AXIS Ultra DLD model having monochromatic Al-K alpha source of 1486.6~eV spectral resolution FWHM 0.45~eV. *In situ* synthesis of silver nanoparticles in the PCL polymer was characterized using TEM (JEOL ARM 200F) combined with an EDX Analyzer.

- 1 For TEM analysis, polymer samples were cut into 90 nm thick slices after fixing it in Devcon
- 2 5@Minute Epoxy using ultra microtome and mounted over the Cu grid. Mechanical
- 3 properties of the PCL composites were assessed using a traction machine (MTS 1/ME)
- 4 equipped with a 5 kN force sensor. PCL composites were 3D printed as standard dog bones
- 5 shapes to measure the mechanical properties and the analysis was performed in the strain rate
- of 0.01 mm s⁻¹. Furthermore, Young's modulus and Poisson's ratio were calculated on
- 7 minimum three assays as demonstrated elsewhere ²⁹⁻³⁰.

Enzymatic degradation of the PCL and PCL/AgNp scaffolds

In vitro degradation of the scaffolds was carried out using lipase enzyme at concentration of 10 units/mL. The lipase solution was prepared from 0.01 M phosphate-buffered saline (PBS) at pH 7.4. The samples were weighed and placed in a vial containing the 1 ml lipase solution and incubated at 37°C. Every 3 days, the enzyme solution was replenished with fresh lipase solution. After definite time, the samples were removed from the enzyme solution, washed, dried at 37°C and weighed. The percentage of degradation of the scaffold was calculated by measuring the ratio of the final weight of the sample to that of the initial weight (taken in the range of 9.0-15.0 mg) of the sample that is after and before the degradation.

Cell viability assay

hFOB osteoblastic cells were cultured using DMEM/F12 (Dulbecco's Modified Eagle Medium α) (Gibco 10565018) conditioned media supplemented with (i) 10 % (V/V) fetal bovine serum (FBS) (Eurobio CVFSVF00-01). Cells were cultured at 37°C in 5% CO₂ in a 10 cm diameter petri dish and trypsinized using 0.05% Trypsin-EDTA (Gibco 25300-054). After sterilization with 70% (w/v) ethanol for 30 mins, the printed scaffolds were dried at room temperature and then placed in contact with hFIB cells for 8 days. Cell viability was analyzed using MTT assay carried out by incubating 100 μ L of 0.5 mg/mL of MTT solution on the cells for 3h. Purple coloured formazan crystals were dissolved using 40 μ L of DMSO (BDH Prolab 23486.297) and the absorbance was recorded at 560 nm using Multiskan plate reader (thermos, USA).

Antibacterial activity

Antibacterial activity of the 3D PCL/AgNp scaffold was characterized by soft agar and liquid tests to study bacterial growth inhibition and bactericidal action respectively (the

1 detailed protocols are given in the supportive information S1). The samples used for the

antibacterial activity trials were sterilized by immersion in a water/ethanol (3:7 v/v) solution

for 1 h and washed afterwards for several times with sterile deionized water to remove the

ethanol traces in the sample. Later the washed samples were sterilely dried at 30°C overnight

and used for the antibacterial activity tests. Bacterial growth inhibition tests were carried out

6 by putting the samples in contact with a nutritive soft agar inoculated with bacteria.

Bactericidal action of the material was characterized by incubating the material in a

suspension of resting bacteria (i.e., un-growing bacteria).

9 10

11

13

14

2

3

4

5

7

8

RESULTS AND DISCUSSION

PCL/AgNps composite was synthesized through in situ reduction —mechanism

12 (equation 1 and 2) as described by Santos et al. ³¹. Obtained PCL/AgNp was utilized for the

fabrication of customized 3D printed structure (Figure 1). Physicochemical properties,

biocompatibility as well as antimicrobial properties of the PCL and PCL/AgNps scaffolds

were analyzed and discussed.

16
$$HCONMe_2 + 2Ag^+ + H_2O \longrightarrow 2Ag^0 + Me_2NCOOH + 2H^+$$
 (1)

Santos et al.³¹. described that the carbamic acid undergoes decomposition at high temperature

18 followed by evaporation.

19
$$Me_2NCOOH \longrightarrow CO_2 + Me_2NH$$
 (2)

20



2122

Figure 1. Photograph of the 3D printed scaffolds (scale bar denotes 1cm)

2324

26

27

28

29

Physicochemical properties of the scaffolds

25 Scanning electron microscopy SEM images of the 3D printed PCL and PCL/AgNps scaffolds

are shown in the Figure 2. SEM micrographs revealed that the PCL and PCL/AgNps 3D

scaffolds matrix displayed uniform porous structures with open and interconnected pores.

Inter filament spacing resulting from the fusion of multiple layers of polymer filaments are

denoted as pores as mentioned in the literature^{21, 32}. 3D structure and pore size of the

scaffolds plays a crucial role in cell infiltration. Murphy *et al.* demonstrated that the scaffolds having 80 to 190 µm pore size display cell aggregation and poor cells infiltration. Scaffolds of 300 µm pores size possess improved cells infiltration and the cells were observed at the center of the scaffolds without cell aggregation. These results prove that the pores sizes above 300 µm is crucial in the scaffolds design³³. Scaffolds obtained in our study displayed pore size larger than 300 µm (Table 2), this dimension being suitable for osteoblast cell infiltration. The diameter of 3D printed filaments is also shown in Table 2. SEM micrographs of 1Ag2 and 3Ag2 revealed homogeneous filament diameters which is crucial in order to obtain scaffolds with uniform architectures. High magnification SEM micrograph reveals wrinkly surface morphology for PCL and almost smooth and uniform surface for 1Ag2 and 3Ag2 (Figure 1). Here, AgNps act as the inorganic filler leading to the increased stiffness which is evident from the increased Young's modulus.




Figure 2. SEM analysis of 3D printed scaffolds

Table 2. Dimensions of the printed 3D scaffold

	PCL	1Ag2	3Ag2
Pore size (µm)	430.0 ± 29.8	379.6 ± 21.2	431.7 ± 24.6
Filament diameter (µm)	349.1 ± 21.6	406.4 ± 23.3	333.9 ± 12.0

FTIR analysis was used to identify the functional groups of the 3D printed PCL and PCL/AgNps scaffolds and the interaction between PCL and AgNps. The FTIR spectra are shown in Figure 3(A). The intense peak at 1721 cm⁻¹ is assigned to the stretching mode of carbonyl groups of PCL. The peaks at 2865 cm⁻¹ and 2944 cm⁻¹ correspond to the symmetric and asymmetric stretching of CH₂ groups in PCL polymer backbone. The peaks at 1238 cm⁻¹ and 1161 cm⁻¹ are due to symmetric and asymmetric stretching of C-O-C groups of PCL. The peaks at 1187 cm⁻¹ and 1292 cm⁻¹ are related to O-C-O stretching, and C-O and C-C stretching modes respectively³⁴. PCL display polar functional groups > C=O and -C-O-C- and their position of the corresponding peaks remains unaffected during the *in situ* reduction of silver ions into silver nanoparticles using DMF³⁵.






Figure 3. (A) FTIR and (B) XPS spectra of 3D printed scaffolds

X-ray photoelectron spectroscopy (XPS) analysis was used to confirm the formation of silver nanoparticles in the PCL/AgNp composite. The 3D printed scaffolds were scanned in the range of 200 to 600 eV.(figure 3(B)) The XPS spectra showed the peaks of C 1S, and O 1S which correspond to the PCL. The Ag 3d peaks (3d_{3/2}, 3d_{5/2}) are observed in the 1Ag2 and

- 1 3Ag2 samples. They confirm the presence of silver in these scaffolds. The peak separation
- 2 (energy difference of Ag3d peaks) of Ag 3d_{3/2}, 3d_{5/2} is 6eV which corresponds to the reduced
- 3 silver. These results show that the reduction of ionic silver into metallic silver is effectively
- 4 achieved using DMF^{31, 36-38}. Furthermore, silver concentration in 1Ag2 and 3Ag2 was
- 5 quantified using AAS as 1.34 and 15.22 mg/g of the 3D printed matrix respectively.
- 6 X-ray diffraction (XRD) was used to determine the crystalline structures of the AgNps/PCL
- 7 3D printed scaffolds (Figure 4(A)) The XRD diffractogram of the scaffolds PCL, 1Ag2 and
- 8 3Ag2 are characterized by diffraction peaks at $2\Theta = 21.2^{\circ}$, 21.7° and 23.5° which correspond
- 9 to (110), (111) and (200) crystal planes of PCL respectively³⁹. The diffraction peak observed
- at 38.8° (Figure 4(B)) in 1Ag2 and 3Ag2 diffractograms corresponds to the (111) plane of
- Ag. It confirms the presence of silver in 1Ag2 and 3Ag2 scaffolds.

14

15




Figure 4. XRD analysis of 3D printed scaffolds, (A) Whole diffractogram and (B) diffractogram of specific regions.

In situ synthesis and distribution of the silver nanoparticles in the 3D printed PCL matrix was analyzed using transmission electron microscopy (TEM) along with EDX analysis (Figure 5(a-d)). TEM bright field micrographs of 3Ag2 clearly reveal the distribution of silver nanoparticles as spots throughout the PCL matrix (Figure 5(a, b)). The sizes distribution is in the range of 20 to 150 nm (Figure 5c) exemplifying wide dispersity of the synthesized silver nanoparticles. Furthermore, EDX analysis confirms the distribution of silver nanoparticles in the PCL polymer matrix. Therefore, the presence of the silver nanoparticles in the PCL matrix is probably responsible of the antibacterial activity as it will be demonstrated later.




Figure 5. (a)-(b) TEM images of 3Ag2 sample, (c) Ag particle size distribution and (d) EDX elemental mapping of 3Ag2 scaffolds; Silver (green) and Carbon(red).

Materials used for implant tissue engineering applications should possess mechanical properties suitable for the targeted tissue. Therefore, the mechanical properties of 3D printed pristine PCL and PCL/Ag were characterized using tensile test analysis (Figure 6). Firstly the Poisson's ratio for PCL was 0.38 and remains constant with the addition of silver nanoparticles. Young's modulus of PCL was found to be 0.35 GPa which is in good agreement with the literature⁴⁰. For PCL/Ag (1Ag2 and 3Ag2), the Young's modulus increases from 0.35 (PCL) to 1 GPa (3Ag2). Generally, the fillers restrict the mobility of polymer matrix and enhance the rigidity of the scaffolds⁴¹⁻⁴². In this study, silver nanoparticles are also acting as fillers which decrease the elastic behavior of PCL and

improve its rigidity. Furthermore, increasing the silver concentration enhanced the Young's modulus of the PCL/AgNP (1Ag1 and 3Ag2) composite scaffolds. Here, the values of Young's modulus of the composites are between that of the cancellous bone (0.05-0.1 GPa) and cortical bone (3-30 GPa)⁴³. These results also support the employment of the composite scaffolds for bone tissue engineering application.




Figure 6. Mechanical property, Young's modulus of 3D printed scaffolds.

Enzymatic degradation test

In vitro enzymatic degradation analysis was used to evaluate stability of the 3D printed PCL/AgNp scaffolds. Lipase was employed because PCL possesses an ester bond prone to hydrolytic degradation by lipase. For this assay, the pre-weighed PCL, 1Ag2 and 3Ag2 scaffolds were immersed in the lipase solution and their degradation was recorded (Figure 6). PCL, 1Ag2 and 3Ag2 scaffolds display <10% degradation in 24 hours. The degradation of PCL scaffolds gradually increased to reach 82% degradation after 20 days. Generally, polymer undergoes surface degradation due to the direct contact of enzyme⁴⁴. Scaffolds (PCL, 1Ag2 and 3Ag2) fabricated in this study are interconnected porous scaffolds which display large surface area to interact with enzymes that can facilitate the degradation. Neumann *et al.* 3D printed PCL and PCL/CaCO₃ scaffolds and analyzed the degradation of the scaffolds using 15U/mL lipase. Our material exhibits a degradation profile similar to the degradation profile obtained by Neumann *et al.* in which PCL undergoes 80% degradation in 20 days⁴⁵.




Figure 7. Enzymatic degradation of 3D printed scaffolds

Biocompatibility analysis

Biocompatibility of the PCL, 1Ag2 and 3Ag2 scaffolds was assessed using hFOB cells which are a good *in vitro* model of bone cells (REF?). Cells grown on the tissue culture plate without scaffold served as tissue culture plate control (TCP). Biocompatibility of the 3D printed scaffolds was calculated by comparing cell viability of the 3D printed scaffolds with the TCP control. Cell viability data shown in Figure 8 were presented as mean ± standard deviation (S.D) and statistical analysis done using Student's t test indicating "ns" not significant and * p <0.05 with sample size, n=8.

Afer 8 days of culture, PCL scaffolds did not show any toxicity to the cells which evidences that the solvents employed for the preparation of 3D scaffolds are effectively removed. 1Ag2 allowed a better proliferation of the cells compared than PCL while 3Ag2 display a decrease in cell viability. Cell viability of 3Ag2 observed is likely due to the high concentration of silver loaded in the PCL matrix. However, cell viability was found to be greater than 80 % after 8 days which fits within the acceptable limits as set by ISO10993-5:2009. Despite their toxicity, silver and silver based formulation are utilized for commercial biomedical products such as PolyMem® Silver, Aquacel® Ag, ActicoatTM, Urgotul®SSD, Contreet®. Indeed, silver can be eliminated through urinary excretion in humans⁴⁷. Nevertheless, 3D printed PCL/AgNps display low cytotoxicity, suggesting that they could be suitable for tissue engineering application.




Figure 8. hFOB osteoblastic cell viability after 8 day of culture on of 3D printed scaffolds. (ns= not significant, * p<0.05, ** p<0.005 and ***** p<0.000005)

Bacterial growth inhibition test

Antibacterial activity of the materials was first characterized by growth inhibition tests. Bacterial growth inhibition test was performed to assess the ability of the material to prevent the implanted site from the formation of bacterial biofilm in presence of nutrients since it could lead to bacterial infection. Figure 9 presents the results obtained for the inhibition tests performed at 24 h.




Figure 9. Soft agar plates inoculated with *E. coli* cells and incubated with 3D printed scaffolds in their center for 24 h (Scale bar denotes 1 cm)

Negative control plates (i.e. without bacteria and material) show clear nutritive soft agar plates while positive control plates (i.e., with bacteria and without material) show a uniform distribution of bacterial colonies within the soft agar (Fig. 9). With 3Ag2 material, a clear inhibition zone of mean diameter 20.4 ± 1.7 mm is observed whereas no clear zone is observed for PCL and 1Ag2 (Fig. 9) for which biofilms are evidenced on the material surfaces. The presence of an inhibition zone around the 3Ag2 material evidences an antibacterial activity based on the diffusion of biocidal agents through the soft agar. These biocidal agents might be silver (most likely Ag0 rather than Ag⁺ according to XPS analysis) and/or ROS. This antibacterial activity does not exclude a bactericidal surface action by the AgNP present on the material, but the soft agar test does not allow to conclude on that.

Bactericidal activity

Bactericidal tests were done to assess the ability of the material to remove bacteria that has already grown on the material implantation zone. Bactericidal activity was assessed by liquid tests in which the material (90 \pm 10 mg) was immersed in a bacterial suspension (10 mL) at about 10^2 CFU/mL. Table 3 shows the bacterial concentrations (CFU/mL) and the associated log-removal values, where the log-removal is defined as the logarithm (log) ratio of the bacterial concentration C measured after respective contact time relative to the initial bacterial concentration C_0 . A log-removal value of -log (C_0) was attributed to the particular

1 case of total removal of the cultivable bacteria. A log-removal value higher than 1 is related

to a significant bactericidal activity, i.e., to a reduction in bacterial concentration higher than

3 90 %. Table 3 reports also the total silver concentration measured by AAS in the liquid after

4 24 h contact.

Table 3. Log-removals and concentrations of released silver obtained in bactericidal tests against an *E. coli* suspension; the initial bacterial concentration C_0 was 175 ± 50 CFU/mL

	After 6 h conta	ct	After 24 h contact			
Test	Bacterial	Log	Bacterial	Log	Total silver	
	concentration	removal	concentration	removal	concentration	
	(CFU/mL)	(-)	(CFU/mL)	(-)	(mg/L)	
C _{Positive} control	175 ± 50	0	175 ± 50	0	-	
CPCL	115 ± 5	0.2	135 ± 0	0.1	-	
C _{1Ag2}	145 ± 40	0.1	10 ± 10	1.2	0.06	
C3Ag2	5 ± 5	1.5	0 ± 0	2.2	0.44	

PCL material shows a low log-removal value of 0.2 and 0.1 for 6 h and 24 h contact time respectively (Table 3). As PCL was not reported to have any antibacterial activity, the log-removal observed is probably due to bacteria adsorption on the PCL. It is thus likely that such an adsorption also occurred for the silver materials. After 6 h only, 3Ag2 material shows a significant decrease of the bacterial concentration corresponding to a log-removal value of 1.5 (Table 3), which is close to the maximal log-removal value reachable (i.e. $-\log C_0 = 2.2$). Hereafter 24 h, 1Ag2 depicted a marked decrease of bacterial concentration leading to a log-removal value of 1.2 and 3Ag2 material managed to inactivate all the bacteria initially present. This result clearly evidences the bactericidal activity of the 1Ag2 and 3Ag2 materials due to the presence of AgNPs in the material.

AAS measurements reveal that small silver concentrations were released in the suspension after 24 h (Table 3), which corresponds to silver mass lost by the material of 6.0×10^{-4} mg for 1Ag2 and 4.4×10^{-3} for 3Ag2 respectively. Since the initial silver content of the materials were 0.13 % w/w for 1Ag2 and 1.5 % w/w for 3Ag2, and the samples weight

were 90 \pm 10 mg, it means that the mass of silver incorporated in PCL were 0.12 mg for

1Ag2 and 1.35 mg for 3Ag2 respectively. After 24 h of reaction, 1Ag2 consequently lost 0.05 % of its silver whereas 3Ag2 lost 0.3 %. This result demonstrates the good chemical stability of both PCL/AgNps materials in presence of bacteria. In the case of 1Ag2, a bactericidal action of the surfaces is mainly evidenced because the silver released in the bacterial suspension is very small (< 0.1 mg/L). For 3Ag2, a coupled action of both the AgNps surface and the silver desorbed can be suspected. The need for a longer contact time (24 h vs 6 h) to observe a bactericidal activity of 1Ag2 might consequently be due to a lower content of silver nanoparticles on the material surface contacting the bacteria. These results are consistent with the fact that the antibacterial activity depends on the quantity of silver nanoparticles which is acting as the antibacterial agent⁴⁸.

Conclusion

PCL/AgNps polymer composite was achieved through *in situ* reduction of silver ions using DMF as a reducing agent as well as solvent. Synthesized PCL/AgNps composites were extruded into self-standing filaments further utilized for the fabrication of customized 3D porous structures using 3D printing technique. XRD, XPS, TEM and EDAX analysis confirmed the presence of silver nanoparticles within the 3D printed matrix. SEM analysis of the scaffolds shows that the 3D printed scaffolds displayed interconnected porous structures wrinkly surface on PCL and uniform smooth surface on 1Ag2 and 3Ag2 scaffolds. Here the presence of silver nanoparticles in the PCL scaffold improved its stiffness (Young's modulus) and enzymatic stability. Soft agar test showed that 3Ag2 scaffold exhibited an inhibition zone where *E. coli* growth is prevented around the scaffold due presumably to ROS and silver nanoparticles diffusion from PCL scaffold to soft agar. Besides, a biocidal surface action was evidenced for both 1Ag2 and 3Ag2. Furthermore, we show that the 3D printed scaffolds exhibit cytocompatibility. Altogether, our study shows that the scaffolds developed could be utilized for the fabrication of antimicrobial scaffolds for bone tissue engineering application.

Acknowledgements

The authors would like to thank for the financial support from Indo-French Centre for the promotion of advanced research-Cefipra (Project 5608-1). This study was supported as well by the University of Montpellier (MUSE "3DTraitCancer" project). I.I and E.C. acknowledge the partial financial support by project H2020-MSCA-RISE-2017, 'Novel 1D photonic metal oxide nanostructures for early stage cancer detection' (Project number: 778157). I.I. also acknowledges the support of dr. Łucja Przysiecka in TEM sample preparation.

References:

- 4 1. Gibson, I.; Rosen, D.; Stucker, B., The Impact of Low-Cost AM Systems. In Additive
- 5 Manufacturing Technologies: 3D Printing, Rapid Prototyping, and Direct Digital Manufacturing,
- 6 Gibson, I.; Rosen, D.; Stucker, B., Eds. Springer New York: New York, NY, 2015, pp 293-301.
- 7 2. Belaid, H.; Nagarajan, S.; Barou, C.; Huon, V.; Bares, J.; Balme, S.; Miele, P.; Cornu, D.;
- 8 Cavaillès, V.; Teyssier, C.; Bechelany, M., Boron Nitride Based Nanobiocomposites: Design by 3D
- 9 Printing for Bone Tissue Engineering. ACS Applied Bio Materials 2020.
- Temple, J. P.; Hutton, D. L.; Hung, B. P.; Huri, P. Y.; Cook, C. A.; Kondragunta, R.; Jia, X.;
- 11 Grayson, W. L., Engineering anatomically shaped vascularized bone grafts with hASCs and 3D-printed
- 12 PCL scaffolds. Journal of Biomedical Materials Research Part A 2014, 102 (12), 4317-4325.
- 4. Belaid, H.; Nagarajan, S.; Teyssier, C.; Barou, C.; Barés, J.; Balme, S.; Garay, H.; Huon, V.;
- 14 Cornu, D.; Cavaillès, V.; Bechelany, M., Development of new biocompatible 3D printed graphene
- oxide-based scaffolds. *Materials Science and Engineering: C* **2020,** *110,* 110595.
- 16 5. He, H.-Y.; Zhang, J.-Y.; Mi, X.; Hu, Y.; Gu, X.-Y., Rapid prototyping for tissue-engineered bone
- scaffold by 3D printing and biocompatibility study. *Int J Clin Exp Med* **2015**, *8* (7), 11777-11785.
- 18 6. Sun, H.; Mei, L.; Song, C.; Cui, X.; Wang, P., The in vivo degradation, absorption and excretion
- 19 of PCL-based implant. *Biomaterials* **2006,** *27* (9), 1735-1740.
- 20 7. Más Estellés, J.; Vidaurre, A.; Meseguer Dueñas, J. M.; Castilla Cortázar, I., Physical
- 21 characterization of polycaprolactone scaffolds. *Journal of Materials Science: Materials in Medicine*
- 22 **2008,** *19* (1), 189-195.
- 23 8. Matzinos, P.; Tserki, V.; Gianikouris, C.; Pavlidou, E.; Panayiotou, C., Processing and
- characterization of LDPE/starch/PCL blends. European Polymer Journal 2002, 38 (9), 1713-1720.
- 25 9. Osteogenic Induction of Human Bone Marrow-Derived Mesenchymal Progenitor Cells in
- 26 Novel Synthetic Polymer–Hydrogel Matrices. *Tissue Engineering* **2003**, *9* (4), 689-702.
- 27 10. Darouiche, R. O., Treatment of Infections Associated with Surgical Implants. New England
- 28 *Journal of Medicine* **2004,** *350* (14), 1422-1429.
- 29 11. Trampuz, A.; Widmer, A. F., Infections associated with orthopedic implants. Current Opinion
- 30 in Infectious Diseases **2006**, 19 (4), 349-356.
- 31 12. Lazzarini, L.; Mader, J. T.; Calhoun, J. H., Osteomyelitis in Long Bones. JBJS 2004, 86 (10),
- 32 2305-2318.
- 33 13. Lew, D. P.; Waldvogel, F. A., Osteomyelitis. *The Lancet* **2004**, *364* (9431), 369-379.
- 34 14. Visscher, L. E.; Dang, H. P.; Knackstedt, M. A.; Hutmacher, D. W.; Tran, P. A., 3D printed
- 35 Polycaprolactone scaffolds with dual macro-microporosity for applications in local delivery of
- antibiotics. *Materials Science and Engineering: C* **2018**, *87*, 78-89.
- 37 15. Morones-Ramirez, J. R.; Winkler, J. A.; Spina, C. S.; Collins, J. J., Silver enhances antibiotic
- 38 activity against gram-negative bacteria. Sci Transl Med 2013, 5 (190), 190ra81-190ra81.
- 39 16. Lu, S.; Yu, J.; Cheng, Y.; Wang, Q.; Barras, A.; Xu, W.; Szunerits, S.; Cornu, D.; Boukherroub,
- 40 R., Preparation of silver nanoparticles/polydopamine functionalized polyacrylonitrile fiber paper and
- 41 its catalytic activity for the reduction 4-nitrophenol. *Applied Surface Science* **2017**, *411*, 163-169.
- 42 17. Patil, D. S.; Pawar, S. A.; Patil, P. S.; Kim, J. H.; Shin, J. C., Silver Nanoparticles Incorporated
- 43 PEDOT-PSS Electrodes for Electrochemical Supercapacitor. Journal of Nanoscience and
- 44 *Nanotechnology* **2016,** *16* (10), 10625-10629.
- 45 18. Lee, T.-W.; Lee, S.-E.; Jeong, Y. G., Highly Effective Electromagnetic Interference Shielding
- 46 Materials based on Silver Nanowire/Cellulose Papers. ACS Applied Materials & Interfaces 2016, 8
- 47 (20), 13123-13132.
- 48 19. Choudhury, A., Polyaniline/silver nanocomposites: Dielectric properties and ethanol vapour
- 49 sensitivity. *Sensors and Actuators B: Chemical* **2009,** *138* (1), 318-325.

- 1 20. Qing, Y. a.; Cheng, L.; Li, R.; Liu, G.; Zhang, Y.; Tang, X.; Wang, J.; Liu, H.; Qin, Y., Potential
- 2 antibacterial mechanism of silver nanoparticles and the optimization of orthopedic implants by
- 3 advanced modification technologies. Int J Nanomedicine 2018, 13, 3311-3327.
- 4 21. Correia, T. R.; Figueira, D. R.; de Sá, K. D.; Miguel, S. P.; Fradique, R. G.; Mendonça, A. G.;
- 5 Correia, I. J., 3D Printed scaffolds with bactericidal activity aimed for bone tissue regeneration.
- 6 International Journal of Biological Macromolecules **2016**, *93*, 1432-1445.
- 7 22. Vasilev, K.; Cook, J.; Griesser, H. J., Antibacterial surfaces for biomedical devices. Expert
- 8 *Review of Medical Devices* **2009,** *6* (5), 553-567.
- 9 23. Muwaffak, Z.; Goyanes, A.; Clark, V.; Basit, A. W.; Hilton, S. T.; Gaisford, S., Patient-specific
- 3D scanned and 3D printed antimicrobial polycaprolactone wound dressings. *International Journal of*
- 11 *Pharmaceutics* **2017,** *527* (1), 161-170.
- 12 24. Deng, L.; Deng, Y.; Xie, K., AgNPs-decorated 3D printed PEEK implant for infection control
- and bone repair. *Colloids and Surfaces B: Biointerfaces* **2017,** *160,* 483-492.
- 14 25. Zhang, Y.; Zhai, D.; Xu, M.; Yao, Q.; Zhu, H.; Chang, J.; Wu, C., 3D-printed bioceramic scaffolds
- with antibacterial and osteogenic activity. *Biofabrication* **2017**, *9* (2), 025037.
- 16 26. Silver Nanoparticle Impregnated Poly (ε-Caprolactone) Scaffolds: Optimization of
- 17 Antimicrobial and Noncytotoxic Concentrations. *Tissue Engineering Part A* **2011,** *17* (3-4), 439-449.
- 18 27. Kalakonda, P.; Aldhahri, M. A.; Abdel-wahab, M. S.; Tamayol, A.; Moghaddam, K. M.; Ben
- 19 Rached, F.; Pain, A.; Khademhosseini, A.; Memic, A.; Chaieb, S., Microfibrous silver-coated polymeric
- scaffolds with tunable mechanical properties. RSC Advances 2017, 7 (55), 34331-34338.
- 21 28. Zhou, Y.; Thakurathi, M.; Quitevis, E. L.; Tan, G. Z., Electrospinning 3D Nanofiber Structure of
- Polycaprolactone Incorporated with Silver Nanoparticles. *JOM* **2019,** *71* (3), 956-962.
- 23 29. Vu, T.-L.; Barés, J., Soft-grain compression: Beyond the jamming point. Physical Review E
- 24 **2019,** *100* (4), 042907.
- 25 30. Vu, T. L.; Barés, J.; Mora, S.; Nezamabadi, S., Deformation Field in Diametrically Loaded Soft
- 26 Cylinders. *Experimental Mechanics* **2019**, *59* (4), 453-467.
- 27 31. Pastoriza-Santos, I.; Liz-Marzán, L. M., N,N-Dimethylformamide as a Reaction Medium for
- 28 Metal Nanoparticle Synthesis. *Advanced Functional Materials* **2009,** *19* (5), 679-688.
- 29 32. Park, J.; Lee, S. J.; Jo, H. H.; Lee, J. H.; Kim, W. D.; Lee, J. Y.; Park, S. A., Fabrication and
- 30 characterization of 3D-printed bone-like β -tricalcium phosphate/polycaprolactone scaffolds for
- dental tissue engineering. Journal of Industrial and Engineering Chemistry 2017, 46, 175-181.
- 32 33. Murphy, C. M.; Haugh, M. G.; O'Brien, F. J., The effect of mean pore size on cell attachment,
- 33 proliferation and migration in collagen–glycosaminoglycan scaffolds for bone tissue engineering.
- 34 *Biomaterials* **2010,** *31* (3), 461-466.
- 35 34. Elzein, T.; Nasser-Eddine, M.; Delaite, C.; Bistac, S.; Dumas, P., FTIR study of
- 36 polycaprolactone chain organization at interfaces. Journal of Colloid and Interface Science 2004, 273
- 37 (2), 381-387.
- 38 35. López-Esparza, J.; Espinosa-Cristóbal, L. F.; Donohue-Cornejo, A.; Reyes-López, S. Y.,
- 39 Antimicrobial Activity of Silver Nanoparticles in Polycaprolactone Nanofibers against Gram-Positive
- 40 and Gram-Negative Bacteria. Industrial & Engineering Chemistry Research 2016, 55 (49), 12532-
- 41 12538.
- 42 36. Thomas, S.; Nair, S. K.; Jamal, E. M. A.; Al-Harthi, S. H.; Varma, M. R.; Anantharaman, M. R.,
- 43 Size-dependent surface plasmon resonance in silver silica nanocomposites. Nanotechnology 2008,
- 44 19 (7), 075710.
- 45 37. Ren, S.; Dong, L.; Zhang, X.; Lei, T.; Ehrenhauser, F.; Song, K.; Li, M.; Sun, X.; Wu, Q.,
- 46 Electrospun Nanofibers Made of Silver Nanoparticles, Cellulose Nanocrystals, and Polyacrylonitrile as
- 47 Substrates for Surface-Enhanced Raman Scattering. *Materials* **2017**, *10* (1), 68.
- 48 38. Pastoriza-Santos, I.; Liz-Marzán, L. M., Formation and Stabilization of Silver Nanoparticles
- 49 through Reduction by N,N-Dimethylformamide. Langmuir 1999, 15 (4), 948-951.

- 1 39. Lv, Q.; Wu, D.; Xie, H.; Peng, S.; Chen, Y.; Xu, C., Crystallization of poly(ε-caprolactone) in its
- 2 immiscible blend with polylactide: insight into the role of annealing histories. RSC Advances 2016, 6
- 3 (44), 37721-37730.
- 4 40. Eshraghi, S.; Das, S., Mechanical and microstructural properties of polycaprolactone
- 5 scaffolds with one-dimensional, two-dimensional, and three-dimensional orthogonally oriented
- 6 porous architectures produced by selective laser sintering. Acta Biomaterialia 2010, 6 (7), 2467-
- 7 2476.
- 8 41. Ahn, S. H.; Kim, S. H.; Kim, B. C.; Shim, K. B.; Cho, B. G., Mechanical properties of silica
- 9 nanoparticle reinforced poly(ethylene 2, 6-naphthalate). Macromolecular Research 2004, 12 (3),
- 10 293-302.
- 42. Guerrica-Echevarría, G.; Eguiazábal, J. I.; Nazábal, J., Influence of molding conditions and talc
- content on the properties of polypropylene composites. European Polymer Journal 1998, 34 (8),
- 13 1213-1219.
- 14 43. The Design of Scaffolds for Use in Tissue Engineering. Part I. Traditional Factors. Tissue
- 15 *Engineering* **2001,** *7* (6), 679-689.
- 16 44. Khan, I.; Nagarjuna, R.; Dutta, J. R.; Ganesan, R., Enzyme-Embedded Degradation of Poly(ε-
- 17 caprolactone) using Lipase-Derived from Probiotic Lactobacillus plantarum. ACS Omega 2019, 4 (2),
- 18 2844-2852.

- 19 45. Neumann, R.; Neunzehn, J.; Hinueber, C.; Flath, T.; Schulze, F. P.; Wiesmann, H. P., 3D-
- 20 printed poly-ε-caprolactone-CaCO3-biocomposite-scaffolds for hard tissue regeneration. *Express*
- 21 Polym. Lett. **2019**, 13, 2-17.
- 22 47. Hadrup, N.; Sharma, A. K.; Loeschner, K., Toxicity of silver ions, metallic silver, and silver
- 23 nanoparticle materials after in vivo dermal and mucosal surface exposure: A review. Regulatory
- 24 *Toxicology and Pharmacology* **2018,** *98,* 257-267.
- 25 48. Erick Pazos-Ortiz, J. H. R.-R., Efrén Amador Hinojos-Márquez , Juan López-Esparza, Alejandro
- 26 Donohué-Cornejo, Juan Carlos Cuevas-González , León Francisco Espinosa-Cristóbal , and Simón
- 27 Yobanny Reyes-López, Dose-Dependent Antimicrobial Activity of Silver Nanoparticles on
- 28 Polycaprolactone Fibers against Gram-Positive and Gram-Negative Bacteria. Journal of
- 29 *nanomaterials* **2017**, *2017*, 1-8.