

Corrosion behaviours in acidic solution of spheroidal cast irons highly alloyed with nickel or cobalt. Part 1: Elaboration and microstructures of the alloys

Kamel Meridja, Patrice Berthod

▶ To cite this version:

Kamel Meridja, Patrice Berthod. Corrosion behaviours in acidic solution of spheroidal cast irons highly alloyed with nickel or cobalt. Part 1: Elaboration and microstructures of the alloys. Eurocorr 2016, Sep 2016, Montpellier, France. hal-03271532

HAL Id: hal-03271532 https://hal.science/hal-03271532

Submitted on 25 Jun 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Faculté des Sciences et

Technologies

Corrosion behaviours in acidic solution of spheroidal cast irons highly alloyed with nickel or cobalt. Part 1: Elaboration and microstructures of the alloys

Kamel Meridja¹ and Patrice Berthod^{1,2}

¹Faculty of Sciences and Technologies, ²Institut Jean Lamour, University of Lorraine, BP 70239, Bd des Aiguillettes, 54506 Vandoeuvre-lès-Nancy, France


patrice.berthod@univ-lorraine.fr

Certainly the most used metallic alloys are the ferrous ones. Initially issued in the liquid state from the reduction of iron ore, at the exit of blast furnaces [1] the liquid cast iron, mainly constituted of Fe but containing also significant amounts in carbon (coke) and in silicon (gangue), may be directly driven to the foundry workshop to be treated then poured in moulds to solidify with the shape wished for the wished pieces [2] or driven to the oxygen converter to lose the main parts of their carbon and silicon to become liquid steel [3]. In both cases they can be enriched with supplementary elements to obtain more or less highly alloyed cast irons or steels for achieving special microstructures and properties [5]. This can be useful to achieve new mechanical behaviours as well as improved corrosion resistance

Alloying cast irons with new elements, foreign to the composition at the exit of blast furnace often supposes that new liquid metal treatments must be done after the addition (inoculation for help graphite nucleation, desulphurization then magnesium treatment for promoting the spheroidal growth of graphite...). But it was also demonstrated that it is possible to take a spheroidal graphite cast iron (SG cast iron), rapidly remelting it, adding the new element, homogenizing a short time the liquid alloy before quickly solidifying it [5]. This was attempted here to obtain SG cast irons highly alloyed to either nickel or cobalt, in order to study the properties that they are able to bring.

Elaboration of the Ni- and Co-alloyed cast irons

dal graphite cast inon ingot of industrial origin, the composition of which is a re preliminary cut in a spheroid 3.5 wt.%C and 2.5 wt.%Si (rest: Fe). Three 30g-weighing there charges (10, 20 and 30g) of mixture of pure elements were prepared and melted together in a High Frequency induction furnace under an inert atmosphere (pure argon).






250 Microstructure of the industrial SG cast iron devoted to be alloyed with the mother allovs

25Ni75Fe





Microstructures of the xNi-(50-x)Fe cast irons


The EDS control of the chemical compositions of the obtained alloys showed that the targeted contents in Ni or Co, Fe and Si were really obtained (carbon cannot be analysed with this technique)

The conservation of the initial spheroidal type of graphite of the industrial SG cast iron was rather successful in the case of the 25Ni75Fe cast iron. The graphite nodules are only a little irregular.


Several cm³ of fresh "Nital4" etchant (96% ethanol + 4% of pure nitric acid HNO₃, in volume) were prepared. This solution is famous for revealing the microstructures of not alloyed ferrous alloys. The metallographic samples were thereafter immersed during 10 seconds in this solution in order to observe the response of the obtained alloysto this oxidant solution. After this immersion at room temperature the metallographic samples were quickly insed with tap water, ethanol and dried with a hair-drier. They were observed again using this time a simple optical microscope (Olympus BX51) equipped with a camera (ToupCam). Visualization and photography were carried out using a computer and the ToupView software.

This led to mother alloys the chemical compositions of which were either Co-3.5C2.5Si, or N-3.5C-2.5Si or Fe-3.5C-2.5Si (all contents in weight percent). The three 30g-weighing part of industrial cast iron were thereafter remetled together with the 10g-weighing ingot of M-ich mother alloy (M=Co, N or Fe), this leading to three 25M75Fe-based alloys. The three 20g-weighing part of industrial cast iron were remetled together with the 20g-weighing ingot of M-ich mother alloy (M=Co, N or Fe), this leading part of industrial cast iron were remetled together with the 20g-weighing part of industrial cast iron were remetled together with the 30g-weighing ingot of M-ich mother alloy (M=Co, N or Fe), this leading to three 50M50Fe-based alloys. The three 10g-weighing part of industrial cast iron were memeted together with the 30g-weighing ingot of M-ich mother alloy (M=Co, N or Fe), this leading to three 75M25Fe-based alloys. The same furace as for preliminarily preparing the mother alloy were the same furace as the

In premining prepand us mouse anyowassies to track. The remetting was carefully done: fast heating, short stage (30 seconds) in liquid state but at a not to high temperature (in order to avoid the most possible losing the benefit of the initial incoulation and spheroidization treatments of the liquid metal industrially done at the origin). Fast decrease in injected power for reprisolatification.



Microstructures of the xFe-(50-x)Fe cast irons




Microstructures of the xCo-(50-x)Fe cast irons

This is not the same case for the 50N50Fe cast iron in which one can see coarse graphile plates together with thin graphite lamellae. Several types of graphite are present in the 75N25Fe cats iron: degenerated spheroids, rather coarse plates and

extra-thirl ameliae. extra-thirl ameliae extra-thirl ameliae extra-thirl ameliae extra-thirl ameliae extra-thirl ameliae The initial graphite spheroids were also kept in the 250o75Fe and 500c50Fe cast inons. Contrariwise the 750o25Fe cast inon tools like the 75N25Fe one. The 25Fe75Fe and 50Fe50Fe cast inons seems being perfectly spheroidal graphite cast irons, but with an rather low apparent volume fraction of graphite. In contrast the 75Fe25Fe is totally different: dendrites and graphite present as very thir lameliae and small compact particles.

Responses of the microstructures to contact with Nital 4 (96% ethanol, 4%HNO₃)

The microstructures of the three xNi(1-x)Fe cast irons are not modified after 10 seconds of immersion in the Nital4 solution. This is not the case of the 25Co75Fe and 50Co50Fe cast alloys which display a "bull's eyes" microstructure as classical fertitic-pearitic SG cast irons. Only the most cobalt-alloyed cast iron (75Co25Fe) seems being only slightly etched. The 25Fe75Fe and 50Fe50Fe cast irons are significantly etched by Nital, with as result the appearance of the nature of the matrix: ledeburite (while austenite-cementite eutedic) together with grey dendrites (austenitic cat solidification, converted in pearlite during the cooling); this is a consequence of the rather fast cooling in the liquid state and thereafter in the solid state).



It appears thus possible to obtain, from parts of industrial SG cast iron, spheroidal graphite cast iron highly alloyed with nickel (at least until 25 wt.% Ni) and with cobalt (at least until 50 wt.%Co). following the procedure applied here. This was also observed (at least until 50% of SG industrial cast iron) with the reference xFe(1-x)Fe alloys were also produced in parallel in order to eventually distinguish a specific role of nickel or of cobalt, farer than the simple dilution of the origin nuclei for graphite (inoculation of the initial industrial cast iron). The corrosion properties, which now remain to extensively specify (Part 2 of this work [6]), were already partly observed here, not in an aqueous solution, but in contact with nitric acid diluted in ethanol. In this way these are the Ni-alloyed cast irons which appeared the most resistant (no visible attack after 10 seconds), followed by the cobalt-richest cast iron. This will be deeper investigated later, in acidic solutions, by long immersions and/or by using electrochemical techniques.

75Ni25Fe

- P61617 (full paper available in the Eurocorr 2016 CDROM)
- [1] [2] [3] Szekely, J., "Blast fumace technology, Science and Practice", Dekker (1972) Davis, J. R., "Cast irons", ASM International (1996).

- Durand-Charre, M., "Microstructures of steels and cast irons Engineering materials and processes", Springer-Verlag, Berlin Heidelberg New York (2004). Diallo, S., Berthod, P., Mater. Sci. Indian. J., 12 (2015) 77.
- Béranger, G., "Le livre de l'acier", Lavoisier, Paris Cachan (1994) [6]

50Ni50

100 µm

Meridja, K., Berthod, P., "Corrosion in acidic solution of SG cast irons highly alloyed with Ni or Co. Part 2: Electrochemical runs", poster, Eurocorr 2017, Prague

