



HAL
open science

Impact of a pressurised membrane: contact time

Loïc Tadrif, Baptiste Darbois Texier, François Lanzetta, Lounès Tadrif

► To cite this version:

Loïc Tadrif, Baptiste Darbois Texier, François Lanzetta, Lounès Tadrif. Impact of a pressurised membrane: contact time. *International Journal of Impact Engineering*, 2021, 156, pp.103963. 10.1016/j.ijimpeng.2021.103963 . hal-03294071

HAL Id: hal-03294071

<https://hal.science/hal-03294071>

Submitted on 21 Jul 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Impact of a pressurised membrane: contact time

Loïc Tadrisk^{a,*}, Baptiste Darbois Texier^b, François Lanzetta^c, Lounès Tadrisk^d

^a*Aix-Marseille Université, CNRS, ISM, Marseille, France*

^b*Université Paris-Saclay, CNRS, FAST, Orsay, France*

^c*Université de Franche-Comté, CNRS, FEMTO-ST, Belfort, France*

^d*Aix-Marseille Université, CNRS, IUSTI, Marseille, France*

Abstract

Pressurised membranes are used in various situations involving humans (protections, sports, etc). In this context, impacts mechanics of membranes is critical since under or over inflated membranes may create injuries. The effect of inflation pressure on contact time is investigated on a model experiment using a spherical membrane. Both gas pressure and impact speed decrease contact time. Direct measurements of gas pressure and temperature variations indicate an adiabatic compression in strong interaction with the membrane. The contact time of an inflated membrane is described by three dimensionless numbers, (i) the relative inflation \tilde{P} , (ii) the presso-elastic number P_E that considers the gas-membrane interaction and (iii) the presso-inertial number I_P that scales membrane inertia to pressure forces. A model of pressurised membrane impact is provided and compared with experiments. It shows that contact time depends mainly on I_P with corrections on P_E and \tilde{P} .

Keywords: pressurised membrane, impact, fluid-structure interaction, contact time

1. Introduction

Inflatable structures are used for their capabilities: easy storage and transport, fast deployment, reduced weight and adjustable mechanical properties. Notably, pressurised membranes are used in various situations involving impacts with human beings. Pressurised membranes are widely used in sports (football, basketball, handball, etc.) but may generate injuries by a single or repetitive impacts [1, 2]. Specifically in football, inflation pressure and impact speed have been shown

*loic.tadrisk@univ-amu.fr

PARAMETERS

P	Absolute inner pressure	
P_{atm}	Atmospheric pressure	986 kPa
ΔP	Pressure variations during impact	
V	Gas volume	
T	Inner gas temperature	
R	Membrane radius	
h	Release height	
U_0	Impact speed	
g	Gravity acceleration	
t	Time	
x	Indentation	
x_g	Membrane center of mass	
t_c	Contact time	

MEMBRANE PARAMETERS

R_0	Radius (deflated)	8.2 cm
m	Mass	179 g
E	Young modulus	4.2 MPa
e	Thickness	2 mm

DIMENSIONLESS NUMBERS

γ	Laplace coefficient	-
\tilde{P}	Reduced pressure	
P_E	Presso-elastic number	
I_P	Presso-Inertial number	

Table 1: Parameter and notations used in the paper. (\dot{x}) denotes the time derivative of x , index $_{\text{max}}$ denotes maximal value during impact.

18 to increase head accelerations during ball-to-head impacts [3]. In rare situations, gas expansion
19 is used to create impacts, for instance with a pneumatic jackhammer [4]. However, pressurised
20 membranes are most often used to milden impacts: running shoes equipped with heel air pockets
21 or foam (ensemble of small air pockets) protect from running impacts [5], inflatable bike helmet
22 [6] or car air-bag [7] protect from traumatic brain injuries (TBI). During an impact, the membrane
23 reaction force depends on inflation pressure which is, for instance, a major concern for airbag-
24 deployment and gas dosage as it may cause facial or eye injuries [8, 9]. The inertial forces created
25 by pressurised membranes are proportional to the typical acceleration U/t_c where U is the impact
26 speed and t_c the contact time. Short contact time occurs for high pressure membranes and may be
27 harmful. The relation between pressure, velocity and contact time is thus necessary to predict the
28 danger of an impact of a pressurised membrane.

29 Contact time has already been observed on various objects. Contact time of inelastic balls has
30 been investigated to understand granular material dynamics [10]. Impacting droplets were studied
31 in order to reduce contact time to avoid possible pinning and keep surfaces clean [11, 12]. Contact
32 time of soap bubbles has also been measured and modelled [13]. Pressurised membranes differ
33 from those system by having their mass in the membrane and gas as a spring.

34 The static deformation of pressurised structures have been studied on spherical and ellipsoidal
35 models [14, 15], and is due to the competition between pressure and bending forces. An elastic
36 shell deforms with an inverted cap instability [16], whereas the contact area of a pressurised mem-
37 brane remains flat [17]. The dynamics of a membrane is mainly driven by gas pressure, membrane
38 shape and bending rigidity[18–20]. During the impact, gas compression has been proposed to be
39 adiabatic [18] or isothermal [21]. However, it has never been measured directly. Measurements
40 of gas temperature, gas pressure and volume are performed simultaneously during the impact of a
41 pressurized membrane.

42 In the following, we chose a spherical membrane (*i.e.* without bending rigidity) as a model
43 experiment. The restoring force was only due to the combination of gas pressure and membrane
44 shape. Differently from [21] where pressure elevation was not taken into account and from [18]
45 where interaction between gas and membrane is not considered, we show that the main source
46 of non-linearity arises from the membrane-gas interaction during the impact. Although impacts

47 are usually characterised by contact time and coefficient of restitution, we mostly focused on the
48 contact time of the impact.

49 In this paper, we first report measurements of the impact properties of pressurised membrane
50 (contact time and coefficient of restitution) by systematically varying impact speed, inflation pres-
51 sure and gas nature. We also describe the observed kinematics of the membrane during the impact.
52 The second part of the paper is devoted to the gas dynamics during the impact and its strong in-
53 teraction with the membrane elasticity. In a third part, we propose a model of the impact of a
54 pressurised membrane. The impact time of a pressurised membrane is shown to be mainly de-
55 pendent on two dimensionless numbers, the presso-inertial number and the presso-elastic number.
56 A rationale is given for the dependency of the contact time with impact velocity arising from the
57 non-linear equations of contact and gas dynamics of the pressurized membrane.

58 **2. Impacts on pressurised membranes : Experiments**

59 An impact is characterised by the contact time t_c , and the coefficient of restitution $\eta = |U_{\text{out}}/U_0|$.
60 $\eta = 1$ corresponds to a lossless impact where the outgoing speed is equal to the ingoing speed.
61 We report here measurements of the impact properties of a pressurised membranes varying impact
62 speed U_0 , inflation pressure $P - P_{\text{atm}}$ and gas nature.

63 *2.1. Material and Methods*

64 Most studies of impacts on pressurized membranes have been carried out on sport balls [18,
65 21, 22] for application to sports but also for supply and cost reasons. Tests were carried out on a set
66 of 4 identical beach-volley balls (Decathlon KIPSTA™, BV100 fun). Those spherical membranes
67 were chosen to be a reference experimental model. They have a minimal composition, they are
68 formed of a single layer of rubber equipped with a valve for inflation, and they are soft enough
69 to expand when inflated at usual inflation pressures and thus to exhibit a strong coupling between
70 gas pressure and membrane elasticity. The membrane weighted $m = 179 \text{ g}$ and had a thickness
71 $e = 2.00 \pm 0.12 \text{ mm}$. The Young modulus of the membrane was measured on a traction bench,
72 $E = 4.22 \pm 0.10 \text{ MPa}$. The deflated membrane radius was $R_0 = 8.2 \pm 0.1 \text{ cm}$. All experiments

73 were performed in the elastic range of the membrane (inflation between 5 and 35 kPa). The main
74 membrane properties and notations are gathered in Table 1.

75 Membranes were inflated at four inflation pressures $P - P_{\text{atm}} = 0.1, 0.15, 0.25$ and 35 kPa and
76 their pressure cross checked with a precise manometer (MPX4250A, NXP). Three different gases
77 were used for inflation, (i) air (diatomic gas with Laplace coefficient $\gamma=7/5$), (ii) pure Helium and
78 (iii) pure Argon which are both monoatomic gases ($\gamma = 5/3$). The pressurised membranes were
79 released at heights (top of the membrane, $h + 2R$) 0.5, 0.75, 0.875, 1, 1.25, 1.35, 1.5, 1.75, 1.85 and
80 2 m with no velocity. The membranes impacted on a massive and non deformable marble stone,
81 figure 1. Impacts were recorded thanks to a high-speed camera (Photron Miro 110) at 5000 frames
82 per second.

83 Impact velocities recorded in the experiment varied from 1 to 6 m/s. Positions were determined
84 by tracking the circular shape on each frame using Matlab[®] 2015b algorithm. The algorithm works
85 as follows, (i) first the scale in pixels per mm is defined and an approximate membrane radius is
86 given after conversion in pixels. (ii) Second, the i^{th} image is loaded. (iii) Third, the membrane
87 location is found using *imfindcircle* Matlab[®] function based on the circular Hough transform. This
88 function outputs the radius and center of the circular shape of the pressurized spherical membrane.
89 (iv) Four, the ground position is detected automatically using the Hough transform for lines. Steps
90 (ii) to (iv) are repeated for all images of the high speed film. With this algorithm, the center of
91 the circle has been measured precisely even when the membrane was deformed, see figure 1b.
92 The algorithm results, ground position, the positions of the center of the circular shape of the
93 membrane and its radius, were post treated. Contact occurred when the distance between the
94 center of the circle and the marble is less than the membrane radius R . Consequently, contact
95 time t_c was defined precisely by fitting linearly the circle center-ground distance *vs* time before
96 and after impact. The absolute value of the slopes of those fits were used to determine the impact
97 speed U_0 and the outgoing speed U_{out} . From these measurements, the coefficient of restitution was
98 computed as $\eta = |U_{\text{out}}/U_0|$.




Figure 1: a. View of the experiment. The pressurised membrane is released without velocity from a height h . ① Flicker-free lighting. ② high speed camera. b. Definition of indentation x and membrane center of mass g during impact. Zoom on membrane oval distortion. c. Chrono-photography of an impact event ($h = 1.85$ m and $P - P_{\text{atm}} = 15$ kPa).




Figure 2: a. Contact time, t_c as a function of inflation pressure $P - P_{\text{atm}}$. Coloured lines are the non-dissipative model prediction for contact time, Eq. (15), for different impact speeds. The speed color map will be conserved for all the figures. Dashed line correspond to the linear model independent of impact speed U_0 . b. Coefficient of restitution η as a function of inflation pressure $P - P_{\text{atm}}$. Inflation gas: \blacklozenge Argon, \star Helium and \bullet Air.

99 2.2. Evolution of contact time as a function of inflation pressure, impact speed and gas nature

100 The contact time t_c is reported in figure 2a as a function of inflation pressure $P - P_{\text{atm}}$ for
 101 different impact velocities. Impact velocities are colour-coded using the color scale of figure 1a.
 102 Contact time decreases with inflation pressure for a fixed impact speed. The spreading of impact
 103 times at a fixed inflation pressure is reduced when inflation pressure is increased.

104 For information, the coefficient of restitution $\eta = |U_{\text{out}}/U_0|$ is plotted in figure 2b as a function
 105 of inflation pressure $P - P_{\text{atm}}$ for different impact velocities. The coefficient of restitution increases
 106 slightly with inflation pressure and decreases with impact speed.

107 2.3. Kinematics of an impact of a spherical pressurised membrane

108 During an impact onto the marble considered as a target of infinite mass and stiffness compared
 109 to the membrane, the spherical pressurised membrane may be described by the position of its
 110 center of mass x_g or the indentation x , see figure 1b. The shape of the membrane during the impact
 111 is an indented spherical cap [18], which radius may slightly increase during the impact. The part of
 112 the membrane in contact with the ground is flattened and no ripples are observed. The volume, V ,
 113 of a spherical cap and the flat area in contact with the ground, A , of a sphere of radius R indented

114 by a length x reads,

$$115 \quad V(x) = \frac{\pi}{3} (4R^3 + x^3 - 3Rx^2) \quad \text{and} \quad A(x) = 2\pi Rx \left(1 - \frac{x}{2R}\right). \quad (1)$$

116 The actual shape of the indented membrane differs from a pure sphere because of oval distortion,
117 see zoom in figure 1b. This effect is taken into account in our model applying a correction to the
118 actual surface in contact with the ground, $A_{\text{contact}} = \beta A$ with $\beta < 1$. The effect of oval distortion on
119 the volume of the spherical cap remains negligible.

120 The deformation of the ball moves its center of mass which is no longer located at the center of
121 the spherical shape, see figure 1b. When the ball gets in contact with the ground, $x = 0$ ($x_g = R$),
122 the ball is not yet deformed and both the center of mass and the center of the sphere are at the same
123 location. For larger and larger indentations the two centres separate one from another. Considering
124 an homogeneous mass distribution of the membrane, the position of the center of mass during the
125 contact reads

$$126 \quad x_g = R \left(1 - \frac{x}{2R}\right)^2. \quad (2)$$

127 **3. Gas-membrane interaction during an impact**

128 *3.1. Material and methods*

129 The behaviour of the gas and its interaction with the membrane during an impact has been
130 explored experimentally. In order to assess the hypothesis that the gas compression-expansion is
131 adiabatic, one has to show that the time scale of thermal exchanges is larger than the impact time
132 scale. To this aim, a first static compression experiment is performed to measure the characteristic
133 time of thermal leaks. Second, the gas dynamical behaviour is analysed during the impact to
134 understand how gas and membrane interact.

135 For both experiments, the membrane was punched with two holes of 5 mm of diameter. In each
136 hole, a home-made hermetic feedthrough was inserted. The two feedthroughs allowed to place a
137 micro-thermocouple and two pressure sensors inside the membrane simultaneously, see figure 3c.
138 The total mass of the feedthroughs and sensors was 6 g, much lower than the membrane mass of
139 179 g (3.2% of the total mass).




Figure 3: Instrumented membrane for gas pressure and temperature measurement. a. Building of a fast K-type thermocouple. b. Cross section of the membrane showing the insertion of the thermocouple in the hermetic feedthrough. Red arrow: thermocouple tip. Black star: membrane. c. Example of an instrumented mini-membrane (radius 57.5 mm) with two feedthroughs. One is devoted to temperature measurement (red arrow) with the micro-thermocouple tip inside the membrane and the other is devoted to the absolute and differential pressure measurements (white star) with the white arrow indicating that the pressure sensors are outside the membrane.

140 The first pressure sensor, sensor A, was an absolute pressure sensor (*Freescale semiconductor*
 141 *MPXAZ6115A*, probing with an accuracy of 3.45 kPa), used to measure the initial pressure inside
 142 the membrane. The second sensor, sensor B, was a differential sensor (*Freescale semiconduc-*
 143 *tor MPXV7007*) with accuracy of 500 Pa. This sensor was used to measure with accuracy the
 144 variations of pressure during impacts and static compression experiment. Differential pressure
 145 measurements were corrected by 1 ms, according to the sensor response time. Both sensors were
 146 linked to the same feedthrough. A manual valve allowed to set the reference of pressure for sensor
 147 B.

148 The indentation of the membrane was optically measured with a high-speed camera (*Photron*
 149 *MIRO 110*). The images were processed with a home-made Matlab[®] code similar to the one
 150 described in Section 2.1.

151 The temperature of the gas was recorded by a fast response type K thermocouple made by the
 152 welding of thin alumel and chromel wires (figure 3a,b). The welded hot junction is realised by a
 153 capacitance discharge device developed by the FEMTO-ST laboratory [23]. The thin wires were
 154 insulated from each other by a ceramic rod of diameter 0.8 mm. For the impact experiment, the
 155 use of extremely thin wires (7.6 μm in diameter) was required to get a sufficiently small thermal

156 inertia to respond to sudden changes of temperature. The thermocouple of $7.6\ \mu\text{m}$ wires had a
 157 time constant of $\approx 5\ \text{ms}$ in air (natural convection) [23]. Conversely such a small thermocouple is
 158 mechanically fragile. To avoid breakage, a K thermocouple with wires of $75\ \mu\text{m}$ in diameter was
 159 used for the static compression experiment (time constant of $\approx 1\ \text{s}$). The home-made thermocouple
 160 was placed in the gas close to the membrane, figure 3b. Temperature signals were filtered for
 161 frequency content larger than $500\ \text{Hz}$ and between 49.5 and $50.5\ \text{Hz}$.

162 Tension signals were converted in absolute temperature using the tabulated Seebeck coefficient
 163 [24]. Sensitivity of the type K thermocouple was $40\ \mu\text{V K}^{-1}$ at $293\ \text{K}$ leading to an uncertainty of
 164 $\pm 0.2\ \text{K}$ in our experiments. The main source of error was the noise due to antenna effect of the
 165 thermocouples.

166 All sensors were linked to a *NI instruments* dacq for acquiring the signal through a *Labview*
 167 interface. Data were acquired at $10^4\ \text{Hz}$. During impact experiments, the high-speed camera was
 168 synchronised with the other measurements (pressures and temperature) with a trigger signal.

169 3.2. Experimental results

170 The membrane has been statically compressed between two plans. The inner pressure rose
 171 quickly, figure 4a, and was maintained for more than $80\ \text{s}$ before being released. The rise of
 172 pressure induced an increase of the gas temperature, see figure 4b. The delay was due to the
 173 response time ($\approx 1\ \text{s}$) of the $75\ \mu\text{m}$ thermocouple. After reaching a maximum the temperature
 174 decreased following a damped exponential (straight line when plotted in lin-log scale, see inset).
 175 The characteristic time of decrease of temperature was $\tau_{\text{th}} = 13.5\ \text{s}$.

176 As the gas cooling is not uniform within the membrane, the characteristic time may depend
 177 on the position of the thermocouple relative to the membrane. The measured time $\tau_{\text{th}} = 13.5\ \text{s}$
 178 compares well with a characteristic diffusive time $\tau_{\text{th}} \sim l^2/D \approx 5\ \text{s}$ where $l = 1\ \text{cm}$ is the distance of
 179 the thermocouple to the membrane and $D = 20 \times 10^{-6}\ \text{m}^2\ \text{s}^{-1}$ is the thermal diffusion coefficient in
 180 air. To get rid off this effect, one can compute an upper bound for thermal transfer by conduction,
 181 considering that the gas cools down to the membrane temperature over a thickness $\sqrt{Dt_c}$

$$182 \quad \frac{\delta\mathcal{E}_{\text{th}}}{\mathcal{E}_{\text{th}}} = \frac{3\sqrt{Dt_c}}{R}. \quad (3)$$




Figure 4: Simultaneous evolution of a. gas pressure variations ΔP and b. temperature variations ΔT for a long (>80 s) compression-expansion cycle. (inset) lin-log graph of the gas temperature decrease showing the typical time $\tau_{th} = 13.5$ s.




Figure 5: Simultaneous measurements of temperature variations ΔT , pressure variations ΔP and indentation x (for impact conditions $P = 15.5 \text{ kPa}$ and $U_0 \approx 6 \text{ m s}^{-1}$). Temperature sensor responds to temperature variations with a delay and has a moderate noise level.

183 Using typical values, $D = 20 \times 10^{-6} \text{ m}^2 \text{ s}^{-1}$, $t_c = 10 \text{ ms}$ and $R = 10 \text{ cm}$, one obtains $\delta\mathcal{E}_{\text{th}}/\mathcal{E}_{\text{th}} \approx 1.3\%$.

184 The adiabatic hypothesis is well verified.

185 The temperature variations, pressure variations and indentation were measured simultaneously
 186 for impacts at different heights h . A typical measurement is shown in Figure 5. The pressure and
 187 indentation evolved simultaneously due to the fast response of the sensors. Differently, the tem-
 188 perature only increased after a delay of $\approx 5 \text{ ms}$ corresponding to the response time of the $7.6 \mu\text{m}$
 189 thermocouple used in the experiment. The temperature increase shows that even for small inden-
 190 tation, gas compression is not isothermal and that gas temperature rises by few Kelvins.

191 *3.3. Model of evolution of pressure during an impact*

192 The pressurised membrane was released at different heights $0.5 \text{ m} < h < 1.85 \text{ m}$. The impact
 193 speed was much lower than sound velocity ($U_0 \ll 340 \text{ m s}^{-1}$), it thus remained under the hypothesis
 194 of quasi-static compression. As shown previously, the gas compression was also adiabatic, it can
 195 be modelled by the Laplace relation,

$$196 \quad \frac{\Delta P}{\Delta V} = -\gamma \frac{P}{V}, \quad (4)$$

197 where γ is the Laplace coefficient. $\gamma = 5/3$ for monoatomic gases, $7/5$ for diatomic gases and
 198 $\gamma \rightarrow 1$ for polyatomic gases. During the impact, the membrane is an indented sphere which radius
 199 slightly increases because of pressure. The increase of radius of a thin elastic sphere reads [25],

$$200 \quad R = R_0 + \frac{(P - P_{\text{atm}})R_0^2}{2eE}. \quad (5)$$

201 The dependence between membrane radius and inflation pressure is shown in figure 5a and fitted
 202 with $E = 4.2 \text{ MPa}$ and $e = 2 \text{ mm}$ to determine $R_0 = 8.2 \text{ cm}$. In the limit of small indentations $x \ll R$,
 203 one may linearise the membrane indented volume Eq (1), and the two above relations, Eqs. (4)
 204 and (5) to find the relation between gas pressure and indentation,

$$205 \quad \frac{\Delta P}{P} = \frac{\gamma}{1 + (2 + 3\gamma)P_E + (1 + 3\gamma)P_E^2} \left(\frac{x}{R_0} \right)^2 \quad \text{with} \quad P_E = \frac{PR_0}{2Ee}. \quad (6)$$

206 P_E is the presso-elastic number which scales the inflation pressure to the elasticity of the mem-
 207 brane. For $P_E \ll 1$, the membrane is rigid and the increase of radius is negligible. In the contrary
 208 if $P_E \gg 1$, the membrane is flexible, the membrane radius increases and pressure variations are
 209 reduced. In the case of the membrane studied experimentally P_E is in the medium range with
 210 $P_E \simeq 0.56$ (using values in Table 1). The relation between pressure and indentation is plotted in
 211 Figure 5b for all impact experiments ($0.5 \text{ m} < h < 1.85 \text{ m}$), and compares well with the theory with-
 212 out fitting parameters. In the inset, the compression-expansion cycle is shown to occur without
 213 hysteresis.




Figure 6: a. Membrane radius vs Inflation pressure. Colours correspond to impact speed following colour map of figure 1. Black line corresponds to Eq. (5) with $E = 4.2$ MPa, $e = 2$ mm and $R_0 = 8.2$ cm. b. Example of normalised pressure vs. normalised indentation squared for an impact from height $h=0.5$ m. Black line corresponds to Eq. (5) with $P_E = 0.56$ and $\gamma = 7/5$ ($P = 114$ kPa, $E = 4.2$ MPa, $e = 2$ mm and $R_0 = 8.2$ cm).

214 4. Effect of gas nature and pressure on contact time

215 4.1. Conservation of momentum

216 In the chosen parametrisation, we compute the acceleration of the center of mass as a function
 217 of x by double differentiation of Eq. (2),

$$218 \quad \ddot{x}_g = -\left(1 - \frac{x}{2R}\right)\ddot{x} + \frac{\dot{x}^2}{2R}. \quad (7)$$

219 The right-hand-side of this equation is compounded of two terms: the first one corresponds to the
 220 variation of momentum due to the acceleration of the mass of the membrane that is not in con-
 221 tact with the ground, $m(1 - x/2R)$. The second term corresponds to the variation of momentum
 222 associated to the membrane mass that actually reaches the ground during a given time interval,
 223 $m\dot{x}/2R$, which velocity drops from \dot{x} to zero. When the membrane is not much squashed on the
 224 ground, $x \ll R$, the second term is much lower than the first one and the acceleration of the center
 225 of mass simply reduces to $\ddot{x}_g = -\ddot{x}(1 - x/2R)$.

226 The force exerted by the membrane onto the ground is the inner pressure, $P + \Delta P(x) - P_{\text{atm}}$
 227 times the surface of contact, A . Conservation of momentum reads,

$$228 \quad m\ddot{x}_g = \beta A(x)(P + \Delta P - P_{\text{atm}}), \quad (8)$$

229 where $\beta \simeq 1/2$ is the fraction of the flattened membrane in contact with the marble, see figure 1b.

230 Under the hypothesis of small indentation $\dot{x}^2/2R \ll \ddot{x}$, one obtains

$$231 \quad -m\ddot{x} = 2\beta\pi R x (P - P_{\text{atm}}) \left(1 + \frac{\Delta P}{P - P_{\text{atm}}} \right). \quad (9)$$

232 The variation of radius due to the increase of pressure is negligible compared to the variation of
233 inner pressure during the impact as $\Delta R/R = R_0 P_E \Delta P / P R < \Delta P / P \ll \Delta P / (P - P_{\text{atm}})$. The quantity

234 $\Delta P / (P - P_{\text{atm}})$ which corresponds to the relative increase of pressure during the impact is thus the
235 main source of force non-linearity in Eq (9). In the following, we neglect variations of membrane

236 radius R . At this step, we define the dimensionless variables $\tilde{x} = x/R$, $\tilde{t} = tU_0/R$ and make Eq.(9)

237 dimensionless. We obtain the presso-inertial number $I_p = mU_0^2/2\beta\pi R^3(P - P_{\text{atm}})$ and the reduced

238 pressure $\tilde{P} = (P - P_{\text{atm}})/P$. For convenience, we note $B = \gamma(1 + P_E^2)/(1 + (2 + 3\gamma)P_E + (1 + 3\gamma)P_E^2)$.

239 Combining Eq. (9) and (6), one finds the dimensionless equation of evolution of the indentation,

$$240 \quad \ddot{\tilde{x}} = -\frac{\tilde{x}}{I_p} - \frac{B\tilde{x}^3}{I_p\tilde{P}}. \quad (10)$$

241 With the initial condition at $\tilde{t} = 0$, $\tilde{x} = 0$ and $\dot{\tilde{x}} = 1$, the first integral of Eq. (9) reads

$$242 \quad \dot{\tilde{x}} = \pm \sqrt{1 - \frac{1}{I_p} \left(\tilde{x}^2 + \frac{B}{2\tilde{P}} \tilde{x}^4 \right)}. \quad (11)$$

243 4.2. Pressure, temperature and indentation maxima

244 The maximal indentation occurs when $\dot{\tilde{x}} = 0$. There exists a single physical solution that reads

$$245 \quad \frac{x_{\text{max}}}{R} = \sqrt{\frac{\tilde{P}}{B} \left(\sqrt{1 + \frac{2BI_p}{\tilde{P}}} - 1 \right)^{1/2}}. \quad (12)$$

246 Under the hypothesis of slow impact $I_p \ll 1$, one gets

$$247 \quad \frac{x_{\text{max}}}{R} = \sqrt{I_p} \left(1 - \frac{BI_p}{4\tilde{P}} \right) + o(I_p^{3/2}). \quad (13)$$

248 Consequently, one finds the maximum of pressure and temperature elevations

$$249 \quad \frac{\Delta P_{\text{max}}}{P} = B \left(\frac{x_{\text{max}}}{R} \right)^2 \quad \text{and} \quad \frac{\Delta T_{\text{max}}}{T} = \frac{(\gamma - 1) \Delta P_{\text{max}}}{\gamma P}. \quad (14)$$

250 The comparison of the predicted maxima to the experimental values is shown in Figure 7. The

251 model predicts the right order of magnitude and tendency for indentation, pressure and tempera-

252 ture.




Figure 7: Maximal values of a. indentation x , b. pressure variation ΔP and c. temperature variation ΔT , with release height of the membrane. Dashed lines correspond to the exact model prediction, Eq. (12) and (14) using $\gamma = 7/5$, $P = 114$ kPa, $T = 293.15$ K and membrane characteristics given in Table 1. Light grey lines correspond to the approximated predictions, Eq. (13) and (14) with the same set of parameters.




Figure 8: Comparison of contact time prediction and measurement for trial at $P - P_{\text{atm}} = 10 \text{ kPa}$. Black line: model prediction Eq.(15).

253 Since dissipation is not taken into account in this model, the contact time is twice the time
 254 needed to get to the maximal indentation,

$$255 \quad t_c = \frac{2R}{U_0} \int_0^{\tilde{x}_{\text{max}}} \frac{d\tilde{x}}{\sqrt{1 - \frac{1}{I_P} \left(\tilde{x}^2 + \frac{B}{2\bar{P}} \tilde{x}^4 \right)}} = \frac{2R}{U_0} \sqrt{\frac{2I_P}{\sqrt{1 + \frac{2BI_P}{\bar{P}} + 1}}} \mathbf{K} \left(\frac{\sqrt{1 + \frac{2BI_P}{\bar{P}} - 1}}{\sqrt{1 + \frac{2BI_P}{\bar{P}} + 1}} \right). \quad (15)$$

256 where \mathbf{K} is the first complete elliptic integral. We plot t_c for various inflation pressure and velocities
 257 in Figure 2a. The model is in good agreement with the data trends. A discrepancy between model
 258 and data exists when comparing the magnitude of the contact time, figure 8. This discrepancy
 259 comes from the term in \dot{x}^2 in Eq 7 that increases the contact time and from ball oval distortion.

260 5. Discussion

261 The model developed for the dynamics of a pressurised membrane impacting a rigid surface
 262 relies on several assumptions which should be discussed. First, we assumed that no energy was
 263 dissipated during the impact (neither sound emission [22], vibrations nor visco-elasticity dissipa-
 264 tion [21, 26]), that leads to overestimate the maximal indentation x_{max} and to underestimate the
 265 contact time t_c . This point will be addressed in a future study on coefficient of restitution, however
 266 it is thought to have little effect on the contact time t_c . Indeed, using a linear damped oscillator
 267 model, one may estimate the lost energy as $2m\xi U_0^2$ where ξ is the reduced damping coefficient.
 268 This compares to the lost energy during the impact $(1 - \eta^2)mU_0^2/2$. One finds $\xi \simeq (1 - \eta^2)/4$.

269 The reduced damping coefficient changes the contact time as $t_{c,\text{damp}} = t_c / \sqrt{1 - \xi^2}$. For $\eta = 0.9$,
270 $(t_{c,\text{damp}} - t_c) / t_c \simeq 10^{-3}$.

271 Second, we made the hypothesis of small indentations of the membrane ($x/R \ll 1$) and con-
272 sequently neglected the term $\dot{x}^2/2R$ in equation (7), this may induce an underestimation of the
273 contact time. This term do not involve any loss of energy. Finally, we have accounted for oval
274 distortion that arise because of membrane inertia through a simple corrective factor β . This is a
275 raw assumption and taking into account the deformation of the ball due to inertia would be the next
276 step of this theory. The quasi-static assumption is quite well verified in the limit of slow impact
277 but may not be exact for impact at large velocities (approaching sound velocity or wave velocity
278 in the membrane), possibly changing the physics of the impact.

279 Under these assumptions, we showed that the impact of a pressurised membrane is ruled by
280 four dimensionless numbers. (i) \tilde{P} is the normalised overpressure inside the membrane; (ii) the
281 presso-elastic number P_E compares the inflation pressure with the membrane elasticity; (iii) I_P
282 scales the initial kinetic energy with the work of the inner gas compression during the contact;
283 finally, (iv) γ is the Laplace coefficient that depends on gas nature. The first three parameters
284 have a major influence of the contact dynamics. In the contrary, γ is bounded between $5/3$ for the
285 adiabatic compression of a mono-atomic gas and 1 for an isothermal compression. In this range
286 of variations (40%) it has only little influence on the contact time. The physical properties of the
287 inflation gas (mono-atomic, polyatomic, etc. . .) only change marginally the bouncing dynamics of
288 the membrane. Differently, the increase of the inner pressure implies an increase of \tilde{P} and P_E and
289 provokes a reduction of the maximal indentation and of the contact time. When the impact speed
290 is increased keeping the overpressure \tilde{P} constant, I_P becomes larger and induces a larger maximal
291 indentation and a shorter contact time.

292 In order to compare the model predictions with experiments, we characterised the impact dy-
293 namics of a model pressurised membrane onto a rigid substrate for different inflation pressures and
294 impacting speeds. These experiments lied on the range of parameters where $P_E < 1$ and $I_P < 1$,
295 corresponding to small membrane elasticity and slow impacts. The good agreement between these
296 observations and model predictions justify the approximations discussed previously. One perspec-
297 tive of this work would be to change the properties of the membrane in order to explore the limit

298 where the non-dimensional numbers P_E and I_P are larger than unity and verify model predictions
299 in this limit.

300 This model of contact time of pressurised membranes allows to discuss the properties of in-
301 flated protections and sport balls. Biological damages are difficult to relate to a unique impact
302 property as, for instance, traumatic brain injuries causes and criteria are numerous and complex
303 [27]. Nevertheless, biological damages are somehow dependent of the maximum force level. In
304 the case of a free pressurised membrane the maximum force is related to the contact duration as
305 $F_{\max} \sim mU/t_c$. Increasing contact time by decreasing inflation pressure or by choosing softer
306 membrane may thus allow to reduce impact injuries. This should help to design safer sports balls
307 [3].

308 In this paper, we considered an ideal target of infinite mass and stiffness. This may represent
309 quite well the impact of a pressurised sport ball on a hard ground such concrete or wooden floor
310 that may be encountered in basketball or handball. Differently, for outdoor sports such as football
311 or rugby, the field is soft enough to be deformed elastically or plastically by the ball during the
312 impact, changing the properties of impact [28, 29]. This remark stands also for impact of pres-
313 surized balls or pressurised protections on humans which soft tissues (skin, muscles, etc.) may
314 deform under impact. To take into account the mass of the target one has to consider the relative
315 velocities in the frame of the center of mass. Compared to the case of infinite target mass $m_t \rightarrow \infty$,
316 the amount of momentum exchanged during the impact is reduced by a factor $m_i/(m_i + m_t)$ where
317 m_i is the mass of the impactor. Regarding the stiffness, the springs of the target k_t and impactor
318 k_i are in series what decreases the total stiffness of the system $k_i k_t / (k_i + k_t)$ and increases contact
319 time consequently. Thus taking into account a real target decreases the amount of momentum
320 exchanged and increases contact time. The case of an impact on an ideal target represents thus an
321 upper limit for inertial forces.

322 Regarding sports, it is unlikely that increasing contact time may increase precision since human
323 response time is much larger than ball contact time. Differently, longer contact time may favour
324 handling and control of the ball since it mostly relies on motion coordination rather than reflex.
325 This explain why ball deflation has been used to cheat in American football where each team
326 uses its own ball, [30]. Questions also arise for the level of trajectory modification following the

327 impact of a spinning ball depending on its inflation pressure since it will increase indentation,
328 contact surface and contact time.

329 **6. Conclusion**

330 We have shown that the contact dynamics of a pressurised membrane is made non-linear by
331 the increase of the internal pressure resulting from the adiabatic compression of the gas. We have
332 proposed a non-linear model that rationalizes the dependency of the contact time with the inflation
333 pressure and the impacting speed. In addition, this model predicts a small effect of the gas nature,
334 a fact that is observed in practice. Our model implies that the contact force F depends on the
335 indentation x in a supra-linear way: $F \propto \tilde{x} + B\tilde{x}^3/\tilde{P}$. The bouncing dynamics of a pressurised
336 membrane strongly differs from the Hertzian law $F \propto x^{3/2}$ which rules the impact of filled spheres
337 made of elastic materials. It is also different from the linear law for shells before buckling $F \propto x$
338 if $x < e$ and the sub-linear law for shells after buckling $F \propto x^{1/2}$ for $x > e$ [31]. It would be
339 interesting to study the implications of such differences in sports where these distinct types of
340 balls are employed.

341 **Acknowledgement**

342 The authors thanks Stéphane Méo and Marie-Pierre Deffargues for their welcome at CERMEL
343 lab and use of the traction bench. The authors thanks Laurent Aprin and Tristan Gilet for the loan
344 of high-speed cameras. Authors thanks Tristan Gilet, Christophe Clanet, Caroline Cohen, Aisha
345 Medina, Jean-Marc Linares, Santiago Arroyave-Tobòn and Julien Chaves-Jacob for valuable help
346 and/or discussions.

347 **References**

- 348 [1] J. Heald, D. Pass, Ball standards relevant to risk of head injury, in: Head and neck injuries in sports, ASTM
349 International, 1994.
- 350 [2] B. C. Buckhout, M. A. Warner, Digital perfusion of handball players: effects of repeated ball impact on structures
351 of the hand, The American journal of sports medicine 8 (1980) 206–207.

- 352 [3] N. J. Cecchi, D. C. Monroe, W. X. Moscoso, J. W. Hicks, D. J. Reinkensmeyer, Effects of soccer ball inflation
353 pressure and velocity on peak linear and rotational accelerations of ball-to-head impacts, *Sports Engineering* 23
354 (2020) 1–6.
- 355 [4] S. Pang, W. Goldsmith, A model of a pneumatic jackhammer system, *Rock mechanics and rock engineering* 25
356 (1992) 49–61.
- 357 [5] N. Mills, Running shoe materials, *Materials in sports equipment* 1 (2003) 65.
- 358 [6] M. Kurt, K. Laksari, C. Kuo, G. A. Grant, D. B. Camarillo, Modeling and optimization of airbag helmets for
359 preventing head injuries in bicycling, *Annals of biomedical engineering* 45 (2017) 1148–1160.
- 360 [7] H. Zhou, Z. Zhong, M. Hu, Design and occupant-protection performance analysis of a new tubular driver airbag,
361 *Engineering* 4 (2018) 291–297.
- 362 [8] A. H. ye, Are airbags a dangerous safety measure? a meta-analysis of the effects of frontal airbags on driver fa-
363 talities, *Accident Analysis & Prevention* 42 (2010) 2030 – 2040. doi:<https://doi.org/10.1016/j.aap.2010.06.014>.
- 364 [9] T. Koisaari, T. Leivo, A. Sahraravand, A.-K. Haavisto, P. Sulander, T. M. Tervo, Airbag deployment–related eye
365 injuries, *Traffic injury prevention* 18 (2017) 493–499.
- 366 [10] E. Falcon, C. Laroche, S. Fauve, C. Coste, Behavior of one inelastic ball bouncing repeatedly off the ground,
367 *The European Physical Journal B-Condensed Matter and Complex Systems* 3 (1998) 45–57.
- 368 [11] J. C. Bird, R. Dhiman, H.-M. Kwon, K. K. Varanasi, Reducing the contact time of a bouncing drop, *Nature* 503
369 (2013) 385–388.
- 370 [12] D. Richard, C. Clanet, D. Quéré, Contact time of a bouncing drop, *Nature* 417 (2002) 811–811.
- 371 [13] F. Vincent, A. Le Goff, G. Lagubeau, D. Quéré, Bouncing bubbles, *Journal of Adhesion* 83 (2007) 897–906.
- 372 [14] A. Lazarus, H. Florijn, P. M. Reis, Geometry-induced rigidity in nonspherical pressurized elastic shells, *Physical*
373 *review letters* 109 (2012) 144301.
- 374 [15] D. Vella, A. Ajdari, A. Vaziri, A. Boudaoud, The indentation of pressurized elastic shells: from polymeric
375 capsules to yeast cells, *Journal of the Royal Society Interface* 9 (2012) 448–455.
- 376 [16] L. Pauchard, S. Rica, Contact and compression of elastic spherical shells: the physics of a ping-pong ball,
377 *Philosophical Magazine B* 78 (1998) 225–233.
- 378 [17] M. Hubbard, W. J. Stronge, Bounce of hollow balls on flat surfaces, *Sports Engineering* 4 (2001) 49–61.
- 379 [18] W. Stronge, A. Ashcroft, Oblique impact of inflated balls at large deflections, *International journal of impact*
380 *engineering* 34 (2007) 1003–1019.
- 381 [19] R. Cross, Dynamic properties of tennis balls, *Sports Engineering* 2 (1999) 23–34.
- 382 [20] R. Cross, Impact behavior of hollow balls, *American Journal of Physics* 82 (2014) 189–195.
- 383 [21] A. Georgallas, G. Landry, The coefficient of restitution of pressurized balls: a mechanistic model, *Canadian*
384 *Journal of Physics* 94 (2015) 42–46.
- 385 [22] J. Katz, Thump, ring: the sound of a bouncing ball, *European journal of physics* 31 (2010) 849.

- 386 [23] F. Lanzetta, E. Gavignet, Temperature measurements: Thermoelectricity and microthermocouples, *Thermal*
387 *Measurements and Inverse Techniques* (2011) 95.
- 388 [24] E. Rathakrishnan, *Instrumentation, measurements, and experiments in fluids*, CRC Press, 2007.
- 389 [25] J. Sigüenza, S. Mendez, D. Ambard, F. Dubois, F. Jourdan, R. Mozul, F. Nicoud, Validation of an immersed
390 thick boundary method for simulating fluid–structure interactions of deformable membranes, *Journal of Com-*
391 *putational Physics* 322 (2016) 723–746.
- 392 [26] A. Ashcroft, W. Stronge, Dynamic dissipation during bounce of tennis balls, *The Engineering of Sport* 1 (2004)
393 386–392.
- 394 [27] J. Antona-Makoshi, *Traumatic brain injuries: animal experiments and numerical simulations to support the*
395 *development of a brain injury criterion*, Chalmers University of Technology Gothenburg, Sweden, 2016.
- 396 [28] M. Ali, J. Sun, N. Lam, L. Zhang, E. Gad, Simple hand calculation method for estimating deflection generated
397 by the low velocity impact of a solid object, *Australian Journal of Structural Engineering* 15 (2014) 243–259.
- 398 [29] Y. Yang, N. Lam, L. Zhang, Estimation of response of plate structure subject to low velocity impact by a solid
399 object, *International Journal of Structural Stability and Dynamics* 12 (2012) 1250053.
- 400 [30] K. A. Hassett, J. W. Sullivan, S. Veuger, Football under pressure: Assessing malfeasance in deflategate, *Journal*
401 *of Sports Analytics* 1 (2015) 103–110.
- 402 [31] B. Audoly, Y. Pomeau, *Elasticity and geometry: from hair curls to the non-linear response of shells*, Oxford
403 university press, 2010.