



Multi-level agent-based modeling - A literature survey

Gildas Morvan

► To cite this version:

| Gildas Morvan. Multi-level agent-based modeling - A literature survey. 2013. hal-03331933

HAL Id: hal-03331933

<https://hal.science/hal-03331933>

Preprint submitted on 2 Sep 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Multi-level agent-based modeling

A literature survey

Gildas Morvan

<http://www.lgi2a.univ-artois.fr/~morvan/>
gildas.morvan@univ-artois.fr

Univ Lille Nord de France, F-59000 Lille, France
UArtois, LGI2A, F-62400, Béthune, France



November 18, 2013

Abstract

During last decade, multi-level agent-based modeling has received significant and dramatically increasing interest. In this article we conduct a comprehensive and structured review of literature on this emerging research domain that aims at extending the classical agent-based modeling paradigm to overcome some of its limitations. We present the main theoretical contributions and applications with an emphasis on social, flow, biological and biomedical models.

Main acronyms used in this paper

ABM According to the context, Agent-Based Model or Agent-Based Modeling

DEVS Discrete Event System Specification

EBM Equation-Based Model

ML-ABM According to the context, Multi-Level Agent-Based Model or Multi-Level Agent-Based Modeling

Contents

1	Introduction	3
1.1	Agent-based modeling	3
1.2	Multi-level agent-based modeling	3
1.3	Terminology issues	4
1.4	Bibliography	5
2	Theoretical issues	6
2.1	Meta-models, simulation engines and platforms	6
2.2	Observation, detection and agentification of emergent phenomena	8
2.3	Representation of aggregated entities	9
3	Application domains	10
3.1	Social simulation	11
3.2	Flow modeling	12
3.3	Biological and biomedical models	14
3.4	Ecology	16
4	Discussion	18
4.1	Level integration	18
4.2	Multi-level technical tools	19
5	Conclusion	20
	References	20

I Introduction

I.1 Agent-based modeling

Agent-based modeling (ABM) is a computational modeling paradigm that allow to simulate the interactions of autonomous agents in an environment. It has been widely used to study complex systems in various domains (Epstein, 2006; Ferber, 1999; Gilbert, 2007; Railsback and Grimm, 2011; Resnick, 1994; Treuil et al., 2008).

However, it suffers from important known limitations that reduce its scope (Drogoul et al., 2003; Scerri et al., 2010). First, ABM is purely bottom-up: a microscopic knowledge, *i.e.*, related to system components, is used to construct models while a macroscopic knowledge, *i.e.*, related to global system properties, is used to validate models. Therefore, it is not straightforward to explicitly introduce bidirectional relations between these two points of view in the general case. It becomes even harder when different spatial or temporal scales or domains of interest are involved in a same simulation. Moreover, agent-based models do not scale easily and generally require large computational resources since many agents are simulated. Finally, most agent-based simulation platforms lack tools to reify complex singular emergent properties: human observation often remains the most efficient way to capture multi-level pattern formation or crowd behavior.

I.2 Multi-level agent-based modeling

I.2.1 Definitions

The works surveyed in this paper aim at extending the classical ABM paradigm to overcome these limitations. While they can be very different (in terms of goals, technical approaches or application domains), these works share a common idea: introducing more levels of description in agent-based models. Therefore, we group them under a common term: Multi-Level Agent-based Modeling (ML-ABM). In the following we propose definitions of the concepts of level and multi-level agent-based model that seem broad enough to encompass the different surveyed approaches (see section 1.3).

Definition 1 *A level is a point of view on a system, integrated in a model as a specific abstraction.*

The name refers to the familiar expressions levels of organization, observation, analysis, etc.

Definition 2 *A multi-level agent-based model integrates heterogenous (agent-based) models, representing complementary points of view, so called levels, of the same system.*

In this definition, three concepts are highlighted and should themselves be defined formally.

Definition 3 *Integration means that the ABMs within a ML-ABM can interact and share entities such as environments and agents.*

Definition 4 *Heterogeneity means that the ABMs integrated in a ML-ABM can be based on different modeling paradigms (differential equations, cellular automata, etc.), use different time representation (discrete events, step-wise) and represent processes at different spatio-temporal scales.*

Definition 5 *Points of view are complementary for a given problem since they can not be taken in isolation to address it.*

This idea is very important in the literature on complex systems (Morin, 1992). Indeed, as Müller and Aubert (2011) note, "the global behavior of a complex system cannot be understood without letting a set of points of view interact".

1.2.2 Types of problems solved using multi-level agent-based approaches

ML-ABM is mainly used to solve three types of *modeling* problems:

- the modeling of **cross-level interactions**, *e.g.*, an explicit top-down feedback control,
- the **coupling of heterogeneous models**,
- the **(dynamic) adaptation of the level of detail** of simulations, *e.g.*, to save computational resources or use the best available model in a given context.

In the first case, the different points of view always co-exist, as they integrate interdependent models, while in the last ones, levels are (de)activated at run-time according to the context, as they represent independent models designed for specific situations.

For instance, in flow hybrid models areas with simple topologies are handled with an equation-based model (EBM) while others are handled with an ABM.

1.3 Terminology issues

Different terms have been used to describe what we call here a level: *e.g.*, perspective, interaction, layer or view (Desmeulles et al., 2009; Parunak et al., 2009; Torii et al., 2005; White, 2007). Some are domain-specific; thus, in the flow modeling domain, when two levels with static relations are considered, models are often described as *hybrid* as shown in the section 3.2 (Burghout et al., 2005; El hmam et al., 2008, 2006a,b,c; Marino et al., 2011; Mathieu et al., 2007a; Nguyen et al., 2012b; Rejniak and Anderson, 2011; Wakeland et al., 2007).

The term multi-scale — or multi-resolution (Jeschke and Uhrmacher, 2008; Zhang et al., 2009a, 2011) — is often used but has a more restrictive meaning as it focuses on the spatial and temporal extents of levels and not on their interactions and organization. Gil-Quijano et al. (2012, p. 622–623) pointed that the term multi-scale can be misleading and advocated for using multi-level instead. Let take as an example the *Simpop3* model, described by their authors as multi-scale (Pumain and Louail, 2009). Two levels are considered: the *city level*, representing the internal dynamics of a city, and the *system of cities level*, representing the interactions between cities. However, the idea of scale does not fit to describe the relation between them: one can easily figure a city bigger (in terms of population, spatial extent, economic exchanges, etc.) than a system of cities. In contrast, the idea of levels of organization in interaction seems more appropriate. Furthermore, to extend the definitions 1 and 2 such models could be more precisely denoted as nested or hierarchical multi-level agent-based models.

1.4 Bibliography

During last decade, ML-ABM has received significant and dramatically increasing interest (fig. 1). In this article we present a comprehensive and structured review of literature on the subject¹.

Another survey on the subject has been previously conducted by Gil-Quijano et al. and published in different versions². While the present article aims at providing an overview of the literature, Gil-Quijano et al. performed a comparative study of three models (Gil-Quijano et al., 2008; Lepagnot and Hutzler, 2009) and (Pumain and Louail, 2009). A similar survey, comparing four models, can be found in Vo (2012, p. 28–34).




Figure 1: Bibliographical statistics on ML-ABM computed from author’s bibliographic database and google scholar data on the Nov. 15, 2013

The paper is structured as follows. Section 2 introduces the main theoretical contributions and section 3 presents the different application domains of ML-ABM, with an emphasis on social, flow, biological and biomedical models. In section 4, some issues about ML-ABM are discussed. Finally, the remaining sections conclude

¹The bibliographic database is available at the following URL: http://www.lgi2a.univ-artois.fr/~morvan/Gildas_Morvan/ML-ABM_files/mlbib.bib.

²This work was first published in french (Gil-Quijano et al., 2009), then extended (Gil-Quijano et al., 2010), (Louail, 2010, p. 185–204) and finally translated into english (Gil-Quijano et al., 2012)

this paper by an analysis of the benefits, drawbacks and current limitations of the existing approaches.

2 Theoretical issues

In the surveyed literature, three main theoretical issues have been addressed so far:

- the definition and implementation of meta-models and simulation engines,
- the detection and reification of emergent phenomena,
- and the definition of generic representations for aggregated entities.

They are described in the following sections.

2.1 Meta-models, simulation engines and platforms

Many meta-models and simulation engines dedicated to ML-ABM have been proposed in the literature. They are briefly presented in the following, in a chronological order.

Approaches based on DEVS have also been included (Zeigler et al., 2000). Indeed, DEVS, as a generic event-based simulation framework, has been extended to support ABM (Duboz, 2004; Duboz et al., 2003; Müller, 2009). A comprehensive survey of the literature on multi-level DEVS extensions can be found in Duhail (2013).

GEAMAS (Marcenac et al., 1998a,b; Marcenac and Giroux, 1998) (GEneric Architecture for MultiAgent Simulation) is a pioneering ML-ABM framework integrating three levels of description (micro, meso, macro). Micro and macro levels represent respectively agent and system points of view while the meso (or middle) level represents an aggregation of agents in a specific context. Communication between levels is asynchronous. **GEAMAS-NG** is a newer version of the framework providing tools to detect and reify emergent phenomena (David et al., 2011).

tMans³ (Scheutz et al., 2005) is a multi-scale agent-based meta-model and platform. Unfortunately, the project seems to have died in the bud.

ML-DEVS (Steiniger et al., 2012; Uhrmacher et al., 2007) is an extension of DEVS that allows the simulation of multi-scale models (and not only coupled models in which the behavior of a model is determined by the behaviors of its sub-models). Two types of relation between levels are defined: *information propagation* and *event activation*. However, ML-DEVS focuses on multi-scale modeling and therefore, only supports pure hierarchies of models: *interaction graphs* are viewed as *trees* (Maus et al., 2008).

CRIO (Gaud, 2007; Gaud et al., 2008a,b) (Capacity Role Interaction Organization) is an organizational meta-model dedicated to ML-ABM based on the concept of holon (Koestler, 1967, 1978). It has been used to develop multi-scale simulations of pedestrian flows (cf. section 3.2).

SPARK⁴ (Solovyev et al., 2010) (Simple Platform for Agent-based Representation of Knowledge) is a framework for multi-scale ABM, dedicated to biomedical research.

Scerri et al. proposed a technical architecture to distribute the simulation of complex agent-based models (Scerri et al., 2010). This approach aims at integrating

³<http://tmans.sourceforge.net/>

⁴<http://www.pitt.edu/~cirm/spark/>

multiple ABMs in a single simulation, each ABM representing a specific aspect of the problem. In their article, authors focus on the management of time in such simulations. Therefore, the proposed platform provides two main technical services that ensure the consistency of simulations: (1) a *time manager* that ensures that integrated ABMs advance in time in a consistent way and (2) a *conflict resolver* that manages the problematic interactions between agents and shared data (such as the environment). Authors evaluate their approach on a modified version of Repast⁵ and show it can scale large-scale models easily.

IRM4MLS⁶ (Morvan and Jolly, 2012; Morvan et al., 2011) (Influence Reaction Model for Multi-Level Simulation) is a multi-level extension of IRM4S (Influence Reaction Model for Simulation) (Michel, 2007), an ABM meta-model based on the Influence Reaction model which views action as a two step process: (1) agents produce "influences", *i.e.*, individual decisions, according to their internal state and perceptions, (2) the system "reacts", *i.e.*, computes the consequences of influences, according to the state of the world (Ferber and Müller, 1996). The relations of perception and influence between levels are specified with digraphs. IRM4MLS relies on a generic vision of multi-level modeling (see section 1). Therefore, interactions between levels are not constrained. It has been applied to simulate and control intelligent transportation systems composed of autonomous intelligent vehicles (Morvan et al., 2012, 2009; Soyez et al., 2013, 2011) (see section 3.2).

ML-Rules (Maus et al., 2011) is a rule-based multi-scale modeling language dedicated to cell biological systems. Rules, describing system dynamics, are described in a similar way as in chemical reaction equations. ML-Rules has been implemented within the simulation framework JAMES II⁷. This approach does not refer explicitly to ABM; however, multi-level rule-based languages seem a promising way to engineer complex individual-based models.

Müller et al. developed an approach that consists in decomposing a problem according to the complementary points of view involved in the modeling (Müller and Aubert, 2011; Müller and Diallo, 2012; Müller et al., 2011). For instance in their case study the problem is the relation between residential and scholar segregation. Three points of view are considered: the geographer, the sociologist and the economist. Then, independent conceptual agent-based models are defined for each point of view. As models share agents and concepts, the conceptual models cannot be merged without some processing. Indeed, a same concept can have different meanings according to the point of view. To solve this issue, Müller et al. adapt a technique described in the modular ontology literature: defining bridge rules that explicit the relations between concepts.

PADAWAN (Picault and Mathieu, 2011) (Pattern for Accurate Design of Agent Worlds in Agent Nests) is a multi-scale ABM meta-model based on a compact matrixial representation of interactions, leading to a simple and elegant simulation framework. This representation is based on the meta-model of IODA (Interaction-Oriented Design of Agent simulations) dedicated to classical (1-level) ABM (Kubera et al., 2008).

GAMA⁸ (Drogoul et al., 2013; Taillandier et al., 2010, 2012) is an ABM platform with a dedicated modeling language, GAML, that offers multi-level capabilities. Moreover, it includes a framework (a set of predefined GAML commands) to

⁵<http://repast.sourceforge.net>

⁶http://www.lgi2a.univ-artois.fr/~morvan/Gildas_Morvan/IRM4MLS.html

⁷<http://www.jamesii.org>

⁸<http://code.google.com/p/gama-platform/>




Figure 2: The Seck and Honig (2012) approach

agentify emerging structures (Vo et al., 2012b). It is certainly the most advanced platform, from an end-user point of view, that integrates a multi-level approach. The multi-scale meta-model focuses on the notion of *situated agent* and therefore, top class abstractions include geometry and topology of simulated entities (Vo et al., 2012a). The notion of level does not appear explicitly but the concept of *species* defines attributes and behaviors of a class of same type agents and the multi-scale structure of the model, *i.e.*, how species can be nested within each other.

Seck and Honig developed an extension of DEVS that allows the simulation of multi-level (*i.e.*, non hierarchically coupled) models (Seck and Honig, 2012). The coupling between levels is done through regular DEVS models, named bridge models (fig. 2).

AA4MM (Camus et al., 2013, 2012; Siebert, 2011; Siebert et al., 2010) (Agent and Artifact for Multi-Modeling) is a multi-modeling (or model coupling) meta-model applied to ML-ABM. Levels are reified by agents that interact through artifacts. This meta-model extends existing ones, see *e.g.*, Bonneaud (2008); Bonneaud et al. (2007), distributing the scheduling between levels.

2.2 Observation, detection and agentification of emergent phenomena

An important issue concerning ML-ABM is to observe, detect and possibly reify (or more precisely agentify) phenomena emerging from agent interactions. Of course, the question is not to detect any emergent phenomenon but those of interest, in order to *e.g.*, adapt the level of detail of simulations, model cross-level interactions or observe multi-level behaviors.

Very different approaches have been proposed to solve this problem. The first ones were of course exploratory. Therefore, they rely on dedicated methods related to specific models. Newer works focus on generic methodologies and frameworks. They are briefly presented in a chronological order.

2.2.1 Dedicated clustering methods

The pioneering RIVAGE project (Servat, 2000; Servat et al., 1998a,b) aimed "at modeling runoff, erosion and infiltration on heterogeneous soil surfaces" (Servat et al., 1998a, p. 184). At the microscopic level, water is viewed as a set of interacting *waterballs*. An indicator characterizes waterball movements to detect two types of remarkable situations: straight trajectories (corresponding to the formation of ravines) and stationary particles (corresponding to the formation of ponds). Close agents sharing such properties are aggregated in ravine or pond macroscopic agents.

Bertelle et al. (2002); Tranouez (2005); Tranouez et al. (2001, 2006); Tranouez and Dutot (2009); Tranouez et al. (2003) aimed at changing the level of detail of fluid flow simulations using the vortex method (Leonard, 1980). The goal was, as in the RIVAGE model, to detect complex structures, *i.e.*, clusters of particles sharing common properties, and aggregate them. However, the detection of emergent phenomena relies on graph-based clustering methods. Moncion et al. (2010) used a similar approach to detect aggregations of agents in flocking simulations.

Gil-Quijano (2007); Gil-Quijano and Piron (2007) and Gil-Quijano et al. (2008) used various clustering algorithms such as self-organizing maps, K-Means and particle swarm algorithms, to detect group formations.

2.2.2 Generic frameworks

Chen (2009, 2013); Chen et al. (2010); Chen and Hardoon (2010); Chen et al. (2008a,b, 2009) proposed a formalism, named *complex event types* to describe multi-level behaviors in ABMs. "Conceptually, complex events are a configuration of simple events where each component event can be located in a region or point in a hyperspace that includes time, physical space and any other dimensions" (Chen et al., 2008b, p. 4). Using this approach, it is then possible to formally define and observe complex phenomena at different levels.

David and Courdier (2008, 2009) developed a conceptual and technical framework to handle emergence reification. It is implemented in the GEAMAS-NG platform (cf. GEAMAS paragraph in the previous section) and has been used in a population model of the Reunion Island, to detect and reify new urban areas (David et al., 2012, 2011).

A similar framework has been integrated in the GAMA platform (see GAMA paragraph in the previous section). It includes various clustering methods developed in the literature (Vo et al., 2012b).

SimAnalyzer is a general-purpose tool, to detect and describe group dynamics in simulations (Caillou and Gil-Quijano, 2012; Caillou et al., 2012).

2.3 Representation of aggregated entities

While developing generic representations for aggregated entities (also called group abstractions) seems an important issue, to the best of our knowledge a few publications are available on the subject. The common idea in these works is to delegate

the computation of agent behavioral functions to less detailed agents, representing groups of aggregated agents, in other levels in order to reduce the complexity of interaction computing.

Sharpanskykh and Treur (2011a,b) proposed two approaches to group abstraction dedicated to models where agent state are represented by variables taking values in $\{0, 1\}$ or $[0, 1]$:

- *weighting averaging*: an aggregated state of a group is estimated by averaging agent states, with a weighting factor related to the strength of influence of an agent in the group (the stronger, the more important).
- *invariant-based abstraction*: this approach consists in determining an invariant in a group of agents, *i.e.*, a property that does not change in time and using it as a conservation law.

Sharpanskykh and Treur applied these methods to a collective decision making model of social diffusion. They performed a comparative study of the methods, focusing on computational efficiency and approximation error.

Parunak (2012) introduced the notion of *pheromone field* (referring to the concept of *mean field* in statistical physics) that "gives the probability of encountering an agent of the type represented by the field at a given location" (Parunak, 2012, p. 115). In this approach, agents act according to their perceptions of pheromone fields (but not of agents).

Navarro et al. (2012) proposed a generic approach based on the notion of *mesoscopic representation*: agents sharing common properties (related to their physical or mental states) delegate the computation of behavioral functions to a mesoscopic agent. Authors developed this approach to reduce the computational cost of simulations while guaranteeing accurate results.

3 Application domains

ML-ABM has been used in various fields such as

- biomedical research
 - cancer modeling (Andasari et al., 2012; Brown et al., 2011; Deisboeck and Stamatakis, 2010; Lepagnot and Hutzler, 2009; Olsen and Siegelmann, 2013; Paiva et al., 2009; Rejniak and Anderson, 2011; Sun et al., 2012; Wang et al., 2013, 2008; Wang and Deisboeck, 2008; Wang et al., 2007; Zhang et al., 2007, 2009a, 2011, 2009b),
 - inflammation modeling (An, 2008; An et al., 2013; An and Wilensky, 2009; Kim et al., 2012; Scheff et al., 2012; Vodovotz et al., 2008; Wakeland et al., 2007),
 - arterial adaptation (Hayenga et al., 2011; Thorne et al., 2011),
 - stent design (Tahir et al., 2011),
 - vascular tissue engineering (Zahedmanesh and Lally, 2012),
 - bone remodeling (Cacciagrande et al., 2010),


- flow modeling of walking (and running) (Gaud et al., 2008a; Navarro et al., 2011; Nguyen et al., 2011, 2012b; Xi and Son, 2012), driving (Bourrel, 2003; Bourrel and Henn., 2002; Bourrel and Lesort, 2003; Burghout et al., 2005; El hmam et al., 2008, 2006a,b,c; Espié et al., 2006; Magne et al., 2000; Mammam and Haj-Salem, 2006; Morvan et al., 2012, 2009; Poschinger et al., 2002; Sewall et al., 2011; Soyez et al., 2013, 2011; Wedde and Senge, 2012) or streaming (Servat et al., 1998a,b; Tranouez et al., 2006) agents,
- biology (Adra et al., 2010; Biggs and Papin, 2013; Christley et al., 2007a,b; Jeschke and Uhrmacher, 2008; Marino et al., 2011; Montagna et al., 2010a,b; Seal et al., 2011; Shimoni et al., 2011; Smallwood et al., 2010; Smallwood and Holcombe, 2006; Stieglmeier et al., 2013; Sun et al., 2009),
- social simulation (Conte et al., 2007; Conte and Castelfranchi, 1996; Dascalu et al., 2009, 2011; Gil-Quijano et al., 2008; Hassoumi et al., 2012; Laperrière, 2012; Louail, 2010; North et al., 2010; Ozik et al., 2008; Parry and Bithell, 2012; Pumain and Louail, 2009; Sawyer, 2001, 2003; Schaller et al., 2012; Schillo et al., 2001; Seck and Honig, 2012; Squazzoni, 2008),
- ecology (Belem, 2009; Belem and Müller, 2009; Belem and Müller, 2013; Cheong et al., 2012; Duboz, 2004; Duboz et al., 2003; Le et al., 2011; Marilleau et al., 2008; Morvan et al., 2008, 2009; Prévost et al., 2004; Ratzé et al., 2007; Rounsevell et al., 2012; Schmidt et al., 2011; Seidl et al., 2012, 2010; Semeniuk et al., 2011; Vincenot et al., 2011),
- military simulation (Mathieu et al., 2007a,b; Parunak et al., 2009).

An interesting comparative analysis of three of these models can be found in Gil-Quijano et al. (2009, 2010); Gil-Quijano et al. (2012) and Louail (2010, p. 185–204).

3.1 Social simulation

Social simulation is defined by Squazzoni (2008, p. 4) as "the study of social outcomes, let us say a macro regularity, by means of computer simulation where agents' behavior, interactions among agents and the environment are explicitly modeled to explore those micro-based assumptions that explain the macro regularity of interest".

Major social theories developed in the second half of the twentieth century, e.g., *structuration* (Giddens, 1987) and *habitus* (Bourdieu, 1994) theories⁹, share a common ambition: solving the micro/macro (so called *agency/structure*) problem that can be summarized by the following question: *To understand social systems, should we observe agent interactions (micro level) or structures emerging from these interactions (macro level)?* Such theories tend to consider altogether agent positions in the social space (objective facts) and goals (subjective facts) to explain their beliefs and actions. Their answer to the previous question could be: *social systems can only be understood by considering simultaneously agent interactions and structures in which they occur:*



⁹These theories are described by some sociologists as hybrid (Sawyer, 2001).

A key concept used by social theorists and modelers to understand downward (or top-down) causation in social systems, *i.e.*, how social structures influence agents, is *reflexivity*. It can be defined as the "regular exercise of the mental ability, shared by all normal people, to consider themselves in relation to their (social) contexts and vice versa" (Archer, 2007, p. 4). Thus, social systems differ from other types of systems, by the reflexive control that agents have on their actions: "The reflexive capacities of the human actor are characteristically involved in a continuous manner with the flow of day-to-day conduct in the contexts of social activity" (Giddens, 1987, p. 22). Two very different approaches, both from technical and methodological perspectives, can be considered to simulate systems composed of reflexive agents:

- a purely emergentist approach, only based on the cognitive capabilities of agents to represent and consider themselves in relation to the structures emerging from their interactions — *e.g.*, Conte and Paolucci (2002); Gilbert (2002),
- a multi-level approach based on the cognitive capabilities of agents and the dynamic *reification* of interactions between social structures and agents, *i.e.*, processes that underlie social practices — *e.g.*, Gil-Quijano et al. (2009); Pumain et al. (2009).

According to Giddens (1987), two forms of reflexivity can be distinguished: *practical* (agents are not conscious of their reflexive capabilities, and therefore, are not able to resonate about them) and *discursive* (agents are conscious of their reflexive capabilities) reflexivity. These two forms are respectively related to the ideas of *immersion* in which agent interactions produce emergent properties that modify the way they produce them (Conte et al., 2007) and *second order emergence* in which agent interactions produce emergent properties that are recognized (incorporated) by agents and influence their actions (Gilbert, 2002).

ML-ABM can also be viewed as a way to link independent social theories (and therefore concepts) defined at different levels (fig. 3) (Sawyer, 2001, 2003; Seck and Honig, 2012). Thus, Seck and Honig (2012) proposed a model of social conflicts integrating agent behaviors and social laws. Gil-Quijano (2007); Gil-Quijano et al. (2007, 2008) developed a multi-scale model of intra-urban mobility. The microscopic level represents households and housing-units, the mesoscopic one, groups of micro-agents and urban-sectors and the macroscopic one, the city itself. A clustering algorithm is applied to detect and reify groups of households and housing-units. Pumain and Louail (2009) developed *Simpop3*, a multi-scale model based on two previously developed single-scale models: *Simpop nano*, simulating the internal dynamics of a city and *Simpop2*, simulating city interactions.

Readers interested in a more comprehensive presentation of these questions may refer to Sawyer (2003); Schillo et al. (2001); Squazzoni (2008) and Raub et al. (2011).

3.2 Flow modeling

A flow of moving agents can be observed at different scales. Thus, in traffic modeling, three levels are generally considered: the *micro*, *meso* and *macro* levels, representing respectively the interactions between vehicles, groups of vehicles sharing common properties (such as a common destination or a common localisation) and flows of vehicles. Each approach is useful in a given context: micro and meso models allow to simulate road networks with complex topologies such as urban area, while macro




Figure 3: ML-ABM in social simulation as a link between concepts defined at different levels

models allow to develop control strategies to prevent congestion in highways. However, to simulate large-scale road networks, it can be interesting to integrate these different representations (fig. 4). The main problem is to determine an appropriate coupling between the different representations, *i.e.*, that preserves the consistency of simulations (Davis and Hillestad, 1993).




Figure 4: ML-ABM and control in traffic simulation

3.2.1 Micro-macro models

An interesting comparison of existing micro-macro traffic models can be found in El hnam (2006, p. 31–44) (table 1). The coupling methods rely on the following idea: creating a virtual section which is both macro and micro at level connections. This virtual section is used as a buffer to generate appropriate micro or macro data according to the type of connection. On this basis, El hnam (2006); El hnam et al. (2008, 2006a,b,c) proposed a generic coupling method between agent-based microscopic models and widely used macroscopic models such as LWR, ARZ and Payne.

While micro-macro flow models were essentially developed in the traffic domain, other applications such as crowd simulation emerged in recent years (Nguyen et al., 2011, 2012b).

However, all the surveyed hybrid models share the same limitation: connections between levels are fixed *a priori* and cannot be changed at runtime. Therefore, to

be able to observe some emerging phenomena such as congestion formation or to find the exact location of a jam in a large macro section, a dynamic hybrid modeling approach is needed (Sewall et al., 2011).

model	micro model	macro model
Magne et al. (2000)	SITRA-B+	SIMRES
Poschinger et al. (2002)	IDM	Payne
Bourrel and Lesort (2003)	optimal velocity	LWR
Mammar and Haj-Salem (2006)		ARZ
Espié et al. (2006)	ARCHISM	SSMT
El hmam (2006)	generic ABM	LWR, ARZ, Payne
Sewall et al. (2011)		ARZ

Table 1: Main micro-macro traffic flow models, adapted from El hmam (2006, p. 42)

3.2.2 Micro-meso models

This kind of models is often used to reduce the complexity of agent interactions. Agents sharing common properties can be aggregated to form up a higher level (mesoscopic) agent and then, save computer resources or describe group dynamics such as in the already mentioned RIVAGE (Servat, 2000; Servat et al., 1998a,b) and DS (David et al., 2011) models (cf. section 2.2). Conversely, mesoscopic agents can be broken up into lower level agents if related structures vanish.

Morvan et al. (2012, 2009) introduced an multi-level approach to solve the dead-lock problem in field-driven autonomous intelligent vehicle systems. These systems generally rely on self-organization to achieve their goals, but AIVs can remain trapped into dead-locks. When such a situation is detected (using a similar approach than Servat (2000); Servat et al. (1998a,b)), it is agentified to solve the problem using hierarchical control.

Flacher et al. (2012); Navarro et al. (2012, 2013, 2011) proposed an innovative framework for such models: (de)aggregation functions rely not only on the observable state of simulations (the environment) but also on the internal state of agents. It has been applied to pedestrian flow simulation. The proximity between agent states (external and internal) is computed by an affinity function.

Soyez et al. (2013, 2011) extended this framework on the basis of IRM4MLS. Agents are "cut" into a set of physical parts (bodies), situated in different levels, and a non-situated part (mind) (see fig. 5). Therefore, these different parts can be (de)aggregated independently. This approach has been applied to dynamically adapt the level of detail in a port operations simulator.

3.3 Biological and biomedical models

A biological system can be considered at different levels of organization:

$$\dots \rightarrow \text{molecule} \rightarrow \text{cell} \rightarrow \text{tissue} \rightarrow \text{organ} \rightarrow \dots,$$

that basically correspond to the segmentation of biological research into specialized communities:

$$\dots \rightarrow \text{molecular biology} \rightarrow \text{cell biology} \rightarrow \text{histology} \rightarrow \text{physiology} \rightarrow \dots$$




Figure 5: Mind/bodies separation in the Soyez et al. (2013) model

Each research area has developed its own ontologies and models to describe the same reality observed at different levels. However, this reductionist approach fails when addressing complex issues (Schnell et al., 2007). Thus, it has been shown that living systems are co-produced by processes at different levels of organization (Maturana and Varela, 1980). Therefore, an explanatory model of such systems should account for the interactions between levels.

3.3.1 Cell biology

At least two levels are explicitly represented in cell biology models: the *macroscopic* one, representing the extracellular environment and the interactions between cells, and the *microscopic* one, representing the intracellular environment and the interactions between cell components such as signaling pathways and gene regulatory networks. A major modeling issue is that these two levels continuously influence each other. It led to the development of multi-scale models.

Montagna et al. (2010a,b) developed a model of morphogenesis in biological systems, in particular for the *Drosophila Melanogaster* species. Maus et al. (2011) proposed a model of *Schizosaccharomyces pombe* (a species of yeast) cell division and mating type switching based on the ML-Rules approach (cf. section 2.1).

3.3.2 Cancer modeling

Cancer is a complex spatialized multi-scale process, starting from genetic mutations and potentially leading to metastasis. Moreover, it has multi-scale (from genetic to environmental) causes. Therefore, it can be studied from various perspectives from the intracellular (molecular) to the population levels.

ML-ABM is a promising paradigm to model cancer development (Wang and Deisboeck, 2008). Indeed, as Schnell et al. (2007, p. 140) note, "a multi-scale model would allow us to explore the effect of combination therapies, approaches that attempt to stop cancer in its tracks by barricading multiple pathways. Most present models, focusing on processes at a single scale, cannot provide this comprehensive view."

Zhang et al. developed an ML-ABM of a brain tumor named *Glioblastoma Multiforme* (GBM) (Zhang et al., 2007, 2009a, 2011, 2009b). This model explicitly defines the relations between scales and uses different modeling approaches: ordinary differential equations (ODE) at the intracellular level, discrete rules typically found in ABM at the cellular level and partial differential equations (PDE) at the tissue level (see fig. 6).

Moreover, this model also relies on a multi-resolution approach: heterogeneous clusters, *i.e.*, composed of migrating and proliferating cells are simulated at a high

resolution while homogenous clusters of dead cells are simulated at a lower resolution. In short, "more computational resource is allocated to heterogenous regions of the cancer and less to homogenous regions" (Zhang et al., 2011, p. 6). This model has been implemented on graphics processing units (GPU), leading to an efficient parallel simulator (Zhang et al., 2011).




Figure 6: ML-ABM in brain tumor modeling (Zhang et al., 2007, 2009a, 2011, 2009b)

Sun et al. (2012) also developed a brain tumor ML-ABM available as a MATLAB library called ABM-TKI¹⁰. It is based on a 4 level architecture (tissue, microenvironmental, cellular, modelcular).

Lepagnot and Hutzler (2009) model the growth of avascular tumors to study the impact of PAI-1 molecules on metastasis. To deal with the problem complexity (a tumor may be composed of millions of cells) two levels are introduced: the cell and the tumor's core levels (fig. 7). Indeed, such cancers are generally structured as a kernel of necrosed or quiescent cells surrounded by living tumor cells. As necrosed and quiescent cells are mostly inactive, tumor's core is reified as a single upper-level agent, interacting with cells and PAI-1 molecules at its boundary. A more comprehensive analysis of this model can be found in Gil-Quijano et al. (2012).




Figure 7: ML-ABM in avascular tumor growth modeling (Lepagnot and Hutzler, 2009)

3.4 Ecology

Ecologists study processes that can have very different spatio-temporal dynamics. Then, characterizing their interactions is a complicated problem and traditional bottom-up or top-down approaches do not seem relevant: ABMs tend to be too

¹⁰<https://sites.google.com/site/agentbasedtumormodeling/home>

complex, requiring a lot of computational resources¹¹ while EBM cannot deal with complex heterogenous environments (Shnerb et al., 2000).

Ecological systems are generally described as hierarchies (Müller et al., 2005; Ratzé et al., 2007). Thus the hierarchy theory is "a view of ecological systems, which takes the scales of observation explicitly into account and which tries to conceptualize the phenomena at their proper scale" (Ratzé et al., 2007, p. 14). ML-ABM seems a interesting way to implement this concept. Different modeling issues in Ecology have been solved by ML-ABM.

Duboz (2004); Duboz et al. (2003) proposed the **scale transfer** approach to link microscopic and macroscopic models: the state of the system is computed by an ABM and is used to parametrize an EBM describing population dynamics. This EBM can then be used to parametrize the ABM environment (fig. 8).




Figure 8: The scale transfer approach (Duboz, 2004; Duboz et al., 2003)

Marilleau et al. (2008) introduced a efficient method to represent complex soils, named **APSF** (Agent, Pores, Solid and fractal). Traditionally, the environment is viewed as a regular grid, discretized into cells. A cell can represent a pore, *i.e.*, a part of a soil cavity, a solid or a fractal. The idea is that a cell is not necessarily an atomic element describing an homogenous area but can be fractal, *i.e.*, composed of smaller pore, solid or fractal cells with a self similar structure. Fractal cells are instantiated at run time, generating finer representations of the environment when it is needed. Thus, this approach based on self-generation allows to represent complex multi-scale environments at a minimal computational cost. It has been used in the SWORM (Simulated WORMS) model that studies the relation between earthworm activity and soil structure (Blanchart et al., 2009; Laville et al., 2012).

Diptera larvae have a complex gregarious behavior that lead to the formation of large groups in which individuals regulate the temperature to optimize their development speed. This phenomenon can be described by a mesoscopic equation-based model (knowing the mass of the group and and the external temperature), while the crowding behavior of larvae can be modeled by an ABM. Moreover, the thermal dynamics of the cadaver can be modeled by a Cellular Automaton (CA). Morvan et al. (2008, 2009) integrated these different models in a ML-ABM to perform more accurate forensic entomology expertises. In this model, the EBM is parametrized according to the ABM state. It computes the increase of temperature caused by *Diptera* interactions at the group level and send it to the CA model that is used as an environment for the ABM (fig. 9). The environment can thus be viewed as an artifact, used to synchronize the different models.

¹¹An interesting solution to this problem is to reduce the complexity of agent interactions using estimation algorithms such as the fast multipole method (Razavi et al., 2011).




Figure 9: Levels of organization in a ML-ABM of necrophagous *Diptera* development (Morvan et al., 2008, 2009)

4 Discussion

In this section two issues are discussed:

- the different forms of level integration,
- the use of ML-ABM to solve technical problems.

4.1 Level integration

In the introduction, ML-ABM has been defined as integrating heterogenous ABMs in a single model. Following the approach of Michel et al. (2003) on interaction, one can distinguish at least two forms of integration:

- **weak integration:** levels share objects, e.g., environment properties, but not agents,
- **strong integration:** levels share objects and agents.

Weak integration can be regarded as a form of multi-modeling (or model coupling) where levels represent different models interacting through shared variables called artifacts (Camus et al., 2012; Seck and Honig, 2012; Siebert et al., 2010).

Weaker forms of integration are not regarded as multi-level modeling. Thus, in the SWARM platform (Minar et al., 1996), integration can be described as bottom-up or isotropic (information flows in one direction). An agent is designed as a russian doll and its behavior at a given level depends on the lower ones.

An simple example of strong integration is given by Picault and Mathieu (2011, p. 334): "a membrane protein, which has an end inside the cell, and the other end outside".

In the meta-models presented in section 2.1, IRM₄MLS and PADAWAN are, to the best of our knowledge, the only ones able to simulate strongly integrated levels. It is not surprising as they are based on formal interaction models (respectively IRM₄S and IODA) that differentiate between agent influences and level reaction and therefore, are able to represent **strong interaction** (Michel et al., 2003). In short, agents are strongly interacting if the interaction output depends on the influences of each agent. Thus, STRIPS-like action models (*i.e.*, that view action as a change of the state of the world), used in most of agent-based simulation platforms, are unable to represent such interactions. Yet, (Michel et al., 2003) showed that modeling a strong interaction as a weak one leads to arbitrary implementation choices and result interpretation issues.

In ML-ABM, the problem is similar since levels can be seen as strongly interacting entities. Thus, we can conclude that a modeling formalism capable of representing strong interaction¹² can be extended to a multi-level one.

4.2 Multi-level technical tools

Although considering cross-level interactions is usually related to the application domain as shown previously in this article, it can also be viewed as a technical tool:

- an ABM (microscopic level) can be used to parametrize an equation based model (macroscopic level) (Duboz, 2004; Duboz et al., 2003; Nguyen et al., 2012a),
- levels can be created at run-time by other levels to generate fractal environments (Marilleau et al., 2008),
- a mesoscopic level can be viewed as a controller (in the control theory meaning) of group-related properties (Morvan and Jolly, 2012).
- automated observation and analysis tools can be introduced at levels not explicitly present in the model to detect and study (multi-level) emergent phenomena¹³ (cf. section 2.2). However, reified emergent phenomena cannot be considered as model entities since they are not re-injected in the simulation (see fig. 10),
- a radical interpretation of ML-ABM is the concept of multi-future (Parunak et al., 2010; Parunak and Brueckner, 2010). The possible trajectories of agent actions are computed by "ghosts" as a pheromone field and agents act according to it, selecting the most probable one.

As these ideas are domain-independent, they could be implemented as a generic library, providing such services to a classical ABM or ML-ABM framework or platform.




Figure 10: Two main uses of detected emergent phenomena: visualization or re-injection in the simulation as agents

¹²Some authors described these approaches as "interaction-based modeling", by opposition to the term "individual-based modeling", as that they focus on interactions rather than on individual behaviors (Desmeulles et al., 2009; Kubera et al., 2008).

¹³Indeed, as An (2008, p. 4) notes about ABM, "since the models rely on an ill-defined principle of 'emergence' in order to transcend the epistemological boundaries represented by the multiple hierarchies of system organization, their behavior is difficult to characterize analytically".

5 Conclusion

An important challenge for the scientific community is to find ways to deal with the complexity of natural and artificial complex systems. This issue led to the development of dedicated modeling paradigms and engineering principles that focus on interaction and organization. We strongly believe that such techniques will play an important role in the future.

In this article, we conducted a comprehensive analysis of the bibliography available on one of them: multi-level agent-based modeling.

As we shown, many papers focus on the application of this technique and then, are published in domain-related journals and conferences. However, a dedicated venue for theoretical or methodological papers is lacking. Such forum would allow to unify the vocabulary and concept definitions, discuss the main issues of this approach and more generally, share ideas with the interested communities.

Acknowledgments

I am particularly grateful to my colleagues Shahin Gelareh, Yoann Kubera and Jean-Baptiste Soyez for their help and support. I also would like to thank Chih-Chun Chen, Jean-Pierre Müller and Sebastian Senge for suggesting new entries in the bibliographical database.

References

- Adra, S., Sun, T., MacNeil, S., Holcombe, M., and Smallwood, R. (2010). Development of a three dimensional multiscale computational model of the human epidermis. *PLoS one*, 5(1):e8511.
- An, G. (2008). Introduction of an agent-based multi-scale modular architecture for dynamic knowledge representation of acute inflammation. *Theoretical Biology and Medical Modelling*, 5(11).
- An, G., Wandling, M., and Christley, S. (2013). Agent-based modeling approaches to multi-scale systems biology: An example agent-based model of acute pulmonary inflammation. In *Systems Biology - Integrative Biology and Simulation Tools*, pages 429–461. Springer.
- An, G. and Wilensky, U. (2009). Artificial life models in software. In *From Artificial Life to In Silico Medicine: NetLogo as a Means of Translational Knowledge Representation in Biomedical Research*, pages 183–212. Springer.
- Andasari, V., Roper, R., and ans M.A.J. Chaplain, M. S. (2012). Integrating intracellular dynamics using compucell3d and bionetsolver: Applications to multiscale modelling of cancer cell growth and invasion. *PLoS ONE*, 7(3):e33726.
- Archer, M. (2007). *Making our Way through the World: Human Reflexivity and Social Mobility*. Cambridge University Press.
- Belem, M. (2009). *A conceptual model for multipoints of view analysis of complex systems. Application to the analysis of the carbon dynamics of village territories of the West African savannas*. PhD thesis, AgroParisTech.
- Belem, M. and Müller, J.-P. (2009). Toward a conceptual framework for multi-points of view analysis in complex system modeling: Orea model. In *7th International Conference on Practical Applications of Agents and Multi-Agent Systems (PAAMS 2009)*, volume 55 of *Advances in Intelligent and Soft Computing*, pages 548–556. Springer.
- Belem, M. and Müller, J.-P. (2013). An organizational model for multi-scale and multi-formalism simulation: Application in carbon dynamics simulation in west-african savanna. *Simulation Modelling Practice and Theory*, 32:83–98.
- Bertelle, C., Jay, V., Lerebourg, S., Olivier, D., and Tranouez, P. (2002). Dynamic clustering for auto-organized structures in complex fluid flows. In *ESS 2002 Conference*.
- Biggs, M. B. and Papin, J. A. (2013). Novel multiscale modeling tool applied to pseudomonas aeruginosa biofilm formation. *PLoS one*, 8(10):e78011.
- Blanchart, E., Marilleau, N., Chotte, J., Drogoul, A., Perrier, E., and Cambier, C. (2009). SWORM: an agent-based model to simulate the effect of earthworms on soil structure. *European Journal of Soil Science*, 60(1):13–21.
- Bonneaud, S. (2008). *Des agents-modèles pour la modélisation et la simulation de systèmes complexes: application à l'écosystème des pêches*. PhD thesis, Université de Bretagne occidentale, Brest.
- Bonneaud, S., Redou, P., and Chevaillier, P. (2007). Pattern oriented agent-based multi-modeling of exploited ecosystems. In *Proceedings of the 6th EUROSIM congress*.
- Bourdieu, P. (1994). *Raisons pratiques: sur la théorie de l'action*, volume 331 of *Points*. Éditions du Seuil.
- Bourrel, E. (2003). *Modélisation dynamique de l'écoulement du trafic routier : du macroscopique au microscopique*. PhD thesis, Institut National des Sciences Appliquées de Lyon, Lyon.
- Bourrel, E. and Henn., V. (2002). Mixing micro and macro representations of traffic flow: a first theoretical step. *Proceedings of the 9th Meeting of the Euro Working Group on Transportation*.

- Bourrel, E. and Lesort, J. (2003). Mixing micro and macro representations of traffic flow: a hybrid model based on the LWR theory. *82th Annual Meeting of the Transportation Research Board*.
- Brown, M., Bowering, E., Epstein, S., Jhaveri, M., Maheswaran, R., Mallick, P., Mumenthaler, S., Povinelli, M., and Tambe, M. (2011). Applying multi-agent techniques to cancer modeling. In *Sixth Annual Workshop on Multiagent Sequential Decision Making in Uncertain Domains (MSDM-2011)*.
- Burghout, W., Koutsopoulos, H., and Andreasson, I. (2005). Hybrid mesoscopic-microscopic traffic simulation. *Transportation Research Record: Journal of the Transportation Research Board*, 1934(1):218–255.
- Cacciagrano, D., Corradini, F., and Merelli, E. (2010). Bone remodelling: A complex automata-based model running in bioshape. *Cellular Automata*, pages 116–127.
- Caillou, P. and Gil-Quijano, J. (2012). Simanalyzer : Automated description of groups dynamics in agent-based simulations. In *Proc. of 11th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2012)*.
- Caillou, P., Gil-Quijano, J., and Zhou, X. (2012). Automated observation of multi-agent based simulations: a statistical analysis approach. to appear in *Studia Informatica Universalis*, 10(3):62–86.
- Camus, B., Bourjot, C., and Chevrier, V. (2013). Multi-level modeling as a society of interacting models. In *SpringSim'13, ADS Symposium-Spring Simulation Multi-Conference, Agent-Directed Simulation Symposium-2013*, volume 1, pages 15–22.
- Camus, B., Siebert, J., Bourjot, C., and Chevrier, V. (2012). Modélisation multi-niveaux dans AA4MM. In *Actes des 20èmes Journées Francophones sur les Systèmes Multi-Agents (JFSMA)*.
- Chen, C. (2009). *Complex Event Types for Agent-Based Simulation*. PhD thesis, University College London.
- Chen, C. (2013). A theoretical framework for conducting multi-level studies of complex social systems with agent-based models and empirical data. *CoRR*, abs/1302.4774.
- Chen, C., Clack, C., and Nagl, S. (2010). Identifying multi-level emergent behaviors in agent-directed simulations using complex event type specifications. *Simulation*, 86(1):41–51.
- Chen, C. and Hardoon, D. (2010). Learning from multi-level behaviours in agent-based simulations: a systems biology application. *Journal of Simulation*, 4(3):196–203.
- Chen, C., Nagl, S., and Clack, C. (2008a). A method for validating and discovering associations between multi-level emergent behaviours in agent-based simulations. In N.T. Nguyen, G.S. Jo, R. H. and Jain, L., editors, *Agent and Multi-Agent Systems: Technologies and Applications*, volume 4953 of *Lecture Notes in Computer Science*, pages 1–10. Springer.
- Chen, C., Nagl, S., and Clack, C. (2008b). Multi-level behaviours in agent-based simulation: colonic crypt cell populations. In *Proceedings of the Seventh International Conference on Complex Systems*.
- Chen, C., Nagl, S., and Clack, C. (2009). A formalism for multi-level emergent behaviours in designed component-based systems and agent-based simulations. In Aziz-Alaoui, M. and Bertelle, C., editors, *From System Complexity to Emergent Properties*, volume 12 of *Understanding Complex Systems*, pages 101–114. Springer.
- Cheong, S., Brown, D., Kok, K., and Lopez-Carr, D. (2012). Mixed methods in land change research: towards integration. *Transactions of the Institute of British Geographers*, 37(1):8–12.
- Christley, S., Newman, S. A., and Alber, M. S. (2007a). Agent-based model for developmental pattern formation with multiscale dynamics and varying cell geometry. In *Mathematical Modeling of Biological Systems*, volume 1, pages 149–161. Springer.
- Christley, S., Zhu, X., Newman, S. A., and Alber, M. S. (2007b). Multiscale agent-based simulation for chondrogenic pattern formation in vitro. *Cybernetics and Systems: An International Journal*, 38(7):707–727.
- Conte, R., Andrighetto, G., Campenni, M., and Paolucci, M. (2007). Emergent and immergent effects in complex social systems. In *Proceedings of AAAI Symposium, Social and Organizational Aspects of Intelligence, Washington DC*.
- Conte, R. and Castelfranchi, C. (1996). Simulating multi-agent interdependencies: a two-way approach to the micro-macro link. In *Social Science Microsimulation*, pages 394–415. Springer.
- Conte, R. and Paolucci, M. (2002). *Reputation in Artificial Societies*. Kluwer Academic Publishers.
- Dascalu, M., Gheorghe, S., and Zafiu, A. (2009). Multi-level simulator for artificial societies. *Romanian Journal of Information Science and Technology*, 12(4):466–484.
- Dascalu, M., Stefan, G., Zafiu, A., and Plavitu, A. (2011). Applications of multilevel cellular automata in epidemiology. In *Proceedings of the 13th WSEAS international conference on Automatic control, modelling & simulation*, pages 439–444. World Scientific and Engineering Academy and Society (WSEAS).
- David, D. and Courdier, R. (2008). Emergence as meta-knowledge: refining simulation models through emergence reification. In *Proceedings of ESM'2008, Le Havre, France*, pages 25–27.
- David, D. and Courdier, R. (2009). See emergence as a metaknowledge: a way to reify emergent phenomena in multiagent simulations? In *Proceedings of ICAART'09*, pages 564–569, Porto, Portugal.
- David, D., Gangat, Y., Payet, D., and Courdier, R. (2012). Reification of emergent urban areas in a land-use simulation model in reunion island. In *ECAI workshop on Intelligent Agents in Urban Simulations and Smart Cities (IAUSSC2012)*, pp. 28–32, Montpellier, pages 28–32, Montpellier, France.
- David, D., Payet, D., and Courdier, R. (2011). Réification de zones urbaines émergentes dans un modèle simulant l'évolution de la population à la réunion. In *Actes des 19èmes Journées Francophones sur les Systèmes Multi-Agents (JFSMA'11)*, pages 63–72, Valenciennes, France. Cepadués.

- Davis, P. K. and Hillestad, R. (1993). Families of models that cross levels of resolution: issues for design, calibration and management. In *Proceedings of the 25th conference on Winter simulation*, WSC '93, pages 1003–1012, New York, NY, USA. ACM.
- Deisboeck, T. and Stamatakis, G. (2010). *Multiscale cancer modeling*, volume 34. CRC Press.
- Desmeulles, G., Bonneaud, S., Redou, P., Rodin, V., and Tisseau, J. (2009). In virtuo experiments based on the multi-interaction system framework: the réiscop meta-model. *Computer Modeling in Engineering and Sciences*, 47(3):299–329.
- Drogoul, A., Amouroux, E., Caillou, P., Gaudou, B., Grignard, A., Marilleau, N., Taillandier, P., Vasseux, M., Vo, D.-A., and Zucker, J.-D. (2013). GAMA: A spatially explicit, multi-level, agent-based modeling and simulation platform. In *Advances on Practical Applications of Agents and Multi-Agent Systems*, pages 271–274. Springer.
- Drogoul, A., Vanbergue, D., and Meurisse, T. (2003). Multi-agent based simulation: Where are the agents? In Sichman, J., Bousquet, F., and Davidsson, P., editors, *Multi-Agent-Based Simulation II*, volume 2581 of *Lecture Notes in Computer Science*, pages 1–15. Springer.
- Duboz, R. (2004). *Intégration de modèles hétérogènes pour la modélisation et la simulation de systèmes complexes*. PhD thesis, Université du Littoral.
- Duboz, R., Ramat, É., and Preux, P. (2003). Scale transfer modeling: using emergent computation for coupling an ordinary differential equation system with a reactive agent model. *Systems Analysis Modelling Simulation*, 43(6):793–814.
- Duhail, N. (2013). DEVs et ses extensions pour des simulations multi-modèles en interaction multi-échelles. Master's thesis, Université de Rennes 1 — Telecom Bretagne.
- El hnam, M. (2006). *Contribution à la modélisation et à la simulation hybride du flux de trafic*. PhD thesis, Université d'Artois.
- El hnam, M., Abouaissa, H., and Jolly, D. (2008). Contribution à la modélisation et la simulation du flux de trafic: approche hybride basée sur les systèmes multi-agents. *Actes INRETS*, pages 93–111.
- El hnam, M., Abouaissa, H., Jolly, D., and Benasser, A. (2006a). Macro-micro simulation of traffic flow. In *Proceedings of the 12th IFAC Symposium on Information Control Problems in Manufacturing (INCOM06)*, pages 351–356, Saint Etienne FRANCE.
- El hnam, M., Abouaissa, H., Jolly, D., and Benasser, A. (2006b). Simulation hybride de flux de trafic basée sur les systèmes multi-agents. In *6e Conférence Francophone de Modélisation et Simulation-MOSIM*.
- El hnam, M., Jolly, D., Abouaissa, H., and Benasser, A. (2006c). Modélisation hybride du flux de trafic. *Revue électronique Sciences et Technologies de l'Automatique*.
- Epstein, J. (2006). *Generative social science: Studies in agent-based computational modeling*. Princeton University Press.
- Espié, S., Gattuso, D., and Galante, F. (2006). Hybrid traffic model coupling macro- and behavioral microsimulation. In *85th Annual Meeting of Transportation Research Board*, Washington D.C.
- Ferber, J. (1999). *Multi-Agent Systems: An Introduction to Distributed Artificial Intelligence*. Addison-Wesley Longman Publishing Co., Inc.
- Ferber, J. and Müller, J.-P. (1996). Influences and reaction: a model of situated multiagent systems. In *2nd International Conference on Multi-agent systems (ICMAS'96)*, pages 72–79.
- Flacher, F., Navarro, L., and Corruble, V. (2012). Multi-agent simulation system. European Patent EP2518711, Thalès S.A.
- Gaud, N. (2007). *Systèmes multi-agent holoniques : De l'analyse à l'implantation. Méta-modèle, méthodologie, et simulation multi-niveaux*. PhD thesis, Université de Technologie de Belfort-Montbéliard.
- Gaud, N., Galland, S., Gechter, F., Hilaire, V., and Koukam, A. (2008a). Holonic multilevel simulation of complex systems : Application to real-time pedestrians simulation in virtual urban environment. *Simulation Modelling Practice and Theory*, 16:1659–1676.
- Gaud, N., Galland, S., and Koukam, A. (2008b). Towards a multilevel simulation approach based on holonic multi-agent systems. In *UKSIM*, pages 180–185, Cambridge, UK.
- Giddens, A. (1987). *La constitution de la société: éléments de la théorie de la structuration*. Presses Universitaires de France.
- Gil-Quijano, J. (2007). *Modèles d'auto-organisation pour l'émergence de formes urbaines à partir de comportements individuels à Bogota*. PhD thesis, Université Paris VI.
- Gil-Quijano, J., Hutzler, G., and Louail, T. (2009). De la cellule biologique à la cellule urbaine : retour sur trois expériences de modélisation multi-échelles à base d'agents. In *Actes des 17èmes Journées Francophones sur les Systèmes Multi-Agents (JFSMA'09)*.
- Gil-Quijano, J., Hutzler, G., and Louail, T. (2010). Accroche-toi au niveau, j'enlève l'échelle: Éléments d'analyse des aspects multiniveaux dans la simulation à base d'agents. *Revue d'Intelligence Artificielle*, 24(5):625–648.
- Gil-Quijano, J., Louail, T., and Hutzler, G. (2012). From biological to urban cells: Lessons from three multi-level agent-based models. In Desai, N., Liu, A., and Winikoff, M., editors, *Principles and Practice of Multi-Agent Systems*, volume 7057 of *Lecture Notes in Computer Science*, pages 620–635. Springer.
- Gil-Quijano, J. and Piron, M. (2007). Formation automatique de groupes d'agents sociaux par techniques d'apprentissage non supervisé. In *Actes de EGC'07 Atelier Fouille de Données et Algorithmes Biomimétiques*.
- Gil-Quijano, J., Piron, M., and Drogoul, A. (2007). Vers une simulation multi-agent de groupes d'individus pour modéliser les mobilités résidentielles intra-urbaines. *Revue internationale de géomatique*, 17(2):161–181.
- Gil-Quijano, J., Piron, M., and Drogoul, A. (2008). *Social Simulation: Technologies, Advances and New Discoveries*, chapter Mechanisms of Automated Formation and Evolution of Social-Groups: A Multi-Agent System to Model the Intra-Urban Mobilities of Bogota City. IGI Global.

- Gilbert, N. (2002). Varieties of emergence. In *Agent 2002 Conference: Social agents: ecology, exchange, and evolution*, Chicago.
- Gilbert, N. (2007). *Agent-Based Models*. Number 153 in Quantitative Applications in the Social Sciences. Sage Publications.
- Hassoumi, I., Lang, C., Marilleau, N., Temani, M., Ghedira, K., and Zucker, J. D. (2012). Toward a spatially-centered approach to integrate heterogeneous and multi-scales urban component models. In *Advances on Practical Applications of Agents and Multi-Agent Systems*, volume 155 of *Advances in Intelligent and Soft Computing Volume*, pages 81–86. Springer.
- Hayenga, H., Thorne, B., Peirce, S., and Humphrey, J. (2011). Ensuring congruency in multiscale modeling: towards linking agent based and continuum biomechanical models of arterial adaptation. *Annals of biomedical engineering*, pages 1–14.
- Jeschke, M. and Uhrmacher, A. (2008). Multi-resolution spatial simulation for molecular crowding. In *Proc. of the Winter Simulation Conference*, pages 1384–1392. IEEE.
- Kim, M., Christley, S., Alverdy, J., Liu, D., and An, G. (2012). A multi-scale agent-based model of necrotizing enterocolitis integrating oxidative stress, inflammation, and microvascular thrombosis. *Journal of Surgical Research*, 172(2):196.
- Koestler, A. (1967). *The Ghost in the Machine*. Hutchinson.
- Koestler, A. (1978). *Janus: A summing up*. Random House.
- Kubera, Y., Mathieu, P., and Picault, S. (2008). Interaction-oriented agent simulations: From theory to implementation. In *Proc. of the 18th European Conf. on Artificial Intelligence (ECAI'08)*, pages 383–387.
- Laperrière, V. (2012). Un cadre de modélisation dynamique multineveau pour la peste bubonique des hautes terres de madagascar. *Bulletin de l'Association de géographes français*, 89(2):278–288.
- Laville, G., Mazouzi, K., Lang, C., Marilleau, N., and Philippe, L. (2012). Using gpu for multi-agent multi-scale simulations. In *Distributed Computing and Artificial Intelligence*, volume 151 of *Advances in Intelligent and Soft Computing*, pages 197–204. Springer.
- Le, Q., Seidl, R., and Scholz, R. (2011). Feedback loops and types of adaptation in the modelling of land-use decisions in an agent-based simulation. *Environmental Modelling & Software*.
- Leonard, A. (1980). Vortex methods for flow simulation. *Journal of Computational Physics*, 37(3):289–335.
- Lepagnot, J. and Hutzler, G. (2009). A multiscale agent-based model for the simulation of avascular tumour growth. *Journal of Biological Physics and Chemistry*, 9(1):17–25.
- Louail, T. (2010). *Comparer les morphogénèses urbaines en Europe et aux États-Unis par la simulation à base d'agents – Approches multi-niveaux et environnements de simulation spatiale*. PhD thesis, Université d'Evry-Val d'Essonne.
- Magne, L., Rabut, S., and Gabard, J. (2000). Towards an hybrid macro-micro traffic flow simulation model. *Proceedings of the INFORMS Salt Lake City String 2000 Conference*.
- Mammar, S. and Lebacque, J. and Haj-Salem, H. (2006). Hybrid model based on second-order traffic model. *85th Annual Meeting of Transportation Research Board*, 1(06-2160).
- Marcenac, P., Courdier, R., and Calderoni, S. (1998a). Towards a toolkit to study emergence in complex systems simulations. http://personnel.univ-reunion.fr/courdier/pdfs/int_iea1998_MC98.pdf.
- Marcenac, P., Courdier, R., Calderoni, S., and Soulie, J. (1998b). Towards an emergence machine for complex systems simulations. In *Tasks and Methods in Applied Artificial Intelligence*, volume 416, pages 785–794. Springer.
- Marcenac, P. and Giroux, S. (1998). Geamas: A generic architecture for agent-oriented simulations of complex processes. *Applied Intelligence*, 8(3):247–267.
- Marilleau, N., Cambier, C., Drogoul, A., Chotte, J., Perrier, E., and Blanchart, E. (2008). Multiscale mas modelling to simulate the soil environment: Application to soil ecology. *Simulation Modelling Practice and Theory*, 16(7):736–745.
- Marino, S., El-Kebir, M., and Kirschner, D. (2011). A hybrid multi-compartment model of granuloma formation and t cell priming in tuberculosis. *Journal of Theoretical Biology*.
- Mathieu, J., James, J., Mahoney, P., Boiney, L., Hubbard, R., and White, B. (2007a). Hybrid systems dynamic, petri net, and agent-based modeling of the air and space operations center. http://www.mitre.org/work/tech_papers/tech_papers_07/07_0455/07_0455.pdf.
- Mathieu, J., Melhuish, J., James, J., Mahoney, P., Boiney, L., and White, B. (2007b). Multi-scale modeling of the air operations center. http://www.mitre.org/work/tech_papers/tech_papers_07/06_1497/06_1497.pdf.
- Maturana, H. R. and Varela, F. J. (1980). *Autopoiesis and Cognition The Realization of the Living*, volume 42 of *Boston Studies in the Philosophy of Science*. Springer Berlin Heidelberg.
- Maus, C., John, M., Röhl, M., and Uhrmacher, A. (2008). Hierarchical modeling for computational biology. In Bernardo, M., Degano, P., and Zavattaro, G., editors, *Formal Methods for Computational Systems Biology*, volume 5016 of *Lecture Notes in Computer Science*, pages 81–124. Springer.
- Maus, C., Rybacki, S., and Uhrmacher, A. (2011). Rule-based multi-level modeling of cell biological systems. *BMC systems biology*, 5(1):166–186.
- Michel, F. (2007). The IRM4S model: the influence/reaction principle for multiagent based simulation. In *Proc. of 6th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2007)*, pages 1–3.
- Michel, F., Gouaïch, A., and Ferber, J. (2003). Weak interaction and strong interaction in agent based simulations. In *Multi-Agent-Based Simulation III*, volume 2927 of *Lecture Notes in Computer Science*, pages 43–56. Springer.
- Minar, N., Burkhart, R., Langton, C., and Askenazi, M. (1996). The swarm simulation system: A toolkit for building multi-agent simulations. Technical Report 96-06-042, Santa Fe Institute.

- Moncion, T., Amar, P., and Hutzler, G. (2010). Automatic characterization of emergent phenomena in complex systems. *Journal of Biological Physics and Chemistry*, 10:16–23.
- Montagna, S., Donati, N., and Omicini, A. (2010a). An agent-based model for the pattern formation in *drosophila melanogaster*. *Artificial Life XII*, pages 110–117.
- Montagna, S., Omicini, A., and Ricci, A. (2010b). A multi-scale agent-based model of morphogenesis in biological systems. In Omicini, A. and Viroli, M., editors, *Proceedings of 11^o Workshop nazionale "Dagli Oggetti agli Agenti" WOA 2010*, Rimini, Italy.
- Morin, E. (1992). *Method: Towards a Study of Humankind*, volume 1. Peter Lang Pub Inc.
- Morvan, G., Dupont, D., Soye, J.-B., and Merzouki, R. (2012). Engineering hierarchical complex systems: an agent-based approach – the case of flexible manufacturing systems. In *Service Orientation in Holonic and Multi Agent Manufacturing Control*, volume 402 of *Studies in Computational Intelligence*. Springer.
- Morvan, G. and Jolly, D. (2012). Multi-level agent-based modeling with the Influence Reaction principle. *CoRR*, abs/1204.0634.
- Morvan, G., Jolly, D., Veremme, A., Dupont, D., and Charabidze, D. (2008). Vers une méthode de modélisation multi-niveaux. In *Actes de la 7^{ème} Conférence de Modélisation et Simulation MOSIM, Paris, France*, volume 1, pages 167–174.
- Morvan, G., Veremme, A., and Dupont, D. (2011). IRM4MLS: the influence reaction model for multi-level simulation. In Bosse, T., Geller, A., and Jonker, C., editors, *Multi-Agent-Based Simulation XI*, volume 6532 of *Lecture Notes in Artificial Intelligence*, pages 16–27. Springer.
- Morvan, G., Veremme, A., Dupont, D., and Jolly, D. (2009). Modélisation et conception multiniveau de systèmes complexes : stratégie d'agentification des organisations. *Journal Européen des Systèmes Automatisés*, 43(4-5):381–406.
- Müller, J.-P. (2009). Towards a formal semantics of event-based multi-agent simulations. In David, N. and Sichman, J., editors, *Multi-Agent-Based Simulation IX*, volume 5269 of *Lecture Notes in Computer Science*, pages 110–126. Springer.
- Müller, J.-P. and Aubert, S. (2011). L'ontologie pour construire une représentation multi-niveau de et par les systèmes sociaux. In *Rencontres interdisciplinaires de Rochebrune sur les systèmes complexes naturels et artificiels*.
- Müller, J.-P. and Diallo, A. (2012). Vers une méthode multi-point de vue de modélisation multi-agent. In *Actes des 20^{èmes} Journées Francophones sur les Systèmes Multi-Agents*, pages 33–42. Cepadues Editions.
- Müller, J.-P., Diallo, A., François, J.-C., Sanders, L., Waldeck, R., and Mathian, H. (2011). Building ontologies from a variety of points of view. In *Proceedings of the 7th European Social Simulation Association Conference*.
- Müller, J.-P., Ratzé, C., Gillet, F., and Stoffel, K. (2005). Modeling and simulating hierarchies using an agent-based approach. In *Proceedings of the MODSIM 2005 International Congress on Modelling and Simulation*, pages 1631–1638.
- Navarro, L., Corruble, V., Flacher, F., and Zucker, J.-D. (2012). Mesoscopic level: A new representation level for large scale agent-based simulations. In *SIMUL 2012, The Fourth International Conference on Advances in System Simulation*, pages 68–73.
- Navarro, L., Corruble, V., and Zucker, J.-D. (2013). A flexible approach to multi-level agent-based simulation with the mesoscopic representation. In *Proc. of 12th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2013)*.
- Navarro, L., Flacher, F., and Corruble, V. (2011). Dynamic level of detail for large scale agent-based urban simulations. In *Proc. of 10th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2011)*, pages 701–708.
- Nguyen, N., Taillandier, P., Drogoul, A., and Auger, P. (2012a). Inferring equation-based models from agent-based models: a case study in competition dynamics. In *Principles and Practice of Multi-Agent Systems*, volume 7455 of *Lecture Notes in Artificial Intelligence*, pages 413–427. Springer.
- Nguyen, T., Zucker, J.-D., Nguyen, D., Drogoul, A., and Vo, A. (2011). Hybrid equation-based and agent-based modeling of crowd evacuation on road network. In *Eighth International Conference on Complex Systems (ICSS)*, pages 558–570.
- Nguyen, T., Zucker, J.-D., Nguyen, D., Drogoul, A., and Vo, A. (2012b). A hybrid macro-micro pedestrians evacuation model to speed up simulation in road networks. In Dechesne, F., Hattori, H., ter Mors, A., Such, J., Weyns, D., and Dignum, F., editors, *Advanced Agent Technology*, volume 7068 of *Lecture Notes in Computer Science*, pages 371–383. Springer.
- North, M., Macal, C., Aubin, J., Thimmapuram, P., Braegen, M., Hahn, J., Karr, J., Brigham, N., Lacy, M., and Hampton, D. (2010). Multiscale agent-based consumer market modeling. *Complexity*, 15(5):37–47.
- Olsen, M. M. and Siegelmann, H. T. (2013). Multiscale agent-based model of tumor angiogenesis. In *International Conference on Computational Science, ICCS 2013*, volume 18 of *Procedia Computer Science*, pages 1026–1035. Elsevier.
- Ozik, J., Sallach, D. L., and Macal, C. M. (2008). Modeling dynamic multiscale social processes in agent-based models. *IEEE Intelligent Systems*, 23(4):36–42.
- Paiva, L., Binny, C., Ferreira Jr., S., and Martins, M. (2009). A multiscale mathematical model for oncolytic virotherapy. *Cancer Research*, 69:1205–1211.
- Parry, H. and Bithell, M. (2012). *Agent-based models of geographical systems*, chapter Large scale agent-based modelling: A review and guidelines for model scaling, pages 271–308. Springer.
- Parunak, H. (2012). Between agents and mean fields. In *Multi-Agent-Based Simulation XII*, volume 7124 of *Lecture Notes in Artificial Intelligence*, pages 113–126. Springer.
- Parunak, H., Bisson, R., and Brueckner, S. (2010). Agent interaction, multiple perspectives, and swarming simulation. In *Proc. of 9th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2010)*, pages 549–556.

- Parunak, H. and Brueckner, S. (2010). Multi-perspective, multi-future modeling and model analysis. In *Proceedings of ICCDM*, Miami, FL.
- Parunak, H., Sauter, J., and Crossman, J. (2009). Multi-layer simulation for analyzing IED threats. In *Technologies for Homeland Security, 2009. HST'09. IEEE Conference on*, pages 323–330. IEEE.
- Picault, S. and Mathieu, P. (2011). An interaction-oriented model for multi-scale simulation. In Walsh, T., editor, *Twenty-Second International Joint Conference on Artificial Intelligence*, pages 332–337, Barcelona, Spain. AAAI Press.
- Poschinger, A., Kates, R., and Keller, H. (2002). Coupling of concurrent macroscopic and microscopic traffic flow models using hybrid stochastic and deterministic disaggregation. *Transportation and Traffic Theory for the 21st century*.
- Prévost, G., Tranouez, P., Lerebourg, S., Bertelle, C., and Olivier, D. (2004). Ecosystem complexity described with ontological tool for a multi-scale, multi-model approaches in distributed environment. In *Jordan International Conference on Computer Sciences and Engineering*, Al-Salt, Jordan.
- Pumain, D. and Louail, T. (2009). Interaction des ontologies informatique et géographique pour simuler les dynamiques multiscalaires. In *XVIèmes rencontres interdisciplinaires de Rochebrune, Ontologies et dynamique des systèmes complexes, perspectives interdisciplinaires*.
- Pumain, D., Sanders, L., Bretagnolle, A., Glisse, B., and Mathian, H. (2009). The future of urban systems: Exploratory models. In Lane, D., Pumain, D., der Leeuw, S. V., and West, G., editors, *Complexity Perspectives in Innovation and Social Change*, volume 7 of *Methodos Series*, pages 331–360. Springer.
- Railsback, S. and Grimm, V. (2011). *Agent-Based and Individual-Based Modeling: A Practical Introduction*. Princeton University Press.
- Ratzé, C., Gillet, F., Müller, J.-P., and Stoffel, K. (2007). Simulation modelling of ecological hierarchies in constructive dynamical systems. *Ecological Complexity*, 4(1-2):13–25.
- Raub, W., Buskens, V., and van Assen, M. A. (2011). Micro-macro links and microfoundations in sociology. *The Journal of Mathematical Sociology*, 35(1-3):1–25.
- Razavi, S., Gaud, N., Mozayani, N., and Koukam, A. (2011). Multi-agent based simulations using fast multipole method: application to large scale simulations of flocking dynamical systems. *Artificial Intelligence Review*, 35(1):53–72.
- Rejniak, K. and Anderson, A. (2011). Hybrid models of tumor growth. *Wiley Interdisciplinary Reviews: Systems Biology and Medicine*, 3(1):115–125.
- Resnick, M. (1994). *Turtles, termites, and traffic jams: Explorations in massively parallel microworlds*. MIT Press.
- Rounsevell, M., Pedrolí, B., Erb, K., Gramberger, M., Busck, A., Haberl, H., Kristensen, S., Kuemmerle, T., Lavorel, S., Lindner, M., et al. (2012). Challenges for land system science. *Land Use Policy*.
- Sawyer, R. (2001). Simulating emergence and downward causation in small groups. In *Multi-agent-based simulation*, Lecture Notes in Artificial Intelligence, pages 49–67. Springer.
- Sawyer, R. (2003). Artificial societies, multiagent systems and the micro-macro link in sociological theory. *Sociological Methods & Research*, 31(3):325–363.
- Scerri, D., Drogoul, A., Hickmott, S., and Padgham, L. (2010). An architecture for modular distributed simulation with agent-based models. In *Proc. of 9th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2010)*, pages 541–548. International Foundation for Autonomous Agents and Multiagent Systems.
- Schaller, N., Lazrak, E., Martin, P., Mari, J., Aubry, C., and Benoit, M. (2012). Combining farmers' decision rules and landscape stochastic regularities for landscape modelling. *Landscape Ecology*, 27(3):1–14.
- Scheff, J., Mavroudis, P., Foteinou, P., An, G., Calvano, S., Doyle, J., Dick, T., Lowry, S., Vodovotz, Y., and Androulakis, I. (2012). A multiscale modeling approach to inflammation: A case study in human endotoxemia. *Journal of Computational Physics*.
- Scheutz, M., Madey, G., and Boyd, S. (2005). tMANS - the multi-scale agent-based networked simulation for the study of multi-scale, multi-level biological and social phenomena. In *Spring Simulation Multiconference*.
- Schillo, M., Fischer, K., and Klein, C. (2001). The micro-macro link in DAI and sociology. In *Multi-Agent Based Simulation*, volume 1979 of *Lecture Notes in Artificial Intelligence*, pages 133–148. Springer.
- Schmidt, S., Picioreanu, C., Craenen, B., Mackay, R., Kreft, J., and Theodoropoulos, G. (2011). A multi-scale agent-based distributed simulation framework for groundwater pollution management. In *15th International Symposium on Distributed Simulation and Real Time Applications (DS-RT)*, pages 18–27. IEEE.
- Schnell, S., Grima, R., and Maini, P. (2007). Multiscale modeling in biology. new insights into cancer illustrate how mathematical tools are enhancing the understanding of life from the smallest scale to the grandest. *American Scientist*, 95(2):134–142.
- Seal, J., Alverdy, J., Zaborina, O., An, G., et al. (2011). Agent-based dynamic knowledge representation of pseudomonas aeruginosa virulence activation in the stressed gut: Towards characterizing host-pathogen interactions in gut-derived sepsis. *Theoretical Biology and Medical Modelling*, 8(1):33.
- Seck, M. and Honig, H. (2012). Multi-perspective modelling of complex phenomena. *Computational & Mathematical Organization Theory*, 18(1):128–144.
- Seidl, R., Rammer, W., Scheller, R., and Spies, T. (2012). An individual-based process model to simulate landscape-scale forest ecosystem dynamics. *Ecological Modelling*, 231:87–100.
- Seidl, R., Rammer, W., Scheller, R., Spies, T., and Lexer, M. (2010). A mechanistic, individual-based approach to modeling complexity and dynamics of forest ecosystems across scales. *The 95th ESA Annual Meeting*.
- Semeniuk, C., Musiani, M., and Marceau, D. (2011). *Biodiversity*, chapter Integrating Spatial Behavioral Ecology in Agent-Based Models for Species Conservation, pages 3–26. InTech.
- Servat, D. (2000). *Modélisation de dynamiques de flux par agents. Application aux processus de ruissellement, infiltration et érosion*. PhD thesis, Université Paris VI.

- Servat, D., Perrier, E., Treuil, J.-P., and Drogoul, A. (1998a). When agents emerge from agents: Introducing multi-scale viewpoints in multi-agent simulations. In *Multi-Agent Systems and Agent-Based Simulation*, volume 1534 of *Lecture Notes in Computer Science*, pages 183–198. Springer.
- Servat, D., Pierré, E., Treuil, J., and Drogoul, A. (1998b). Towards virtual experiment laboratories : How multi-agent simulations can cope with multiple scales of analysis and viewpoints. In *Virtual Worlds*, volume 1434 of *Lecture Notes in Computer Science*, pages 205–217. Springer.
- Sewall, J., Wilkie, D., and Lin, M. C. (2011). Interactive hybrid simulation of large-scale traffic. *ACM Transaction on Graphics (Proceedings of SIGGRAPH Asia)*, 30(6).
- Sharpanskykh, A. and Treur, J. (2011a). Group abstraction for large-scale agent-based social diffusion models. In *International conference on Privacy, security, risk and trust and international conference on social computing*, pages 830–837. IEEE.
- Sharpanskykh, A. and Treur, J. (2011b). Group abstraction for large-scale agent-based social diffusion models with unaffected agents. In *Agents in Principle, Agents in Practice*, volume 7047 of *Lecture Notes in Artificial Intelligence*, pages 129–142. Springer.
- Shimoni, Y., Nudelman, G., Hayot, F., and Sealton, S. (2011). Multi-scale stochastic simulation of diffusion-coupled agents and its application to cell culture simulation. *PloS one*, 6(12):e29298.
- Shnerb, N., Louzoun, Y., Bettelheim, E., and Solomon, S. (2000). The importance of being discrete: Life always wins on the surface. *Proceedings of the National Academy of Sciences*, 97(19):10322–10324.
- Siebert, J. (2011). *Approche multi-agent pour la multi-modélisation et le couplage de simulations. Application à l'étude des influences entre le fonctionnement des réseaux ambiants et le comportement de leurs utilisateurs*. PhD thesis, Université Henri Poincaré-Nancy I.
- Siebert, J., Ciarletta, L., and Chevrier, V. (2010). Agents and artefacts for multiple models co-evolution. building complex system simulation as a set of interacting models. In *Proc. of 9th Int. Conf. on Autonomous Agents and Multiagent Systems (AAMAS 2010)*, pages 509–516.
- Smallwood, R., Adra, S., and Khodabakshi, G. (2010). Multiscale, multi-paradigm modelling of tissues: embedding development in tissue behaviour. http://www.dcs.shef.ac.uk/~rod/integrative_biology/Smallwood_Cellular_dynamics_and_tissue_behaviour.pdf.
- Smallwood, R. and Holcombe, M. (2006). The epitheliome project: multiscale agent-based modeling of epithelial cells. In *Biomedical Imaging: Nano to Macro, 2006. 3rd IEEE International Symposium on*, pages 816–819. IEEE.
- Solovyev, A., Mikheev, M., Z., L., Dutta-Moscato, J., Ziraldo, C., An, G., Vodovotz, Y., and Mi, Q. (2010). SPARK: A framework for multi-scale agent-based biomedical modeling. *International Journal of Agent Technologies and Systems*, 2(3):18–30.
- Soyez, J.-B., Morvan, G., Dupont, D., and Merzouki, R. (2013). A methodology to engineer and validate dynamic multi-level multi-agent based simulations. In *Multi-Agent-Based Simulation XIII*, volume 7838 of *Lecture Notes in Artificial Intelligence*, pages 130–142. Springer.
- Soyez, J.-B., Morvan, G., Merzouki, R., Dupont, D., and Kubiak, P. (2011). Multi-agent multi-level modeling – a methodology to simulate complex systems. In *Proceedings of the 23rd European Modeling & Simulation Symposium*.
- Squazzoni, F. (2008). The micro-macro link in social simulation. *Sociologica*, 1.
- Steiniger, A., Kruger, F., and Uhrmacher, A. M. (2012). Modeling agents and their environment in multi-level-DEVS. In *Proc. of the Winter Simulation Conference*, pages 1–12. IEEE.
- Stieglmeier, S. M., Giddings, M. C., et al. (2013). Agent-based modeling of competence phenotype switching in *bacillus subtilis*. *Theoretical Biology and Medical Modelling*, 10(1):23.
- Sun, T., Adra, S., Smallwood, R., Holcombe, M., and MacNeil, S. (2009). Exploring hypotheses of the actions of $\text{tgf-}\beta 1$ in epidermal wound healing using a 3d computational multiscale model of the human epidermis. *PloS one*, 4(12):e8515.
- Sun, X., Zhang, L., Tan, H., Bao, J., Strouthos, C., and Zhou, X. (2012). Multi-scale agent-based brain cancer modeling and prediction of tki treatment response: Incorporating egfr signaling pathway and angiogenesis. *BMC bioinformatics*, 13(1):218.
- Tahir, H., Hoekstra, A., Lorenz, E., Lawford, P., Hose, D., Gunn, J., and Evans, D. (2011). Multi-scale simulations of the dynamics of in-stent restenosis: impact of stent deployment and design. *Interface Focus*, 1(3):365–373.
- Taillandier, P., Vo, D.-A., Amouroux, E., and Drogoul, A. (2010). GAMA: bringing GIS and multi-level capabilities to multi-agent simulation. In *European Workshop on Multi-Agent Systems*.
- Taillandier, P., Vo, D.-A., Amouroux, E., and Drogoul, A. (2012). GAMA: A simulation platform that integrates geographical information data, agent-based modeling and multi-scale control. In Desai, N., Liu, A., and Winikoff, M., editors, *Principles and Practice of Multi-Agent Systems*, volume 7057 of *Lecture Notes in Computer Science*, pages 242–258. Springer.
- Thorne, B., Hayenga, H., Humphrey, J., and Peirce, S. (2011). Toward a multi-scale computational model of arterial adaptation in hypertension: verification of a multi-cell agent based model. *Frontiers in Physiology*, 2.
- Torii, D., Ishida, T., Bonneaud, S., and Drogoul, A. (2005). Layering social interaction scenarios on environmental simulation. In *Multi-Agent and Multi-Agent-Based Simulation*, volume 3415 of *Lecture Notes in Artificial Intelligence*, pages 78–88. Springer.
- Tranouez, P. (2005). *Contribution à la modélisation et à la prise en compte informatique de niveaux de descriptions multiples. Application aux écosystèmes aquatiques (Penicillo haere, nam scalas aufero)*. PhD thesis, Université du Havre.
- Tranouez, P., Bertelle, C., and Olivier, D. (2001). Changing the level of description of a fluid flow in agent-based simulation. In *ESS Conference*.

- Tranouez, P., Bertelle, C., and Olivier, D. (2006). *Emergent properties in natural and artificial dynamical systems*, chapter Changing levels of description in a fluid flow simulation, pages 87–99. Springer.
- Tranouez, P. and Dutot, A. (2009). Different goals in multiscale simulations and how to reach them. In *Complex Systems and Self-organization Modelling*, Understanding Complex Systems, pages 29–39. Springer.
- Tranouez, P., Lerebourg, S., Bertelle, C., and Olivier, D. (2003). Contribution à la représentation multi-échelle des écosystèmes aquatiques. *Technique et Science Informatiques*, 22(4):255–259.
- Treuil, J.-P., Drogoul, A., and Zucker, J.-D. (2008). *Modélisation et simulation à base d'agents*. Dunod.
- Uhrmacher, A. M., Ewald, R., John, M., Maus, C., Jeschke, M., and Biermann, S. (2007). Combining micro and macro-modeling in DEVS for computational biology. In *Proceedings of the 39th conference on Winter simulation*, pages 871–880.
- Vincenot, C., Giannino, F., Rietkerk, M., Moriya, K., and Mazzoleni, S. (2011). Theoretical considerations on the combined use of system dynamics and individual-based modeling in ecology. *Ecological Modelling*, 222(1):210–218.
- Vo, A. (2012). *An operational architecture to handle multiple levels of representation in agent-based models*. PhD thesis, Université Paris VI.
- Vo, D.-A., Drogoul, A., and Zucker, J.-D. (2012a). An operational meta-model for handling multiple scales in agent-based simulations. In *International Conference on Computing and Communication Technologies, Research, Innovation, and Vision for the Future (RIVF)*, pages 1–6, Ho Chi Minh City. IEEE.
- Vo, D.-A., Drogoul, A., Zucker, J.-D., and Ho, T.-V. (2012b). A modelling language to represent and specify emerging structures in agent-based model. In Desai, N., Liu, A., and Winikoff, M., editors, *Principles and Practice of Multi-Agent Systems*, volume 7057 of *Lecture Notes in Computer Science*, pages 212–227. Springer.
- Vodovotz, Y., Csete, M., Bartels, J., Chang, S., and An, G. (2008). Translational systems biology of inflammation. *PLoS Comput Biol*, 4(4):e1000014.
- Wakeland, W., Macovsky, L., and An, G. (2007). A hybrid simulation model for studying acute inflammatory response. In *Proceedings of the 2007 spring simulation multiconference*, volume 2 of *SpringSim '07*, pages 39–46. Society for Computer Simulation International.
- Wang, J., Zhang, L., Jing, C., Ye, G., Wu, H., Miao, H., Wu, Y., and Zhou, X. (2013). Multi-scale agent-based modeling on melanoma and its related angiogenesis analysis. *Theoretical Biology and Medical Modelling*, 10(1):41.
- Wang, Z., Birch, C., and Deisboeck, T. (2008). Cross-scale sensitivity analysis of a non-small cell lung cancer model: linking molecular signaling properties to cellular behavior. *Biosystems*, 92(3):249–258.
- Wang, Z. and Deisboeck, T. (2008). Computational modeling of brain tumors: discrete, continuum or hybrid? *Scientific Modeling and Simulation*, 15(1):381–393.
- Wang, Z., Zhang, L., Sagotsky, J., and Deisboeck, T. (2007). Simulating non-small cell lung cancer with a multiscale agent-based model. *Theoretical Biology and Medical Modelling*, 4.
- Wedde, H. and Senge, S. (2012). 2-way evaluation of the distributed BeeJamA vehicle routing approach. In *Proceedings of the IEEE Intelligent Vehicles Symposium*, pages 205–210.
- White, B. (2007). On interpreting scale (or view) and emergence in complex systems engineering. In *Systems Conference, 2007 1st Annual IEEE*, pages 1–7. IEEE.
- Xi, H. and Son, Y.-J. (2012). Two-level modeling framework for pedestrian route choice and walking behaviors. *Simulation Modelling Practice and Theory*, 22:28–46.
- Zahedmanesh, H. and Lally, C. (2012). A multiscale mechanobiological modelling framework using agent-based models and finite element analysis: application to vascular tissue engineering. *Biomechanics and Modeling in Mechanobiology*, 11:363–377.
- Zeigler, B., Kim, T., and Praehofer, H. (2000). *Theory of Modeling and Simulation*. Academic Press, 2nd edition.
- Zhang, L., Athale, C., and Deisboeck, T. (2007). Development of a three-dimensional multiscale agent-based tumor model: Simulating gene-protein interaction profiles, cell phenotypes and multicellular patterns in brain cancer. *Journal of Theoretical Biology*, 244(1):96–107.
- Zhang, L., Chen, L., and Deisboeck, T. (2009a). Multi-scale, multi-resolution brain cancer modeling. *Mathematics and computers in simulation*, 79(7):2021–2035.
- Zhang, L., Jiang, B., Wu, Y., Strouthos, C., Sun, P., Su, J., and Zhou, X. (2011). Developing a multiscale, multi-resolution agent-based brain tumor model by graphics processing units. *Theoretical Biology and Medical Modelling*, 8(1):46.
- Zhang, L., Wang, Z., Sagotsky, J., and Deisboeck, T. (2009b). Multiscale agent-based cancer modeling. *Journal of Mathematical Biology*, 48(4–5):545–559.