

# Current and future chemical treatments to fight biodeterioration of outdoor building materials and associated biofilms: moving away from ecotoxic and towards efficient, sustainable solutions

Mattea Romani, Thomas Warscheid, Lionel Nicole, Lionel Marcon, Patrick Di Martino, Marcelino T Suzuki, Philippe Lebaron, Raphaël Lami

#### ▶ To cite this version:

Mattea Romani, Thomas Warscheid, Lionel Nicole, Lionel Marcon, Patrick Di Martino, et al.. Current and future chemical treatments to fight biodeterioration of outdoor building materials and associated biofilms: moving away from ecotoxic and towards efficient, sustainable solutions. Science of the Total Environment, 2022, 802, pp.149846. 10.1016/j.scitotenv.2021.149846. hal-03328324

# HAL Id: hal-03328324 https://hal.sorbonne-universite.fr/hal-03328324

Submitted on 29 Aug 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

- 1 Current and future chemical treatments to fight biodeterioration of outdoor
- 2 building materials and associated biofilms: moving away from ecotoxic and
- 3 towards efficient, sustainable solutions.
- 4 Mattea Romani<sup>1</sup>, Thomas Warscheid<sup>2</sup>, Lionel Nicole<sup>3</sup>, Lionel Marcon<sup>1</sup>, Patrick Di Martino<sup>4</sup>,
- 5 Marcelino T. Suzuki<sup>1</sup>, Philippe Lebaron<sup>1</sup>, Raphaël Lami<sup>1\*</sup>
- 6 Corresponding author: \*raphael.lami@obs-banyuls.fr
- 7 ¹ Sorbonne Université, CNRS, Laboratoire de Biodiversité et Biotechnologies Microbiennes
- 8 (LBBM), Observatoire Océanologique de Banyuls sur Mer, Avenue Pierre Fabre, 66650
- 9 Banyuls-sur-Mer, France.
- 10 <sup>2</sup> LBW-Bioconsult, Schwarzer Weg 27, 26215 Wiefelstede, Deutschland
- 11 <sup>3</sup> Sorbonne Université, CNRS, Laboratoire de chimie de la matière condensée de Paris
- 12 (LCMCP), 4 Place Jussieu, 75005 Paris, France.
- <sup>4</sup> Université de Cergy-Pontoise, Laboratoire ERRMECe, Université de Cergy-Pontoise, rue
- Descartes site de Neuville-sur-Oise, 95031 Cergy-Pontoise, France.

15

- Running title: antifouling and biodeterioration: a review
- 17 Submitted to Science of the Total Environment **REVISION 2**

18

#### Abbreviations

AHL: acyl-homoserine lactone – AOP: advanced oxidation process – ATMAC: alkyl trimethylammonium compounds – BAC: benzalkonium chloride – BIT: 1,2-benzisothiazol-3(2H)-one – BPR: Biocidal Products Regulation – CMC: critical micelle concentrations – CMIT: 5-5-chloro-2-methyl-2H-isothiazol-3-one – DB: benzalkonium bromide – DCOIT: 4,5-dichloro-2-octyl-2H-isothiazol-3-one – DDMAC: didecyldimethylammonium chloride – DMSO: dimethyl sulfoxide – ECHA: European Chemicals Agency – ENT: eye nose throat – EO: essential oil – EU: European Union – FDA: Food and Drug Administration – FHWA: Federal Highway Administration – ILs: ionic liquids – IT: isothiazolinone – MIC: microbial induced corrosion – MIT: 2-methyl-2H-isothiazol-3-one – *MRSA*: Methicillin-resistant *Staphylococcus aureus* – MVOC: microbial volatile organic compounds – NACE: National Association of Corrosion Engineers – OEO: oregano essential oil – OIT: 2-octyl-2H-isothiazol-3-one – PAMAM: quaternary ammonium functionalized polyamidoamine – PT: product type – QAC: quaternary ammonium compound – QS: quorum sensing – ROS: reactive oxygen species – SAILs: surface active ionic liquids – TiO<sub>2</sub>: titanium dioxide – ZnO: zinc oxide.

# 19 <u>Table of content</u>

20	Abstract	4
21	Keywords	5
22	1. Introduction	5
23	2. Mechanical cleaning approaches	
24	3. The extensive use of wide-spectrum bioci	des10
25	3.1 Isothiazolinones	10
26	☐ 3.1.1 Nature and commercially available co	mpounds 10
27	□ 3.1.2 Historical and current use	11
28	□ 3.1.3 Efficacy	11
29	☐ 3.1.4 Advantages and drawbacks	12
30	□ 3.1.5 Future and perspectives	14
31	3.2 Quaternary ammonium compounds	14
32	☐ 3.2.1 Nature and commercially available co	empounds
33	☐ 3.2.2 Historical and current use	15
34	□ 3.2.3 Efficacy	16
35	☐ 3.2.4 Advantages and drawbacks	17
36	□ 3.2.5 Future and perspectives	
37	3.3 Other types of widely-used biocides	19
38	□ 3.3.1 Sodium hypochlorite	19
39	□ 3.3.2 Acid compounds	20
40	☐ 3.3.3 Chlorinated phenol compounds	20
41	☐ 3.3.4 Other compounds broad-spectrum bio	cides
42	3.4 Innovative use of biocides	21

43	3.5 Conclusions about the usage of biocides to prevent biodeterioration of building	
44	materials	22
45	4. Water-repellent compounds and surfaces offer interesting antifouling properties	s 23
46	4.1 Conventional water-repellent treatments	24
47	☐ 4.1.1 Nature and commercially available compounds	24
48	☐ 4.1.2 Historical and current use	26
49	□ 4.1.3 Efficacy	27
50	☐ 4.1.4 Advantages and drawbacks	27
51	□ 4.1.5 Future and perspectives	29
52	4.2 The case of superhydrophobic materials	30
53	☐ 4.2.1 Nature and commercially available compounds	30
54	☐ 4.2.2 Historical and current use	31
55	□ 4.2.3 Efficacy	32
56	☐ 4.2.4 Advantages and drawbacks	32
57	☐ 4.2.5 Future and perspectives	33
58	5. The efficacy of the photocatalysis mechanisms	33
59	☐ 5.1. Nature and commercially available compounds	34
60	□ 5.2 Historical and current use	34
61	□ 5.3 Efficacy	35
62	□ 5.4 Advantages and drawbacks	35
63	□ 5.5 Future and perspectives	36
64	6. Ionic liquids: promising eco-friendly synthetic molecules	37
65	7. "Natural compounds": on the path to the discovery of sustainable antifoulings?	39
66	7.1 Plants and essential oils	40
67	☐ 7.1.1 Nature and commercially available compounds	40
68	□ 7.1.2 Historical and current use	40
69	□ 7.1.3 Efficacy	41

70	□ 7.1.4 Advantages and drawbacks			
71	□ 7.1.5 Future and perspectives			
72	7.2 "Natural" compounds: conclusions43			
73	8. Future research and development strategies to develop "green" and sustainable			
74	antifouling for building materials?44			
75	9. Conclusions: A toolbox and methodology for the development of innovative, efficient,			
76	and eco-friendly solutions: case by case analysis, multidisciplinary, integrative, and			
77	pragmatic approaches			
78	Credit authorship contribution statement50			
79	Acknowledgments50			
80	References51			
81	Figures			
82				
83	Abstract			
84	All types of building materials are rapidly colonized by microorganisms, initially through			
85	an invisible and then later a visible biofilm that leads to their biodeterioration. Over centuries,			
86	this natural phenomenon has been managed using mechanical procedures, oils, or even wax. In			
87	modern history, many treatments such as high-pressure cleaners, biocides (mainly			
88	isothiazolinones and quaternary ammonium compounds) are commercially available, as well			
89	as preventive ones, such as the use of water-repellent coatings in the fabrication process. While			
90	all these cleaning techniques offer excellent cost-benefit ratios, their limitations are numerous.			
91	Indeed, building materials are often quickly recolonized after application, and microorganisms			
92	are increasingly reported as resistant to chemical treatments. Furthermore, many antifouling			

compounds are ecotoxic, harmful to human health and the environment, and new regulations tend to limit their use and constrain their commercialization. The current state-of-the-art highlights an urgent need to develop innovative antifouling strategies and the widespread use of safe and eco-friendly solutions to biodeterioration. Interestingly, innovative approaches and compounds have recently been identified, including the use of photocatalysts or natural compounds such as essential oils or quorum sensing inhibitors. Most of these solutions developed in laboratory settings appear very promising, although their efficiency and ecotoxicological features remain to be further tested before being widely marketed. This review highlights the complexity of choosing the adequate antifouling compounds when fighting biodeterioration and proposes developing case-to-case innovative strategies to raise this challenge, relying on integrative and multidisciplinary approaches.

# **Keywords**

biodeterioration, building materials, cleaning procedures, biocides, water-repellents, natural compounds

#### 1. Introduction

Biodeterioration of mineral building materials (*i.e.*, stone, ceramics, cement, concrete) is a global and expensive problem for manufacturers and building owners (Romani et al., 2019; Saiz-Jimenez, 2001; Warscheid and Braams, 2000). Biodeterioration consists of the natural degradation of these materials by (micro)organisms (Guiamet et al., 2013; Warscheid and Braams, 2000), which grow as multispecies biofilms that develop on all types of surfaces (Di Martino, 2016; Romani et al., 2019). Such biofilms are usually composed of multiple interacting microorganisms (bacteria, fungi, algae) (Krakova et al., 2015) embedded in a

protective and very resistant polymeric matrix (Figure 1) (Flemming and Wingender, 2010). Vital microbial activities, such as cell division, biofilm formation, acid production, and redox activities, lead to the long-term degradation of materials (Guiamet et al., 2013). This phenomenon is also known as microbiologically-influenced or microbially-induced corrosion (MIC) (Enning and Garrelfs, 2014). Biofilms that grow on building materials are initially invisible but turn visible with time, as their development leads to thick and pigmented structures. Finally, the last step of biodeterioration implicates the colonization of such a mature biofilm by mosses or higher plants, especially on stones (Coutinho et al., 2015; Gulotta et al., 2018; Li et al., 2018; Q. Li et al., 2016; Norma Italiana UNI 11182, 2006).

According to the building materials industry, the first problem with microbial colonization is its unsightly aspect (Coutinho et al., 2015; Di Martino, 2016). Indeed, the biofilm that develops on the materials is often pigmented, which forms unaesthetic dark or green streaks or spots (Di Martino, 2016), which is undesirable since customers expect their product to stay stable over time (The Brick Industry Association, 2018). The unaesthetic aspect of the darkening of buildings and other materials is also an essential aspect of historic monument conservation (Di Martino, 2016; Grabek-Lejko et al., 2017; Saiz-Jimenez, 2001). Therefore, manufacturers of building materials invest massively in strategies to prevent their products to rapidly turn green or black, and building owners face significant expenses to clean and restore materials that have deteriorated over time. Thus, in addition to the unsightly appearance, biodeterioration causes less visible but more significant damages, including the modification or loss of physical properties of many types of materials (Coutinho et al., 2015). Indeed, as the biofilm grows, surface and deep cracks increasing the porosity of materials are observed (Berdahl et al., 2008; Coutinho et al., 2015). In addition, this increased porosity facilitates the colonization of materials by other microorganisms and promotes their growth. Furthermore, many colonizing microorganisms accelerate deterioration due to the metabolites they produce,

such as organic acids (Dubosc, 2000). Overall, the weakening of materials caused by biofilms development leads to faster decay by accelerating the effects of rain or freeze/thaw events (Berdahl et al., 2008; Gladis and Schumann, 2011; Joseph, 2021). Finally, advanced biodeterioration results in the loss of the structural or thermal insulation, drainage, or solar reflectance (proportion of light reflected from the surface of a material) of the materials (Berdahl et al., 2008; Pena-Poza et al., 2018).

Because of the aesthetic issues they cause and their impact on the durability of materials described above, biofilms colonizing building materials must be regularly eliminated (Tiano, 2016). Cleaning techniques have been developed over centuries (Cappitelli et al., 2020; Sanmartín et al., 2018), and some were even reported and documented in antiquity (Plinius Secundus, 77AD; Vitruvius Pollio, 27BC). Such mechanical cleaning strategies are still widely used even though they slowly disappear nowadays to favor low-cost and efficient chemical compounds. However, these latest treatments have a high environmental and economic cost due to their intensive (Scheerer et al., 2009). For example, biocides applied on façades and roofs runoff in soils and are frequently persistent in the environment. Many (like terbutryn or isoproturon) are poorly biodegradable and lead to long-term soil and water pollution (Bollmann et al., 2017; Chand et al., 2018). Also, the degradation products issued from these biocides remain poorly understood and are suspected to be extremely ecotoxic (Paijens et al., 2020). Finally, these marketed broad-spectrum and harsh biocides cause human health issues for customers, especially when used without basic personal protections (Garcia-hidalgo et al., 2016; Wieck et al., 2018, 2016).

The ecotoxicity of commercial large-spectrum and aggressive biocides is a significant factor associated with their use on outdoor building materials, and the regulations concerning these compounds are increasingly restrictive (Scheerer et al., 2009; Tiano, 2016; Warscheid and Braams, 2000). The biocidal products that can be used for preventive or curative treatments of

outdoor building materials are classified in product type (PT) 2 of main group 1 corresponding to disinfectants, and PT 10 of main group 2 corresponding to preservatives in annex V to the Biocidal Products Regulation (BPR), Regulation (EU) 528/2012 (Commission Européenne, 2012). All these products target both microbial and algal organisms. While the costs of the fight against biodeterioration are challenging to evaluate, they will undoubtedly rise in the future since it will include not only the cost of treatments (i.e., biocides, paints) but also the costs associated with their application in safe conditions for customers and likely the costs associated with their environmental impact (Gaylarde et al., 2003; Guézennec, 2017).

This review aims to provide a comprehensive understanding of the different commercially available methods to clean outdoor building materials, focusing on chemical treatment strategies as well as their environmental and health impacts. We will discuss the potential of future and more eco-friendly solutions leading to "greener" and sustainable antifouling compounds and strategies, even though most of these upcoming solutions still require a wider efficacy and more thorough ecotoxicological evaluations. Overall, our primary goal is to provide a case-by-case analysis of chemical control strategies against biodeterioration of outdoor building materials based on multidisciplinary approaches combining the viewpoint of microbiologists, eco-toxicologists, chemists, and material engineers.

# 2. Mechanical cleaning approaches

Building materials have always biodeteriorated over time, and over centuries humankind has tried to prevent or limit this phenomenon. For example, the famous French architect Viollet-le-Duc reported on the preoccupation with tile colonization since the 10th century. Also, he pointed out that as early as the 11th century that the shape of the tiles in the North of France (plain) was different from that of the South (barrel) to limit the development of "mosses and vegetation" (Viollet-le-Duc, 1854).

Mechanical cleaning has been, since, the first type of treatment applied to building materials to remove the deteriorating biofilm and is currently often conducted before chemical treatments (Table 1). The utilization of water pressure and steam systems is the widest spread and easy to employ. They have shown their efficacity on various types of microorganisms, such as Apatococcus lobatus (Sanmartín et al., 2020). However, if these methods are efficient in the short term on superficial biofilms, they can also spread the microorganisms on the substrate (Favero-Longo and Viles, 2020). In addition, a difficulty associated with these strategies is to correctly adjust the water pressure, which must be sufficient to remove the biofilm but not too high and leading to the degradation of the materials (Slaton and Normandin, 2005). Abrasive systems are another mechanical strategy employed to clean the materials through abrasion, roughening, or erosion (Table 1). For example, sandblasting methods have shown their efficiency on lichens as *Diploschistes scruposus* (Pozo-Antonio et al., 2021). Unfortunately, these methods also damage building materials: high-pressure sand or grit blasting are no longer used to restore historic buildings because of their induced severe damages (Slaton and Normandin, 2005). For the cleaning of historical monuments, other mechanical methods based on lasers are sometimes applied (Di Martino, 2016). These devices operate by applying a laser in a pulse frequency while the output power is controlled (Slaton and Normandin, 2005). The use of these lasers on objects and monuments has shown promise (Table 1). For instance, laser cleaning is efficient on black removal, including *Desulfovibrio desulfuricans* (Elhagrassy et al., 2018); Verrucaria nigrescens (Speranza et al., 2013), Circinaria hoffmanniana (Pozo-Antonio et al., 2019). However, their large-scale application has so far been minimal, partly due to the high costs (Di Martino, 2016; Slaton and Normandin, 2005). Their use has other drawbacks since it does not eliminate the encrusted part of the biofilm. Even worse, laser treatment can increase the porosity of materials such as tiles, facilitating their recolonization (Barberousse et al., 2006; Di Martino, 2016).

192

193

194

195

196

197

198

199

200

201

202

203

204

205

206

207

208

209

210

211

212

213

214

215

216

# 3. The extensive use of wide-spectrum biocides.

According to the BPR, Regulation (EU) 528/2012, biocidal products are substances or mixtures used to destroy, prevent the action of, or exert a controlling effect on harmful organisms by a mechanism that is not purely physical or mechanical (Commission Européenne, 2012). In this review, biocides will be defined as chemical molecules that are widely and commonly used to kill and remove macro- and microorganisms on the surfaces of building materials. As described below, it is worth noting that the same families of biocides are used in a wide variety of industrial fields and also in the household (*i.e.*, cosmetic, medical care, food industry, metalworking fluids, building cleaning, etc.). The market for these antiseptics and disinfectants never ceases to grow, and customer demand is continuously increasing. For instance, it was expected in 2016 that this market will increase by more than 6 % (Merchel Piovesan Pereira and Tagkopoulos, 2019) and will generate more than US\$8.1 billion by 2021 (Zion Market Research, 2016). However, the use of biocides is also increasingly being questioned, as more and more research and publications are demonstrating their toxic effects on humans and the environment.

#### 3.1 Isothiazolinones

#### • 3.1.1 Nature and commercially available compounds

The isothiazolinones (ITs) constitute a major class of antifouling and biocides compounds used to treat biofilms growing on building materials chemically (Table 1). ITs are sometimes used as reference biocides to test the efficacy of new antimicrobials for the treatment of biodeteriorated stones (Boccalon et al., 2021). ITs are heterocyclic organic compounds containing vicinal sulfur and nitrogen atoms. The four most commonly used molecules in these products are 2-methyl-2H-isothiazol-3-one (MIT, CAS: 2682-20-04), 5- 5-chloro-2-methyl-2H-isothiazol-3-one (CMIT, CAS: 26172-55-4), 1,2-benzisothiazol-3(2H)-one (BIT, CAS:

242 2634-33-5) and 2-octyl-2H-isothiazol-3-one (OIT, CAS: 26530-20-1) (Table 2) (Garcia-243 hidalgo et al., 2016). These compounds are found in common commercially available products 244 to treat and prevent biodeterioration, such as Biotin R (CTS) or Algicid-Plus (Keim).

#### • 3.1.2 Historical and current use

ITs have been marketed since the 1970s as cleaning chemicals for home or professional usage, as well as preservatives, and these applications are still ubiquitous (Schwensen and Johansen, 2018). ITs can be used directly for their biocide effects as in household products (laundry, detergents) and marine antifouling paints (Amara et al., 2018; Batista-Andrade et al., 2018; Callow and Callow, 2011; Soroldoni et al., 2017), but also as preservatives in products containing water such as cosmetics and personal care products (i.e., shower gels, soaps, creams, infant products) (Garcia-hidalgo et al., 2016; Wieck et al., 2018). This domestic application is responsible for a large part of releasing these compounds into the environment and the environmental impact (Wieck et al., 2018).

Finally, ITs are very frequently used to prevent the biodeterioration of buildings, roofs, stones, and facades. For example, ITs and especially OIT and its derivative the 4,5-dichloro-2-octyl-2H-isothiazol-3-one (DCOIT, CAS: 64359-81-5) are utilized in paints that are sold to protect house facades (Vermeirssen et al., 2018), such as Lichenicida 468 (Bresciani) (Favero-Longo et al., 2017) or Algi 201 (Algimouss Pro, ITs concentration 0.45%). They can be employed alone or combined with other antifouling compounds, such as quaternary ammonium compounds (see below).

#### • 3.1.3 Efficacy

ITs are wide-spectrum biocidal molecules, particularly effective in combating the biodeterioration of building materials. They are typically reported as more bioactive when compared to quaternary ammoniums (benzalkonium chloride), especially at low (<5%) concentration ranges (Favero-Longo et al., 2018). The biocidal efficiency of ITs is based on

their electrophilic nature. They are transported into cells by active transport, where they interfere with many cell processes (Williams, 2007). In particular, ITs block O<sub>2</sub> consumption of cells, and consequently, all aerobic processes cease; energy production (ATP) is reduced, slowing down metabolism and growth (Williams, 2007). ITs also inhibit several types of enzymes, including dehydrogenases (*i.e.*, pyruvate, NADH-, lactate dehydrogenase) as well as the adenosine triphosphatase. The inhibition of these enzymes interrupts the TCA cycle, thus perturbating the entire cell metabolism (Williams, 2007). Besides, ITs also oxidizes thiol-containing cytoplasmic and membrane-bound molecules, including those in numerous enzymes' active sites (Williams, 2007). These oxidations also lead to inhibition of metabolism (Favero-Longo et al., 2018). Collectively, all these effects induced by ITs actively damage cells, leading to the production of many free radicals or reactive oxygen species (ROS), which, combined with the inhibition of cell repair mechanisms, quickly leads to the death of (micro)organisms (Williams, 2007).

#### • 3.1.4 Advantages and drawbacks

One of the major advantages of ITs is that they act on a wide range of (micro)organisms (*i.e.*, bacteria, fungi, lichens, algae) over a wide pH range (pH 1 to 11) (Favero-Longo et al., 2017; Garcia-hidalgo et al., 2016; Silva et al., 2020). Thus, these compounds can attack very diverse types of multispecies biofilms under numerous environmental conditions. For example, ITs are efficient on filamentous fungi such as *Cladosporium* sp., *Penicillium* sp., and *Fusarium* sp.; but ITs are not effective on cyanobacteria (Table 1) (Barrionuevo and Gaylarde, 2011). As preservatives, the MIT/CMIT combination is one of the most cost-effective solutions currently known (Karsa and Ashworth, 2007). However, some commercial products containing ITs may cause alterations to stone, especially limestone and granite surfaces, after application (Tirado Hernández et al. 2015; Sanmartín et al. 2020). Moreover, the safety of these products has now been questioned by different studies (Thomsen et al., 2018; Wieck et al., 2016). ITs are known

to be responsible for contact allergies, called contact dermatitis (Garcia-hidalgo et al., 2016). Humankind is increasingly affected by ITs but understanding this impact remains challenging to estimate due to the diversity of exposure sources (Garcia-hidalgo et al., 2016; Wieck et al., 2018, 2016). For instance, occupational sources of exposure remain difficult to determine due to the lack of information on the composition of marketed products (Garcia-Hidalgo et al., 2018; Ripert et al., 2012).

292

293

294

295

296

297

298

299

300

301

302

303

304

305

306

307

308

309

310

311

312

313

314

315

316

Though, the safety of these molecules must be reassessed and challenged with the deployment of wider ecotoxicological testings. However, the current state of affairs suggests that their usage will be reduced in the future (Wieck et al., 2016). Since 2016 the European Union (EU) and Swiss legislations are quite restrictive for cosmetics use. Commission Regulation (EU) 2017/1224 of 6 July 2017 limits the usage of MIT at 0,0015% (15 ppm) in rinse-off products and prohibits its use in leave-on products; BIT and OIT are now totally forbidden (European Commission, 2017a; Garcia-Hidalgo et al., 2018). Further, ITs are considered as "Dangerous Substances" by the EU Ecolabel criteria [EU. Substances Rendering Goods Ineligible for EU Ecolabel, Art. 6(6), Reg. 66/2010/EC, L 27/1, 30 January 2010 (T. 3 of Anx VI to CLP; Candidate List of SVHCs)]. For example, the EU Ecolabel criteria for hard surface cleaning products limit MIT and BIT concentrations at 0,0050% and CMIT at 0,0015% weight by weight (Commission Decision (EU) 2017/1217 of 23 June 2017) (European Commission, 2017b). Contrastingly, currently, there are no regulations for using ITs to prevent building biodeterioration, and the estimated employed concentrations are higher than 0.5% (5 000 ppm) in most commercially available products (Garcia-Hidalgo et al., 2018). Moreover, ecotoxicological evaluations have recently reported the high toxicity of OIT and DCOIT against environmental bacteria leaching from facade paints, demonstrating potential deleterious effects on biodiversity and ecosystems (Vermeirssen et al., 2018). In addition, photodegradation products of ITs were found more toxic than ITs themselves in a few studies (Varga et al., 2020),

which is very concerning given their extensive applications on outdoor building materials (Vermeirssen et al., 2018). However, ecotoxicity studies concerning degradation products available today are scarce, and further investigations should be conducted to better characterize the potential cytotoxic effects of ITs.

## • 3.1.5 Future and perspectives

317

318

319

320

321

322

323

324

325

326

327

328

329

330

331

332

333

334

335

336

337

338

339

340

341

The 2016 changes in EU cosmetic legislation seemed to stabilize the occurrence of contact allergic reactions to MIT and CMIT (Garcia-Hidalgo et al., 2018; Wieck et al., 2018). Nevertheless, the widespread use of OIT and the lesser-studied DCOIT by the chemical industry could lead to a new contact dermatitis outbreak (Herman et al., 2019). Moreover, crossreactions between MIT and OIT may occur (i.e., exposure to OIT may induce allergic reactions to MIT that would not occur without this sensitization) (Aerts et al., 2017). Therefore, new regulations to limit the usage of ITs as anti-biodeterioration agents are expected in a near future, and this risk has to be considered by the industry before expanding the commercialization of these products. To address these concerns, the concentrations of these compounds should also be reduced in marketed products, for example, by the combined use with other less toxic biocides. Such modifications are essential for manufacturers to anticipate and adapt their industrial processes for potential upcoming legislative changes and develop greener and sustainable industrial processes and compounds. In the same vein, more studies evaluating the ecotoxicological risks of these molecules are needed, and recommendations towards using adapted protective devices when spraying such products on buildings have also to be reinforced to protect customer's health.

#### 3.2 Quaternary ammonium compounds

#### • 3.2.1 Nature and commercially available compounds

Quaternary ammonium compounds (QACs) are the most commonly used biocides after ITs (Table 1). QACs are composed of a quaternary nitrogen atom surrounded by four organic

functional groups, so the nitrogen is permanently positively charged (Mulder et al., 2017). An anion balances this charge, usually a chloride or bromide ion, and therefore, OACs exist in the form of water-soluble salts (Mulder et al., 2017; Nunez et al., 2004). The functional groups (R) include at least one long-chain alkyl group, while the others are methyl, benzyl, or ester groups (Tezel and Pavlostathis, 2011). The most commonly employed biocide QACs are benzalkonium chloride (BAC, CAS: 121-54-0) (Gadea et al., 2017a; Mulder et al., 2017; Nuńez et al., 2004); benzalkonium bromide (DB, CAS: 91080-29-4) (Gadea et al., 2017a), didecyldimethylammonium chloride (DDMAC, CAS: 7173-51-5) (Nuńez et al., 2004), alkyl CAS: dimethylbenzyl ammonium chloride (ADMAC, 8001-54-5), and alkyl trimethylammonium compounds (ATMAC, CAS: 61789-18-2) (Table 2) (Mulder et al., 2017; Nunez et al., 2004). In BAC-homolog compounds, the nitrogen atom is surrounded by a benzyl group, two methyl groups, and an alkyl chain of variable length (C8 to C18). The highest biocidal activity is associated with C12-C14 homologs, which are the main components of disinfection products (Mulder et al., 2017). The most commonly consumed BACs are C12-BAC, C14-BAC, and C16-BAC. Each homolog has different biocidal ranges. Indeed, C12-BAC has been demonstrated to be effective against yeasts and fungi, while C14-BAC against Gram-positive bacteria and C16-BAC targets Gram-negative bacteria (Nunez et al., 2004).

#### • 3.2.2 Historical and current use

342

343

344

345

346

347

348

349

350

351

352

353

354

355

356

357

358

359

360

361

362

363

364

365

366

BACs were introduced in 1935 by Gerhard Domagk as zephiran chlorides (Price, 1950). Since they were first commercialized, their use has continuously grown, and their applications diversified. Today, BACs are widely used for domestic applications (softeners, conditioners, or medication for the ENT (eye, nose, throat) therapy); and as disinfectants for industrial, agricultural, and clinical areas (Merchel Piovesan Pereira and Tagkopoulos, 2019; Zhang et al., 2015). Finally, BACs are applied to building materials (walls, floors, roofs, pools, woods) to prevent their biodeterioration (Merchel Piovesan Pereira and Tagkopoulos, 2019). Thus,

protocols using DDMAC are effective for the preventive and curative control of the greening of historic building materials (Nowicka-Krawczyk et al., 2019). DDMAC associated with OIT in ROCIMA<sup>TM</sup> 103 (Dow<sup>®</sup>) induces in-depth killing of fouling microorganisms and prevents most biological recolonization of sandstone and marble tombs surfaces for a period of five years after treatment (Mascalchi et al., 2020). The effectiveness of benzalkonium chloride treatment in preventing bacterial recolonization of stone was also observed after the treatment of the granite walls of the San Martiño Pinario Monastery in Santiago de Compostela (NW Spain) (Sanmartín and Carballeira, 2021). QACs are components of several cleaning and disinfection solutions such as Algicid-Plus (Keim, DDMAC 0.36% and OIT 0.081%), Preventol<sup>®</sup> RI50 and R180 (Lanxess), Organcide QC50 (formerly Vitalub QC50, France Organo Chimique, ADMAC 50%, used in solution between 3 and 5%), Algidal (Algimouss Pro, CAQ C12-C16 20%), Sikagard<sup>®</sup> Stop Algues Pro (Sika<sup>®</sup>), and Dalep PE (Dalep<sup>®</sup>).

#### • 3.2.3 Efficacy

The biocidal effects of QACs rely on their ability to lyse cells by disrupting lipid bilayers. The cationic nitrogen interacts with the phospholipid head *via* ionic interactions, while the alkyl chain of quaternary ammonium integrates into the hydrophobic tails of phospholipids through hydrophobic interactions (Heerklotz, 2008). Such interplays increase surface pressure in the exposed part of the membrane and decrease its fluidity. Thus, the cell membrane is rapidly disintegrated (Tezel and Pavlostathis, 2011). Even when QACs are present at non-lytic or sub-inhibitory concentrations in the environment (*i.e.*, below the minimum inhibitory concentration), they are reported to disrupt microorganisms by inhibiting specific membrane processes such as solute transport and cell wall biosynthesis (Tezel and Pavlostathis, 2011). However, at these low concentrations, QACs can also increase biofilm formation and induce oxidative stress, amplifying genetic variation in some microorganisms that may lead to

microbial resistance (Gadea et al., 2017a; Houari and Di Martino, 2007; Tezel and Pavlostathis,2015).

#### • 3.2.4 Advantages and drawbacks

393

394

395

396

397

398

399

400

401

402

403

404

405

406

407

408

409

410

411

412

413

414

415

The success of QACs relies on their multiple biological targets and their wide range of applications. They also have shown efficiency on numerous microorganisms, like fungi as Aspergillus sp., Penicillium sp., Chaetomium sp. (Isquith et al., 1972), and lichens as Diploschistes actinostomus, Parmelia conspersa, Parmelia ioxodes (Table 1) (Pinna et al., 2012). Their multiple usages and low production cost make these molecules the best-selling biocides along with ITs (Merchel Piovesan Pereira and Tagkopoulos, 2019; Tezel and Pavlostathis, 2011). As they are widely consumed, they are also released in large amounts into the environment during their production and use. It is estimated that approximately 25% of the QACs are directly discharged into the environment as a result of their multiple usages (Tezel and Pavlostathis, 2011). For example, QACs are released into nature at high concentrations (5 to 30 mg.L<sup>-1</sup>) from roof runoffs, even after several months after tiles' treatment (Gromaire et al., 2015). Their long-term effects on ecosystems and human health are still poorly understood (Zhang et al., 2015). Nevertheless, it has been shown that their accumulation in the environment leads to the development of drug-resistant microorganisms (Merchel Piovesan Pereira and Tagkopoulos, 2019; Mulder et al., 2017). The main mechanisms of microbial adaptation to QACs are the same as those responsible for antibiotic resistance, such as modification of membrane structure and composition, improvement of biofilm formation (which protects microorganisms), lateral acquisition of genes coding various types of efflux pumps, and overexpression of these efflux pump systems (Gadea et al., 2017a; Slipski et al., 2017; Tezel and Pavlostathis, 2015). Consequently, the development of bacterial populations resistant to QACs also potentially increases antibiotic resistance in ecosystems (Gadea et al., 2017a; Kim et al., 2018). It has already been shown that some nosocomial outbreaks were due to resistant

pathogens to antiseptics or contaminated disinfectants, especially those based on OACs and those using BACs as major active compounds (Weber et al., 2007). Microorganisms on building materials exposed to QACs can adapt and thus promote biodeterioration by resisting current treatments (Gadea et al., 2017a; Tezel and Pavlostathis, 2015). The effectiveness of quaternary ammoniums is influenced by the chemical composition and the physical properties of the material to which they are applied (Favero-Longo et al., 2017). The application of solutions containing OACs to porous materials like sandstone can lead to their penetration and their gradual release, resulting in the exposure of microorganisms and other algae to low concentrations of biocides over a relatively long period (Favero-Longo et al., 2017). This process may facilitate the induction of a decrease in the sensitivity of the target organisms to the biocides. Finally, QACs are considered one of the most toxic products among biocides with ITs and antifouling products (Roy, 2020). BACs are responsible, for instance, for skin and respiratory irritations, and they are considered to be skin sensitizers (Merchel Piovesan Pereira and Tagkopoulos, 2019). As with ITs, the application of commercial products containing QACs can lead to alterations in the stone material (Sanmartín et al., 2020; Tirado Hernández et al., 2015).

#### • 3.2.5 Future and perspectives

416

417

418

419

420

421

422

423

424

425

426

427

428

429

430

431

432

433

434

435

436

437

438

439

440

As with ITs, the use of QACs will be increasingly regulated in a near future. For example, since 2016, the EU has drastically reduced the number of BACs allowed in food products and has banned them in antiseptic hand and body soaps. Similarly, the US Food and Drug Administration (FDA) is considering banning BACs in these same products (Merchel Piovesan Pereira and Tagkopoulos, 2019). Moreover, CAQs have been reported to be toxic to various aquatic organisms, such as *Daphnia magna* and *Criodaphnia dubia*, where they are highly poisonous at lower concentrations (0.4 to 4 ng.L<sup>-1</sup>) than those found in the environment (on the order of mg.L<sup>-1</sup>) (Lavorgna et al., 2016). The long-term effects of CAQs are also of serious

concern due to their ecotoxicity, bioavailability, and possible interactions with other chemicals (Lavorgna et al., 2016; U.S. Environmental Protection Agency (EPA), 2006).

Consequently, the proven toxicity of QACs for the environment and especially aquatic ecosystems (Di Nica et al., 2017; Merchel Piovesan Pereira and Tagkopoulos, 2019) may lead authorities to limit their application on outdoor surfaces in the coming years. As for IT's, such ecotoxicological effects have to be considered before widespread commercialization and launch of new products. The use of adapted personal protection devices has to be strongly recommended to avoid impact on users' health. Decreasing the usage of QAC's, reducing their concentrations at their minimum, and combining QACs products with less toxic biocides is essential before considering any use of these products. Finally, more ecotoxicological studies should be conducted to better precise the effects of these widely marketed products on health and the environments

# 3.3 Other types of widely-used biocides

Many other chemical products are commercialized to prevent biodeterioration. They are all employed as wide-spectrum biocides, but they are less commonly used than ITs and QACs (Tezel and Pavlostathis, 2011). Their mode of action, their potentially hazardous effects on health and the environment are also much less documented.

#### • 3.3.1 Sodium hypochlorite

Among those other types of broad-spectrum biocides utilized to clean building materials is sodium hypochlorite (CAS: 7681-52-9) (Table 2), also known as bleach (Table 1). This compound is, for example, commercialized under the names Clorox® or 30 seconds® outdoor cleaner. Sodium hypochlorite is cheap and rapidly efficient on a wide range of microorganisms (Fukuzaki, 2006). For instance, sodium hypochlorite is effective on filamentous green algae and cyanobacteria (Pozo-Antonio et al., 2017). However, this application could have deleterious effects on metals or stones, as its degradation can lead to the formation of

chlorinated compounds that are toxic to aquatic organisms (Fukuzaki, 2006). Bleach may also affect energy metabolism and damage DNA (Emmanuel et al., 2004). Besides, sodium hypochlorite is a harmful compound responsible for mucosal irritations (Fukuzaki, 2006).

# • 3.3.2 Acid compounds

466

467

468

469

470

471

472

473

474

475

476

477

478

479

480

481

482

483

484

485

486

487

488

489

490

Some other biocides, like Biorox®, commercialized to clean natural stones are based on oleic acid activity (CAS: 112-80-1) (Table 2). These molecules were first employed as herbicides in agriculture. The most common oleic acid is the nonanoic acid (also named pelargonic acid, CAS: 112-05-0), and is included in many commercialized products like Natria® (Bayer), Premiumgreen total (Finalsan plus) mixed with maleic hydrazide by CTS, or Dalep eco (Dalep®). The use of pelargonic acid seems to be efficient in preventing biodeterioration of building materials, and this molecule is quickly degraded in soils (Marin et al., 2016), limiting its ecotoxicity. Norstictic (CAS: 571-67-5) and usnic (CAS: 7562-61-0) acids, which are lichen secondary metabolites, have also shown efficiency and low toxicity on various microorganisms as cyanobacteria (Chroococcus minutus) and fungi (Coniosporium perforans, Phaeococcomyces chersonesos) (Table 1) (Fidanza and Caneva, 2019; Gazzano et al., 2013) However, there are few available studies on these compounds, and more research is needed to confirm these preliminary observations. As with QACs (especially BACs), pelargonic acid causes slow onset irritancy, erythema and is an irritant compound (Frosch and John, 2011). Other families of acids are employed and commercialized to prevent biodeterioration like lactic acid (CAS: 50-21-5) as MossKade® supplied by HortiPro. However, some studies have also highlighted the effects of lactic acid on human health, which has been shown to be responsible for erythema and stinging when used at 5% in water (Frosch and John, 2011). For this reason, the supplier recommends that customers wear gloves and eye protection to avoid its potential hazards (Hortipro B.V., 2014).

#### • 3.3.3 Chlorinated phenol compounds

Besides, some biocides containing chlorinated phenol compounds are also commercialized to prevent biodeterioration, such as Atagol sodique from CTS containing *p*-chlorocresol (4-chloro-3-méthylphenol, CAS: 59-50-7) and Panacide® containing dichlorophen (2,2'-Methylenebis(4-chlorophenol), CAS: 97-23-4) (Table 2) (Rosado et al., 2017). For example, Panacide® has shown to be efficient on filamentous fungi as *Aspergillus* sp., *Cladosporium* sp., and *Penicillium* sp. (Table 1) (Rosado et al., 2017). However, as the other biocides, they are also mentioned as an irritant if not used with personal protection gear (Frosch and John, 2011), and in 2019 government of Canada has assessed *p*-chlorocresol as posing a risk to human health and has recommended a reduction in its usage (Government of Canada, 2019).

#### • 3.3.4 Other compounds broad-spectrum biocides

Finally, among the other biocides used to prevent biodeterioration, disodium metasilicate (CAS: 229-912-9) has been commercialized as in AlgiClean (Algimouss pro), and dimethyl sulfoxide (DMSO, CAS: 67-68-5) can be found in "Solvent Gels" utilized to restore historical monuments (Table 2) (Toreno et al., 2018). However, both molecules are noted for their toxicity and corrosive effects, and personal protection gears (gloves and goggles) are recommended when handling these compounds (Frosch and John, 2011).

#### 3.4 Innovative use of biocides

Among innovative biocidal compounds are gemini surfactants (Table 1). These are amphiphilic compounds composed of two conventional surfactant molecules covalently bonded together by a spacer. Geminis are characterized by very low critical micelle concentrations (CMC), low surface tension ( $\gamma$ ), anti-adhesive activities, and low minimal inhibitory concentrations as compared to the related monomeric surfactants. For these reasons, such compounds are very attractive as biocides in materials science, especially when they expose ammoniums as polar groups (Brycki et al., 2017; Tyagi and Tyagi, 2009). For instance, the antifungal activity of cationic gemini surfactants has been recently demonstrated against

Aspergillus brasiliensis by measuring the content of ergosterol, a method used to estimate the level of mold infestation in buildings (Koziróg et al., 2018). Additionally, it has been shown that the antimicrobial efficiency of these compounds depends on the length and type of spacer as well as their hydrophobic counterpart. As expected, diquaternary ammonium geminis of structure  $[C_{12}H_{25}N^+(CH_3)_2CH_2CONH]_2Y\cdot 2Cl^-]$  where  $Y = -(CH_2)_4$  or  $-(CH_2)_2SS(CH_2)_2$ — were shown to exhibit a higher antimicrobial activity against gram-positive/negative organisms and *Candida albicans* than "plain" hexadecyltrimethyl ammonium bromide (Diz et al., 1994). Also, Winnicki *et al.* showed the anti-algal activity of pentylene-1,5-bis(dimethyl dodecylammonium bromide) against *Chlorella*, single-celled green freshwater algae also known to foul industrial cooling systems and building facades (Table 1) (Winnicki et al., 2021).

Another way to expose antimicrobial moieties is to derive the end groups of dendrimers (Table 1). Once functionalized with quaternary ammonium salts, these highly branched and star-shaped globular macromolecules exert a more potent biocidal activity than their small-molecule counterparts (Chen and Cooper, 2000; Karthikeyan et al., 2016). Chen et al. demonstrated that dimethyl dodecylammonium chloride functionalized poly-(propylene imine) dendrimers were over two orders of magnitude more potent than their mono-functional counterparts against *E. coli* (Chen et al., 1999). Another dendrimer scaffold based on quaternary ammonium functionalized polyamidoamine (PAMAM) has been successfully used against a group of common Gram-negative and Gram-positive bacteria (Zainul Abid et al., 2016) and *Staphylococcus aureus* as a coating on textile fabrics (Ghosh et al., 2010). However, to the best of our knowledge, such promising architectures have never been applied yet to prevent the biodeterioration of building materials.

# 3.5 Conclusions about the usage of biocides to prevent biodeterioration of building materials

To conclude, it is essential to note that the composition of marketed biocidal products used to control the biodeterioration of building materials is unclear and difficult to obtain. Moreover,

many commercialized products mix several families of molecules such as Biotin T (CTS), Algicid-Plus (Keim), which are mixtures of OIT and OACs, or Net 9 Anti-Lichen (Dalep®), which is a mixture of sodium hypochlorite with other compounds. Many, if not all, of these compounds are now recognized by many research as harmful to human and environmental health. In the future, regulations for many biocidal molecules could follow the same path as ITs and QACs. For instance, this is already the case for p-chlorocresol, as the EU and Canada have limited their use in cosmetics (Government of Canada, 2019). Even in the case of ITs and CAQs, their effect remains to be better understood, and multidisciplinary efforts (combining expertise in microbiology, building materials, chemistry, ecotoxicology, medicine) remain to be conducted in order to evaluate their usage and effects. Environmental and legal risks have to be considered by major industries commercializing these products to maintain their economic profitability and by customers to limit their environmental footprint. In this perspective, massive investments in research and development of more sustainable and environmentallyfriendly antifouling compounds appear to be an urgent need and a promising economic strategy. After comparative studies of the effectiveness of commercial biocidal solutions to control outdoor colonization of stone in historical monuments and consider their toxicity, some authors recommend water-based treatments and brushing to remove the colonizing biomass (Sanmartín et al., 2020). There remains the problem of controlling microbial regrowth and recolonization of the substrate after cleaning.

560

561

562

563

564

541

542

543

544

545

546

547

548

549

550

551

552

553

554

555

556

557

558

559

# 4. Water-repellent compounds and surfaces offer interesting antifouling properties.

Throughout the ages, the biodeterioration of building materials, especially stone, has been of significant concern to builders. Over time and civilizations, many different treatments have

been developed and used, such as oils, waxes, or sacrificial layers (Charola, 2001; Rossi-Manaresi, 1996). Sacrificial layers are paints, renders, or plasters deposited on building materials to protect them from weather and the time effects (Charola, 1995). For instance, Pliny the Elder explained that the Carthaginian pitch-coated their walls made of tuff, a stone highly sensitive to biodeterioration (Plinius Secundus, 77AD; Rossi-Manaresi, 1996). Vitruvius also described that Roman coated their walls with three layers of plaster and two layers of stucco to protect fragile materials (limestone and tuff) from biodeterioration and to mimic at the same time more precious stones like marble (Rossi-Manaresi, 1996; Vitruvius Pollio, 27BC). It has also been reported that water repellent coatings such as wax or oils have been used in ancient times (Rossi-Manaresi, 1996), and to date, waterproofing strategies are still widely employed alone or in combination with biocidal treatments (Moreau et al., 2008; Pinna et al., 2012; Urzì and De Leo, 2007). The development of innovative superhydrophobic materials remains a major industrial challenge.

#### 4.1 Conventional water-repellent treatments

#### • 4.1.1 Nature and commercially available compounds

Different water-repellents are available on the market, but the most popular ones are all silicone derivatives (Table 1) (Roos et al., 2008). These compounds consist of an inorganic network of Si-O-Si bonds with an organic pendant group bearing by silicon atoms. In antifouling applications and water-repellent treatments, organic pendant groups are usually alkyl chains or aromatic groups due to their intrinsic hydrophobic character. Whatever the precursors used in antifouling or water-repellent treatments, the chemistry involved in the production of silicone derivatives remains the same and is the sol-gel chemistry implying hydrolysis and condensation reactions (Brinker and Scherer, 2013; Iler, 1979). Thus, silicone derivatives could be produced starting with organosilanes, siloxanes, and/or siliconates. Organosilanes are monomeric species containing at least one hydrolytically sensitive group,

mainly chloride atom or alkoxy group (OR), which could undergo hydrolysis (formation of reactive silanol Si-OH) and condensation reactions allowing the growth of Si-O-Si backbone and/or covalent bonding on a substrate. Organosilanes also possess one or more organic substitutions linked to a silicon atom with a hydrolytically stable Si-C bond, silicon atom being tetravalent. Siliconates are their basic salts, and siloxanes correspond to their oligomeric or polymeric forms.

590

591

592

593

594

595

596

597

598

599

600

601

602

603

604

605

606

607

608

609

610

611

612

613

614

Regarding antifouling building materials, alkyltrialkoxysilanes of such triethoxyisobutylsilane (CAS: 17980-47-1), N-octyltriethoxysilane (CAS: 2943-75-1), and isooctyltriethoxysilanes (CAS: 35435-21-3) are the most utilized compounds (Table 2) (Roos et al., 2008). Interestingly, when the alkyl chain is long (C12-C16), the resistance of these molecules to alkalis is more important, making them able to penetrate deeply into a substrate such as concrete (Roos et al., 2008; Urzì and De Leo, 2007). In comparison, siloxanes have a much more complex structure due to their oligomeric or polymeric state (Roos et al., 2008). Siloxanes, which are liquid due to their low intermolecular forces, have better thermal stability than silanes. Still, they cannot penetrate a substrate as deeply as monomeric silanes because of a steric hindrance (Roos et al., 2008). As they are also alkali-resistant, they can be used on concrete. However, they are much better suited to porous substrates such as ceramics (i.e., bricks, ceramic roof tiles) and stone (Roos et al., 2008; Urzì and De Leo, 2007). Organomodified siloxanes are mainly used for building material protection, as their methyl groups around the silicon atom are replaced by other organic groups (Roos et al., 2008). Finally, siliconates are smaller molecules than silanes and siloxanes; therefore, they provide the deepest penetration (Urzì and De Leo, 2007). They also present no water sensitivity, unlike organosilane and siloxane species, and they are water-soluble, meaning that they are fully compatible with water-based processes and less expensive. Commercially available waterrepellents include the following molecules: alkyl alkoxysilane (Hydrophase superfici supplied

by Phase), alkyltrialkoxysilane (Hydrophase malta PH91503, Phase) (Urzì and De Leo, 2007), trimethoxy-(2,4,4-trimethylpentyl)silane (CAS: 34396-03-7) (Sikaguard® Roof Protection, Sika), polydimethylsiloxane (Rhodorsil RC80, Phase) (Urzì and De Leo, 2007), or potassium methylsiliconate (or potassium methylsilanetriolate, CAS: 031795-24-1) (Table 2) (SILRES® BS 16, Wacker).

In addition to silicon derivatives, fluoropolymer coatings are also marketed for their water-repellent properties. For example, some of them have lowered biofilm formation by some bacteria, such as *Bacillus subtilis* (Table 1) (Bao et al., 2017). However, they also have shown high toxicity for both human health and the environment. Consequently, these compounds will not be described in this review, as their use is not recommended on building materials (Daubert et al., 2009; Hekster et al., 2003; Sznajder-Katarzyńska et al., 2019).

#### • 4.1.2 Historical and current use

To protect building materials, the most popular water-repellents are alkyl-silicone products like alkyl-silanes, alkyl-siliconates (Charola, 2001), oligomeric and polymeric siloxanes (Khoshnevis et al., 2020; Roos et al., 2008). These products are derivatives of ethyl-silicate (CAS: 78-10-4) (Table 2), discovered by the French chemist Ebelmen in 1845 (Charola, 2001; Ebelmen, 1855). Shortly after this discovery, in 1861, tetraethoxysilane (developed by Ebelmen in 1846) (Ebelmen, 1855) was suggested by W. von Hoffman as a protectant to the House of Parliament in London. However, it was not until the 1920s that the use of ethyl-silicate as a stone treatment was revived with the work of A.P. Laurie (Laurie, 1926a, 1926b, 1926c, 1925, 1923; Wheeler, 2005). It was only in the 1950s that silicone-based solutions gained popularity, and their applications were multiplied for both industry and consumers (Noll, 1954). For instance, these silicone-based solutions have been used to protect building materials, as shown in the patent by Bayard R. Brick, for the treatment with a non-aqueous solution of organo-siloxane resins (Bayar R. Brick, 1951). Until the late 1980s, water-repellents were

solvent-based, but due to environmental concerns, their composition was modified to a water-based emulsion form (Charola, 2001; Roos et al., 2008). Today, silicones are widely used in the preservation of building materials, as well as in domestic applications (shampoos, conditioners) (Roos et al., 2008).

#### • 4.1.3 Efficacy

Water-repellent coatings consist of depositing a hydrophobic substance on targeted materials to prevent liquid water penetration (Charola, 2001; Fassier, 2009). The goal is to obtain a contact angle between 90° and 150° on the treated surface. Hydrophobic substances increase the solid-liquid interfacial tension and thus limit wetting and liquid water penetration into the material (Fassier, 2009) necessary for biofilm establishment and growth. The extent of water-repellency depends on the substrate (Roos et al., 2008) and the nature of the alkyl group(s) attached to the silicon atom (Charola, 2001).

# • 4.1.4 Advantages and drawbacks

Water-repellents reduce water availability for microorganisms, thus slowing down their growth and, in turn, the biodeterioration of building materials (Fassier, 2009; Urzì and De Leo, 2007). For example, silanes and siloxanes efficiently reduce building material colonization by photosynthetic microorganisms, such as filamentous *Nostoc*-like cyanobacteria (Urzì and De Leo, 2007), and *Stichococcus bacillaris* (Romani et al., 2021b). Potassium methyl siliconate has also shown *in vitro* effects on the growth of *Cladosporium cladosporioides* (Table 1) (Romani et al., 2021b). Additionally, silicone-based water-repellents are insensitive to UV radiations, making them particularly stable through time (Charola, 2001; Fort González et al., 2000; Wendler, 1997). Water-based silicone formulations also offer adequate protection for granites and low-porosity limestones, while siloxanes are mostly used for the treatment of facades, despite their low affinity with alkali substrates and the fact that they exhibit a lesser hydrophobicity in comparison with silanes (Bruchertseifer et al., 1995; Roos et al., 2008).

However, the use of water-repellents also has some drawbacks. Indeed, it has been reported that they increase the sensitivity of some materials to freezing (Snethlage and Wendler, 1996) and impact their surface rigidity (Sasse and Snethlage, 1997). These properties lead to a higher erosion and biodegradation of the building materials over time (Charola, 2001). Moreover, water-repellent treatments have a short lifespan since they are poorly resistant to decay and bad weather (Fassier, 2009; Ferreira Pinto and Delgado Rodrigues, 2000; Pinna et al., 2012). They are less effective than solvent-based formulations when facing many freeze-thaw periods. They are also destabilized by salts in the material (Charola, 2001) and thus less efficient when used on buildings constructed in coastal areas.

Evaluation of advantages and drawbacks of water repellents remains a complex task as there is a gap between nature as well as the importance of biofilms' development and the type of water-repellent treatments sprayed on the construction or the cultural heritage preservation fields. The effectiveness of some of these water-repellents to prevent microbial colonization of stone or mortars has been tested in various studies (Moreau et al., 2008; Pinna et al., 2012; Urzì and De Leo, 2007). The main results of the work published by Urzì and De Leo pointed out that applying a hydrophobic compound alone was not sufficient to stop the development of biofilm over 15 months of exposure and that only the combined use of water-repellent and a biocidal substance reduced the colonization of materials by algae and bacteria (Pozo-Antonio et al., 2016; Urzì and De Leo, 2007). Moreover, they do not lower the colonization of materials by "black" fungi such as Alternaria sp. or Cladosporium sp., which are the most resistant to chemical treatments (Hallmann et al., 2011; Krause et al., 2006; Romani et al., 2021b; Urzì and De Leo, 2007). Combining polysiloxane with copper nanoparticles reduces biocolonization and blackening of marble surfaces (Pinna et al., 2012). When treating successively with a water repellent and a biocide, the question of the order of application of each chemical arises (Moreau et al., 2008). A water-repellent applied after a quaternary ammonium treatment loses

effectiveness. When the biocide is used after the water repellent, the surface hydrophobicity of the stone is reduced, and the biocide penetrates little into the material. Treating a surface previously treated with a water repellent with a quaternary ammonium compound can remove the biofouling that has developed at a given time but cannot prevent recolonization in the longer term (Moreau et al., 2008). Nevertheless, we have some clues about the efficiency of silicone-based coatings towards the development of biofilms in marine fouling since they are commercially used as fouling release coatings (Lejars et al., 2012).

Evaluating the ecotoxicity of water-repellents remains a major challenge, and more research and assessment are urgently needed. On the one hand, coating building surfaces with water repellents reduced microbial growth and protected materials. Thus, the use of water-repellent coatings leads to a reduction in the use of biocides compounds. On the other hand, water repellent molecules also present ecotoxicological effects, as reported in a few studies, and their runoff with time could damage humans and environmental health. Again, multidisciplinary studies would be required to fully address these yet unsolved questions.

# • 4.1.5 Future and perspectives

The use of water-repellents is widespread in the construction industry, which has successfully adapted to environmental concerns to propose safer products (Charola, 2001; Roos et al., 2008). However, to properly apply water-repellents and avoid risk for the materials (Sauder, 1999), a "holistic approach" is needed. This means that it is necessary to consider the treatment, application, and the substrate for successful waterproofing (Charola, 2001, 1995). Otherwise, an innovative approach consists of creating superhydrophobic surfaces on the building materials (see below). In this regard, some silicones are promising, such as poly(dimethylsiloxane) (CAS: 70131-67-8) (Table 2) (Amara et al., 2018). From a regulation and environmental point of view, since oligomeric-polymeric silicone derivatives could be

714 considered as microplastics, their release from substrates could be limited and even forbidden 715 in the future (ECHA, 2019).

## 4.2 The case of superhydrophobic materials

The abovementioned water-repellents offer hydrophobic properties to building materials, which means that the resulting apparent contact angle is between 90° and 150°. In the case of superhydrophobic compounds, the apparent contact angle is higher than 150° on material surfaces with a low hysteresis or a low tilting angle (less than 10°) (Table 1) (Jeevahan et al., 2018). Research on superhydrophobic materials is relatively recent and has rapidly grown over the last ten years, from around 100 publications per year in 2009 to more than 700 in 2018 (Dalawai et al., 2020). This section of this review will mainly focus on silicones used to develop this type of coating. As described above, water repellent compounds have been known for a long time, have an excellent cost-benefit ratio, and are widely used. Other techniques exist to develop superhydrophobic materials, but they are more complex and less developed, and at this time, they remain promising research strategies that needed to be developed and widely tested (Dalawai et al., 2020; Li et al., 2017).

#### • 4.2.1 Nature and commercially available compounds

The design of silicone-based superhydrophobic surfaces is generally achieved by two different pathways: the top-down approach and the bottom-up strategy (Dalawai et al., 2020; L. Li et al., 2016; Niu et al., 2020; Wang et al., 2020). The top-down allows the formation of superhydrophobic surfaces by selective matter removal, while the bottom-up approach corresponds to the assembly of precursors (monomeric, oligomeric, or polymeric chemical species, nanoparticles, microparticles ...). The top-down approach is generally a two-step procedure involving first surface etching (either physical or chemical) leading to a patterned master and then forming a master negative replica with silicone derivatives. The second step usually implies pouring silicone prepolymers over the master, followed by curing and peeling

off phases (Xia and Whitesides, 1998). Alternatively, some authors have directly modified silicone rubbers by laser irradiation and/or chemical etching (Wang et al., 2020). Concerning the second strategy, i.e., the bottom-up approach, it generally involves the preparation of a solution containing silicon precursors, solvents, particles and nanoparticles, and catalysts. This solution is next deposited on the surface of the substrate, and evaporation of volatile species (solvent) leads to the formation of the superhydrophobic surface by a multiscale component assembly. A subsequent treatment (often thermal or UV curing) allows the stiffening of the superhydrophobic coating. The deposition step could be achieved by dip-, spin- or spraycoating. It appears thus that the bottom-up approach is much more convenient for treating building materials since its synthesis procedure is fully compatible with outdoor treatments, especially when spray-coating on large surfaces with commercial equipment is required (Faustini et al., 2018). Several commercialized superhydrophobic paint are currently marketed, such as SuperCN<sup>TM</sup> (NEI Corporation), NeverWet® anti-icing coating, HydroFoe<sup>TM</sup> (LotusLeaf Coatings), Lotusan®, (Sto) (Sto, 2020). Today, in addition to building materials, superhydrophobicity is under development for many applications such as photovoltaic devices, fabrics, and textiles, anti-corrosion, anti-snow, and freeze and anti-reflective (Dalawai et al., 2020).

#### • 4.2.2 Historical and current use

739

740

741

742

743

744

745

746

747

748

749

750

751

752

753

754

755

756

757

758

759

760

761

762

763

Superhydrophobicity was first studied in 1756 by the German physician Leidenfrost by depositing a water drop on a hot solid surface (>200°C) and observing the drop flowing everywhere. The water drop had an apparent contact angle of 180°, constituting what was then named "the Leidenfrost effect" (Leidenfrost, 1756; Quéré and Reyssat, 2008). Also, the superhydrophobic property of lotus (*Nelumbus* sp.) leaves is due to their unique nanostructuration combined with the production of a hydrophobic coating (a wax made of various non-polar methyl groups, such as nonacosane diols) (Ensikat et al., 2011; Sanchez, 2012;

Sanchez et al., 2010). The lotus "self-cleaning" phenomenon has been known in Asia for at least 2000 years, where the lotus is a symbol of purity in many cultures (Cheng and Rodak, 2005). Nevertheless, it was not until the early 1970s that the lotus phenomenon was studied and then luckily understood by the German botanist Barthlott after realizing that he did not need to dust off the lotus leaves before observing them under a microscope, unlike other plants (Barthlott and Neinhuis, 1997; Cheng and Rodak, 2005). This discovery led to the "Lotus-Effekt" patent in cooperation with Sto, producer of the Lotusan® paint (Sto, 2020).

Thanks to 3.8 billion years of evolution, various organisms, such as lotus, have developed non-wetting traits that protect them from microbial colonization and pathogenic agents. For example, these properties were depicted in ramee leaves (contact angle 164°) or insects like some Homoptera (*Meimuna opalifera*, contact angle 165°) (Wolfs et al., 2013). Researchers and industrials aim to develop materials with superhydrophobic properties to allow their self-cleaning and protect them against biodeterioration, following a modern and very promising approach called biomimicry (Zhang et al., 2017). Indeed, observation of natural phenomena is frequently recognized as a promising way of developing eco-friendly solutions (Scardino and de Nys, 2011; Wolfs et al., 2013; Zhang et al., 2017).

#### • 4.2.3 Efficacy

To the best of our knowledge, no studies have evaluated the effectiveness of superhydrophobic coatings in preventing long-term microbial colonization and biodeterioration of building materials (Xiang et al., 2019). Again, integrative and multidisciplinary research is needed to assess better the efficiency of these antifouling strategies, which, for the moment, mostly rely on empirical observations and assessments.

#### • 4.2.4 Advantages and drawbacks

Superhydrophobic coatings under development provide amphiphobic properties to building materials, which means that they prevent water (hydrophobic) and oil (oleophobic) uptakes

(Facio et al., 2017). Moreover, superhydrophobicity provides self-cleaning properties that avoid microbial and dirt attachment, delaying building material biodeterioration (Dalawai et al., 2020; Jeevahan et al., 2018). However, the real-world applications of superhydrophobic coatings are minimal due to low durability, expensive and toxic reagents, and complex preparation processes (Li et al., 2017). These coatings may also be toxic for the environment and human health due to some of their components, such as methanol (Zulfiqar et al., 2017) or fluorinated molecules (Arabzadeh et al., 2017; Facio et al., 2017; Guo et al., 2005). However, determining the toxicity level of such compounds remains an open question, as previously discussed for conventional water-repellents.

#### • 4.2.5 Future and perspectives

Superhydrophobic coatings appear to be promising by conferring self-cleaning properties to building materials. However, their durability and environmental impacts remain to be assessed. They appear at first sight as interesting alternatives to avoid applying biocides. However, a few studies also report that the toxicity of such water repellents could cause health or environmental issues (Arabzadeh et al., 2017; Facio et al., 2017; Guo et al., 2005; Zulfiqar et al., 2017). To the best of our knowledge, these coatings have only been evaluated under laboratory conditions (Zulfiqar et al., 2017), and comprehensive tests under various *in situ* conditions are needed to evaluate the toxicity of these compounds (Arabzadeh et al., 2017; Facio et al., 2017; Guo et al., 2005; Zulfiqar et al., 2017). This nature-inspired approach to prevent biodeterioration is attractive and recent compared to the use of biocide or silicones. Consequently, more research is needed to improve superhydrophobic coatings before commercializing durable and eco-friendly products (Dalawai et al., 2020).

# 5. The efficacy of the photocatalysis mechanisms

A promising and eco-friendly way to develop self-cleaning building materials relies on using the photocatalysis process (Table 1) (Wang et al., 2014). This approach was discovered more than a century ago in Germany (Coronado et al., 2013; Eibner, 1911). Its principle relies on an advanced oxidation process (AOP) based on the absorption of photons by a photocatalyst and the subsequent production of ROS (Ameta et al., 2018). Thanks to the high stability of photocatalysts, this AOP has many applications in different fields: from converting water to hydrogen gas to disinfection and use in antifouling coatings (Ameta et al., 2018).

#### • 5.1. Nature and commercially available compounds

Most of the employed photocatalysts are semiconductors, as they can conduct electricity in the presence of light and at room temperature (Ameta et al., 2018; Wang et al., 2014). Semiconductors are defined by their bandgap comprised between 1.5 and 3.0 eV (the bandgap is the energy difference between the valence band and the conduction band (Ameta et al., 2018). For the photocatalysis-induced AOP, the semiconductor can simultaneously drive reduction and oxidation of the substrate when the redox level of the substrate is lower than the conduction band and higher than the valence band (Ameta et al., 2018; Wang et al., 2014). The most commonly commercialized semiconductors are binary oxides such as titanium dioxides (TiO<sub>2</sub>, CAS: 13463-67-7) or zinc oxides (ZnO, CAS: 1314-13-2) (Chen et al., 2010). For example, 270 patents registered for ceramic roof tiles include the use of binary oxides for photocatalysis (Ranogajec and Radeka, 2013). For example, this is the case with Erlus Lotus air® tiles, which are coated with TiO<sub>2</sub> to reduce nitrogen oxide pollution ("Erlus Lotus Air®," n.d.).

#### • 5.2 Historical and current use

Photocatalysis was first mentioned in 1911 by German chemist Eibner, who studied the effect of illumination of ZnO on the bleaching of Prussian blue, a dark blue pigment (Coronado et al., 2013; Eibner, 1911). However, it was not until 1938 that Goodeve and Kitchener discovered the photocatalytic effect of TiO<sub>2</sub> (Goodeve and Kitchener, 1938). These authors

provided the first description of ROS production induced by UV absorption and leading to photooxidation (Coronado et al., 2013). Today, photocatalysis is employed in many different fields (*i.e.*, wastewater treatment (Cantiello et al., 2020), air purification ("Erlus Lotus Air®," n.d.), antifouling coatings (Gladis et al., 2010)).

## • 5.3 Efficacy

838

839

840

841

842

843

844

845

846

847

848

849

850

851

852

853

854

855

856

857

858

859

860

861

862

The efficiency of photocatalysts relied on ROS production coupled with the oxidation and reduction process. These photochemical properties are intrinsic to semiconductors like TiO<sub>2</sub> or ZnO (Ameta et al., 2018; Carretero-Genevrier et al., 2012; Coronado et al., 2013). The interesting property which is exploited in the context of the present review is that ROS produced during photocatalysis have deleterious effects on many types of microorganisms by degrading coenzyme A or disrupting the cell wall membranes. For that reason, photocatalysts are also used as antifouling or in disinfection treatments (Ganguly et al., 2018). The use of TiO<sub>2</sub> and ZnO to prevent the biodeterioration of buildings and heritage monuments has been recently reviewed (Ganguli and Chaudhuri, 2021). For instance, ZnO has shown better efficiency than TiO<sub>2</sub> to prevent the biodeterioration of building materials, mainly by fungal growth, even without light exposure (Loh et al., 2018). Moreover, higher efficiency of photocatalysts has been shown when they are combined with metallic nanoparticles as silver (Becerra et al., 2020, 2018; Fellahi et al., 2013; Goffredo et al., 2019, 2017). Such TiO<sub>2</sub> association with Ag can be used as coatings for outdoor treatment of limestone façades to prevent microalgal fouling (Becerra et al., 2020). When a TiO<sub>2</sub> treatment is applied after a biocide treatment on stone, there is a reduction in recolonization of the treated area (Ruffolo et al., 2017).

#### • 5.4 Advantages and drawbacks

One of the significant advantages of photocatalysts, compared to biocides or water-repellents, is that they resist the firing along with the industrial production of building materials (*i.e.*, around 1,000°C for ceramic roof tiles). Thus, they can be added during the manufacturing

process, and their usage does not need an additional coating step at the end of fabrication (Gladis et al., 2010; Gladis and Schumann, 2011; Ranogajec and Radeka, 2013), facilitating the industrialization of antifouling solutions based on photocatalysts. Moreover, photocatalysts and especially TiO<sub>2</sub>, are very stable over time (Hashimoto et al., 2005) and thus have shown suitable antimicrobial activity and prevent biodeterioration over a long time (Dyshlyuk et al., 2020). For example, photocatalysts are efficient on lichens, such as *Diploschistes actinostomus*, *Parmelia conspersa*, *Parmelia ioxodes* (Table 1) (Pinna et al., 2012). However, TiO<sub>2</sub> is a white powder that can alter building material color over time (Hashimoto et al., 2005). Photocatalysts also increase the hydrophily of building materials, promoting microbial colonization due to a higher water uptake level of the materials (Ranogajec and Radeka, 2013). The effectiveness of TiO<sub>2</sub> coatings is highly dependent on the substrate material and, in particular, its porosity and roughness. However, many stone materials in historic buildings are very porous and rough (Gladis and Schumann, 2011; Graziani et al., 2016, 2014; Quagliarini et al., 2018).

On the negative side, some studies revealed that some photocatalysts applied to prevent building biodeterioration (especially facades) were detected at significant concentrations in the aquatic environments where they are potentially harmful to many organisms (Kaegi et al., 2008). Also, as pointed out by a few studies, the photocatalysts' size and nature could constitute a serious issue for both human health and the environment (Remzova et al., 2019). The risks of photocatalysts used as TiO<sub>2</sub> or ZnO nanoparticles in cosmetics to human health have been pointed out, especially when inhaled (Dréno et al., 2019; Subramaniam et al., 2019). Regarding the risks associated with their inhalation, some studies suggested a potential link between exposure to TiO<sub>2</sub> nanoparticles and certain pulmonary and cardiovascular conditions in workers exposed to these nanoparticles (Dréno et al., 2019; Pelclova et al., 2018, 2015; Rossnerova et al., 2020).

#### • 5.5 Future and perspectives

Photocatalysis is clearly an up-and-coming solution for air-purification and self-cleaning of building materials to prevent their colonization and biodeterioration (Loh et al., 2018; Nath et al., 2016). The choice of photocatalysts, their size, and how they are incorporated in the process of manufacturing materials remain to this day a matter of debate. Photocatalytic small (nano)particles appear as the most efficient; however, the smaller the particles are, the higher the risk that they will be inhaled during the industrial process, which may be harmful to the health of operators (Remzova et al., 2019; Tobaldi et al., 2017). Nevertheless, the ecotoxicological risks of nanoparticles remain a large subject of debate, and clearly, much more scientific studies to evaluate their potentially hazardous effects remain to be conducted. Moreover, managing the durability and efficiency of photocatalytic building materials is still challenging since it depends on the main microbial colonizers, nature of the substrate, and environmental conditions (Boonen et al., 2016; Goffredo et al., 2017). Finally, it is essential to note that further studies are really needed to develop innovative and more efficient photocatalytic building materials at supportable costs for this industry.

# 6. Ionic liquids: promising eco-friendly synthetic molecules

Lo Schiavo *et al.* recently underlined that ionic liquids could be valid alternatives to conventional biocides for stone-built cultural heritage (Table 1) (Lo Schiavo et al., 2020). Ionic liquids (ILs) are salts with a melting point <100°C comprising organic cations (imidazolium, ammonium, pyrrolidinium, etc.) associated with inorganic anions (Cl-, AlCl<sup>4-</sup>, PF<sup>6-</sup>, BF<sup>4-</sup>, NTf<sup>2-</sup>, etc.) or organic anions (CH<sub>3</sub>COO<sup>-</sup>, CH<sub>3</sub>SO<sub>3</sub><sup>-</sup>, etc.) which are liquid around room temperature. Their structure can be tuned to access physicochemical properties such as wide electrochemical window, high thermal stability, and null vapor pressure. Due to their structural analogies with conventional amphiphilic quaternary ammonium (QACs) species, ILs have an intense antimicrobial activity since the cation is responsible for the primary electrostatic interactions

with cell walls (Pendleton and Gilmore, 2015). Consequently, ILs have been successfully applied to clean calcium crust (CaCO<sub>3</sub>, CaSO<sub>4</sub>, CaC<sub>2</sub>O<sub>4</sub>) from stained glasses (Machado et al., 2011) as well as from synthetic and natural varnishes (Pacheco et al., 2013). Phosphonium-based ILs were also tested for corrosion crust removal from medieval glasses (Delgado et al., 2017). For instance, it has been recently demonstrated that surface active ionic liquids (SAILs), based on cholinium and dodecylbenzenesulfonate, have been tested to prevent the biodeterioration of stone-built cultural heritage (Table 1). These SAILs have shown antimicrobial activity on pure Gram-positive (Micrococcus luteus) and Gram-negative (Stenotrophomonas maltophilia) bacteria, yeasts (Cladosporium sp.), hyphomycetes (Aureobasidium sp.), and algae (Chlorella sp.) (De Leo et al., 2021).

Polyoxometalates (POMs) are also being considered as biocidal agents. POMs are a large

group of anionic polynuclear metal—oxo clusters with discrete and chemically modifiable structures (Gumerova and Rompel, 2020; Miras et al., 2012). Generally based on group 6 transition metals (Mo, W), and sometimes group 5 (V, Nb, Ta), these closed 3-dimensional frameworks are characterized by a wide and versatile range of physicochemical properties that can be specifically tailored at a molecular level. Their polyanionic feature allows them to form complexes with many proteins or peptides containing cationic residues through ionic bonds. For these reasons, many reports have reported both a direct antibacterial activity and a synergistic one with conventional antibiotics (Bijelic et al., 2018). For instance, polyoxotungstates have been shown to exhibit antibacterial activities against *Helicobacter pylori* (Inoue et al., 2005). Moreover, Gumerova *et al.* demonstrated that of the 29 different POMS tested, the polyoxotungstate [NaP<sub>5</sub>W<sub>30</sub>O<sub>110</sub>]<sup>14-</sup> showed the highest activity against *Moraxella catarrhalis* (Gumerova et al., 2018). However, most of the inorganic POMs do not exhibit biocidal activities strong enough to be exploited yet as coatings for building materials. It is also worthy of mention that attempts have been made to combine the properties of

polyoxametalated anions and the organic cations coming from ionic liquids. In this way, silicotungstate and phosphotungstate-based POM-ILs fused with long-chain quaternary alkylammonium cations have been shown to exhibit an enhanced antifungal activity on historical bricks (Rajkowska et al., 2020). Another study demonstrated that hydrophobic polyoxotungstate POM-ILs could be used as suitable anti-corrosion and antibacterial coatings for natural stones (Misra et al., 2018).

# 7. "Natural compounds": on the path to the discovery of sustainable antifoulings?

We explained above that Nature is a source of inspiration for manufacturers and researchers, particularly through the design of biomimetic materials like, for example, those imitating the "lotus effect". The natural environment is also a source of antifouling compounds, and more especially plants and algae that are naturally resistant to microbial damage. Thus, naturalist observations also inspire another type of biomimetic approach to discover efficient antifouling compounds: observing nature to identify bioactive compounds before producing them at the industrial scale. "Natural compounds", *i.e.*, compounds that are not molecules purely synthesized by industrial processes but primarily by natural organisms, are hypothesized to be less toxic than purely synthetic alternatives. They thus appear as promising molecules to fight biodeterioration. The scientific literature on natural biocides that can be used against biodeterioration of stone cultural heritage is extensive (Fidanza and Caneva, 2019). More than sixty natural substances, mainly essential oils and substances of plant origin, have been the subject of published scientific evaluations for this type of application. However, in most cases, their substantial cost of production makes them, for the moment, non-adapted to fight biodeterioration at large scales.

#### 7.1 Plants and essential oils

## • 7.1.1 Nature and commercially available compounds

Many plants have shown antimicrobial properties, such as Chili peppers, Eucalyptus globulus, *Melaleuca alternifolia* (tea tree), or *Thymus vulgaris* (Jeong et al., 2018; Omolo et al., 2014; Palla et al., 2020) (Table 1). For peppers and especially species related to the genus *Capsicum*, the active molecule has been identified and is called capsaicin (8-Methyl-N-vanillyl-trans-6-nonenamide, CAS: 404-86-4) (Table 2) (Omolo et al., 2014). This compound has shown antibacterial activities against many pathogens, such as *Vibrio cholerae* and *Staphylococcus aureus* (Mokhtar et al., 2017; Omolo et al., 2014), and also antifungal properties (Martini et al., 2014). Often, the active molecule produced by plants is available through the use of essential oils (EOs) or purified secondary metabolites such as thymol (2-isopropyl-5-methylphenol, CAS: 89-83-8), eugenol (2-Methoxy-4-(2-propenyl)phenol, CAS Number: 97-53-0) or cinnamaldehyde (3-Phenylprop-2-enal, CAS: 104-55-2) (Table 2) (Jesus et al., 2015; Marchese et al., 2016; Palla et al., 2020; Veneranda et al., 2018). EOs and secondary metabolites are readily available commercially or from specialized chemical companies (e.g., Sigma-Aldrich). The capsaicin and its synthetic equivalent, the N-vanillynonanamide (CAS: 2444-46-4), are also easily purchased (Table 2).

#### • 7.1.2 Historical and current use

Plants and their derivatives as EOs have been employed for centuries for their natural antimicrobial properties (Algburi et al., 2017; Nazzaro et al., 2013). The earliest documented traces of the medicinal application of plants date back 5,000 years (Petrovska, 2012). Today, in addition to being used in the pharmaceutical and aromatherapy industries, EOs are also applied in the food industry (Gadea et al., 2017b; Palla et al., 2020). EOs and their component (secondary plant metabolites) are also tested in conservation due to the need for new cleaning procedures using less harmful molecules for both human health and cultural heritage

preservation (Fidanza and Caneva, 2019; Palla et al., 2020; Sasso et al., 2016; Veneranda et al.,2018).

#### • 7.1.3 Efficacy

989

990

991

992

993

994

995

996

997

998

999

1000

1001

1002

1003

1004

1005

1006

1007

1008

1009

1010

1011

Some EOs and plant secondary metabolites are very effective against bacteria, algae, and fungi at low concentrations (Gómez de Saravia et al., 2018; Nazzaro et al., 2013; Owen and Laird, 2018; Sasso et al., 2016; Veneranda et al., 2018). For instance, only 0.4 mg.mL<sup>-1</sup> of oregano essential oil (OEO) is sufficient to inhibit the bacterial growth of methicillin-resistant Staphylococcus aureus (MRSA) (Cui et al., 2019). Moreover, EOs have shown synergistic interactions with antibiotics reducing drug resistance (Owen and Laird, 2018). However, their action mechanisms remain poorly understood due to their high chemical variability and broadspectrum activities (Algburi et al., 2017; Owen and Laird, 2018). For example, OEO has been demonstrated to affect cell membrane permeability, respiratory metabolism, energy metabolism, and gene expression of MRSA (Cui et al., 2019). Essential oils are complex mixtures of active substances whose antimicrobial activities vary from one substance to another. OEO and its components, carvacrol (5-Isopropyl-2-methylphenol, CAS number 499-75-2) and thymol, are also described as putative efflux-pump blockers (Table 2) (Cirino et al., 2015). Finally, some EOs as of *Eucalyptus* sp. are quorum sensing (QS) inhibitors, and QS is a key bacterial mechanism involved in biofilm formation (more details below) (Algburi et al., 2017; Nazzaro et al., 2013; Szabó et al., 2010).

### • 7.1.4 Advantages and drawbacks

Due to their wide range of targets, EOs are promising in many different applications to avoid the use of antibiotics and biocides, such as cultural heritage preservation (Algburi et al., 2017; Fidanza and Caneva, 2019; Gadea et al., 2017b; Owen and Laird, 2018; Veneranda et al., 2018). Some EOs appear very efficient, even at low concentrations as described above (Nazzaro et al., 2013; Owen and Laird, 2018). Some of EOs or plant extracts such as Lavendin oil (CAS:

91722-69-9) and geraniol (CAS: 106-24-1) are already included in the European Biocidal Products Regulation list (Article 95 of the Biocidal Products Regulation (BPR), as amended by Regulation (EU) No 334/2014 of 11 March 2014) (European Chemicals Agency, 2014; Veneranda et al., 2018). The most recently added biocidal plant compound was garlic extract (CAS: 8008-99-9) in April 2020 (European Chemicals Agency, 2020). These additions to the BPR list also highlight the interest of private companies in the development of new natural biocidal products. Many EOs have shown antimicrobial properties against various types of microorganisms, like cyanobacteria as *Nostoc* sp. and *Gloeocapsa* sp. (Table 1) (Bartolini and Pietrini, 2016; Cuzman, 2009; Devreux et al., 2015). For example, EO from Melaleuca alternifolia had been efficient against bacteria like Micrococcus luteus and Bacillus subtilis; and against fungi as Aspergillus sp. and Cladosporium sp. (Fidanza and Caneva, 2019; Mansour, 2013; Rotolo et al., 2016). In addition, EO from *Thymus vulgare* has also shown antialgal effect on Chlorella sp. and Aptacoccus sp. (Bartolini and Pietrini, 2016; Fidanza and Caneva, 2019). Despite their enormous potential, the safety of EOs must be assessed. Especially in the medical field, where EO-antibiotic combinations need to be more closely studied and their potential toxicity measured before further development (Algburi et al., 2017; Owen and Laird, 2018). For building materials, most of the studies were carried out *in-vitro* (Gómez de Saravia et al., 2018; Veneranda et al., 2018). Therefore, it is necessary to explore the possible interactions between EOs and building materials before considering their usage at larger scales. Finally, some natural products are pointed to their deleterious effects on human health. For example, while capsaicin and chili peppers derivatives are very efficient as antimicrobials or pain relievers (Martini et al., 2014; Omolo et al., 2014); but they are also very irritant, as shown by their use in pepper sprays (Oliveira Junior et al., 2020; Omolo et al., 2014). This is also the case of Geraniol (3,7-dimethylocta-trans-2,6-dien-1-ol, CAS: 106-24-1), which is one of the

1012

1013

1014

1015

1016

1017

1018

1019

1020

1021

1022

1023

1024

1025

1026

1027

1028

1029

1030

1031

1032

1033

1034

1035

1036

most important molecules in cosmetic industries for its antimicrobial activities (Chen and Viljoen, 2010) and can induce allergic reactions such as irritant contact dermatitis (Johansen et al., 2020).

### • 7.1.5 Future and perspectives

If we suppose low toxicity of EOs, and the use of these compounds does not induce deleterious effects on building materials, these substances may represent an up-and-coming alternative to purely synthetic compounds to prevent building biodeterioration due to their broad spectrum of activities and targets. However, a major obstacle to use this type of natural compound is their substantial cost to manufacturers, which is much higher than the cost of the conventional biocides currently in use. For example, natural products like geraniol are sold between 1 and 5€ per gram and EOs in between 50 and 100€ per kilogram, while solutions based on quaternary ammonium compounds (like Organcide QC50) are sold between 10 and 20€ per kilogram.

#### 7.2 "Natural" compounds: conclusions

Natural compounds are highly effective against a large number of targets (bacteria, fungi, algae) through a wide diversity of action mechanisms (QS inhibition, modification of cell permeability, or energy metabolism), and they can bypass the resistance of some bacteria to biocides (efflux pump inhibition). Consequently, they appear very promising to prevent the biodeterioration of building materials. They also could be mixed with conventional biocide as on temples in Angkor Vat (Cambodia), where they have shown excellent results (Charola and Salvadori, 2011). The "Mélange d'Angkor" is made of thymol, quaternary ammonium compounds, borax, copper-complex, Mergal S90, and S88, Zn-Omadine, Algophase (PHASE, Firenze, Italy), Parmetol DF 12 (Schülke & Mayr, Norderstedt, Germany). In the latter, the "Mélange d'Angkor" was applied in the field, and the cleaning effect lasted up to 10 years, depending on the site and time of treatment. However, the effectiveness of natural compounds

has so far mainly been demonstrated *in-vitro*, and their potentially deleterious effects on materials remain unknown, as well as the cost of their application on industrial scales.

# 8. Future research and development strategies to develop "green" and sustainable antifouling for building materials?

Throughout this review, an apparent contradiction exists in the challenge we discuss: On the one hand, antifouling compounds should present a very strong biocidal activity to prevent the development of very diverse microorganisms forming multispecies biofilms including various types of eukaryotes and prokaryotes. On the other hand, sustainable antifoulings should ideally be compounds that have a low impact on health and the environment, thus, *a priori*, low biological activity. Thus, the goal of current research and development strategies is to find solutions to address this *a priori* unsolvable paradox (Lami, 2019). This analysis highlights the reason why the antifouling "miracle" compounds, which are advertised on the market from time-to-time, cannot completely solve the problem of biodeterioration on building materials. One potential solution is to target specific biological mechanisms that control biofilm development without killing the microbial cells, *i.e.*, inhibiting specific microbial functions (in other words, *antibiofilm* solutions that are not *biocide*).

In this perspective, the development of quorum quenching compounds (QQ) appears extremely promising (Lami, 2019). The biofilm that grows on building materials promotes bacterial interactions, in particular by facilitating chemical communication between microorganisms; among those, one common type is named quorum sensing (QS) (Romani et al., 2021a; Xavier and Foster, 2007). QS is a coordinated response of the microbial community from a certain cell density (quorum), which involves the production of extracellular chemical signals (sensing) (Henke and Bassler, 2004). These signals accumulate in the immediate

environment until they reach the level necessary to activate the transcription of specific genes (Whiteley et al., 2017). QS was first demonstrated in the marine model *Vibrio fischeri*, which emits bioluminescence when the cell concentration in the environment is sufficient (Whiteley et al., 2017). However, QS is involved in a wide range of bacterial mechanisms, including, among others, biofilm formation (Girard et al., 2019; Kalia, 2018). Therefore, inhibiting this key bacterial mechanism seems particularly promising in the fight against environmental biofilms (Algburi et al., 2017; Kalia, 2018), as QQs are not biocides but inhibit cell mechanisms involved in biofilm formation. Consequently, such compounds hold the promise to solve the paradox we raise previously, targeting the biofilm without presenting high cytotoxicity. Also, the resistance of microorganisms to these compounds is suspected of appearing at lower rates compared to that against biocides substances (Rémy et al., 2018).

Interestingly, these bioactive compounds are frequently discovered, setting up biomimetic approaches (Scardino and de Nys, 2011), after an attentive observation of antifouling traits among natural species and in combination with an in-depth analysis of their microbiota (Tourneroche et al., 2019; Vallet et al., 2020). In addition to the EOs described above, some organisms are capable of producing anti-QS molecules (quorum quenchers), such as bacteria as *Bacillus* sp., *Pseudomonas* sp., *Rhodococcus* sp., and *Streptomyces* sp. or fungi as *Cladosporium cladosporioides*, and algae as *Stichococcus bacillaris*, which, interestingly, were also previously identified on building materials (Coutinho et al., 2015; Di Martino, 2016; Paul et al., 2018; Romani et al., 2021a, 2019; Urzì et al., 2010). This is also the case of the halogenated furanones discovered in *Delisea pulchra* (Manefield et al., 1999) or of the butyrolactones identified in the microbiota of the brown macroalga *Saccharina latissima* (Vallet et al., 2020). The best-known quorum quenchers are enzymes AHL-lactonases that hydrolyze QS compounds (the acyl-homoserine lactones) by cleaving the ester bond of their lactone ring (Paul et al., 2018). Despite these advances, more research and development efforts

are needed to better understand the mechanisms of action of these promising compounds and their effective innocuity on health and the environment (Lami, 2019). Thus, the development of these new treatments will require more investment, and even if this research strategy appears promising, the road remains long before the commercialization of such products at large scales. Nevertheless, the challenge has been taken by a few startups, in partnership with academic research labs, like Green&GeneTK at the IHU Marseille, France, a consortium specialized in the production of anti-QS enzymes.

Another promising strategy that has already produced interesting results in the field is the use of microorganisms capable of removing corrosive substances, especially on metal surfaces where aerobic biofilms have been shown to protect against corrosion by reactive oxygen species (Kip and Van Veen, 2015). For example, *Bacillus* sp. presented anti-corrosion activities related to the production of two enzymes, a catalase and a peroxidase. By contrast, strains that produced little or no catalase tended to induce the corrosion process (Karn et al., 2017). Certain noncorrosive microorganisms can also form a protective layer on materials (De Muynck et al., 2010). This method is used to prevent corrosion of stone, limestone, and concrete and is based on microbial carbonate precipitation (Kip and Van Veen, 2015). The carbonate precipitates (mainly calcium carbonate) produced by bacteria are similar to concrete and mortar, attach to them and thus strengthen the material, and can even fill and repair small cracks (Jonkers et al., 2010). For example, Bacillus subtilis, which has been identified on many building materials (Coutinho et al., 2015; Di Martino, 2016), can produce calcium carbonates. It has also been shown that the use of bacterial fractions containing their cell walls alone is sufficient to induce the production of calcium carbonates, thus avoiding the inoculation of living microorganisms on the materials (Perito et al., 2014).

1111

1112

1113

1114

1115

1116

1117

1118

1119

1120

1121

1122

1123

1124

1125

1126

1127

1128

1129

1130

1131

1132

1133

# 9. Conclusions: A toolbox and methodology for the development of innovative, efficient, and eco-friendly solutions: case by case analysis, multidisciplinary, integrative, and pragmatic approaches.

When considering the list of compounds and solutions reviewed here, it appears that no "gold standard" methodology against biodeterioration has been yet established. Such a reference approach would have to combine high efficiency against biofilms growth and their induced building biodeterioration, low production cost, and high ecological standards. While in the present state of scientific knowledge, the combination of these criteria appears too paradoxical to be solved (Figure 2). Some interesting, innovative research strategies presented in this review are currently being developed in research labs and might pave the way for the future. Furthermore, the recent development of "omics" approaches combining metagenomics, metatranscriptomics, metabolomics, and metaproteomics will also contribute to this quest in the near future (Stien et al., 2020, 2019). Indeed, such a multi-omics approach will help to point out novel and unsuspected metabolic pathways and mechanisms to serve as targets in the design of innovative solutions.

In the present situation, since no "gold standard methodology" has yet been established, our recommendation would be to address the problem of biodeterioration on a case-by-case basis, adopting a multidisciplinary research strategy, associating the skills of biologists, chemists, and material designers. Such an approach enables to draw solutions adapted to each particular situation and type of biodeterioration (Liu et al., 2020). For example, this process of work was used to treat temples in Angkor Vat (Cambodia) (Warscheid and Leisen, 2011) and ruins of the archeological site of Milet (Turkey), where the black microbial biofilm needed to be removed as it enhanced the heating effect leading to a microcracking of the marble (Charola and

Salvadori, 2011). On both sites, innovative case-by-case solutions were successfully designed without mechanical impact.

The design of innovative solutions should systematically rely on a very detailed analysis of biofilm composition and activities, which consist of an in-depth analysis of the bacterial, algal, and fungal diversities (and functions) forming the deteriorating multispecies biofilms, combining the state of the art of culture-dependent and culture-independent methodologies (Romani et al., 2021a, 2019). From this precise assessment, different possible solutions can be considered and likely combined in a specific fashion for each specific case. For example, a pretreatment with water-repellent coatings helps to lower the required concentrations of various types of biocides, which is a first step in the design of more ecologically friendly solutions (Romani et al., 2021b). Also, an in-depth analysis of the microbial composition colonizing building materials is essential to select the best biocide or coating to use, thus avoiding the use of non-essential compounds and their release in the environment. In this logic, targeting pioneering bacteria and pioneering biofilms, which can develop even on unexposed materials (Romani et al., 2019), appears to be one of the most promising strategies to lower the amount and concentrations of the applied antifouling compounds.

In addition to the choice of chemicals, it is important to optimize their application to the materials. Thus, the development of adapted protocols for biocides has a significant impact on their effectiveness (Favero-Longo et al., 2020). For example, the effectiveness of different biocides is higher if the lichen thalli are hydrated before their use and if the biocidal substance is applied with a cellulose poultice. Similarly, when a hydrogel is used to apply a biocide solution to a polymicrobial patina, a high percentage of water loading is essential to ensure a deep antimicrobial action (Boccalon et al., 2021). The application of hydrogels delivering biocides has shown great results on stone (Gabriele et al., 2021); however, their use on highly

porous stones is not recommended, as antimicrobial action remains superficial in such cases (Favero-Longo et al., 2020).

As shown in this paper, fundamental scientific knowledge is necessary to prevent the biodeterioration of outdoor building materials efficiently. Today, all biocidal products used for building preservation are registered as preservatives or disinfectants in annex V of the BPR, EU 528/2012, which means that they are tested only on human pathogens. Also, the usage concentrations of these biocidal products are determined on the basis of such tests conducted on non-environmentally relevant microbial models. Such observation highlights the urgent need to isolate more representative microbial models from the environment and to test the effectiveness of current and future solutions in suitable biotests which rely on their culture rather than on representative human pathogens. Such effort will lead to better adapt current regulations and will allow the industry to improve the marketed solutions for the control of outdoor building materials biodeterioration.

Collectively, all these observations reinforce the necessity to establish strong links between academic research labs and building materials manufacturers, to transfer the multidisciplinary scientific knowledge and tools, and to custom solutions to the end-user needs (Figure 2). Some countries develop governmental programs to favor the establishment of these academy-industry links. For example, the French government offers specific funding like the Ph.D. CIFRE program (which is leading the Ph.D. student to work at the interface in between academic labs and companies), or through the "Crédit Impôt Recherche", which gives many financial advantages to the companies that invest in research in partnership with the academic labs (tax reduction). The creation of deep tech startups is also encouraged and allows public financial support.

The development of innovative and sustainable solutions will rely on a significant investment throughout the entire production chain: in fundamental research to develop

alternative and lower toxic compounds, in applied research to select the best solutions, in production systems to industrialize at large scales the innovative solutions, in commercialization and marketing to raise end-user awareness to the health and environmental challenges and undoubtedly to increase customer tolerance to biodeterioration.

## **Credit authorship contribution statement**

This review was built according to the guidelines of the Transparent Reporting of Systematic Reviews and Meta-Analysis extension for scoping reviews (PRISMA-Scr). Electronic sources were Medline (via Pubmed), Scopus (Elsevier: Amsterdam, The Netherlands), and Web of Science (Clarivate Analytics: Philadelphia, PA, USA). Papers were retrieved using the following keywords: biodeterioration + building material (or stone or ceramic) + cleaning procedures, biodeterioration + building material (or stone or ceramic) + type of biocide, biodeterioration + building material (or stone or ceramic) + water repellent, biodeterioration + building material (or stone or ceramic) + natural compounds. Research excluded from this analysis were articles related to indoor materials and articles related to human health.

# Acknowledgments

This work was funded by the Sorbonne University Grant n°C17/2072-P16/0888. The work reported in this article was partly financed by the building material industry. The authors declare full access to all study data and declare that the work was neither supervised nor audited by the company. The interpretation and views expressed in this manuscript are not those of the company. The authors had authority over the manuscript preparation and decisions to submit the manuscript for publication.

1	1232	References
	1 Z <b>3</b> Z	References

- 1233 Aerts, O., Lambert, J., Goossens, A., 2017. Structures chimiques et allergies croisées entre
- isothiazolinones. Rev. Fr. Allergol. 57, 178–180.
- 1235 https://doi.org/10.1016/j.reval.2017.02.013
- 1236 Algburi, A., Comito, N., Kashtanov, D., Dicks, L.M.T., Chikindas, M.L., 2017. Control of
- biofilm formation: Antibiotics and beyond. Appl. Environ. Microbiol. 83.
- 1238 https://doi.org/10.1128/AEM.02508-16
- 1239 Amara, I., Miled, W., Slama, R. Ben, Ladhari, N., 2018. Antifouling processes and toxicity
- effects of antifouling paints on marine environment. A review. Environ. Toxicol.
- Pharmacol. 57, 115–130. https://doi.org/10.1016/j.etap.2017.12.001
- 1242 Ameta, R., Solanki, M.S., Benjamin, S., Ameta, S.C., 2018. Photocatalysis, Advanced
- oxidation processes for wastewater treatment: Emerging green chemical technology.
- 1244 https://doi.org/10.1016/B978-0-12-810499-6.00006-1
- 1245 Arabzadeh, A., Ceylan, H., Kim, S., Gopalakrishnan, K., Sassani, A., Sundararajan, S., Taylor,
- P.C., 2017. Superhydrophobic coatings on Portland cement concrete surfaces. Constr.
- Build. Mater. 141, 393–401. https://doi.org/10.1016/j.conbuildmat.2017.03.012
- Bao, O., Nishimura, N., Kamata, H., Furue, K., Ono, Y., Hosomi, M., Terada, A., 2017.
- 1249 Antibacterial and anti-biofilm efficacy of fluoropolymer coating by a 2,3,5,6-tetrafluoro-
- p-phenylenedimethanol structure. Colloids Surfaces B Biointerfaces 151, 363–371.
- 1251 https://doi.org/https://doi.org/10.1016/j.colsurfb.2016.12.020
- Barberousse, H., Lombardo, R.J., Tell, G., Couté, A., 2006. Factors involved in the colonisation
- of building façades by algae and cyanobacteria in France. Biofouling 22, 69–77.
- 1254 https://doi.org/10.1080/08927010600564712
- Barrionuevo, M.R.E., Gaylarde, C.C., 2011. Biocide-containing varnish for the protection of

- sandstone: comparison of formulations and laboratory test methods. Curr. Microbiol. 62,
- 1257 1671–1676. https://doi.org/https://doi.org/10.1007/s00284-011-9912-6
- Barthlott, W., Neinhuis, C., 1997. Purity of the sacred lotus, or escape from contamination in
- biological surfaces. Planta 202, 1–8. https://doi.org/10.1007/s004250050096
- Bartolini, M., Pietrini, A.M., 2016. La disinfezione delle patine biologiche sui manufatti
- lapidei: Biocidi chimici e naturali a confronto. Boll. ICR 33, 40–49.
- Batista-Andrade, J.A., Caldas, S.S., Batista, R.M., Castro, I.B., Fillmann, G., Primel, E.G.,
- 1263 2018. From TBT to booster biocides: Levels and impacts of antifouling along coastal areas
- of Panama. Environ. Pollut. 234, 243–252. https://doi.org/10.1016/j.envpol.2017.11.063
- Bayar R. Brick, 1951. Method of coating porous mansory to render it water repellent US
- 1266 2,572,168. https://doi.org/10.1145/178951.178972
- 1267 Becerra, J., Ortiz, P., Zaderenko, A.P., Karapanagiotis, I., 2020. Assessment of
- nanoparticles/nanocomposites to inhibit micro-algal fouling on limestone façades. Build.
- Res. Inf. 48, 180–190. https://doi.org/10.1080/09613218.2019.1609233
- Becerra, J., Zaderenko, A.P., Sayagués, M.J., Ortiz, R., Ortiz, P., 2018. Synergy achieved in
- silver-TiO2 nanocomposites for the inhibition of biofouling on limestone. Build. Environ.
- 1272 141, 80–90. https://doi.org/https://doi.org/10.1016/j.buildenv.2018.05.020
- Berdahl, P., Akbari, H., Levinson, R., Miller, W.A., 2008. Weathering of roofing materials –
- 1274 An overview. Constr. Build. Mater. 22, 423–433.
- 1275 https://doi.org/10.1016/j.conbuildmat.2006.10.015
- Bijelic, A., Aureliano, M., Rompel, A., 2018. The antibacterial activity of polyoxometalates:
- structures, antibiotic effects and future perspectives. Chem. Commun. 54, 1153–1169.
- 1278 https://doi.org/10.1039/C7CC07549A
- Boccalon, E., Nocchetti, M., Pica, M., Romani, A., Sterflinger, K., 2021. Hydrogels: A
- 1280 'stepping stone' towards new cleaning strategies for biodeteriorated surfaces. J. Cult.

- Herit. 47, 1–11. https://doi.org/10.1016/j.culher.2020.07.008
- Bollmann, U.E., Fernández-Calviño, D., Brandt, K.K., Storgaard, M.S., Sanderson, H., Bester,
- 1283 K., 2017. Biocide runoff from building facades: degradation kinetics in soil. Environ. Sci.
- Technol. 51, 3694–3702. https://doi.org/10.1021/acs.est.6b05512
- Boonen, E., Beeldens, A., Dirkx, I., Bams, V., 2016. Durability of cementitious photocatalytic
- building materials. Catal. Today 287, 196–202.
- 1287 https://doi.org/10.1016/j.cattod.2016.10.012
- Brinker, C.J., Scherer, G.W., 2013. Sol-gel science: the physics and chemistry of sol-gel
- 1289 processing. Academic press.
- Bruchertseifer, C., Brüggerhoff, S., Grobe, J., Stoppek-Langner, K., 1995. Long-term exposure
- of traited natural stone development and first results of a testing concept. Proc. First Int.
- 1292 Symp. Surf. Treat. Build. Mater. with Water Repel. Agents 1–11.
- Brycki, B.E., Kowalczyk, I.H., Szulc, A., Kaczerewska, O., Pakiet, M., 2017. Multifunctional
- gemini surfactants: structure, synthesis, properties and applications. Appl. Charact.
- 1295 Surfactants 97–155. https://doi.org/10.5772/intechopen.68755
- 1296 Callow, J.A., Callow, M.E., 2011. Trends in the development of environmentally friendly
- fouling-resistant marine coatings. Nat. Commun. 2, 244.
- 1298 https://doi.org/10.1038/ncomms1251
- 1299 Cantiello, A., Candamano, S., De Luca, P., 2020. Use of zinc ferrite for photocatalytic treatment
- of water contaminated with organic dye, in: IOP Conference Series: Materials Science and
- Engineering. https://doi.org/10.1088/1757-899X/739/1/012054
- Cappitelli, F., Cattò, C., Villa, F., 2020. The control of cultural heritage microbial deterioration.
- Microorganisms 8, 1–20. https://doi.org/10.3390/microorganisms8101542
- 1304 Carretero-Genevrier, A., Boissiere, C., Nicole, L., Grosso, D., 2012. Distance dependence of
- the photocatalytic efficiency of TiO2 revealed by in situ ellipsometry. J. Am. Chem. Soc.

- 1306 134, 10761–10764. https://doi.org/https://doi.org/10.1021/ja303170h
- 1307 Chand, R., Tulucan, T., Aburlacitei, M., 2018. Investigation of biocide biodegradation in
- wastewater under laboratory set-up in anaerobic, aerobic and aerobic with substrate
- 1309 conditions. J Civ. Env. Eng 8, 2. https://doi.org/https://doi.org/10.4172/2165-
- 1310 784X.1000295
- 1311 Charola, A.E., 2001. Water repellents and other "protective" treatments: A critical review, in:
- Restoration of Buildings and Monuments. pp. 3–22.
- 1313 https://doi.org/https://doi.org/10.1515/rbm-2003-5727
- 1314 Charola, A.E., 1995. Water-repellent treatments for building stones: a practical overview. APT
- Bull. 26, 10. https://doi.org/10.2307/1504480
- 1316 Charola, E., Salvadori, O., 2011. Methods to prevent biocolonization and recolonization: An
- overview of current research for architectural and archaeological heritage. Biocolonization
- 1318 Stone Control Prev. methods, Proc. from MCI Work. Ser. 38–39.
- 1319 Chen, C.Z., Cooper, S.L., 2000. Recent advances in antimicrobial dendrimers. Adv. Mater. 12,
- 1320 843–846. https://doi.org/https://doi.org/10.1002/(SICI)1521-
- 1321 4095(200006)12:11<843::AID-ADMA843>3.0.CO;2-T
- 1322 Chen, C.Z., Cooper, S.L., Tan, N.C.B., 1999. Incorporation of dimethyldodecylammonium
- chloride functionalities onto poly (propylene imine) dendrimers significantly enhances
- their antibacterial properties. Chem. Commun. 1585–1586.
- 1325 Chen, F., Yang, X., Mak, H.K.C., Chan, D.W.T., 2010. Photocatalytic oxidation for
- antimicrobial control in built environment: A brief literature overview. Build. Environ. 45,
- 1327 1747–1754. https://doi.org/10.1016/j.buildenv.2010.01.024
- 1328 Chen, W., Viljoen, A.M., 2010. Geraniol A review of a commercially important fragrance
- material. South African J. Bot. 76, 643–651. https://doi.org/10.1016/j.sajb.2010.05.008
- 1330 Cheng, Y.T., Rodak, D.E., 2005. Is the lotus leaf superhydrophobic? Appl. Phys. Lett. 86, 1–3.

- 1331 https://doi.org/10.1063/1.1895487
- 1332 Cirino, I.C.S., Menezes-Silva, S.M.P., Silva, H.T.D., De Souza, E.L., Siqueira-Júnior, J.P.,
- 1333 2015. The Essential Oil from Origanum vulgare L. and Its Individual Constituents
- 1334 Carvacrol and Thymol Enhance the Effect of Tetracycline against Staphylococcus aureus.
- 1335 Chemotherapy 60, 290–293. https://doi.org/10.1159/000381175
- 1336 Commission Européenne, 2012. Règlement (UE) N° 528/2012 du parlement européen et du
- 1337 conseil du 22 mai 2012 concerant la mise à disposition sur le marché et l'utilisation des
- produits biocides. J. Off. l'union Eur. 1–123.
- 1339 Coronado, J.M., Fresno, F., Hernández-Alonso, M.D., Portela, R., 2013. Design of advanced
- photocatalytic materials for energy and environmental applications. Green Energy
- 1341 Technol. 71, 1–4. https://doi.org/10.1007/978-1-4471-5061-9
- 1342 Coutinho, M.L., Miller, A.Z., Macedo, M.F., 2015. Biological colonization and
- biodeterioration of architectural ceramic materials: An overview. J. Cult. Herit. 16, 759–
- 1344 777. https://doi.org/10.1016/j.culher.2015.01.006
- Cui, H., Zhang, C., Li, C., Lin, L., 2019. Antibacterial mechanism of oregano essential oil. Ind.
- 1346 Crops Prod. 139, 111498. https://doi.org/10.1016/j.indcrop.2019.111498
- Cuzman, O.A., 2009. Biofilms on exposed monumental stones: mechanism of formation and
- development of new control methods. https://doi.org/10.6092/unibo/amsdottorato/2257
- Dalawai, S.P., Saad Aly, M.A., Latthe, S.S., Xing, R., Sutar, R.S., Nagappan, S., Ha, C.S.,
- Kumar Sadasivuni, K., Liu, S., 2020. Recent Advances in durability of superhydrophobic
- self-cleaning technology: A critical review. Prog. Org. Coatings.
- https://doi.org/10.1016/j.porgcoat.2019.105381
- Daubert, G.P., Spiller, H.A., Crouch, B.I., Seiferta, S.A., Simone, K.E., Smolinske, S.C., 2009.
- Pulmonary toxicity following exposure to waterproofing grout sealer. J. Med. Toxicol. 5,
- 1355 125–129. https://doi.org/https://dx.doi.org/10.1007%2FBF03161222

- De Leo, F., Marchetta, A., Capillo, G., Germanà, A., Primerano, P., Schiavo, S. Lo, Urzì, C.,
- 1357 2021. Surface active ionic liquids based coatings as subaerial anti-biofilms for stone built
- 1358 cultural heritage. Coatings 11, 26.
- https://doi.org/https://doi.org/10.3390/coatings11010026
- De Muynck, W., De Belie, N., Verstraete, W., 2010. Microbial carbonate precipitation in
- 1361 construction materials: A review. Ecol. Eng. 36, 118–136.
- https://doi.org/10.1016/j.ecoleng.2009.02.006
- Delgado, J.M., Nunes, D., Fortunato, E., Laia, C.A.T., Branco, L.C., Vilarigues, M., 2017. The
- effect of three luminescent ionic liquids on corroded glass surfaces—A first step into
- stained-glass cleaning. Corros. Sci. 118, 109–117.
- 1366 https://doi.org/10.1016/j.corsci.2017.01.027
- Devreux, G., Santamaria, U., Morresi, F., Rodolfo, A., Barbabietola, N., Fratini, F., Reale, R.,
- 1368 2015. Fitoconservazione. Trattamenti alternativi sulle opere in materiale lapideo nei
- giardini vaticani, in: Proceedings of the 13th Congresso Nazionale IGIIC-Lo Stato
- 1370 Dell'Arte. pp. 199–206.
- Di Martino, P., 2016. What about biofilms on the surface of stone monuments. Open Conf.
- 1372 Proc. J. 7, 14–28. https://doi.org/10.2174/22102892016070220014
- Di Nica, V., Gallet, J., Villa, S., Mezzanotte, V., 2017. Toxicity of Quaternary Ammonium
- 1374 Compounds (QACs) as single compounds and mixtures to aquatic non-target
- microorganisms: Experimental data and predictive models. Ecotoxicol. Environ. Saf. 142,
- 1376 567–577. https://doi.org/10.1016/j.ecoenv.2017.04.028
- Diz, M., Manresa, A., Pinazo, A., Erra, P., Infante, M., 1994. Synthesis, surface active
- properties and antimicrobial activity of new bis quaternary ammonium compounds. J.
- 1379 Chem. Soc. Perkin Trans. 2 1871–1876.
- Dréno, B., Alexis, A., Chuberre, B., Marinovich, M., 2019. Safety of titanium dioxide

- nanoparticles in cosmetics. J. Eur. Acad. Dermatology Venereol. 33, 34-46.
- 1382 https://doi.org/10.1111/jdv.15943
- Dubosc, A., 2000. Étude du développement de salissures biologiques sur les parements en
- béton : Mise au point d'essais accélérés de vieillissement. Institut National des Sciences
- 1385 Appliquées de Toulouse, Toulouse, France.
- Dyshlyuk, L., Babich, O., Ivanova, S., Vasilchenco, N., Atuchin, V., Korolkov, I., Russakov,
- D., Prosekov, A., 2020. Antimicrobial potential of ZnO, TiO2 and SiO2 nanoparticles in
- protecting building materials from biodegradation. Int. Biodeterior. Biodegrad. 146.
- 1389 https://doi.org/10.1016/j.ibiod.2019.104821
- Ebelmen, J.J., 1855. Recueil des travaux scientifiques de M. Ébelmen, Tome premier.
- ECHA, 2019. Annex XV restriction report Microplastics.
- Eibner, A., 1911. Action of Light on Pigments I. Chem-ZTG 35, 753–755.
- Elhagrassy, A.F., Hakeem, A., Alhagrassy, A.F., 2018. Comparative study of biological
- cleaning and laser techniques for conservation of weathered stone in Failaka island,
- 1395 Kuwait. Sci. Cult 4, 43–50. https://doi.org/10.5281/zenodo.1214561
- Emmanuel, E., Keck, G., Blanchard, J.M., Vermande, P., Perrodin, Y., 2004. Toxicological
- effects of disinfections using sodium hypochlorite on aquatic organisms and its
- 1398 contribution to AOX formation in hospital wastewater. Environ. Int. 30, 891–900.
- https://doi.org/10.1016/j.envint.2004.02.004
- Enning, D., Garrelfs, J., 2014. Corrosion of iron by sulfate-reducing bacteria: New views of an
- old problem. Appl. Environ. Microbiol. https://doi.org/10.1128/AEM.02848-13
- Ensikat, H.J., Ditsche-Kuru, P., Neinhuis, C., Barthlott, W., 2011. Superhydrophobicity in
- perfection: the outstanding properties of the lotus leaf. Beilstein J. Nanotechnol. 2, 152–
- 1404 161. https://doi.org/10.3762/bjnano.2.19
- 1405 Erlus Lotus Air® [WWW Document], n.d. URL https://www.erlus.com/fr/lotus

- European Chemicals Agency, 2020. Article 95 of the Biocidal Products Regulation (BPR) List.
- European Chemicals Agency, 2014. Article 95 of the Biocidal Products Regulation (BPR), as
- amended by Regulation (EU) No 334/2014 of 11 March 2014.
- 1409 European Commission, 2017a. COMMISSION REGULATION (EU) 2017/1224 of 6 July
- 1410 2017 amending Annex V to Regulation (EC) No 1223/2009 of the European Parliament
- and of the Council on cosmetic products. Comm. Regul. No 752/2014 15, 1–71.
- 1412 https://doi.org/http://eur-
- lex.europa.eu/pri/en/oj/dat/2003/1 285/1 28520031101en00330037.pdf
- European Commission, 2017b. COMMISSION DECISION (EU) 2017/1219 of 23 June 2017
- establishing the EU Ecolabel criteria for industrial and institutional laundry detergents.
- 1416 Off. J. Eur. Union L180, 79–96.
- 1417 Facio, D.S., Carrascosa, L.A.M., Mosquera, M.J., 2017. Producing Lasting Amphiphobic
- Building Surfaces with Self-Cleaning Properties. Nanotechnology 28, 0–12.
- 1419 https://doi.org/https://doi.org/10.1088/1361-6528/aa73a3
- Fassier, M., 2009. Interactions entre l'environnement et la terre cuite. Université de Limoges,
- Limoges, France.
- Faustini, M., Nicole, L., Ruiz-Hitzky, E., Sanchez, C., 2018. History of organic-inorganic
- hybrid materials: prehistory, art, science, and advanced applications. Adv. Funct. Mater.
- 28, 1704158. https://doi.org/https://doi.org/10.1002/adfm.201704158
- Favero-Longo, S.E., Benesperi, R., Bertuzzi, S., Bianchi, E., Buffa, G., Giordani, P., Loppi, S.,
- Malaspina, P., Matteucci, E., Paoli, L., Ravera, S., Roccardi, A., Segimiro, A., Vannini,
- 1427 A., 2017. Species- and site-specific efficacy of commercial biocides and application
- solvents against lichens. Int. Biodeterior. Biodegrad. 123, 127–137.
- 1429 https://doi.org/10.1016/j.ibiod.2017.06.009
- 1430 Favero-Longo, S.E., Brigadeci, F., Segimiro, A., Voyron, S., Cardinali, M., Girlanda, M.,

- Piervittori, R., 2018. Biocide efficacy and consolidant effect on the mycoflora of historical
- stuccos in indoor environment. J. Cult. Herit. 34, 33-42.
- 1433 https://doi.org/10.1016/j.culher.2018.03.017
- 1434 Favero-Longo, S.E., Vannini, A., Benesperi, R., Bianchi, E., Fačkovcová, Z., Giordani, P.,
- Malaspina, P., Martire, L., Matteucci, E., Paoli, L., Ravera, S., Roccardi, A., Tonon, C.,
- Loppi, S., 2020. The application protocol impacts the effectiveness of biocides against
- lichens. Int. Biodeterior. Biodegrad. 155. https://doi.org/10.1016/j.ibiod.2020.105105
- Favero-Longo, S.E., Viles, H.A., 2020. A review of the nature, role and control of lithobionts
- on stone cultural heritage: weighing-up and managing biodeterioration and bioprotection.
- World J. Microbiol. Biotechnol. 36, 100. https://doi.org/10.1007/s11274-020-02878-3
- 1441 Fellahi, O., Sarma, R.K., Das, M.R., Saikia, R., Marcon, L., Coffinier, Y., Hadjersi, T.,
- Maamache, M., Boukherroub, R., 2013. The antimicrobial effect of silicon nanowires
- decorated with silver and copper nanoparticles. Nanotechnology 24, 495101.
- 1444 https://doi.org/https://doi.org/10.1088/0957-4484/24/49/495101
- 1445 Ferreira Pinto, A.P., Delgado Rodrigues, J., 2000. Assessment of durability of water repellents
- by means of exposure tests. 9th Int. Congr. Deterior. Conserv. Stone 273–285.
- 1447 Fidanza, M.R., Caneva, G., 2019. Natural biocides for the conservation of stone cultural
- heritage: A review. J. Cult. Herit. https://doi.org/10.1016/j.culher.2019.01.005
- Flemming, H.C., Wingender, J., 2010. The biofilm matrix. Nat. Rev. Microbiol. 8, 623–633.
- 1450 https://doi.org/10.1038/nrmicro2415
- 1451 Fort González, R., López de Azcona, M.C., Mingarro Martín, F., Alvarez de Burgo Ballester,
- 1452 M., Rodriguez Blanco, J., 2000. A Comparative Study of the Efficiency of Siloxanes,
- Methacrylates and Microwaxes-Based Treatments Applied to the Stone Materials of the
- 1454 Royal Palace of Madrid, Spain. Proc. Ninth Int. Congr. Deterior. Conserv. Stone 2, 235–
- 1455 243.

- 1456 Frosch, P.J., John, S.M., 2011. Clinical aspects of irritant contact dermatitis, in: Contact
- Dermatitis (Fifth Edition), pp. 305–345. https://doi.org/10.1007/978-3-642-03827-3 16
- Fukuzaki, S., 2006. Mechanisms of actions of sodium hypochlorite in cleaning and disinfection
- processes. Biocontrol Sci. 11, 147–157. https://doi.org/10.4265/bio.11.147
- Gabriele, F., Vetrano, A., Bruno, L., Casieri, C., Germani, R., Rugnini, L., Spreti, N., 2021.
- New oxidative alginate-biocide hydrogels against stone biodeterioration. Int. Biodeterior.
- Biodegradation 163, 105281. https://doi.org/10.1016/j.ibiod.2021.105281
- Gadea, R., Fernández Fuentes, M.Á., Pérez Pulido, R., Gálvez, A., Ortega, E., 2017a. Effects
- of exposure to quaternary-ammonium-based biocides on antimicrobial susceptibility and
- tolerance to physical stresses in bacteria from organic foods. Food Microbiol. 63, 58–71.
- 1466 https://doi.org/10.1016/j.fm.2016.10.037
- Gadea, R., Glibota, N., Pérez Pulido, R., Gálvez, A., Ortega, E., 2017b. Effects of exposure to
- biocides on susceptibility to essential oils and chemical preservatives in bacteria from
- organic foods. Food Control 80, 176–182. https://doi.org/10.1016/j.foodcont.2017.05.002
- Ganguli, P., Chaudhuri, S., 2021. Nanomaterials in antimicrobial paints and coatings to prevent
- biodegradation of man-made surfaces: A review. Mater. Today Proc. 45, 3769–3777.
- 1472 https://doi.org/10.1016/j.matpr.2021.01.275
- Ganguly, P., Byrne, C., Breen, A., Pillai, S.C., 2018. Antimicrobial activity of photocatalysts:
- 1474 Fundamentals, mechanisms, kinetics and recent advances. Appl. Catal. B Environ. 225,
- 1475 51–75. https://doi.org/10.1016/j.apcatb.2017.11.018
- Garcia-Hidalgo, E., Schneider, D., von Goetz, N., Delmaar, C., Siegrist, M., Hungerbühler, K.,
- 1477 2018. Aggregate consumer exposure to isothiazolinones via household care and personal
- care products: Probabilistic modelling and benzisothiazolinone risk assessment. Environ.
- 1479 Int. 118, 245–256. https://doi.org/10.1016/j.envint.2018.05.047
- Garcia-hidalgo, E., Sottas, V., Goetz, N. Von, Hauri, U., Bogdal, C., Hungerbühler, K., 2016.

1481	Occurrence and concentrations of isothiazolinones in detergents and cosmetics in	
1482	Switzerland. Contact Dermatitis 96–106. https://doi.org/10.1111/cod.12700	
1483	Gaylarde, C., Ribas Silva, M., Warscheid, T., 2003. Microbial impact on building materials:	
1484	An overview. Mater. Struct. Constr. 36, 342–352. https://doi.org/10.1617/13867	
1485	Gazzano, C., Favero-Longo, S.E., Iacomussi, P., Piervittori, R., 2013. Biocidal effect of lichen	
1486	secondary metabolites against rock-dwelling microcolonial fungi, cyanobacteria and green	
1487	algae. Int. Biodeterior. Biodegrad. 84, 300–306.	
1488	https://doi.org/10.1016/j.ibiod.2012.05.033	
1489	Ghosh, S., Yadav, S., Vasanthan, N., Sekosan, G., 2010. A study of antimicrobial property of	
1490	textile fabric treated with modified dendrimers. J. Appl. Polym. Sci. 115, 716-722.	
1491	https://doi.org/https://doi.org/10.1002/app.31127gumero	
1492	Girard, L., Lantoine, F., Lami, R., Vouvé, F., Suzuki, M.T., Baudart, J., 2019. Genetic diversity	
1493	and phenotypic plasticity of AHL-mediated Quorum sensing in environmental strains of	
1494	Vibrio mediterranei. ISME J. 13, 159–169. https://doi.org/10.1038/s41396-018-0260-4	
1495	Gladis, F., Eggert, A., Karsten, U., Schumann, R., 2010. Prevention of biofilm growth on man-	
1496	made surfaces: Evaluation of antialgal activity of two biocides and photocatalytic	
1497	nanoparticles. Biofouling 26, 89–101. https://doi.org/10.1080/08927010903278184	
1498	Gladis, F., Schumann, R., 2011. Influence of material properties and photocatalysis on	
1499	phototrophic growth in multi-year roof weathering. Int. Biodeterior. Biodegrad. 65, 36-	
1500	44. https://doi.org/10.1016/j.ibiod.2010.05.014	
1501	Goffredo, G.B., Accoroni, S., Totti, C., 2019. Nanotreatments to inhibit microalgal fouling on	
1502	building stone surfaces, in: Nanotechnology in Eco-Efficient Construction. Elsevier Ltd,	
1503	pp. 619–647. https://doi.org/10.1016/b978-0-08-102641-0.00025-6	
1504	Goffredo, G.B., Accoroni, S., Totti, C., Romagnoli, T., Valentini, L., Munafò, P., 2017.	
1505	Titanium dioxide based nanotreatments to inhibit microalgal fouling on building stone	

- surfaces. Build. Environ. 112, 209–222. https://doi.org/10.1016/j.buildenv.2016.11.034
- 1507 Gómez de Saravia, S.G., Rastelli, S.E., Blustein, G., Viera, M.R., 2018. Natural compounds as
- potential algaecides for waterborne paints. J. Coatings Technol. Res. 15, 1191–1200.
- 1509 https://doi.org/10.1007/s11998-018-0099-7
- 1510 Goodeve, C.F., Kitchener, J.A., 1938. The mechanism of photosensitisation by solids. Trans.
- Faraday Soc. 34, 902–908. https://doi.org/10.1039/TF9383400902
- 1512 Government of Canada, 2019. Risk Management Scope for Phenol, 4-chloro-3-methyl
- 1513 (Chlorocresol), Chemical Abstracts Service Registry Number 59-50-7.
- 1514 Grabek-Lejko, D., Tekiela, A., Kasprzyk, I., 2017. Risk of biodeterioration of cultural heritage
- objects, stored in the historical and modern repositories in the Regional Museum in
- Rzeszow (Poland). A case study. Int. Biodeterior. Biodegrad. 123, 46–55.
- 1517 https://doi.org/10.1016/j.ibiod.2017.05.028
- Graziani, L., Quagliarini, E., D'Orazio, M., 2016. The role of roughness and porosity on the
- self-cleaning and anti-biofouling efficiency of TiO2-Cu and TiO2-Ag nanocoatings
- applied on fired bricks. Constr. Build. Mater. 129, 116–124.
- 1521 https://doi.org/https://doi.org/10.1016/j.conbuildmat.2016.10.111
- 1522 Graziani, L., Quagliarini, E., Osimani, A., Aquilanti, L., Clementi, F., D'Orazio, M., 2014. The
- influence of clay brick substratum on the inhibitory efficiency of TiO2 nanocoating against
- 1524 biofouling. Build. Environ. 82, 128–134.
- 1525 https://doi.org/https://doi.org/10.1016/j.buildenv.2014.08.013
- 1526 Gromaire, M.C., Van de Voorde, A., Lorgeoux, C., Chebbo, G., 2015. Benzalkonium runoff
- from roofs treated with biocide products In situ pilot-scale study. Water Res. 81, 279–
- 1528 287. https://doi.org/10.1016/j.watres.2015.05.060
- 1529 Guézennec, J., 2017. Biodégradation des matériaux quels risques pour la santé et
- 1530 l'environnement, Quae. ed.

- Guiamet, P., Crespo, M., Lavin, P., Ponce, B., Gaylarde, C., de Saravia, S.G., 2013.
- Biodeterioration of funeral sculptures in La Recoleta Cemetery, Buenos Aires, Argentina:
- Pre- and post-intervention studies. Colloids Surfaces B Biointerfaces 101, 337–342.
- 1534 https://doi.org/10.1016/j.colsurfb.2012.06.025
- 1535 Gulotta, D., Villa, F., Cappitelli, F., Toniolo, L., 2018. Biofilm colonization of metamorphic
- lithotypes of a renaissance cathedral exposed to urban atmosphere. Sci. Total Environ.
- 1537 639, 1480–1490. https://doi.org/10.1016/j.scitotenv.2018.05.277
- 1538 Gumerova, N.I., Al-Sayed, E., Krivosudský, L., Čipčić-Paljetak, H., Verbanac, D., Rompel, A.,
- 1539 2018. Antibacterial activity of polyoxometalates against Moraxella catarrhalis. Front.
- 1540 Chem. 6, 336. https://doi.org/10.3389/fchem.2018.00336
- Gumerova, N.I., Rompel, A., 2020. Polyoxometalates in solution: speciation under spotlight.
- 1542 Chem. Soc. Rev. 49, 7568–7601. https://doi.org/DOI
- 1543 https://doi.org/10.1039/D0CS00392A
- 1544 Guo, Z., Zhou, F., Hao, J., Liu, W., 2005. Stable biomimetic super-hydrophobic engineering
- materials. J. Am. Chem. Soc. 127, 15670–15671. https://doi.org/10.1021/ja0547836
- Hallmann, C., Rüdrich, J., Enseleit, M., Friedl, T., Hoppert, M., 2011. Microbial diversity on a
- marble monument: A case study. Environ. Earth Sci. 63, 1701–1711.
- 1548 https://doi.org/10.1007/s12665-010-0772-3
- Hashimoto, K., Irie, H., Fujishima, A., 2005. TiO 2 photocatalysis: A historical overview and
- future prospects. Japanese J. Appl. Physics, Part 1 Regul. Pap. Short Notes Rev. Pap. 44,
- 1551 8269–8285. https://doi.org/10.1143/JJAP.44.8269
- Heerklotz, H., 2008. Interactions of surfactants with lipid membranes. Q. Rev. Biophys. 41,
- 1553 205–264. https://doi.org/10.1017/S0033583508004721
- Hekster, F.M., Laane, R.W.P.M., De Voogt, P., 2003. Environmental and toxicity effects of
- perfluoroalkylated substances, in: Reviews of Environmental Contamination and

- Toxicology. Springer, pp. 99–121. https://doi.org/10.1007/0-387-21731-2 4
- Henke, J.M., Bassler, B.L., 2004. Three Parallel Quorum-Sensing Systems Regulate Gene
- Expression in Vibrio harveyi. J. Bacteriol. 186, 6902–6914.
- 1559 https://doi.org/10.1128/JB.186.20.6902
- Herman, A., Aerts, O., de Montjoye, L., Tromme, I., Goossens, A., Baeck, M., 2019.
- 1561 Isothiazolinone derivatives and allergic contact dermatitis: a review and update. J. Eur.
- Acad. Dermatology Venereol. https://doi.org/10.1111/jdv.15267
- Hortipro B.V., 2014. Material safety data sheet MossKade ®.
- Houari, A., Di Martino, P., 2007. Effect of chlorhexidine and benzalkonium chloride on
- bacterial biofilm formation. Lett. Appl. Microbiol. 45, 652–656.
- 1566 https://doi.org/10.1111/j.1472-765X.2007.02249.x
- 1567 Iler, K.R., 1979. The chemistry of silica: solubility, polymerization, colloid and surface
- properties, and biochemistry. John Wiley and Sons Inc.
- 1569 Inoue, M., Segawa, K., Matsunaga, S., Matsumoto, N., Oda, M., Yamase, T., 2005.
- 1570 Antibacterial activity of highly negative charged polyoxotungstates, K27
- 1571 [KAs4W40O140] and K18 [KSb9W21O86], and Keggin-structural polyoxotungstates
- 1572 against Helicobacter pylori. J. Inorg. Biochem. 99, 1023–1031.
- 1573 https://doi.org/10.1016/j.jinorgbio.2005.01.010
- 1574 Isquith, A.J., Abbott, E.A., Walters, P.A., 1972. Surface-bonded antimicrobial activity of an
- organosilicon quaternary ammonium chloride. Appl. Microbiol. 24, 859–863.
- Jeevahan, J., Chandrasekaran, M., Britto Joseph, G., Durairaj, R.B., Mageshwaran, G., 2018.
- Superhydrophobic surfaces: a review on fundamentals, applications, and challenges. J.
- Coatings Technol. Res. 15, 231–250. https://doi.org/10.1007/s11998-017-0011-x
- Jeong, S.H., Lee, H.J., Kim, D.W., Chung, Y.J., 2018. New biocide for eco-friendly biofilm
- removal on outdoor stone monuments. Int. Biodeterior. Biodegrad. 131, 19–28.

- 1581 https://doi.org/10.1016/j.ibiod.2017.03.004
- 1582 Jesus, F.P.K., Ferreiro, L., Bizzi, K.S., Loreto, S., Pilotto, M.B., Ludwig, A., Alves, S.H.,
- Zanette, R.A., Santurio, J.M., 2015. In vitro activity of carvacrol and thymol combined
- with antifungals or antibacterials against Pythium insidiosum. J. Mycol. Med. 25, 89–93.
- 1585 https://doi.org/10.1016/j.mycmed.2014.10.023
- Johansen, J.D., Uter, W., Frosch, P., Lepoittevin, J., 2020. Contact Allergy to Fragrances, in:
- 1587 Contact Dermatitis. pp. 1–33. https://doi.org/10.1007/978-3-319-72451-5\_86-1
- Jonkers, H.M., Thijssen, A., Muyzer, G., Copuroglu, O., Schlangen, E., 2010. Application of
- bacteria as self-healing agent for the development of sustainable concrete. Ecol. Eng. 36,
- 1590 230–235. https://doi.org/10.1016/j.ecoleng.2008.12.036
- Joseph, E., 2021. Microorganisms in the deterioration and preservation of cultural heritage,
- 1592 Microorganisms in the Deterioration and Preservation of Cultural Heritage.
- 1593 https://doi.org/10.1007/978-3-030-69411-1
- Kaegi, R., Ulrich, A., Sinnet, B., Vonbank, R., Wichser, A., Zuleeg, S., Simmler, H., Brunner,
- S., Vonmont, H., Burkhardt, M., Boller, M., 2008. Synthetic TiO2 nanoparticle emission
- from exterior facades into the aquatic environment. Environ. Pollut. 156, 233–239.
- 1597 https://doi.org/10.1016/j.envpol.2008.08.004
- 1598 Kalia, V.C., 2018. Biotechnological applications of quorum sensing inhibitors,
- 1599 Biotechnological Applications of Quorum Sensing Inhibitors.
- 1600 https://doi.org/10.1007/978-981-10-9026-4
- 1601 Karn, S.K., Fang, G., Duan, J., 2017. Bacillus sp. acting as dual role for corrosion induction
- and corrosion inhibition with carbon steel (CS). Front. Microbiol. 8, 1–11.
- 1603 https://doi.org/10.3389/fmicb.2017.02038
- Karsa, D.R., Ashworth, D., 2007. Industrial Biocides: Selection and Application.
- Karthikeyan, R., Kumar, P. V., Koushik, O.S., 2016. Dendrimeric Biocides-a tool for effective

- antimicrobial therapy. J Nanomed Nanotechnol 7, 2. https://doi.org/10.4172/2157-
- 1607 7439.1000359
- 1608 Khoshnevis, M., Carozzo, C., Brown, R., Bardiès, M., Bonnefont-Rebeix, C., Belluco, S.,
- Nennig, C., Marcon, L., Tillement, O., Gehan, H., 2020. Feasibility of intratumoral
- 1610 165Holmium siloxane delivery to induced U87 glioblastoma in a large animal model, the
- 1611 Yucatan minipig. PLoS One 15, e0234772. https://doi.org/10.1371/journal.pone.0234772
- 1612 Kim, M., Weigand, M.R., Oh, S., Hatt, J.K., Krishnan, R., Tezel, U.T., Pavlostathis, S.G.,
- 1613 Konstantinidisa, K.T., 2018. Widely used benzalkonium chloride disinfectants can
- promote antibiotic resistance. Appl. Environ. Microbiol. 84, 1–14.
- 1615 https://doi.org/https://doi.org/10 .1128/AEM.01201-18. Editor
- 1616 Kip, N., Van Veen, J.A., 2015. The dual role of microbes in corrosion. ISME J. 9, 542–551.
- 1617 https://doi.org/10.1038/ismej.2014.169
- 1618 Koziróg, A., Brycki, B., Pielech-Przybylska, K., 2018. Impact of cationic and neutral gemini
- surfactants on conidia and hyphal forms of Aspergillus brasiliensis. Int. J. Mol. Sci. 19,
- 1620 873. https://doi.org/https://doi.org/10.3390/ijms19030873
- 1621 Krakova, L., De Leo, F., Bruno, L., Pangallo, D., Urzì, C., 2015. Complex bacterial diversity
- in the white biofilms of the Catacombs of St. Callixtus in Rome evidenced by different
- investigation strategies: Bacterial diversity in white biofilms. Environ. Microbiol. 17,
- 1624 1738–1752. https://doi.org/10.1111/1462-2920.12626
- Krause, M., Geer, W., Swenson, L., Fallah, P., Robbins, C., 2006. Controlled study of mold
- growth and cleaning procedure on treated and untreated wet gypsum wallboard in an
- indoor environment. J. Occup. Environ. Hyg. 3, 435–441.
- 1628 https://doi.org/10.1080/15459620600798663
- Lami, R., 2019. Quorum sensing in marine biofilms and environments., in: Quorum Sensing.
- pp. 55–96. https://doi.org/10.1016/B978-0-12-814905-8.00003-4

- Laurie, A.P., 1926a. The Painter's Methods and Materials.
- Laurie, A.P., 1926b. Preservation of stone. U.S. Patent Application 732,574, 16 August 1924.
- 1633 U.S. Patent 1,585,103, issued 18 May 1926.
- Laurie, A.P., 1926c. Preservation of stone. U.S. Patent 1,607,762, issued 23 November 1926.
- Laurie, A.P., 1925. Preservation of stone. U.S. Patent 1,561,988, issued 17 November 1925.
- Laurie, A.P., 1923. Improvements relating to the preservation of stone. U.K. Patent 203,042,
- issued 6 September 1923.
- Lavorgna, M., Russo, C., D'Abrosca, B., Parrella, A., Isidori, M., 2016. Toxicity and
- genotoxicity of the quaternary ammonium compound benzalkonium chloride (BAC) using
- Daphnia magna and Ceriodaphnia dubia as model systems. Environ. Pollut. 210, 34–39.
- 1641 https://doi.org/10.1016/j.envpol.2015.11.042
- Leidenfrost, J.G., 1756. De aquae communis nonnullis qualitatibus tractatus, Duisburg.
- Lejars, M., Margaillan, A., Bressy, C., 2012. Fouling release coatings: a nontoxic alternative to
- 1644 biocidal antifouling coatings. Chem. Rev. 112, 4347–4390.
- 1645 https://doi.org/https://doi.org/10.1021/cr200350v
- 1646 Li, L., Li, B., Dong, J., Zhang, J., 2016. Roles of silanes and silicones in forming
- superhydrophobic and superoleophobic materials. J. Mater. Chem. A 4, 13677–13725.
- 1648 https://doi.org/https://doi.org/10.1039/C6TA05441B
- Li, Q., Zhang, B., He, Z., Yang, X., 2016. Distribution and diversity of bacteria and fungi
- 1650 colonization in stone monuments analyzed by high-throughput sequencing. PLoS One 11,
- 1651 1–17. https://doi.org/10.1371/journal.pone.0163287
- Li, Q., Zhang, B., Yang, X., Ge, Q., 2018. Deterioration-Associated Microbiome of Stone
- 1653 Monuments: Structure, Variation, and Assembly. Appl. Environ. Microbiol. 1–19.
- 1654 https://doi.org/10.1128/AEM.02680-17
- Li, Y., Zhang, Z., Wang, M., Men, X., Xue, Q., 2017. Environmentally safe, substrate-

- independent and repairable nanoporous coatings: Large-scale preparation, high
- transparency and antifouling properties. J. Mater. Chem. A 5, 20277–20288.
- 1658 https://doi.org/10.1039/c7ta05112c
- Liu, X., Koestler, R.J., Warscheid, T., Katayama, Y., Gu, J.-D., 2020. Microbial deterioration
- and sustainable conservation of stone monuments and buildings. Nat. Sustain. 1–14.
- https://doi.org/https://doi.org/10.1038/s41893-020-00602-5
- Lo Schiavo, S., De Leo, F., Urzì, C., 2020. Present and future perspectives for biocides and
- antifouling products for stone-built cultural heritage: Ionic liquids as a challenging
- alternative. Appl. Sci. 10, 6568.
- Loh, K., Gaylarde, C.C., Shirakawa, M.A., 2018. Photocatalytic activity of ZnO and TiO2
- 1666 'nanoparticles' for use in cement mixes. Constr. Build. Mater. 167, 853–859.
- 1667 https://doi.org/10.1016/j.conbuildmat.2018.02.103
- Machado, A., Redol, P., Branco, L., Vilarigues, M., 2011. Ionic liquids for medieval stained
- glass cleaning: a new frontier, in: Proceedings of the ICOM-CC Lisbon. Portugal: 16th
- 1670 Triennal Conference, Lisbon, Portugal. pp. 19–23.
- Manefield, M., de Nys, R., Naresh, K., Roger, R., Givskov, M., Peter, S., Kjelleberg, S., 1999.
- 1672 Evidence that halogenated furanones from Delisea pulchra inhibit acylated homoserine
- lactone (AHL)-mediated gene expression by displacing the AHL signal from its receptor
- protein. Microbiology 145, 283–291. https://doi.org/10.1099/13500872-145-2-283
- 1675 Mansour, M.M., 2013. Proactive investigation using bioagents and fungicide for preservation
- of Egyptian stone sarcophagus. J. Appl. Sci. Res. 9, 1917–1930.
- Marchese, A., Orhan, I.E., Daglia, M., Barbieri, R., Di Lorenzo, A., Nabavi, S.F., Gortzi, O.,
- 1678 Izadi, M., Nabavi, S.M., 2016. Antibacterial and antifungal activities of thymol: A brief
- review of the literature. Food Chem. https://doi.org/10.1016/j.foodchem.2016.04.111
- Marin, E., Vaccaro, C., Leis, M., 2016. Biotechnology applied to historic stoneworks

- 1681 conservation: testing the potential harmfulness of two biological biocides. Int. J. Conserv.
- 1682 Sci. 7, 185–196.
- Martini, R., Serrano, L., Barbosa, S., Labidi, J., 2014. Antifungal cellulose by capsaicin
- grafting. Cellulose 21, 1909–1919. https://doi.org/10.1007/s10570-014-0219-1
- 1685 Mascalchi, M., Orsini, C., Pinna, D., Salvadori, B., Siano, S., Riminesi, C., 2020. Assessment
- of different methods for the removal of biofilms and lichens on gravestones of the English
- 1687 Cemetery in Florence. Int. Biodeterior. Biodegradation 154, 105041.
- 1688 https://doi.org/https://doi.org/10.1016/j.ibiod.2020.105041
- Merchel Piovesan Pereira, B., Tagkopoulos, I., 2019. Benzalkonium chlorides: Uses, regulatory
- status, and microbial resistance. Appl. Environ. Microbiol. 85, 1–13.
- 1691 https://doi.org/10.1128/AEM.00377-19
- 1692 Miras, H.N., Yan, J., Long, D.-L., Cronin, L., 2012. Engineering polyoxometalates with
- 1693 emergent properties. Chem. Soc. Rev. 41, 7403–7430.
- 1694 https://doi.org/https://doi.org/10.1039/C2CS35190K
- 1695 Misra, A., Franco Castillo, I., Müller, D.P., González, C., Eyssautier-Chuine, S., Ziegler, A.,
- de la Fuente, J.M., Mitchell, S.G., Streb, C., 2018. Polyoxometalate-Ionic Liquids (POM-
- ILs) as Anticorrosion and Antibacterial Coatings for Natural Stones. Angew. Chemie Int.
- 1698 Ed. 57, 14926–14931. https://doi.org/10.1002/anie.201809893
- Mokhtar, M., Ginestra, G., Youcefi, F., Filocamo, A., Bisignano, C., Riazi, A., 2017.
- 1700 Antimicrobial activity of selected polyphenols and capsaicinoids identified in pepper
- 1701 (Capsicum annuum L.) and their possible mode of interaction. Curr. Microbiol. 74, 1253–
- 1702 1260. https://doi.org/10.1007/s00284-017-1310-2
- Moreau, C., Vergès-Belmin, V., Leroux, L., Orial, G., Fronteau, G., Barbin, V., 2008. Water-
- repellent and biocide treatments: Assessment of the potential combinations. J. Cult. Herit.
- 9, 394–400. https://doi.org/https://doi.org/10.1016/j.culher.2008.02.002

- Mulder, I., Siemens, J., Sentek, V., Amelung, W., Smalla, K., Jechalke, S., 2017. Quaternary
- ammonium compounds in soil: implications for antibiotic resistance development. Rev.
- 1708 Environ. Sci. Biotechnol. 17, 1–27. https://doi.org/10.1007/s11157-017-9457-7
- Nath, R.K., Zain, M.F.M., Jamil, M., 2016. An environment-friendly solution for indoor air
- purification by using renewable photocatalysts in concrete: A review. Renew. Sustain.
- 1711 Energy Rev. 62, 1184–1194. https://doi.org/10.1016/j.rser.2016.05.018
- Nazzaro, F., Fratianni, F., De Martino, L., Coppola, R., De Feo, V., 2013. Effect of essential
- oils on pathogenic bacteria. Pharmaceuticals 6, 1451–1474.
- 1714 https://doi.org/10.3390/ph6121451
- 1715 Niu, C.N., Han, J.Y., Hu, S.P., Chao, D.Y., Song, X.G., Howlader, M.M.R., Cao, J., 2020. Fast
- and Environmentally Friendly Fabrication of Superhydrophilic-Superhydrophobic
- 1717 Patterned Aluminum Surfaces. Surfaces and Interfaces 22, 100830.
- 1718 https://doi.org/https://doi.org/10.1016/j.surfin.2020.100830
- Noll, W., 1954. Zur Chemie und Technologie der Silicone. Angew. Chemie Int. Ed. 66, 41–
- 1720 64.
- Norma Italiana UNI 11182, 2006. Cultural heritage Natural and artificial stone Description of
- the alteration Terminology and definition.
- Nowicka-Krawczyk, P., Żelazna-Wieczorek, J., Koziróg, A., Otlewska, A., Rajkowska, K.,
- Piotrowska, M., Gutarowska, B., Brycki, B., 2019. Multistep approach to control
- microbial fouling of historic building materials by aerial phototrophs. Biofouling 35, 284–
- 1726 298. https://doi.org/https://doi.org/10.1080/08927014.2019.1598396
- Nunez, O., Moyano, E., Galceran, M.T., 2004. Determination of quaternary ammonium
- biocides by liquid chromatography-mass spectrometry. J. Chromatogr. A 1058, 89–95.
- 1729 https://doi.org/10.1016/j.chroma.2004.08.085
- Oliveira Junior, N., Padulla, V., Ferraço, V., Ferronato, G., 2020. Use of Capsaicin for nonlethal

- technology, in: IntechOpen. https://doi.org/10.1016/j.colsurfa.2011.12.014
- Omolo, M.A., Wong, Z., Mergen, A.K., Hastings, J.C., Le, N.C., Reiland, H.A., Case, K.A.,
- Baumler, D.J., 2014. Antimicrobial Properties of Chili Peppers. Infect. Dis. Ther. 2, 8.
- 1734 https://doi.org/10.4172/2332-0877.1000145
- Owen, L., Laird, K., 2018. Synchronous application of antibiotics and essential oils: dual
- mechanisms of action as a potential solution to antibiotic resistance. Crit. Rev. Microbiol.
- 1737 44, 414–435. https://doi.org/10.1080/1040841X.2018.1423616
- Pacheco, M.F., Pereira, A.I., Branco, L.C., Parola, A.J., 2013. Varnish removal from paintings
- using ionic liquids. J. Mater. Chem. A 1, 7016–7018.
- 1740 https://doi.org/https://doi.org/10.1039/C3TA10679A
- Paijens, C., Bressy, A., Frère, B., Moilleron, R., 2020. Biocide emissions from building
- materials during wet weather: identification of substances, mechanism of release and
- transfer to the aquatic environment. Environ. Sci. Pollut. Res. 27, 3768–3791.
- 1744 https://doi.org/10.1007/s11356-019-06608-7
- Palla, F., Bruno, M., Mercurio, F., Tantillo, A., Rotolo, V., 2020. Essential oils as natural
- biocides in conservation of cultural heritage. Molecules 25, 1–11.
- 1747 https://doi.org/10.3390/molecules25030730
- Paul, D., Gopal, J., Kumar, M., Manikandan, M., 2018. Nature to the natural rescue: Silencing
- 1749 microbial chats. Chem. Biol. Interact. 280, 86–98.
- 1750 https://doi.org/10.1016/j.cbi.2017.12.018
- Pelclova, D., Barosova, H., Kukutschova, J., Zdimal, V., Navratil, T., Fenclova, Z., Vlckova,
- 1752 S., Schwarz, J., Zikova, N., Kacer, P., Komarc, M., Belacek, J., Zakharov, S., 2015. Raman
- microspectroscopy of exhaled breath condensate and urine in workers exposed to fine and
- nano TiO2 particles: A cross-sectional study. J. Breath Res. 9, 36008.
- 1755 https://doi.org/10.1088/1752-7155/9/3/036008

- Pelclova, D., Zdimal, V., Komarc, M., Vlckova, S., Fenclova, Z., Ondracek, J., Schwarz, J.,
- 1757 Kostejn, M., Kacer, P., Dvorackova, S., Popov, A., Klusackova, P., Zakharov, S., Bello,
- D., 2018. Deep airway inflammation and respiratory disorders in nanocomposite workers.
- Nanomaterials 8, 1–13. https://doi.org/10.3390/nano8090731
- 1760 Pena-Poza, J., Ascaso, C., Sanz, M., Pérez-Ortega, S., Oujja, M., Wierzchos, J., Souza-Egipsy,
- 1761 V., Cañamares, M. V., Urizal, M., Castillejo, M., García-Heras, M., 2018. Effect of
- biological colonization on ceramic roofing tiles by lichens and a combined laser and
- biocide procedure for its removal. Int. Biodeterior. Biodegrad. 126, 86–94.
- 1764 https://doi.org/10.1016/j.ibiod.2017.10.003
- Pendleton, J.N., Gilmore, B.F., 2015. The antimicrobial potential of ionic liquids: A source of
- 1766 chemical diversity for infection and biofilm control. Int. J. Antimicrob. Agents 46, 131–
- 1767 139. https://doi.org/10.1016/j.ijantimicag.2015.02.016
- 1768 Perito, B., Marvasi, M., Barabesi, C., Mastromei, G., Bracci, S., Vendrell, M., Tiano, P., 2014.
- A Bacillus subtilis cell fraction (BCF) inducing calcium carbonate precipitation:
- Biotechnological perspectives for monumental stone reinforcement. J. Cult. Herit. 15,
- 1771 345–351. https://doi.org/10.1016/j.culher.2013.10.001
- 1772 Petrovska, B.B., 2012. Historical review of medicinal plants' usage. Pharmacogn. Rev. 6, 1–5.
- 1773 https://doi.org/10.4103/0973-7847.95849
- 1774 Pinna, D., Salvadori, B., Galeotti, M., 2012. Monitoring the performance of innovative and
- traditional biocides mixed with consolidants and water-repellents for the prevention of
- biological growth on stone. Sci. Total Environ. 423, 132–141.
- 1777 https://doi.org/10.1016/j.scitotenv.2012.02.012
- 1778 Plinius Secundus, G., 77AD. Naturalis Historia.
- 1779 Pozo-Antonio, J.S., Alonso-Villar, E.M., Rivas, T., 2021. Efficacy of mechanical procedures
- for removal of a lichen and a gypsum black crust from granite. J. Build. Eng. 102986.

- 1781 https://doi.org/https://doi.org/10.1016/j.jobe.2021.102986
- Pozo-Antonio, J.S., Barreiro, P., González, P., Paz-Bermúdez, G., 2019. Nd: YAG and Er:
- 1783 YAG laser cleaning to remove Circinaria hoffmanniana (Lichenes, Ascomycota) from
- schist located in the Côa Valley Archaeological Park. Int. Biodeterior. Biodegradation 144,
- 1785 104748. https://doi.org/https://doi.org/10.1016/j.ibiod.2019.104748
- 1786 Pozo-Antonio, J.S., Montojo, C., Lopez de Silanes, M.E., de Rosario, I., Rivas, T., 2017. In situ
- evaluation by colour spectrophotometry of cleaning and protective treatments in granitic
- 1788 Cultural Heritage. Int. Biodeterior. Biodegrad. 123, 251–261.
- 1789 https://doi.org/10.1016/j.ibiod.2017.07.004
- 1790 Pozo-Antonio, J.S., Rivas, T., Lopez, A.J., Fiorucci, M.P., Ramil, A., 2016. Effectiveness of
- granite cleaning procedures in cultural heritage: A review. Sci. Total Environ. 571, 1017–
- 1792 1028. https://doi.org/10.1016/j.scitotenv.2016.07.090
- 1793 Price, P.B., 1950. Benzalkonium chloride (zephiran chloride) as a skin disinfectant. Arch. Surg.
- 1794 61, 23–33. https://doi.org/10.1001/archsurg.1950.01250020026004
- 1795 Quagliarini, E., Graziani, L., Diso, D., Licciulli, A., D'Orazio, M., 2018. Is nano-TiO2 alone
- an effective strategy for the maintenance of stones in Cultural Heritage? J. Cult. Herit. 30,
- 1797 81–91. https://doi.org/https://doi.org/10.1016/j.culher.2017.09.016
- 1798 Quéré, D., Reyssat, M., 2008. Non-adhesive lotus and other hydrophobic materials. Philos.
- 1799 Trans. R. Soc. A Math. Phys. Eng. Sci. 366, 1539–1556.
- 1800 https://doi.org/10.1098/rsta.2007.2171
- Rajkowska, K., Koziróg, A., Otlewska, A., Piotrowska, M., Atrián-Blasco, E., Franco-Castillo,
- I., Mitchell, S.G., 2020. Antifungal activity of polyoxometalate-ionic liquids on historical
- brick. Molecules 25, 5663. https://doi.org/https://doi.org/10.3390/molecules25235663
- Ranogajec, J., Radeka, M., 2013. Self-cleaning surface of clay roofing tiles, in: Self-Cleaning
- Materials and Surfaces. pp. 89–128. https://doi.org/10.1002/9781118652336.ch4

- 1806 Rémy, B., Mion, S., Plener, L., Elias, M., Chabrière, E., Daudé, D., 2018. Interference in
- bacterial quorum sensing: a biopharmaceutical perspective. Front. Pharmacol. 9.
- 1808 https://doi.org/https://doi.org/10.3389/fphar.2018.00203
- 1809 Remzova, M., Zouzelka, R., Brzicova, T., Vrbova, K., Pinkas, D., Rőssner, P., Topinka, J.,
- 1810 Rathousky, J., 2019. Toxicity of TiO2, ZnO, and SiO2 nanoparticles in human lung cells:
- 1811 Safe-by-design development of construction materials. Nanomaterials 9.
- 1812 https://doi.org/10.3390/nano9070968
- Ripert, C., Leleu, C., Boulitrop, C., Bel, B., Jeudy, G., Dalac-Rat, S., Vabres, P., Collet, E.,
- 1814 2012. Allergie de contact aux isothiazolinones : il n'y a pas que les cosmétiques ! Ann.
- Dermatol. Venereol. 139, B123. https://doi.org/10.1016/j.annder.2012.10.162
- 1816 Romani, M., Adouane, E., Carrion, C., Veckerle, C., Lefevre, M., Intertaglia, L., Rodrigues,
- 1817 A.M.S., Lebaron, P., Lami, R., 2021a. Diversity and activities of pioneer bacteria, algae,
- and fungi colonizing ceramic roof tiles during the first year of outdoor exposure. Int.
- Biodeterior. Biodegradation 162, 105230. https://doi.org/10.1016/j.ibiod.2021.105230
- Romani, M., Carrion, C., Fernandez, F., Intertaglia, L., Pecqueur, D., Lebaron, P., Lami, R.,
- 1821 2019. High bacterial diversity in pioneer biofilms colonizing ceramic roof tiles. Int.
- Biodeterior. Biodegrad. 144, 104745. https://doi.org/10.1016/j.ibiod.2019.104745
- Romani, M., Carrion, C., Fernandez, F., Lebaron, P., Lami, R., 2021b. Methyl potassium
- siliconate and siloxane inhibit the formation of multispecies biofilms on ceramic roof tiles:
- 1825 Efficiency and comparison of two common water repellents. Microorganisms 9, 1–12.
- https://doi.org/10.3390/microorganisms9020394
- 1827 Roos, M., König, F., Stadtmüller, S., Weyershausen, B., 2008. Evolution of silicone based
- water repellents for modern building protection, in: 5th International Conference on Water
- 1829 Repellent Treatment of Building Materials. pp. 3–16.
- 1830 Rosado, T., Silva, M., Dias, L., Candeias, A., Gil, M., Mirão, J., Pestana, J., Caldeira, A.T.,

- 1831 2017. Microorganisms and the integrated conservation-intervention process of the
- renaissance mural paintings from Casas Pintadas in Évora Know to act, act to preserve.
- J. King Saud Univ. Sci. 29, 478–486. https://doi.org/10.1016/j.jksus.2017.09.001
- 1834 Rossi-Manaresi, R., 1996. Stone protection from antiquity to the beginning of the Industrial
- 1835 Revolution TT Twenty years of stone conservation 1976-96: results and perspectives.
- Zum Thema zwanzig Jahre Steinkonservierung 1976-1996 Bilanz und Perspekt. 23–30.
- 1837 Rossnerova, A., Honkova, K., Pelclova, D., Zdimal, V., Hubacek, J.A., Chvojkova, I., Vrbova,
- 1838 K., Rossner, P., Topinka, J., Vlckova, S., Fenclova, Z., Lischkova, L., Klusackova, P.,
- Schwarz, J., Ondracek, J., Ondrackova, L., Kostejn, M., Klema, J., Dvorackova, S., 2020.
- DNA methylation profiles in a group of workers occupationally exposed to nanoparticles.
- 1841 Int. J. Mol. Sci. 21. https://doi.org/10.3390/ijms21072420
- Rotolo, V., Barresi, G., Di Carlo, E., Giordano, A., Lombardo, G., Crimi, E., Costa, E., Bruno,
- 1843 M., Palla, F., 2016. Plant extracts as green potential strategies to control the
- biodeterioration of cultural heritage. Int. J. Conserv. Sci.
- 1845 Roy, K., 2020. Ecotoxicological QSARs, Springer Protocols. ed.
- 1846 https://doi.org/https://doi.org/10.1007/978-1-0716-0150-1
- Ruffolo, S.A., De Leo, F., Ricca, M., Arcudi, A., Silvestri, C., Bruno, L., Urzì, C., La Russa,
- 1848 M.F., 2017. Medium-term in situ experiment by using organic biocides and titanium
- dioxide for the mitigation of microbial colonization on stone surfaces. Int. Biodeterior.
- Biodegrad. 123. https://doi.org/10.1016/j.ibiod.2017.05.016
- Saiz-Jimenez, C., 2001. Biodeterioration: An overview of the state-of-the-art and assessment
- of future directions. Biodegrad. Cult. Herit. 10–16, 520.
- Sanchez, C., 2012. Matériaux inorganiques hybrides et bio-inspiré, in: La Chimie et La Nature.
- 1854 pp. 117–138.
- Sanchez, C., Rozes, L., Ribot, F., Laberty-Robert, C., Grosso, D., Sassoye, C., Boissiere, C.,

- Nicole, L., 2010. "Chimie douce": a land of opportunities for the designed construction of
- functional inorganic and hybrid organic-inorganic nanomaterials. Comptes Rendus Chim.
- 1858 13, 3–39. https://doi.org/https://doi.org/10.1016/j.crci.2009.06.001
- Sanmartín, P., Carballeira, R., 2021. Changes in heterotrophic microbial communities induced
- by biocidal treatments in the Monastery of San Martiño Pinario (Santiago de Compostela,
- 1861 NW Spain). Int. Biodeterior. Biodegrad. 156, 105130.
- 1862 https://doi.org/10.1016/j.ibiod.2020.105130
- Sanmartín, P., DeAraujo, A., Vasanthakumar, A., 2018. Melding the old with the new: Trends
- in methods used to identify, monitor, and control microorganisms on cultural heritage
- materials. Microb. Ecol. 76, 64–80. https://doi.org/10.1007/s00248-016-0770-4
- Sanmartín, P., Rodríguez, A., Aguiar, U., 2020. Medium-term field evaluation of several widely
- used cleaning-restoration techniques applied to algal biofilm formed on a granite-built
- historical monument. Int. Biodeterior. Biodegradation 147, 104870.
- https://doi.org/https://doi.org/10.1016/j.ibiod.2019.104870
- 1870 Sasse, H.R., Snethlage, R., 1997. Methods for the Evaluation of Stone Conservation
- 1871 Treatments, in: Baer, N.S., Snethlage, R. (Ed.), The Conservation of Historic Stone
- 1872 Structures. pp. 223–243.
- 1873 Sasso, S., Miller, A.Z., Rogerio-Candelera, M.A., Cubero, B., Coutinho, M.L., Scrano, L.,
- Bufo, S.A., 2016. Potential of natural biocides for biocontrolling phototrophic
- 1875 colonization on limestone. Int. Biodeterior. Biodegrad. 107, 102–110.
- 1876 https://doi.org/10.1016/j.ibiod.2015.11.017
- 1877 Sauder, M., 1999. Damage Caused by Water Repellent Agents Reasons and Counter-
- 1878 Measures. Int. J. Restor. Build. Monum. 5, 311–322.
- Scardino, A.J., de Nys, R., 2011. Mini review: biomimetic models and bioinspired surfaces for
- fouling control. Biofouling 27, 73–86. https://doi.org/10.1080/08927014.2010.536837

- Scheerer, S., Ortega-Morales, O., Gaylarde, C., 2009. Chapter 5 Microbial Deterioration of
- 1882 Stone Monuments-An Updated Overview, in: Advances in Applied Microbiology.
- 1883 Elesvier Inc., pp. 97–139. https://doi.org/10.1016/S0065-2164(08)00805-8
- 1884 Schwensen, J.F., Johansen, J.D., 2018. Isothiazolinones, The Lancet.
- 1885 https://doi.org/10.1016/S0140-6736(89)90104-9
- 1886 Silva, V., Silva, C., Soares, P., Garrido, E.M., Borges, F., Garrido, J., 2020. Isothiazolinone
- biocides: Chemistry, biological, and toxicity profiles. Molecules 25.
- 1888 https://doi.org/10.3390/molecules25040991
- 1889 Slaton, D., Normandin, K.C., 2005. Masonry cleaning technologies: Overview of current
- practice and techniques. J. Archit. Conserv. 11, 7–31.
- 1891 https://doi.org/10.1080/13556207.2005.10784950
- 1892 Slipski, C.J., Zhanel, G.G., Bay, D.C., 2017. Biocide selective TolC-independent efflux pumps
- in enterobacteriaceae. J. Membr. Biol. 251, 1–19. https://doi.org/10.1007/s00232-017-
- 1894 9992-8
- 1895 Snethlage, R., Wendler, E., 1996. Methoden der Steinkonservierung Anforde- rungen und
- Bewertungskriterien. Natursteinkonservierung der Denkmal 3–21.
- Soroldoni, S., Abreu, F., Castro, Í.B., Duarte, F.A., Pinho, G.L.L., 2017. Are antifouling paint
- particles a continuous source of toxic chemicals to the marine environment? J. Hazard.
- Mater. 330, 76–82. https://doi.org/10.1016/j.jhazmat.2017.02.001
- 1900 Speranza, M., Sanz, M., Oujja, M., De los Rios, A., Wierzchos, J., Pérez-Ortega, S., Castillejo,
- 1901 M., Ascaso, C., 2013. Nd-YAG laser irradiation damages to Verrucaria nigrescens. Int.
- 1902 Biodeterior. Biodegradation 84, 281–290.
- 1903 https://doi.org/https://doi.org/10.1016/j.ibiod.2012.02.010
- 1904 Stien, D., Clergeaud, F., Rodrigues, A.M.S., Lebaron, K., Pillot, R., Romans, P., Fagervold, S.,
- Lebaron, P., 2019. Metabolomics reveal that octocrylene accumulates in Pocillopora

- damicornis tissues as fatty acid conjugates and triggers coral cell mitochondrial
- dysfunction. Anal. Chem. 91, 990–995. https://doi.org/10.1021/acs.analchem.8b04187
- 1908 Stien, D., Suzuki, M., Rodrigues, A.M.S., Yvin, M., Clergeaud, F., Thorel, E., Lebaron, P.,
- 1909 2020. A unique approach to monitor stress in coral exposed to emerging pollutants. Sci.
- 1910 Rep. 10, 9601. https://doi.org/10.1038/s41598-020-66117-3
- 1911 Sto, 2020. Quand Sto s'inspire de la nature pour créer des peintures de facade aux fonctions
- 1912 innovantes! [WWW Document]. URL
- https://www.sto.fr/media/documents/CP\_Peintures\_bioniques\_Mars\_2020.pdf
- 1914 Subramaniam, V.D., Prasad, S.V., Banerjee, A., Gopinath, M., Murugesan, R., Marotta, F.,
- 1915 Sun, X.-F., Pathak, S., 2019. Health hazards of nanoparticles: understanding the toxicity
- mechanism of nanosized ZnO in cosmetic products. Drug Chem. Toxicol. 42, 84–93.
- 1917 https://doi.org/10.1080/01480545.2018.1491987
- 1918 Szabó, M.Á., Varga, G.Z., Hohmann, J., Schelz, Z., Szegedi, E., Amaral, L., Molnár, J., 2010.
- 1919 Inhibition of quorum-sensing signals by essential oils. Phyther. Res. 24, 782–786.
- 1920 https://doi.org/10.1002/ptr.3010
- 1921 Sznajder-Katarzyńska, K., Surma, M., Cieślik, I., 2019. A review of perfluoroalkyl acids
- 1922 (PFAAs) in terms of sources, applications, human exposure, dietary intake, toxicity, legal
- regulation, and methods of determination. J. Chem. 2019.
- 1924 https://doi.org/https://doi.org/10.1155/2019/2717528
- 1925 Tezel, U., Pavlostathis, S.G., 2015. Quaternary ammonium disinfectants: Microbial
- adaptation, Degradation and ecology. Curr. Opin. Biotechnol. 33, 296–304.
- 1927 https://doi.org/10.1016/j.copbio.2015.03.018
- 1928 Tezel, U., Pavlostathis, S.G., 2011. Role of Quaternary Ammonium Compounds on
- Antimicrobial Resistance in the Environment. Antimicrob. Resist. Environ. 349–388.
- 1930 https://doi.org/10.1002/9781118156247.ch20

- 1931 The Brick Industry Association, 2018. Cleaning Brickwork.
- 1932 Thomsen, A. V, Schwensen, J.F., Bossi, R., Banerjee, P., Giménez-Arnau, E., Lepoittevin, J.P.,
- Lidén, C., Uter, W., White, I.R., Johansen, J.D., 2018. Isothiazolinones are still widely
- used in paints purchased in five European countries: a follow-up study. Contact Dermatitis
- 1935 78, 246–253. https://doi.org/10.1111/cod.12937
- 1936 Tiano, P., 2016. Biodeterioration of stone monuments a worldwide issue. Open Conf. Proc. J.
- 1937 29–38. https://doi.org/10.2174/22102892016070
- 1938 Tirado Hernández, A.M., Puerto, S.M., Velázquez, M., 2015. Estimación de la biomasa
- fotosintética en el estudio de la eficiencia de tratamientos biocidas sobre sustratos pétreos.,
- in: Moreno Oliva, M., Rogerio-Candelera, M.A., López Navarrete, J.T., Hernández Jolín,
- 1941 V. (Eds.), Estudio y Conservación Del Patrimonio Cultural. Universidad de Málaga y Red
- de Ciencia y Tecnología para la Conservación del Patrimonio Cultura, Malaga, pp. 184–
- 1943 187.
- 1944 Tobaldi, D.M., Graziani, L., Seabra, M.P., Hennetier, L., Ferreira, P., Quagliarini, E.,
- Labrincha, J.A., 2017. Functionalised exposed building materials: Self-cleaning,
- 1946 photocatalytic and biofouling abilities. Ceram. Int. 43, 10316–10325.
- 1947 https://doi.org/10.1016/j.ceramint.2017.05.061
- Toreno, G., Isola, D., Meloni, P., Carcangiu, G., Selbmann, L., Onofri, S., Caneva, G., Zucconi,
- L., 2018. Biological colonization on stone monuments: A new low impact cleaning
- method. J. Cult. Herit. 30, 100–109. https://doi.org/10.1016/j.culher.2017.09.004
- Tourneroche, A., Lami, R., Hubas, C., Blanchet, E., Vallet, M., Escoubeyrou, K., Prado, S.,
- 1952 2019. Bacterial–Fungal Interactions in the Kelp Endomicrobiota Drive Autoinducer-2
- Ouorum Sensing. Front. Microbiol. 10. https://doi.org/doi:10.3389/fmicb.2019.01693
- 1954 Tyagi, P., Tyagi, R., 2009. Synthesis, structural properties and applications of gemini
- 1955 surfactants: a review. Tenside Surfactants Deterg. 46, 373–382.

- 1956 https://doi.org/https://doi.org/10.3139/113.110045
- 1957 U.S. Environmental Protection Agency (EPA), 2006. EPA739-R-06-009 Reregistration
- 1958 Eligibility Decision for Alkyl Dimethyl Benzyl Ammonium Chloride (ADBAC),
- 1959 Prevention, Pesticides and Toxic Substances (7510C). Washington.
- 1960 Urzì, C., De Leo, F., 2007. Evaluation of the efficiency of water-repellent and biocide
- 1961 compounds against microbial colonization of mortars. Int. Biodeterior. Biodegrad. 60, 25–
- 1962 34. https://doi.org/10.1016/j.ibiod.2006.11.003
- 1963 Urzì, C., De Leo, F., Bruno, L., Albertano, P., 2010. Microbial Diversity in Paleolithic Caves:
- 1964 A Study Case on the Phototrophic Biofilms of the Cave of Bats (Zuheros, Spain). Environ.
- 1965 Microbiol. 60, 116–129. https://doi.org/10.1007/s00248-010-9710-x
- 1966 Vallet, M., Chong, Y.M., Tourneroche, A., Genta-Jouve, G., Hubas, C., Lami, R., Prado, S.,
- 1967 2020. Novel alpha-hydroxy gamma-butenolides of kelp endophytes disrupt bacterial cell-
- 1968 to-cell signaling. Front. Mar. Sci. 7.
- https://doi.org/10.3389/fmars.2020.0060110.3389/fmars.2020.00601.s001
- 1970 Varga, Z., Nicol, E., Bouchonnet, S., 2020. Photodegradation of benzisothiazolinone:
- 1971 Identification and biological activity of degradation products. Chemosphere 240.
- 1972 https://doi.org/10.1016/j.chemosphere.2019.124862
- 1973 Veneranda, M., Blanco-Zubiaguirre, L., Roselli, G., Di Girolami, G., Castro, K., Madariaga,
- J.M., 2018. Evaluating the exploitability of several essential oils constituents as a novel
- biological treatment against cultural heritage biocolonization. Microchem. J. 138, 1–6.
- 1976 https://doi.org/10.1016/j.microc.2017.12.019
- 1977 Vermeirssen, E.L.M., Campiche, S., Dietschweiler, C., Werner, I., Burkhardt, M., 2018.
- 1978 Ecotoxicological Assessment of Immersion Samples from Facade Render Containing Free
- or Encapsulated Biocides. Environ. Toxicol. Chem. 37, 2246–2256.
- 1980 https://doi.org/10.1002/etc.4176

- 1981 Viollet-le-Duc, E.E., 1854. Dictionnaire raisonné de l'architecture française du XIe au XVIe
- siècle, A. Morel. ed.
- 1983 Vitruvius Pollio, M., 27BC. De Architectura.
- 1984 Wang, G., Li, A., Zhao, W., Xu, Z., Ma, Y., Zhang, F., Zhang, Y., Zhou, J., He, Q., 2020. A
- 1985 Review on Fabrication Methods and Research Progress of Superhydrophobic Silicone
- 1986 Rubber Materials. Adv. Mater. Interfaces 2001460.
- 1987 https://doi.org/10.1002/admi.202001460
- Wang, H., Zhang, L., Chen, Z., Hu, J., Li, S., Wang, Z., Liu, J., Wang, X., 2014. Semiconductor
- heterojunction photocatalysts: Design, construction, and photocatalytic performances.
- 1990 Chem. Soc. Rev. https://doi.org/10.1039/c4cs00126e
- 1991 Warscheid, T., Braams, J., 2000. Biodeterioration of stone: a review. Int. Biodeterior.
- 1992 Biodegrad. 46, 343–368.
- 1993 Warscheid, T., Leisen, H., 2011. Microbiological studies on stone deterioration and
- development of conservation measures at Angkor Wat. Biocolonization Stone Control.
- 1995 Prev. Methods 1–18.
- 1996 Weber, D.J., Rutala, W.A., Sickbert-Bennett, E.E., 2007. Outbreaks associated with
- 1997 contaminated antiseptics and disinfectants. Antimicrob. Agents Chemother. 51, 4217–
- 1998 4224. https://doi.org/10.1128/AAC.00138-07
- 1999 Wendler, E., 1997. New Materials and Approaches for the Conservation of Stone, in: Baer,
- N.S., Snethlage, R. (Eds.), The Conservation of Historic Stone Structures. Chichester, pp.
- 2001 181–196.
- Wheeler, G., 2005. Alkoxysilanes and the Consolidation of Stone, Journal of the American
- 2003 Institute for Conservation. https://doi.org/10.1007/s13398-014-0173-7.2
- Whiteley, M., Diggle, S.P., Greenberg, E.P., 2017. Progress in and promise of bacterial quorum
- sensing research. Nature 551, 313–320. https://doi.org/10.1038/nature24624

- Wieck, S., Olsson, O., Kümmerer, K., 2018. Not only biocidal products: Washing and cleaning
- agents and personal care products can act as further sources of biocidal active substances
- in wastewater. Environ. Int. 115, 247–256. https://doi.org/10.1016/j.envint.2018.03.040
- Wieck, S., Olsson, O., Kümmerer, K., 2016. Possible underestimations of risks for the
- 2010 environment due to unregulated emissions of biocides from households to wastewater.
- 2011 Environ. Int. 94, 695–705. https://doi.org/10.1016/j.envint.2016.07.007
- 2012 Williams, T.M., 2007. The Mechanism of Action of Isothiazolone Biocides.
- 2013 PowerPlantChemistry 9, 3–11.
- Winnicki, K., Łudzik, K., Żabka, A., Polit, J.T., Zawisza, A., Maszewski, J., 2021. Anti-algal
- 2015 activity of the 12-5-12 gemini surfactant results from its impact on the photosynthetic
- 2016 apparatus. Sci. Rep. 11, 1–12. https://doi.org/https://doi.org/10.1038/s41598-021-82165-
- 2017 9
- Wolfs, M., Darmanin, T., Guittard, F., 2013. Superhydrophobic fibrous polymers. Polym. Rev.
- 2019 53, 460–505. https://doi.org/10.1080/15583724.2013.808666
- 2020 Xavier, J.B., Foster, K.R., 2007. Cooperation and conflict in microbial biofilms. Proc. Natl.
- 2021 Acad. Sci. U. S. A. 104, 876–881. https://doi.org/10.1073/pnas.0607651104
- 2022 Xia, Y., Whitesides, G.M., 1998. Soft lithography. Annu. Rev. Mater. Sci. 28, 153–184.
- 2023 Xiang, T., Lv, Z., Wei, F., Liu, J., Dong, W., Li, C., Zhao, Y., Chen, D., 2019.
- Superhydrophobic civil engineering materials: A review from recent developments.
- 2025 Coatings. https://doi.org/10.3390/coatings9110753
- Zainul Abid, C.K. V, Jackeray, R., Jain, S., Chattopadhyay, S., Asif, S., Singh, H., 2016.
- 2027 Antimicrobial efficacy of synthesized quaternary ammonium polyamidoamine dendrimers
- and dendritic polymer network. J. Nanosci. Nanotechnol. 16, 998–1007.
- 2029 https://doi.org/10.1166/jnn.2016.10656
- 2030 Zhang, C., Cui, F., Zeng, G.M., Jiang, M., Yang, Z.Z., Yu, Z.G., Zhu, M.Y., Shen, L.Q., 2015.

2031	Quaternary ammonium compounds (QACs): A review on occurrence, fate and toxicity in						
2032	the	environment.	Sci.	Total	Environ.	518,	352–362.
2033	https://doi.org/10.1016/j.scitotenv.2015.03.007						
2034	Zhang, X., Brodus, D.S., Hollimon, V., Hu, H., 2017. A brief review of recent developments in						
2035	the designs that prevent bio-fouling on silicon and silicon-based materials. Chem. Cent. J.						
2036	11, 1. https://doi.org/10.1186/s13065-017-0246-8						
2037	Zion Market Research, 2016. Antiseptics and disinfectants market by type (alcohol and						
2038	aldehyde, phenols and derivatives, biguanides and amides, quaternary ammonium						
2039	compounds, iodine compounds and others) for domestics, institutional and other end-						
2040	users-global industry perspective, c.						
2041	Zulfiqar, U., Awais, M., Hussain, S.Z., Hussain, I., Husain, S.W., Subhani, T., 2017. Durable						
2042	and sel	f-healing superhydr	ophobic su	irfaces for bu	uilding material	s. Mater. L	ett. 192, 56–
2043	59. http	os://doi.org/10.1016	/j.matlet.20	017.01.070			
2044							

Figures Figures

Figure 1: Biofilm formation pattern. (a) Bacterial adhesion, (b) pioneering biofilm formation embedded in the extracellular matrix, and then (c) pigmented mature biofilm development. During all these stages, many microbial functions are expressed as communication (quorum sensing), cooperation (nitrification, microbial consortia), biodeterioration processes (extracellular enzymes, acids, hyphae), competition (antimicrobial and quorum quenching compounds), and resistance and tolerance to antifouling treatments (inhibited diffusion, sublethal concentrations, tolerance forms, resistance genes).

Figure 2: Targets (bacteria, algae, fungi), mechanisms of action (cell membrane modification, metabolism modification, ROS production, adhesion inhibition, quorum sensing inhibition), commercial interests (efficiency, lixiviation, duration, cost, commercial

availability), and side-effects of antifouling molecules (human health, environment, building materials); (a) biocides, (b), water-repellents, (c) superhydrophobic materials, (d) photocatalysts, and (e) natural compounds.