



HAL
open science

Polyaniline Nanocomposites for Hydrogen Sulfide Detection at ppb Level

Caroline Duc, Mohamed-Lamine Boukhenane, Thomas Fagniez, Nathalie Redon, Jean-Luc Wojkiewicz

► **To cite this version:**

Caroline Duc, Mohamed-Lamine Boukhenane, Thomas Fagniez, Nathalie Redon, Jean-Luc Wojkiewicz. Polyaniline Nanocomposites for Hydrogen Sulfide Detection at ppb Level. 8th International Symposium on Sensor Science, May 2021, Dresden, Germany. pp.69, 10.3390/I3S2021Dresden-10183 . hal-03380266

HAL Id: hal-03380266

<https://hal.science/hal-03380266v1>





Submitted on 22 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Abstract

Polyaniline Nanocomposites for Hydrogen Sulfide Detection at ppb Level [†]

Caroline Duc ^{*} , Mohamed-Lamine Boukhenane , Thomas Fagniez, Nathalie Redon 
and Jean-Luc Wojkiewicz 

Centre for Energy and Environment, IMT Lille Douai, Institut Mines-Télécom, University of Lille, 59000 Lille, France; mohamed-lamine.boukhenane@imt-lille-douai.fr (M.-L.B.); thomas.fagniez@imt-lille-douai.fr (T.F.); nathalie.redon@imt-lille-douai.fr (N.R.); jean-luc.wojkiewicz@imt-lille-douai.fr (J.-L.W.)

* Correspondence: caroline.duc@imt-lille-douai.fr

[†] Presented at the 8th International Symposium on Sensor Science, 17–28 May 2021; Available online: <https://i3s2021dresden.sciforum.net/>.

Abstract: Coming from natural and anthropogenic sources, hydrogen sulfide gas (H₂S) is a smelly hazardous substance at the sub-ppm level, which can lead to poisoning deaths at higher concentrations. New sensors with high metrological properties (detection limit lower than 1 ppm) and good stability are still needed to monitor and control the risk associated with this gas. The properties of a high-performance hydrogen sulfide gas sensor based on tin oxide and conductive polymers (polyaniline and poly(3,4-ethylenedioxythiophene):polystyrene sulfonate (PEDOT:PSS) are investigated. The principle of detection of this resistive sensor consists of a two steps reaction. H₂S reacts with tin oxide producing hydrochloride acid, which dopes polyaniline, leading to the increase of its conductivity. Those systems present high repeatability and reproducibility, with sensitivities around 10%/ppm and a limit of detection close to 30 ppb. Moreover, the effect of interfering species such as humidity and oxidative gases (ammonia) is addressed. Those species have a limited impact, corrigible by data treatment. Finally, the sensors present an increase of sensitivity with time, apparently due to the modification of the interface between the electrodes and the sensitive materials.

Keywords: gas sensing; hydrogen sulfide; conductive polymer; resistive sensor



check for
updates

Citation: Duc, C.; Boukhenane, M.-L.; Fagniez, T.; Redon, N.; Wojkiewicz, J.-L. Polyaniline Nanocomposites for Hydrogen Sulfide Detection at ppb Level. *Eng. Proc.* **2021**, *6*, 69. <https://doi.org/10.3390/I3S2021Dresden-10183>

Academic Editors: Gianarelio Cuniberti and Larysa Baraban

Published: 25 May 2021

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Copyright: © 2021 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (<https://creativecommons.org/licenses/by/4.0/>).

Institutional Review Board Statement: Not applicable.

Informed Consent Statement: Not applicable.