

# Light in the Cave: Opal coating detection by UV-light illumination and fluorescence in a rock art context. Methodological development and application in Points Cave (Gard, France)

Marine Quiers, Claire Chanteraud, Andréa Maris-Froelich, Emilie Chalmin, Stéphane Jaillet, Camille Noûs, Sébastien Pairis, Yves Perrette, Hélène Salomon, Julien Monney

#### ▶ To cite this version:

Marine Quiers, Claire Chanteraud, Andréa Maris-Froelich, Emilie Chalmin, Stéphane Jaillet, et al.. Light in the Cave: Opal coating detection by UV-light illumination and fluorescence in a rock art context. Methodological development and application in Points Cave (Gard, France). 2021. hal-03383193v2

# HAL Id: hal-03383193 https://hal.science/hal-03383193v2

Preprint submitted on 26 Oct 2021 (v2), last revised 14 Jun 2022 (v5)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Light in the Cave: Opal coating detection by UV-light illumination and fluorescence in a rock art context

#### Methodological development and application in Points Cave (Gard, France)

Marine Quiers <sup>a,\*</sup>, Claire Chanteraud <sup>b,c</sup>, Andréa Maris-Froelich <sup>a</sup>, Émilie Chalmin-Aljanabi <sup>c</sup>,
 Stéphane Jaillet <sup>c</sup>, Camille Noûs <sup>e</sup>, Sébastien Pairis <sup>d</sup>, Yves Perrette <sup>c,b</sup>, Hélène Salomon <sup>c</sup>, Julien
 Monney <sup>c</sup>

<sup>a</sup>Laboratoire Commun SpecSolE, Envisol – CNRS - Univ. Savoie Mont Blanc, Chambéry, 73000, France

<sup>b</sup>Missouri University Research reactor - University of Missouri 65203 Columbia MO

11 °EDYTEM UMR5204, CNRS, Univ. Savoie Mont Blanc, Chambéry, 73000, France

<sup>d</sup>Univ. Grenoble Alpes, CNRS, Grenoble INP, Institut Néel, Grenoble, 38000, France

<sup>e</sup>Laboratoire Cogitamus, 1 <sup>3</sup>/<sub>4</sub> rue Descartes, Paris, 75005, France

\* Corresponding author: m.quiers@envisol.fr

#### Abstract

Silica coatings developed on rock art walls in Points Cave question the access to pictorial matter specificities (geochemistry and petrography) and the rock art conservation state in the context of pigment studies. However, classical *in situ* spectroscopic techniques appear unsuccessful to identify these coatings, which also prevent pigment characterization. In this study, we propose using a UV fluorescence method for opal coating detection based on the fluorescence specificities of uranyl-silica complexes composing these deposits. A coupling of spectral identification using UV laser-induced fluorescence spectroscopy with UV illumination was performed on samples and μ-samples from the Points Cave rock art site. The well-defined peaks observed in fluorescence emission spectra due to uranyl ions validate opal detection and its correspondence with green fluorescence observed under UV light at micro- and macroscopic scales. *In situ* optical measurements under UV illumination reveal the presence of opal coating, especially on rock art walls in Points Cave. Opal occurrence and repartition observations provide the first insights into Points Cave wall evolution and chronological constraints linked to opal coating development. Regarding the strong interactions with pigment suggested by

multiscale observations of samples and  $\mu$ -samples, the impact of the presence of opal coating on Points Cave rock art conservation quality is questioned. Thus, by developing a specific and non-destructive characterization method for opal coatings, this study opens up a new approach for the study of decorated wall taphonomy and proposes utilizing mineralization both as markers of the natural history of caves and as an indication for their occupation by ancient human groups.

- **Keywords**: Silica coating, uranyl, UV fluorescence, *in situ* detection, rock art cave, Quaternary,
- 42 archaeology, Ardèche, France, optical methods

#### 1. Introduction

Natural activity in caves, mostly weathering, transforms the physical, chemical and mechanical conditions on the surface of the walls (Bassel, 2017; Chalmin *et al.*, 2018). Thus, the traces of all these transformations (environmental input) can be a source of information regarding natural and anthropological events on the wall surface, such as drawing and painting realizations, cave environment evolution, and human attendance in the cave (Sadier, 2013; Pons-Branchu *et al.*, 2014; Quilès *et al.*, 2015; Quing-Feng *et al.*, 2017; Garate *et al.* 2018; Valladas *et al.*, 2017; Money & Jaillet, 2019).

Among the taphonomic processes impacting rock art pictorial matter, mineral-coating formation as weathering products is well described in rock art research (Huntley, 2012). Silica rich amorphous deposits, also called silica skins, have been observed at different cave and open-air parietal sites (Watchman, 1990; Aubert *et al.*, 2004; Aubert *et al.*, 2012; Huntley, 2012). Thus, studies have suggested both a positive and negative impact on rock art conservation due to opal coating

development. Indeed, the strong interaction suspected with haematite pigments has been suggested as an element of conservation enhancement, notably compared with other pigments (Watchman, 1990). However, some authors have also observed exfoliation processes of silica skins, which could play a role in rock art weathering (Aubert *et al.*, 2004; Green *et al.*, 2017). To our knowledge, there is still no clear answer on the role of silica coatings as conservation factors of pictorial matter. In addition to this conservation issue, silica skins have been proposed as tools for indirect dating of parietal art, especially in the case of inorganic pictorial matter (Aubert *et al.*, 2004; Aubert *et al.*, 2012). Indeed, this mineral phase is known to be enriched in uranyl ions, but the U-Th dating application remains hypothetical due to silica skin thickness and absence of stratigraphy, which complicate both sampling and measurement reliability (Green *et al.*, 2017).

Thus, even if silica skin characterization represents a key issue in the rock art context, it remains difficult to identify and characterize, especially with non-invasive techniques. Currently, the use of *in situ* spectroscopic techniques in rock art studies is increasing, as these methods can provide information on both pictorial matter and pigment environments (substrate, deposits, concretions, etc.). The portability and decreasing cost of instruments coupled with the rapidity and the non-destructive character of analyses have led to a quasi-systematic use of these techniques in recent rock art studies (Huntley, 2012). However, amorphous silica characterization, even in the rock art context, is generally based on laboratory observations such as SEM or XRD analyses (Watchman, 1990; Gaillou *et al.*, 2008; Garcia-Guinea *et al.*, 2013; Huntley *et al.*, 2015; Green *et al.*, 2017). In addition, the signal of pictorial matter acquired with portable spectroscopic techniques could be impacted by the presence of silica skins, as observed by Huntley (2012) in the case of pXRF measurements.

In this paper, we propose a new method for the *in situ* detection and characterization of amorphous silica in a rock art context based on UV laser-induced fluorescence (LIF). Indeed, uranyl fluorescence characteristics under UV light are well known and have been observed in silica mineralization, especially in opal (deNeufville *et al.*, 1981; Gorobets *et al.*, 1977; Fritsch *et al.*, 2001; Gaillou *et al.*,


2008). Thus, UV spectroscopy presents the same advantages as other portable spectroscopic techniques, but the bright green fluorescence and the specific spectral features displayed by uranyl ions enable the targeted identification of opal coatings. To our knowledge, only one study has reported opal detection in caves using optical methods based on UV techniques (Garcia-Guinea *et al.*, 2013), and no study has applied UV spectroscopic methods in a rock art context for opal identification. Here, we propose a methodological development based on laboratory and field experiments to validate the use of *in situ* UV techniques for opal detection in a rock art context by coupling *in situ* optical and spectroscopic analyses to obtain multiscale information.

This study was performed in Points Cave (Aiguèze, Gard, France), which contains an important spread of opal coating on the cave walls. In this approach, Points Cave perfectly illustrates the importance of environmental input characterization in the study of rock art. The advantage of this site is given by the presence of colouring flakes falling from cave walls, allowing transport,  $\mu$ -sampling and analysis in the laboratory. Analysis of these coloured flakes allows us to identify and measure the environmental input, which modifies and obscures the identification of pictorial matter characteristics.

#### 2. Material

#### 2.1 Study site: Points Cave

Located in the Ardèche River gorge less than 10 km downstream of Chauvet Cave, Points Cave is a Palaeolithic rock art site identified in 1993 (Figure 1) (Deschamps *et al.*, 2018). Archaeological studies have been performed since 2011 as part of the "Datation Grotte Ornées" project ("Cave Art Dating" project, Monney, 2011; 2018). The entrance opens on a hundred-metre long gallery in Urgonian limestone. Rock art, exclusively composed of red imprints, is present in a unique sector in the middle part of the gallery, preserved from sunlight. Excavations conducted at the entrance indicated human and animal occupation during the Upper Palaeolithic (Monney & Jaillet, 2019).



Photogrammetric model of the Niche aux Points

Figure 1: Points Cave location in southeastern France and topographic map; photography of graphic entities: "Niche aux Points".


Points Cave is currently disconnected from hydrogeological flows (Jaillet & Monney, 2018). Only a few infiltrations can be observed after strong precipitation events. The low level of leaching on the wall and the quasi-absence of a calcite veil are due to this weak hydrogeological activity. Millimetric to centimetric concretions and efflorescences (coralloid type of crystallization) have developed on the wall surface in the decorated sector.

#### 2.2 Points Cave pictorial matter

1	า	7
ı	/	/

Parietal ornamentation, composed exclusively of reddish tracings and paintings, is currently observed in the middle part of the gallery. It comprises 59 palm-printed dots, commonly referred to as "palm points". This ornamentation also consists of five animal representations (three ibexes, a horse and a bison), two bilobed signs, an angular line and a few indeterminate traces (isolated lines and dots) (Monney, 2018). Moreover, archaeological colouring matter has been found in this sedimentary sequence at the entrance of the cave (Chanteraud & al., 2019; Chanteraud, 2020).

Investigations carried out at the foot of the rock art panel known as the "Great Signs" found five coloured wall flakes: S-ECA-01 to S-ECA-05 (Figure 2). Composed of limestone detached from the wall under mechanical action, these 3 to 20 cm flakes are covered on one side with colouring matter, probably coming from the large bilobed sign (graphic entity PTS-10) or from other unknown rock art panels that may have crumbled entirely from the walls nearby. These flakes are a major asset of Points Cave because they allowed us actual fragments of the decorated wall and transport them to the laboratory.



*Figure 2*: Limestone flakes found at the foot of the Bilobed Signs panel, location of  $\mu$ -sampling.

To identify both the iron-oxide morphologies and the natural mineralization that can form on the surface of the decorated walls, our study was centred around the five wall flakes discovered in the decorated sector of Points Cave and the 20  $\mu$ -samples taking from the decorated panels of the cave. One  $\mu$ -sample of pictorial matter was performed on each coloured flake ( $\mu$ S-ECA-01 to  $\mu$ S-ECA-05). All  $\mu$ -samples were observed and analysed without any preparation (Figure 2).

#### 3. Methods

#### 3.1 Macroscopic and microscopic observations

# 3.1.1 Laboratory and in situ observations at macroscopic scale

Image capture for macroscopic observations was performed in two steps: 1) a photograph was taken

under white light, and 2) another photograph was taken under UV light illumination. Observations at the macroscopic scale in the laboratory and in the cave were realized with a Canon EOS 5D Mark III camera and a Canon EOS 7D camera fixed on a tripod. A detached flash was used for image capture under white light. For UV light illumination, 4 UV LEDs (280 nm, 2.26 W, NewEnergy) were fixed on orientable macroflash bars on each side (2 LEDs per side) of the camera, allowing both macrophotography and general views of cave walls. Camera parameters are available in Table 1.

**Table 1**: Camera parameters used for both white and UV light illumination during field and laboratory macroscopic observations.

			Aperture	Obturation speed (sec)	Iso
Laboratory	White light		F/7.1	1/320	1600
·	UV light		F/7.1	10	1600
	White light	Macro	F/11	1/2	320
Field		Wall view	F/11	1/60	100
	UV light	Macro	F/4.5	1/2	320
		Wall view	F/11	15	320

Laboratory observations were also performed using a stereomicroscope (LEICA M165 C) under white and UV light. The same 4 LEDs were used for UV illumination.

### 3.1.2 Laboratory observations at the microscopic scale

At the microscopic scale, observations of  $\mu$ -samples of flakes on carbon tape were realized with a field-emission scanning electronic microscope (SEM) ZEISS Ultra+ associated with an EDX (energy

dispersive X-ray) probe (SDD, Bruker) working in high-vacuum mode with a 15 keV voltage. Images were taken with secondary electrons using in-lens or Everhart-Thornley detectors (SE2) and with backscatter electrons (BSE-AsB detector) (Néel Institut, Grenoble).

#### 3.2 UV fluorescence analyses

Stationary fluorescence signal of flake and flake  $\mu$ -samples was measured in the laboratory with a solid-phase spectrofluorimeter designed in the EDYTEM laboratory for non-destructive solid-phase measurements (Perrette *et al.*, 2000).

This instrument is divided into excitation and detection compartments associated with a translation stage system for sample surface measurement. For this experiment, the excitation system was composed of a Nd:YAG laser (Crylas, FQSS266-Q1) with a 266 nm excitation wavelength. The fluorescence emission response was collected after sample excitation by focusing the laser beam (~30 µm) on its surface. The detection system was composed of a low-pass filter monochromator (Jobin Yvon, MicroHr) for light diffraction, fitted with a 300-g/mm diffraction-grating centred at 620 nm, associated with a thermoelectric-cooled, back-illuminated CCD (Jobin Yvon, Sincerity) for high-efficiency signal detection in the UV-visible light domain. As no manipulation, modification or destruction of the sample surface occurred during analysis, this technique is suitable for archaeological sample measurements.

Two types of fluorescence measurements were realized:

- Single point measurements were performed on flake μ-samples (μS-ECA-03, μS-ECA-04 and μS-ECA-05). One spectrum was independently acquired on the sample. Measurement location was determined manually. An acquisition time of 1 s and a monochromator entrance slit of 0.25 mm (~1 nm spectral resolution) were used for spot spectrum acquisition.
- Surface measurement was performed on flake S-ECA-05. The motorized translation stage

202 system allowed movements in two directions for surface measurements. The image was 203 obtained by stacking lines along the Y-axis. For this study, fluorescence surface imaging was 204 performed with a 100×100 µm resolution using a 0.1 s acquisition time and a 0.05 mm 205 entrance slit. 206 207 Data pre-processing was performed with MATLAB software. Spectra were corrected from baseline 208 and instrument responses and then filtered with the Savitsky-Golay method (Savitzky & Golay 1964). 209 210 4. Results 211 212 213 4.1 Macroscopic scale observations 214 At the macroscopic scale, no mineralization was observed on the walls, flakes or μ-sample surfaces. 215 Here, the coralloid type of crystallization was not taken into account due to its centimetric size. In fact, 216 217 at this observation scale, surfaces seemed to be well preserved with strong colouration from the 218 pictorial matter and clear access to the calcareous substrate (Figure 2). 219 It has been shown that decorated panels of the cave display various mineralizations, such as calcium 220 221 sulphate (Chanteraud et al., 2020). However, these deposits remain invisible even after inspection 222 under a stereomicroscope, revealing the need for microscopic inspection using SEM. 223 224 4.2 Microscopic scale observations 225

At the microscopic scale, a 1 µm-thin mineral film consisting of nonordered spheres was identified as

silica mineralization on flake μ-samples (Figure 3). Its geochemistry and hummocky morphology are

226


related to a type A-g amorphous opal with a SiO<sub>2</sub>nH<sub>2</sub>O formula (Flörke et al., 1991). The mineral structure present on coloured flakes suggested its formation from a water film containing a high concentration of silica (Monger and Kelly, 2002; Curtis et al., 2019).

231

228

229

230



232

Figure 3: SEM observations of μ-S-ECA-05. 1/ Corrosion gulf in hematite plate observation in Secondary Electron mode (SE); 2/ Pillow-like silica coating on surface in SE mode; White rectangle =

Area of EDX spectra on the pillow-like silica coating.

234

235

236

237

238

Concerning the µ-samples from the decorated walls, the same observations were noted, including pseudohexagonal platy haematite and some strong indications of opal. Importantly, these samples showed significant opal development, with a complete coating of the pictorial matter to the extent that the morphology of the haematite was no longer observable on the surface.

240

241

242

243

244

245

SEM observations of flake µ-samples allowed us to identify pictorial matter as haematite due to its colour and macro- and micromorphologies. Typically, the haematite composing the pictorial matter was pseudohexagonal and showed corrosion gulfs (Figure 3). Weathered haematite plates seem to have been "ingested" by the silicate coating and could only be observed when a section was accessible on the surface of the sample (Figure 4). However, preliminary studies on the walls of Points Cave using portable spectroscopic techniques (pXRF and Raman) could not identify the presence of opal coating in situ (Chanteraud et al., 2020).

247

246




Figure 4: Haematite plates embedded in the opal coating on PRM-19-10 and PRM-19-16 μ-samples (SEM observation in SE and BSE mode).


4.3	Opal	identification	by	UV-fluorescence	9
-----	------	----------------	----	-----------------	---

251	
252	

To evaluate the potential of UV fluorescence to detect the opal mineral phase, fluorescence analyses were first performed on 3 flake  $\mu$ -samples ( $\mu$ S-ECA-03,  $\mu$ S-ECA-04 and  $\mu$ S-ECA-05) that were previously characterized by different geochemical analyses. Due to the small size of the samples (approximately 200  $\mu$ m), only a few localized spectra were recorded. The spectra obtained could be divided into different emission regions depending on the main signal sources (Figure 5):

- From 300 to 470 nm, this region corresponds to the fluorescence emission of the sample matrix. Peaks and shoulders were detected at approximately 350 nm, 380-390 nm, 410 nm and 430-440 nm. According to the literature, they could be associated with organic matter entrapped in the crystalline matrix (McGarry & Baker, 2000; Perrette *et al.*, 2000; Van Beynen *et al.*, 2001; Perrette *et al.*, 2005; Quiers *et al.*, 2015) or with the silica material fluorescence response to UV-light excitation (Boyko *et al.*, 2011; Garcia-Guinea *et al.*, 2013).

From 470 to 750 nm, special features were identified in this part of the spectra for samples  $\mu$ S-ECA-04 and  $\mu$ S-ECA-05. They were characterized by a sequence of 3 defined peaks at 501, 521, and 545 nm and a shoulder at approximately 572 nm. These peaks were identical in all spectra measured on  $\mu$ -samples  $\mu$ S-ECA-04 and  $\mu$ S-ECA-05 and coincided with the uranyl ion spectrum in silica matrices based on a review in the literature (Table 2).



**Figure 5**: Mean fluorescence emission spectra (excitation 266 nm) of samples μS-ECA-04 (blue), μS-ECA-05 (red) and μS-ECA-03 (orange). Spectra are divided into three different regions as a function of the main fluorescence signal sources: sample matrix, uranyl ions and laser emission reflectance.

Entrapment of uranyl ions in siliceous matrices, especially opal phases, is well documented in the literature (Zielinski, 1980; Kasdan *et al.*, 1981; Kinnunen & Ikonen, 1991; Neymark *et al.*, 2000; Fritsch *et al.*, 2001; Gaillou *et al.*, 2008; Devès *et al.*, 2012; Fritsch *et al.*, 2015; Othmane *et al.*, 2016). The strong affinity of uranyl groups for amorphous silica leads to a strong U-opal association, which is stable at the scale of geological time (Othmane *et al.*, 2016). Thus, uranyl-specific spectra could be associated with the presence of opal on samples, and UV fluorescence analysis represents an efficient tool for its identification. As opal detection was subject to uranyl fluorescence properties, detection using UV fluorescence was dependent on uranium entrapment in silica crystalline structures. In their study of opal gems from different geographic and geological contexts, Gaillou *et al.* (2008) showed that not all opals are fluorescent. Opal fluorescence can be divided into two classes: blue fluorescence

caused by intrinsic oxygen-related defects typical of amorphous silica structures and green fluorescence attributed to uranyl groups (Fritsch *et al.*, 2001, 2003), which is believed to be typical of common opals. A low content of U ( $\geq$  1 ppm) automatically induces a green fluorescence response to UV light excitation and can reach more than 100 ppm in some deposits (Gaillou *et al.*, 2008). Garcia-Guinea *et al.* (2013) measured a uranium amount of 193 ppm in stalactites in Castanar Cave. Thus, detection of opal via UV fluorescence is not systematic but common, as a low content of uranium allows fluorescence emission. However, uranium concentration in Points Cave  $\mu$ -samples have not been measured due to the particularly thin opal layer and the impossibility of destroying  $\mu$ -samples.

**Table 2**: Fluorescence emission peaks for different opal or amorphous silica deposits reviewed in the literature.

#### Fluorescence emission peaks (nm)

Othmane et al. 2016	504	524	546	570	-
Ottimane et al. 2010	504	523	545	573	-
Fritsch et al. 2015	504	524	546	572	604
Brennan & White 2013	502	520	-	-	-
Garcia-Guinea et al. 2013	505	524	543	569	650
This study	501	521	545	572	-

To evaluate method accuracy at a larger scale, a second experiment was performed directly on flake S-ECA-05. UV fluorescence cartography (100 x 100 µm resolution) showed a range of spectra presenting uranyl spectral characteristics. Assuming that the fluorescence signal can be interpreted as a mixing of a uranyl signal with a matrix signal, opal information was extracted from fluorescence cartography using a mixing algorithm, MCR-ALS, with the MCR-ALS toolbox in MATLAB software

(Jaumot *et al.*, 2015). MCR-ALS has become a popular chemometric method in solving mixture analytical models. It is based on an additive bilinear model of pure contributions that depends on the concentration and the specific spectral sensitivity of each component. This algorithm can also be applied to obtain quantitative information (Jaumot *et al.*, 2005; de Juan *et al.*, 2014; Zhang & Tauler, 2013). A singular value decomposition (SVD) method was first used in the MCR calculation to define the number of initial loadings. Thus, three components were estimated that mainly contributed to the fluorescence signal. These three initial loadings were calculated using the PURE algorithm, a commonly used method to find the purest variable, and could be associated with uranyl fluorescence spectra, matrix fluorescence signal and background signal (Figure 6).




Figure 6: Initial loadings obtained with the PURE algorithm on fluorescence cartography spectra.

MCR-ALS was then performed based on these 3 initial loadings. Non-negativity constraints were applied. Model results ( $r^2$ =99.88) indicated a contribution of uranyl to the sample fluorescence signal

% of opal contribution to fluorescence signal Number of measured points (100 µm step) Number of measured points (100 µm step)

Figure 7: Opal fluorescence signal proportions measured on the S-ECA-05 flake and obtained with the MCR-ALS algorithm.


Evaluation of opal proportions on the sample using this method is, however, subject to certain biases. Similar to the majority of spectroscopic techniques, this detection method can only detect surface deposits. Thus, opal mineralization located under other mineral or organic deposits cannot be detected. Moreover, for quantitative measurement, the measurement sensitivity to changes in sample surface microtopography must be taken into account. As the laser beam is focused on the surface, variations in fluorescence intensities measured on the sample, and thus opal estimations, can be biased by millimetric changes in surface relief.

In addition, this method remains effective in extracting information on opal mineralization even on heterogeneous matrices, such as the Points Cave μ-samples. Due to its specific spectral shape, uranyl signal can be easily extracted from mixed fluorescence signals. In addition, mixing algorithms could provide quantitative information if combined with calibration methods. Indeed, the MCR-ALS algorithm has been used for the quantification of different target molecules based on various spectroscopic data (Mas *et al.*, 2010; Araya *et al.*, 2017; Kumar *et al.*, 2018; Castro *et al.*, 2021). Regarding sample complexity, calibration protocols based on standard references and prepared or artificial mixtures are difficult to apply (Araya *et al.*, 2017). Quantification strategies need to be developed for archaeological materials, reaching a balance between sample destruction and model result robustness, such as those developed for hyperspectral data. Then, the estimated concentration accuracy will depend on the legitimacy of the assumption made in the quantification strategy (Araya *et al.*, 2017).

#### 4.4 Visual detection under UV light: laboratory experiments

As explained previously, minerals containing uranyl ions (UO<sub>2</sub><sup>2+</sup>) have been known to exhibit strong fluorescence marked by specific spectral features and temporal characteristics since at least early 1900 (deNeufville *et al.*, 1981). The bright green fluorescence of uraniferous opal is a well-known characteristic of this mineral phase and has been related to the presence of uranium (Gorobets *et al.*, 1977; Fritsch *et al.*, 2001). To evaluate whether this specificity can be used for opal detection, flake μ-samples were exposed to UV light (see 3.1.1). The results show that μ-samples μS-ECA-04 and μS-ECA-05 exhibited a bright green-light response (Figure 8). These two sample spectra contained specific features corresponding to the fluorescence emission of uranyl ions. Green illumination was thus associated with the presence of U-opal on these samples. The case of μ-sample μS-ECA-03 was more complex. While the fluorescence spectrum did not show any spectral features associated with the uranyl signal, localized greenish fluorescence could be distinguished on the sample. This could be

explained by a less precise measurement due to a more difficult targeting of opal because of the higher sample size or more scattered opal distribution. Second, the sample surface was more coloured and had more pictorial matter (cf. §4.1), suggesting decreased ability for detection.



*Figure 8*: Photographs of three  $\mu$ -samples taken on flakes under white and UV light.

Considering that uranyl green illumination is representative of the presence of opal, detection concordance between spectral and visual techniques was tested at a larger scale by comparing UV-illuminated photographs with UV fluorescence cartography of flake S-ECA-05 (Figure 9). For this purpose, the green component of the RGB image was extracted from UV-light photos. The grayscale image was subtracted to avoid the luminosity effect, and a threshold was applied to the image obtained to select only pixels containing green colour. To help compare the opal information provided by both techniques, images were aligned using point control selection and geometric transformation functions in MATLAB.

The results show a high correspondence between spectral and visual detection methods. To evaluate the efficiency of the optical method, opal cartographies with different detection limits were simulated using the opal contribution percentage to the fluorescence signal from spectroscopic measurements and compared with optical data. The opal contribution threshold of 27% presented the best correlation coefficient with opal extracted from UV photographs (R<sup>2</sup>=0.50). This indicated that opal detection with the optical method was efficient when opal fluorescence emission contributed at least 27% of the total fluorescence signal of the sample. Under this threshold, the detection efficiency decreased for the optical method. The rather low correlation coefficient between both images could mainly be explained by the point control selection and geometric transformation applied to readjust them together. Angle disposition of the sample and detector combined with image resolution could have led to difficulties in adjusting the images. Further research in the computational image domain could improve the methodology and enhance the correlation between the two techniques.




Figure 9: Detection and location of opal mineralization on flake S-ECA-05 obtained using UV illumination (A) and UV fluorescence techniques (B).

#### The two methods are compared in C.

#### 4.5 Visual detection under UV light: field experiments

An *in situ* photographic protocol that alternated white light and UV illumination was applied to the Points Cave walls. As shown in Figure 1, three rock art panels were investigated with one wall where rock art was absent. Images were realized at both the wall and macroscopic scales.

At the wall scale, the rock art panels investigated (Niche aux Points, Bilobed Signs and Ibexes) displayed large green fluorescent zones when illuminated by UV LEDs (Figure 10). This green fluorescence response was consistent with preliminary results obtained in the laboratory on cave wall flakes and  $\mu$ -samples from these zones. Thus, UV illumination successfully enabled the detection of opal coatings on these walls, according to the green response observed in photographs.

In contrast, no opal signal appeared clearly distinguishable in photographs of the wall situated a few metres before the art panel. These photographs displayed greenish fluorescence mixed with other signals, making it difficult to identify and extract green colour with accuracy. Spectroscopic measurements need to be performed to precisely identify the presence of opal.

Macroscopic-scale observations under UV light allowed the targeting of specific deposits or zones on cave walls. In the particular case of the Bilobed Signs panel, macroscopic investigation targeting flaking zones revealed a contrast between the rock art panel and the zones where flakes had detached from the wall. Indeed, the left part of the UV photograph (Figure 10) displayed numerous green fluorescent spots, whereas they were absent from the right part of the photograph. Efflorescence

concretions on cave walls, which are widely spread in Points Cave, were also investigated, but the presence of opal has not yet been validated.

#### 5. Discussion: Implications of opal detection for rock art studies at Points Cave

#### 5.1 Contribution of UV fluorescence techniques

According to the first results obtained using the *in situ* UV illumination method and the preliminary results obtained in the laboratory on cave wall flakes and μ-samples from rock art panels, *in situ* measurements successfully detected the presence of opal in Points cave. Indeed, the green fluorescence observed on Niche aux Points, Bilobed Signs and Ibexes panels suggests that opal development covers a large area of cave walls, especially in rock art zones. Macroscopic observations also help to provide initial insights into rock art-opal interactions, as UV light allows for the targeting of specific deposits or zones on cave walls. It provides complementary information on opal distribution and interaction with archaeological material. For example, investigation of the flaking zone suggests a current absence of extended opal film or opal mineralization, probably due to desquamation occurring on this wall.

However, the opal signal is not always clearly distinguishable, as observed on the wall outside of the rock art zone or on coralloid concretions. Yet, these speleothems are known to contain a silica layer enriched with uranium (Monney *et al.*, 2019; Barbarand et Nouet, 2020). Alternating layers of silica and calcite or the presence of calcite cover could explain the ambiguous signal. First, this highlights the need for *in situ* fluorescence spectroscopic measurements to validate the photographic identification of the opal mineral phase in cases where the green response is not clearly detectable. Second, colour perception varies greatly from one image to another, even within the same site, making it difficult to evaluate the mineral phase distribution. Even if camera and image treatment parameters

influencing colour display (white balance, exposure time, filters, etc.) can be easily standardized, lighting variations (LED orientation, position, distance from wall, etc.) are difficult to homogenize. As this paper presents preliminary results attempting to validate the detection method, no protocol for colour calibration was applied. Further research on the Points Cave site will be subject to the development of a colour calibration procedure.

Finally, UV illumination also highlights various types of deposits, sometimes not clearly detected under white light. After fluorescence analyses in the laboratory or directly *in situ*, this technique could help to detect other mineral or organic phases. Moreover, it is interesting to note that UV illumination emphasizes the presence of pigments due to their iron composition. Indeed, iron ions are known to have a quenching effect on the fluorescence signal, including that of uranyl ions (Gaillou *et al.*, 2008; Chen *et al.*, 2011). Thus, pigments appear clearly as no fluorescence zones on UV photographs, which can be an interesting tool for rock art analysis, such as determination of sampling protocol or dermatoglyph analysis.

Thus, UV methodology appears to be an efficient non-invasive tool for the *in situ* identification of U-opal mineralization. Due to the green fluorescence resulting from UV excitation, it allows rapid *in situ* detection of the opal mineral phase with direct results and very simple and low-cost equipment. As this method has already been applied with success in some caves, rarely calcareous, for the detection of U-silica complex deposits or concretions, as in Castañar Cave (Garcia-Guinea *et al.*, 2013), this study differs in two ways. First, to our knowledge, this method has never been applied to opal detection in a rock art context. Second, we propose *in situ* opal identification based on spectral features for result validation using a portable UV-LIF instrument. This instrument is currently in development and could not yet be taken into the cave, but preliminary tests applied to flakes in the laboratory confirm its ability to detect opal. Finally, opal mineral characterization can also be achieved with high-spatial resolution at the microscopic scale with a laboratory LIF instrument. Spatially high-resolution fluorescence maps can also provide more information on mineral phase repartition,

development and interaction with other organic and mineral phases present on the sample. Thus, the combination of these two methodologies provides a complete solution for the identification and detection of opal mineralization in both sampling and analytical strategies and *in situ* characterization.

#### 5.2 What do we know about Points Cave opal

The results obtained with the analyses presented in this paper and with UV methods applied to samples and *in situ* have provided the first information on opal coatings in Points Cave. Indeed, based on SEM analyses of flakes and μ-samples, Points Cave opal is associated with the amorphous opal type (type A). XRD is usually performed for precise opal type determination (Curtis *et al.*, 2019). However, in the case of Points Cave opal, this analysis is difficult to perform due to the opal thin layer on calcareous substrate and iron-rich pigments. Analyses at macro- and microscopic scales suggest thin film deposition as a mineralization type, such as silica skins observed at various rock art sites (Watchman, 1990; Green *et al.*, 2017). This film appears to be deposited under or at the interface with pigment and other crusts. SEM analyses show that the opal structure encapsulates haematite plates on several samples, suggesting strong interactions with pictorial matter (Figure 4). Further studies must be conducted to understand how these two phases interact, but a preliminary hypothesis regarding dissolution and corrosion of haematite plaques by opal can be proposed.

The presence of uranyl ions entrapped in the opal structure was verified by UV spectroscopic analyses. High fluorescence intensities of opal at Points Cave suggest significant content of uranium trapped in the crystalline structure. Similar enrichment in uranium has been found in numerous common opals (Amelin & Black, 2006). However, no quantification of uranium content has yet been realized. Although uranium isotopic measurements were realized on speleothems from Points Cave (stalagmites and coralloids), none was applied on flakes, or flake and wall  $\mu$ -samples because of their destructive character. According to the literature, as no minerals containing U4+ are known to fluoresce, uraniferous silica precipitation involves oxidizing conditions sufficient to mobilize U6+ (Zielinski,

1982). For example, Garcia-Guinea *et al.* (2013) explained uranium-bearing opal deposition in Castañar Cave by oxidation of host rocks with meteoritic waters. Zielinski (1982) explained that the initial precipitation of silica was as an amorphous silica gel, with which dissolved uranium coprecipitated before the silica gel dehydrated to form opal. The formation of uranyl-silica complexes is favoured by the natural affinity between aqueous uranyl ions and the silica gel surface, which is very sensitive to pH (optimum range = pH 5-5.5) (Garcia-Guinea *et al.*, 2013).

The *in situ* approach shows an important spread of this coating on Points Cave walls, especially on rock art panels. Concerning the walls a few metres before the rock art panels, the presence of opal needs to be confirmed by spectroscopic measurement and laboratory analyses. Points Cave chronology is constrained by different periods marked by cave wall evolution under climatic and anthropogenic factors (Monney & Jaillet, 2019). The presence of opal mineralization throughout its formation and developmental processes could provide insights into cave chronology. A flaking period was identified subsequent to ornamentation, resulting from mechanical expansion or desquamation, affecting the deepest zones of the cave, and possibly concurrent with gelifraction during MIS2 (Marine Isotope Stage 2) (Monney & Jaillet, 2019). As described previously, UV photographs indicated the absence of a well-developed opal film in the flaking zone, suggesting that opal formation occurred principally before this flaking period. This could also explain why photographs taken on walls between the cave angle and the rock art sectors displayed less marked fluorescence, as this zone presents high flaking rates (Jaillet & Monney, 2018) (Figure 10).




Figure 10: Topographic section of Points Cave with estimated flaking and location of white and UV light photographs according to Jaillet & Monney, 2018.

The chronology of opal deposits over art paintings and drawings cannot be confirmed at this stage. SEM observations show that opal mineralization colonizes empty spaces under, below, and inside pictorial matter. These observations suggest opal postdeposition over painting realization, although prior mineralization cannot be ruled out.

Thus, ongoing studies are crucial in completing opal coating characterization in Points Cave. This is a tool in understanding cave wall and pigment interactions throughout the factors and processes of opal formation and other mineralization.

#### 5.3 Opal factors and formation

Mineralization origin and formation mechanisms and factors are clues for understanding past climate and cave wall evolution. As this paper presents preliminary results, only hypotheses for opal origin and formation are presented.

Opal, as a hydrated mineral, is associated with fluid circulation. Thus, water is generally involved in precipitation, and silica has to be in solution before precipitation (Chauviré *et al.*, 2017). In Points Cave, the presence of silica coating with high uranium content in the limestone context supports the hypothesis of mineralization originating from groundwater. Wall humidification and water physicochemical properties directly influence the coating formation rate. In very wet sites, the silica skin growth rate can reach 0.25 mm per millennia, whereas occasionally wet sites present a mineralization rate on the order of 0.02 mm per millennia (Aubert *et al.*, 2004). Silica coatings can only be formed and preserved if low infiltration volumes occur, as higher volumes favour dissolution of soluble compounds and decrease silica precipitation (Aubert *et al.*, 2004).

Chauviré *et al.* (2017) explained that even though opal is found in various geological contexts, three main types of formation can be identified: 1) hydrothermal activity, 2) continental weathering and 3) biological precipitation. As no hydrothermal activity was identified at Points Cave, only the latter two types can be involved in opal formation at this site.

Biological formation of opal in caves is less documented than hydrothermal alteration and continental weathering. Various microbial forms and algae have been observed to be associated with opal in caves, such as siliceous algal diatoms (Northup *et al.*, 2001), and are often linked to coralloid concretions. In the case of Points Cave, a few microscopic and cave wall μ-sample observations show undetermined structures containing high carbon content, which could be associated with biological activity. Nevertheless, the hypothesis of biological formation of opal cannot be ruled out or confirmed at this stage, and further studies need to be conducted.

554

555

556

557

558

559

560

561

562

563

564

565

566

567

568

569

570

571

572

Continental weathering is defined by rock transformation by meteoric water and a precipitation temperature below 50°C, in contrast to hydrothermal alteration (Chauviré et al., 2017). Silica anions released by this process precipitate because of fluid supersaturation due to various changes in conditions, such as pH or temperature (Devès et al., 2012; Chauviré et al., 2017). Thus, supersaturation of silica solutions may be initiated by a drop in temperature or pH or an increase in salinity. When a solution is supersaturated in SiO2, silicic acid could polymerize to form a colloidal suspension from which amorphous silica can precipitate. Polymerization is controlled by temperature (decreasing T° increases the polymerization rate), degree of supersaturation, salinity and mainly pH (maximum polymerization rate around pH 7.5; minimum polymerization rate under pH 3 and above 9) (Devès et al., 2012). One of the most efficient pH-driven mechanisms for silica precipitation involves acidification of highly alkaline solutions (Zielinski, 1982). Such alkaline conditions are not common, but in the case of calcite-dominant material in sediment, pH could reach this threshold (Karkanas et al., 1999). Freezing temperature has also been shown to help supersaturation, polymerization and rapid precipitation of opal, whereas low or moderate temperatures induce slow polymerization (months or years) (Devès et al., 2012). Cryo-segregation is another reported genesis, caused by moisture freezing on cave walls, which concentrates dissolved salts. They precipitate out in the case of supersaturation of the solution (Devès et al., 2012). As opal formation probably occurred between the Upper Palaeolithic and the Last Glacial Maximum and because freezing temperatures have been shown to have modified Points Cave wall topography, a temperature decrease represents a realistic factor for opal formation. However, there is currently a lack of evidence to confirm this hypothesis.

573

574

575

576

577

578

Silica solutions can originate from 1) superficial cover, 2) host rock, or 3) volcanic ash in a continental weathering context (Devès *et al.*, 2012). Volcanic ash is an interesting hypothesis, as it is assumed to provide high contents of silica and uranium and because the Ardèche region had recent volcanic episodes during the Upper Palaeolithic. Indeed, Nomade *et al.* (2016) dated volcanic eruptions in the Bas-Vivarais region between  $29 \pm 10$  ka and  $35 \pm 8$  ka and suggested that Chauvet rock art, 35 km

away, could depict volcanic eruption representations. The current alluvial plain and the lowest former alluvial level (+8 m) deposits contain much basaltic material partly derived from Bas-Vivarais lava, which were subjected to intense erosion and weathering in the alluvium terraces (Genuite *et al.*, 2021). Thus, the location and chronology of the volcanic activity (approximately 45 km from Points Cave) represent an interesting origin hypothesis for both silica and uranium contents in opal. However, determining the origin of uranyl-enriched silica solutions is difficult with our current information. Another hypothesis for silica solution origin can be supported by the presence of a marl layer within the Urgonian limestone, which constitutes the cave environment (Sadier, 2013); or by pebbles originating from the Ardèche River and providing silica by infiltration from the overlaying alluvium terrace or by river deposition (Mocochain *et al.*, 2009; Genuite *et al.*, 2021).

Thus, understanding the origin and mineralization factors that influence opal formation could provide information on chemical and physical processes occurring on the cave wall surface. According to Green *et al.* (2017), this knowledge is "crucial for targeted sample collection and the application of a range of dating techniques as well as for the development of conservation strategies". Further studies still need to be performed to identify opal origin and formation factors at Points Cave.

#### 5.4 Chronology and dating

Red pigments used in rock art are difficult to date precisely (Aubert *et al.*, 2007). Thus, several studies have proposed indirect dating methods using associated mineral deposits interlaying pictorial matter to date or to provide chronological constraints on rock paintings (Watchman, 1990; Aubert *et al.*, 2007; Aubert *et al.*, 2017), such as opal coatings.

Indeed, in the first place, opal coating could help to precise relative chronology thanks to knowledge regarding climatic and environmental factors controlling its mineralization, and to its distribution on walls in comparison to other deposits and archaeological material.

Amorphous silica skins have been used for radiocarbon analyses based on organic remains trapped by mineralization, such as diatoms or algal matter, on different Australian rock art sites (Watchman, 2000; Morwood *et al.*, 2010). However, as silica coatings may contain various organic materials, each presenting a specific radiocarbon signature, dating could result in a mixture of different ages by incorporation of younger or older material (Aubert *et al.*, 2017; Green *et al.*, 2017). In addition, the formation processes of these coatings are not fully understood, requiring great caution when using radiocarbon methods (Aubert *et al.*, 2017). Using compound-specific carbon analyses could potentially avoid this problem (Aubert *et al.*, 2017) but are more difficult to apply to thin deposits, especially in rock art contexts.

Moreover, opal often contains high uranium contents, which could be used for high-precision dating with methods such as <sup>230</sup>U/Th or U/Pb (Zielinski, 1980; Oster *et al.*, 2017). Because of opal's ability to concentrate uranium from water while rejecting Pb and Th, amorphous silica is an interesting alternative to carbonate minerals (Amelin & Black, 2006). Indeed, <sup>230</sup>Th/U and U/Pb methods have been applied to opal and have provided reliable ages (Neymark & Paces, 2013). They enable chronological constraints or dating hydrogenic subsurface water flow, pedogenesis, and processes such as ore formation deposits (Neymark & Paces, 2013). They also have been applied in the case of paleoclimate reconstruction in silica speleothem studies (Lundberg *et al.*, 2010). Depending on the formation processes, opal coating could thus be used for dating purposes.

In rock art research, dating of amorphous silica deposits could be used as an age constraint for rock drawing events, depending on the pigments and mineral phase superposition. In their study, Aubert *et al.* (2007) performed U-series dating on a 2.5 mm thick calcite coating using the MC-ICPMS technique, allowing high spatial and temporal resolution. Even though only micrograms of samples are needed, authors (Aubert *et al.*, 2007; Aubert *et al.*, 2017) have suggested that for samples with U concentrations > 1 ppm, sampling could be largely reduced, and LIBS techniques could also be

applied *in situ* with a 100-200 µm diameter ablation spot. As opal concentrates more U than calcite, these techniques appear to be possible. However, for some authors, the application of uranium series dating to silica skins appears difficult to achieve (Green *et al.*, 2017). Sampling that provides sufficient intact fragments for LA-ICP-MS analysis without damaging rock paintings is one of the main issues regarding this application. The difficulty of performing closed system conditions and replicability tests for evaluating dating reliability has also been highlighted by authors.

Moreover, methods for opal detection could offer supplemental help before sampling for dating. Indeed, precise targeting of uranium-bearing opal enables identification of pure silica phases in mixed samples, detection of high uranium contents or impurity avoidance. In the case of thin layer deposits, such as coralloids, sampling could decrease dating accuracy when mixing different layers (Devès *et al.*, 2012). Tracking the location of opal phases could avoid this issue by spatially constraining sampling.

# 5.5 Implication of opal mineral characterization for conservation of rock art material

Taphonomy represents a range of transformations affecting archaeological material that distort archaeological records. Thus, rock paintings have undergone a plurality of transformations impacting pigment longevity, colour (Bednarik, 1994) and identification. The exceptional of Points Cave dermatoglyphs has no comparison with other associated parietal sites in Ardèche and begs the question of opal impact on pigment conservation.

The association of silica skins composed of opal and pigments has been frequently observed at rock art sites, mainly in open-air sites on sandstone and quartzite substrates in Australia or Canada (Watchman, 1990; Aubert *et al.*, 2004; Aubert *et al.*, 2012; Huntley, 2012). Some studies have suggested that pigment binding in silica coatings aids rock art visual preservation (Watchman, 1990), providing a resistant layer to chemical weathering. SEM observations on Points Cave flake and wall μ-samples

indeed suggest a strong interaction between pigments and opal, as mineralization penetrates pigment deposits. If the quality of Points Cave paintings tends to corroborate this hypothesis, exfoliation impacting silica skins observed at some sites should also be mentioned, as it could cause removal of associated pigments (Aubert *et al.*, 2004; Green *et al.*, 2017). Thus, exploiting the observed benefits of silica film deposits for conservation strategies has not yet been proven (Green *et al.*, 2017). Furthermore, it has also been observed at open-air sites that silica skins could reduce the colour tone of paintings and drawings at some locations (Green *et al.*, 2017).

If pigment weathering can be influenced by their own properties by inducing changes in surface area, albedo, light transmissivity or moisture (Huntley, 2012), mineral deposits have been recognized to be important factors in rock art taphonomy (Chalmin *et al.*, 2018). In addition to analytical impacts, knowledge of mineral phases is essential because it informs us regarding the physical and chemical impacts on pictorial matter and whether they favour conservation or degradation effects. Mineral phase characterization is thus an important part of conservation strategies, and adapted identification and analytical methods are needed.

#### 6. Conclusion

The methodological development proposed in this paper was motivated by the identification of opal in different contexts:  $in \ situ$ , in the laboratory, on centimetric objects and on  $\mu$ -samples. The aim of this identification is to question the possibility of accessing the specificities of the colouring matter applied on the walls (petrography and geochemistry). Therefore,  $in \ situ$  identification of silica coating observed in the laboratory was crucial for further studies on pigment characterization.

The results obtained on flakes and flake  $\mu$ -samples from Points Cave show that UV LIF is an efficient technique to detect and identify uranyl-silica complexes, even on heterogeneous and complex surfaces.

Although opal coating detection is limited by scale (laser beam) and by the outcropping nature of the deposit, UV LIF spectroscopy offers a rapid and non-invasive tool that can easily be brought to the site and positioned in front of the decorated panels. A photograph of green bright fluorescence emitted by opal was used here as a method of *in situ* detection of this mineral coating. A comparison with the UV LIF method shows a great correspondence between the two methods. The first tests of UV illumination in the cave highlight the need to develop an accurate measurement protocol, especially to homogenize light and colour, and the need to validate the identification using UV spectroscopy. In addition to further methodological development, UV optical technique shows great potential because it successfully detects the presence of opal and its distribution on rock art panels.

Thus, the results obtained with our methodology provide insights into disturbances in the classical *in situ* spectroscopic analyses (pXRF and Raman) observed at Points Cave. The identification and characterization of opal coatings is thus essential because of their impact on *in situ* analysis, which does not allow the detection of iron spectroscopic signal. For this reason, we propose early, on-site observations combined with sampling of surrounding material, such as fallen flakes from cave walls, as an alternative strategy to i) characterize pigment-associated mineral phases, ii) choose the best site-adapted combination of techniques and devices for *in situ* analyses and iii) define laboratory analytical strategies depending on the pictorial matter environment.

Moreover, optical methods with *in situ* visual detection, such as the UV light illumination method

proposed in this paper, represent an interesting tool to add to sampling and analytical strategies. Visualization at a larger scale of the presence and distribution of mineral deposits that could interfere with pigment analyses is a great help in locating sampling or *in situ* measurements to avoid

708 interference.

In addition to analytical impacts, the detection and identification of mineral phases can provide valuable information on the pigment environment and human practice chronology. If speleothems are considered an accurate archive for past climate and environment, other mineral deposits could provide

713	informative records on the setting and evolution of archaeological evidence. Applying a specific
714	methodology for their characterization is thus an efficient tool in improving rock art knowledge.
715	
716	Thanks to opal mineralization detection utilizing UV methodologies on cave walls, a discussion on its
717	formation and associated factors, such as climatic, hydrologic or geomorphologic conditions over time
718	can be started. Thus, the mineral form described as opal-A can provide elements on cave natural
719	history.
720	
721	Acknowledgements
722	
723	We would like to thank Frédérique Charlot, microscopist at CMTC (INPE, Grenoble).
724	Funding was provided by ANR LabCom SpecSolE, DRAC Occitanie, DRAC AURA
725	(Pigmentothèque project), French Ministry of Culture and University Savoie Mont Blanc.
726	
727	Conflict of interest disclosure
728	The authors declare they have no conflict of interest relating to the content of this article.
729	
730	Data, script and code availability
731	SEM data:
732	https://doi.org/10.6084/m9.figshare.16832593.v2
733	https://doi.org/10.6084/m9.figshare.16832557.v3
734	https://doi.org/10.6084/m9.figshare.16832452
735	https://doi.org/10.6084/m9.figshare.16832605
736	Single UV fluorescence measurement (raw data): <a href="https://doi.org/10.6084/m9.figshare.16837180.v1">https://doi.org/10.6084/m9.figshare.16837180.v1</a>
737	UV fluorescence cartography measurement (raw data):
738	https://doi.org/10.6084/m9.figshare.16837324.v1

739	UV fluorescence data processing (Matlab script): https://doi.org/10.6084/m9.figshare.16837405.v1
740	
741	Bibliography
742	
743	Amelin, Y., Back, M., 2006. Opal as a U-Pb geochronometer: search for a standard. Chemical
744	Geology 232, 67–86.
745	
746	Araya, J.A., Carneiro, R.L., Arévalo, C., Freer, J., Castillo, R. del P., 2017. Single pixel quantification
747	strategies using middle infrared hyperspectral imaging of lignocellulosic fibers and MCR-ALS
748	analysis. Microchemical Journal 134, 164–172.
749	
750	Aubert, M., Brumm, A., Taçon, P.S., 2017. The timing and nature of human colonization of Southeast
751	Asia in the late Pleistocene: A rock art perspective. Current Anthropology 58, S553–S566.
752	
753	Aubert, M., 2012. A review of rock art dating in the Kimberley, Western Australia. Journal of
754	Archaeological Science 39, 573–577.
755	
756	Aubert, M., O'Connor, S., McCulloch, M., Mortimer, G., Watchman, A., Richer-LaFlèche, M., 2007.
757	Uranium-series dating rock art in East Timor. Journal of Archaeological Science 34, 991–996.
758	
759	Aubert, M., Watchman, A., Arsenault, D., Gagnon, L., 2004. L'archéologie rupestre du Bouclier
760	canadien : Potentiel archéométrique. Canadian Journal of Archaeology/Journal Canadien
761	d'Archéologie 51–74.
762	
763	Barbarand, J., Nouet, J., 2020. Pétrographie et minéralogie des coralloïdes de la grotte au Points, in:
764	Monney J. (Dir.). Projet Datation Grottes Ornées: Rapport d'activité 2020. Grotte Aux Points

765 (Aiguèze). Rapport Non Publié., Ministère de La Culture, SRA Occitanie, Montpellier.

766

- 767 Bassel, L., 2017. Genèse de faciès calcitiques : mondmilch et coralloïdes. Étude multiphysique des
- 768 concrétions de la grotte laboratoire de Leye (Dordogne) (Thèse). Université Bordeaux Montaigne.

769

Bednarik, R.G., 1994. A taphonomy of palaeoart. Antiquity 68, 68–74.

771

- Boyko, V., Dovbeshko, G., Fesenko, O., Gorelik, V., Moiseyenko, V., Romanyuk, V., others, 2011.
- New optical properties of synthetic opals infiltrated by DNA. Molecular Crystals and Liquid Crystals
- 774 535 (1), 30-41.

775

- Castro, R.C., Ribeiro, D.S., Santos, J.L., Páscoa, R.N., 2021. Near infrared spectroscopy coupled to
- MCR-ALS for the identification and quantification of saffron adulterants: Application to complex
- 778 mixtures. Food Control 123, 107776.

779

- 780 Chalmin, E., Hoerlé, S.H., Reiche, I., 2018. Taphonomy on the Surface of the Rock Wall. Oxford
- 781 University Press.

782

- 783 Chanteraud, C., 2020. Matières colorantes et grottes ornées des gorges de l'Ardèche. Méthodes
- d'analyse des ressources et liens culturels au Paléolithique supérieur : application à la grotte aux Points
- 785 (Aiguèze, Gard, France) (Thèse). Université Savoie Mont Blanc.

786

- 787 Chanteraud, C., Chalmin, E., Hoerlé, S., Salomon, H., Monney, J., 2019. Relation entre les matières
- 788 colorantes issues des fouilles et des parois ornées. Méthodologie et première perspective comparative
- 789 à la Grotte aux Points (Aiguèze, Gard, France). Karstologia pp 1-12.

790

791 Chauviré, B., Rondeau, B., Mangold, N., 2017. Near infrared signature of opal and chalcedony as a

- proxy for their structure and formation conditions. European Journal of Mineralogy 29, 409–421.
- De Juan, A., Jaumot, J., Tauler, R., 2014. Multivariate Curve Resolution (MCR). Solving the mixture
   analysis problem. Analytical Methods 6, 4964–4976.
- 797 Curtis, N.J., Gascooke, J.R., Johnston, M.R., Pring, A., 2019. A review of the classification of opal

with reference to recent new localities. Minerals 9, 299.

796

798

799

803

806

810

813

- DeNeufville, J., Kasdan, A., Chimenti, R., 1981. Selective detection of uranium by laser-induced fluorescence: a potential remote-sensing technique. 1: Optical characteristics of uranyl geologic targets. Applied Optics 20, 1279–1296.
- Deschamps, E.B., Chauvet, J.M., Hillaire, C., 2018. La grotte aux Points d'Aiguèze : récits de découverte d'une ornementation pariétale. Karstologia 72, 13–14.
- Devès, G., Perroux, A.-S., Bacquart, T., Plaisir, C., Rose, J., Jaillet, S., Ghaleb, B., Ortega, R., Maire,
- 808 R., 2012. Chemical element imaging for speleothem geochemistry: Application to a uranium-bearing
- corallite with aragonite diagenesis to opal (Eastern Siberia, Russia). Chemical Geology 294, 190–202.
- Flörke, O., Graetsch, H., Röller, K., Martin, B., Wirth, R., 1991. Nomenclature of micro-and non-
- crystalline silica minerals. Neues Jahrbuch für Mineralogie, Abhandlungen 163, 19–42.
- Fritsch, E., Megaw, P.K., Spano, T.L., Chauviré, B., Rondeau, B., Gray, M., Hainschwang, T., Renfro,
- N., 2015. Green-luminescing hyalite opal from Zacatecas, Mexico. J. Gemmol 34, 490–508.
- Fritsch, E., Mihut, L., Baibarac, M., Baltog, I., Ostrooumov, M., Lefrant, S., Wery, J., 2001.
- 818 Luminescence of oxidized porous silicon: Surface-induced emissions from disordered silica micro-to

nanotextures. Journal of Applied Physics 90, 4777–4782. 819 820 821 Fritsch, E., Wéry, J., Jonusauskas, G., Faulques, E., 2003. Transient photoluminescence from highly 822 disordered silica-rich natural phases with and without nanostructures. Physics and chemistry of 823 minerals 30, 393–400. 824 825 Gaillou, E., Delaunay, A., Rondeau, B., Bouhnik-le-Coz, M., Fritsch, E., Cornen, G., Monnier, C., 2008. The geochemistry of gem opals as evidence of their origin. Ore Geology Reviews 34, 113–126. 826 827 828 Garcia-Guinea, J., Fernandez-Cortes, A., Alvarez-Gallego, M., García-Antón, E., Casas-Ruiz, M., 829 Blázquez-Pérez, D., Teijón, O., Cuezva, S., Correcher, V., Sanchez-Moral, S., 2013. Leaching of 830 uranyl-silica complexes from the host metapelite rock favoring high radon activity of subsoil air: case of Castañar cave (Spain). Journal of Radioanalytical and Nuclear Chemistry 298, 1567–1585. 831 832 833 Gorobets, B., Engoyan, S., Sidorenko, G., 1977. Investigation of uranium and uranium-containing 834 minerals by their luminescence spectra. Soviet Atomic Energy 42, 196–202. 835 836 Green, H., Gleadow, A., Finch, D., Hergt, J., Ouzman, S., 2017. Mineral deposition systems at rock art 837 sites, Kimberley, Northern Australia—Field observations. Journal of Archaeological Science: Reports 14, 340–352. 838 839 Huntley, J., 2012. Taphonomy or painT recipe: In situ portable x-ray fluorescence analysis of two 840 841 anthropomorphic motifs from the Woronora Plateau, New South Wales. Australian Archaeology 75, 842 78–94. 843 Huntley, J., Aubert, M., Ross, J., Brand, H. E., Morwood, M. J., 2015. One colour, (at least) two 844 minerals: a study of mulberry rock art pigment and a mulberry pigment 'quarry' from the Kimberley, 845

846	northern Australia. Archaeometry 57 (1), 77-99.
847	
848	Jaillet, S., Monney, J., 2018. Analyse 3D des volumes et remplissages souterrains de la grotte aux
849	Points au temps des fréquentations paléolithiques (Aiguèze, Gard). Karstologia 72, 27–36.
850	
851	Jaumot, J., de Juan, A., Tauler, R., 2015. MCR-ALS GUI 2.0: New features and applications.
852	Chemometrics and Intelligent Laboratory Systems 140, 1–12.
853	
854	Jaumot, J., Gargallo, R., de Juan, A., Tauler, R., 2005. A graphical user-friendly interface for MCR-
855	ALS: a new tool for multivariate curve resolution in MATLAB. Chemometrics and intelligent
856	laboratory systems 76, 101–110.
857	
858	Karkanas, P., Kyparissi-Apostolika, N., Bar-Yosef, O., Weiner, S., 1999. Mineral assemblages in
859	Theopetra, Greece: a framework for understanding diagenesis in a prehistoric cave. Journal of
860	Archaeological Science 26, 1171–1180.
861	
862	Kasdan, A., Chimenti, R.J.L., deNeufville, J.P., 1981. Selective detection of uranium by laser-induced
863	fluorescence: a potential remote-sensing technique. 2: Experimental assessment of the remote sensing
864	of uranyl geologic targets. Appl. Opt. 20, 1297–1307.
865	
866	Kinnunen, K.A., Ikonen, L., 1991. Opal, a new hydromorphic precipitate type from gravel deposits in
867	southern Finland. Bulletin of the Geological Society of Finland 63, 95–104.
868	
869	Kumar, K., 2018. Application of Genetic Algorithm (GA) Assisted Partial Least Square (PLS)
870	Analysis on Trilinear and Non-trilinear Fluorescence Data Sets to Quantify the Fluorophores in
871	Multifluorophoric Mixtures: Improving Quantification Accuracy of Fluorimetric Estimations of Dilute
872	Aqueous Mixtures. Journal of fluorescence 28, 589–596.

873	
874	Mas, S., de Juan, A., Tauler, R., Olivieri, A.C., Escandar, G.M., 2010. Application of chemometric
875	methods to environmental analysis of organic pollutants: a review. Talanta 80, 1052-1067.
876	
877	McGarry, S. F., Baker, A., 2000. Organic acid fluorescence: applications to speleothem
878	palaeoenvironmental reconstruction. Quaternary Science Reviews 19(11), 1087-1101.
879	
880	Monger, H.C., Kelly, E.F., 2002. Silica minerals. Soil mineralogy with environmental applications 7,
881	611–636.
882	
883	Monney, J., 2018. L'art pariétal paléolithique de la grotte aux Points d'Aiguèze: définition d'un
884	dispositif pariétal singulier et discussion de ses implications. Karstologia 72, 45-60.
885	
886	Monney, J., 2011. Projet Datation Grottes Ornées : Rapport d'activité 2011. Grotte aux Points
887	(Aiguèze). Rapport non publié, Ministère de la Culture, SRA Occitanie, Montpellier.
888	
889	Monney, J., Jaillet, S., 2019. Phases de fréquentations humaines, ornementation pariétale et processus
890	naturels : Mise en place d'un cadre chronologique pour la grotte aux Points d'Aiguèze. Karstologia 72
891	49–62.
892	
893	Morwood, M.J., Walsh, G.L., Watchman, A.L., 2010. AMS radiocarbon ages for beeswax and
894	charcoal pigments in north Kimberley rock art. Rock Art Research: The Journal of the Australian
895	Rock Art Research Association (AURA) 27 (1), 3–8.
896	
897	Neymark, L., Paces, J.B., 2013. Ion-probe U-Pb dating of authigenic and detrital opal from Neogene-
898	Quaternary alluvium. Earth and Planetary Science Letters 361, 98–109.

- 900 Neymark, L.A., Amelin, Y.V., Paces, J.B., 2000. 206Pb–230Th–234U–238U and 207Pb–235U
- 901 geochronology of Quaternary opal, Yucca Mountain, Nevada. Geochimica et Cosmochimica Acta 64,
- 902 2913–2928.

- Nomade, S., Genty, D., Sasco, R., Scao, V., Féruglio, V., Baffier, D., Guillou, H., Bourdier, C.,
- Valladas, H., Reigner, E., others, 2016. A 36,000-year-old volcanic eruption depicted in the Chauvet-
- Pont d'Arc Cave (Ardèche, France)? PloS one 11(1), e0146621.

907

- Northup, K.H., Diana, Lavoie, 2001. Geomicrobiology of caves: a review. Geomicrobiology journal
- 909 18, 199–222.

910

- Ospitali, F., Smith, D.C., Lorblanchet, M., 2006. Preliminary investigations by Raman microscopy of
- 912 prehistoric pigments in the wall-painted cave at Roucadour, Quercy, France. J. Raman Spectroscopy.
- 913 37, 1063–1071.

914

- 915 Oster, J.L., Kitajima, K., Valley, J.W., Rogers, B., Maher, K., 2017. An evaluation of paired δ18O and
- 916 (234U/238U) 0 in opal as a tool for paleoclimate reconstruction in semi-arid environments. Chemical
- 917 Geology 449, 236–252.

918

- 919 Othmane, G., Allard, T., Vercouter, T., Morin, G., Fayek, M., Calas, G., 2016. Luminescence of
- 920 uranium-bearing opals: Origin and use as a pH record. Chemical Geology 423, 1–6.

921

- Perrette, Y., Delannoy, J.-J., Bolvin, H., Cordonnier, M., Destombes, J.-L., Zhilinskaya, E.A.,
- Aboukais, A., 2000. Comparative study of a stalagmite sample by stratigraphy, laser induced
- 924 fluorescence spectroscopy, EPR spectrometry and reflectance imaging. Chemical Geology 162, 221–
- 925 243.

- Perrette, Y., Delannoy, J. J., Desmet, M., Lignier, V., Destombes, J. L., 2005. Speleothem organic
- matter content imaging. The use of a Fluorescence Index to characterise the maximum emission
- 929 wavelength. Chemical Geology 214 (3-4), 193-208.

- Pons-Branchu, E., Bourrillon, R., Conkey, M.W., Fontugne, M., Fritz, C., Gárate, D., Quiles, A.,
- Rivero, O., Sauvet, G., Tosello, G., 2014. Uranium-series dating of carbonate formations overlying
- Paleolithic art: interest and limitations. Bulletin de la Société préhistorique française 211–224.

934

- Quiers, M., Perrette, Y., Chalmin, E., Fanget, B., Poulenard, J., 2015. Geochemical mapping of
- organic carbon in stalagmites using liquid-phase and solid-phase fluorescence. Chemical Geology 411,
- 937 240-247.

938

- 939 Quiles, A., Fritz, C., Alcaide, M.Á.M., Pons-Branchu, E., Torti, J.L.S., Tosello, G., Valladas, H.,
- 2015. Chronologies croisées (C-14 et U/Th) pour l'étude de l'art préhistorique dans la grotte de Nerja:
- 941 méthodologie. Presented at the Sobre rocas y huesos: las sociedades prehistóricas y sus
- manifestaciones plásticas, UCO Press. Editorial de la Universidad de Córdoba, pp. 420–427.

943

- 944 Sadier, B., 2013. 3D et géomorphologie karstique : La grotte Chauvet et les cavités des Gorges de
- 945 l'Ardèche (Thèse). Université de Savoie, Le-Bourget-Du-Lac.

946

- 947 Savitzky, A., Golay, M.J.E., 1964. Smoothing and Differentiation of Data by Simplified Least
- 948 Squares Procedures. Analytical Chemistry. 36, 1627–1639.

- 950 Shao, Q.-F., Pons-Branchu, E., Zhu, Q.-P., Wang, W., Valladas, H., Fontugne, M., 2017. High
- 951 precision U/Th dating of the rock paintings at Mt. Huashan, Guangxi, southern China. Quaternary
- 952 Research 88, 1–13.

953	
954	Valladas, H., Pons-Branchu, E., Dumoulin, J.P., Quiles, A., Sanchidrián, J.L., Medina-Alcaide, M.Á.,
955	2017. U/Th and 14 C Crossdating of Parietal Calcite Deposits: Application to Nerja Cave (Andalusia,
956	Spain) and Future Perspectives. Radiocarbon 59, 1955–1967.
957	
958	Van Beynen, P., Bourbonniere, R., Ford, D., Schwarcz, H., 2001. Causes of colour and fluorescence in
959	speleothems. Chemical Geology 175 (3-4), 319-341.
960	
961	Watchman, A., 2000. A review of the history of dating rock varnishes. Earth-Science Reviews 49,
962	261–277.
963	
964	Watchman, A., 1990. What are silica skins and how are they important in rock art conservation?
965	Australian Aboriginal Studies 1, 21–29.
966	
967	Zhang, X., Tauler, R., 2013. Application of multivariate curve resolution alternating least squares
968	(MCR-ALS) to remote sensing hyperspectral imaging. Analytica chimica acta 762, 25–38.
969	
970	Zielinski, R.A., 1982. Uraniferous opal, Virgin Valley, Nevada: Conditions of formation and
971	implications for uranium exploration. Journal of Geochemical Exploration 16, 197–216.
972	
973	Zielinski, R.A., 1980. Uranium in secondary silica; a possible exploration guide. Economic Geology
97/	75 592_602