

Influence of the isothermally formed oxide thickness and of the cooling rate on the oxide scale spallation behaviour of chromia-forming Ni-based alloys; thermogravimetry and post-mortem study

Elodie Conrath, Patrice Berthod

▶ To cite this version:

Elodie Conrath, Patrice Berthod. Influence of the isothermally formed oxide thickness and of the cooling rate on the oxide scale spallation behaviour of chromia-forming Ni-based alloys; thermogravimetry and post-mortem study. Eurocorr 2015, Sep 2015, Graz, Austria. hal-03391596

HAL Id: hal-03391596 https://hal.science/hal-03391596

Submitted on 21 Oct 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Faculté des Sciences et

Technologies

Influence of the isothermally formed oxide thickness and of the cooling rate on the oxide scale spallation behaviour of chromia-forming Ni-based alloys; thermogravimetry and post-mortem study



Elodie Conrath and Patrice Berthod


Institut Jean Lamour, Faculty of Sciences and Technologies, University of Lorraine, BP 70239, Bd des Aiguillettes, 54506 Vandoeuvre-lès-Nancy, France


patrice.berthod@univ-lorraine.fr

In addition to the isothermal oxidation rate one must often take into account the resistance of the alloys to oxide spallation when temperature varies to more completely characterize their behaviour in high temperature oxidation [1]. The severity of this phenomenon may be dependent on a lot of parameters as the type of alloy, the minor elements present in its chemical composition, the cooling rate and the different characteristics of the external oxide scales, notably: average thickness, simple or complex constitution, grain size, defects in the scales, presence of water vapour [2,3]... This is thus rather difficult for a given commercial alloy to clearly separate the effects of the too numerous involved factors.


In this work we have focused the study on a ternary alloy, a cast Ni-25Cr-0.5C type which usually behaves as chromia-forming thanks to its high Cr content and the interdendritic chromium carbides network facilitating Cr diffusion, to simplify the constitution of the obtained oxide. Many oxidation tests were undertaken in dry synthetic air with various values of the isothermal stage temperature, of its duration and of the post-isothermal cooling rate. The cooling parts of the obtained mass gain curves were analysed to specify the temperature of spallation start or the temperature decrease before spallation started and the final mass variation (sometimes negative in case of severe spallation), while the percentage of surface coverage of the oxidized samples by the remaining scales was measured by image analysis.

Thermogravimetry curves plotted as mass gain versus temperature





Effect of the cooling rate





| C 1200 |
|--------|
| 817 |
| 2.2 |
| -0.5 |
| 2.8 |
| 13. |
| |
| |

| 1200°C | 46 hours | 114 hours | |
|----------------------------------|----------|-----------|-------------------|
| -5°C/min | | | 46h 1 |
| T spall.start (°C) | 817 | 901 | T spall st |
| mass before spall. (mg/cm²) | 2.29 | 2.79 | mass bef (mg/ |
| final mass (mg/cm²) | -0.59 | -4.17 | final (mg/ |
| mass lost by spall. (mg/cm²) | 2.88 | 6.96 | mass lost (mg/ |
| Fraction of denuded surf. (%) | 13.8 | 15.0 | Fracti denuded |
| 1 cm | | | 1 c |

| 46h 1200°C | -5°C/min | -10°C/min | -20°C/min |
|----------------------------------|----------|-----------|-----------|
| T spall start (°C) | 817 | 885 | 852 |
| mass before spall. (mg/cm²) | 2.29 | 2.36 | 2.40 |
| final mass (mg/cm²) | -0.59 | -3.07 | -3.69 |
| mass lost by spall. (mg/cm²) | 2.88 | 5.43 | 6.09 |
| Fraction of denuded surf. (%) | 13.8 | 14.4 | 17.8 |
| 1 cm | 197 | (23) | |

Plotting the mass gain, not versus time as usually done for identifying the type of oxidation and for determining the kinetic constants, but versus temperature, allow evidencing the eventual oxide scale spallation at cooling and accessing several parameters characterizing this phenomenon. Here this was the temperature at which spallation began and the amount of lost mass until return to room temperature. The mass gain files recorded during six thermogravimetry tests, carried out for the same alloy oxidized in a same atmosphere, were thus corrected from the air buoyancy variations then plotted versus temperature, in order to specify the effect of several parameters on the behaviour in spallation.

Besides the expected effect of a more or less fast cooling rate (right hand) it appears that the stage temperature (left hand) and the isothermal stage duration (middle) also influences oxide spallation at cooling. The higher the stage temperature or the longer the stage duration is, the higher are the spallation start temperature, the mass loss by spallation and the final surface fraction of denuded surface. Thus these effect are similar to faster cooling rate.

As this is also observed for not more complex Ni-based, Fe-based and Co-based cast alloys [4], the oxide thickness, governed by both the temperature and the duration of the isothermal stage, appears as being a parameter as important as the cooling rate itself.

- Young, D., "High Temperature Oxidation and Corrosion of Metals", Elsevier Corrosion Series, Amsterdam (2008)
- Berthod, P., Aranda, L., Mathieu ST., Vilasi, M., "Influence of Water Vapour on the Rate of Oxidation of a N-25wt.%Cr Alloy at High Temperature", Oxidation of Metals, Vol. 79 (2013), pp. 517-527
- Aranda, L., Schweitzer, T., Mouton, L., Mathieu, SA., Rouer, O., Villeger, P., Berthod, P., Conrath, E., "Kinetic and metallographic study of oxidation at high temperature of cast N 25Cr alloy in water vapour rich air", Materials at High Temperature, Vol. 32 (2015), pp. 530-538. [3
- [4] Bernold, P., Conrath, E., "Thermogravimetry and post-mortem study of the oxide scale spallation behavior during post-isothermal oxidation cooling of Cr-rich (Co, Ni or Fe)-based cast alloys with various Hf contents", oral presentation at Eurocorr 2015, Graz.