

Consistency between air and biological monitoring for assessing polycyclic aromatic hydrocarbon exposure and cancer risk of workers

Mélodie Valière, Pascal Petit, Renaud Persoons, Christine Demeilliers, Anne

Maître

► To cite this version:

Mélodie Valière, Pascal Petit, Renaud Persoons, Christine Demeilliers, Anne Maître. Consistency between air and biological monitoring for assessing polycyclic aromatic hydrocarbon exposure and cancer risk of workers. Environmental Research, 2022, 207, pp.112268. 10.1016/j.envres.2021.112268 . hal-03400361

HAL Id: hal-03400361 https://hal.science/hal-03400361

Submitted on 22 Jul 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Version of Record: https://www.sciencedirect.com/science/article/pii/S0013935121015693 Manuscript_f15231828241b6ca32078a1cc279ea6e

1 Consistency between air and biological monitoring for assessing polycyclic

2 aromatic hydrocarbon exposure and cancer risk of workers

3

4 Mélodie Valière, Pascal Petit, Renaud Persoons, Christine Demeilliers, Anne Maître*

- 5 Univ. Grenoble Alpes, CNRS, Grenoble INP, CHU Grenoble Alpes, TIMC laboratory (UMR CNRS
- 6 5525), EPSP Team, 38000 Grenoble, France
- 7
- 8 * Corresponding author at Laboratoire TIMC, Equipe EPSP, UFR de Médecine de Grenoble, Domaine
- 9 de La Merci, 38706 La Tronche Cedex, France. Tel.: + 33 (0)4 76 63 75 03
- 10 *E-mail address:* anne.maitre@univ-grenoble-alpes.fr (Anne Maître)

11 Abstract

Background: Atmospheric levels of polycyclic aromatic hydrocarbons (PAHs) have been monitored in many companies since 1940. Because of the use of respiratory protective equipment (RPE) and cutaneous absorption, the measurement of urinary 1-hydroxypyrene (1-OHP), metabolite of pyrene (Pyr), and, more recently, 3-hydroxybenzo[a]pyrene (3-OHBaP), metabolite of benzo[a]pyrene (BaP), has been carried out to assess PAH exposure and estimate health risks.

17 *Objectives*: This study aimed to investigate the agreement between 523 air and biological levels recorded
18 in the Exporisq-HAP database by taking into account the effectiveness of RPE.

Methods: The agreement/consistency between 523 air and biological exposure levels was assessed by estimating and comparing the probability of exceeding French limit values (LVs) for both BaP and 3-OHBaP and ACGIH LV for 1-OHP, respectively. PAH airborne levels (wPAHs) were weighted by an assigned protection factor (APF) depending on the type of mask worn by workers, while urinary 1-OHP concentrations were adjusted with the wBaP/wPyr ratio of each industrial sector (wadj1-OHP).

Results: Within occupational groups, there was an overall agreement between airborne PAH levels and urinary biomarker concentrations. A clear dichotomy was found between "petroleum-derived" and "coal-derived" groups, with much higher exposures in the latest group despite the use of RPEs by twothirds of the workers. The type of RPE varied from one plant to another, which underlines the importance of taking into account their effectiveness. The analysis of urinary 3-OHBaP was not relevant for low PAH exposure levels. In addition, this biomarker underdiagnosed the exceedance of LV relative to BaP levels for 6% of "coal-derived" groups.

31 *Conclusions*: The use of urinary wadj1-OHP seemed to be more protective to assess the exceedance of 32 LVs than those of urinary 3-OHBaP and air wBaP, but adjustment of the 1-OHP concentration by the 33 BaP/Pyr ratio requires air sampling due to highly variable ratios observed in the studied occupational 34 groups.

35

36 Keywords

Polycyclic aromatic hydrocarbons; exposure assessment; occupational limit values of benzo[a]pyrene;
1-OHP; 3-OHB[a]P; health risk; respiratory mask

39 1. Introduction

40 Polycyclic aromatic hydrocarbons (PAHs) are a family of ubiquitous compounds resulting from the 41 incomplete combustion of fossil fuels or organic matter. In addition to environmental exposure to tobacco smoke, vehicle engine exhaust and district heating emissions, PAH exposure can be encountered 42 in many occupational contexts, where they are mainly emitted as byproducts derived from coal or 43 44 petroleum distillation. Millions of workers are exposed to PAHs, such as road pavers, aluminum, silicon, 45 or electrode production workers, but exposures differ greatly from one industrial sector to another (46 IARC, 2010; Marczynski et al., 2009). The number of French workers exposed to PAHs was estimated 47 to be between 2 and 4 million (Arnaudo et al., 2012; Petit et al., 2020). PAHs are associated with the 48 occurrence of different types of cancers, among which respiratory cancers are the most common (IARC, 49 2010). In France, for the year 2000, it was estimated that nearly 3% of lung cancers in men were 50 attributable to occupational PAH exposure (Boffetta et al., 2010). While numerous particulate PAHs are 51 classified as probably carcinogenic to humans by the European Chemicals Agency (ECHA, 2016) and 52 possibly carcinogenic by the International Agency for Research on Cancer (IARC), benzo[a]pyrene 53 (BaP) is the only PAH classified as a known human carcinogen (IARC, 2010).

54 To reduce the incidence of respiratory cancers, atmospheric PAH concentrations have been monitored 55 in many companies since 1940 to ensure that available occupational exposure limit values (OELs) are 56 not exceeded. However, discrepancies between OELs exist depending on the country and organization 57 (SCOEL, 2016). Assessment of airborne levels alone may not always provide a complete picture of exposure because many industries rely on the use of respiratory protective equipment (RPE) to control 58 59 exposure (Unwin et al., 2006). Very few studies take into account their effectiveness for assessing PAH 60 exposure and estimating health risk. In addition, although workers are mainly exposed to PAHs via 61 inhalation, skin contamination is another important PAH absorption pathway (Bourgart et al., 2019; 62 Fustinoni et al., 2010).

Biological monitoring is a more recent approach that takes into account all uptake pathways and the use
of personal protective equipment. Because pyrene (Pyr) (both gaseous and particulate forms) is one of
the most abundant PAHs in mixtures, monitoring of its urinary metabolite, 1-hydroxypyrene (1-OHP),
was developed first and became the gold standard for estimating internal PAH exposure over the past

67 30 years (Jongeneleen, 2001; SCOEL, 2016). More recently, the analysis of 3-hydroxybenzo[a]pyrene (3-OHBaP), an urinary metabolite of BaP, has been developed but requires a more sensitive analytical 68 69 technique than 1-OHP due to levels that are 1,000 to 10,000 times lower (Barbeau et al., 2011). Various 70 biological limit values (BLVs) or guidance values (GVs) have been proposed for these two biomarkers 71 by several organizations (ACGIH, 2017; Nikolova-Pavageau et al, 2018). In addition, to account for 72 different relative proportions of Pyr and BaP in PAH mixtures encountered in various industrial sectors, 73 it was proposed to adjust the 1-OHP BLV for different Pyr/BaP ratios in a specific exposure context 74 (ACGIH, 2017). Indeed, the BEI published by ACGIH considered a Pyr/BaP ratio of 2.5 that was 75 observed in coke oven plants but should be adjusted to other industrial environments. While air and 76 biological monitoring approaches are complementary, many questions remain unanswered regarding 77 their ability to assess the exceedance of existing OELs or BLVs to estimate PAH health risk.

78 The objective of this study was to investigate the consistency between biological and airborne 79 monitoring by taking into account the effectiveness of respiratory protection.

80

81 **2.** Materials and methods

82 2.1 Data selection

Since 1998, the Exporisq-HAP (E-HAP) database has prospectively recorded individual atmospheric
PAH levels and urinary metabolite concentrations of workers exposed to PAHs. For each worker, data
on age, smoking habits, job activities and RPE were collected. This database has been the subject of
several previous publications (Maître et al., 2018; Petit et al., 2017).

In the present study, only individual airborne and urine samples collected on the same working day were selected. These two associated samples are referred to as "air *vs.* biocouple" or simply "couple" throughout this manuscript. Only couples with the analysis of urinary 1-OHP measured at the end of the work week-end of the shift (EWES) or of urinary 3-OHBaP at EWES plus sixteen hours (EWES+16) were considered. Occupational activities outside of France or before the year 2000 (no gaseous PAH samples), samples with a short sampling duration < 2 h, samples with urinary creatinine outside the tolerable limits (< 0.3 g. L⁻¹ or > 3 g. L⁻¹), or samples with coding errors were excluded.

- A total of 1,433 air *vs.* biocouples collected in 12 industrial sectors were found in the E-HAP database (Fig. 1). Overall, 910 couples were excluded, mainly (78%) couples that were not sampled on the days and moments of interest (Fig. 1). A total of 523 couples sampled in 98 plants between 2006 and 2019 were included in the present study. Among them, 508 air *vs.* biocouples included a measure of 1-OHP (BaP *vs.* 1-OHP couples) and 188 of 3-OHBaP (BaP *vs.* 3-OHBaP couples). For 173 subjects, there were measures of BaP, 1-OHP and 3-OHBaP.
- 100
- 101 Fig.1 here
- 102



104

105 **Fig 1:** Flow-chart of the data selection step

106 E-HAP: Exporisq-HAP database, EWES: end of work week - end of shift, EWES+16: end of work week 107 - end of shift plus 16 hours, Pyr: pyrene, BaP: benzo[a]pyrene, APF: assigned protection factor 108 depending on the type of mask worn by the worker, couples: association of a PAH air sample with a 109 urinary PAH metabolite sample performed in parallel on the same day for a given worker (BaP vs. 1-110 OHP couples: association of a BaP sample and an EWES 1-OHP sample, BaP vs. 3-OHBaP couples: 111 association of a BaP sample and an EWES+16 3-OHBaP sample, <u>BaP vs. adj1-OHP couples</u>: association of a BaP sample and an EWES 1-OHP sample adjusted for real $\left[\frac{tPyr}{BaP}\right]$ ratios, w<u>BaP vs. wadj</u>1-OHP couples: 112 association of a BaP sample weighted by an APF and an EWES 1-OHP sample adjusted by the weighted 113 wBaP/wpyr ratio, wBaP vs. 3-OHBaP couples: association of a BaP sample weighted by an APF and an 114 115 EWES+16 3-OHBaP sample).

116 **2.2** Urinary biomarker concentrations and atmospheric PAH levels

117 The urinary 1-OHP and 3-OHBaP concentrations were measured by liquid chromatography with 118 fluorescence detection (LC-Fluo) since 2000 and 2007, respectively (Barbeau *et al.*, 2011). The limits 119 of quantification (LoQ) ranged from 0.02 μ g. L⁻¹ to 0.1 μ g. L⁻¹ for 1-OHP and from 0.05 ng. L⁻¹ to 0.2 120 ng. L⁻¹ for 3-OHBaP. Values below the LoQ were replaced with random values ranging from 0 121 (excluded) to the LoQ.

122 Regarding airborne levels, gaseous and particulate PAHs were collected using a polypropylene cassette 123 holding a 37-mm-diameter quartz filter connected in series to an XAD2 tube according to the NF X43-124 294 standard, which is recommended in France (AFNOR 1995). PAHs were measured by LC-Fluo. The LoQ for BaP, gaseous pyrene (gPyr) and particulate pyrene (pPyr) was 0.05 ng.sample⁻¹. The sum of 125 126 pPyr and gPyr, corresponding to total pyrene (tPyr), was calculated, as well as the tPyr/BaP ratio. The 127 toxic equivalent BaP (BaPteq6) was calculated using PAHs classified as carcinogenic 1A or 1B by the 128 EU and associated with their toxic equivalence factors (TEFs). A total of six particulate PAHs were 129 included in the BaPteq6 calculation, namely, BaP, dibenzo[a,h]anthracene (DahA), benzo[a]anthracene 130 (BaA), benzo[b]fluoranthene (Bbf), benzo[k]fluoranthene (BkF), and chrysene (Chr). The French 131 INERIS recommended TEFs were used for the BaPteq6 calculation (Doornaert et al., 2003) (Eq. 1). $BaPteq6 = \sum_{i=1}^{n} (Ci \times TEFi) = [BaP] \times 1 + [DahA] \times 1 + 0.1 \times ([BaA] + [BbF] + [BkF]) + [BkF]) + [BkF] + [BkF]$ 132 133 $[Chr] \times 0.01$ [1]

134 where *C* is the concentration of a given PAH congener designated by the letter *i*.

135

136 2.3 Occupational groups

Monitoring campaigns were performed in several industrial sectors using either products derived from
 coal, from petroleum or from products emitting combustion fume. Sectors were subdivided into similar
 activity groups according to the job description and workplace studies.

The distribution of airborne PAH levels and urinary biomarker concentrations were assessed in each of these occupational groups (industrial sectors and job activities) that included at least five air *vs*. biocouples. Following the same approach as in a previous work (Petit *et al.*, 2017), the geometric standard deviations (GSDs) of atmospheric levels and urinary concentrations were determined to assess 144 the exposure variability within occupational groups. The groups were considered similar exposure

145 groups (SEGs) for a given PAH or biomarker if its GSD concentration was ≤ 3 .

146

147 **2.4** Respiratory protective equipment

148 RPEs were classified into four groups depending on the nature of the filtering media (FFP2/3 or P2/3 149 particle filtering masks and A/ABEK gas masks with cartridges). Table 1 presents the mask group, with 150 the mask and cartridge type considered for each group as well as the considered efficiency against PAHs. 151

152 **Table 1**: List of mask groups

Mask group	Mask and cartridge type	Efficiency
Gas masks	FFR with A or ABEK cartridge	gPAH
	EHPR with A or ABEK cartridge	gPAH
Particulate masks	FFR with FFP2 or FFP3 cartridge	рРАН
	EHPR with P2 or P3 cartridge	рРАН
Combined masks	FFR with A or ABEK cartridge and FFP2 or FFP3 cartridge	gPAH and pPAH
	EHPR with A or ABEK cartridge and P2 or P3 cartridge	gPAH and pPAH
SAR	Supplied-air respirator	gPAH and pPAH

153 Note: EHPR: elastomeric half face piece respirators, FFR: face piece respirator, SAR: supplied-air

154 respirator.

155

156	To take into account the efficiency of RPEs worn by workers, airborne PAH levels were weighted by
157	an APF, as recommended by the French Department of Labor and the French National Institute for
158	Research and Safety (INRS) (Ministère du Travail, 2009). When information about RPE was missing,
159	air vs. biocouples were excluded from the analysis to calculate weighted PAH levels. The weighted
160	levels are indicated by a "w" preceding the considered PAH throughout this manuscript as follows:
161	wBaP, wPyr
162	The APF used for weighting PAH levels was presented in Table 2. For instance, for workers wearing a
163	"particulate mask", an APF of 10 was assigned to particulate PAHs and an APF of 1 to gaseous PAHs.
164	Thus, the levels of particulate PAHs were divided by 10 while those of gaseous PAHs remained the
165	same.

166

167 **Table 2**: Assigned protection factor used for the weighted level calculation depending on the type of

168 mask worn

Type of mask worn	APF for pPAHs	APF for gPAHs	pPAH levels	gPAH levels
No mask	1	1	Unchanged	Unchanged
Gas mask	1	10	Unchanged	Divided by 10
Particulate mask	10	1	Divided by 10	Unchanged
Combined mask	10	10	Divided by 10	Divided by 10
SAR	250	250	Divided by 250	Divided by 250

169 Note: APF: assigned protection factor, gPAHs: gaseous PAHs, pPAHs: particulate PAHs, SAR:
170 supplied-air respirator.

171

172 **2.5** Assessing health risk within occupational groups

To assess health risk within occupational groups, the CEN 689 recommendations (AFNOR, 2019) were 173 followed using the exceedance fraction of limit values (LVs) (i.e. OEL or BLV). According to this 174 175 standard, health risk is considered high if more than 5% of the concentrations of the group exceed the LV (corresponding to the 95th percentile of the concentration distribution equal to or higher than the 176 LV). By contrast, the risk is considered low when less than 0.1% of the concentrations exceed the LV 177 (corresponding to the 99.9th percentile equal to or higher than the LV). When the LV is located between 178 the 95th and 99.9th percentiles of the concentrations, health risk conclusions are impossible to 179 180 determine/reach.

181

For BaP, two different OELs were considered: the OEL recommended by the French National Health Insurance Fund (OEL_{CNAM}) set at 150 ng.m⁻³ (Nikolova-Pavageau et al, 2018) and the OEL used in several European countries (Sweden, Switzerland, Poland) (OEL_{EU}) set at 2000 ng.m⁻³ (SCOEL, 2016). These OELs were applied to the BaP, _wBaP (BaP levels weighted by an APF) and BaPteq6 concentrations. To our knowledge, no OEL has been published for pyrene.

187

For 1-OHP, the BLV recommended by the ACGIH (BLV_A) set at 2.5 μ g/L (ACGIH, 2017) adjusted to the airborne tPyr/BaP ratio was used. However, instead of comparing 1-OHP levels to several *BLV_A* 190 (based on their respective tPyr/BaP ratios), it was more convenient to use a BLV_A of 1 µg. L⁻¹ and 191 compare it with 1-OHP levels adjusted by the BaP/tPyr ratio ($_{adj}$ 1-OHP) as follows (Eq.2):

192
$$_{adj}10HP = 10HP \times \left[\frac{BaP}{tPyr}\right]$$
 [2]

193

To determine the usefulness of integrating APF for PAH exposure, the analyses were also performed with weighted airborne levels, which means that the weighted $_{adj}1$ -OHP ($_{wadj}1$ -OHP) was calculated by adjusting the 1-OHP concentration to the weighted $_{w}BaP/_{w}tPyr$ ratio of the air *vs.* biocouple and comparing it to a stated weighted BLV_A of 1 µg. L⁻¹ (Eq.3), as follows:

198
$$_{wadj}10HP = 10HP \times \left[\frac{_{wBaP}}{_{wtPyr}}\right] = 10HP \times \left[\frac{_{wBaP}}{_{wgPyr+wpPyr}}\right]$$
[3]

199

For 3-OHBaP, the French guidance value proposed by INRS (BLV_{INRS}) set at 0.97 ng.g⁻¹ creatinine (equivalent to 0.40 nmol.mol⁻¹ creatinine) was considered (Nikolova-Pavageau et al, 2018). This reference concentration, measured at the beginning of the shift on the 5th day of exposure, is assumed to result from atmospheric BaP exposure of 150 ng.m⁻³ (OEL_{CNAM}) over the work week.

204

For the analysis using an APF to calculate weighted BaP levels (wBaP) and weighted adj1-OHP (wadj1-OHP) concentrations, 497 wBaP *vs.* wadj1-OHP couples were included, and 181 wBaP *vs.* 3-OHBaP couples (corresponding to 166 couples with a measure of both biomarkers) were included (Fig. 1).

208

209 2.6 Consistency of BaP OEL_{CNAM} vs. BLV exceedances for couples

The consistency of airborne OEL_{CNAM} and urinary BLV exceedances was analyzed on the scale of the air *vs.* biocouples. A total of 4 situations were considered: an exceedance of the OEL_{CNAM} alone, an exceedance of the BLV alone, an exceedance of both LVs or no exceedance at all. The last two situations corresponded to consistent conclusions regarding LV exceedances.

214 For BaP vs. adj1-OHP couples, the OEL_{CNAM} exceedance of the BaP level was compared to the BLV_A

215 exceedance of _{adj}1-OHP levels. The same analysis was conducted with weighted levels. For BaP vs. 3-

OHBaP couples, the OEL_{CNAM} exceedance of BaP and _wBaP levels was compared to the BLV_{INRS}
exceedance of 3-OHBaP.

218

219 **2.7** Software

Analyses were performed using R version 4.1.1 for Windows 10[®].

221

222 3. **Results**

223 **3.1** Air vs. biocouple characteristics

Among 523 couples, 218 workers (42%) were involved in 15 plants of 6 "coal-derived" sectors, namely, coke production, silicon production, aluminum production, carbon product manufacturing, steel foundry and railroad maintenance. The remaining 305 workers from 83 plants were exposed to petroleum distillates or combustion fumes in 4 "petroleum-derived" sectors, namely, combustion processes, the handling of lubricating oils, engine exhaust emissions, and bitumen (Table 3). Combustion processes were included in the "petroleum-derived" sector due to the similarly relatively low PAH exposure levels that are usually found in these sectors.

Most workers (99%) were men with a median age of 41 years. The proportion of smokers was the same in the "coal-derived" and "petroleum-derived" sectors, with an average of 37% (Table 3). Data for smoking habits were missing for only 2% of the population.

234 The efficiency of RPE against gaseous and particulate PAHs varied greatly from one sector to another. 235 There were only 2% missing mask data, with the exception of steel foundries, where data were missing 236 for 44% of workers (Table 3). More than 50% of the workers involved in "coal-derived" sectors were wearing an effective RPE against particulate PAHs ("particulate mask") or "combined mask"). Nearly 237 as many were wearing effective RPE against gaseous PAHs ("gaseous mask" or "combined mask"), 238 239 while 26% did not wear any RPE. These respective proportions were 9%, 6% and 86% in "petroleum-240 derived" sectors; however, there were two exceptions. In railroad maintenance, no worker wore a RPE, and for the combustion processes, approximately 40% of the workers wore a "particulate mask". Only 241 6 workers involved in silicon production or carbon product manufacturing wore a SAR. 242

The 188 BaP *vs.* 3-OHBaP couples represented only one-third of the 523 air *vs.* biocouples, but their overall characteristics were the same (data not shown). For these couples, no data were available for coke production. In addition, none of the workers wore a "gas mask", whereas the "particulate mask" proportion was slightly greater (21% of workers), mainly due to aluminum production, for which all workers wore such masks. Similar proportions of data were missing among these couples regarding smoking habits (2%) and the type of mask worn (4% corresponding to the steel foundry).

- 249 Table 3: Distribution of air vs. biocouples for each occupational sector depending on smoking status
- 250 and mask type

	Number	Number	Number of			Mask type			
Industrial sectors	of plants	of workers	smokers	None	Ρ	G	Combined	Unknown	
"Coal-derived" sectors	15	218 (42%)	81 (37%)	56 (26%)	59 (27%)	39 (18%)	57 (26%)	7 (3%)	
Coke production	1	40	17 (42%)	12 (30%)	1 (2%)	27 (68%)	0	0	
Silicon production	5	67	24 (36%)	11 (16%)	14 (21%)	0	42 (63%)	0	
Aluminum production	2	32	18 (56%)	2 (6%)	13 (41%)	12 (38%)	5 (16%)	0	
Carbon product manufacturing	4	57	11 (19%)	25 (44%)	22 (39%)	0	10 (18%)	0	
Railroad maintenance	1	6	2 (33%)	6 (100%)	0	0	0	0	
Steel foundries	2	16	9 (56%)	0	9 (56%)	0	0	7 (44%)	
"Petroleum-derived" sectors	83	305 (58%)	112 (37%)	263 (86%)	20 (7%)	11 (4%)	7 (2%)	4 (1%)	
Combustion processes	8	17	4 (24%)	7 (41%)	5 (29%)	3 (18%)	2 (12%)	0	
Handling of lubricating oils	5	44	12 (27%)	40 (91%)	1 (2%)	0	0	3 (7%)	
Engine exhaust emissions	43	117	36 (31%)	89 (76%)	14 (12%)	8 (7%)	5 (4%)	1 (1%)	
Bitumen	27	127	60 (47%)	127 (100%)	0	0	0	0	
TOTAL	98	523	193 (37%)	319 (61%)	79 (15%)	50 (10%)	64 (12%)	11 (2%)	

Note: air vs biocouples: association of an air sample and a urinary sample performed on the same day, 251 252 at the end of shift (for 1-OHP analysis) or at the end of shift plus 16 hours (for 3-OHBaP analysis). P: "particulate mask", G: "gaseous mask", combined: association of a gaseous cartridge and particulate 253

filter (or air-supplied respirator), unknown: information not available. 254

255

3.2 Comparison of airborne PAH levels and urinary biomarker concentrations within 256 257 occupational groups

- 258
- 259 3.2.1 BaP vs. 1-OHP couples

260 Among the "coal-derived" sectors, 4 to 6 different job activities were identified for each sector (Table 261 4), with the exception of the steel foundry where all workers were heating attendant masons, and the railroad maintenance consisting of 6 workers replacing creosote-impregnated wood in railroad ties. In 262 the "petroleum-derived" sectors, there was one single job activity (chimney sweeper) in combustion 263 processes and 9 job activities in engine exhaust emissions. 264

265 For the 508 BaP vs. 1-OHP couples, gPyr levels were rarely below the LoQ, with the exception of combustion processes (29%) and vehicle drivers (73%). Nearly 20% of the pPyr and BaP levels were 266

below the LoQ in the "petroleum-derived" sectors, while their levels were always quantifiable in the"coal-derived" sectors.

269 The levels of particulate PAHs (pPyr and BaP) were approximately 300 times lower in "petroleum-270 derived" sectors (BaP geometric mean (GM) of 0.5 ng.m^{-3}) than in "coal-derived" sectors (BaP GM = 271 186 ng.m⁻³), while the levels of gPyr were only 20 times lower. Among "petroleum-derived" sectors, 272 combustion processes and some activities of engine exhaust emissions (working in closed environments 273 and waste management drivers) stood out with slightly higher levels of pPyr and BaP. The highest PAH 274 levels were measured in coke production ($GM = 102 \text{ ng.m}^{-3}$, 1370 ng.m^{-3} and 1500 ng.m^{-3} for gPyr, pPyr and BaP, respectively), and a maximum of BaP GM at 2320 ng.m⁻³ was found for furnace battery 275 276 cleaning-up.

The median tPyr/BaP ratio was 4 times higher in "petroleum-derived" sectors than in "coal-derived" sectors. Indeed, this ratio was above 2.5 in most "petroleum-derived" job activities and even above 20 in bitumen, whereas it was mainly below 2.5 in "coal-derived" sectors, with the exception of steel foundry and railroad maintenance, where it exceeded a value of 8.

281 For 1-OHP, the only values below the LoQ were found for 6 workers involved in bitumen roofing. The 282 GM of 1-OHP concentrations was 9 times lower in "petroleum-derived" sectors than in "coal-derived" sectors, with GM of 0.08 and 0.70 µmol.mol⁻¹ creatinine, respectively. The highest levels were once 283 284 again found for the activity of furnace battery cleaning-up in coke production (GM = $3.92 \,\mu \text{mol.mol}^{-1}$ 285 creatinine). Some activities were associated with high levels of 1-OHP considering the corresponding 286 airborne concentrations, such as anode production in aluminum production or raw carbon extrusion in 287 carbon product manufacturing. Workers involved in railroad maintenance had particularly high levels of 1-OHP (GM = 1.52μ mol.mol⁻¹ creatinine) in parallel with relatively high levels of both gPyr (GM = 288 289 42 ng.m⁻³) and pPyr (GM = 31 ng.m⁻³), while BaP levels remained very low (GM = 8.4 ng.m^{-3}).

Table 4: Airborne BaP levels at the end of week and urinary 1-OHP concentrations on the same day at the end of shift for multiple occupational groups

Occupational groups							Airborne PAH											Urinary 1- OHP		
Industrial sectors Job activities	N	GM	<u>gPyr</u> 95th <i>(ng.m⁻³)</i>	GSD	<loq (%)</loq 	GM	<u>pPyr</u> 95th <i>(ng.m⁻³)</i>	GSD	<loq (%)</loq 	GM	<u>BaP</u> 95th (ng.m ⁻³)	GSD	<loq (%)</loq 	Med	<u>tPyr/BaP</u> 5th	95th	GM	95th (µmol.mol¹)	GSD	<loq (%)</loq
"Coal-derived" sectors	209	31	675	7.1	0%	272	17 290	8.8	0%	186	6 780	9.3	0%	1.5	0.7	10	0.70	4.83	3.3	0%
Coke production	40	102	527	3.7	0%	1 370	11 870	4.5	0%	1 500	9 060	3.4	0%	1.1	0.6	1.8	1.42	4.87	2.3	0%
Coke pusher	6	107	319	5.8	0%	1 230	3 910	7	0%	1 290	3 520	5.7	0%	1.1	0.8	1.3	0.79	1.38	1.7	0%
Furnace door settings	5	34	174	4	0%	769	3 990	6.1	0%	851	3 070	4.4	0%	1.1	0.7	1.3	0.83	2.29	2	0%
Furnace battery cleaning-up	7	195	341	1.7	0%	2 310	4 270	1.6	0%	2 320	4 920	1.6	0%	1.1	0.7	1.5	3.92	9.51	1.9	0%
Watchman	6	185	594	3.1	0%	1 860	16 320	5.2	0%	1 730	9 770	3.7	0%	1.3	0.8	1.7	1.02	1.86	1.6	0%
Mason	9	137	1 040	3.7	0%	1 360	10 760	4.8	0%	1 570	9 370	3.5	0%	1	0.6	1.9	1.72	3.42	2	0%
Silicon production	63	38	1 550	8.5	0%	676	50 420	13	0%	364	7 040	10	0%	1.7	0.8	8	0.56	8.75	4.7	0%
Paste loading in the composite	10	04	101	4 4	00/	040	2 0 0 0		00/	774	2 260	0 E	00/		0.0	0.0	0.26	2.00	10	00/
electrode	12	34	101	4.1	0%	640	3 020	2.2	0%	//4	3 260	2.5	0%	1.1	0.8	2.3	0.36	2.09	4.0	0%
Casing welding of the composite	10	70	074	0 F	00/	1 0 1 0	E 710	2.2	00/	1 000	4 000	26	00/		0.7	0 5	0.00	1 00	• •	00/
electrode	12	12	0/4	3.5	0%	1 040	5710	3.3	0%	1 000	4 990	3.0	0%	1.1	0.7	2.5	0.30	1.03	2.2	0%
Manufacture	11	11	487	4.8	0%	44	642	5.3	0%	22	80	2.9	0%	1.7	1	21	0.21	0.68	2.7	0%
Annual maintenance (cold furnace)	12	62	1 100	9	0%	2 140	42 140	12	0%	634	7 690	7.5	0%	3.5	1.6	9.3	2.06	9.87	3.9	0%
Hot furnace maintenance	7	37	1 540	11	0%	3 010	66 040	66	0%	749	21 430	40	0%	6.4	2.1	7.8	1.97	10.1	6.5	0%
Aluminum production	32	19	142	3.3	0%	148	690	3.8	0%	80	353	3.9	0%	2.3	1	6.8	0.75	2.14	2.2	0%
Maintenance of paste tower and furnace	6	12	21	1.8	0%	171	510	2.1	0%	99	195	1.7	0%	1.8	1	4.5	0.73	1.7	2.2	0%
Ramming: furnace restoration	13	38	155	4.1	0%	182	504	2.1	0%	104	283	2.2	0%	2.3	1.2	6.2	0.52	1.11	2	0%
Anode baking	6	9.8	16	1.6	0%	32	74	1.8	0%	21	54	2.1	0%	2.2	1.3	2.6	0.73	1.73	2.1	0%
Anode production – paste tower	7	12	35	2.8	0%	336	10 870	7.5	0%	126	10 760	10	0%	3.3	1.1	9.1	1.54	3.01	1.6	0%
Carbon product manufacturing	53	32	324	4.4	0%	83	640	3.5	0%	96	1 130	4.1	0%	1.3	0.5	6.1	0.57	4.33	3	0%
Raw carbon cathode extruding	20	50	343	3.8	0%	135	497	2.1	0%	175	951	2.3	0%	0.9	0.5	6.9	0.57	1.59	2.2	0%
Raw graphite cathode extruding	11	13	81	2.5	0%	53	141	2.3	0%	69	218	2.4	0%	1	0.5	2.8	0.49	0.84	1.6	0%
Cathode graphitization	5	14	92	3.2	0%	25	62	2.4	0%	18	59	4.1	0%	2	1.2	8	0.28	0.44	2	0%
Laboratory analysis	6	33	1 010	9.3	0%	75	4 900	13	0%	68	3 820	13	0%	1.7	1	3.1	0.37	1.15	2.9	0%
Railroad maintenance (replacing	5	42	54	1.2	0%	31	48	1.4	0%	84	15	1.6	0%	91	59	14	1.52	2.68	1.7	0%
creosote-impregnated wood ties)	Ŭ		01		070	01	10		070	0.1	10		070	0.1	0.0	• •	1.02	2.00		0 / 0
Steel foundries	16	15	12	93	6%	45	964	48	6%	92	95	46	0%	82	12	13	0.36	0.78	2	0%
(heating attendant mason)		1.0	12	0.0	070	40	004	4.0	070	0.2		4.0	0 /0	0.2	1.2	10	0.00	0.70		070
"Petroleum-derived" sectors	299	1.3	26	5.2	6%	1.5	57	9.9	21%	0.5	14	7.7	24%	6.4	0.8	142	0.08	0.48	3.1	2%
Combustion processes	17	0.2	0.7	3.3	29%	4.3	66	8	29%	3	65	10	6%	1.8	0.6	5.4	0.1	0.33	2.1	0%
Chimney sweeper	5	0.2	0.5	3.3	20%	19	118	4.5	20%	8.8	58	3.9	0%	2	1.6	3.3	0.09	0.18	1.7	0%
Handling of lubricating oils	44	1.3	7.3	3.4	2%	2.7	24	5	14%	0.7	10	5.6	11%	6.4	1.8	50	0.1	0.28	2.1	0%
Undercutting	5	0.4	0.6	1.6	0%	0.06	0.2	2.7	100%	0.06	0.2	4.3	60%	5.3	3.4	45	0.08	0.13	1.5	0%
Turning	22	1.2	2	1.7	0%	3.2	4.3	1.3	0%	0.3	0.6	2.1	9%	12	5.9	104	0.09	0.28	2.2	0%
Discharge mold	10	4.7	25	3.4	0%	5.2	27	3.9	0%	4.7	13	2.4	0%	3.2	1.1	4.2	0.18	0.36	1.7	0%
Vehicles	7	0.8	4.6	5.9	14%	8.4	23	2.8	14%	3	7.2	2.5	0%	3.7	2.1	3.9	0.08	0.17	1.7	0%
Engine exhaust emissions	117	0.7	8	4.4	9%	1.1	61	12	22%	0.7	13	8.1	21%	3.7	0.4	45	0.07	0.34	2.8	0%
Mechanic of light vehicles	16	0.5	2.2	2.6	0%	0.3	4.9	6	31%	0.9	7.6	3.5	0%	1.3	0.3	4.2	0.09	0.19	1.8	0%
Technical control of light vehicles	7	0.5	1.6	2.3	0%	0.6	10	4.9	0%	0.3	4.2	4.8	14%	4	1.9	16	0.04	0.1	1.9	0%

Mechanic of heavy trucks	9	0.8	5.1	2.4	0%	3.8	24	5.7	0%	1	6.5	5.8	11%	3.9	1.4	80	0.05	0.2	4.8	0%
Technical control of heavy trucks	7	0.2	0.4	1.5	14%	0.2	0.4	1.7	29%	0.6	16	7.6	14%	1	0.1	4.7	0.03	0.03	1.3	0%
Vehicle driver	11	0.07	0.7	4.1	73%	0.2	2.7	5.3	73%	0.2	1.3	4.4	36%	2.3	0.4	6.5	0.04	0.19	3	0%
Use of 2-Stroke and 4-Stroke engines	12	3.5	25	4.1	0%	8	40	3.5	0%	2.3	13	2.8	0%	4.5	3	25	0.12	0.36	2.1	0%
Generator system maintenance	10	2.4	7.7	2.5	0%	3.5	45	6.9	10%	1	5.5	7.7	10%	3.9	2.2	76	0.09	0.2	2.1	0%
Working in closed environment (tunnel)	10	2	25	5.1	10%	31	174	6.6	10%	3.6	40	8.1	10%	10	1.9	219	0.11	0.36	2.8	0%
Waste management driver	21	0.6	5.1	2.6	0%	0.6	190	13	24%	0.2	161	18	57%	8.6	1.2	45	0.09	0.61	3.3	0%
Bitumen	121	3.3	41	4.4	2%	1.3	37	10	21%	0.3	7.8	6.6	33%	22	1.9	457	0.09	0.51	3.9	5%
Roofing	15	2.4	93	7.4	13%	2.3	38	7.2	13%	1.2	97	11	27%	3.6	1.4	18	0.02	0.42	8.7	40%
Road paving with hot bitumen	85	3.5	40	4.5	0%	2	69	9.2	14%	0.3	4.3	5.4	32%	27	2	518	0.1	0.48	2.9	0%
Road paving with warm bitumen in tunnel	19	3.5	8.6	2.5	0%	0.2	1	6	47%	0.1	2.4	6.5	37%	28	2.7	466	0.16	0.62	3	0%

291

292 Note: The occupational groups are subdivided into two main categories: "coal-derived sectors" using coal products and "petroleum-derived sectors" exposed to

293 petroleum distillates or organic combustion. Groups in bold correspond to occupational sectors and those in grey to job activities (the sum of the job activity

samples is not necessarily equal to the number of samples in their given sector, as groups of "extreme" size (either inferior to 5 samples, or very close to the

295 number of samples in the sector) are not shown here.

296 pPyr: particulate pyrene, tPyr: total pyrene (sum of particulate and gaseous pyrene), BaP: benzo[a]pyrene, 1-OHP: 1-hydroxypyrene, LoQ: limit of quantification,

297 N: number of samples, GM: geometric mean, 5th: 5^{th} percentile, 95th: 95^{th} percentile, GSD: geometric standard deviation (in bold: \leq 3, normal: 3-6, in italic: >

298 6), Med: median.

299 3.2.2 BaP vs. 3-OHBaP couples

Regarding the 188 BaP *vs.* 3-OHBaP couples (Table 5), airborne BaP levels were very low in "petroleum-derived" sectors, with 30% of the values below the LoQ. This proportion rose to 60% when handling lubricating oils. A maximum BaP GM of 8.8 ng.m⁻³ was found for chimney sweepers. The levels in "coal-derived" sectors were almost 300 times higher than in "petroleum" sectors as they were for BaP *vs.* 1-OHP couples. The BaP levels in silicon production, aluminum production and carbon product manufacturing were 10 to 50 higher than those found in the steel foundry and railroad maintenance.

307 For 3-OHBaP, approximately 70% of the values were below the LoQ in most "petroleum-derived" 308 sectors. Conversely, these values were rare in "coal-derived" sectors, affecting less than 20% of the 309 couples, with the exception of railroad maintenance (40%). In this last group, as well as in the steel 310 foundry, relatively low levels of both BaP (GM ≤ 10 ng.m⁻³) and 3-OHBaP (GM ≤ 0.05 nmol.mol⁻¹ 311 creatinine) were recorded. In contrast, the highest 3-OHBaP concentrations were measured in carbon product manufacturing (GM = 0.19 nmol.mol⁻¹ creatinine), while those of silicon production were 312 313 almost twice as low. These results were not consistent with airborne BaP levels, which were 3 times 314 higher in silicon production ($GM = 309 \text{ ng.m}^{-3}$) than those recorded for carbon product manufacturing 315 $(GM = 94 \text{ ng.m}^{-3}).$

316 **Table 5**: Airborne BaP levels at the end of week and urinary 3-OHBaP concentrations on the same day at the end of shift plus 16 hours for multiple occupational

317 groups

Occupational groups			Airborne BaP				Urinary 3- OHBaP		
Industrial sectors	N	GM	95th	GSD	<loq< td=""><td>GM</td><td>95th</td><td>GSD</td><td><loq< td=""></loq<></td></loq<>	GM	95th	GSD	<loq< td=""></loq<>
Job activities			(ng.m⁻³)		(%)		(nmol.mol ⁻¹)		(%)
"Coal-derived" sectors	101	103	3 550	7.9	0%	0.12	2.08	5	6%
Silicon production	32	309	8 070	9.9	0%	0.11	1.81	4.8	3%
Paste loading in the composite electrode	5	429	1 500	4.3	0%	0.09	1.43	5.5	0%
Manufacture	5	28	89	4.4	0%	0.04	0.15	3.3	0%
Annual maintenance (cold furnace)	10	426	6 890	7.2	0%	0.12	1.39	4	10%
Aluminum production	11	124	313	1.7	0%	0.08	0.36	4.9	18%
Ramming: furnace restoration	7	147	372	1.8	0%	0.11	0.36	4.7	14%
Carbon product manufacturing	46	94	1 300	4.7	0%	0.19	2.54	4.7	2%
Raw carbon cathode extruding	19	182	976	2.3	0%	0.21	2.08	3.7	0%
Raw graphite cathode extruding	9	47	188	2.9	0%	0.09	0.21	2.9	11%
Railroad maintenance (replacing creosote-impregnated wood ties)	5	7.7	14	1.5	0%	0.02	0.09	5.8	40%
Steel foundries (heating attendant mason)	7	6	155	7.3	0%	0.04	0.13	2	0%
"Petroleum-derived" sectors	87	0.4	16	9.6	30%	0.01	0.09	3.9	69%
Combustion processes	10	2.7	47	10	10%	0.01	0.05	3.8	70%
Chimney sweeper	5	8.8	58	3.9	0%	0.008	0.05	5.4	60%
Handling of lubricating oils (undercutting)	5	0.06	0.2	4.3	60%	0.1	0.23	2.7	20%
Engine exhaust emissions	22	0.3	3.5	4.4	23%	0.01	0.05	3.2	77%
Mechanic of light vehicles	5	0.6	1.7	2.7	0%	0.01	0.01	1.5	60%
Technical control of light vehicles	6	0.2	0.4	2.3	17%	0.007	0.02	3.9	100%
Bitumen	50	0.3	12	11	34%	0.01	0.07	3.8	70%
Roofing	17	1	90	10	29%	0.02	0.07	2.4	76%
Road paving with hot bitumen	22	0.2	6	10	41%	0.008	0.06	4.7	68%
Road paving with warm bitumen in tunnel	11	0.2	1.7	8.8	27%	0.008	0.05	3.8	64%

318

319 Note: The occupational groups are subdivided into two main categories: "coal-derived sectors" using coal products and "petroleum-derived sectors" exposed to

320 petroleum distillates or organic combustion. Groups in bold correspond to occupational sectors and those in grey to job activities (the sum of the job activity

321 samples is not necessarily equal to the number of samples in their given sector, as groups of "extreme" size (either inferior to 5 samples, or very close to the

322 number of samples in the sector) are not shown here.

- 323 pPyr: particulate pyrene, tPyr: total pyrene (sum of particulate and gaseous pyrene), BaP: benzo[a]pyrene, 3-OHPBaP: 3-hydroxybenzo[a]pyrene, LoQ: limit of
- 324 quantification, N: number of samples, GM: geometric mean, 5th: 5^{th} percentile, 95th: 95^{th} percentile, GSD: geometric standard deviation (in bold: \leq 3, normal:
- 325 3-6, in italic: > 6), Med: median.

- 326 **3.3** Comparison of airborne PAH and urinary biomarker GSDs within occupational groups
- 327

328 Within each occupational group, the dispersion of urinary 1-OHP concentrations was usually lower than 329 that of atmospheric PAHs measured in parallel (Table 4). Indeed, at the industrial sector level, GSDs were below 3 in 70% of the cases for 1-OHP concentrations but in only 10% of the cases for BaP, gPyr 330 and pPyr. At the job/activity level, lower GSDs were observed, with nearly 75% of GSDs below 3 for 331 332 1-OHP, and 40% for PAH levels. 333 The GSDs of gPyr, pPyr and BaP were similar to each other in "coal-derived" sectors, while gPyr GSDs 334 tended to be lower than the other two in "petroleum-derived" sectors and thus were closer to the 1-OHP 335 distribution GSDs. 336 The dispersion of 3-OHBaP concentrations was higher than that of 1-OHP but was again lower than that 337 of atmospheric BaP levels. Regardless of the occupational groups, most 3-OHBaP GSDs ranged from 3 338 to 6 and were in all cases below 6. Conversely, 40% of the BaP GSDs were above 6. Aluminum 339 production had higher 3-OHBaP GSDs than BaP GSDs. 340 341 3.4 Assessing health risk within occupational groups 342 3.4.1 *wBaP vs. wadj1-OHP couples* 343 The distributions of airborne BaP concentrations weighted by APF (wBaP) and 1-OHP concentrations 344 adjusted by the wBaP/wPyr ratio (wadi1-OHP) are presented within each occupational group in Fig. 2. 345 Both OEL_{CNAM} and BLV_A are represented to assess the health risk depending on their exceedance 346 fraction. The OEL_{EU} is also drawn for information. 347 The conclusions regarding the health risk were similar according to the exceedance fraction of OEL_{CNAM} 348 and BLV_A for 75% of the occupational groups. More precisely, every activity estimated at high risk 349 when using OEL_{CNAM} was also considered at high risk based on BLVA, with the exception of the

- 350 laboratory analysis in carbon product manufacturing. Conversely, several activities estimated at high
- 351 risk when using BLV_A were estimated at low risk with OEL_{CNAM}, both in "petroleum-derived" and "coal-
- derived" sectors.

In "petroleum-derived" sectors, only the activity of waste management drivers was estimated to be at high risk according to OEL_{CNAM} , while 20% of all job activities presented a high risk according to BLV_A . Conversely, in "coal-derived" sectors, health risk according to OEL_{CNAM} was high for all sectors, with the exception of the steel foundry and railroad maintenance. It was also high for all activities of coke production. When using BLV_A , health risk was considered high in all sectors, with the exception of steel foundries, and in most job activities.

Overall, twice as many occupational groups were estimated to be at high risk when considering OEL_{CNAM} instead of OEL_{EU}. Coke production was the only sector considered at high risk when using OEL_{EU}, but three other "coal-derived" sectors could possibly be at risk, as the estimation was inconclusive. Conclusions were identical when considering _wBaPteq6 instead of _wBaP.



363

Fig 2: Distribution of weighted BaP levels and adjusted 1-OHP concentrations and health risk
 assessment within occupational groups

366 wBaP: benzo[a]pyrene concentrations weighted by an assigned protection factor (APF) depending on
 367 the type of mask worn by the worker, wadj1-OHP: 1-OHP concentration adjusted by the weighted wBaP
 368 / wtPyr ratio (wtPyr corresponding to the sum of gaseous and particulate pyrene levels weighted by an

APF). Health risk was assessed depending on the exceedance fraction of the limit values (OEL_{CNAM} and
 BLV_A, respectively).

371

372 3.4.2 wBaP vs. 3-OHBaP couples

373 The distributions of _wBaP and 3-OHBaP within each occupational group are presented in Fig. 3 for the 374 181 couples. The health risk was assessed by the respective exceedance fraction of OEL_{CNAM} and 375 BLV_{INRS}. No data were available for the coke production and steel foundries.

The conclusions regarding health risk were identical according to OEL_{CNAM} and BLV_{INRS} for 90% of the occupational groups. Regardless of the LV considered, health risk was low for all "petroleum-derived" sectors and for two "coal-derived" sectors (railroad maintenance and aluminum production). All groups estimated at high risk according to BLV_{INRS} were also estimated at high risk (or inconclusive) with OEL_{CNAM} . Conversely, the activity of the extruding raw graphite cathode was estimated to be at high risk according to OEL_{CNAM} but not according to BLV_{INRS} . According to OEL_{EU} , no group was estimated to be at high risk, and only silicon production could be at

risk with an inconclusive estimation. Conclusions were identical when considering _wBaPteq6 instead of





385

Fig 3: Distributions of weighted BaP levels and 3-OHBaP concentrations and health risk assessment
 within occupational groups

388 wBaP: benzo[a]pyrene concentrations weighted by an assigned protection factor (APF) depending on
389 the type of mask worn by the worker, 3-OHBaP: 3-hydroxybenzo[a]pyrene concentrations. Health risk
390 is assessed depending on the exceedance fraction of the limit values (OEL_{CNAM} and BLV_{INRs},
391 respectively).

- 392
- 393

3.5 Consistency of LV exceedances within couples

- 394
- 395 *3.5.1 wBaP vs. wadj1-OHP couples*

396 For each of the 497 couples, the OEL_{CNAM} exceedance of the wBaP level was compared to BLV_A 397 exceedance of wadil-OHP and analyzed according to the occupational sector and mask type (Fig. 4A). Regarding "petroleum-derived" sectors, no exceedance of OEL_{CNAM} or BLV_A was found for 97% of the 398 399 couples. An exceedance of OEL_{CNAM} alone was found for less than 1% of the couples, and an exceedance 400 of BLVA alone for less than 3%. Conversely, the exceedances of OELCNAM and BLVA were much less 401 consistent for "coal-derived" sectors. Only the levels in the steel foundry were consistent with no LV exceedance, and in coke production where both LVs were exceeded in 90% of the cases. For the other 402 403 sectors, exceedances of BLVA alone were observed in 9% of couples in aluminum production, 15% in 404 carbon product manufacturing, 20% in railroad maintenance and 27% in silicon production. The 405 exceedances of OEL_{CNAM} alone were related only to 4% in carbon product manufacturing, 5% in coke 406 production and 11% in silicon production.

407 Regarding mask type, when workers wore no mask, a "particulate mask" or a "gas mask", the OEL_{CNAM} 408 exceedance of _wBaP was consistent with BLV_A exceedance of _{wadj}1-OHP for 90% of the couples (Fig. 409 4A). This was mainly due to an absence of LV exceedance in the first two cases, whereas more than 410 50% of the couples with a "gas mask" presented an exceedance of both LVs. For "combined masks", 411 consistent results were found for only 60% of the couples, a quarter of which exceeded both LVs. While 412 the exceedances of OEL_{CNAM} alone were related to only 8% of the couples, those of BLV_A alone were 413 related to 29% of them.



209

09 Coke Sili

209

Global

Both LVs

BLV_A alone

OEL_{CNAM} alone



416 Fig. 4: Consistency between the exceedances of the atmospheric limit value (OEL_{CNAM}) and the 417 biological limit value (BLV_A) for BaP vs. adj1-OHP couples according to occupational sector and mask 418 type, with or without weighting by an APF

Alu.

Carb. Rail.

Occupational group

Steel Petrol

20

None

P

Mask type

Ġ Comb.

419 A: with weighting by AFP = $_{w}BaP vs. _{wadj}$ 1-OHP couples, B: without weighting by AFP = BaP vs. $_{adj}$ 1-420 OHP couples.

421 Couple: association of a PAH air sample with a urinary PAH metabolite sample performed on the same 422 day for a given worker, wBaP: benzo[a]pyrene concentrations weighted by an assigned protection factor 423 (APF) depending on the type of mask worn by the worker, wadi1-OHP: 1-OHP concentrations adjusted 424 by the weighted wBaP/wtPyr ratio (wtPyr corresponding to the sum of gaseous and particulate pyrene levels weighted by an APF), adi1-OHP: 1-OHP concentrations adjusted by the nonweighted BaP/tPyr 425 426 ratio, LV: limit value, OEL_{CNAM}: occupational exposure LV defined for BaP by the French CNAM, 427 BLVA: biological LV defined for adj1-OHP by the ACGIH, Sili: silicon production, Alu: aluminum 428 production, Carb: carbon product manufacturing, Rail: railroad maintenance, Steel: steel foundry, 429 Petrol: "petroleum-derived sectors, P: "particulate mask", G: "gas mask", Comb: "combined mask".

430 *3.5.2 BaP vs. 1-OHP couples*

431 The same analyses were performed without taking into account the efficiency of the mask worn by the 432 workers, using non-weighted BLV_A for $_{adj}$ 1-OHP and OEL_{CNAM} for non-weighted BaP (Fig. 4B). The 433 results were the same as those of weighted levels for "petroleum-derived" sectors, coke production and 434 railroad maintenance. For the other "coal-derived" sectors, the exceedance of OEL_{CNAM} alone increased, 435 and the percentage exceeding both LVs was twice as high, with the exception of the steel foundry. While 436 the exceedance of BLV_A alone decreased from 27% to 6% in silicon production, it increased from 0%

437 to 11% in the steel foundry.

Without weighting by APF, the exceedances of BLV_A alone decreased from 4% to 2% for workers wearing a "gas mask" (Fig. 4B). For those wearing a "particulate mask", the exceedances of LVs increased to approximately 15% for OEL_{CNAM} alone, BLV_A alone and for both LVs. For workers wearing a "combined mask", only 37% of couples did not exceed any LV. While the exceedance of OEL_{CNAM} alone and the exceedance of both LVs more than doubled, the exceedance of BLV_A alone decreased from 28% to 3% without weighting by APF.

- 444
- 445

3.5.3 wBaP vs. 3-OHBaP couples

Among the 181 couples for which BaP levels were weighted by an APF, OEL_{CNAM} and BLV_{INRS} exceedances were consistent for 90% of the couples, with no LV exceedance for 85% of them. Only 5% exceeded BLV_{INRS} alone and 5% exceeded OEL_{CNAM} alone (Fig. 5A). No data were available for the coke production and steel foundries. No LV exceedance was found for "petroleum-derived" sectors, railroad maintenance or aluminum production. Conversely, the results of 20% of the couples were not consistent in silicon production and carbon product manufacturing, with as many exceedances of BLV_{INRS} alone as of OEL_{CNAM} alone.

Regarding the mask type, the results were consistent for almost 95% of the workers wearing no mask or a "particulate mask", with few LV exceedances. However, 6% of workers not wearing any mask presented an exceedance of OEL_{CNAM} alone. For workers wearing "combined masks", the results were consistent only for 70% of the couples, including 15% exceeding both LVs. In this group, 19% exceeded the BLV_{INRS} alone, while 12% exceeded the OEL_{CNAM} alone.





Fig. 5: Consistency between the exceedances of the atmospheric limit value (OEL_{CNAM}) and the
biological limit value (BLV_{INRS}) for BaP vs. 3-OHBaP couples according to occupational sector and
mask type, with or without weighting by an APF

462 A: with weighting by $AFP = {}_{w}BaP vs.$ 3-OHBaP couples, B: without weighting by AFP = BaP vs. 3-463 OHBaP couples.

464 Couple: association of a PAH air sample with a urinary PAH metabolite sample performed on the same 465 day for a given worker; wBaP: benzo[a]pyrene concentrations weighted by an assigned protection factor 466 (APF) depending on the type of mask worn by the worker, LV: limit value, OEL_{CNAM}: occupational 467 exposure LV defined for BaP by the French CNAM, BLV_{INRS}: biological LV defined for 3-OHBaP by 468 the French INRS, Sili: silicon production, Alu: aluminum production, Carb: carbon product 469 manufacturing, Rail: railroad maintenance Steel: steel foundry, Petrol: "petroleum-derived" sectors, P: 470 "particulate mask", G: "gas mask", Comb: "combined mask", NA: no data available.

471 3.5.4 BaP vs. 3-OHBaP couples

When using OEL_{CNAM} for non-weighted BaP (Fig. 5B), the results were the same as those of weighted levels for "petroleum-derived" sectors and railroad maintenance. The results were less consistent in the 3 other "coal-derived" sectors due to an increase in the exceedance of OEL_{CNAM} alone, reaching more than 20% in carbon product manufacturing and aluminum production and almost 40% in silicon production. Conversely, the exceedance of BLV_{INRS} alone decreased, and the percentage of couples did not exceed any LV.

For workers wearing no mask, the results were the same regardless of whether the levels were weighted (Fig. 5B). For those wearing a "particulate mask", the exceedances of OEL_{CNAM} alone reached 30% without weighting (instead of 0%), while the couples not exceeding any LV decreased by the same percentage. For workers wearing a "combined mask", only 31% of couples did not exceed any LV, while an exceedance of both LVs and OEL_{CNAM} alone was found for 35% of the couples.

483

484 4. **Discussion**

This study aimed to investigate the consistency between biological and airborne monitoring by taking into account the effectiveness of RPE. To achieve this goal, comparisons between airborne BaP exposure levels and urinary metabolite concentrations were performed in different occupational groups (industrial sectors and job activities).

489

490 4.1 Urinary metabolite selection

3-OHBaP was chosen because it is the main metabolite of the carcinogenic BaP, which has been shown
to be a specific and sensitive biomarker for determining the internal exposure to PAHs of workers in
different industries (Barbeau et al. 2014, 2015; Forster et al. 2008).

1-OHP was selected because it is the most widely used urinary PAH metabolite in occupational
environment, even though it reflects the absorption of particulate pyrene and especially gaseous pyrene,
a non-carcinogenic PAH (Barbeau et al. 2015, 2017; Gao et al. 2018; Ifegwu et al. 2012; Jongeneelen
2014).

498 Other urinary metabolites of gaseous PAHs have been used to assess environmental exposure but they 499 do not reflect carcinogenic PAH exposure and are strongly linked to individual behaviors (e.g., dietary 500 patterns, tobacco smoke...) and air pollution (Patel et al. 2021). Furthermore, 3-OHBaP and 1-OHP are 501 the only urinary PAH biomarkers with existing guidance/limit values.

502

503 4.2 Exposure levels within petroleum-derived sectors

504 Regarding "petroleum-derived" sectors, airborne BaP levels of workers exposed to asphalt and engine 505 exhaust fume (GM of 0.3 and 0.7 ng.m⁻³) were very low and from the same order of magnitude as 506 workers in Italy (mean of 0.3 ng.m⁻³) (Campo et al., 2006), but slightly lower than workers in the UK 507 (BaP of approximately 10 ng.m⁻³) (Unwin et al., 2006). However, the 1-OHP levels in both of these 508 studies were 2 to 3 times higher than ours (median of $0.7 \,\mu g.L^{-1} vs. 0.3 \,\mu g.L^{-1}$). This difference could be 509 due to a larger number of smokers or to less cutaneous protection for their workers. The "petroleumderived" groups presented a 95th percentile (P95) of 1-OHP at 0.5 µmol.mol⁻¹, equivalent to that of the 510 511 general population. Indeed, urinary concentrations ranged from 0.04 to 0.53 μ mol.mol⁻¹ for smokers and 512 from 0.01 to 0.15 µmol.mol⁻¹ for nonsmokers in a French study (Lafontaine et al, 2006), while the P95 513 value was equal to 0.46 µmol.mol⁻¹ for smokers and 0.15 µmol.mol⁻¹ for nonsmokers in the NHANES 514 study (CDC, 2019). For 3-OHBaP, the large number of < LoQ values (70%) prevented the accurate 515 analysis of low PAH exposure levels. This result was consistent with the scarce literature regarding 3-516 OHBaP in non-occupationally exposed subjects, with 30% of the values below the LoQ (Raponi et al., 517 2017) and up to 80% for nonsmokers (Barbeau et al., 2011; Leroyer et al., 2010). Consequently, urinary 518 3-OHBaP analysis is not relevant for assessing low PAH exposures in "petroleum-derived" sectors.

519

520 4.3 Exposure levels within coal derived sectors

Regarding "coal-derived" sectors, the BaP and pyrene levels as well as the 1-OHP and 3-OHBaP concentrations were consistent with previously published data as well as the very low proportion of 3-OHBaP levels < LoQ (Förster et al., 2008). The highest airborne BaP levels ($GM = 1.5 \ \mu g.m^{-3}$) were found in coking plants and were in the same range as those of a large study conducted in the UK (Unwin et al., 2006) and 2 times higher than those performed in Germany (median of 0.89 $\mu g.m^{-3}$) (Förster et 526 al., 2008). The corresponding 1-OHP urinary levels found in our study (GM = $1.4 \mu mol.mol^{-1}$) were 527 similar to those of the UK study (Unwin et al., 2006) but 2 times lower than those reported in an 528 European study (Talaska et al., 2014). The differences between studies result from various job activities 529 and RPE efficiency but also from various coking plant features with a clear improvement over time, with average levels divided by 10-fold in a few years (Pyy et al., 1997). Moreover, the sampling time of 530 day and the work week has a strong influence on biomarker levels. While the best sampling time for 1-531 532 OHP was at EWES (Jongeneleen, 2014), that of 3-OHBaP was at EWES+16 because of its urinary 533 elimination delay (Barbeau et al., 2015; Lafontaine et al., 2004). However, urine samples were 534 sometimes collected only at the end of the shift for scheduling reasons (Talaska et al., 2014), which can 535 modify the results and explain the observed differences.

536 For aluminum production using prebaked anodes, the airborne BaP levels and the urinary 1-OHP 537 concentrations were also similar to those previously reported (Unwin et al., 2006) but were 10 times 538 lower than those found in the Netherlands before 1990 (VanSchooten et al., 1995). In this industrial 539 sector, PAH exposures have considerably decreased because of the change in the anode composition 540 and the disappearance of coal tar pitch from products used for pot relining. In the same way, the BaP 541 and pyrene levels measured in carbon product manufacturing were 15 to 22 times lower than those 542 measured 15 years earlier in Germany (medians of 1.5 and 2.2 μ g.m⁻³, respectively), while the 1-OHP 543 and 3-OHBaP concentrations were 2 to 3 times lower (Förster et al., 2008). In steel foundries, the BaP 544 levels as well as the 1-OHP and 3-OHBaP concentrations were low, as previously reported (Campo et 545 al., 2016; Unwin et al., 2006). Compared with the other "coal-derived" sectors, railroad maintenance 546 presented a unique profile, as already pointed out (Hebisch et al., 2020; Unwin et al., 2006), with 547 particularly low BaP exposure associated with notably high 1-OHP urinary levels due to the absence of 548 worn RPE and a very high tPyr/BaP ratio.

549 While atmospheric levels of "coal-derived" sectors were 30 times higher for gPyr, 200 times higher for 550 pPyr and 300 times higher for BaP than those of "petroleum-derived" sectors, urinary biomarker 551 concentrations were only 10 times higher.

552

553 4.4 Variability of air and urinary levels

554 The variability of urinary concentrations of 1-OHP and 3-OHBaP was 1.5 to 3 times lower than those 555 of the atmospheric levels of gPyr, pPyr and BaP. For industrial sectors with less than 40% values of 3-556 OHBaP below the LoQ, the GSD of 3-OHBaP was higher than that of 1-OHP, which could be explained 557 by fewer workers in each group. This lower variability in biological levels had already been pointed out within a large cohort of Korean workers with a GSD of only 3.07 for 1-OHP concentrations (Koh et al., 558 559 2020) and by several studies comparing biological and atmospheric variances (Lin et al., 2005; 560 Symanski and Greeson, 2002). The difference between air and biological levels could be explained by 561 the fact that urinary concentrations are averaged over several hours but also because 74% of workers 562 involved in "coal-derived" sectors wore a RPE. In "petroleum-derived" sectors, only 14% of workers 563 were wearing RPE, but PAH exposure was very low.

564

565 4.5 Pyrene/BaP ratio

566 In the present study, the airborne PAH proportions were found to be highly variable depending on the 567 occupational group—hence the atmospheric mixtures—with a tPyr/BaP ratio ranging from 0.6 to 28. 568 This variable composition was even more pronounced in two other French studies, with tPyr/BaP ratios 569 ranging from 2.3 to 274 in coal sectors (Lafontaine et al., 2004) and a global proportion of particulate 570 PAHs ranging from 1% to 32% (Maître et al., 2018). The PAH mixture composition (gas/particle 571 partitioning) depends on the source of emission and environmental conditions and is highly variable 572 from one source to another. The highest levels of particulate PAHs, carcinogenic PAHs and BaP were 573 found in coal derived sectors because of the raw material composition and the high temperatures 574 observed in these sectors. Indeed, a high temperature is associated with a higher proportion of particulate 575 PAHs within the emitted mixture as a result of the lower volatility of these compounds compared with 576 gaseous PAHs (Kim et al., 2013). To take into account the great variability of PAHs contained in 577 atmospheric mixtures, the urinary 1-OHP concentrations were adjusted in our study by the ratio of the 578 airborne concentration of BaP to that of total pyrene (BaP/tPyr ratio).

579

580 4.6 Respiratory protective equipment and assigned protection factors

581 The type of mask and its effectiveness in stopping gases or particles varied from one sector to another 582 but also from one company to another. In silicon production, carbon product manufacturing and steel 583 foundries, all the RPEs worn by workers were effective against particulate PAHs (and sometimes against 584 gases), while those worn by workers at coking plants were effective solely against gaseous PAHs. This 585 variability highlights the need to take into account the efficiency of RPE for assessing occupational 586 exposure and health risk of workers exposed to PAHs, as previously pointed out by several authors 587 (Crawford et al., 2014; Unwin et al., 2006). Because of the difficulty of collecting accurate information 588 about RPE and the technical complexity of atmospheric sampling, biological monitoring alone is often 589 preferred for assessing occupational health risk.

To assess health risk, the _wBaP levels and the _wtPyr/_wBaP ratios were calculated by weighting the atmospheric levels with an APF depending on the type of mask worn by the worker. The APF values chosen in this study corresponded to the French recommendations (Ministère du Travail, 2010) and were in agreement with values published by other authors (Crawford et al., 2014). However, some authors have recommended that the current half-mask APF should be reduced from 10 to 5 (Nicas and Neuhaus, 2004).

596

597 4.7 Health risk assessment

598

599 4.7.1 Choice of the relevant limit values

600 Due to the existence of different LVs and the lack of studies reporting a relationship between PAH 601 exposure and carcinogenic effects, the most protective value was used for assessing health risk.

602 For BaP and _wBaP, French OEL_{CNAM} at 150 ng.m⁻³ was more protective than OEL_{EU} at 2,000 ng.m⁻³.

603 Indeed, the exceedance of OEL_{CNAM} and OEL_{EU} occurred for 14% and 4% of the couples, respectively.

604 This OEL_{CNAM} is used in Latvia and is very close to that of Australia set at 200 ng.m⁻³ (SCOEL, 2016).

605 In the same way, no BLV of PAH biomarkers derives from a dose/response relationship between the

606 hydroxylated metabolite levels and carcinogenic effects. The most commonly used BLVs in France were

607 established from an extrapolation of existing atmospheric OELs (Jongeneelen, 2001). Indeed, the

608 BLV_{INRS} of 3-OHBaP set up to 0.40 nmol.mol⁻¹ creatinine was proposed for concentrations measured at

609 the beginning of the shift on the 5th day of exposure and was assumed to result from atmospheric BaP 610 exposure of 150 ng.m⁻³ over the working week (Nikolova-Pavageau *et al*, 2018).

For 1-OHP, there was no French BLV, but ACGIH proposed adjusting the BLV_A established for coke
oven workers by the ratio of the airborne concentration of total pyrene to that of BaP (tPyr/BaP ratio)
(ACGIH, 2017).

614

615 4.7.2 Exceedance of limit values within occupational group

The health risk assessment with OEL_{CNAM} for wBaP and the two BLVs (BLVA and BLV_{INRS}) for wadj1-616 617 OHP provided the same conclusions in most cases. However, wadi1-OHP seemed more protective than 618 "BaP, since every group except one (due to one single worker exposed to particularly high PAH levels), 619 estimated to be at high risk with atmospheric OEL_{CNAM}, was also considered at risk with urinary BLV_A. 620 Moreover, several groups presented a high health risk according to wadi 1-OHP, while wBaP levels were 621 below OEL_{CNAM}, probably due to dermal exposure. In contrast, most "petroleum-derived" groups 622 exposed to low BaP levels were considered at low risk based on wadil-OHP monitoring, suggesting a 623 satisfying specificity of this biomarker.

Regarding 3-OHBaP, a large number of values < LoQ were mainly found in "petroleum-derived" groups, where wBaP concentrations were below OEL_{CNAM} . The agreement of conclusions regarding LV exceedances between 3-OHBaP monitoring and air monitoring was almost perfect for "coal-derived" groups, but 3-OHBaP seemed less protective than wBaP. Indeed, while raw graphite cathode extrusion was estimated to be at high risk with wBaP levels, the 3-OHBaP concentrations of 19 workers were all below BLV_{INRS}.

630

631 4.7.3 Exceedance of limit values for each worker – comparison by occupational groups

The consistency between airborne and urinary LV exceedance for each worker was excellent for the lowest ("petroleum-derived" sector) and the highest (coke production) exposure groups. For the other "coal-derived" sectors, the results were inconsistent for 10% to 40% of the couples. In railroad maintenance, there were many exceedances of BLV_A alone with the measure of _{adj}1-OHP (weighted or not), whereas no exceedance of BLV_{INRS} alone was recorded. In this sector, dermal absorption accounted for up to 90% of the internal dose (Jongeneelen, 2001), and BaP levels were 10 times lower than tPyr, with nearly 60% in gaseous form. Thus, it is unclear whether these exceedances of BLV_A alone indicate a better ability of _{adj}1-OHP to reflect cutaneous exposure or if it is biased by the high proportion of pyrene despite the adjustment.

641 When using wBaP and wadj1-OHP levels weighted by an APF, the risk of exceeding OEL_{CNAM} alone, 642 BLV_A alone and both LVs (BLV_A and OEL_{CNAM} , or BLV_{INRS} and OEL_{CNAM}) was globally lower than 643 that without weighting. However, in numerous "coal-derived" sectors, LV exceedances were still 644 frequent despite this weighting. Stratification by mask type is useful to understand them.

645

646 4.7.4 Exceedance of limit values for each worker – comparison by mask types

For workers using a "gas mask", the exceedances of BLV_A and OEL_{CNAM} were approximately the same with and without weighting, since BaP is not stopped by this type of mask and the filtered gPyr represents only 10% of tPyr in atmospheric mixtures of "coal-derived" sectors. Those workers presented a large number of parallel exceedances of both LVs, which were largely met in coke production, where 70% of the workers wore a "gas mask" and the rest wore no mask. This finding suggests the capacity of wadi 1-OHP to detect wBaP levels exceeding OEL_{CNAM} .

653 For "particulate masks", the weighting drastically reduced all LV exceedances, as it affected both BaP 654 levels and the wBaP/wtPyr ratios. In contrast, the weighting of this ratio did not affect the wadil-OHP 655 levels (hence the BLV_A exceedances) for workers wearing a "combined mask", for which only OEL_{CNAM} 656 exceedances were reduced. Would the BaP levels not have been weighted, there would indeed have been 657 more than twice as many total exceedances of OEL_{CNAM} for "combined mask" and five times as many 658 for "particulate masks", which would have greatly increased the considered occupational risk. Despite 659 the weighting, when workers wore a "combined mask", the exceedances of both LVs were still high at 660 15%, indicating insufficient protection despite respiratory PPE. This phenomenon was especially 661 apparent in silicon production, for activities near furnace, and in carbon product manufacturing for raw 662 cathode extrusion. Furthermore, 10% of couples presented an exceedance of OEL_{CNAM} alone, which could be due to insufficient respiratory protection or to an underestimation of the mask efficiency by the 663 664 APF value. However, when RPE was taken into account, exceedances of BLV_A or BLV_{INRS} alone existed regardless of the mask type but in a much higher proportion when the worker wore a "combined mask" (30% for BLV_A or 20% for BLV_{INRS}). This phenomenon could be explained by an APF that was too high, as previously reported (Nicas and Neuhaus, 2004), or/and by an added skin absorption because these exceedances of BLV alone were found in 3 industrial sectors with high exposure levels, low tPyr/BaP ratios and frequent cutaneous exposure.

In fact, the exceedances of all LVs were particularly high for workers wearing a RPE, as the most 670 671 exposed workers were also the best protected. For high exposure levels, the use of biological monitoring 672 is thus justified to ensure that workers are properly protected and to take into account the cutaneous 673 exposure route. While using an APF allowed us to more accurately assess external and internal exposure 674 levels, it increased the points of uncertainty due to possible over- or underestimations of the protective 675 effect of the RPE. Among workers not wearing any RPE, no exceedance of OEL_{CNAM} alone existed for the "wadil-OHP vs. wBaP couples", but 6% of the "3-OHBaP vs. wBaP couples" presented an exceedance 676 677 of OEL_{CNAM} alone without a parallel exceedance of BLV_{INRS}. For these last couples, although the 678 maximum BaP reached 925 ng/m³, the corresponding 3-OHBaP concentrations ranged only from 0.04 679 to 0.33 nmol.mol⁻¹. The BLV_{INRS} was directly derived from this OEL_{CNAM}, and the samplings were indeed performed at the start of the 5th day shift as recommended (Nikolova-Pavageau et al, 2018), 680 681 eliminating all possible confounding factors. Thus, the measurement of urinary 3-OHBaP could lead to 682 underdiagnoses, a problem that was not encountered with wadil-OHP.

Finally, for the 166 couples with a measure of $_{wadj}$ 1-OHP and 3-OHBaP, there were twice as few exceedances of 3-OHBaP BLV_{INRS} than of $_{wadj}$ 1-OHP BLV_A, and only two-thirds of the exceedances of the BLV_{INRS} were associated with a parallel exceedance of the BLV_A.

686

687 **5.** Conclusion

This study highlights the importance of taking into account the effectiveness of RPE for assessing health risk, although using an APF increased the degree of uncertainty due to possible over- or underestimations of the protective effect of the RPE.

691 The urinary 3-OHBaP was not relevant for occupational groups with low PAH exposure levels and could
692 lead to underdiagnoses for assessing health risk, which has never been encountered with wadj1-OHP.

693 This last biomarker seems to be more protective than 3-OHBaP and $_{w}BaP$ but requires air sampling to 694 provide the BaP/tPyr ratio. However, the use of $_{wadj}$ 1-OHP has been shown to be faulty in the case of 695 very high pyrene proportions in PAH mixtures.

Given the complexity and cost of monitoring atmospheric levels, alternative approaches to simultaneous airborne and urine sampling could be developed, such as the use of abacus/tables providing the best weight to use for adjusting 1-OHP levels according to job activities and type of mask. Thus, there is a need for further analyses and studies, particularly for modeling and studying the relationship between biomarkers and air PAH levels in various industrial sectors.

701

702 Declaration of competing interest

The authors declare that they have no known competing financial interests or personal relationships thatcould have appeared to influence the work reported in this paper.

705

706 CRediT author statement

Mélodie Valière: Conceptualization, Methodology, Software, Formal analysis, Investigation, Data
Curation, Writing - Original Draft, Visualization. Pascal Petit: Conceptualization, Methodology,
Software, Formal analysis, Investigation, Data Curation, Writing - Review & Editing, Visualization,
Supervision. Renaud Persoons: Conceptualization, Methodology, Investigation, Formal analysis,
Writing - Review & Editing, Resources. Christine Demeilliers: Writing - Review & Editing. Anne
Maître: Conceptualization, Methodology, Formal analysis, Investigation, Data Curation, Writing Review & Editing, Supervision, Resources, Project administration.

714

715 Acknowledgements

The Exporisq-HAP was partially funded by French sanitary agency ANSES. The authors thank Sylvette

717 Liaudy for her help on references and Franck Balducci for his help on statistical analysis.

718

719 Data availability statement

- 720 The data and datasets generated during and/or analyzed during the current study are not publicly
- available due to the confidential nature of data (individual measurements and monitoring performed in
- 722 plants).

723 References

- ACGIH, 2020. Polyclyclic aromatic hydrocarbons (PAHs). Update 2017. In: Documentation of the
- 725 TLVs and BEIs with Worldwide occupational exposure values. Seventh ed. ACGIH, Cincinnati (USA)
- 726 Polycyclic Aromatic Hydrocarbons (PAHs). Update 2017. In : Documentation of the TLVs and BEIs
- 727 with Worldwide occupational exposure values. Cincinnati : ACGIH ; 2020.
- 728 AFNOR (1995) Workplace air. Sampling and analysis of the polycyclic aromatic hydrocarbons.
- 729 Standard NF X43-294. AFNOR, La Plaine Saint Denis, France.
 730 http://www.boutique.afnor.org/norme/nf-x43-294/workplace-air-sampling-and-analysis-ofthe-
- 731 polycyclic-aromatic-hydrocarbons/article/625508/fa038887
- AFNOR, 2019. Norme X43-279 Exposition sur les lieux de travail Mesurage de l'exposition par
 inhalation d'agents chimiques Stratégie pour vérifier la conformité à des valeurs limites d'exposition
 professionnelle. NF EN 689+AC. AFNOR, La Plaine St-Denis (France).
- Arnaudo, B., Leonard, M., Sandret, N., Cavet, M., 2012. L'évolution des risques professionnels dans
 le secteur privé entre 1994 et 2010. Premiers résultats de l'enquête SUMER. DARES Analyses. 23,
- 737 1-10. ISSN 2109 4128.
- Barbeau, D., Lutier, S., Bonneterre, V., Persoons, R., Marques, M., Hervé, C., Maitre, A., 2015.
 Occupational exposure to polycyclic aromatic hydrocarbons : Relations between atmospheric mixtures,
 urinary metabolites and sampling times. Int. Arch. Occup. Environ. Health 88, 1119-1129.
 https://doi.org/10.1007/s00420-015-1042-1
- Barbeau, D., Lutier, S., Choisnard, L., Marques, M., Persoons, R., Maitre, A., 2018. Urinary trans-anti7,8,9,10-tetrahydroxy-7,8,9,10-tetrahydrobenzo[a]pyrene as the most relevant biomarker for assessing
 carcinogenic polycyclic aromatic hydrocarbons exposure. Environ. Int. 112, 147-155.
 https://doi.org/10.1016/j.envint.2017.12.012
- Barbeau, D., Maître, A., Marques, M., 2011. Highly sensitive routine method for urinary 3hydroxybenzo[a]pyrene quantitation using liquid chromatography-fluorescence detection and
 automated off-line solid phase extraction. Analyst 136, 1183-1191. https://doi.org/10.1039/c0an00428f
 Barbeau, D., Persoons, R., Marques, M., Hervé, C., Laffitte-Rigaud, G., Maître, A., 2014. Relevance of
- virinary 3-hydroxybenzo(a)pyrene and 1-hydroxypyrene to assess exposure to carcinogenic polycyclic

- aromatic hydrocarbon mixtures in metallurgy workers. Ann. Occup. Hyg. 58(5), 579-590.
 https://doi.org/10.1093/annhyg/meu004.
- Barbeau, D., Lutier, S., Marques, M. et al., 2017. Comparison of gaseous polycyclic aromatic
 hydrocarbon metabolites according to their specificity as biomarkers of occupational exposure:
 Selection of 2-hydroxyfluorene and 2-hydroxyphenanthrene. J. Hazard. Mater. 332, 185-194.
 https://doi.org/10.1016/j.jhazmat.2017.03.011.
- 757 Boffetta, P., Autier, P., Boniol, M., Boyle, P., Hill, C., Aurengo, A., Masse, R., Thé, G. de, Valleron,
- A.J., Monier, R., Tubiana, M., 2010. An estimate of cancers attributable to occupational exposures in
- 759 France. J. Occup. Environ. Med. 52, 399-406. https://doi.org/10.1097/JOM.0b013e3181d5e355
- 760 Bourgart, E., Barbeau, D., Marques, M., von Koschembahr, A., Béal, D., Persoons, R., Leccia, M.T.,
- 761 Douki, T., Maitre, A., 2019. A realistic human skin model to study benzo[a]pyrene cutaneous absorption
- in order to determine the most relevant biomarker for carcinogenic exposure. Arch. Toxicol. 93, 81-93.
- 763 https://doi.org/10.1007/s00204-018-2329-2
- Buchet, J.P., Ferreira, M., Burrion, J.B., Leroy, T., Kirsch-Volders, M., Van Hummelen, P., Jacques, J.,
- 765 Cupers, L., Delavignette, J.P., Lauwerys, R., 1995. Tumor markers in serum, polyamines and modified
- nucleosides in urine, and cytogenetic aberrations in lymphocytes of workers exposed to polycyclic
- 767 aromatic hydrocarbons. Am. J. Ind. Med. 27, 523-543. https://doi.org/10.1002/ajim.4700270406
- 768 Burstyn, I., Randem, B., Lien, J.E., Langård, S., Kromhout, H., 2002. Bitumen, polycyclic aromatic
- 769 hydrocarbons and vehicle exhaust : Exposure levels and controls among Norwegian asphalt workers.
- 770 Ann. Occup. Hyg. 46, 79-87. https://doi.org/10.1093/annhyg/mef023
- 771 Campo, L., Buratti, M., Fustinoni, S., Cirla, P.E., Martinotti, I., Longhi, O., Cavallo, D., Foà, V., 2006.
- 772 Evaluation of exposure to PAHs in asphalt workers by environmental and biological monitoring. Ann
- 773 N. Y. Acad. Sci. 1076, 405-420. https://doi.org/10.1196/annals.1371.013
- Campo, L., Hanchi, M., Olgiati, L., Polledri, E., Consonni, D., Zrafi, I., Saidane-Mosbahi, D., Fustinoni,
- 5., 2016. Biological Monitoring of Occupational Exposure to Polycyclic Aromatic Hydrocarbons at an
- 776 Electric Steel Foundry in Tunisia. Ann. Occup. Hyg. 60, 700–716. doi:10.1093/annhyg/mew024
- 777 Centers for Disease Control and Prevention USA, 2019. National Report on Human Exposure to
- 778 Environmental Chemicals. January 2019. https://www.cdc.gov/exposurereport/

- Crawford, J.O., Dixon, K., Miller, B.G., Cherrie, J.W, 2014. A review of the effectiveness of respirators
 in reducing exposure to polycyclic aromatic hydrocarbons for coke oven workers. Ann. Occup Hyg.
 58, 943-54. doi: 10.1093/annhyg/meu048.
- 782 Doornaert, B., Pichard, A., Gillet, C., 2003. Hydrocarbures Aromatiques Polycycliques (HAPs).
- 783 Evaluation de la relation dose-réponse pour des effets cancérigènes: Approche substance par substance
- 784 (facteurs d'équivalence toxique –FET) et approche par mélanges. Evaluation de la relation dose-réponse
- pour des effets non cancérigène : Valeurs Toxicologiques de Référence (VTR). INERIS, Verneuil-enHalatte (France).
- 787 European Chemicals Agency, 2016. Inventory database. Summary of Classification and Labelling.
- 788 https://echa.europa.eu/fr/information-on-chemicals/cl-inventory-database/-/discli/details/20004.
- 789 Accessed 02.09.2016.
- 790 Förster, K., Preuss, R., Rossbach, B., Brüning, T., Angerer, J., Simon, P., 2008. 3-791 Hydroxybenzo[a]pyrene in the urine of workers with occupational exposure to polycyclic aromatic 792 hydrocarbons in different industries. Occup. Environ. Med. 65, 224-229. 793 https://doi.org/10.1136/oem.2006.030809
- Fustinoni, S., Campo, L., Cirla, P.E., Martinotti, I., Buratti, M., Longhi, O., Foà, V., Bertazzi, P., 2010.
- 795 Dermal exposure to polycyclic aromatic hydrocarbons in asphalt workers. Occup. Environ. Med. 67,
- 796 456-463. https://doi.org/10.1136/oem.2009.050344
- Gao, P., da Silva, E., Hou, L., et al., 2018. Human exposure to polycyclic aromatic hydrocarbons:
 Metabolomics perspective. Environ. Int. 119, 466-477. https://doi.org/10.1016/j.envint.2018.07.017.
- Hebisch, R., Karmann, J., Schäferhenrich, A., Göen, T., Berger, M., Poppek, U., Roitzsch, M., 2020.
- 800 Inhalation and dermal exposure of workers during timber impregnation with creosote and subsequent
- 801 processing of impregnated wood. Environ. Res. 181, 108877.
 802 https://doi.org/10.1016/j.envres.2019.108877
- Ifegwu, C., Osunjaye, K., Fashogbpn, F., et al., 2012. Urinary 1-hydroxypyrene as a biomarker to
 carcinogenic polycyclic aromatic hydrocarbon exposure. Biomark. Cancer. 4, 7-17.
 https://doi.org/10.4137/bic.s10065.

- International Agency for Research on Cancer, 2010. Some non-heterocyclic polycyclic aromatic
 hydrocarbons and some related exposures. IARC Monographs on the Evaluation of Carcinogenic Risks
 to Humans, Volume 92. IARC, Lyon. ISBN 978-92-832-1592-9
- Jongeneelen, F.J., 2001. Benchmark guideline for urinary 1-hydroxypyrene as biomarker of
 occupational exposure to polycyclic aromatic hydrocarbons. Ann. Occup. Hyg. 45, 3-13.
 https://doi.org/10.1016/S0003-4878(00)00009-0
- Jongeneelen, F.J., 2014. A guidance value of 1-hydroxypyrene in urine in view of acceptable
 occupational exposure to polycyclic aromatic hydrocarbons. Toxicol. Lett. 231, 239-248.
 https://doi.org/10.1016/j.toxlet.2014.05.001
- 815 Kim, K.H., Jahan, S.A., Kabir, E., Brown, R.J.C., 2013. A review of airborne polycyclic aromatic 816 and their human hydrocarbons (PAHs) health effects. Environ. Int. 60, 71-80. 817 https://doi.org/10.1016/j.envint.2013.07.019.
- 818 Koh, D.H., Park, J.H., Lee, S.G., Kim, H.C., Choi, S., Jung, H., Park, D., 2020. Comparison of
- 819 Polycyclic Aromatic Hydrocarbons Exposure Across Occupations Using Urinary Metabolite 1-
- 820 Hydroxypyrene. Ann. Work Expo. Health. 64, 445-454. https://doi.org/10.1093/annweh/wxaa014
- Lafontaine, M., Champmartin, C., Simon, P., Delsaut, P., Funck-Brentano, C., 2006. 3Hydroxybenzo[a]pyrene in the urine of smokers and non-smokers. Toxicol. Lett. 162, 181-185.
 https://doi.org/10.1016/j.toxlet.2005.09.019
- Lafontaine, M., Gendre, C., Delsaut, P., Simon, P., 2004. Urinary 3-hydroxybenzo[a]pyrene as a biomarker of exposure to polycyclic aromatic hydrocarbons : An approach for determining a biological
- 826 limit value. Polycycl. Aromat. Compd. 24, 441-450. DOI: 10.1080/10406630490471447
- 827 Lafontaine, M., Payan, J.P., Delsaut, P., Morele, Y., 2000. Polycyclic aromatic hydrocarbon exposure
- in an artificial shooting target factory : Assessment of 1-hydroxypyrene urinary excretion as a biological
 indicator of exposure. Ann. Occup. Hyg. 44, 89-100.
- Leroyer, A., Jeandel, F., Maitre, A., Howsam, M., Deplanque, D., Mazzuca, M., Nisse, C., 2010. 1Hydroxypyrene and 3-hydroxybenzo[a]pyrene as biomarkers of exposure to PAH in various
 environmental exposure situations. Sci. Total Environ. 408, 1166-1173.
 https://doi.org/10.1016/j.scitotenv.2009.10.073

- Lin, Y.S., Kupper, L.L., Rappaport, S.M., 2005. Air samples versus biomarkers for epidemiology.
- 835 Occup. Environ. Med. 62, 750-760. https://doi.org/10.1136/oem.2004.013102
- 836 Lutier, S., Maître, A., Bonneterre, V., Bicout, D.J., Marques, M., Persoons, R., Barbeau, D., 2016.
- 837 Urinary elimination kinetics of 3-hydroxybenzo[a]pyrene and 1-hydroxypyrene of workers in a prebake
- 838 aluminum electrode production plant : Evaluation of diuresis correction methods for routine biological
- 839 monitoring. Environ. Res. 147, 469-479. https://doi.org/10.1016/j.envres.2016.02.035
- 840 Maître, A., Petit, P., Marques, M., Hervé, C., Montlevier, S., Persoons, R., Bicout, D.J., 2018. Exporisq-
- 841 HAP database: 20 years of monitoring French occupational exposure to polycyclic aromatic
- 842 hydrocarbon mixtures and identification of exposure determinants. Int. J. Hyg. Environ. Health 221,
- 843 334-346. https://doi.org/10.1016/j.ijheh.2017.12.008
- 844 Marczynski, B., Pesch, B., Wilhelm, M., Rossbach, B., Preuss, R., Hahn, J.U., Rabstein, S., Raulf-
- 845 Heimsoth, M., Seidel, A., Rihs, H.P., Adams, A., Scherenberg, M., Erkes, A., Engelhardt, B., Straif, K.,
- 846 Käfferlein, H.U., Angerer, J., Brüning, T., 2009. Occupational exposure to polycyclic aromatic
- 847 hydrocarbons and DNA damage by industry: a nationwide study in Germany. Arch. Toxicol. 83,
- 848 947-957. https://doi.org/10.1007/s00204-009-0444-9
- 849 Ministère du Travail (France). Circulaire de la Direction générale du Travail (DGT) 2010/03 du 13 avril
- 850 2010 relative au contrôle du risque chimique sur les lieux de travail. NOR : MTST1010075C. Bulletin
- 851 officiel du Ministère du travail, France. https://www.legifrance.gouv.fr/circulaire/id/30897
- Nicas, M., Neuhaus, J., 2004. Variability in respiratory protection and the assigned protection factor. J.
- 853 Occup. Environ. Hyg. 1,99-109. doi: 10.1080/15459620490275821.
- Nikolova-Pavageau, N., Pillière, F., 2018. Cartographie des expositions aux hydrocarbures aromatiques
 polycycliques (HAP) par secteur d'activité : Focus sur la surveillance biologique des expositions
 professionnelles. Références en Santé au travail. 154, 41-63. ISSN 2261-544X
- 857 Patel, A.P., Mehta, S.S., White, A.J., et al., 2021. Urinary polycyclic aromatic hydrocarbon metabolites 858 mortality in the United States: А prospective analysis. PloS. and One. 859 https://doi.org/10.1371/journal.pone.0252719.

- 860 Payan, J.P., Lafontaine, M., Simon, P., Marquet, F., Champmartin-Gendre, C., Beydon, D., Wathier, L.,
- 861 Ferrari, E., 2009. 3-Hydroxybenzo[a]pyrene as a biomarker of dermal exposure to benzo[a]pyrene. Arch
- 862 . Toxicol. 83, 873-883. https://doi.org/10.1007/s00204-009-0440-0
- 863 Petit, P., Bicout, D. J., Persoons, R., Bonneterre, V., Barbeau, D., Maître, A., 2017. Constructing a
- 864 Database of Similar Exposure Groups : The Application of the Exporisq-HAP Database from 1995 to
- 865 2015. Ann. Work Expo. Health. 61, 440-456. https://doi.org/10.1093/annweh/wxx017
- Petit, P., Maître, A., Persoons, R., Bicout, D.J., 2019. Lung cancer risk assessment for workers exposed
 to polycyclic aromatic hydrocarbons in various industries. Environ. Int. 124:109-120. doi:
 10.1016/j.envint.2018.12.058.
- 869 Pyy, L., Mäkelä, M., Hakala, E., Kakko, K., Lapinlampi, T., Lisko, A., Yrjänheikki, E., Vähäkangas,
- 870 K., 1997. Ambient and biological monitoring of exposure to polycyclic aromatic hydrocarbons at a
- 871 coking plant. Sci. Total Environ. 199, 151-158. https://doi.org/10.1016/s0048-9697(97)00065-x
- 872 Raponi, F., Bauleo, L., Ancona, C., Forastiere, F., Paci, E., Pigini, D., Tranfo, G., 2017. Quantification
- 873 of 1-hydroxypyrene, 1- and 2-hydroxynaphthalene, 3-hydroxybenzo[a]pyrene and 6-
- 874 hydroxynitropyrene by HPLC-MS/MS in human urine as exposure biomarkers for environmental and
- 875 occupational surveys. Biomark. 22, 575-583. https://doi.org/10.1080/1354750X.2016.1252959
- Rappaport, S.M., Symanski, E., Yager, J.W., Kupper, L.L., 1995. The relationship between
 environmental monitoring and biological markers in exposure assessment. Environ. Health Perspect.
- 878 103 Suppl 3, 49-53. https://doi.org/10.1289/ehp.95103s349
- 879 Scientific Committee on Occupational Exposure Limits, 2016. SCOEL/REC/404, Polycyclic Aromatic
- Hydrocarbon mixtures containing benzo[a]pyrene (PAH). Recommendation from the Scientific
 Committee on Occupational Exposure Limits. European Union, Brussels. doi:10.2767/97750
- Symanski, E., Greeson, N.M.H., 2002. Assessment of variability in biomonitoring data using a large
 database of biological measures of exposure. AIHA J. 63, 390-401.
 https://doi.org/10.1080/15428110208984727
- Talaska, G., Thoroman, J., Schuman, B., Käfferlein, H.U., 2014. Biomarkers of polycyclic aromatic
 hydrocarbon exposure in European coke oven workers. Toxicol. Lett. 231, 213-216.
 https://doi.org/10.1016/j.toxlet.2014.10.025
 - 42

- 888 Unwin, J., Cocker, J., Scobbie, E., Chambers, H. 2006. An assessment of occupational exposure to
- 889 polycyclic aromatic hydrocarbons in the UK. Ann. Occup. Hyg. 50, 395-403. 890 https://doi.org/10.1093/annhyg/mel010