



Christelle Combescure

Académie Militaire Saint-Cyr Coëtquidan Institut de Recherche Dupuy de Lôme

IUTAM Symposium 19-23 July 2021



1. Context

- 2. Research Question
- 3. Our Study
- 4. Conclusions & Work in progress



•000000000

Context

Research Question

Our Study



Architectured Materials

Definition and applications

Macroscopic	Mesoscopic	Microscopic
L~ 10 cm	l~ 5 mm	λ~ 100 μm
Structure	Cell	Material
20 mm	No.	500 µm





- large number of cells
- local or global buckling
- interaction between adjacent cells
- loading commensurate with cell size



- large number of cells \Rightarrow equivalent continuum model
- local or global buckling
- interaction between adjacent cells
- loading commensurate with cell size



- large number of cells \Rightarrow equivalent continuum model
- local or global buckling
- interaction between adjacent cells
- loading commensurate with cell size

focus on buckling







Christelle Combescure







Avoid buckling

Onset of instability

[Ohno et al. 2002] [Triantafyllidis & Schraad 1998]

Tools

- Bloch-wave theory for commensurate buckling
- Rank-one convexity for macroscopic buckling
- Computation at the scale of 1 or several cells







[Shan et al. 2014]













Which generalized continuum model is better suited to capture both commensurate and macroscopic instabilities in periodic media?



Our Study





non-linear stored energy density in a spring p = 1 or p = 2

$$w_{p}(\varepsilon) = \frac{1}{2}K_{p}\varepsilon^{2} - \frac{1}{4}M_{p}\varepsilon^{4} + \frac{1}{6}N_{p}\varepsilon^{6}$$

inspired from [Triantafyllidis & Bardenhagen 1994] [Truskinovsky & Vainchtein 2014]



Mesoscopic study

non-linear stored energy density in a spring p = 1 or p = 2

$$w_{p}(\varepsilon) = \frac{1}{2}K_{p}\varepsilon^{2} - \frac{1}{4}M_{p}\varepsilon^{4} + \frac{1}{6}N_{p}\varepsilon^{6}$$

Stored energy density of the full system

$$\mathcal{W} = \frac{1}{2b} \sum_{n=0}^{n=N} \sum_{p=1}^{q} p\left[w_p(\epsilon_p^{n+}) + w_p(\epsilon_p^{n-}) \right]$$



F end forces associated with end displacement u_N



Equilibrium \Rightarrow principal path $\stackrel{0}{\varepsilon}$ = uniform strain of all springs

Bloch-wave perturbation predicts 2 possible unstable regimes

- macroscopic : $g_1(\stackrel{0}{\varepsilon}) + 2g_2(\stackrel{0}{\varepsilon}) = 0$
- commensurate $(\lambda = 2\ell)$: $g_1(\stackrel{0}{\varepsilon}) = 0$

with
$$g_p(\varepsilon) = K_p - 3M_p\epsilon^2 + 5N_p\epsilon^4$$

Coherent with [Truskinovsky et al. 2004]







Stability of paths depends on the values of parameters K_p , M_p and N_p

commensurate mode :



Macro mode :

















Micromorphic energy density: E macroscopic strain & s internal shift

$$\mathcal{W}^{m}(E,s) = w_1(E) + 2w_2(E) + G_1(E)\left(\frac{s}{\ell}\right)^2 + k_1(E)\left(\frac{s}{\ell}\right)^4 + \frac{N_1}{6}\left(\frac{s}{\ell}\right)^6$$



Equivalent media

Micromorphic

Micromorphic energy density: E macroscopic strain & s internal shift

$$\mathcal{W}^{m}(E,s) = w_{1}(E) + 2w_{2}(E) + G_{1}(E) \left(\frac{s}{\ell}\right)^{2} + k_{1}(E) \left(\frac{s}{\ell}\right)^{4} + \frac{N_{1}}{6} \left(\frac{s}{\ell}\right)^{6}$$

Equilibrium equations $\frac{\partial \mathcal{W}^m}{\partial E}$ and $\frac{\partial \mathcal{W}^m}{\partial s}$ Macro internal Stability condition

$$\begin{bmatrix} \frac{\partial^2 W^s}{\partial E^2} & \frac{\partial^2 W^s}{\partial E \partial s} \\ \frac{\partial^2 W^s}{\partial E \partial s} & \frac{\partial^2 W^s}{\partial s^2} \end{bmatrix} \Big|_{s=0}$$
 def positive



• $g_1(\overset{0}{E}) = 0$

Micromorphic medium able to capture both instabilities

 \approx vibration where micromorphic media can capture optical branches





Equivalent media

Second gradient

[Triantafyllidis & Bardenhagen 1994]

Taylor-series expansion of displacement in strain expression

$$\epsilon_n^{p+} = \frac{u_{n+p} - u_n}{p\ell} = u_{,x} + \frac{1}{2}p\ell u_{,xx} + \frac{1}{6}(p\ell)^2 u_{,xxx} + \dots$$

$$\epsilon_n^{p-} = \frac{u_n - u_{n-p}}{p\ell} = u_{,x} - \frac{1}{2}p\ell u_{,xx} + \frac{1}{6}(p\ell)^2 u_{,xxx} - \dots$$

Second gradient energy density:

$$\mathcal{W}^{s}(u_{x}) = w_{1}(u_{x}) + 2w_{2}(u_{x}) + (u_{xx})^{2} \frac{\ell^{2}}{2} h(u_{x})$$



Second gradient

[Triantafyllidis & Bardenhagen 1994]

Second gradient energy:

 $\mathcal{E}^{s}(u,x) = \int_{0}^{L} w_{1}(u,x) + 2w_{2}(u,x) + (u,x)^{2} \frac{\ell^{2}}{2} h(u,x) dx$

Equilibrium equation: $\mathcal{E}^s_{,u}\delta u = 0$ $w'_1(u_{,x}) + 2w'_2(u_{,x}) - \ell^2(\frac{h'(u_{,x})}{2}(u_{,xx})^2 + h(u_{,x})u_{,xxx}) = F$

Stability condition: $\mathcal{E}^{s}_{,uu}\delta u\delta u = 0$

$$g_1(u_{x}^0) + 2g_2(u_{x}^0) + \left(\frac{\ell n\pi}{L}\right)^2 h(u_{x}^0) = 0 \quad \forall n \in \mathbb{Z}$$





Conclusions & Work in progress





- implement both equivalent media in numerical continuation solver to compare on example BVP
- look at incommensurate instabilities appearing if p = 3 (next-to-next-to-neighbour interaction)



Conclusions

Comparing generalized continua vs instabilities

Micromorphic:

- Can capture both modes with criteria = mesoscopic
- Requires *a priori* knowledge of buckling mode wavelength

Second gradient:

- Can capture Macro mode appropriately with criterion = mesoscopic
- Can capture commensurate mode but BP point not exact
- Does not require any *a priori* knowledge & Systematic construction

Conclusions are the same as for vibration studies



Research Question

Thank you!

Context

Our Study

Conclusions



Max-OASIS





ANR-19-CE08-0005