



HAL
open science

Ultrafast laser-induced microplasmas inside band-gap solids: precision and controllability over the spectrum

D Grojo

► **To cite this version:**

D Grojo. Ultrafast laser-induced microplasmas inside band-gap solids: precision and controllability over the spectrum. GDR EMILI, Journées 2021, Oct 2021, Plaiseau, France. hal-03423382

HAL Id: hal-03423382

<https://hal.science/hal-03423382>

Submitted on 10 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Ultrafast laser-induced microplasmas inside band-gap solids: precision and controllability over the spectrum

D. Grojo¹

¹*Aix Marseille University, CNRS, LP3, UMR7341, 13288 Marseille, France*

Email : david.grojo@univ-amu.fr

High-peak power compact femtosecond lasers allow strong-field interactions that are the basis for high-precision laser processing. However, a relatively narrow region of the spectrum remains exploited today in this field. We study femtosecond laser interactions in various band-gap materials at non-conventional driving wavelengths up to the mid-infrared part of the spectrum.

The range of nonlinear responses accessible by radiation tuning allows revisiting questions as important as the achievable precision in surface machining technologies. In particular, we establish that the concept of nonlinear resolution is not applicable for femtosecond laser ablation. Independently of the nonlinearity of interaction, we find a systematic one-to-one mapping between femtosecond laser ablation features in dielectrics and beam contours at a strict threshold-intensity [1]. This is because any observable based on a threshold-based response (as ablation) simply ruins all potential benefits that could be expected on resolution from the nonlinear confinement of absorption. Another important consequence is that the achievable precision and repeatability can be directly derived from the level of determinism of the interaction. By comparing the results of a simple 'noise' model accounting for laser fluctuations and statistical analyses of ablation experiments, we quantify the degradation of the machining repeatability with increased pulse duration [2]. In this way, we assess the precision limits in laser machining. Overall, these works indicate that stable UV sources must provide a direct route to reach the nanoscale resolutions routinely achieved in lithography.

At the opposite side of the spectrum, ultrashort infrared laser pulses open a way for internal structuring of semiconductor materials that are extremely challenging to process in the three dimensions (3D writing) [3]. Our first proposed solution used hyper-focused beams to achieve microplasmas up to permanent modifications in the bulk of silicon with sub-100-fs pulses [4]. For more practical alternatives, we rely today on optimizations in the time domain. We investigate the picosecond regime limiting the nonlinearities and improving the process reliability by provoking progressive thermal band gap closure to assist pulse energy deposition [5,6]. Another approach is to rely on transient accumulation strategies. To this aim, we generate and apply ultrafast trains of pulses at up to Terahertz repetition-rates [7]. An important aspect also addressed by our experiments is the unusually high sensitivity of 3D writing in semiconductors to the temporal contrast of the pulses [8]. This causes laser-technology dependent results and represents an important finding for a comprehensive reading of the literature on this topic. Taken these approaches together, we introduce unique multi-timescale control parameters exploited for improved energy coupling and reliable 3D laser writing deep inside silicon chips that would not be possible otherwise.

References

- [1] M. Garcia Lechuga, et al. Evidencing the nonlinearity independence of resolution in femtosecond laser ablation, *Optics Letters* 45, 952-955 (2020).
- [2] M. Garcia Lechuga, et al. Assessing the limits of determinism and precision in ultrafast laser ablation, *Applied Physics Letters* 117, 171604. (2020).
- [3] A. Wang, et al. Three-dimensional luminescence microscopy for quantitative plasma characterization in bulk semiconductors *Applied Physics Letters* 119, 041108 (2021)
- [4] M. Chanal, et al. Crossing the threshold of ultrafast laser writing in bulk silicon. *Nature Communications* 8, 773 (2017).
- [5] M. Chambonneau, et al. Competing nonlinear delocalization of light for laser inscription inside silicon with a 2- μm picosecond laser. *Physical Review Applied* 12, 024009 (2019) ; A. Das, et al. Pulse duration dependence of laser-induced modifications inside silicon *Optics Express* 28, 26623 (2020).
- [7] A. Wang, et al. Ultrafast Laser Writing Deep Inside Silicon with THz-repetition-rate Trains of Pulses, *Research* 8149764 (2020).
- [8] A. Wang, et al. Temporal Contrast Imperfections as Drivers for Ultrafast Laser Modifications in Bulk Silicon, *Physical Review Research* 2, 033023 (2020)