

Implementing a new texture-based soil evaporation reduction coefficient in the FAO 2Kc method

Abdelhakim Amazirh, Olivier Merlin, Salah Er-Raki, Elhoussaine Bouras,

Abdelghani Chehbouni

▶ To cite this version:

Abdelhakim Amazirh, Olivier Merlin, Salah Er-Raki, Elhoussaine Bouras, Abdelghani Chehbouni. Implementing a new texture-based soil evaporation reduction coefficient in the FAO 2Kc method. Agricultural Water Management, 2021, 250, pp.106827. 10.1016/j.agwat.2021.106827 . hal-03438678

HAL Id: hal-03438678 https://hal.science/hal-03438678v1

Submitted on 21 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

1	Implementing a new texture-based soil
2	evaporation reduction coefficient in the FAO-
3	2Kc method
4 5	Abdelhakim Amazirh ^{a,*} , Olivier Merlin ^b , Salah Er-Raki ^{a,c} , Elhoussaine Bouras ^{b,c} , Abdelghani Chehbouni ^{a,b} .
6 7	^a Mohammed VI Polytechnic University (UM6P), Morocco, Center for Remote Sensing Applications (CRSA).
8 9	^b Centre d'Etudes Spatiales de la Biosphère (CESBIO), Université de Toulouse, CNES, CNRS, IRD, UPS, Toulouse, France.
10 11	^c ProcEDE, Département de Physique Appliquée, Faculté des Sciences et Techniques, Université Cadi Ayyad, Marrakech, Maroc.
12	Corresponding author*: Dr. Amazirh Abdelhakim
13	Email: abdelhakim.amazirh@um6p.ma/ abdelhakim.amazirh@gmail.com
14 15	Center for Remote Sensing Applications (CRSA), Mohammed VI Polytechnic University (UM6P), Hay Moulay Rachid-Benguerir, Morocco.
16	

17 Abstract

Crop evapotranspiration (ET) is a fundamental component of the hydrological cycle, 18 especially in arid/semi-arid regions. The FAO-56 offers an operational method for deriving 19 ET from the reduction (dual crop coefficient K_c) of the atmospheric evaporative demand 20 (ET₀). The dual coefficient approach (FAO-2Kc) is intended to improve the daily estimation 21 of ET by separating the contribution of bare soil evaporation (E) and crop transpiration 22 components. The FAO-2Kc has been a well-known reference for the operational monitoring 23 of crop water needs. However, its performance for estimating the water use efficiency is 24 limited by uncertainties in the modeled evaporation/transpiration partitioning. This paper aims 25 at improving the soil module of the FAO-2Kc by modifying the E reduction coefficient (K_r) 26 27 according to soil texture information and state-of-the-art formulations, hence, to amend the mismatch between FAO-2Kc and field-measured data beyond standard conditions. In practice 28 this work evaluates the performance of two evaporation models, using the classical Kr 29 (K_{r,FAO}) and a new texture-based Kr (K_{r,text}) over 33 bare soil sites under different evaporative 30 31 demand and soil conditions. An offline validation is investigated by forcing both models with

observed soil moisture (θ_s) data as input. The K_{r,text} methodology provides more accurate E 32 estimations compared to the K_{r.FAO} method and systematically reduces biases. Using 33 Kr,text allows reaching the lowest root means square error (RMSE) of 0.16 mm/day compared 34 to the K_{r.FAO} where the lowest RMSE reached is 0.88 mm/day. As a step further in the 35 assessment of the proposed methodology, ET was estimated in three wheat fields across the 36 entire agricultural season. Both approaches were thus inter-compared in terms of ET estimates 37 forced by SM estimated as a residual of the water balance model (online validation). 38 Compared to ET measurements, the new formulation provided more accurate results. The 39 RMSE was 0.66 mm/day (0.71 mm/day) and the R^2 was 0.83 (0.78) for the texture-based 40 41 (classical) Kr.

42 *Keywords: FAO-2Kc, soil evaporation, soil texture, soil moisture, evapotranspiration.*

43 **1. Introduction**

Surface evapotranspiration (ET) is an important flux in water and energy exchange processes 44 at the interface between land surfaces and the atmosphere. Soil evaporation (E) is one of the 45 main components of ET beside plant transpiration. E accounts for a substantial part of ET 46 from the exposed soil surface in growing crops, where its spatial distribution plays an 47 important role in various fields such as hydrology, meteorology and agronomy. In addition, E 48 49 is the only hydrological flow that connects both water (through soil moisture) and energy (through land surface temperature) balances. About 50 % to 70 % of annual precipitation is 50 51 consumed by E to the atmosphere which is considered as a water loss and not used for crop 52 productivity (Harrold et al., 1959; Peters, 1960; Wallace, 2000).

Partitioning ET is essential in modeling land atmosphere interactions and vegetation water 53 uptake and it is crucial in the monitoring of plant water uptake and water stress (Er-raki et al., 54 2010; Merlin et al., 2016; Porporato et al., 2001; Rafi et al., 2019). In agricultural crops, water 55 is mainly lost by E during the germination and emergence stage of growing crops. Then, 56 through the crop growth and development, the surface is covered; therefore, E impacts less 57 the water change in the soil while the transpiration becomes the main process and dominates 58 59 ET. In arid and semi-arid regions including irrigated areas, E is the main outward flux and influences the soil water budget, which is very vital for agriculture (Suleiman and Ritchie, 60 2003). Schlesinger and Jasechko, (2014) reported that the E contribution into ET ranges from 61 20 % to 40 %, and it is an essential boundary condition between soil and atmosphere. 62

It is well known that the E process occurs in two main stages. The first stage is characterized 63 64 by a constant rate of E which is also known as the energy-limited stage. It corresponds to when the evaporation occurs at a maximum rate meaning that it is limited only by the external 65 meteorological (radiation, wind speed and relative humidity) conditions. This stage continues 66 as long as the soil underneath has enough water storage. The second stage, also named the 67 falling rate stage, corresponds to when the surface dries so that the evaporation becomes 68 limited by soil moisture (θ_s) and by the soil hydraulic properties that determine the transfer of 69 liquid and vaporized water to the surface. In this stage the soil resistance to water diffusion 70 71 increases until θ_s reaches its minimal value (Chanzy et al., 1993). The rate of evaporation and the duration of both stages vary with soil texture. Therefore, more water can be evaporated 72 73 from saturated clayey soil than from saturated sandy soils because more water is stored in a clayey soil than in a sandy soil. 74

Different techniques have been used to measure E. Among them, we cite weighing lysimetry (Balwinder-Singh et al., 2011; Boast and Robertson, 1982; Leuning et al., 1994), isotopy (Aouade et al., 2016; Zhang et al., 2011) and portable evaporation chamber (Luo et al., 2018; Raz-Yaseef et al., 2010). Recently, Rafi et al. (2019) intercompared different methods based on eddy covariance, sap flow and weighing lysimetry measurements to assess E. The above techniques provided E measurements at a crop field scale.

- The FAO dual crop coefficient model (FAO-2Kc, Allen, 2000) is one of the most widely used 81 82 models to estimate crop ET due to its simplicity and operationality, and it has been applied in standard and beyond standard conditions (Suleiman et al., 2007). The FAO-2Kc consists in 83 84 splitting the crop coefficient K_c into two separate coefficients, one for crop transpiration, called the basal crop coefficient (K_{cb}) and one for soil evaporation (K_e). FAO-2Kc model 85 86 requires limited input parameters and it has been used to simulate ET of crops like wheat (Drerup et al., 2017; Er-raki et al., 2010; Er-Raki et al., 2007; Jin et al., 2017), olive (Er-raki 87 et al., 2008; Er-Raki et al., 2010), citrus (Rallo et al., 2017), table grapes (Er-Raki et al., 88 2013), sugar beet (Anderson et al., 2017; Diarra et al., 2017) crops grown under different 89
- 90 climates (Ayyoub et al., 2017; Debnath et al., 2015).
- 91 Despite the numerous applications of FAO-2Kc, many studies reported that the E component
- 92 is not well quantified. In some studies, the FAO-2Kc method overestimates E at the start of
- 93 the season and underestimates it at the end of the season (Mutziger et al., 2005; Parlange et
- al., 1992; Torres and Calera, 2010). Rafi et al., (2019) and Olivera-Guerra et al., (2018) found
- an underestimation of E at the start and the end of the wheat growing season. This is

- 96 potentially due to the classical K_e or more specifically to the reduction coefficient K_r of FAO-
- 97 2Kc which is based on an ad hoc relationship with texture via the θ_s at field capacity (Merlin
- 98 et al., 2016). Moreover, Phillips et al., (2017) stated that most land-surface models used to
- 99 estimate E cannot differentiate soil texture and this is due to the difficulty to incorporate the
- soil texture effect on the E rate.
- Merlin et al., (2016) showed that the nonlinear relationship between E rate and surface θ_s over 101 bare soils varied systematically with soil texture across several well-instrumented sites. Based 102 103 on this work, a new K_r formula was proposed based on the soil texture information using a new pedo-transfer function that physically links Kr to texture (Kr,text). The new pedo-transfer 104 function was developed in Merlin et al. (2016) using a meta-analysis approach and was 105 recently corroborated by a physically-based modelling approach relying on soil 106 hydrodynamical properties to simulate capillary flow (Lehmann et al. 2018). This gives 107 108 independent insight and additional confidence on the robustness of the proposed pedo-transfer function. 109
- The aim of the study is therefore to assess the usefulness of the pedo-transfer function of 110 Merlin et al. (2016) within the FAO formalism using - for the first time - 36 contrasted sites. 111 First, the new (K_{r,text}) and classical (K_{r,FAO}) formulations are tested over 33 bare (or 112 approximately bare) soil sites with different soil textures and compared against E 113 measurements. In this case, in situ soil moisture data are used as forcing (offline validation), 114 by considering the evaporation module separately from the water budget model, meaning that 115 the soil moisture forcing of Kr is measured. Note that among the 33 bare sites used to evaluate 116 the FAO evaporation estimates in the offline mode, 32 sites belong to the calibration data set 117 of Merlin et al. (2016) while the remaining site (MOBou) is used in this paper for the 118 119 evaluation. Then, as a complementary assessment of the new evaporation formulation, crop 120 ET was retrieved during the entire agricultural season. In this case, the simulated soil moisture (θ_{FAO}) is used as forcing to $K_{r,FAO}$ and $K_{r,text}$ (online validation) by considering the evaporation 121 module coupled to the water budget model, meaning that the soil moisture forcing of Kr is 122 123 simulated by the FAO water budget model. Both formulations of soil evaporation were evaluated in terms of total ET estimates over three wheat sites located in Morocco near 124 125 Marrakech. Note that the 3 wheat sites (B123, EC1, EC2) was used in this paper to validate the online implementation of the soil evaporation reduction coefficient in the FAO model. All 126 127 the three sites do not belong to the calibration data set of Merlin et al. (2016).
- 128 2. Sites and data description

In this study, a significant number of sites (33 bare soil and 3 wheat sites) have been used and divided into two categories depending on the desired objectives: i) the 33 bare soil sites have been used for comparing $K_{r,FAO}$ and $K_{r,text}$ under bare soil conditions only, and ii) the 3 wheat plots have been used to evaluate the new evaporation module when coupled to the crop water budget during the entire growing season including all phenological stages of wheat. A description of all the sites is presented below. More details about all the 32 bare soil sites but MOBou can be found in Merlin et al. (2016).

The studied 33 bare soil sites were differing in climatic conditions and soil textures (Table 1). 136 These sites are situated in 13 countries all over the world among which 8 are located over 137 uncropped lands, containing the natural lands including sand desert (NIHAP), savanna fallow 138 (NISav) and degraded land (NIDeg), native grass (AUStu), grass for silage or hay (USDk1), 139 short grass following fireforest (USFwf), and sparse shrub (USMo1 and USMo7). The 140 remaining 25 sites are located over agricultural fields where an identification of bare soil 141 periods is performed. In this study, "bare soil" period is defined as a time period when the 142 plant transpiration is either negligible or small compared to E. Hence the term "bare soil" 143 includes both actual bare soil conditions, and soils partially covered by mulch, crop residue, 144 or sparse vegetation. The data were collected from several national and international flux 145 station networks, intensive field measurements and extracted during bare or quasi bare soil 146 periods by Merlin et al. (2016). Table 1 indicates the localization of the different 33 bare soil 147 148 sites, where most sites are located in Europe continent. In Table 1, the clay and sand fractions are presented. The sand fraction ranges from 0.05-0.92 and clay fraction from 0.02-0.56. Such 149 150 a wide observation range of sand and clay fraction allows for testing the methodologies over different soils. Additional soil physical properties are also given in Table 1 such as, the 151 152 volumetric soil moisture at saturation (θ_{SAT}), soil moisture at field capacity (θ_{FC}) and soil moisture at wilting point (θ_{WP}) as well as the readily evaporable water (REW). These 153 parameter values are estimated with pedotransfer functions based on clay and sand fractions 154 (Brisson and Perrier, 1991; Cosby et al., 1984; Noilhan et al., 1996). 155

Sites	Sand (%)	Clay (%)	$ heta_{SAT} \ (m^3/m^3)$	$\theta_{WP}(m^3/m^3)$	$\theta_{FC}(m^3/m^3)$	REW (mm)	Country
AUStu	34.3	14.5	0.4079	0.205	0.335	9.5	Australia
BELon	7.5	20	0.4566	0.205	0.335	9.5	Belgium
CHOe2	9.5	43	0.4940	0.23	0.36	10	Switzerland
DEGeb	9.5	30	0.467	0.205	0.335	9.5	Germany
DEKli	21.5	55.7	0.4798	0.22	0.36	10	Germany

156 *Table 1: Study sites and their soil physical properties.*

DESeh	16.8	12.2	0.4465	0.205	0.335	9.5	Germany
DKVou	92	2	0.3816	0.045	0.12	4.5	Denmark
ESES2	10.4	47.5	0.4963	0.23	0.36	10	Spain
FRAur	20.6	32.3	0.4570	0.205	0.335	9.5	France
FRAvi	13.2	32.8	0.4691	0.205	0.335	9.5	France
FRGri	9.8	18.9	0.4522	0.205	0.335	9.5	France
FRLam	12	54.3	0.4984	0.22	0.36	10	France
FRRE1	5	40	0.4979	0.205	0.335	9.5	France
FRRE2	5	40	0.4979	0.205	0.335	9.5	France
IECa1	57	17	0.3893	0.11	0.23	8	Ireland
ITBCi	32	46	0.4491	0.22	0.36	10	Italy
ITCas	25	22	0.4274	0.15	0.29	9.5	Italy
MEYaq	36	44	0.4387	0.22	0.36	10	Mexico
MOBou	41	18	0.4373	0.15	0.244	8	Morocco
MOSR1	18.5	47	0.4787	0.22	0.36	10	Morocco
MOSR2	18.5	47	0.4787	0.22	0.36	10	Morocco
NIDeg	77	8	0.3835	0.11	0.23	8	Niger
NIHAP	93	5.7	0.3714	0.045	0.12	4.5	Niger
NIMil	77	8	0.3835	0.11	0.23	8	Niger
NISav	77	8	0.3835	0.11	0.23	8	Niger
USArm	28	43	0.4548	0.22	0.36	10	USA
USDk1	48	9	0.3966	0.12	0.25	9	USA
USFwf	30	13	0.4163	0.15	0.29	9.5	USA
USIb1	10	35	0.4791	0.205	0.335	9.5	USA
USIHO	58	28	0.3886	0.205	0.335	9.5	China
USM01	66	10	0.3860	0.11	0.23	8	USA
USM07	80	6	0.3847	0.065	0.15	6	USA
USSGP	26	24	0.4301	0.23	0.36	10	USA

In addition to soil texture, continuous measurements of energy fluxes had been monitored in each site such as net radiation (Rn), soil conduction (G) and sensible and latent heat fluxes (H) and (LE), respectively. Measured LE is corrected using the Bowen ratio (Twine et al., 2000). Note that, in some sites LE is missing. In this case, LE is estimated as the residual of the energy balance equation.

162 The three wheat crops used for evaluating E estimations by simulating total ET are located close to Marrakech, Morocco (Figure 1). This region is characterized by a semi-arid to arid 163 164 climate with high reference ET and low precipitation. Agricultural areas are generally covered by winter wheat crops. The three winter wheat fields are comprised of one flood irrigation 165 plot (B123) of 4 ha located in an irrigated agricultural zone (called R3) and two drip-irrigated 166 fields, both being 1.5 ha and situated in Chichaoua region. Both regions are located in the 167 Haouz plain. The area undergoes contrasted atmospheric conditions all over the year with 168 high temperature and low rainfall (less than 250 mm/ year) during summer and low 169 170 temperature and irregular rainfall from autumn to spring with a high evaporative demand (1600 mm/year). Wheat is the dominating crop (50 %) of the R3 zone, which is known for its 171 heterogeneity and contains different types of land cover (alfalfa, wheat, olive, orange and 172

horticulture). Numerous studies have been carried out since 2002 on this area (Ait Hssaine et 173 al., 2018; Amazirh et al., 2019, 2018, 2017; Chehbouni et al., 2008; Khabba et al., 2013; Ojha 174 et al., 2019; Olivera-Guerra et al., 2020). The Chichaoua site has been monitored since 2016. 175 Both wheat sites in Chichaoua were sown in November 2016, with the same drip irrigation 176 system. One of the plots (EC1) had been irrigated according to FAO crop water requirements 177 and the other plot (EC2) had undergone stress in controlled conditions. Additional details and 178 information about the study sites can be found in Amazirh et al. (2018), Merlin et al. (2018) 179 180 and Rafi et al. (2019). During the investigated agricultural seasons, all the three sites were monitored by an eddy 181

During the investigated agricultural seasons, all the three sites were monitored by an eddy covariance system, equipped with different sensors providing continuous measurements of energy and water fluxes exchanged between soil, vegetation and atmosphere. The installed hygrometer provided continuous measurements of H and LE fluxes. Additional instruments were installed in the tower providing extra measurements such as a Sonic 3D anemometer designed to measure the wind speed over the 3 orthogonal axes. R_n was measured by the net radiometer Kipp and Zonen CNR4.



189 Figure

188

Figure 1: Study areas where the coupled approach $(K_{r,text}$ -FAO-2Kc) is evaluated.

190 Half-hourly or sub-hourly measurements of classical meteorological data composed of air temperature T_a, wind speed u_a, incoming solar radiation R_g and air relative humidity rh_a were 191 collected at a reference height (2 m). Soil moisture data were also measured by Time Domain 192 Reflectometry sensors over the 3 sites at different soil depths (5, 10, 15, 30, 100 cm). In this 193 work two surface layers were used: 5 and 10 cm. A mean value between the two layers has 194 195 been used to assess soil moisture within the 0-10 cm soil column. For the sites where the soil moisture at 10 cm is unavailable and only soil moisture at 5 and 15 cm are available, a 196 197 linearly interpolation as in Merlin et al. (2011) was used to estimate the integrated soil moisture from 0 to 10 cm depth. 198

199 **3. Methodologies**

200 3.1. Dual crop coefficient method FAO-56

Allen et al. (1998) describe with details the theoretical background to assess crop ET. The 201 FAO-56 method is based on FAO-24 (Doorembos and Pruitt, 1975), where ET is estimated 202 based on the crop coefficient (K_c) and the reference evapotranspiration (ET₀). Allen, (2000) 203 and Allen et al. (2005b, 2005a, 1998) incorporate the dual crop coefficient, splitting K_c into 204 crop and bare soil contributions. Using the dual crop coefficient method allows for 205 partitioning ET into bare soil evaporation and plant transpiration beyond standard conditions 206 using two coefficients: the soil water evaporation coefficient (Ke) to describe E from the soil 207 surface and the basal crop coefficient (K_{cb}) to describe plant transpiration (Equation 1). The 208 209 daily variation in the crop coefficient is a function of the wetness of the soil surface and plant development. The crop ET under well-watered conditions is written as (Steduto et al., 2009): 210

211
$$ET_c = (K_{cb} + K_e)ET_0$$
 (1)

with ET_c being the maximal crop ET, ET_0 being the ET rate over a well-watered crop land covered by a short green, grass-like crop (reference ET), depending only on atmospheric conditions. An adjustment is made to obtain the actual estimates of the real crop ET_a by introducing the water stress coefficient K_s into the Equation (1), and it becomes:

216
$$ET_a = (K_{cb}K_s + K_e)ET_0$$
 (2)

In this paper we aim to improve the representation of E in Equation (2). Under bare soil conditions, crop transpiration is equal to zero ($K_{cb}=0$). E from Equation (3) is expressed as:

$$E = K_e E T_0 \tag{3}$$

Soil evaporative coefficient (K_e) is a function of the amount of water in the soil, soil properties and the exposed and wetted soil fraction to solar radiation where most E occurs (f_{ew}). K_e is defined using Eq. 4:

223
$$K_e = \min\{[K_r(K_{cmax} - K_{cb})], [f_{ew}K_{cmax}]\}$$
 (4)

where few = min (1-fc, fw) with fw being the fraction of the soil surface wetted by irrigation or rainfall (fw is 1 in case rainfall) and fc the fraction of surface covered by vegetation, and where K_{cmax} is the maximum value (ranging from 1.05 to 1.30) of crop coefficient K_c following rain or irrigation. It represents the upper limit on E and transpiration that reflects the natural constraints on available energy. For bare soil, K_{cb} is again equal to 0 and K_{cmax} is equal to 1.2 (Allen et al., 2005b, 1998). K_e formula becomes: $230 K_e = K_{cmax}K_{r,FAO}$

231 with K_r being the reduction coefficient, which depends on the cumulative depth of water depleted (D_e) and the amount of water that can be depleted by E during a complete drying 232 cycle (TEW). Following wetting by precipitation or irrigation, K_{r,FAO} can be as high as 1. 233 When the soil surface is dry, K_{r,FAO} is small and can even reach zero. E is presumed to take 234 235 place in two stages and the reduction coefficient K_{r.FAO} is expressed differently for both stages (Figure 2): energy is the limiting factor of E during stage I (constant drying rate) and soil 236 237 moisture is the limiting factor during stage II (falling drying rate). Stage I begins from D_e=0 and holds until D_e is equal to the readily evaporable water (REW) and where the soil moisture 238 239 equals to a given critical soil moisture θ_{cr} (value when soil begins to resist to evaporation). In this stage, the soil surface remains wet and the evaporation rate is controlled by the energy 240 available at the soil surface. Stage I holds until water cannot be transported to near surface as 241 fast as the rate to supply the atmospheric demand. Here stage II begins (D_e exceeds REW). 242

(5)



243 244

Figure 2: $K_{r,FAO}$ as function of De for classical FAO (Allen et al., 1998)

The reduction coefficient decreases and becomes smaller than 1 in proportion to the amount of water present in the surface soil layer. $K_{r,FAO}$ of Equation (5) is written as:

247
$$K_{r,FAO} = \frac{TEW - D_e}{TEW - REW} ; D_e > REW$$
(6)

$$K_{r,FAO} = 1 \qquad ; D_e < REW$$

with REW (mm) depending on soil texture. FAO-56 provides a table for each soil type. REW normally ranges from 5 to 12 mm and is highest for medium and fine textured soils (Ritchie, 1972; Ritchie et al., 1989). D_e is the cumulative depletion from the soil surface layer by evaporation (mm). The estimation of D_e requires a daily water balance model of the topsoil 253 layer. Otherwise soil moisture (θ_s) information can be used directly in the D_e calculation as 254 follows.

255
$$De = 1000(\theta_{FC} - \theta_s)Ze$$
(7)

256 TEW (mm) is the maximum depth of water evaporated from the surface layer:

257 TEW = $1000(\theta_{FC} - 0.5\theta_{WP})$ Ze (8)

where Ze is the effective depth of soil in which the atmosphere can extract water by E.

259 θ_{FC} , θ_{WP} and REW are reported for each site in table 1 depending on the soil texture 260 classification. For Ze, FAO-56 recommended a value of 10 cm for coarse soils and 15 cm for 261 fine textured soils (Hanks and Hill, 1980; Ritchie, 1972; Wright, 1982). The values of TEW, 262 Z_e and REW are important factors that control and influence the E process.

Step calculation of the classical Kr_{FAO} evaporation model is presented in the flowchart (Figure
3).

265 **3.2.** New texture-based approach

The FAO-56 classical E method (Kr_{FAO}) is sensitive to the E depth. Thus, the FAO-2Kc E 266 equation uses a given soil thickness. In the FAO-2Kc, they recommended a value of Z_e of 0.1 267 to 0.15 m which is suitable for the water balance model. Jacquemin and Noilhan. (1990), Lee 268 269 and Pielke. (1992) and Noilhan and Planton. (1989) proposed a formulation of soil evaporative efficiency based on surface soil moisture and soil moisture at the field capacity in 270 271 two specific soil thickness layers. Chanzy and Bruckler, (1993), Komatsu. (2003) and Merlin et al. (2016, 2011) found a nonlinear behavior of soil evaporative efficiency as a function of 272 273 soil moisture.

274 Merlin et al. (2011) proposed an expression of the soil evaporative efficiency for various soil 275 thicknesses based on soil moisture and soil texture information. The reduction coefficient K_r 276 based on soil texture ($K_{r,text}$) is written as:

277
$$K_{r,text} = \left[0.5 - 0.5 \cos\left(\frac{\pi \,\theta_s}{\theta_{max}}\right)\right]^p; \ \theta_s < \theta_{max}$$
(9)

278
$$K_{r,text} = 1$$
 ; $\theta_s > \theta_{max}$

where θ_s is the surface soil moisture, θ_{max} is taken equal to soil moisture at saturation θ_{SAT} by contrast of the work of Jacquemin and Noilhan. (1990) and Lee and Pielke. (1992), and P is a semi-empirical parameter depending on the soil moisture sensing depth and soil proprieties (texture).

283 Merlin et al. (2016) proposed an empirical Pedo-transfer (PTF) equation of the critical soil moisture $(\theta_{1/2})$ at which the actual E rate is half the potential E rate. In practice $\theta_{1/2}$ was 284 correlated with soil texture (clay and sand content) with a good correlation coefficient (0.6 for 285 sand fraction and 0.8 for clay fraction). A negative correlation was found between $\theta_{1/2}$ and 286 sand fraction while it increases as a function of clay fraction. To benefit from the 287 complementary information on soil water retention capacity, a multilinear regression of 288 $\theta_{1/2}$ with both sand and clay fractions has been established named as the texture-based PTF. In 289 this study, the PTF of Merlin et al. (2016), is used to check out its utility within the FAO 290 291 formalism. This formulation is tested over 33 study sites to evaluate the FAO evaporation estimates, with 32 sites belonging to the calibration data set of Merlin et al. (2016) and the 292 293 remaining site (MOBou) used as an independent data set for the evaluation of E estimates. Then, the three additional independent sites (EC1, EC2, B123) are used to assess wheat 294 surface evapotranspiration. All the three sites were not used in the calibration process in 295 Merlin et al. (2016). 296

297 $\theta_{1/2}$ is then written as:

298
$$\theta_{1/2} = 0.20 + 0.28 f_{clay} - 0.16 f_{sand}$$
 (10)

The advantage of the Eq 9, is that it can be calibrated using one single parameter P as shown in Merlin et al. (2011). Indeed, the formulation presented in Merlin et al. (2011) is a parsimonious formulation well adapted for parameterization with texture information. Hence, the idea is to parametrize simply $\theta_{1/2}$ presented in Equation (10) as a function of the single parameter P in which $K_{r,text}$ is approached linearly at the mid-value $(K_{r,text} (\theta_{1/2}) = 0.5)$. Therefore, P parameter can be deduced at $\theta_s = \theta_{1/2}$ by inverting Eq 9:

305
$$P = \frac{\ln \left[K_{r,text}\left(\theta_{1/2}\right)\right]}{\ln \left[0.5 - 0.5 \cos \left(\frac{\pi \theta_1}{2}{\theta_{SAT}}\right)\right]} \quad \text{where} \quad K_{r,text}\left(\theta_{1/2}\right) = 0.5 \quad (11)$$



306 The flowchart for E calculation using the new approach is also illustrated in Figure 3.

Figure 3: Flowchart presenting an overview of the main input and output data of the classical
Kr_{FAO} (Em-dashed red rectangle) and the new textural-based approach Kr_{text} (Em-dashed
blue rectangle) to estimate soil evaporation (E).

4. Results and discussions

Figure 4 plots the texture-based simulated Kr (K_{r.text}) as a function of soil moisture at 0-5 cm 312 depth for all bare studied sites. Looking at the Figure 4, it can be observed that the $K_{r,text}$ - θ_s 313 relationship shows two different shape curves: The S-shaped curve and the Γ -shaped curve. 314 315 The shape curves depend on the P value which is different for each site due to the soil texture information. For the 33 bare soil sites, the P values ranged from 0.24 to 2.46 from sandy 316 $(\theta_{1/2,1})$ to clayey $(\theta_{1/2,2})$ soils, respectively. For fine textured soils $K_{r,text}$ increased rapidly 317 with the increase of θ_s while K_{r,text} increased slowlier for coarse texture soils. The same 318 319 behavior was observed with physically-based simulated Kr in Chanzy and Bruckler. (1993). For P value higher than 0.5 the K_{r,text} increases rapidly with θ_s . In this case the derivative of 320 Kr with respect to θ_s is equal to zero at $\theta_s = 0$ and when θ_s reaches the saturation (θ_{sat}) 321 $K_{r,text}$ equals 1. Contrarily, for the sites with a P value smaller than 0.5, the slope $\frac{\partial K_{r,text}}{\partial Q}$ at 322 $\theta_s = 0$ tends to infinity. 323



324

Figure 4: Texture-based K_r simulated by the new model as function of in situ surface soil
moisture for the different 33 used sites. The very clayey soil and very sandy soil in our data
set correspond to P values equal to 2.46 and 0.24, respectively.

4.1. Evaporation estimates over bare soils using observed soil moisture data

In this sub-section we present the performance of the texture-based (K_{r,text}) by implementing a 330 pedo-transfer function developed in Merlin et al. (2016) within the FAO formalism and the 331 FAO (K_{r.FAO}) classical evaporation model compared to E measurements for some sites where 332 the measurements are available. The developed model was tested over different soil texture 333 sites (covering the range of clayey, silty, sandy soil types). Both methods were tested using in 334 situ soil moisture measured at 0-5cm soil depth as forcing. Figure 5 shows the performance of 335 the two methodologies; classical FAO (E_{FAO}) and texture-based formulation (E_{New}) compared 336 337 to measurements for different ranges of clay, sand and silt fractions: silty loam (DESeh, AUStu, BELon and ITCas), sandy loam (NISav, USMo1), Clay (MEYaq) loam (USDk1) and 338 loamy sand (USMo7). Key statistical information about model performance are reported in 339 Figure 6 for all study sites, such as root mean square error (RMSE), determination coefficient 340 (R^2) and mean bias error (MBE). 341



343Figure 5: Evaporation estimates from new model (E_{New}) and FAO-2Kc (E_{FAO}) using soil344moisture at 5-cm depth compared to measured evaporation.



345

Figure 6: Bar graph of R^2 , RMSE, MBE, intercept and slope of the linear regression between simulated and observed E using the Kr_{text} (black) and Kr_{FAO} (grey) for each site.

The scatter plot between observed and predicted E using the based-texture K_r (Figure 5) appears less dispersed around the 1:1 line compared to the classical Kr_{FAO} . Also, the bias is almost systematically reduced with the new texture-based formulation. A linear correlation is generally observed, which reveals that the new approach could be effective and successfully used to retrieve soil evaporation under different soil and climate conditions.

Although the statistical analyses provided relevant information about the effectiveness of the new developed model, statistical summary from Figure 6 revealed that the new K_r formalism has the capability to predict soil evaporation more accurately than the classical Kr_{FAO} . When

comparing the R², RMSE, MBE, slope and intercept for each site, one can observe that the 356 performance of the new K_r based on soil texture information is better than the classical 357 representation of K_r . By using the new formalism, an improvement of R^2 from 0.57, 0.40 and 358 0.46 to 0.69, 0.57 and 0.75 with a decrease of RMSE from 2.43, 1.86 and 2.40 mm/day to 359 0.83, 0.85 and 0.62 mm/day is obtained for AUStu, BELon and NISav sites, respectively. The 360 texture-based K_{r,text} appears to show its better performance for all soil types. For sandy loamy 361 soil we reached an R^2 of 0.75 (0.60) and a RMSE of 0.62 mm/day (0.86) for the NISav 362 (USMo1) site. For loamy sandy soil, R^2 reaches 0.54 with an RMSE equal to 1.01 mm/day for 363 USMo7 site, while for clayey soil as we reached an R^2 of 0.96 and RMSE of 0.80 for MOSR2 364 365 site.

In some study sites, even if the new approach still provides better results, a relatively poor 366 performance may occur for both approaches, (eg. USIb1, FRAur and CHOe2 sites). The 367 relatively poor results obtained at those sites are not due to the model itself but might be due 368 to the collected true measurements. As indicated in Merlin et al. (2016) most of the study sites 369 were not in a fully bare soil condition, as these sites were cropped and a selection of the 370 periods when soil is quasi bare was investigated, assuming no crop (no transpiration) over the 371 sites. This assumption could be a source of errors and could degrade the data quality. In 372 addition, soil depth could impact the results and could generate some uncertainties. To assess 373 374 the impact of the soil depth on the proposed approach, a sensitivity analysis is carried out by 375 using soil moisture at 0-10 cm depth. Overly, the new textural based Kr provides more accurate results than the K_{r,FAO}. This is due to its physical basis, given that the K_{r,text} is 376 implemented in a phenomenological model based on observational data, while the K_{r.FAO} was 377 mainly built on ad hoc assumptions. Lehmann et al. (2018) showed the importance of soil 378 379 texture on the variation of surface evaporation as a function of soil moisture content. Moreover, as cited in Merlin et al. (2016) and Wetzel and Chang (1988), the nonlinear 380 381 relationship between soil evaporation and soil moisture varied systematically with soil properties. In addition, the critical soil moisture content where the evaporation rate drops 382 below potential rate, was related to soil texture through the field capacity (Budyko, 1956; 383 Manabe, 1969). Through the new K_{r,text}, we succeeded in introducing the effect of soil texture 384 on E rate, which is not taken into account properly in other land surface models (Phillips et 385 al., 2017). 386

387 4.2. Sensitivity of Kr formulations to the thickness of surface soil layer

In this study the E estimates is assessed using soil moisture data at shallow depths near the 388 soil surface (0-5 cm and 0-10 cm depending on the site). As a prospect to integrate K_{r,text} in 389 the FAO-2Kc (next sub-section), which uses a surface soil thickness (Z_e) of either 10 or 15 390 cm, we need to assess the applicability of the $K_{r,text}$ to the 0-15 cm soil layer. This is more 391 crucial as all soil evaporation formulations are sensitive to the thickness of the surface soil 392 layer (Merlin et al., 2011). Therefore, a sensitivity analysis has been made to quantify the 393 impact of active soil evaporation depth to E as well as the integration of the new K_{r,text} into the 394 FAO-2Kc formulation. This was made for both approaches using 0-10 cm (in replacement of 395 the 0-5 cm) collected soil moisture. Note that, only the sites where soil moisture data at 10 cm 396 397 were available have been used for the sensitivity analysis. Figure 7 presents the simulated soil 398 E using texture-based Krtext and classical KrFAO compared to in-situ measurements for the 0-10 cm soil moisture depth. Due to the non-availability of soil moisture at 10 cm depth for all 399 400 sites, eleven sites were selected to test the new approach where soil moisture data at 10 cm depth were available. Figure 7 shows the simulated evaporation using both classical Kr_{FAO} 401 402 and new model Krtext compared to in situ measurements for six sites with different soil textures and climate conditions: clayey (MOBou, MEYaq), silty loam (BELon, FRGri, 403 404 DESeh) and sandy loam (IECa1). Figure 8 presents the performance of the approaches over 405 all the eleven study sites.



407 Figure 7: Evaporation estimates from new model (E_{New}) and K_{FAO} (E_{FAO}) using soil moisture 408 at 10 cm depth compared to measured evaporation.

406



410 Figure 8: Bar graph of the statistical parameters (R^2 , RMSE, MBE), the intercept and slope of the 411 linear regression between simulated and observed E using the new texture-based (black '5cm', grey

409

412 '10 cm') and Kr_{FAO} (Brown '5cm', orange '10 cm') for each site. 5 cm and 10 cm are the soil depths.

Looking at the results in Figures 7 and 8, generally the new textural-based model captures well the variation of evaporation measurements. Mostly the new model provides a more accurate prediction of E all over the 11 study sites. The new model shows its capabilities to solve the common overestimation problem that occurs especially under arid and semi-arid conditions (Michel et al., 2016) as shown at sites MOBou, BELon and DESeh. The new model yielded lower RMSEs over almost all sites in comparison with classical Kr_{FAO}, with a value of 0.94 mm.day⁻¹ and 1.70 mm.day⁻¹, respectively, at BELon site as an example.

The statistical results are presented in Figure 8, showing the performance of both approaches 420 421 (classic Kr_{FAO} and new texture-based Kr_{text}) using soil moisture data at 0-5 cm and 0-10 cm depth. In same sites, it appears from the statistical results that the performance of the new 422 423 approach slightly decreases while the classical Kr_{FAO} slightly improves providing better results by using soil moisture at 0-10 cm instead of 0-5 cm depths. However, the new 424 425 approach still outperformed the Kr_{FAO} approach regardless of the sensing depth (0-5 or 0-10 cm) of the soil moisture measurements. The error between Kr_{FAO} and *in-situ* evaporation 426 427 measurements is slightly reduced when using soil moisture at 0-10 cm instead of 0-5 cm depths, from 0.85 to 0.60 mm.day⁻¹ while by using new model the error is slightly increased 428 from 0.58 to 0.75 mm.day⁻¹ over FRGri site. The improvement of the performance of Kr_{FAO} 429 approach by using soil moisture at 0-10 cm instead of soil moisture at 0-5cm, is due to the fact 430 that the evaporation process can occur from deeper layers than the 0-5 cm layer. This is 431 especially occurred in arid and semi-arid areas in which the FAO-2Kc recommends the use of 432 a layer of 0-15 cm. Similarly, the new formulation of the evaporation reduction factor is 433 intrinsically dependent on the soil moisture measurements depth. It is reminded that the used 434 formulation has been developed and calibrated using a 0-5 cm soil layer. As stated by Merlin 435 et al. (2011), the P value is an increasing function of the soil depth for a given soil moisture 436 value. This could be responsible for the slight underestimation of new model when using the 437 0-10 cm layer. However, the Kr_{FAO} formulation is generally based on moisture data from 0 to 438 15 cm (Allen, 2000). The sensitivity analysis shows that the new approach generally 439 440 outperformed the classical Kr_{FAO} at either 5cm or 10 cm soil depths.

441 4.3. Coupling the K_{r,text} model with the FAO crop water budget model: 442 application to wheat cropped fields

443 As mentioned above, the main objective is to improve the soil evaporation estimates through 444 using a formulation of Kr based on soil texture information and soil moisture estimates. The

point is that retrieving soil evaporation is more relevant over bare soils and sparse areas. 445 However, over cropped area, retrieving surface evapotranspiration is more important. For this 446 reason, as a source of validating of our approach, we tested the new textural-based Kr 447 approach over the cropped fields defined before: B123 (2002-2003), EC1 and EC2 (2016-448 2017). Two cases were tested for each approach, where the soil evaporation component is 449 forced by i) *in-situ* soil moisture θ_s , using the classical FAO-2Kc ($E_{FAO}+\theta_s$) or the new 450 451 approach $(E_{New}+\theta_s)$ and ii) simulated soil moisture from the water balance (θ_{FAO}) , for 452 classical FAO-2Kc and new approach termed in the plots as $(E_{FAO} + \theta_{FAO})$ and $(E_{New} + \theta_{FAO})$, 453 respectively.

In order to observe the response of the evaporation coefficients to water supply, Figure 9 shows the temporal variation of Kr for FAO-2Kc ($K_{r,FAO}$) and new textural-based Kr ($K_{r,text}$) approaches for the cropped fields.



457



460 Figure 9: Time variation of the K_r estimated from FAO-2Kc ($K_{r,FAO}$) and new textural based 461 $Kr(K_{r,text})$ for the studied fields.

From the Figure 9, it can be observed that at the initial stage of crop growth, the $K_{r,FAO}$ values are high and reach its maximal value (1). This is due to the small fraction of soil surface covered by wheat crop. In addition, following rain or irrigation both Kr increase, while the Kr is small and can reach zero in the drier periods when the soil resistance to evaporation increases.

Overall, K_{r,text} detects soil stress periods and responds well to the water supplied by 467 precipitation or/and irrigation. After an irrigation or precipitation event both Kr increase with 468 different amplitudes. The new textural-based Kr appears to be more physical than the K_{r.FAO}. 469 It consistently increases following the supplied water amounts and then gradually decreases. 470 This is not the case for K_{r,FAO}, which increases and decreases rapidly. This is due to the 471 response and the soil drying time which is well taken into account in the K_{r,text} approach. 472 Especially in stage 2 when soil moisture is the limiting factor, the K_{r.text} decreases 473 progressively for each soil type depending on the soil properties. 474

An increase of Kr comes with an increase of the evaporation rate after a water supply by irrigation or/and rain. Consequently, soil evaporation losses are considerable. Figure 10 presents a daily evolution comparison of the measured ET (ET_{obs}) with simulated ET using standard FAO-2Kc ($E_{FAO}+\theta_{FAO}$) and new approach ($E_{New}+\theta_{FAO}$). Soil evaporation and wheat transpiration were also presented in the same figure for the three studied fields.





Figure 10: Time series comparison of daily plant transpiration (T), soil evaporation (E), ET_0 as well as the ET observed by EC (ET_{obs}) and simulated by FAO-2Kc (left) and new model (right) over the study fields.

According to figure 10, we notice that the new approach follows correctly the measured ET. 485 486 As it is seen, the new formulation of E helps catch the variation of surface ET especially at the beginning and the end of the season when ET is dominated by E and when transpiration is 487 relatively small. This behavior of the classical FAO-2Kc was also reported in Rafi et al. 488 (2019), where the classical FAO was found to underestimate E leading to an underestimation 489 490 of ET especially during the senescence period. While in Olivera-Guerra et al. (2018) an overestimation issue was observed using thermal-derived E estimates. Using soil moisture and 491 492 texture information lead to a correction of E in the initial and late stage. To evaluate visually and quantitatively the used approaches, the predicted ET were plotted against the observed ET 493 494 (ET_{EC}) and are presented in Figure 11 for the three wheat crop fields.

495



496

497 Figure 11: Scatterplot of simulated ET-FAO using the FAO-2Kc (left plot) and the new model forced 498 by simulated soil moisture (θ_{FAO}) (right plot) versus Eddy covariance ET (ET_{EC}) over the B123, EC1 499 and EC2 study fields.

From the statistical results presented in Figure 11, the new method provides the best results in term of accuracy and stability over the three wheat crop fields. The ET is estimated with an RMSE equal to 0.71 and 0.66 mm/day and an R^2 equal to 0.78 and 0.83 by using the classical FAO-2Kc and the proposed method for B123 field, respectively. An improvement is observed when using the new method. This is especially seen for small values of ET where the estimations are less scattered around the 1:1 line.

Statistics of the studied four cases are shown and reported in Figure 12. Using in situ soil 506 moisture or simulated θ_s from water balance in the new model gives almost the same results. 507 A slight difference is observed in the statistical results in terms of RMSE and R^2 . The 508 $E_{New}+\theta_s$ shows the best results compared to the other methods with the lowest RMSE (0.55 509 mm/day) and the highest R^2 of about 0.84 in the B123 field. The reason behind the good 510 results when *in-situ* soil moisture was used is the fact that soil moisture is directly measured 511 512 using TDR sensors while the simulated soil moisture is estimated using water balance equation where errors can accumulate from each water balance components. However, the 513 classical approach shows good results compared to new approach in the EC2 field, although 514 the difference between both approaches is smaller. 515

516 Overly, results showed that the new textural approach for E provided more accurate results in 517 terms of ET regardless of the source (direct measurements and model simulations) of soil 518 moisture estimates.



519

Figure 12: Bar graph of R², RMSE, MBE, intercept and slope of the linear regression between
 simulated and observed ET using the 4 approaches.

522 **5.** Conclusion

This work aims to improve the representation of the soil evaporation (E) component of the total evapotranspiration (ET). In the classical FAO-2Kc, the evaporation reduction coefficient Kr is estimated based on an ad-hoc relationship with soil texture. This standard formulation provides some limitation to quantify the E process. Rafi et al. (2019) and Olivera-Guerra et al. (2018) reported that the standard FAO-2Kc overestimates or underestimates E in the beginning or/and the end of the agricultural season.

529 A new E formulation is developed by including the soil texture information into Kr. The idea here is to adapt the Kr representation to the nonlinear relationship between soil moisture and 530 531 E in a range of soil texture types and surface conditions as in Merlin et al. (2016a, 2018). By including the new formulation into the FAO-2Kc the typical drying process is modified. The 532 533 new evaporation formulation was tested over 33 bare soil sites distributed all over the world. The sites are different in term of soil texture and meteorological conditions. Soil moisture 534 measurements at 0-5cm and 0-10 cm were used to further assess the impact of soil 535 measurement depths on the E rate. FAO-2Kc and the new texture-based approach were 536 537 evaluated by comparing them against in situ E measurements. From the obtained results, the 538 new approach provides the best results in term of accuracy and robustness. The new model provided solid basis for describing the soil texture impact on the E reduction coefficient. 539 540 However, some uncertainties were observed, and this could be due to the water diffusion flux which is not taken into account in the FAO-2Kc model and represents the soil as a simple 541 542 reservoir. Further, the new evaporation model was evaluated over a 3 monitored wheat cropped fields, where evapotranspiration is retrieved. The simulated evapotranspiration was 543 544 compared to eddy covariance measurements installed in the 3 sites. A comparison of the 4 545 cases is investigated by using both standard FAO-2Kc and the new approach. Each model is 546 forced by soil moisture either measured in situ or simulated by the water balance model. Results showed that the texture-based approach provides the best results with low errors over 547 the studied sites using field-scale measurements data. 548

To cope with some limitations of FAO-2Kc model, remote sensing data can be assimilated (Amazirh et al., 2021, 2018). However, the use of remote sensing data in the FAO-2Kc would require a match between the soil layers represented by the model and the sensing depth of spaceborne observations. The point is that the sensed thickness of remote sensing data rarely exceeds 0-5 cm. In this vein, coupling the FAO-2Kc with remote sensing data will be an asset for minimizing modeling errors, and for better constraining the 'often unavailable over most 555 irrigated area' irrigation input data. To do this, changing the depth of the top-soil layer 556 represented by the FAO-2Kc model to fit with the near-surface soil moisture derived from 557 remote sensing is needed.

558

559 Acknowledgements

This study was conducted within the Center of remote sensing applications, at the Mohammed 560 VI university-Morocco and was funded by the European Commission Horizon 2020 561 Programme for Research and Innovation (H2020) in the context of the Marie Sklodowska-562 Curie Research and Innovation Staff Exchange (RISE) action (REC project, grant agreement 563 no: 645642), followed by ACCWA project, grant agreement no. 823965). The in situ data set 564 was provided by the Joint International Laboratory TREMA (http://trema.ucam.ac.ma), the 565 European Fluxes Database Cluster (http://www.europe-fluxdata.eu), the AmeriFlux sites, 566 OzFlux site, long term observatories (AMMA, HOBE and SudMed), and the short term 567 568 intensive field campaigns (EFEDA, ReSeDa, Yaqui'08, HAPEX-Sahel, IHOP, Monsoon'90 and SGP'97). The French Agence Nationale de la Recherche (MIXMOD-E project, ANR-13-569 JS06-0003-01) is also acknowledged for extracting and pre-processing the bare soil 570 evaporation database. 571

572 **References**

- Ait Hssaine, B., Merlin, O., Rafi, Z., Ezzahar, J., Jarlan, L., Khabba, S., Er-Raki, S., 2018.
 Calibrating an evapotranspiration model using radiometric surface temperature,
 vegetation cover fraction and near-surface soil moisture data. Agricultural and Forest
 Meteorology 256–257, 104–115. doi:10.1016/j.agrformet.2018.02.033
- Allen, R.G., 2000. Using the FAO-56 dual crop coefficient method over an irrigated region as
 part of an evapotranspiration intercomparison study. Journal of Hydrology 229, 27–41.
 doi:10.1016/S0022-1694(99)00194-8
- Allen, R.G., Pereira, L.S., Raes, D., Smith, M., 1998. Crop evapotranspiration Guidelines
 for computing crop water requirements FAO Irrigation and drainage paper 56,
 Irrigation and Drainage. doi:10.1016/j.eja.2010.12.001
- Allen, R.G., Pereira, L.S., Smith, M., Raes, D., Wright, J.L., 2005a. FAO-56 Dual Crop Coefficient Method for Estimating Evaporation from Soil and Application Extensions. Journal of Irrigation and Drainage Engineering 131, 2–13. doi:10.1061/(ASCE)0733-9437(2005)131:1(2)
- Allen, R.G., Pruitt, W.O., Wright, J.L., Howell, T.A., Ventura, F., Snyder, R., Itenfisu, D.,
 Steduto, P., Berengena, J., Baselga, J., Smith, M., Pereira, L.S., Raes, D., Perrier, A.,
 Alves, I., Walter, I., Elliott, R., 2005b. A recommendation on standardized surface
 resistance for hourly calculation of reference ET o by the FAO56 Penman-Monteith
 method. doi:10.1016/j.agwat.2005.03.007
- Amazirh, A., Chehbouni, A., Ojha, N., Rivalland, V., Merlin, O., Er-Raki, S., 2021.
 Improving FAO-56 estimates of ET in semi-arid region through combined assimilation of SMAP based disaggregated soil moisture and Landsat Surface Temperature. AFM.
- Amazirh, A., Er-Raki, S., Chehbouni, A., Rivalland, V., Diarra, A., Khabba, S., Ezzahar, J., 595 Penman–Monteith 596 Merlin, O., 2017. Modified equation for monitoring evapotranspiration of wheat crop: Relationship between the surface resistance and 597 Engineering remotely Biosystems 598 sensed stress index. 164. 68-84.

- doi:10.1016/j.biosystemseng.2017.09.015
- Amazirh, A., Merlin, O., Er-Raki, S., 2019. Including Sentinel-1 radar data to improve the
 disaggregation of MODIS land surface temperature data. ISPRS Journal of
 Photogrammetry and Remote Sensing 150, 11–26. doi:10.1016/j.isprsjprs.2019.02.004
- Amazirh, A., Merlin, O., Er-Raki, S., Gao, Q., Rivalland, V., Malbeteau, Y., Khabba, S., 603 604 Escorihuela, M.J., 2018. Retrieving surface soil moisture at high spatio-temporal resolution from a synergy between Sentinel-1 radar and Landsat thermal data: A study 605 Remote Sensing 606 case over bare soil. of Environment 211. 321-337. doi:10.1016/j.rse.2018.04.013 607
- Anderson, R.G., Alfieri, J.G., Tirado-Corbalá, R., Gartung, J., McKee, L.G., Prueger, J.H.,
 Wang, D., Ayars, J.E., Kustas, W.P., 2017. Assessing FAO-56 dual crop coefficients
 using eddy covariance flux partitioning. Agricultural Water Management.
 doi:10.1016/j.agwat.2016.07.027
- Aouade, G., Ezzahar, J., Amenzou, N., Er-Raki, S., Benkaddour, A., Khabba, S., Jarlan, L.,
 2016. Combining stable isotopes, Eddy Covariance system and meteorological
 measurements for partitioning evapotranspiration, of winter wheat, into soil evaporation
 and plant transpiration in a semi-arid region. Agricultural Water Management.
 doi:10.1016/j.agwat.2016.07.021
- Ayyoub, A., Er-Raki, S., Khabba, S., Merlin, O., Ezzahar, J., Rodriguez, J.C., Bahlaoui, A.,
 Chehbouni, A., 2017. A simple and alternative approach based on reference
 evapotranspiration and leaf area index for estimating tree transpiration in semi-arid
 regions. Agricultural Water Management 188, 61–68. doi:10.1016/j.agwat.2017.04.005
- Balwinder-Singh, Eberbach, P.L., Humphreys, E., Kukal, S.S., 2011. The effect of rice straw
 mulch on evapotranspiration, transpiration and soil evaporation of irrigated wheat in
 Punjab, India. Agricultural Water Management 98, 1847–1855.
 doi:10.1016/j.agwat.2011.07.002
- Boast, C.W., Robertson, T.M., 1982. A "Micro-Lysimeter" Method for Determining
 Evaporation from Bare Soil: Description and Laboratory Evaluation. Soil Science
 Society of America Journal 46, 689–696.
 doi:10.2136/sssaj1982.03615995004600040005x
- Brisson, Perrier, 1991. A semi-empirical model of bare soil evaporation for crop simulation
 models. Water resources 27, 719–727.
- Budyko, M.I., 1956. Heat balance of the Earth's surface. Gidrometeoizdat, Leningrad. Cahill,
 255.
- Chanzy, A., Bruckler, L., Evaporation, S., 1993. Significance of Soil Surface Moisture With
 Respect to Daily Bare Soil Evaporation. Water Resources Research 29, 1113–1125.
 doi:10.1029/92WR02747
- Chehbouni, A., Escadafal, R., Duchemin, B., Boulet, G., Simonneaux, V., Dedieu, G., 636 Mougenot, B., Khabba, S., Kharrou, H., Maisongrande, P., Merlin, O., Chaponnière, A., 637 Ezzahar, J., Er-Raki, S., Hoedjes, J., Hadria, R., Abourida, A., Cheggour, A., Raibi, F., 638 Boudhar, A., I.Benhadj, Hanich, L., Benkaddour, A., Guemouria, N., Chehbouni, A., 639 Lahrouni, A., Olioso, A., Jacob, F., Williams, D.G., Sobrino, J. a, 2008. An Integrated 640 Modelling and Remote Sensing Approach for Hydrological Study in Arid and Semi-arid 641 642 Regions: The SUDMED Programme. International Journal of Remote Sensing 29, 5161-643 81.
- Cosby, B.J., Hornberger, G.M., Clapp, R.B., Ginn, T.R., 1984. A Statistical Exploration of the
 Relationships of Soil Moisture Characteristics to the Physical Properties of Soils. Water
 Resources Research 20, 682–690. doi:10.1029/WR020i006p00682
- Debnath, S., Adamala, S., Raghuwanshi, N.S., 2015. Sensitivity Analysis of FAO-56
 Penman-Monteith Method for Different Agro-ecological Regions of India.

- 649 Environmental Processes 2, 689–704. doi:10.1007/s40710-015-0107-1
- Diarra, A., Jarlan, L., Er-Raki, S., Le Page, M., Aouade, G., Tavernier, A., Boulet, G., 650 Ezzahar, J., Merlin, O., Khabba, S., 2017. Performance of the two-source energy budget 651 (TSEB) model for the monitoring of evapotranspiration over irrigated annual crops in 652 Agricultural Water Management 653 North Africa. 193. 71-88. 654 doi:10.1016/j.agwat.2017.08.007
- Doorembos, J.&, Pruitt, W.O., 1975. Guidelines for Predicting Crop Water Requirements.
 FAO Irrigation and Drainage Paper 24.
- Drerup, P., Brueck, H., Scherer, H.W., 2017. Evapotranspiration of winter wheat estimated
 with the FAO 56 approach and NDVI measurements in a temperate humid climate of
 NW Europe. Agricultural Water Management 192, 180–188.
 doi:10.1016/j.agwat.2017.07.010
- Er-Raki, S., Chehbouni, A., Boulet, G., Williams, D.G.G., 2010. Using the dual approach of
 FAO-56 for partitioning ET into soil and plant components for olive orchards in a semiarid region. Agricultural Water Management 97, 1769–1778.
 doi:10.1016/J.AGWAT.2010.06.009
- Er-raki, S., Chehbouni, A., Duchemin, B., 2010. Combining Satellite Remote Sensing Data
 with the FAO-56 Dual Approach for Water Use Mapping In Irrigated Wheat Fields of a
 Semi-Arid Region 375–387. doi:10.3390/rs2010375
- Er-Raki, S., Chehbouni, A., Guemouria, N., Duchemin, B., Ezzahar, J., Hadria, R., 2007.
 Combining FAO-56 model and ground-based remote sensing to estimate water
 consumptions of wheat crops in a semi-arid region. Agricultural Water Management 87,
 41–54. doi:10.1016/J.AGWAT.2006.02.004
- Er-raki, S., Chehbouni, A., Hoedjes, J., Ezzahar, J., Duchemin, B., Jacob, F., 2008.
 Improvement of FAO-56 method for olive orchards through sequential assimilation of
 thermal infrared-based estimates of ET. Agricultural Water Management 95, 309–321.
 doi:10.1016/j.agwat.2007.10.013
- Er-raki, S., Rodriguez, J.C., Garatuza-payan, J., Watts, C.J., Chehbouni, A., 2013.
 Determination of crop evapotranspiration of table grapes in a semi-arid region of
 Northwest Mexico using multi-spectral vegetation index. Agricultural Water
 Management 122, 12–19. doi:10.1016/j.agwat.2013.02.007
- Hanks, R.J., Hill, R.W., 1980. Modeling crop response to irrigation in relation to soils,
 climate and salinity. International Irrigation Infor- mation Center, 6.
- Harrold, L.L., Peters, D.B., Dreibelbis, F.R., McGuinness, J.L., 1959. Transpiration
 Evaluation of Corn Grown on a Plastic-Covered Lysimeter 1. Soil Science Society of
 America. doi:10.2136/sssaj1959.03615995002300020027x
- Jacquemin, B., Noilhan, J., 1990. Sensitivity study and validation of a land surface
 parameterization using the HAPEX-MOBILHY data set. Boundary-Layer Meteorology
 52, 93–134. doi:10.1007/BF00123180
- Jin, X., Yang, G., Xue, X., Xu, X., Li, Z., Feng, H., 2017. Validation of two Huanjing-1A/B
 satellite-based FAO-56 models for estimating winter wheat crop evapotranspiration
 during mid-season. Agricultural Water Management 189, 27–38.
 doi:10.1016/J.AGWAT.2017.04.017
- Khabba, S., Jarlan, L., Er-Raki, S., Page, M. Le, Ezzahar, J., Boulet, G., Simonneaux, V.,
 Kharrou, M.H., Hanich, L., Chehbouni, G., 2013. The SudMed Program and the Joint
 International Laboratory TREMA: A Decade of Water Transfer Study in the Soil-PlantAtmosphere System over Irrigated Crops in Semi-Arid Area. Procedia Environmental
 Sciences 19, 524–33.
- Komatsu, T.S., 2003. Toward a robust phenomenological expression of evaporation
 efficiency for unsaturated soil surfaces. Journal of Applied Meteorology 42, 1330–1334.

- 699 doi:10.1175/1520-0450(2003)042<1330:TARPEO>2.0.CO;2
- Lee, T.J., Pielke, R.A., 1992. Estimating the soil surface specific humidity. Journal of Applied
 Meteorology 31. doi:10.1175/1520-0450(1992)031<0480:ETSSSH>2.0.CO;2
- Lehmann, P., Merlin, O., Gentine, P., Or, D., 2018. Soil Texture Effects on Surface
 Resistance to Bare-Soil Evaporation. Geophysical Research Letters 45, 10,398-10,405.
 doi:10.1029/2018GL078803
- Leuning, R., Condon, A.G., Dunin, F.X., Zegelin, S., Denmead, O.T., 1994. Rainfall
 interception and evaporation from soil below a wheat canopy. Agricultural and Forest
 Meteorology 67, 221–238. doi:10.1016/0168-1923(94)90004-3
- Luo, C., Wang, Z., Sauer, T.J., Helmers, M.J., Horton, R., 2018. Portable canopy chamber
 measurements of evapotranspiration in corn, soybean, and reconstructed prairie.
 Agricultural Water Management 198, 1–9. doi:10.1016/j.agwat.2017.11.024
- Manabe, S., 1969. Climate and the Ocean Circulation I. The Atmospheric Circulation and the
 Hydrology of the Earth's Surface. Monthly Weather Review. doi:10.1175/1520 0493(1969)097<0739:CATOC>2.3.CO;2
- Merlin, O., Al Bitar, A., Rivalland, V., Béziat, P., Ceschia, E., Dedieu, G., 2011. An analytical model of evaporation efficiency for unsaturated soil surfaces with an arbitrary thickness. Journal of Applied Meteorology and Climatology 50, 457–471. doi:10.1175/2010JAMC2418.1
- Merlin, O., Olivera-guerra, L., Aït Hssaine, B., Amazirh, A., Ra, Z., Ezzahar, J., Gentine, P.,
 Khabba, S., Gascoin, S., Er-raki, S., 2018. A phenomenological model of soil
 evaporative e ffi ciency using surface soil moisture and temperature data. Agricultural
 and Forest Meteorology 257, 501–515. doi:10.1016/j.agrformet.2018.04.010
- Merlin, O., Stefan, V.G.V.G.G., Amazirh, A., Chanzy, A., Ceschia, E., Er-Raki, S., Gentine,
 P., Tallec, T., Ezzahar, J., Bircher, S., Beringer, J., Khabba, S., Gentine, P., Er-Raki, S.,
 Bircher, S., Khabba, S., 2016. Modeling soil evaporation efficiency in a range of soil and
 atmospheric conditions using ameta-analysis approach. Water Resources Research 52,
 3663–3684. doi:10.1002/2015WR018233.Received
- Michel, D., Jiménez, C., Miralles, D.G., Jung, M., Hirschi, M., Ershadi, A., Martens, B.,
 Mccabe, M.F., Fisher, J.B., Mu, Q., Seneviratne, S.I., Wood, E.F., Fernández-Prieto, D.,
 2016. The WACMOS-ET project Part 1: Tower-scale evaluation of four remotesensing-based evapotranspiration algorithms. Hydrology and Earth System Sciences 20.
 doi:10.5194/hess-20-803-2016
- Mutziger, A.J., Burt, C.M., Howes, D.J., Allen, R.G., 2005. Comparison of measured and
 FAO-56 modeled evaporation from bare soil. Journal of Irrigation and Drainage
 Engineering 131, 59–72. doi:10.1061/(ASCE)0733-9437(2005)131:1(59)
- Noilhan, J., Mahfouf, J.-F., Change, G., Change, P., 1996. The ISBA land surface
 parameterisation scheme. Global and Planetary Change 13, 145–159. doi:10.1016/09218181(95)00043-7
- Noilhan, J., Planton, S., 1989. A Simple Parameterization of Land Surface Processes for
 Meteorological Models. Monthly Weather Review 117, 536–549. doi:10.1175/15200493(1989)117<0536:ASPOLS>2.0.CO;2
- Ojha, N., Merlin, O., Molero, B., Suere, C., Olivera-Guerra, L., Ait Hssaine, B., Amazirh, A.,
 Al Bitar, A., Escorihuela, M., Er-Raki, S., 2019. Stepwise Disaggregation of SMAP Soil
 Moisture at 100 m Resolution Using Landsat-7/8 Data and a Varying Intermediate
 Resolution. Remote Sensing 11, 1863. doi:10.3390/rs11161863
- Olivera-Guerra, L., Merlin, O., Er-Raki, S., 2020. Irrigation retrieval from Landsat optical/thermal data integrated into a crop water balance model: A case study over winter wheat fields in a semi-arid region. Remote Sensing of Environment 239, 111627. doi:10.1016/j.rse.2019.111627

- Olivera-Guerra, L., Merlin, O., Er-Raki, S., Khabba, S., Escorihuela, M.J., 2018. Estimating
 the water budget components of irrigated crops: Combining the FAO-56 dual crop
 coefficient with surface temperature and vegetation index data. Agricultural Water
 Management 208, 120–131. doi:10.1016/j.agwat.2018.06.014
- Parlange, M.B., Katul, G.G., H., C.R., Levent, K.M., Nielsen, D.R., Michael, M., 1992.
 physical basis for time series model of soil water content. Water Resources Research.
- Peters, D.B., 1960. Relative Magnitude of Evaporation and Transpiration 1 . Agronomy
 Journal 52, 536–538. doi:10.2134/agronj1960.00021962005200090015x
- Phillips, T.J., Klein, S.A., Ma, H.Y., Tang, Q., Xie, S., Williams, I.N., Santanello, J.A., Cook,
 D.R., Torn, M.S., 2017. Using ARM Observations to Evaluate Climate Model
 Simulations of Land-Atmosphere Coupling on the U.S. Southern Great Plains. Journal of
 Geophysical Research: Atmospheres 122, 11,524-11,548. doi:10.1002/2017JD027141
- Porporato, A., Laio, F., Ridolfi, L., Rodriguez-Iturbe, I., 2001. Plants in water-controlled 761 ecosystems: Active role in hydrologic processes and responce to water stress IV. 762 real cases. Advances in Water Resources 24, 763 Discussion of 745-762. doi:10.1016/S0309-1708(01)00007-0 764
- Raes, D., Steduto, P., Hsiao, T.C., Fereres, E., 2009. AquaCropThe FAO Crop Model to
 Simulate Yield Response to Water: II. Main Algorithms and Software Description.
 Agronomy Journal 101, 438. doi:10.2134/agronj2008.0140s
- Rafi, Z., Merlin, O., Le Dantec, V., Khabba, S., Mordelet, P., Er-Raki, S., Amazirh, A.,
 Olivera-Guerra, L., Ait Hssaine, B., Simonneaux, V., Ezzahar, J., Ferrer, F., 2019a.
 Partitioning evapotranspiration of a drip-irrigated wheat crop: Inter-comparing eddy
 covariance-, sap flow-, lysimeter- and FAO-based methods. Agricultural and Forest
 Meteorology 265, 310–326. doi:10.1016/J.AGRFORMET.2018.11.031
- Rafi, Z., Merlin, O., Le Dantec, V., Khabba, S., Mordelet, P., Er-Raki, S., Amazirh, A.,
 Olivera-Guerra, L., Ait Hssaine, B., Simonneaux, V., Ezzahar, J., Ferrer, F., 2019b.
 Partitioning evapotranspiration of a drip-irrigated wheat crop: Inter-comparing eddy
 covariance-, sap flow-, lysimeter- and FAO-based methods. Agricultural and Forest
 Meteorology 265, 310–326. doi:10.1016/J.AGRFORMET.2018.11.031
- Rallo, G., González-Altozano, P., Manzano-Juárez, J., Provenzano, G., 2017. Using field
 measurements and FAO-56 model to assess the eco-physiological response of citrus
 orchards under regulated deficit irrigation. Agricultural Water Management 180, 136–
 147. doi:10.1016/J.AGWAT.2016.11.011
- Raz-Yaseef, N., Rotenberg, E., Yakir, D., 2010. Effects of spatial variations in soil
 evaporation caused by tree shading on water flux partitioning in a semi-arid pine forest.
 Agricultural and Forest Meteorology 150, 454–462.
 doi:10.1016/j.agrformet.2010.01.010
- Ritchie, J.T., 1972. Model [or PredictingE vaporatio[nr oma Row Crop with Incomplete
 Cover. Water Resources Research 8, 1204–1213.
- Ritchie, J.T., Godwin, D.C., Singh, U., 1989. Soil and weather inputs for the IBSNAT crop models. Proc., IBSNAT Symp.: Decision Support System for Agrotechnology Transfer:
 Part I., IBSNAT, Dept. Agronomy and Soil Science, College of Tropical Ag- riculture and Human Resources, Univ. of Hawaii, Honolulu, 31–45.
- Schlesinger, W.H., Jasechko, S., 2014. Transpiration in the global water cycle. Agricultural
 and Forest Meteorology 189–190, 115–117. doi:10.1016/j.agrformet.2014.01.011
- Steduto, P., Hsiao, T.C., Raes, D., Fereres, E., 2009. Aquacrop-the FAO crop model to
 simulate yield response to water: I. concepts and underlying principles. Agronomy
 Journal 101, 426–437. doi:10.2134/agronj2008.0139s
- Suleiman, A.A., Ritchie, J.T., 2003. Modeling Soil Water Redistribution during Second-Stage
 Evaporation. Soil Science Society of America Journal 67, 377.

- 799 doi:10.2136/sssaj2003.0377
- Suleiman, A.A., Tojo Soler, C.M., Hoogenboom, G., 2007. Evaluation of FAO-56 crop
 coefficient procedures for deficit irrigation management of cotton in a humid climate.
 Agricultural Water Management 91, 33–42. doi:10.1016/j.agwat.2007.03.006
- Torres, E.A., Calera, A., 2010. Bare soil evaporation under high evaporation demand: a
 proposed modification to the FAO-56 model. Hydrological Sciences Journal 55, 303–
 315. doi:10.1080/02626661003683249
- 806 Twine, T.E., Kustas, W.P., Norman, J.M., Cook, D.R., Houser, P.R., Meyers, T.P., Prueger, J.H., Starks, P.J., Wesely, M.L., 2000. Correcting eddy-covariance flux underestimates 807 808 grassland. Agricultural and Forest Meteorology 103. 279-300. over a doi:10.1016/S0168-1923(00)00123-4 809
- Wallace, J.S., 2000. Increasing agricultural water use efficiency to meet future food
 production. Agriculture, Ecosystems and Environment 82, 105–119. doi:10.1016/S01678809(00)00220-6
- Wetzel, P.J., Chang, J.-T., 1988. Evapotranspiration from nonuniform surfaces: a first
 approach for short-term numerical weather prediction. Monthly Weather Review 116.
 doi:10.1175/1520-0493(1988)116<0600:EFNSAF>2.0.CO;2
- Wright, J.L., 1982. New evapotranspiration crop coefficients. Journal of the Irrigation &
 Drainage Division ASCE 108.
- Zhang, Y., Shen, Y., Sun, H., Gates, J.B., 2011. Evapotranspiration and its partitioning in an
 irrigated winter wheat field: A combined isotopic and micrometeorologic approach.
 Journal of Hydrology 408, 203–211. doi:10.1016/j.jhydrol.2011.07.036
- 821