

# A non-invasive radar system for automated behavioural tracking: application to sheep

Alexandre Dore, Cristian Pasquaretta, Dominique Henry, Edmond Ricard, Jean-François Bompard, Mathieu Bonneau, Alain Boissy, Dominique Hazard, Hervé Aubert, Lihoreau Mathieu

# ▶ To cite this version:

Alexandre Dore, Cristian Pasquaretta, Dominique Henry, Edmond Ricard, Jean-François Bompard, et al.. A non-invasive radar system for automated behavioural tracking: application to sheep. 2021. hal-03438808v2

# HAL Id: hal-03438808 https://hal.science/hal-03438808v2

Preprint submitted on 22 Nov 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.

# A non-invasive radar system for automated 2 behavioural tracking: application to sheep

3

Alexandre Dore<sup>1,2</sup>, Cristian Pasquaretta<sup>2</sup>, Dominique henry<sup>1</sup>, Edmond Ricard<sup>3</sup>, Jean François Bompard<sup>3</sup>, Mathieu Bonneau<sup>4</sup>, Alain Boissy<sup>5</sup>, Dominique Hazard<sup>3</sup>, Hervé
 Aubert<sup>1</sup>, Mathieu Lihoreau<sup>2</sup>

7

8 <sup>1</sup> Laboratory for Analysis and Architecture of Systems (LAAS), Toulouse University,

9 CNRS, INPT, F-31400, Toulouse, France

<sup>2</sup> Research Center on Animal Cognition (CRCA), Center for Integrative Biology (CBI);

11 CNRS, University Paul Sabatier – Toulouse III, France

<sup>12</sup> <sup>3</sup>GenPhySE Université de Toulouse, INRAE, ENVT, F-31326 Castanet Tolosan, France

13 <sup>4</sup> Guadeloupe INRAE

<sup>5</sup> UMR Herbivores, Université de Clermont, INRAE, VetAgro Sup, F-63122 Saint-Genès

- 15 Champanelle, France
- 16

# 17 Abstract

18

19 Automated quantification of the behaviour of freely moving animals is increasingly 20 needed in ethology, ecology, genetics and evolution. State-of-the-art approaches often 21 require tags to identify animals, high computational power for data collection and 22 processing, and are sensitive to environmental conditions, which limits their large-scale 23 utilisation. Here we introduce a new automated tracking system based on millimetre-24 wave radars for real time robust and high precision monitoring of untagged animals. To validate our system, we tracked 64 sheep in a standard indoor behavioural test used for 25 26 genetic selection. First, we show that the proposed radar application is faster and more 27 accurate than conventional video and infrared tracking systems. Next, we illustrate how 28 new behavioural estimators can be derived from the radar data to assess personality 29 traits in sheep for behavioural phenotyping. Finally, we demonstrate that radars can be 30 used for movement tracking at larger spatial scales, in the field, by adjusting operating

frequency and radiated electromagnetic power. Millimetre-wave radars thus hold considerable promises for high-throughput recording of the behaviour of animals with various sizes and locomotor modes, in different types of environments.

34

Keywords: computational ethology, radar tracking, behavioural phenotyping, *Ovis aries*,
 corridor test.

37

# 38 **1. Introduction**

39

Animal behaviour research increasingly requires automated recording and analyses of movements (Branson et al., 2009). The emerging field of computational ethology provides methods for high-throughput monitoring and statistical analyses of movements that enable the quantitative characterisation of behaviour on large numbers of individuals, the discovery of new behaviours, but also the objective comparison of behavioural data across studies and species (Anderson and Perona, 2014; Brown and de Bivort, 2018).

47 These quantitative approaches are particularly powerful to study inter-individual behavioural variability or personalities in animal populations (Morand-Ferron et al., 48 49 2015). In livestock, for instance, large-scale genetic selection programmes are based on 50 the measurements of several hundreds (if not thousands) of farm animals (O'Brien et al. 51 2014). Many behavioural tests have been developed to assess behavioural and personality traits in farm animals (Canario et al. 2013), and some applications have 52 53 been developed in breeding programmes for instance to discard the more aggressive individuals for beef cattle production (Phocas et al. 2006). Behavioural measures are 54 55 frequently obtained from direct observations by the experimenters or farmers (e.g., 56 Boissy et al., 2005), limiting use of behavioural criteria for breeding programmes. Indeed, the absence of automated measurements make data collection cumbersome, 57 58 time-consuming and prone to biases, which currently limits the ability to quantify 59 behavioural traits at the experimental or commercial farm level.

60 Tracking methods involving on-board devices, such as Global Positioning 61 Systems (GPS) (Tomkiewicz et al., 2010), radio telemetry (Cadahia et al., 2010), radio frequency identification (RFID) (Voulodimos et al., 2010) or harmonic radar (Riley et al., 1996), are hardly suitable for detailed high throughput behavioural phenotyping due to the limited accuracy and duration of measurements. Best available methods therefore involve image-based analyses (Pérez-Escudero et al., 2014; Romero-Ferrero et al., 2019). However, these techniques often require large computational resources to acquire and process images (Garcia et al 2019) and are sensitive to light variation (Dell et al., 2014).

69 Recently, Frequency-Modulated Continuous-Wave (FMCW) radars operating in the millimetre-wave frequency band have been proposed for automated tracking of 70 71 animal behaviour (sow: Dore et al., 2020b, bees: 2020a; sheep: Henry et al., 2018). In 72 this approach, it is possible to record the 1D movements (distance to radar) of individual 73 sheep in an arena test (Henry et al., 2018). Tracking with FMCW radars has the great 74 advantage of being non-invasive (does not require a tag), insensitive to light intensity 75 variations, and fast (as it does not require large memory resource). FMCW radars 76 therefore provide considerable advantages for the development of automated high-77 throughput analyses in regard to more conventional approaches (e.g. video and infrared 78 tracking systems).

79 Here we developed a millimetre-wave FMCW radar system for automated 80 tracking and analyses of the 2D trajectories of freely moving animals. We illustrated our approach by analysing the behaviour of 64 sheep in an "arena test" commonly used to 81 82 estimate the sociability of individual sheep in genetic selection (Boissy et al., 2005; 83 Hazard et al., 2014). First, we compared the speed and accuracy of radar tracking with 84 more conventional video and infrared tracking systems. We then derived new behavioural estimators computed from the radar data, that could be used for large-scale 85 behavioural phenotyping. Finally, we tested the radar system for long-distance tracking, 86 87 in the field, by adjusting radar emission frequency and radiated electromagnetic power.

- 88
- 89 2. Materials and methods
- 90
- 91 Sheep
- 92

93 We ran the experiments in July 2019 at the experimental farm La Fage of the French 94 National Research Institute for Agriculture, Food, and Environment (INRAE), France 95 (43.918304, 3.094309). We tested 64 lambs (32 males, 32 females) Ovis aries with known weight (range: 12kg - 31.3kg) and age (range: 59 days - 88 days). Ewes and 96 97 their lambs were reared outdoor on rangelands. After weaning, lambs were reared 98 together outside and tested for behaviour 10 days later. This delay allowed the 99 development of social preferences for conspecifics instead of preference for mother. All 100 the lambs were previously tested in a "corridor test" to estimate their docility towards a 101 human. Briefly the test pen consisted of a closed, wide rectangular circuit (4.5 x 7.5 m) 102 with opaque walls (Boissy et al., 2005). A non-familiar human entered the testing pen 103 and moves at constant speed through the corridor until two complete tours had been 104 achieved. Every 5 s (i.e. the corridor was divided into 6 virtual zones and 1 zone was 105 crossed every 5 s by the human) the zones in which the human and the animal were 106 located were recorded and the mean distance separating the human and the lamb was 107 calculated. The walking human also recorded with a stopwatch the total duration when 108 the human saw the head of the lamb to discriminate between fleeing and following 109 lambs. The reactivity criteria towards an approaching human was constructed by 110 combining both measurements (for more details see Hazard et al., 2016). The higher was the resulting variable (i.e. docility variable), the more docile was the animal. 111

112

#### 113 Arena test

114

115 We tested all the sheep in the arena test, a standard protocol for assessing the 116 sociability of sheep through measures of inter-individual variability in social motivation in 117 the absence or presence of a shepherd (Boissy et al., 2005; Hazard et al., 2014). Briefly, 118 a sheep (focal sheep) was introduced in the pen (2mx7m) with artificial lights (Fig. 1A; 119 for more details see Ligout et al. 2011). Three other sheep from the same cohort (social 120 stimuli) were placed behind a grid barrier, on the opposite side of the corridor entrance. 121 The test involved three phases (Fig. 1B). In phase 1, the focal sheep could explore the 122 corridor for 15s and see its conspecifics through a grid barrier. In phase 2, visual contact 123 between the focal sheep and the social stimuli was disrupted using an opaque panel

pulled down from the outside of the pen. This phase was used to assess the sociability of the sheep towards its conspecifics and lasted 60s. In phase 3, visual contact between the focal sheep and its conspecifics was re-established and a man was standing still in front of grid barrier for 60s. This phase was used to assess the sociability of the focal sheep towards conspecifics in presence of a motionless human.

129

#### 130 Data collection

131

We measured the displacement of the focal sheep in phases 2 and 3 of the arena test (phase 1 is the initiation phase) using three automated tracking systems: infrared sensors, a video camera, and a millimetre-wave FMCW radar. During the measures, an experimenter also recorded the number of high-pitched bleats by the focal sheep, a proxy of the sociability (i.e. sociability variable) of the sheep (Boissy et al., 2005).

137

# 138 Tracking with infrared cells

139

Infrared cells were previously used to quantify sheep behaviour in the arena test. We placed two infrared sensors every meter along the arena length (Fig. 1A). We used two infrared sensors to determine the direction of the moving sheep. The focal sheep was recorded each time it passed through one of these sensors. Sheep movements were thus tracked in 1D (longitudinal movements in the corridor) and data resolution was 1m.

145

# 146 Video tracking

147

We placed a video camera on one end of the arena (opposite to entrance side, Fig. 1B). The camera was elevated 2m above ground in order to film the entire arena. Sheep movements were tracked in 2D. For image processing, we applied a detection algorithm using the state-of-the-art image object detector tiny-YOLO (You Only Look Once) network, which is a version of the YOLO model adapted for faster processing allowing 244 images of 0.17 mega pixels (416 x 416 pixels) per second (on a TITAN X graphics 154 card) (Redmon et al., 2016). This neural network was pre-trained on the PASCAL Visual
155 Object Classes Challenge dataset (Everingham et al., 2012).

156

#### 157 Radar tracking

158

159 We placed a millimetre-wave FMCW radar (Fig. 1C, see technical characteristics in 160 Table 1) at one end of the arena (entrance side, Fig. 1B). The radar was setup outside 161 of the test pen behind a Styrofoam wall transparent to millimetre-wave (Dietlein et al., 2008). The transmitting antenna array radiated a repetition over time of a so-called chirp 162 (i.e. a saw-tooth frequency-modulated signal (Balanis, 2011)). The chirp was 163 164 backscattered by the targeted focal sheep, but also by the surrounding scene which 165 provides undesirable radar echoes called the electromagnetic clutter. The total 166 backscattered signal was then collected by the receiving antenna array and processed 167 to mitigate the clutter and to derive the sheep 2D trajectory from radar data. In the 168 millimetre-wave frequency range, the detectability of the sheep depends mainly on the 169 bandwidth of the frequency modulation, the beamwidth of the radar antennas, and the 170 radiated electromagnetic power (Balanis, 2011)).

171

# 172 Radar signal processing

173

Processing of radar data included two main steps. First, we extracted the position of the animal. Next, we computed behavioural parameters to characterize the movement of the animal.

# 178 Extraction of sheep positions

179

We extracted the distance of the focal sheep to the radar and its direction in the horizontal plane of the scene. To mitigate the electromagnetic clutter, we estimated the mean value (*mean*) and standard deviation (*std*) of the signal provided by the radar in absence of the sheep and derived the signal *Detection*( $r, \theta$ ) from the signal S<sub>radar</sub>( $r, \theta$ ) delivered in presence of the animal, as follows:

$$Detection(t, r, \theta) = \frac{S_{radar}(t, r, \theta) - mean(r, \theta)}{std(r, \theta)}$$

185 Where *r* is the distance to the sheep, *mean* is the time-averaged signal radar coming 186 from the range *r* and angular position  $\theta$ , *std* is the time-standard deviation of the radar 187 signal. Fig. 1D shows an example of position estimations of a sheep over time after 188 removing the clutter.

189

# 190 Extraction of new behavioural parameters

191

192 From the 2D trajectory data, we extracted new behavioural parameters to characterize193 sheep movements using three approaches.

194

# 195 Computation of behavioural classes

196

197 We statistically identified broad classes of behaviour using automated classification. 198 First, we extracted movement parameters (speed, sinuosity and speed of displacement) 199 from the trajectories. Then, to differentiate the movement modifying the distance of the 200 sheep from the social stimuli (i.e. the three conspecifics) and a lateral movement, the 201 speed vector was split in two dimensions: along the two lateral walls of the corridor and 202 across the two longitudinal walls. These characteristics were estimated on time windows 203 of 1s for each sheep and for each experimental phase. Finally, to derive behavioural 204 classes, we performed an extraction from a Gaussian mixture model using the extracted 205 data for each lamb (Reynolds and Rose, n.d.). The number of classes (i.e. the number of Gaussians to be used) was determined by comparing models using 1 to 15 classes.
We selected the model with the lowest Akaike score which represents the model with
the features best explaining the parameter under consideration (Burnham and
Anderson, 2002).

- 210
- 211 Computation of behavioural transitions
- 212

213 We determined behavioural changes over time using Ricker wavelet processing (Ryan, 214 1994; see examples Fig. 3). Wavelet processing consists in filtering the sheep position 215 signal using a wavelet as a filter (Poirier et al., 2009). This type of filtering is applied to 216 several time scales, thus allowing the detection of a behaviour regardless of how long 217 this behaviour lasts. Our aim was to determine the precise moments when the focal 218 sheep changed its moving behaviour, which was estimated using the spectrum 219 described by each wavelet. We observed that the number of local maxima in the wavelet 220 transform coefficients is sensitive to the number of behaviour changes (see example in 221 Fig. S1B).

222

# 223 Computation of space coverage

224

225 We investigated the space occupied across time by the focal sheep using heatmaps 226 (see examples Fig. 4). We partitioned the arena into 80 zones of 44x40cm each (i.e. 16 227 partitions along the arena length and 5 partitions along the arena width). We chose this 228 zone dimension because it corresponded to the width of a small lamb (Idris et al., 2011). 229 We counted the number of zones the focal sheep remained in for more than 200ms. We 230 considered that a lamb stayed in a given zone for less than 200ms either because it was 231 positioned at the edge of this zone or because the estimation of position by the radar was inaccurate (this situation occurred for less than 10% of detections). 232

- 234 Outdoor radar tracking
- 235

236 We ran outdoor experiments in order to demonstrate the applicability of our radar 237 system for long-range tracking of sheep (Fig. 4). These measurements where done in 238 an open space with no obstacles (60m x 15m). A man moved in order to induce animal 239 movements. We tested one female sheep (2 years, 60 Kg). To enhance detection range 240 to 40 m, we used a FMCW radar with a lower operating frequency (24GHz; (Simon et 241 al., 2014)). At constant transmitted power, lower frequencies enables to reduce the free-242 space attenuation of the radiated electromagnetic power (Balanis, 2011). We used the 243 same signal processing as with the 77GHz radar.

244

#### 245 Statistical analyses

246

We ran all analyses using the programming environment R(R Core Team, 2014). Raw trajectory data extracted from radar and video measures are available in Dataset S1.

249

# 250 Comparison of the performances of the different tracking systems

251

252 We tested the ability of radar and video tracking systems to capture the same 253 information as the infrared cells from the computation of two parameters: (1) a crossing 254 rate and (2) a proximity score (respectively LOCOM and PROX in Hazard et al. 2014). 255 The crossing rate is the number of times the animal moved between virtual zones 256 defined by the infrared cells (1x2m) without distinguishing between the zones nor the 257 direction of movement. This rate thus provides information on the displacement activity 258 of animals seeking contact with their conspecifics. The proximity score is the total 259 duration the focal sheep remained in each zone weighted as the animal moves closer to 260 its conspecifics. The weight depends on the distance between the sheep and the 261 conspecifics:

$$w_i = \frac{1}{i}$$

with  $w_i$  the weight of the zone considered, *i* the index of the zone delimited by the infrared sensors. *i* = 1 corresponds to the zone close to the conspecifics, and *i* = 7 corresponds to the zone close to the corridor entrance. Thus, an animal with a high proximity score spent more time close to its conspecifics. We calculated these two parameters from data collected from infrared cells, video and radar tracking systems
 and compared them using Pearson's correlation tests (using 'stats' R package).

We compared the accuracy of radar and video data systems by running a general linear mixed model (GLMM using glmer function in 'Ime4' R package (Bates et al., 2014)) testing the effect of the tracking method on the proportion of false detections, with sheep identity as random factor. We estimated the correlation between the number of false detections with the two methods using the Pearson's correlation test.

273

#### 274 Analyses of new movement features

275

276 We tested the influence of the sheep characteristics on behavioural classes using 277 generalised models (GLMMs). Models (binomial family) tested the effects of phase, 278 docility, weight, age, sociability, sex, and dual interactions of each variable with test 279 phase, on the proportion of time spent in fast movements (behavioural class 2). 280 Interactions between more than two variables were excluded because of the high 281 number of variables relative to sample size. Sheep identity was included as a random 282 factor. We ran a model selection by using all features combinations (age, weight, 283 docility, sociability, sex and the phase when the radar measurement was done). We kept 284 the model with the highest Akaike score. We used a similar procedure to test the 285 influence of the sheep characteristics of the lambs on continuous wavelet transforms 286 (Gaussian models) and heatmaps (Poisson models). For the continuous wavelet 287 transform, we performed two different wavelet transforms on the lateral and on the 288 longitudinal position of the sheep. For heatmaps, we tested different grid resolutions 289 characterised by zone sizes: a low resolution grid with 21 zones (3 x 7) and a high 290 resolution grid with 45 zones (5 x 15).

291

#### 292 <u>Classification of behavioural types</u>

293

To classify sheep from on our new behavioural estimators, we ran a principal component analysis (PCA) based on the eight behavioural measures extracted from the radar data in phase 2 and phase 3: proportion of fast movements (class 1) out of all 297 movements (class 1 + class 2), longitudinal movements (wavelets Y), latitudinal 298 movements (wavelets X), space coverage (heatmaps).

299

### 300 **3. Results**

301

# 302 Radar tracking is more faster and more accurate than video tracking

303

To validate the radar tracking system, we compared the data obtained from the infrared cells, video and radar. We analysed data from 58 (29 males, 29 females) out of the 64 sheep initially tested, because some recordings failed during measurements due to human errors or miss detection by infrared cells.

308 Both data collected by radar and video enabled to capture information given by 309 infrared cells with high fidelity. Proximity scores and crossing rates obtained from 310 infrared cells were positively correlated with data obtained from radar (Pearson 311 correlation; proximity: r = 0.77, p < 0.001; crossing rate: r = 0.87, p < 0.001) and video 312 (Pearson correlation test; proximity: r = 0.91, p < 0.001; crossing rate: r = 0.34, p =313 <0.001). Imperfect correlation between proximity scores and crossing rates obtained 314 from different tracking methods are caused by the different reference points used for tracking: infrared cells detect the full body of the sheep, whereas image analysis detects 315 316 the centre of mass of the sheep, and the radar detects body parts of the sheep that are 317 closest to it.

318 The comparison between the radar and the video data showed both tracking 319 systems involved low levels of false detections (i.e. when the distance between the body 320 centre of the sheep and its estimated position is greater than one sheep body length). 321 However, radar tracking generated ca. three times less false detections than video 322 tracking (Binomial GLMM, z = -3.595, p < 0.001; Table 2). False detection with the two 323 methods had different origins. False video detections resulted from insufficient colour 324 contrast between the lamb and the background (e.g. when the lamb was close to the 325 wall of the corridor), whereas false radar detections resulted from the low angular 326 resolution of the radar and potential multiple reflections of the transmitted 327 electromagnetic signal by obstacles in the scene (such as walls, ground, human). Radar and video tracking systems are therefore complementary. The combination of the two
 systems gave the exact position of the sheep in 97.83% of the measures.

330 Radar tracking had additional advantages over video tracking in terms of data 331 processing (Table 2). The radar produced two times more measures per second. Radar 332 processing was also much faster and therefore it may be used for real time data 333 analyses. Radar measures were of similar size as video measures (ROM), but required 334 ca. 7 times less memory (RAM) to process. Finally, radar processing did not require a 335 learning phase with important data collection and a time-consuming training phase that 336 can last several hours just for the adaptation of the model, or several days if the network 337 is not trained beforehand.

338

#### 339 New behavioural indicators from radar data

340

The following analyses were made on the 64 sheep tested (32 males, 32 females). The obtained 2D trajectory data offered the opportunity for high resolution analyses of sheep movements.

344

# 345 Behavioural classes: detection of slow and fast movements

346

347 We applied a Gaussian Mixture Model (GMM) procedure to statistically identify 348 behavioural classes from the 2D trajectory data. We found four behavioural classes (Fig. 349 2A). Class 1 (51.3% of measures) was characterized by null or slow movements ("slow 350 movements"). Class 2 (35.48% of measures) was characterized by fast movements with 351 low sinuosity ("fast movement"). Class 3 (10.2% of measures) was characterized by fast 352 movements with high sinuosity ("fast tortuous"). Class 4 (3.01% of measures) was 353 characterized by slow movements with high sinuosity ("slow tortuous"). Each of the two 354 behavioural classes with strong sinuosity (classes 3 and 4) represented less than 10% 355 of all data. We thus focused our analyses on slow and fast movements (classes 1 and 356 2).

357 We tested the effects of the individual characteristics of sheep on time spent in 358 each behavioural class using GLMMs. Results of the best model (i.e. highest Akaike score) are summarized in Table 3 (see model selection in Table S1). Male, old, large
and highly docile sheep spent significantly more time in slow movement during phase 3
than during phase 2 (Fig. 2C). Highly sociable sheep also spent more time in slow
movements during phase 3 than during phase 2 (Fig. 2D).

363

# 364 <u>Wavelet analyses: detection of erratic behavioural transitions</u>

365

366 We quantified behavioural changes during time (variation in speed, direction, or both) 367 using continuous wavelet analyses. We tested the effects of the individual characteristics of sheep on the frequency of behavioural changes using GLMMs and 368 369 model selection (Tables S2 and S3). When considering longitudinal movements along 370 the corridor length (Table 4A), we found that males made more behavioural transitions 371 in phase 3 than in phase 2. Highly sociable sheep made more behavioural transitions in 372 phase 3 than in phase 2 (Fig. 3A). When considering latitudinal movements along the 373 corridor width (Table 4B), we found that highly docile sheep made more behavioural 374 transitions in phase 3 than in phase 2 (Fig. 3B). Thus overall, wavelet analyses of 375 longitudinal movements can be used as a proxy of sociability, and analyses of latitudinal 376 movements give information about docility.

377

# 378 Heatmap analyses: Detection of occupied space

379

380 We quantified spatial coverage by individual sheep (number of zones occupied in the 381 corridor) using heatmaps. We tested the effects of the individual characteristics on the 382 number of zones in which the sheep spent more than 200ms using GLMMs and model 383 selection (Tables S4 and S5). When considering a grid with low spatial resolution, i.e. 384 similar zone dimensions as with infrared cells (i.e., dimension: 0.6 x 1m; example Fig. 4A), we found that sheep used 2.37 times less space in phase 3 than in phase 2 (Table 385 386 5A). Larger individuals used more space than smaller ones (Table 5A). Increasing the 387 spatial resolution of the grid, i.e. similar zone dimension as a lamb body size (i.e. 388 dimension: 0.44 x 0.40 m; example Fig 4A), revealed that highly docile sheep used more 389 space in phase 3 than in phase 2 (Table 5B). Young and highly social individuals used 390 more space than old and poorly social individuals in both phases. Body size effect, 391 however, was not significant anymore. Therefore, heatmap analyses are sensitive to 392 grid size resolution. Decreasing grid size increased behavioural resolution.

393

#### 394 Sheep behavioural phenotype

395

We explored whether the new behavioural measures extracted from the radar data could capture information from behavioural traits measured manually by the experimenter in the corridor test. We focused on docility and sociability.

399 We ran a PCA based on the eight behavioural measures extracted from the radar data in phase 2 and phase 3: proportion of fast movements (class 1) out of all 400 401 movements (class 1 + class 2), longitudinal movements (wavelets Y), latitudinal 402 movements (wavelets X), space coverage (heatmaps). We retained two PCs using the 403 Kaiser-Guttman criterion (Kaiser, 1991). PC1 explained 36% of the variance and PC2 404 explained 22% of the variance. PC1 was positively associated with all behavioural 405 variables (Fig. 5A). Sheep with high PC1 values moved more often faster, made more 406 behavioural transitions, and used more zones than sheep with low PC1 values. We 407 therefore interpreted PC1 as a "movement speed" variable. PC2 was positively 408 associated with the four behavioural variables of phase 3 and negatively associated with 409 the four behavioural variables of phase 2 (Fig. 5A). Sheep with high PC2 values showed 410 a more important increase of time spent moving fast, of the frequency of behavioural 411 transitions, and numbers of zones occupied from phase 2 to phase 3 than sheep with 412 low PC2 levels. We interpreted PC2 as a variable of "movement increase between 413 phases".

Sociability was significantly explained by PC1 (LM, PC1: estimate = 0.027, t = 2.552, p = 0.014; PC2: estimate = -0.104, t = -0.764, p = 0.448; Fig. 5B). Docility was significantly explained by PC2 (LM, PC1: estimate = -0.081, t = -0.943, p = 0.350; PC2: estimate = 0.283, t = 2.547, p = 0.014; Fig. 5C). Therefore, the automatically extracted radar data can capture inter-individual variability in sociability and docility traits usually measured by experimenters.

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.

#### 421 **Outdoor radar tracking**

422

423 To demonstrate that our tracking system can be used in various experimental contexts,

424 we tracked sheep in an outside corridor at a larger spatial scale (10 x 60m; Fig. 6A). We

- 425 monitored the 2D trajectory of one sheep over a maximum distance of 45m (Fig. 6B).
- 426 The presence of the man to induce sheep movement did not impair tracking (Fig. 6C).
- 427

# 428 **Discussion**

429

430 Research in behaviour and ecology increasingly requires automated monitoring and 431 annotation of animal movements for comparative quantitative analyses (Anderson and 432 Perona, 2014; Brown and de Bivort, 2018). Here we introduced a radar tracking system 433 suitable to study the 2D movements of sheep within a range of 45 m. The system is non-434 sensitive to light variations, compatible with real time data analyses, transportable, fast 435 processing and adaptable to various species and experimental contexts. Moreover, it 436 does not require to use tags or transponders for tracking the animals. It is therefore 437 suitable for the collection of large sets of behavioural data in an automated way required 438 in many areas of biological and ecological research.

439 FMCW radars were recently used to track sheep and pigs in 1D (Dore et al., 440 2020b; Henry et al., 2018) and bees in 3D (Dore et al., in press). Here, for the first time, 441 we demonstrate the applicability of this approach to monitor 2D trajectories of untagged 442 walking animals within a range of 45 meters with high spatial resolution. Radar 443 acquisition system has several advantages over more conventional methods, and in 444 particular video tracking, as it collects more data per seconds, requires less RAM, less 445 processing time (e.g. does not require to train neural networks) and generates less false 446 detection rates. It can therefore be applied for real-time detection of animal position. 447 Importantly, the radar is not dependent on brightness and can be used for outside tracking over long distances by adjusting operating frequencies. It also enables the 448 449 tracking of individualised animals without tags, based on the size and shape of the radar 450 echoes of the different targets. Others methods can be used to estimate the sheep 451 position. The main two methods are video detection (Bonneau et al., 2020), which can detect sheep in 2D up to 25m but with a precision of about 2m, and GPS detection(Gwyn et al., 1995), but this requires to animals.

454 Our application of radar-based tracking to behavioural phenotyping of sheep 455 shows that the radar analysis is consistent with current manual or semi-automated 456 analyses. we found that sheep tend to have a greater displacement in phase 2 than in 457 phase 3 of the corridor test. This is consistent with previous work showing that sheep 458 are more active when socially isolated, presumably as the result of them searching for 459 social contact with conspecifics. These docile animals tend to move less when they are 460 in contact with men. Importantly, the high resolution 2D trajectories obtained from the 461 radar enabled to identify new behavioural estimators that could greatly benefit the fast 462 and automated identification of behavioural phenotypes. These different estimators are 463 not dependent on the radar tracking system per se, but requires to detect the position of 464 the sheep with sufficient time resolution. For example, our application of unsupervised 465 behavioural annotation to identify statistically significant behaviours by sheep in the 466 corridor test showed that sheep exhibit less fast movements in phase 3 than in phase 2. 467 Our utilisation of wavelet analyses revealed the occurrence of erratic displacements. 468 The more the sheep was sociable the more it made erratic longitudinal movements. The 469 more the sheep was docile, the more it made erratic latitudinal movements. We also 470 analysed space occupation by sheep, showing that individuals exploit narrower areas in 471 phase 3 than in phase 2. All these results are consistent with previous observations 472 using manual or semi-automated recording methods. Most importantly, the combination 473 of these new automatically computed estimators appears to be correlated with 474 behavioural traits of interest that were until now measured manually by an experimenter 475 during the corridor test or in complementary tests (e.g. carousel test). Therefore, in 476 principle, our automated tracking and analysis system can be used for automated 477 classification of animal behavioural profiles, which is a major issue for mass phenotyping 478 in animal selection (Beausoleil et al., 2012). Note however that our pioneering study is 479 based on relatively low sample sizes (64 individuals) and further measurements are 480 needed to verify the biological trends observed on a much larger number of sheep.

481 Beyond genetic selection of farm animals, our system can be tuned to suit a large 482 diversity of animal sizes and experimental contexts. Range and resolution of detection 483 can be improved using different radars. For instance, we had to placed the radar at 1 484 meter from the corridor in order to track the entire corridor area. But with other antennas 485 and a radar with larger field of view could have been placed at the edge of the corridor. 486 Moreover, the detection was limited to a few meters but it is possible to detect a sheep 487 at tens of meters using a radar operating at a lower frequency (24GHz) and/or 488 transmitting higher electromagnetic power. It is also possible to improve radar detection 489 by using more antennas. Indeed, by multiplying the number of antennas, we multiply the 490 number of signal estimations and then the noise from the radar can be decreased. In the 491 future, the same radar technology could be used to track individuals in groups over 492 longer distances in open fields, for instance to explore the mechanisms underpinning 493 social network structures and collective behaviour (Ginelli et al., 2015; King et al., 2012). 494 Furthermore, it is possible to improve the processing of the radar signal for tracking 495 large number of sheep simultaneously by using deep radar processing but this would 496 require the use of a large amount of annotated data to train the neural networks (Huang 497 et al., 2018). Individual tracking within groups could be improved with non-invasive 498 passive tags that depolarize radar signal in specific directions (Lui and Shuley, 2006).

499 To conclude we demonstrate the feasibility of tracking a sheep in a restricted 500 area using a FMCW radar. This detection is possible even if each wall of the corridor 501 backscatters the transmitted electromagnetic signal. This radar can also be 502 advantageously used to extract features that are relied to the movement of the sheep 503 and can estimate if it is erratic, fast and the space occupied in the corridor. In contrast to 504 other short-range methods, this 2D detection method does not require pre-annotated 505 data and can be applied in real time. This flexibility holds considerable premises for 506 tracking the behaviour of animals of various sizes and environments in a wide range of 507 contexts and research fields.

508

# 509 Acknowledgements

510

AD was funded by a PhD fellowship from the Council of the Région Occitanie (SIDIPAR Project). HA and ML also received support from grant of the French National Research Agency (ANR-DFG 3DNaviBee; ANR TERC BEE-MOVE).

# 515 **References**

- Anderson, D.J., Perona, P., 2014. Towards a science of computational ethology. Neuron 84, 18–31.
- 518 Balanis, C.A., 2011. Modern antenna handbook, John Wiley&Sons. ed.
- 519 Bates, D., Maechler, M., Bolker, B., Waleker, S., 2014. lme4: linear mixed-effects models using
- 520 Eigen and S4. R package version 1.
- 521 Beausoleil, N.J., Blache, D., Stafford, K.J., Mellor, D.J., Noble, A.D.L., 2012. Selection for
- temperament in sheep: Domain-general and context-specific traits. Applied Animal BehaviourScience 139.
- 524 Boissy, A., Bouix, J., Orgeur, P., Poindron, P., Bibe, B., Le Neindre, P., 2005. Genetic analysis
- 525 of emotional reactivity in sheep: effects of the genotypes of the lambs and of their dams. Genetics 526 Selection Evolution 37, 381–401.
- 526 Selection Evolution 37, 381–401.
- 527 Bonneau, M., Vayssade, J.A., Troupe, W., Arquet, R., 2020. Outdoor animal tracking combining
- neural network and time-lapse cameras. Computers and Electronics in Agriculture 168.
- 529 Branson, K., Robie, A.A., Bender, J., Perona, P., Dickinson, M.H., 2009. High-throughput
- 530 ethomics in large groups of Drosophila. Nat Methods 6, 451–457.
- 531 Brown, A.E.X., de Bivort, B., 2018. Ethology as a physical science. Nat Phys 14, 653–657.
- Burnham, K.P., Anderson, D.R., 2002. Model selection and multimodel inference: a practical
  information-theoretic approach, 2nd Edition. ed. Springer, New York, NY.
- 534 Cadahia, L., López-López, P., Urios, V., Negro, J.J., 2010. Satellite telemetry reveals individual
- 535 variation in juvenile Bonelli's eagle dispersal areas. European Journal of Wildlife Research 56.
- Canario, L., Mignon-Grasteau, S., Dupont-Nivet, M., Phocas, F., 2013. genetics of behavioural
   adaptation of livestock to farming conditions. Animal 7, 357-377.
- 538 Dell, A.I., Bender, J.A., Branson, K., Couzin, I.D., de Polavieja, G.G., Noldus, L., Pérez-
- 539 Escudero, A., Perona, P., Straw, A.D., Wikelski, M., Brose, U., 2014. Automated image-based
- 540 tracking and its application in ecology. Trends Ecol Evol 29, 417–428.
- 541 https://doi.org/10.1016/j.tree.2014.05.004
- 542 Dietlein, C.R., Bjarnason, J.E., Grossman, E.N., Popovic, Z., 2008. Absorption, transmission, and
- 543 scattering of expanded polystyrene at millimeter-wave and terahertz frequencies. Passive
- 544 Millimeter-Wave Imaging Technology XI 6948–69480.
- 545 Dore, A., Henry, D., Aubert, H., Lihoreau, M., 2020a. 3D trajectories of multiple untagged flying
- 546 insects from millimetre-wave beamscanning radar. Presented at the IEEE International
- 547 Symposium on Antennas and Propagation and Notth American Radio Science Meeting, Québec,548 Canada.
- 549 Dore, A., Henry, D., Aubert, H., Lihoreau, M., in press. 3D trajectories of multiple untagged
- 550 flying insects from millimetre-wave beamscanning radar. IEEE Antennas and Propagation.
- 551 Dore, A., Lihoreau, M., Billon, Y., Ravon, L., Reignier, S., Bailly, J., Bompa, J.F., Ricard, E.,
- 552 Aubert, H., Henry, D., Canario, L., 2020b. Millimeter-wave Radars for the Automatic Recording
- of Sow Postural Activity. Presented at the 71st Annual Meeting of European Federation ofAnimal Science, Porto, Portugal.
- 555 Everingham, M., Van Gool, L., Williams, C.K.I., Winn, J., Zisserman, A., 2012. Results 2012.
- 556 The PASCAL Visual Object Classes Challenge 2012 (VOC2012).
- 557 Ginelli, F., Peruani, F., Pillot, M.H., Chaté, H., Theraulaz, G., Bon, R., 2015. Intermittent
- 558 collective dynamics emerge from conflicting imperatives in sheep herds. Proc Natl Acad Sci

- 559 USA 112, 12729–12734.
- 560 Gwyn, R., Williams, A., Last, J.D., Penning, P.D., Mark Rutter, S., 1995. A Low-Power
- 561 Postprocessed DGPS System for Logging the Locations of Sheep on Hill Pastures. Navigation562 42.
- 563 Haderer, A., Wagner, C., Feger, R., Stelzer, A., 2008. A 77-GHz FMCW front-end with FPGA
- and DSP support, in: 2008 International Radar Symposium. pp. 1–6.
- 565 Hazard, D., Moreno, C., Foulquié, D., Delval, D., François, D., Bouix, J., Sallé, G., Boissy, A.,
- 566 2014. Identification of QTLs for behavioral reactivity to social separation and humans in sheep
- using the OvineSNP50 BeadChip. BMC Genomics 15, Artilce 778.
- 568 Hazard, D., Bouix, J., Chassier, M., Delval, E., Foulquié, D., Fassier, T., Bourdillon, Y.,
- François, D., Boissy, A., 2016. Genotype by environment interactions for behavioral reactivity in
  sheep. J Anim Sci 94, 1459-1471.
- 571 Henry, D., Aubert, H., Ricard, E., Hazard, D., Lihoreau, M., 2018. Automated monitoring of
- 572 livestock behavior using frequency-modulated continuous-wave radars. Prog Electromagn Res 69,573 151–160.
- 574 Huang, H., Gui, G., Sari, H., Adachi, F., 2018. Deep learning for super-resolution DOA
- 575 estimation in massive MIMO systems. Presented at the IEEE 88th Vehicular Technology
- 576 Conference (VTC-Fall).
- 577 Idris, A., Moors, E., Budnick, C., Herrmann, A., Erhardt, G., Gauly, M., 2011. Is the
- 578 establishment rate and fecundity of Haemonchus contortus related to body or abomasal
- 579 measurements in sheep? Animal 5, 1276–1282.
- 580 Kaiser, H.F., 1991. Coefficient alpha for a principal component and the Kaiser-Guttman rule.
  581 Psychol Rep 68, 855–858.
- 582 King, A.J., Wilson, A.M., Wilshin, S.D., Lowe, J., Haddadi, H., Hailes, S., Morton, J., 2012.
- 583 Selfish-herd behaviour of sheep under threat. Curr Biol 22, R561-562.
- 584 Ligout, S., Foulquié, D., Sèbe, F., Bouix, T., Boissy, A., 2011. Assessement of sociality in farm
- animals: the use of the arena test in lambs. Appl Anim Behav Sci 135, 57-62.
- 586 Lui, H.S., Shuley, N., 2006. Resonance based radar target identification with multiple
- 587 polarizations. Presented at the EEE Antennas and Propagation Society International Symposium.
- 588 Morand-Ferron, J., Cole, E.F., Quinn, J.L., 2015. Studying the evolutionary ecology of cognition
- in the wild: a review of practical and conceptual challenges. Biol Rev 91, 367–389.
- 590 Pérez-Escudero, A., Vicente-Page, J., Hinz, R.C., Arganda, S., de Polavieja, G.G., 2014.
- 591 idTracker: tracking individuals in a group by automatic identification of unmarked animals. Nat
- 592 Methods 11, 743–748. https://doi.org/10.1038/nmeth.2994
- 593 Phocas, F., Boivin, X., Sapa, J., Trillat, G., Boissy, A., Le Neindre, P., 2006. Genetic correlations
- between temperament and breedng traits in Limousin heifers. Animal Science 82, 805-811.
- 595 Poirier, J.R., Aubert, H., Jaggard, D.L., 2009. Lacunarity of rough surfaces from the wavelet
- analysis of scattering data. IEEE Transactions on Antennas and Propagation 57, 2130–2136.
- 597 R Core Team, 2014. R: a Language and Environment for Statistical Computing, R Foundation for
- 598 Statistical Computing. ed. Vienna, Austria.
- 599 Redmon, J., Divvala, S., Girshick, R., Farhadi, A., 2016. You Only Look Once: Unified, Real-
- 600 Time Object Detection. Proceedings of the IEEE Conference on Computer Vision and Pattern
- 601 Recognition 779–788.
- 602 Reynolds, D.A., Rose, R.C., n.d. Robust text-independent speaker identification using Gaussian
- mixture speaker models. IEEE Transactions on Speech and Audio Processing 3, 72–83.
- Riley, J.R., Smith, A.D., Reynolds, D.R., Edwards, A.S., Osborne, J.L., Williams, I.H., Carreck,
- N.L., Poppy, G.M., 1996. Tracking bees with harmonic radar. Nature 379, 29–30.

- 606 https://doi.org/10.1038/379029b0
- 607 Romero-Ferrero, F., Bergomi, M.G., Hinz, R.C., Heras, F.J.H., de Polavieja, G.G., 2019.
- 608 idtracker.ai: tracking all individuals in small or large collectives of unmarked animals. Nature
- 609 Methods 16, 179–182.
- Ryan, H., 1994. Ricker, Ormsby, Klauder, Butterworth A choice of wavelets. CSEG Recorder8–9.
- 612 Simon, W., Klein, T., Litschke, O., 2014. Small and light 24 GHz multi-channel radar. Presented
- 613 at the IEEEAntennas and Propagation Society International Symposium (APSURSI).
- Tomkiewicz, S.M., Fuller, M.R., Kie, J.G., Bates, K.K., 2010. Global positioning system and
- 615 associated technologies in animal behaviour and ecological research. Philosophical Transactions
- of the Royal Society B. https://doi.org/10.1098/rstb.2010.0090
- 617 Voulodimos, A.S., Patrikakis, C.Z., Sideridis, A.B., Ntafis, V.A., Xylouri, E.M., 2010. A
- 618 complete farm management system based on animal identification using RFID technology.
- 619 Computers and Electronics in Agriculture 70, 380–388.
- 620 https://doi.org/10.1016/j.compag.2009.07.009
- 621
- 622

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.

# 623 Tables

624

- 625 **Table 1**: Technical characteristics of the FMCW radar used for indoor tracking (Haderer
- 626 et al., 2008) and outdoor tracking (Simon et al., 2014).

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.

Name	maoor	Outdoor	Note
	tracking	tracking	
Operating	77GHz	24GHz	This frequency is also called the
frequency			carrier frequency of the frequency-
			modulated signal transmitted by the
			radar
Modulation	3GHz	800MHz	Frequency interval, centred at the
Bandwidth			operating frequency, used for the
			saw-tooth frequency modulation of
			the transmitted signal
Resolution	5cm	18.75cm	Resolution $=\frac{c}{2B}$ , with c the celerity
			and B the modulation bandwidth
Ramp time	256 µsec	1ms	Up-ramp duration of the saw-tooth
			frequency-modulated signal (or
			chirp duration)
Repetition time	50ms	30ms	Period of the transmitted frequency-
			modulated signal (or chirp repetition
			interval)
Number of linear	4	1	One linear array composed of 8x2
arrays in the			rectangular patches radiating
transmitting array			elements
antenna			
Number of linear	8	2	Eight linear arrays composed of 8
arrays in the			rectangular patches radiating
receiving array			elements
antenna			
Main lobe	50°	58°	Angular range (or field of view) of
beamwidth of the			the radar illumination in the
transmitting array			horizontal plane
antenna in the			
horizontal plane			
Transmitted	100mW	100mW	Power delivered at the input
			terminals of the transmitting array

antenna (the radiated power is
defined as the product of the
transmitted power by the efficiency
of the antenna)

Table 2: Comparison of data processing characteristics with radar and video tracking systems.

Tracking method	Radar	Video
Number of measures per second	50	25
Read Only Memory (ROM) for all measures of a	151Mo	62Mo
sheep		
Random Access Memory (RAM) per measure	524Kb	3.7Mb
Processing time per measure	<20ms	250ms
Total false detection rate	6%	16%

**Table 3:** Analyses of behavioural classes. Results of the best GLMM (binomial family, after model selection – see Table S1). The model tested the effects of phase, docility, weight, sex, age, sociability, and dual interaction of each variable with phase, on the proportion of time spent in fast movements (behavioural class 2). Sheep identity was included as a random factor. Significant effects (p<0.05) are shown in bold.

643

Variable	Estimate	z-value	P-value
Phase	-1.272453	-102.321	< 0.001
Docility	-0.134811	-2.725	0.006
Weight	0.042312	0.753	0.451
Sex	-0.018224	-0.165	0.869
Age	-0.095193	-1.673	0.094
Sociability	0.137659	3.596	< 0.001
Phase x docility	0.156352	19.868	< 0.001
Phase x weight	0.046431	5.223	< 0.001
Phase x sex	0.068090	3.882	< 0.001
Phase x age	0.078200	8.537	< 0.001
Phase x sociability	-0.127900	-20.900	< 0.001

644

645

646

**Table 4:** Wavelet analyses. Results of the best GLMM (Poisson family, after model selection – see details in Tables S2 and S3). The model tested the effects of phase, docility, weight, sex, age, sociability, and binary interactions of each variable with phase, on the number of wavelets. Lamb identity was included as a random factor. Significant effects (p<0.05) are shown in bold. Wavelet Y: longitudinal movements. Wavelet X: latitudinal movements.

	Variable	Estimate	t-value	P-value
Wavelet	Phase	513.352	54.603	<0.001

Y	Sex	-11.392	-0.835	0.405
	Weight	2,417	0.349	0.727
	Age	-3,875	0,552	0.582
	Docility	-3.342	-0,548	0.585
	Sociability	17.371	3.679	<0.001
	Phase x sex	38.656	2.103	0.0403
	Phase x weight	1.941	0.208	0.836
	Phase x age	-2.426	-0.257	0.798
	Phase x docility	1.253	0.152	0.879
Wavelet	Phase	-67.0684	-5.68335	< 0.001
Х	Sex	-2.70137	-0.21731	0.828
	Weight	-1.28441	-0.203557	0.839
	Age	-0.193189	-0.0302208	0.976
	Docility	-9.23551	-1.66137	0.100
	Sociability	0.669471	0.155654	0.877
	Phase x sex	27.8832	1.64681	0.106
	Phase x weight	-5.40654	-0.629084	0.532
	Phase x age	-1.34492	-0.154463	0.878
	Phase x docility	17.9056	2.36483	0.022
	Phase x sociability	7.0736	1.207	0.233

**Table 5:** Heatmap analyses. Results of the best GLMM (Poisson family, after model selection – see details in Tables S4 and S5). The model tested the effects of phase, docility, weight, sex, age, sociability, and dual interactions of each variable with phase, on the number of areas where the lamb spent more than 1s. Sheep identity was included as a random factor. Significant effects (p<0.05) are shown in bold. A. Low spatial resolution. B. High spatial resolution.

662


	Variable	Estimate	t-value	P-value
А	Phase	-0.597701	-9.20941	< 0.001
	Weight	0.0615106	1.99628	0.046
	Sociability	0.0365622	1.63703	0.102
В	Sex	0.0188161	0.299427	0.765
	Age	-0.0653912	-2.04381	0.041
	Phase	-0.765708	-14.4685	< 0.001
	Docility	-0.0837715	-2.665	0.008
	Sociability	0.0480015	2.19218	0.029
	Weight	0.0407016	1.27774	0.201
	Phase x docility	0.0978634	2.15262	0.031

663

664


665 Figures

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.



667


Figure 1: Corridor test. A. Top view of the focal sheep and the social stimuli in the corridor (example image extracted from video data). B. schematic representation of experiments phases 1, 2 and 3. C. Image of the FMCW radar frontend (phot credit AD). Each rectangle corresponds to rectangular patch (Haderer et al., 2008). D. Example of position estimations of a sheep over time after removing the clutter and normalizing the estimated value.



**Figure 2:** Analyses of behavioural classes. A. Distribution of the four behavioural classes after a Gaussian Mixture Model. B. Frequency of behavioural classes during phase 2 and phase 3 of the corridor test. C. Correlation between the proportion of time spent in slow movements and the sociability score of sheep during phase 2 and 3 (see details of models in Table 3). D. Correlation between the proportion of time spent in slow movements and the sociability score of sheep during phase 2 and 3 (Table 3). N = 64 sheep.


bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.





685


Figure 3: Wavelet analyses. A. Example of wavelet transform for lateral movements (X). 686 687 Red dots correspond to the detection of a change in the displacement at scale factor and time position (i.e., a local maximum of the wavelet transform of the signal position). 688 B. Example of wavelet transform for longitudinal movements (Y). C. Relationship 689 between the number of local maxima (red dots in Figures A and B) in the wavelet 690 691 extraction and the degree of sociability of sheep during phases 2 and 3. D. Relationship between the number of wavelets and the degree of docility of sheep during phases 2 692 693 and 3. See details of models in Table 4. N = 64 sheep.



695

Figure 4: Heatmap analyses. Relationship between the number of zones occupied by the lambs and the degree of docility in phase 2 and phase 3. A. Low spatial resolution grid (cell dimension:  $0.6 \times 1m$ ). B. High spatial resolution grid (cell dimension:  $0.44 \times 0.40 m$ ). Top: examples of heatmaps. Bottom: Correlations. See details of models in Table 6. N = 64 sheep.

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.




703

704 Figure 5: A. Correlations between the two first components (PCs) of the principal 705 component analysis (PCA). Arrows represent the eight behavioural variables on PC1 706 (movement speed) and PC2 (movement increase between phases). Contribution of 707 variables to the variance explained is colour coded. Each data point represents the PC1 708 and PC2 scores of a given lamb (N = 64). B. Relationship between PC1 and sociability. 709 C. Relationship between PC2 and docility. Blue lines represent linear models (see main 710 text). N = 64 sheep.

bioRxiv preprint doi: https://doi.org/10.1101/2020.12.09.418038; this version posted December 10, 2020. The copyright holder for this preprint (which was not certified by peer review) is the author/funder. All rights reserved. No reuse allowed without permission.

712



713

**Figure 6.** A. Picture of the outside corridor used for radar tracking of a sheep. The radar was positioned 60m from the end of the corridor. B. Example of trajectory of a sheep derived from radar data. C. Example of trajectory derived from radar data of a sheep (red) and a man (green) to induce the sheep movement.

718

# 720 Supplementary materials

- 721
- 722 **Data S1:** Raw trajectories obtained from radar and video for each sheep.
- 723
- 724 Table S1: Model selection for behavioural class analyses. Null model, best model,
- second and third best models are displayed.

Variables	AIC	Delta AIC	Weight
age x phase + weight x phase + docility x phase + sex x phase + sociability x phase	5423.774	0	9.92E-01
age x phase + weight x phase + docility x phase + sociability x phase	5433.82	10.04546	6.53E-03
age x phase + weight x phase + docility x phase + sex + sociability x phase	5436.306	12.5314	1.88E-03
Age x phase + docility x phase + sex x phase + sociability x phase	5447.138	23.36415	8.37E-06

- 727 **Table S2:** Model selection for X wavelet analyses (latitudinal movements). Null model,
- 528 best model, second and third best models are displayed.

Variables	AIC	Delta AIC	Weight
age x phase + weight x phase + docility x phase + sex + sociability x phase	1170.346	0	5.93E-01
age + weight x phase + docility x phase + sex + sociability x phase	1173.937	3.591115	9.85E-02
age x phase + weight + docility x phase + sex + sociability x phase	1174.289	3.942563	8.26E-02
age x phase + weight + docility x phase + sex + sociability	1174.586	4.239789	7.12E-02

- 730 **Table S3:** Model selection for Y wavelet analyses (longitudinal movements). Null model,
- 731 best model, second and third best models are displayed.

Variables	AIC	Delta AIC	Weight
age x phase + weight x phase + docility x phase + sex + sociability x phase	1189.577	0	5.73E-01
age x phase + weight x phase + docility + sex + sociability x phase	1193.051	3.474946	1.01E-01
age x phase + weight + docility x phase + sex + sociability x phase	1193.325	3.748755	8.79E-02
age + weight x phase + docility x phase + sex + sociability x phase	1193.374	3.797822	8.57E-02

732

733 Table S4: Model selection for heatmap analyses (low spatial resolution). Null model,

best model, second and third best models are displayed.

735

Variables	AIC	Delta AIC	Weight
weight x phase + sociability x phase	544.1552	0	1.35E-01
weight x phase + sex x phase + sociability x phase	546.3065	2.151297	4.61E-02
sex x phase + sociability x phase	546.376	2.220815	4.46E-02
weight x phase + sociability x phase + docility x phase	546.569	2.413782	4.05E-02

- 737 **Table S5:** Model selection for heatmap analyses (high spatial resolution). Null model,
- best model, second and third best models are displayed.
- 739

Variables	AIC	Delta AIC	Weight
age + docility x phase + weight x phase + sociability	664.2827	0	0.058719217
age + docility x phase + weight + sociability	664.9303	0.6476525	0.042476067

age + docility x phase + sociability x phase	665.5479	1.2652317	0.031191675
docility x phase + weight x phase + sociability x phase	665.8718	1.5891709	0.026527492