



**HAL**  
open science

# Hydrofoil Flow Induced Vibration Mitigation by Passive Resonant Piezoelectric Shunt

Yann Watine, Boris Lossouarn, Céline Gabillet, Jacques-André Astolfi,  
Jean-François Deü

► **To cite this version:**

Yann Watine, Boris Lossouarn, Céline Gabillet, Jacques-André Astolfi, Jean-François Deü. Hydrofoil Flow Induced Vibration Mitigation by Passive Resonant Piezoelectric Shunt. 11èmes Journées Jeunes Chercheurs en vibrations, Acoustique et Bruit, JJCAB 2021, Nov 2021, Compiègne, France. hal-03445730

**HAL Id: hal-03445730**

**<https://hal.science/hal-03445730>**

Submitted on 24 Nov 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Context

Hydrofoils are subjected to flow induced vibrations.

⇒ **Structural fatigue + acoustic noise**


If vortex shedding frequency = natural frequency.

⇒ **Resonance**

⇒ **High amplitude vibrations**

## Objective

**Use a resonant piezoelectric shunt to mitigate flow induced vibrations at resonance**




## Methodology

### Hydrodynamic tunnel

$U_0 = 3.0$  to  $5.5$  m/s

$Re = 2.40 \times 10^5$  to  $4.40 \times 10^5$

Incidence =  $0^\circ$



### Laser Vibrometry + TR-PIV + POD

### Hydrofoil natural frequencies


$f_1 = 40$  Hz : Bending

$f_2 = 282$  Hz : Twisting


$f_3 = 320$  Hz : Bending

### Shunt tuning


At twisting mode frequency ( $f_2$ )



## Vibration mitigation



Vibration velocity signal at  $U_0 = 4.4$  m/s



Effect of the shunt on  $V_{rms}$  at various flow velocities.

⇒ **High vibration level reduction at resonance (50 % on  $V_{rms}$ ).**


⇒ **Twisting mode resonance observed at  $U_0 = 4.4$  m/s.**

⇒ **Bending mode resonance at  $U_0 = 4.9$  m/s.**

⇒ **Impact of the shunt from 4.0 to 5.0 m/s.**

## Impact on the wake at twisting resonance, $U_0 = 4.4$ m/s

### Turbulent Kinetic Energy (TKE)




POD modes percentage of total TKE.

⇒ **Modes 1 and 2 : High TKE**

⇒ **Modes 3 and 4 : Low TKE**

⇒ **Weak impact of shunt on TKE**

### Modes dominant frequencies




POD modes dominant frequencies.

⇒  **$f_2 = 282$  Hz : twisting frequency, Karman modes.**

⇒  **$2 \times f_2 = 564$  Hz : Harmonic of twisting frequency.**


⇒  **$2 \times f_3 = 641$  Hz : Harmonic of bending frequency.**

### POD spatial modes, without shunt



(x,y) cartography of vorticity at  $U_0 = 4.4$  m/s, without shunt.

### POD spatial modes, with shunt



(x,y) cartography of vorticity at  $U_0 = 4.4$  m/s, with shunt.

⇒ **Modes 1 and 2 : Karman type coherent structures, no alteration by the shunt.**

⇒ **Modification of spatial modes 3 and 4 by the shunt.**

## Further work

⇒ **Investigate the impact of the shunt on the wake by vortex detection algorithm.**

⇒ **Apply POD to various main flow velocities.**

## Reference

- L. Pernod, B. Lossouarn, J.-A. Astolfi, J.-F. Deü, Vibration damping of marine lifting surfaces with resonant piezoelectric shunts, JSV, 2021

- Y. Watine, C. Gabillet, J.-A. Astolfi, L. Pernod, B. Lossouarn, J.-F. Deü. Vortex Induced Vibrations Analysis of a Cantilevered Blunt Plate by Proper Orthogonal Decomposition of TR-PIV and Structural Modal Analysis. Proc. ASME-FEDSM 2020