



HAL
open science

Simulation numérique de fracturation hydraulique à l'échelle mésoscopique à l'aide d'un modèle lattice

David Grégoire, Vincent Lefort, Gilles Pijaudier-Cabot

► **To cite this version:**

David Grégoire, Vincent Lefort, Gilles Pijaudier-Cabot. Simulation numérique de fracturation hydraulique à l'échelle mésoscopique à l'aide d'un modèle lattice. CFM 2015 - 22ème Congrès Français de Mécanique, Aug 2015, Lyon, France. hal-03446435

HAL Id: hal-03446435

<https://hal.science/hal-03446435>

Submitted on 24 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Simulation numérique de fracturation hydraulique à l'échelle mésoscopique à l'aide d'un modèle lattice

D. GREGOIRE, V. LEFORT, G. PIJAUDIER-CABOT

LFC-R, UMR5150, Université de Pau et des Pays de l'Adour
Campus Montaury, 64600 Anglet, France
david.gregoire@univ-pau.fr

Keywords : Fracture Process Zone, Hydro-mechanical Coupling, Lattice Analysis, Ripley Functions, Stimulated Reservoir Volume.

Characterizing the path of the hydraulic fracture in a heterogeneous medium and the change of the transport properties of this medium is one of the challenges of current research on hydraulic fracturing.

A 2D lattice hydro-mechanical model is used to describe hydraulic fracturing. Coupling is achieved with a staggered scheme that comprises two dual lattices, one for the mechanical problem and another one for fluid flow. In the mechanical problem [1], natural joints are added. They are represented by introducing elements with a Mohr-Coulomb behavior. In the fluid problem, Poiseuille flow is considered in each lattice element. A local permeability, which depends on the viscosity of the fluid and on the lattice geometry (opening between two solid parallel planes), is introduced. Macroscopically, it yields a Darcy-type equation in the case of a homogeneous material. The action of fluid pressure on the solid skeleton is represented using Biot's theory. The effect of cracks on fluid flow is captured by increasing the local permeability according to the increase of relative displacements in the dual mechanical lattice element. This increase results from the non-linear response of the skeleton.

First, we present the propagation of fracture restricted to the mechanical case. The influence of a natural joint crossed by the fracture is analyzed with the help of a parametric study. Then, the hydro-mechanical coupling is introduced. Results concerning characteristic length and hydraulic fracture behavior are discussed. The size of the area concerned by the change of transport properties, the stimulated reservoir volume, with respect to permeability, is analyzed. This parameter is important in order to evaluate the efficiency of the stimulation by hydraulic fracture in the context of tight hydrocarbon reservoirs.

Acknowledgments

Financial support from TOTAL Exploration & Production is gratefully acknowledged. University of Bordeaux is gratefully acknowledged for the use of the cluster AVAKAS.

References

[1] Peter Grassl, David Grégoire, Laura Rojas Solano, and Gilles Pijaudier-Cabot. Meso-scale modelling of the size effect on the fracture process zone of concrete. *International Journal of Solids and Structures*, 49(13):1818–1827, 2012.