



HAL
open science

Identification method of Non Linear Generalized Maxwell Model for viscoelastic components

Jean-Luc Dion, Hanen Jrad, Franck Renaud, Imad Tawfiq

► **To cite this version:**

Jean-Luc Dion, Hanen Jrad, Franck Renaud, Imad Tawfiq. Identification method of Non Linear Generalized Maxwell Model for viscoelastic components. CFM 2015 - 22ème Congrès Français de Mécanique, AFM, Aug 2015, Lyon, France. hal-03446442

HAL Id: hal-03446442

<https://hal.science/hal-03446442>

Submitted on 24 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Identification method of Non Linear Generalized Maxwell Model for viscoelastic components

J.-L. Dion, H.Jrad, F. Renaud, I. Tawfiq

SUPMECA, EA2336, jean-luc.dion@supmeca.fr

Abstract :

The dynamic characteristics of viscoelastic components depend on frequency, amplitude, preload, and temperature. A Non Linear Generalized Maxwell Model (NLGMM), with only 4 independent parameters is proposed. The proposed NLGMM is based on the decomposition between the linear viscoelasticity [1-3] and the non linear stiffness. This assumption is validated on a large range of experimental measures. The efficiency of the NLGMM is shown for different kinds of excitations in non linear dynamics : periodic, transient or random excitations. The non linear stiffness is represented by a simple polynomial function. Comparisons between measures and computed values have been carried on several viscoelastic samples. The NLGMM shows a good accordance with experimental results.




Fig. 1. Dynamic stiffness magnitude and phase angle versus of amplitude and frequency for each preload.

Mots clefs :

Non linear viscoelasticity ; Generalized Maxwell Model ; DMA tests ; identification technique

Références

- [1] Dion, J.L., Vialard, S., 1997. Identification of rubber shock absorber mounts. *Mécanique industrielle et matériaux* 50, 232-237.
- [2] Renaud, F., Dion, J.L., Chevallier, G., Tawfiq, I., Lemaire, R., 2011. A new identification method of viscoelastic behavior: application to the generalized Maxwell model, *Mechanical Systems and Signal Processing* 25 (3), 991-1010.
- [3] H. Jrad, J. L. Dion, F. Renaud, I. Tawfiq, and M. Haddar, “Experimental characterization, modeling and parametric identification of the non linear dynamic behavior of viscoelastic components,” *European Journal of Mechanics - A/Solids*, vol. 42, no. 0, pp. 176 – 187, 2013.