



HAL
open science

Moment Tensors of Ring-Faulting at Active Volcanoes: Insights Into Vertical-CLVD Earthquakes at the Sierra Negra Caldera, Galápagos Islands

Osamu Sandanbata, Hiroo Kanamori, Luis Rivera, Zhongwen Zhan, Shingo
Watada, Kenji Satake

► **To cite this version:**

Osamu Sandanbata, Hiroo Kanamori, Luis Rivera, Zhongwen Zhan, Shingo Watada, et al.. Moment Tensors of Ring-Faulting at Active Volcanoes: Insights Into Vertical-CLVD Earthquakes at the Sierra Negra Caldera, Galápagos Islands. *Journal of Geophysical Research: Solid Earth*, 2021, 126 (6), 10.1029/2021JB021693 . hal-03450343

HAL Id: hal-03450343

<https://hal.science/hal-03450343>

Submitted on 9 Aug 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Copyright

JGR Solid Earth

RESEARCH ARTICLE

10.1029/2021JB021693

Key Points:

- Dip slip along curved ring faults at volcanoes generates $M_w > 5$ earthquakes dominated by a compensated-linear-vector-dipole component
- We propose a method for estimating ring-fault parameters by moment tensor inversion using long-period seismic data
- Our estimation of ring-fault parameters of earthquakes at the Sierra Negra caldera yields results consistent with geodetic observations

Supporting Information:

Supporting Information may be found in the online version of this article.

Correspondence to:

O. Sandanbata,
osm3@bosai.go.jp

Citation:

Sandanbata, O., Kanamori, H., Rivera, L., Zhan, Z., Watada, S., & Satake, K. (2021). Moment tensors of ring-faulting at active volcanoes: Insights into vertical-CLVD earthquakes at the Sierra Negra Caldera, Galápagos Islands. *Journal of Geophysical Research: Solid Earth*, 126, e2021JB021693. <https://doi.org/10.1029/2021JB021693>

Received 19 JAN 2021

Accepted 11 MAY 2021

Moment Tensors of Ring-Faulting at Active Volcanoes: Insights Into Vertical-CLVD Earthquakes at the Sierra Negra Caldera, Galápagos Islands

Osamu Sandanbata^{1,2} , Hiroo Kanamori³ , Luis Rivera⁴, Zhongwen Zhan³ , Shingo Watada¹ , and Kenji Satake¹ 

¹Earthquake Research Institute, The University of Tokyo, Tokyo, Japan, ²National Research Institute for Earth Science and Disaster Resilience, Ibaraki, Japan, ³Seismological Laboratory, California Institute of Technology, Pasadena, CA, USA, ⁴Université de Strasbourg, CNRS, ITES UMR 7063, Strasbourg, France

Abstract Moderate earthquakes ($M_w > 5$) with moment tensors (MTs) dominated by a vertical compensated-linear-vector-dipole (vertical-CLVD) component are often generated by dip slip along a curved ring-fault system at active volcanoes. However, relating their MTs to ring-fault parameters has been proved difficult. The objective of this study is to find a robust way of estimating some ring-fault parameters based on their MT solutions obtained from long-period seismic records. We first model the MTs of idealized ring-faulting and show that MT components representing the vertical-CLVD and vertical strike-slip mechanisms are resolvable by the deviatoric MT inversion using long-period seismic waves, whereas a component representing the vertical dip-slip mechanism is indeterminate owing to a shallow source depth. We then propose a new method for estimating the arc angle and orientation of ring-faulting using the two resolvable MT components. For validation, we study a vertical-CLVD earthquake that occurred during the 2005 volcanic activity at the Sierra Negra caldera, Galápagos Islands. The resolvable MT components are stably determined with long-period seismic waves, and our estimation of the ring-fault parameters is consistent with the ring-fault geometry identified by previous geodetic studies and field surveys. We also estimate ring-fault parameters of two earthquakes that took place during the 2018 activity at the caldera, revealing significant differences between the two earthquakes in terms of slip direction and location. These results show the usefulness of our method for estimating ring-fault parameters, enabling us to examine the kinematics and structures below active volcanoes with ring faults that are distributed globally.

1. Introduction

Seismological methods can be used for the study of active volcanoes to investigate geometries of subsurface structures and the physics of fluid transport into the magma plumbing system. Observations and analyses of shallow earthquakes with volcanic origins provide information on stress levels in volcanic edifices caused by magmatic pressures ascending from depth. This information is important for predicting eruptions and assessing hazards related to volcanic activity (e.g., Chouet, 2003; Kawakatsu & Yamamoto, 2015; McNutt, 2002). In most cases, small earthquakes are analyzed with in situ or near-field observations to infer detailed dynamics of magma transport or brittle fractures of volcanoes, for example, Kilauea in Hawaii (e.g., Neal et al., 2019; Shelly & Thelen, 2019) or Bárðarbunga in Iceland (e.g., Gudmundsson et al., 2016; Parks et al., 2017). In contrast, moderate volcanic earthquakes are sometimes recorded by regional and global seismic networks (e.g., Ekström, 1994; Kanamori & Given, 1982; Kanamori et al., 1984; Kanamori & Mori, 1992; Shuler, Nettles, et al., 2013). If seismic signals radiated by such earthquakes can be utilized, it is possible to study volcanoes distributed globally, including those on remote islands or underwater without local observation systems. These include submarine volcanoes near Torishima Island, south of Japan (e.g., Fukao et al., 2018; Kanamori et al., 1993; Sandanbata et al., 2018; Satake & Kanamori, 1991), and near Curtis Island, north of New Zealand (Gusman et al., 2020), which caused earthquakes with seismic magnitudes of > 5 , and submarine volcanic areas near Mayotte Island in the Comoro Islands, which showed significant seismicity during 2018–2019 (Cesca et al., 2020; Darnet et al., 2020).

One of the most notable types of volcanic earthquake observed at regional or global scales are those with seismic magnitudes of $M_w > 5$ that are characterized by deviatoric moment tensors (MTs) having a dominant




Figure 1. Two types of vertical-CLVD earthquakes caused by ring-faulting. (a–d) The kinematics and geometry of ring-faulting corresponding to the two endmembers of vertical-CLVD earthquakes (shown on the left). The circle represents the up-dip end of the ring fault, with short lines indicating the dip direction to the down-dip end. The direction of motion of the central block is indicated at the center of the circle.

vertical compensated-linear-vector-dipole (vertical-CLVD) component (e.g., Ekström, 1994; Frohlich, 1994; Kanamori et al., 1993; Shuler, Ekström, et al., 2013; Shuler, Nettles, et al., 2013). There are two types of vertical-CLVD earthquakes: one contains a dominant tension axis (vertical-T CLVD earthquakes), and the other contains a dominant pressure axis (vertical-P CLVD earthquakes) (e.g., Ekström, 1994; Shuler, Nettles, et al., 2013) (Figure 1). Vertical-CLVD earthquakes cannot be explained by shear rupture on a planar fault, indicating that their anomalous mechanisms are associated with complex source structures or magmatic processes. For vertical-CLVD earthquakes at volcanoes, several models have been proposed, including ring-faulting (e.g., Ekström, 1994), rapid water-magma interaction initiated by magma intrusion into shallow crust (Kanamori et al., 1993), and opening or closing of a horizontal crack (e.g., Fukao et al., 2018; Riel et al., 2015).

Among the different proposed source models, the ring-faulting mechanism explains many features of vertical-CLVD earthquakes (e.g., Ekström, 1994; Shuler, Ekström, et al., 2013; Shuler, Nettles, et al., 2013). Ekström (1994) showed that deviatoric MT analyses of long-period seismic signals radiated by pure dip slips on a curved ring fault result in vertical-CLVD focal mechanisms. Shuler, Nettles, et al. (2013) and Shuler, Ekström, et al. (2013) surveyed vertical-CLVD earthquakes near volcanoes from 1976 to 2009 and located their centroids within the top 10 km of the crust, which is consistent with the formation process of ring faults during caldera collapse (e.g., Acocella, 2007; Cole et al., 2005; Geyer & Martí, 2014). Shuler, Nettles, et al. (2013) showed that most vertical-CLVD earthquakes were temporally associated with activity at nearby volcanoes with caldera structures. Vertical-CLVD earthquakes near Bárðarbunga in Iceland and Nyiragongo in the Democratic Republic of the Congo have also been attributed to slips on nonplanar ring faults (e.g., Gudmundsson et al., 2016; Nettles & Ekström, 1998; Parks et al., 2017; Shuler & Ekström, 2009). The recurrence of vertical-CLVD earthquakes at two shield volcanoes showing pronounced surface deformation or microseismicity along well-documented ring-fault structures has indicted their origins related to ring-faulting at the Rabaul caldera in Papua New Guinea (e.g., McKee et al., 1984; Mori & McKee, 1987; Mori et al., 1989; Shuler, Ekström, et al., 2013) and the Sierra Negra caldera in the Galápagos Islands (e.g., Amelung et al., 2000; Bell et al., 2021; Jónsson, 2009; Yun, 2007; Yun et al., 2006).

MT inversion using long-period seismic waves has been applied to study the sources of vertical-CLVD earthquakes from far-field observations (e.g., Duputel & Rivera, 2019; Fontaine et al., 2019; Shuler, Ekström, et al., 2013). Because of long-period properties, detailed 3-D velocity structures of the volcanic edifices are not required. MT solutions of ring-faulting are known to reflect the properties of earthquake sources, such as the kinematics of a central block and the dip directions of a ring fault (Ekström, 1994). When the central block moves upward on the inward-dipping ring fault (Figure 1a), or downward on the outward-dipping ring fault (Figure 1b), vertical-T CLVD earthquakes are produced; in contrast, if the kinematics of the block are reversed, vertical-P CLVD earthquakes are produced (Figures 1c and 1d). Hence, the polarity of the MT solutions (vertical-T or vertical-P) helps to determine either the kinematics of the central block (upward or downward) or the dip direction of the ring fault (inward or downward), once either of the two is constrained from other observations such as crustal deformation or microseismicity (e.g., Gudmundsson et al., 2016; Shuler & Ekström, 2009).

However, it has been proved challenging to relate MT solutions obtained from long-period seismic waves directly to ring-fault parameters such as arc angle, dip angle, and the location of slip along the ring fault. One of the reasons for the difficulty is that amplitudes of radiated long-period seismic waves are reduced owing to partial cancellations of long-period seismic waves from different portions of a ring fault (Ekström, 1994). Another reason is the instability of MT inversion for shallow earthquakes (e.g., Dziewonski et al., 1981; Kanamori & Given, 1981). Although Shuler, Ekström, et al. (2013) related MT solutions obtained from long-period seismic records to ring-fault parameters using the plunge of the tension or pressure axis and a parameter representing the dominance of the non-double-couple component, their estimations were not always consistent with those observed in nature or analog models. Contreras-Arratia and Neuberg (2020) showed that detailed ring-fault parameters can be recovered from near-field seismic stations with good azimuth coverage. Once reliable relationships between ring-fault parameters and MT solutions obtained from long-period seismic records are established, MT inversion will be a more powerful tool to remotely study the kinematics and subsurface structures of active volcanoes distributed globally that cause ring-faulting.

The objective of this study is to find a robust way of estimating ring-fault parameters using the MT solutions of vertical-CLVD earthquakes. We first model theoretical MTs of idealized ring-faulting with variable ring-fault parameters and decompose them into MT components. Although the MT component representing the vertical dip-slip mechanism is difficult to determine with long-period seismic waves, we show that the remaining MT components can be used to estimate some ring-fault parameters. To validate the theoretical argument, we estimate the ring-fault parameters of vertical-CLVD earthquakes at the Sierra Negra caldera by investigating their resolvable components of MT solutions determined with long-period seismic waves and then compare the estimated parameters with those identified in previous studies using geodetic observations and field surveys. We also discuss possible bias in MT inversion caused by a seismic source with a volume change close to the ring-faulting.

2. Analysis

2.1. Modeling and Decomposition of Moment Tensors of Ring-Faulting

In this section, we theoretically explore robust relationships between MTs and ring-fault parameters. We consider ring-faulting along a uniformly inward-dipping fault system that traces the circumference of a circle. We define several ring-fault parameters as follows (Figure 2). The ring-faulting has a dip angle δ that is constant along the fault system. The arc angle Θ is the central angle that measures the ruptured segment along the circumference. The ring-fault azimuth is defined by the azimuth (from the north) of the vector \overline{OM} , where O is the center of the circle and M is the midpoint of the ruptured segment. The ring-fault azimuth indicates the ring fault's location along the circumference. The ring-fault orientation is the geometrical orientation, measured clockwise from the north, of the tangent to the circle at M , and is normal to \overline{OM} . The ring-fault azimuth can vary from 0° to 360° , whereas the ring-fault orientation can vary only from 0° to 180° .

Here, we consider idealized ring-faulting for a vertical-T CLVD mechanism: a pure reverse slip of 1 m along a circular inward-dipping ring fault (5 km radius at the surface) that extends from the surface to a depth of




Figure 2. Modeling and decomposition of theoretical moment tensors of idealized ring-faulting. (a) Ring-fault parameters. Thick and thin arc curves represent up-dip and down-dip ends, respectively. Arc angle Θ , dip angle δ , and ring-fault azimuth OM are variable parameters. The ring-fault orientation is perpendicular to the ring-fault azimuth. The dip angle is uniform along the ring fault. (b) Three decomposed moment tensor (MT) components. (c)–(d) Theoretical MTs of ring-faulting with arc angles of 90°, 180°, 270°, and 360° and with dip angles of (c) 60° and (d) 75°. For reference, an MT of a planar faulting is also shown in the top row. Columns: (1) kinematics and geometry of ring-faulting, (2–6) focal mechanism diagrams of (2) the theoretical MT, (3–5) decomposed MT components (CLVD, SS, and DS) with their ratios, and (6) resolvable MT. The orientation of the best double-couple solution is shown by thin curves in columns 2 and 6. All focal mechanisms are shown by projection of the lower focal hemisphere. The diameter of the focal mechanism diagram is proportional to its scalar moment but slightly exaggerated for the component with percentages of < 10% for clear visualization.

2 km. We model the theoretical MT of ring-faulting in a similar way to Ekström (1994) and Shuler, Ekström, et al. (2013); we discretize the ring fault into planar rhomboidal subfaults with a central angle of 1° for each, compute the MT of each subfault (Box 4.4 in Aki and Richards [2002]), and sum up the MTs of the subfaults. A ring fault is smaller than the wavelength, and the typical source time duration of vertical-CLVD earthquakes is ~10 s (Shuler, Ekström, et al., 2013), which is shorter than the wave period of the long-period seismic waves that we use; hence, we can ignore the rupture propagation along the ring fault and assume the point-source approximation. While fixing the ring-fault azimuth as 0° (i.e., the midpoint on the north), we vary two ring-fault parameters, that is, the dip angle δ ranging from 45° to 90°, and the arc angle Θ ranging from 0° to 360°. Only vertical-T earthquakes are discussed here because MTs of vertical-P earthquakes can be examined by changing the signs of the MTs.

The scalar moment of the theoretical MTs is computed by following the definition given by Silver and Jordan (1982) and Dahlen and Tromp (1998):

$$M_0 = \sqrt{\sum_{ij} M_{ij} M_{ij}} / 2, \quad (1)$$

where M_{ij} are the ij elements of an MT in spherical coordinates (r , θ , and ϕ) representing up, south, and east, respectively. The moment magnitude is computed as:

$$M_w = \frac{2}{3}(\log_{10} M_0 - 9.10). \quad (2)$$

with M_0 being measured in N m (e.g., Hanks & Kanamori, 1979; Kanamori, 1977).

We next decompose the theoretical MTs in a similar way to Kawakatsu (1996). For the decomposition, we define three moment scales corresponding to isotropic (ISO), vertical-CLVD ($CLVD$), and difference (D) components with the three diagonal elements (M_{rr} , $M_{\theta\theta}$, and $M_{\phi\phi}$):

$$M_{ISO} = \frac{1}{3}(M_{rr} + M_{\theta\theta} + M_{\phi\phi}), \quad (3)$$

$$M_{CLVD} = \frac{1}{3}(2M_{rr} - M_{\theta\theta} - M_{\phi\phi}), \quad (4)$$

and

$$M_D = \frac{1}{2}(M_{\theta\theta} - M_{\phi\phi}). \quad (5)$$

Note that the MT of ring-faulting contains no isotropic component ($M_{ISO} = 0$). Hence, using the two moment scales (M_{CLVD} and M_D) and the nondiagonal elements ($M_{r\theta}$, $M_{r\phi}$, and $M_{\theta\phi}$), the MT of ring-faulting can be uniquely decomposed into three deviatoric MT components in the following form:

$$\mathbf{M} = \mathbf{M}_{CLVD} + \mathbf{M}_{SS} + \mathbf{M}_{DS}, \quad (6)$$

where

$$\mathbf{M}_{CLVD} = M_{CLVD} \begin{bmatrix} 1 & & \\ 0 & -0.5 & \\ 0 & 0 & -0.5 \end{bmatrix}, \quad (7)$$

$$\mathbf{M}_{SS} = \mathbf{M}_D + \mathbf{M}_{\theta\phi} = M_D \begin{bmatrix} 0 & & \\ 0 & 1 & \\ 0 & 0 & -1 \end{bmatrix} + M_{\theta\phi} \begin{bmatrix} 0 & & \\ 0 & 0 & \\ 0 & 1 & 0 \end{bmatrix}, \quad (8)$$

and

$$\mathbf{M}_{DS} = \mathbf{M}_{r\theta} + \mathbf{M}_{r\phi} = M_{r\theta} \begin{bmatrix} 0 & & \\ 1 & 0 & \\ 0 & 0 & 0 \end{bmatrix} + M_{r\phi} \begin{bmatrix} 0 & & \\ 0 & 0 & \\ 1 & 0 & 0 \end{bmatrix}. \quad (9)$$

Note that the moment scales (Equations 3–5) are scalars, whereas the MT components (Equations 7–9) are tensors.

The three MT components \mathbf{M}_{CLVD} , \mathbf{M}_{SS} , and \mathbf{M}_{DS} represent different source types, that is, the vertical-CLVD ($CLVD$), vertical strike-slip (SS), and vertical dip-slip (DS) mechanisms, respectively (Figure 2b). The sign of M_{CLVD} in Equation 7 depends on the type of vertical-CLVD earthquake: $M_{CLVD} > 0$ for vertical-T earthquakes, and $M_{CLVD} < 0$ for vertical-P earthquakes.

Using absolute values defined by $|M_{CLVD}|$, $M_{SS} = \sqrt{M_D^2 + M_{\theta\phi}^2}$, and $M_{DS} = \sqrt{M_{r\theta}^2 + M_{r\phi}^2}$, we can quantify the ratios of the *CLVD*, *SS*, and *DS* components in the MT of ring-faulting as:

$$\frac{|M_i|}{|M_{CLVD}| + M_{SS} + M_{DS}} \times 100 [\%], \quad (10)$$

where i represents *CLVD*, *SS*, or *DS*.

Figures 2c and 2d show the theoretical MTs and components for reverse slips on ring faults with dip angles of 60° and 75°, respectively, which have arc angles of 90°, 180°, 270°, and 360° (2nd–5th rows, respectively). The ring-fault azimuths are 0°, and the ring-fault orientations are 90° (i.e., the midpoint of the ring fault is located on the north along the circumference of the circle). For comparison, MTs of slip on planar faults with the same dip angles that are parallel to the ring-fault orientation are shown (first row). Ring-faulting has a vertical-*CLVD* mechanism, as long-period seismic contributions from different segments along the curved ring fault partially cancel out (Ekström, 1994). Because the azimuths of principal axes of the two double-couple components, M_{SS} and M_{DS} , are determined by the strike angle of a planar fault (first row), the double-couple components from different portions of the ring fault cause the geometric cancellation. In contrast, as the *CLVD* component, M_{CLVD} , of a planar fault does not change with its strike angle, the component of the ring fault accumulates and becomes more dominant in the MT as the arc angle increases.

2.2. Indeterminate *DS* Component at a Shallow Source Depth

Once the MT solution of ring-faulting is determined, the ring-fault parameters, namely, dip angle, arc angle, and ring-fault azimuth (Figure 2a), can be estimated from the ratios of the three MT components and azimuths of the principal axes of the *SS* and *DS* components. However, the *DS* component of such shallow earthquakes is indeterminate from long-period seismic waves, because the component near the solid surface has little contribution to long-period seismic waves (e.g., Dziewonski et al., 1981; Kanamori & Given, 1981). The indeterminacy of the *DS* component makes it difficult to estimate the dip angle and seismic magnitude of ring-faulting from long-period seismic waves. In addition, we cannot determine the ring-fault azimuth, which is reflected in the azimuth of the tension axis of the *DS* component.

To confirm the indeterminacy of the *DS* component at a shallow depth, we synthesize long-period (0.005–0.0125 Hz) seismic waveforms, including all the relevant phases (e.g., P, S, and surface waves), at a virtual station from five hypothetical sources representing elementary components, M_{CLVD} , M_D , $M_{\theta\phi}$, $M_{r\theta}$, and $M_{r\phi}$. We assume the same scalar moment $M_0 = 1.0 \times 10^{18}$ N m (M_w 5.9) using Equation 1 for the sources (Figure 3). Details of the numerical method are described in the caption of Figure 3. For a source at 2.5 km depth in the crust, amplitudes of long-period seismic waves radiated from the *DS* component ($M_{r\theta}$ and $M_{r\phi}$) are much smaller than those from the *CLVD* component (M_{CLVD}) and the *SS* component (M_D and $M_{\theta\phi}$) (Figure 3a). Because of the inefficient seismic excitation, estimation of the *DS* component is unstable. Also, small errors in the depth of the source result in large uncertainties in the *DS* components owing to large variations in the amplitudes of synthetic long-period seismic waves. If the source is at 10.5 km depth, the *DS* component radiates larger seismic waves (Figure 3b).

2.3. Resolvable MTs of Ring-Faulting

Given the indeterminacy of the *DS* component, we propose a method for estimating two ring-fault parameters using only the *CLVD* and *SS* components, which are resolvable with long-period seismic waves. Here, we define the resolvable MT (M_{res}) by:

$$M_{res} = M_{CLVD} + M_{SS}. \quad (11)$$

M_{res} for the idealized ring-faulting is shown in the sixth column in Figures 2c and 2d. Here, we introduce two new dimensionless physical parameters extracted from M_{res} , as follows. The first parameter, k_{CLVD} , is the ratio of $|M_{CLVD}|$ to $|M_{CLVD}| + M_{SS}$ of M_{res} defined by:




Figure 3. Synthetic long-period seismic waveforms from sources representing five elementary moment tensor components. The centroid depth is (a) 2.5 km and (b) 10.5 km in the crust. M_D and $M_{\theta\phi}$ determine the *SS* component, and $M_{r\theta}$ and $M_{r\phi}$ determine the *DS* component. The virtual station is located at $(\varphi, \Delta) = (19.2^\circ, 17.8^\circ)$, where φ is the station azimuth from the north (eastward positive), and Δ is the distance from the source. We use the W-phase code (Duputel et al., 2012; Hayes et al., 2009; Kanamori & Rivera, 2008) for the convolution of Green's functions and filtering. Green's functions are computed by the normal mode method (e.g., Takeuchi & Saito, 1972), with the 1-D Preliminary Reference Earth Model (PREM; Dziewonski & Anderson, 1981). A one-pass and fourth-order Butterworth bandpass filter with corner frequencies of 0.005 and 0.0125 Hz is applied.

$$k_{CLVD} = \frac{|M_{CLVD}|}{|M_{CLVD}| + M_{SS}} \times 100 [\%], \quad (12)$$

which we call the *CLVD ratio*. This parameter can be used to estimate the ring-fault arc angle Θ (Figure 4a). As Θ increases from 0° (i.e., a planar fault) to 180° , k_{CLVD} increases from 66.7% to 100%. From $\Theta = 180^\circ$, k_{CLVD} decreases to a local minimum of 90% at $\sim 255^\circ$, and then increases to 100% at 360° . k_{CLVD} reaches 100% when Θ is 180° or 360° , where the *SS* component vanishes. When the dip angle is constant along the ring fault, the relationship between k_{CLVD} and Θ does not depend on the dip angle because pure dip slip on a planar fault




Figure 4. Relationship between M_{res} and ring-fault parameters. (a) The CLVD ratio, k_{CLVD} , of the resolvable MT, M_{res} , as a function of arc angle Θ . Note that the relationship between k_{CLVD} and Θ is independent of the dip angle of the ring fault. (b–c) Relationship between ring-fault geometry and M_{res} for (b) vertical-T earthquakes and (c) vertical-P earthquakes. In the second column, the dip direction of the ring fault (inward or outward), the kinematics of the central block (up or down), and the ring-fault orientation (an arrow) are shown. In the third column, M_{res} is shown with the orientation of its N-axis (arrow). In the fourth column, the SS component is shown with its T-axis or P-axis (arrow). Note that the N-axis of M_{res} is the same as the T- and P-axis of the SS component for vertical-T and vertical-P earthquakes, respectively.

with any dip angle in all cases results in the same CLVD-to-SS component ratio of 2:1 (top row in Figures 2c and 2d). Thus, we can use k_{CLVD} to estimate some values of Θ even if the DS component is indeterminate.

The second parameter, ψ , is defined as follows. The resolvable MT M_{res} discussed here is expressed by three orthogonal dipoles. We use the orientation of the dipole with the smallest absolute moment to estimate the orientation of the ring fault. As shown in Figures 2c and 2d (sixth column), this dipole determines the elongation direction of the nodal-line pattern of the mechanism diagrams of M_{res} . It can also be shown that this orientation is the same as the orientation of the Null (N) axis of the best-fitting double-couple moment

tensor (pp. 248–251 of Shearer, 2009) shown by thin curves on the mechanism diagrams (sixth column of Figures 2c and 2d). We refer to the dipole axis as the *N*-axis and denote its orientation by ψ , which is measured from the north, eastward-reckoned positive, $0 \leq \psi < 180^\circ$. Figures 4b and 4c show the relationships between the ring-fault orientation and the *N*-axis for vertical-T and vertical-P CLVD earthquakes. The ring-fault orientation is parallel or perpendicular to the *N*-axis depending on $\Theta < 180^\circ$ or $\Theta > 180^\circ$, respectively. Because ψ is independent of the dip angle, this parameter can be used to estimate the ring-fault orientation without knowing the *DS* component. We note that what can be estimated from ψ is not the ring-fault azimuth but the orientation (Figure 2a); we cannot distinguish two different ring faults with the same arc angle but rotated by 180° to each other.

Thus, \mathbf{M}_{res} for shallow ring-faulting is useful for estimating ring-fault parameters by using k_{CLVD} and ψ together. If k_{CLVD} is less than $\sim 90\%$, Θ can be uniquely determined by k_{CLVD} because Θ is a single-valued function of k_{CLVD} (Figure 4a). In this case, the ring-fault orientation is parallel to the *N*-axis (Figures 4b and 4c). In contrast, if k_{CLVD} is larger than $\sim 90\%$, Θ cannot be determined uniquely and three values of Θ are possible for a given k_{CLVD} (Figure 4a); there also remain two possibilities for the ring-fault orientation, parallel or perpendicular to the *N*-axis, depending on Θ (Figures 4b and 4c). When $\Theta = 180^\circ$, the *N*-axis orientation is indeterminate (Figures 2c and 2d), and the ring-fault orientation cannot be determined. When $\Theta = 360^\circ$, the ring-fault orientation is irrelevant.

3. Case Study: Vertical-CLVD Earthquakes at the Sierra Negra Caldera, Galápagos Islands

In the previous section, we showed that the resolvable MT, \mathbf{M}_{res} , which is composed of the *CLVD* and *SS* components, of ring-faulting is useful for estimating the arc angle Θ and the orientation of the ring fault. Here, we investigate the relationships for a vertical-CLVD earthquake that occurred at the Sierra Negra caldera during the 2005 volcanic activity. We first test the stability of \mathbf{M}_{res} obtained from MT inversion using long-period seismic records at far-field. Then, we analyze \mathbf{M}_{res} to estimate the ring-fault parameters and compare them with other observations. We also investigate two vertical-CLVD earthquakes at the caldera during volcanic activity in 2018.

3.1. M_w 5.5 Vertical-T CLVD Earthquake Before the 2005 Eruption

The Sierra Negra is a shield volcano located at the southern end of Isabella Island, in the Galápagos Islands (Figure 5a). A shallow 7×10.5 km² caldera structure is formed at the summit of the 1124-m-high volcano (Figure 5b; Reynolds et al., 1995). On October 22, 2005, the Sierra Negra caldera started eruption activity at $\sim 23:30$ in UTC (e.g., Geist et al., 2008; Global Volcanism Program, 2005). At 20:34 on the same day, about 3 h before initiation of the eruption, a vertical-T CLVD earthquake with M_w 5.5 occurred (Chadwick et al., 2006; Jónsson, 2009). Clear long-period seismic signals from this earthquake were observed at far-field stations (black lines in Figure 6). Geodetic observations with Global Positioning System (GPS) and Interferometric Synthetic Aperture Radar (InSAR) suggested reverse slip along a sinuous fault system with an inward dip angle on the western to southern parts of the caldera caused by a pressurized sill-like magma chamber; this fault-motion mechanism is termed *trapdoor faulting* (e.g., Amelung et al., 2000; Jónsson, 2009). The occurrence of ring-faulting was indicated by a fresh fault scarp on the southwestern part of the caldera (black dotted and solid curves in Figure 5b) identified by Geist et al. (2008), who conducted field surveys at the caldera after the 2005 eruption. The shallow sill-like magma chamber estimated from geodetic data (Jónsson, 2009) suggests that the earthquake occurred in the top ~ 2 km of the crust. For this geometry at such a shallow depth, the indeterminacy of the *DS* component is an issue. Thus, this is a good example for investigating how the MT solution of a vertical-CLVD earthquake caused by ring-faulting is related to the geometry of the ring fault identified by geodetic studies and field surveys.

3.2. Data and Methods

We perform MT inversion for the M_w 5.5 vertical-T earthquake near the Sierra Negra caldera. We use the W-phase code for the inversion, including filtering, data screening, and convolution of Green's functions (Duputel et al., 2012; Hayes et al., 2009; Kanamori & Rivera, 2008). We use the normal mode method (e.g.,




Figure 5. (a) Map of the Galápagos Islands. Topographic and bathymetric data are from GEMBCO_2020. The black rectangle in the inset panel indicates the area shown in (a). The black cross represents the centroid location of the vertical-T earthquake of October 22, 2005, reported in the GCMT Catalog. (b) Map of the Sierra Negra caldera. Topographic data is from the Advanced Land Observation Satellite (ALOS) World 3D–30 m DEM (AW3D30) provided by the Japan Aerospace Exploration Agency (JAXA) (e.g., Tadono et al., 2014). The black curve indicates the fresh vertical scarp identified by Geist et al. (2008) during a field survey in June 2006; the part represented by the solid curve was clearly identified, whereas those along the dotted curves were less clearly defined. The red circles represent the locations of GPS stations used by Bell et al. (2021). The gray dotted curve indicates a possible geometry inferred in this study for the 2018 vertical-P earthquake (see Section 3.4).

Takeuchi and Saito, 1972) to compute Green's functions for the 1-D Preliminary Reference Earth Model (PREM; Dziewonski & Anderson, 1981), in the same way as we did for the synthetic test in Section 2.2. Long-period seismic waves are extracted from synthetic and observed waveforms by applying a one-pass and fourth-order Butterworth bandpass filter with corner frequencies at 0.005 and 0.0125 Hz. The inversion time window is set to include P, S, and surface waves. We assume zero contribution by a volume change to the long-period seismic waves by imposing the zero-trace constraint, $M_{rr} + M_{\theta\theta} + M_{\phi\phi} = 0$. This means that the seismic waves are entirely attributed to ring-faulting. Possible bias caused by a volume change is discussed later in Section 4.2.

We use long-period seismic records at far-field stations for the inversion. We download seismic records at stations within 5° – 60° of the epicentral distance from the Data Management Center of the Incorporated Research Institutions for Seismology (IRIS). For data screening (i.e., to remove bad data with glitch, or low signal-to-noise ratio), we conduct a trial MT inversion using a source placed at 2.5 km depth in the crust (i.e., 5.5 km depth of PREM including a 3-km oceanic layer) just below the Sierra Negra caldera (0.83° S, 91.14° W). We assume a half duration and a centroid time shift reported in the Global Centroid Moment Tensor (GCMT) Catalog. As a result of the trial inversion, we remove clearly bad data yielding a normalized root mean square (NRMS) misfit > 0.9 ; the NRMS is defined by $\rho_i = \sqrt{\|s_i - d_i\|^2 / \|s_i\|^2}$, where s_i and d_i are synthetic and observed data in the inversion time window at the i -th station, respectively, and $\|s\|$ represents the L2 norm of data vector s . The selected data set is composed of 25 seismic records at stations for the epicentral distance range from 12.4° to 46.6° and has a good azimuthal coverage (Figure 6). The stations are from different seismic networks: the Global Seismograph Network (II, IU), Broadband Tomography Under Costa Rica and Nicaragua (YO, 2003–2006), GEOSCOPE (G), and the United States National Seismic Network (US).

To examine the stability of the MT solutions, we repeat MT inversion while moving the centroid location in a 3-D space around the Sierra Negra caldera. By examining the variation in the MT solutions, we can assess the sensitivity of the solutions to small variations in estimated centroid location. For MT inversion in the 3-D space, centroid locations are distributed on two planes: the x - y (longitude-latitude) plane at a depth of 2.5 km in the crust (Figure 7a), and the x - z (longitude-depth) plane along a latitude of 0.83° S across the




Figure 6. Model performance of MT inversion for the M_w 5.5 vertical-T CLVD earthquake of October 22, 2005. Red and black lines represent synthetic and observed waveforms, respectively. The start and end points of the inversion time window are indicated by red circles. In each inset map, the blue star and the large red circle represent locations of the epicenter (0.83°S , 91.14°W) and the station. The station azimuth (ϕ) and epicentral distance (Δ) are indicated at the top of each panel.




Figure 7. MT inversion for the vertical-T CLVD earthquake of October 22, 2005 at the Sierra Negra caldera. (a, b) Global NRMS misfits ρ of MT solutions at source locations distributed on (a) the x - y plane at a depth of 2.5 km in the crust and (b) the x - z plane along a latitude of 0.83° (dashed white line in [a]). The red circle in (a) and the red line in (b) represent the approximate locations of the Sierra Negra caldera. (c, d) MT solutions at different centroid locations on (c) the x - y plane around the caldera (in the area shown by the white rectangle in [a]) and (d) the x - z plane. (e and f) Resolvable MTs on (e) the x - y plane around the caldera and (f) the x - z plane. All focal mechanisms are shown by projection of the lower focal hemisphere. In (b, d, and f), the vertical axis represents the centroid depth in the crust.

caldera (Figure 7b). The centroid location intervals are 0.1° in the horizontal direction and 2.0 km in the vertical direction. At each centroid location, we try the inversion with different values for the half duration t_h of the source time function and the centroid time shift t_c , assuming $t_h = t_c$, and then determine an optimal value by a grid search minimizing the waveform misfit. The waveform fit for the MT solution is measured with a global version of the NRMS misfit, $\rho = \sqrt{\sum_i \|s_i - d_i\|^2 / \sum_i \|s_i\|^2}$, where each sum goes over the number of seismic records. Then, from the solution, we obtain \mathbf{M}_{res} defined by Equation 11. Strictly speaking, to estimate \mathbf{M}_{res} exactly with the constraint of $M_{r\theta} = M_{r\phi} = 0$, we need to perform three-element MT inversions with the three constraints, $M_{r\theta} = M_{r\phi} = 0$, and $M_{rr} + M_{\theta\theta} + M_{\phi\phi} = 0$. However, to compare our solutions with the GCMT solutions which were obtained for the five MT elements with the only constraint $M_{rr} + M_{\theta\theta} + M_{\phi\phi} = 0$, we here perform five-element MT inversions only with the constraint $M_{rr} + M_{\theta\theta} + M_{\phi\phi} = 0$, and after the solution was obtained we set $M_{r\theta} = M_{r\phi} = 0$. In supporting information, we compare \mathbf{M}_{res} obtained with these two methods and show that the results are very similar when the data sets are good.

3.3. Results

3.3.1. Indeterminate DS Component and Stability of the Resolvable MT

Figure 7a shows the global NRMS values for the MT solutions at locations on the x - y plane at a depth of 2.5 km in the crust. In the area around the Sierra Negra caldera (white rectangle in Figure 7a), the NRMS values are small. Figure 7b shows the global NRMS values for the MT solutions on the x - z plane along latitude 0.83° S (dashed line in Figure 7a). Similarly, small NRMS values are given by most MT solutions in the top ~ 15 km of the crust. For example, the MT solution at the caldera (0.83° S, 91.14° W; red circle in




Figure 8. Histograms of the parameters of acceptable MT solutions. (a) M_w and (b) the ratio of the DS component of the acceptable MT solutions. (c) M_w , (d) the CLVD ratio k_{CLVD} , and (e) the N -axis azimuth ψ of \mathbf{M}_{res} extracted from the acceptable MT solutions.

Figure 7a) at a depth of 2.5 km reproduces the observed records well with an NRMS value of 0.365 (Figure 6). From the MT solutions in the 3-D space, 53 solutions at different centroid grids yield NRMS values of ≤ 0.365 , which we refer to as *acceptable solutions* hereafter.

Figure 7c shows the MT solutions on the x - y plane at a depth of 2.5 km in the area around the caldera (white rectangle in Figure 7a) and Figure 7d shows the solutions on the x - z plane along a latitude of 0.83°S (white dashed line in Figure 7a) in the top ~ 10 km of the crust. The solutions on the two planes differ significantly depending on centroid locations in the 3-D space, although they yield similar small NRMS values. Notably, at shallower depths in the crust, estimated M_w values and ratios of the DS component are larger (Figure 7d). For the 53 acceptable solutions, M_w values are distributed widely from 5.50 to 6.49 (Figure 8a), and the ratio of the DS component, computed with Equation 10, ranges from 44.8% to 97.7% (Figure 8b). These results demonstrate the instability of MT inversion caused by the indeterminate DS component, as discussed in Section 2.2.

From the MT solutions at centroid locations on the x - y and x - z planes, we extract \mathbf{M}_{res} defined by Equation 11 (Figures 7e and 7f). \mathbf{M}_{res} on the two planes have similar focal mechanisms and M_w . M_w values of \mathbf{M}_{res} are in a narrow range (5.33 ± 0.04) for the 53 acceptable solutions (Figure 8c). Also, \mathbf{M}_{res} for the acceptable solutions contain stable values of the CLVD ratio k_{CLVD} ($73.0 \pm 3.0\%$; Figure 8d) and the N -axis azimuth ψ ($102.7 \pm 3.0^\circ$; Figure 8e). These results confirm that \mathbf{M}_{res} is stably obtained for vertical-CLVD earthquakes, even in the cases where centroid locations are not accurately determined, indicating its stability under the presence of noise in observed data. Thus, the two physical parameters (i.e., k_{CLVD} and ψ) obtained from \mathbf{M}_{res} can be used to reliably estimate ring-fault parameters.

In Figure 9 and Table 1, we compare the MT solution obtained for the centroid location at a depth of 2.5 km just below the caldera (0.83°S , 91.14°W) with the solution from the GCMT Catalog. The centroid depth of




Figure 9. MT solutions and resolvable MTs of the M_w 5.5 vertical-T CLVD earthquake of October 22, 2005. (a) MT solution with the ratios of the three MT components and (c) resolvable MT with the ratio of the CLVD component k_{CLVD} and the N -axis azimuth ψ obtained from our MT inversion at a depth of 2.5 km in the crust just below the caldera. (b) MT and (d) resolvable MT obtained from the GCMT Catalog. All focal mechanisms are shown by projection of the lower focal hemisphere.

the GCMT solution is 9.0 km in the crust (i.e., 12 km of PREM including a 3-km oceanic layer). The two MT solutions, including the indeterminate DS component, have very different focal mechanisms, M_w values, and ratios of the DS component (Figures 9a and 9b). In contrast, M_{res} extracted from the two different solutions show similar values for M_w (5.31 and 5.31), k_{CLVD} (73.4% and 77.3%), and ψ (101.9° and 96.3°; Figures 9c and 9d). These results demonstrate that M_{res} can be reliably estimated from various available catalogs such as the GCMT, even if the centroid depth and the complete MT are not accurately determined for the shallow earthquakes (e.g., Chu et al., 2009; Wimpenny and Watson, 2020).

3.3.2. Ring-Fault Parameters Inferred From the Resolvable MT

We next estimate ring-fault parameters for the 2005 vertical-T CLVD earthquake at the Sierra Negra caldera from M_{res} of the MT solution (Figure 9c). If we assume that the seismic waves are generated entirely from idealized ring-faulting (uniform slip along a circular ring fault with a constant dip angle), M_{res} with a value of k_{CLVD} of 73.4% indicates a ring fault with an arc angle Θ of $\sim 80^\circ$ (Figure 4a). In such a case of $\Theta < 180^\circ$, the N -axis with ψ of 101.9° suggests that the ring-fault orientation is a direction rotated slightly clockwise from the E-W direction. Similarly, the intra-caldera fault (black curve in Figure 5b), which was attributed to the earthquake source by geodetic observations and field surveys (Amelung et al., 2000; Geist et al., 2008; Jónsson, 2009), has an arc angle a little smaller than 90° and its orientation is slightly rotated clockwise from the E-W direction, if we approximate the fault as a circular arc. Although here we do not consider complexities of the actual fault geometry and slip distributions, the overall agreement of the ring-fault parameters

Table 1
Moment Tensor Solutions of Vertical-CLVD Earthquakes for the Sierra Negra Caldera

Event date	Source of solution	Longitude (°W)	Latitude (°S)	Depth in the crust (km)	Elements of moment tensor (N m)						Scale factor (10exp)	M_w
					M_{rr}	$M_{\theta\theta}$	$M_{\phi\phi}$	$M_{r\theta}$	$M_{r\phi}$	$M_{\theta\phi}$		
October 22, 2005	This study	91.14	0.83	2.5	1.246	-1.035	-0.210	-6.127	-3.718	0.182	17	5.84
October 22, 2005	GCMT	91.35	1.00	9.0	1.260	-0.989	-0.268	0.459	-1.510	0.080	17	5.46
June 26, 2018	GCMT	91.33	0.96	9.0	1.230	-1.090	-0.148	0.118	-0.592	-0.059	17	5.35
July 5, 2018	GCMT	90.98	0.88	9.0	-3.880	2.490	1.400	0.314	-3.300	1.420	16	5.06

Centroids and moment tensor solutions of vertical-CLVD earthquakes for the Sierra Negra caldera obtained by MT inversion in this study or taken from the GCMT Catalog. Note that the centroid depth of the GCMT Catalog may be determined at a greater depth of 9 km in the crust (i.e., 12 km of PREM including a 3-km oceanic layer) than the accurate centroid depth of the earthquakes to maintain the stability of the solutions (Ekström et al., 2012).




Figure 10. GCMT solutions for two vertical-CLVD earthquakes during the 2018 volcanic activity. (a) MT solution with the ratios of the three MT components and (b) resolvable MT of the M_w 5.3 earthquake of June 26, 2018 with the ratio of the CLVD component k_{CLVD} and the N -axis azimuth ψ obtained from the GCMT Catalog. (c, d) The same as (a, b) but for the M_w 5.1 earthquake of July 5, 2018. All focal mechanisms are shown by projection of the lower focal hemisphere.

with the well-documented intra-caldera fault geometry strongly suggests that we can study geometries of ring faults at volcanoes by analyzing the M_{res} of MT solutions obtained from long-period seismic records at far-field.

3.4. Insights Into Two Vertical-CLVD Earthquakes Before and During the 2018 Eruption

The Sierra Negra caldera renewed its eruption activity at \sim 19:40 on June 26, 2018 (UTC), which lasted until August 23 (Bell et al., 2021; Global Volcanism Program, 2018; Vasconez et al., 2018). The activity included eruptions from several fissure vents along the northern part of the caldera rim and on the northern side of the volcanic flank, and large surface deformation with increased seismicity along the intra-caldera fault system (Bell et al., 2021). Before and during the eruption, two vertical-CLVD earthquakes with $M_w > 5$ were reported near the Sierra Negra caldera: a vertical-T earthquake with M_w 5.3 at 9:15 on June 26, about 10 h before the initiation of the eruption, and a vertical-P earthquake with M_w 5.1 at 0:30 on July 5. Bell et al. (2021) analyzed GPS records at the caldera and attributed the two earthquakes to trapdoor faulting events on the intra-caldera fault structure. This indicates the ring-faulting origin of the earthquakes.

The difference in the types of vertical-CLVD earthquakes (vertical-T or vertical-P) can be explained by flipped kinematics of slips on inward-dipping ring faults. Bell et al. (2021) reported that the first (vertical-T) earthquake took place during the inflation phase of the caldera, preceding the eruption, and caused large uplift of the inner caldera floor; on the other hand, the second (vertical-P) earthquake occurred during a rapid deflation phase after the initiation of the eruption and the caldera floor subsided. Shuler, Nettles, et al. (2013) demonstrated similar temporal relationships between vertical-CLVD earthquakes and an eruption by global observations; in other words, vertical-T earthquakes were often observed before an eruption, whereas most vertical-P earthquakes occurred after an eruption started. Considering the co-seismic deformation patterns of the caldera, it is reasonable to attribute the vertical-T earthquake to upward motion of the central block along an inward-dipping ring fault (Figure 1a), and the vertical-P earthquake to a drop of the block slipping on an inward-dipping ring fault (Figure 1c).

To provide insights into the source geometries of two vertical-CLVD earthquakes, we here analyze their MT solutions from the GCMT catalog (Table 1, Figures 10a and 10c). Focal mechanisms and the parameters (k_{CLVD} and ψ) of M_{res} extracted from the MT solutions of the vertical-T and vertical-P earthquakes are shown in Figures 10b and 10d, respectively. For the vertical-T earthquake, k_{CLVD} is 72.2% and ψ is 86.4° (approximately E-W), and for the vertical-P earthquake, k_{CLVD} is 71.9% and ψ is 55.5° (approximately NE-SW). The small values of k_{CLVD} , 72.2% for the vertical-T earthquake and 71.9% for the vertical-P earthquake, indicate that both earthquakes occurred along short ring faults with arc angles Θ of \sim 80°, according to the relationship between k_{CLVD} and Θ (Figure 4a). In contrast, the significant difference in ψ of \sim 31° implies that

the earthquakes occurred at different locations along the intra-caldera fault system. Using the relationship between the N -axis of \mathbf{M}_{res} and the orientation of the ring fault with $\Theta < 180^\circ$ (top row in Figure 4b), the N -axis of \mathbf{M}_{res} is expected to be parallel to the ring-fault orientation. Therefore, we estimate that the vertical-T earthquake occurred on a ring-fault segment oriented in the E-W direction, whereas the vertical-P earthquake occurred on a different segment oriented in the NE-SW direction. Given the fault structures exposed on the caldera floor (Figure 5b), we suggest that the vertical-T earthquake was generated by reverse slip on the southern intra-caldera fault, which may partially correspond to the fault estimated as generating the 2005 earthquake (the eastern part of black curve in Figure 5b). By contrast, we infer that the vertical-P earthquake occurred on another ring-fault segment on the southeastern or northwestern portion, although we cannot determine which of the two segments from \mathbf{M}_{res} .

We compare our estimations with geodetic observations by Bell et al. (2021), who used GPS data recorded on the caldera floor. The authors reported that the vertical-T earthquake caused large co-seismic uplift of 1.8 and 1.4 m at GPS stations GV09 and GV06, respectively (Figure 5b), which supports our estimation of the vertical-T earthquake along the southern fault. On the other hand, the second earthquake caused large subsidence of 71 cm at GV06, but only 15 cm at GV09. The larger displacement at GV06 than GV09 supports that the main rupture of the vertical-P earthquake was on the southeastern part of the intra-caldera fault, which is consistent with one of the two candidates that we estimate for the geometry of the vertical-P earthquake (i.e., southeastern or northwestern intra-caldera fault). For reference, we indicate the more plausible ring-fault geometry of the vertical-P earthquake by a gray dotted curve in Figure 5b. Thus, we suggest that the clear differences between the parameters of \mathbf{M}_{res} for the two vertical-CLVD earthquakes offer information about significant differences in source locations along the intra-caldera fault system.

4. Discussion

4.1. Efficiency of Long-Period Seismic Excitation From Ring-Faulting

As demonstrated above, the nature of seismic excitation from ring-faulting is very different from that of regular tectonic earthquakes. In general, despite the spectacular surface expression of ring faults, the seismic excitation, especially at long periods (greater than ~ 100 s), is inefficient, which often causes difficulty in interpretation. We have already discussed several specific cases above, and here we add some general discussion to clarify the problem with the inefficient seismic excitation.

There are two aspects to this problem. First, as previously discussed by Ekström (1994) and Shuler, Ekström, et al. (2013), the ring-fault geometry results in cancellation of the source strength, as measured by the scalar moment. As discussed in Section 2, we represent the MT of ring-faulting by the sum of MTs of planar rhomboidal subfaults under the point-source approximation. We then compute the scalar moment M_0 of the ring-faulting using Equation 1. Figure 11a shows the normalized scalar moment defined by:

$$\frac{M_0}{\sum_i \Delta M_0^i} \quad (13)$$

as a function of the dip and arc angles, where ΔM_0^i is the scalar moment of the i -th subfault along the ring fault computed using Equation 1. The normalized scalar moment is generally smaller than 1 owing to the geometrical cancellation of the double-couple components (i.e., \mathbf{M}_{SS} and \mathbf{M}_{DS}).

In addition to this geometrical cancellation, the efficiency of seismic excitation of ring-faulting is reduced because of its shallow source property. As expressed by Equation 6, the MT of ring-faulting can be expressed by the sum of the three components, \mathbf{M}_{CLVD} , \mathbf{M}_{SS} , and \mathbf{M}_{DS} . Because of the very shallow depth, \mathbf{M}_{DS} does not contribute to long-period seismic excitation; by contrast, the other two components (\mathbf{M}_{CLVD} and \mathbf{M}_{SS}), which we referred to as resolvable components, have contributions. The effect of little seismic excitation from \mathbf{M}_{DS} can be expressed by the ratio of the scalar moment of \mathbf{M}_{res} to that of the theoretical MT (Figures 11b):

$$\frac{M_0^{res}}{M_0}, \quad (14)$$




Figure 11. Seismic excitation efficiency of ring-faulting at a shallow source depth. (a) Geometrical cancellation of the scalar moment of idealized ring-faulting, calculated using Equation 13. (b) The ratio of M_0^{res} to M_0 of idealized ring-faulting, calculated using Equation 14. (c) The combined effect of (a) and (b), calculated using Equation 15.

where M_0^{res} is the scalar moment based on Equation 1 for \mathbf{M}_{res} (defined by Equation 11).

Then, the combined effect can be given by:

$$\frac{M_0}{\sum_i \Delta M_0^i} \times \frac{M_0^{res}}{M_0} = \frac{M_0^{res}}{\sum_i \Delta M_0^i}. \quad (15)$$

As shown in Figure 11c, the excitation efficiency of long-period seismic waves from ring-faulting at a shallow depth is generally low, being lower for ring faults dipping more steeply.

The inefficient excitation of long-period seismic waves explains many peculiar characteristics of vertical-CLVD earthquakes. Ring-faulting may generate greater surface deformation than expected empirically from their seismic magnitudes estimated with long-period seismic waves. This may explain that the moment magnitude of the slip model geodetically estimated for an intra-caldera earthquake at the Sierra Negra caldera was much larger than that determined with seismic data independently (Jónsson, 2009). If vertical-T CLVD earthquakes at the submarine volcanoes near Torishima Island and Curtis Island are related to ring-faulting, the disproportionately large tsunamis for their seismic magnitudes may be partially a result of the inefficient seismic excitation. Kanamori et al. (1993) identified an azimuthally uniform radiation pattern of Rayleigh waves and an absence of Love waves from a vertical-T earthquake. This peculiarity can be explained by the inefficient excitation of the DS component, as well as the geometrical cancellation of the double-couple components (Ekström, 1994; Shuler, Ekström, et al., 2013).

4.2. Effect of Volume Change on the Zero-Trace Estimate of the CLVD Component

In previous sections, we estimated the CLVD moment scale M_{CLVD} of ring-faulting, defined by Equation 4, at a very shallow depth, with the assumption of a vanishing isotropic component M_{ISO} , defined by Equation 3. If a volume change occurs near ring-faulting, the estimated M_{CLVD} might be biased. As the bias depends on the geometry of the magma reservoir, we discuss three cases below.

4.2.1. Horizontal Tensile Crack

The MT for a horizontal tensile (or compressional) crack with a volume change ΔV is given in the (r, θ, ϕ) coordinate system by (e.g., Kawakatsu & Yamamoto, 2015)

$$\mathbf{M}_{Tensile} = \Delta V \begin{bmatrix} \lambda + 2\mu & & \\ 0 & \lambda & \\ 0 & 0 & \lambda \end{bmatrix}. \quad (16)$$

As seismic excitation of an MT \mathbf{M} is determined by $(\mathbf{M} : \boldsymbol{\varepsilon})$, where $\boldsymbol{\varepsilon}$ is the strain tensor at the source (Gilbert, 1971), the excitation by the horizontal tensile crack is proportional to $(\lambda + 2\mu)\varepsilon_{rr} + \lambda\varepsilon_{\theta\theta} + \lambda\varepsilon_{\phi\phi}$, which is equal to σ_{rr} , where ε_{rr} , $\varepsilon_{\theta\theta}$, and $\varepsilon_{\phi\phi}$ are the rr , $\theta\theta$, and $\phi\phi$ elements of the strain tensor, respectively, and σ_{rr} is the rr element of the stress tensor. For a very shallow source, $\sigma_{rr} \approx 0$. This means that a very shallow horizontal tensile crack has little seismic excitation (pp. 180–183 of Dahlen & Tromp, 1998; Fukao et al., 2018).

Previous studies have suggested that the Sierra Negra caldera has a sill-like magma reservoir at a depth of ~ 2 km (e.g., Amelung et al., 2000; Chadwick et al., 2006; Jónsson, 2009). Because a volume change of such a shallow sill-like reservoir involves an MT defined by Equation 16 and does not contribute to long-period seismic waves, it is reasonable to attribute the seismic waves from the vertical-CLVD earthquakes at the caldera only to ring-faulting, as done in Section 3.

The case for a horizontal tensile crack has an important implication for other types of volume change. $\mathbf{M}_{Tensile}$ can be decomposed as:

$$\Delta V \begin{bmatrix} \lambda + 2\mu & & & \\ & 0 & \lambda & \\ & & & \lambda \\ & & & & \lambda \end{bmatrix} = \left(\lambda + \frac{2}{3}\mu \right) \Delta V \begin{bmatrix} 1 & & & \\ & 0 & 1 & \\ & & & 1 \\ & & & & 1 \end{bmatrix} + \frac{4}{3}\mu \Delta V \begin{bmatrix} 1 & & & \\ & 0 & -0.5 & \\ & & & -0.5 \\ & & & & -0.5 \end{bmatrix}. \quad (17)$$

The first and second terms on the right-hand side represent isotropic and CLVD sources, respectively. Thus,

the vanishing excitation by a horizontal tensile crack simply means that a unit isotropic tensor $\begin{bmatrix} 1 & & \\ & 0 & 1 \\ & & 0 & 0 & 1 \end{bmatrix}$

is equivalent to a CLVD tensor $-\frac{4\mu}{3\lambda + 2\mu} \begin{bmatrix} 1 & & \\ & 0 & -0.5 \\ & & 0 & -0.5 \end{bmatrix}$ for seismic excitation at a very shallow depth.

4.2.2. Spherical Source

If the deformation below ring-faulting is represented by a spherical source given by an MT

$$\mathbf{M}_{Sphere} = \Delta V \begin{bmatrix} \lambda + \frac{2}{3}\mu & & & \\ & 0 & \lambda + \frac{2}{3}\mu & \\ & & & \lambda + \frac{2}{3}\mu \\ & & & & \lambda + \frac{2}{3}\mu \end{bmatrix} = M_{ISO}^{Sphere} \begin{bmatrix} 1 & & \\ & 0 & 1 \\ & & 0 & 0 & 1 \end{bmatrix}, \quad (18)$$

where

$$M_{ISO}^{Sphere} = \left(\lambda + \frac{2}{3}\mu \right) \Delta V, \quad (19)$$

then, using the equivalence relation between the isotropic and CLVD tensors, the CLVD moment scale of ring-faulting at a shallow depth is observed as a CLVD source with

$$M'_{CLVD} = M_{CLVD} - \frac{4\mu}{3\lambda + 2\mu} M_{ISO}^{Sphere} = M_{CLVD} - \frac{4}{3}\mu \Delta V. \quad (20)$$

Thus, to estimate M_{CLVD} for ring-faulting, we need to add $\frac{4}{3}\mu \Delta V$ to the observed M'_{CLVD} estimated with the assumption of $\Delta V = 0$.

4.2.3. Vertical Cylindrical Source

If the deformation below ring-faulting is represented by a vertical cylindrical source given by an MT

$$\begin{aligned} \mathbf{M}_{Cylinder} &= \Delta V \begin{bmatrix} \lambda & & & \\ & 0 & \lambda + \mu & \\ & & & \lambda + \mu \\ & & & & \lambda + \mu \end{bmatrix} = \left(-\frac{2}{3}\mu \Delta V \right) \begin{bmatrix} 1 & & & \\ & 0 & -0.5 & \\ & & & -0.5 \\ & & & & -0.5 \end{bmatrix} + \left(\lambda + \frac{2}{3}\mu \right) \Delta V \begin{bmatrix} 1 & & \\ & 0 & 1 \\ & & 0 & 0 & 1 \end{bmatrix} \\ &= M_{CLVD}^{Cylinder} \begin{bmatrix} 1 & & \\ & 0 & -0.5 \\ & & 0 & -0.5 \end{bmatrix} + M_{ISO}^{Cylinder} \begin{bmatrix} 1 & & \\ & 0 & 1 \\ & & 0 & 0 & 1 \end{bmatrix}, \end{aligned} \quad (21)$$

where

$$M_{CLVD}^{Cylinder} = -\frac{2}{3}\mu \Delta V \quad (22)$$




Figure 12. Effects of an isotropic source on estimation of the CLVD source. Synthetic long-period seismic waveforms of (a) a CLVD source (Equation 25), (b) an isotropic source (Equation 26), and (c) a horizontal tensile source (Equation 27). The MT of the horizontal tensile crack consists of CLVD and ISO components with a ratio of $M_{ISO} : M_{CLVD} = \left(\lambda + \frac{2}{3}\mu\right) : \frac{4}{3}\mu$, as given in Equation 17. The centroid depth is assumed to be 2.5 km in the crust. The station location and filtering procedure are the same as those used in Figure 3.

and

$$M_{ISO}^{Cylinder} = \left(\lambda + \frac{2}{3}\mu\right)\Delta V, \quad (23)$$

then, considering the additional isotropic and CLVD components from the vertical cylindrical source, the CLVD moment scale of ring-faulting is equivalent to a CLVD source with

$$\begin{aligned} M'_{CLVD} &= M_{CLVD} + \left(M_{CLVD}^{Cylinder} - \frac{4\mu}{3\lambda + 2\mu} M_{ISO}^{Cylinder} \right) \\ &= M_{CLVD} + \left\{ -\frac{2}{3}\mu \Delta V - \frac{4\mu}{3\lambda + 2\mu} \left(\lambda + \frac{2}{3}\mu\right) \Delta V \right\} \\ &= M_{CLVD} - 2\mu \Delta V. \end{aligned} \quad (24)$$

Thus, we need to add $2\mu \Delta V$ to the observed M'_{CLVD} to estimate M_{CLVD} for ring-faulting.

To illustrate the equivalence relation between the isotropic and CLVD tensors discussed above, we show synthetic long-period waveforms computed for a CLVD source, an isotropic source, and a horizontal tensile crack source (Figure 12). For this comparison, we use a common metric for M_{CLVD} , M_{ISO} , and $M_{Tensile}$. If we

use the definition of a scalar moment M_0 , given by Equation 1, then a CLVD source, $\begin{bmatrix} 1 & & \\ 0 & -0.5 & \\ 0 & 0 & -0.5 \end{bmatrix}$, an

isotropic source, $\begin{bmatrix} 1 & & \\ 0 & 1 & \\ 0 & 0 & 1 \end{bmatrix}$, and a horizontal tensile crack source, $\begin{bmatrix} \lambda + 2\mu & & \\ 0 & \lambda & \\ 0 & 0 & \lambda \end{bmatrix}$, can be written, respec-

tively, as

$$M_0 \begin{bmatrix} \sqrt{4/3} & & \\ 0 & -\sqrt{1/3} & \\ 0 & 0 & -\sqrt{1/3} \end{bmatrix}, \quad (25)$$

$$M_0 \begin{bmatrix} \sqrt{2/3} & & \\ 0 & \sqrt{2/3} & \\ 0 & 0 & \sqrt{2/3} \end{bmatrix}, \quad (26)$$

and

$$M_0 \sqrt{\frac{2}{(\lambda + 2\mu)^2 + 2\lambda^2}} \begin{bmatrix} \lambda + 2\mu & & \\ 0 & \lambda & \\ 0 & 0 & \lambda \end{bmatrix}. \quad (27)$$

Here, we use the same scalar moment of $M_0 = 1.0 \times 10^{18}$ N m (M_w 5.9). The waveforms for the CLVD and isotropic sources are quite similar to each other, except for the polarity and amplitude (Figures 12a and 12b). Figure 12c shows waveforms for the horizontal tensile source. The amplitudes are very small, reflecting the cancellation effects of \mathbf{M}_{CLVD} and \mathbf{M}_{ISO} .

4.3. Limitations in Analysis of Long-Period Seismic Waves From Ring-Faulting

We have demonstrated the usefulness of MT inversion using long-period seismic waveforms for studying slip kinematics and geometries of ring faults at active volcanoes. However, limitations in the use of long-period seismic waves remain. Some MT elements of ring-faulting are inefficient for generating long-period seismic waves, so that parts of source parameters cannot be determined only with the records. The temporal-spatial history of rupture propagation along a ring fault may not be resolved owing to the long-period property. Additionally, our method assumes simple cases of ring-faulting, that is, pure dip-slip motion along a circular fault geometry with uniform slip; however, ring-faulting can contain slightly strike-slip motion, complex fault geometry, and nonuniform slip distribution. To recover such detailed information of ring-faulting, shorter-period seismic waves may be utilized with heterogeneous 3-D velocity structures around the calderas (e.g., Contreras-Arratia & Neuberg, 2019; Hejrani & Tkalčić, 2020). Also, recent studies demonstrated that inversion analysis using a simple 1-D Earth model can affect the MT inversion results (Hejrani et al., 2017; Hjörleifsdóttir & Ekström, 2010); hence, effects of the 3-D velocity structures on the resolvable MTs need to be further examined. It is also difficult to constrain a source with a volume change that may accompany ring-faulting by using long-period seismic waves alone. To constrain the mechanism of a source with a change in volume, geodetic observations of surface deformation using such as GPS, tiltmeters, or InSAR are useful (e.g., Anderson et al., 2019; Segall et al., 2019, 2020; Yun, 2007). Combinations of seismic analyses with geodetic observations will provide more details about source processes of ring-faulting that involve volume change of a magma reservoir.

5. Conclusions

In this study, we investigated how source parameters of ring-faulting are related to MTs of vertical-CLVD earthquakes determined with long-period seismic waves. Avoiding the indeterminate issue of the vertical dip-slip component for shallow earthquakes, we proposed a new method to estimate the arc angle and the orientation of the ring fault based on two physical parameters, namely, the CLVD ratio k_{CLVD} and the N -axis azimuth ψ , of the resolvable MT \mathbf{M}_{res} , which is composed of the vertical-CLVD and vertical strike-slip components. Through a case study of the 2005 vertical-CLVD earthquake at the Sierra Negra caldera, we showed the stability of \mathbf{M}_{res} obtained by MT inversion using long-period seismic records at far-field. We also demonstrated that the ring-fault parameters estimated with \mathbf{M}_{res} were consistent with the geometry of the ring fault identified by geodetic observations and field surveys. In addition, we pointed out clear differences between \mathbf{M}_{res} of two vertical-CLVD earthquakes during the 2018 activity at the caldera and suggested significant differences in the kinematics and source locations of the two ring-faulting events. Analyses of long-period seismic waves from moderate vertical-CLVD earthquakes observed globally allow remote estimation of ring-fault parameters at active volcanoes even without local observation networks. A better understanding

of ring-faulting will provide insights into interactions of fault systems at volcanoes with magmatic processes, potentially leading to assessments of volcanic hazards.

Data Availability Statement

The authors used topography and bathymetry data downloaded from the Advance Land Observation Satellite (ALOS) World 3D-30 m DEM (AW3D30; available from <https://www.eorc.jaxa.jp/ALOS/en/index.htm>) provided by the Japan Aerospace Exploration Agency (JAXA), and from GEBCO_2020 Grid (available from https://www.gebco.net/data_and_products/gridded_bathymetry_data/). The W-phase code can be downloaded from <http://wphase.unistra.fr/wiki/doku.php/wphase>. The authors obtained earthquake information from the GCMT Catalog (<https://www.globalcmt.org/>). The authors plotted focal mechanisms representing moment tensors with a MATLAB code developed by James Conder (available from MATLAB Central File Exchange (<https://www.mathworks.com/matlabcentral/fileexchange/61227-focal-mech-fm-centerx-centery-diam-varargin>)). Data sets of MT solutions obtained in this study and used for Figures 7 and S1 are provided in an open access repository, Zenodo (<https://doi.org/10.5281/zenodo.4414990>).

Acknowledgments

The authors thank the editor, Yehuda Ben-Zion, and the two reviewers, Göran Ekström and Babak Hejrani, for their valuable comments and suggestions. The authors also thank Kiwamu Nishida, Shunsuke Takemura, and Tatsuhiko Saito for helpful discussion. This study is funded by the JSPS KAKENHI (Grant numbers JP17J02919, JP20J01689, and JP19K04034), by the JST J-RAPID (Grant number JPMJRR1805), and partially by the Gordon and Betty Moore Foundation. Osamu Sandanbata's travel to the California Institute of Technology was supported by the Overseas Internship Program of the Earthquake Research Institute, the University of Tokyo.

References

- Acocella, V. (2007). Understanding caldera structure and development: An overview of analogue models compared to natural calderas. *Earth-Science Reviews*, 85(3–4), 125–160. <https://doi.org/10.1016/j.earscirev.2007.08.004>
- Aki, K., & Richards, P. G. (2002). *Quantitative seismology*. University Science Books.
- Amelung, F., Jónsson, S., Zebker, H., & Segall, P. (2000). Widespread uplift and 'trapdoor' faulting on Galápagos volcanoes observed with radar interferometry. *Nature*, 407(6807), 993–996. <https://doi.org/10.1038/35039604>
- Anderson, K. R., Johanson, I. A., Patrick, M. R., Gu, M., Segall, P., Poland, M. P., et al. (2019). Magma reservoir failure and the onset of caldera collapse at Kilauea Volcano in 2018. *Science*, 366(6470), eaaz1822. <https://doi.org/10.1126/science.aaz1822>
- Bell, A. F., La Femina, P. C., Ruiz, M., Amelung, F., Bagnardi, M., Bean, C. J., et al. (2021). Caldera resurgence during the 2018 eruption of Sierra Negra volcano, Galápagos Islands. *Nature Communications*, 12(1), 1397. <https://doi.org/10.1038/s41467-021-21596-4>
- Cesca, S., Letort, J., Razafindrakoto, H. N. T., Heimann, S., Rivalta, E., Isken, M. P., et al. (2020). Drainage of a deep magma reservoir near Mayotte inferred from seismicity and deformation. *Nature Geoscience*, 13(1), 87–93. <https://doi.org/10.1038/s41561-019-0505-5>
- Chadwick, W. W., Geist, D. J., Jónsson, S., Poland, M., Johnson, D. J., & Meertens, C. M. (2006). A volcano bursting at the seams: Inflation, faulting, and eruption at Sierra Negra volcano, Galápagos. *Geology*, 34(12), 1025–1028. <https://doi.org/10.1130/G22826A.1>
- Chouet, B. (2003). Volcano seismology. *Pure and Applied Geophysics*, 160(3), 739–788. <https://doi.org/10.1007/PL00012556>
- Chu, R., Zhu, L., & Helmberger, D. V. (2009). Determination of earthquake focal depths and source time functions in central Asia using teleseismic P waveforms. *Geophysical Research Letters*, 36(17), 7–10. <https://doi.org/10.1029/2009GL039494>
- Cole, J., Milner, D., & Spinks, K. (2005). Calderas and caldera structures: A review. *Earth-Science Reviews*, 69(1–2), 1–26. <https://doi.org/10.1016/j.earscirev.2004.06.004>
- Contreras-Arratia, R., & Neuberg, J. W. (2019). Complex seismic sources in volcanic environments: Radiation modelling and moment tensor inversions. *Journal of Volcanology and Geothermal Research*, 381, 262–272. <https://doi.org/10.1016/j.jvolgeores.2019.06.005>
- Contreras-Arratia, R., & Neuberg, J. W. (2020). Towards reconciling seismic and geodetic moment estimations: Case Bárðarbunga. *Journal of Volcanology and Geothermal Research*, 408, 107034. <https://doi.org/10.1016/j.jvolgeores.2020.107034>
- Dahlen, F. A., & Tromp, J. (1998). *Theoretical Global Seismology*. Princeton, N.J: Princeton Univ. Press.
- Darnet, M., Wawrzyniak, P., Tarits, P., Hautot, S., & D'Eu, J. F. (2020). Mapping the geometry of volcanic systems with magnetotelluric soundings: Results from a land and marine magnetotelluric survey performed during the 2018–2019 Mayotte seismovolcanic crisis. *Journal of Volcanology and Geothermal Research*, 406, 107046. <https://doi.org/10.1016/j.jvolgeores.2020.107046>
- Duputel, Z., & Rivera, L. (2019). The 2007 caldera collapse of Piton de la Fournaise volcano: Source process from very-long-period seismic signals. *Earth and Planetary Science Letters*, 527, 115786. <https://doi.org/10.1016/j.epsl.2019.115786>
- Duputel, Z., Rivera, L., Kanamori, H., & Hayes, G. (2012). W phase source inversion for moderate to large earthquakes (1990–2010). *Geophysical Journal International*, 189(2), 1125–1147. <https://doi.org/10.1111/j.1365-246X.2012.05419.x>
- Dziewonski, A. M., & Anderson, D. L. (1981). Preliminary reference Earth model. *Physics of the Earth and Planetary Interiors*, 25(4), 297–356. [https://doi.org/10.1016/0031-9201\(81\)90046-7](https://doi.org/10.1016/0031-9201(81)90046-7)
- Dziewonski, A. M., Chou, T.-A., & Woodhouse, J. H. (1981). Determination of earthquake source parameters from waveform data for studies of global and regional seismicity. *Journal of Geophysical Research*, 86, 2825–2852. <https://doi.org/10.1029/JB086iB04p02825>
- Ekström, G. (1994). Anomalous earthquakes on volcano ring-fault structures. *Earth and Planetary Science Letters*, 128(3–4), 707–712. [https://doi.org/10.1016/0012-821X\(94\)90184-8](https://doi.org/10.1016/0012-821X(94)90184-8)
- Ekström, G., Nettles, M., & Dziewoński, A. M. (2012). The global CMT project 2004–2010: Centroid-moment tensors for 13,017 earthquakes. *Physics of the Earth and Planetary Interiors*, 200–201, 1–9. <https://doi.org/10.1016/j.pepi.2012.04.002>
- Fontaine, F. R., Roullet, G., Hejrani, B., Michon, L., Ferrazzini, V., Barruol, G., et al. (2019). Very- and ultra-long-period seismic signals prior to and during caldera formation on La Réunion Island. *Scientific Reports*, 9(1). <https://doi.org/10.1038/s41598-019-44439-1>
- Frohlich, C. (1994). Earthquakes with non-double-couple mechanisms. *Science*, 264(5160), 804–809. <https://doi.org/10.1126/science.264.5160.804>
- Fukao, Y., Sandanbata, O., Sugioka, H., Ito, A., Shiobara, H., Watada, S., & Satake, K. (2018). Mechanism of the 2015 volcanic tsunami earthquake near Torishima, Japan. *Science Advances*, 4(4), eaao0219. <https://doi.org/10.1126/sciadv.aao0219>
- Geist, D. J., Harpp, K. S., Naumann, T. R., Poland, M., Chadwick, W. W., Hall, M., & Rader, E. (2008). The 2005 eruption of Sierra Negra volcano, Galápagos, Ecuador. *Bulletin of Volcanology*, 70(6), 655–673. <https://doi.org/10.1007/s00445-007-0160-3>
- Geyer, A., & Martí, J. (2014). A short review of our current understanding of the development of ring faults during collapse caldera formation. *Frontiers of Earth Science*, 2, 1–13. <https://doi.org/10.3389/feart.2014.00022>

- Gilbert, F. (1971). Excitation of the normal modes of the Earth by earthquake sources. *Geophysical Journal International*, 22(2), 223–226. <https://doi.org/10.1111/j.1365-246X.1971.tb03593.x>
- Global Volcanism Program. (2005). Report on Sierra Negra (Ecuador). *Bulletin of the Global Volcanism Network*, 30(9). <https://doi.org/10.5479/si.GVP.BGVN200509-353050>
- Global Volcanism Program. (2018). Report on Sierra Negra (Ecuador). *Bulletin of the Global Volcanism Network*, 43(9). <https://doi.org/10.5479/si.GVP.BGVN201809-353050>
- Gudmundsson, M. T., Jónsdóttir, K., Hooper, A., Holohan, E. P., Halldórsson, S. A., Ófeigsson, B. G., et al. (2016). Gradual caldera collapse at Bárðarbunga volcano, Iceland, regulated by lateral magma outflow. *Science*, 353(6296), aaf8988. <https://doi.org/10.1126/science.aaf8988>
- Gusman, A. R., Kaneko, Y., Power, W., & Burbidge, D. (2020). Source process for two enigmatic repeating vertical-T CLVD tsunamis earthquakes in the Kermadec Ridge. *Geophysical Research Letters*, 47(16). <https://doi.org/10.1029/2020gl087805>
- Hanks, T. C., & Kanamori, H. (1979). A moment magnitude scale. *Journal of Geophysical Research*, 84, 2348. <https://doi.org/10.1029/JB084iB05p02348>
- Hayes, G. P., Rivera, L., & Kanamori, H. (2009). Source inversion of the W-phase: Real-time implementation and extension to low magnitudes. *Seismological Research Letters*, 80(5), 817–822. <https://doi.org/10.1785/gssrl.80.5.817>
- Hejrani, B., & Tkalčić, H. (2020). Resolvability of the centroid-moment-tensors for shallow seismic sources and improvements from modeling high-frequency waveforms. *Journal of Geophysical Research: Solid Earth*, 125, 1–13. <https://doi.org/10.1029/2020JB019643>
- Hejrani, B., Tkalčić, H., & Fichtner, A. (2017). Centroid moment tensor catalogue using a 3-D continental scale Earth model: Application to earthquakes in Papua New Guinea and the Solomon Islands. *Journal of Geophysical Research: Solid Earth*, 122(7), 5517–5543. <https://doi.org/10.1002/2017JB014230>
- Hjörleifsdóttir, V., & Ekström, G. (2010). Effects of three-dimensional Earth structure on CMT earthquake parameters. *Physics of the Earth and Planetary Interiors*, 179(3–4), 178–190. <https://doi.org/10.1016/j.pepi.2009.11.003>
- Jónsson, S. (2009). Stress interaction between magma accumulation and trapdoor faulting on Sierra Negra volcano, Galápagos. *Tectonophysics*, 471(1–2), 36–44. <https://doi.org/10.1016/j.tecto.2008.08.005>
- Kanamori, H. (1977). The energy release in great earthquakes. *Journal of Geophysical Research*, 82, 2981–2987. <https://doi.org/10.1029/jb082i020p02981>
- Kanamori, H., Ekström, G., Dziewonski, A., Barker, J. S., & Sipkin, S. A. (1993). Seismic radiation by magma injection: An anomalous seismic event near Tori Shima, Japan. *Journal of Geophysical Research*, 98(B4), 6511–6522. <https://doi.org/10.1029/92JB02867>
- Kanamori, H., & Given, J. W. (1981). Use of long-period surface waves for rapid determination of earthquake-source parameters. *Physics of the Earth and Planetary Interiors*, 27(1), 8–31. [https://doi.org/10.1016/0031-9201\(81\)90083-2](https://doi.org/10.1016/0031-9201(81)90083-2)
- Kanamori, H., & Given, J. W. (1982). Analysis of long-period seismic waves excited by the May 18, 1980, eruption of Mount St. Helens—A terrestrial monopole? *Journal of Geophysical Research*, 87(B7), 5422–5432. <https://doi.org/10.1029/JB087iB07p05422>
- Kanamori, H., Given, J. W., & Lay, T. (1984). Analysis of seismic body waves excited by the Mount St. Helens eruption of May 18, 1980. *Journal of Geophysical Research*, 89(B3), 1856–1866. <https://doi.org/10.1029/JB089iB03p01856>
- Kanamori, H., & Mori, J. (1992). Harmonic excitation of mantle Rayleigh waves by the 1991 eruption of Mount Pinatubo, Philippines. *Geophysical Research Letters*, 19(7), 721–724. <https://doi.org/10.1029/92GL00258>
- Kanamori, H., & Rivera, L. (2008). Source inversion of W phase: Speeding up seismic tsunami warning. *Geophysical Journal International*, 175(1), 222–238. <https://doi.org/10.1111/j.1365-246X.2008.03887.x>
- Kawakatsu, H. (1996). Observability of the isotropic component of a moment tensor. *Geophysical Journal International*, 126(2), 525–544. <https://doi.org/10.1111/j.1365-246X.1996.tb05308.x>
- Kawakatsu, H., & Yamamoto, M. (2015). Volcano seismology. Treatise on geophysics (2nd ed.), (Vol. 4, pp. 389–419). Elsevier B.V. <https://doi.org/10.1016/B978-0-444-53802-4.00081-6>
- McKee, C. O., Lowenstein, P. L., Saint Ours, P., Talai, B., Itikarai, I., & Mori, J. J. (1984). Seismic and ground deformation crises at Rabaul Caldera: Prelude to an eruption?. *Bulletin of Volcanology*, 47(2), 397–411. <https://doi.org/10.1007/BF01961569>
- McNutt, S. R. (2002). 25 Volcano seismology and monitoring for eruptions. *International Geophysics*, 81(A), 383–406. [https://doi.org/10.1016/S0074-6142\(02\)80228-5](https://doi.org/10.1016/S0074-6142(02)80228-5)
- Mori, J., & McKee, C. (1987). Outward-dipping ring-fault structure at Rabaul caldera as shown by earthquake locations. *Science*, 235(4785), 193–195. <https://doi.org/10.1126/science.235.4785.193>
- Mori, J., McKee, C., Itikarai, I., Lowenstein, P., & de Saint Ours, P. (1989). Earthquakes of the Rabaul Seismo-Deformational Crisis September 1983 to July 1985: Seismicity on a Caldera Ring Fault. *Volcanic Hazards. IAVCEI Proceedings in Volcanology*, vol. 1 (pp. 429–462). Springer. https://doi.org/10.1007/978-3-642-73759-6_25
- Neal, C. A., Brantley, S. R., Antolik, L., Babb, J. L., Burgess, M., Calles, K., et al. (2019). The 2018 rift eruption and summit collapse of Kilauea Volcano. *Science*, 363(6425), 367–374. <https://doi.org/10.1126/science.aav7046>
- Nettles, M., & Ekström, G. (1998). Faulting mechanism of anomalous earthquakes near Bárðarbunga Volcano, Iceland. *Journal of Geophysical Research*, 103(8), 17973–17983. <https://doi.org/10.1029/98jb01392>
- Parks, M. M., Heimisson, E. R., Sigmundsson, F., Hooper, A., Vogfjörð, K. S., Árnadóttir, T., et al. (2017). Evolution of deformation and stress changes during the caldera collapse and dyking at Bárðarbunga, 2014–2015: Implication for triggering of seismicity at nearby Tungnafellsjökull volcano. *Earth and Planetary Science Letters*, 462, 212–223. <https://doi.org/10.1016/j.epsl.2017.01.020>
- Reynolds, R. W., Geist, D., & Kurz, M. D. (1995). Physical volcanology and structural development of Sierra Negra volcano, Isabela Island, Galápagos archipelago. *The Geological Society of America Bulletin*, 107(12), 1398–1410. [https://doi.org/10.1130/0016-7606\(1995\)107<1398:PVASDO>2.3.CO;2](https://doi.org/10.1130/0016-7606(1995)107<1398:PVASDO>2.3.CO;2)
- Riel, B., Milillo, P., Simons, M., Lundgren, P., Kanamori, H., & Samsonov, S. (2015). The collapse of Bárðarbunga caldera, Iceland. *Geophysical Journal International*, 202(1), 446–453. <https://doi.org/10.1093/gji/ggv157>
- Sandanbata, O., Watada, S., Satake, K., Fukao, Y., Sugioka, H., Ito, A., & Shiohara, H. (2018). Ray tracing for dispersive tsunamis and source amplitude estimation based on Green's law: Application to the 2015 volcanic tsunami earthquake near Torishima, South of Japan. *Pure and Applied Geophysics*, 175(4), 1371–1385. <https://doi.org/10.1007/s00024-017-1746-0>
- Satake, K., & Kanamori, H. (1991). Abnormal tsunamis caused by the June 13, 1984, Torishima, Japan, earthquake. *Journal of Geophysical Research*, 96(B12), 19933–19939. <https://doi.org/10.1029/91jb01903>
- Segall, P., Anderson, K. R., Johanson, I., & Miklius, A. (2019). Mechanics of inflationary deformation during caldera collapse: Evidence from the 2018 Kilauea eruption. *Geophysical Research Letters*, 46(21), 11782–11789. <https://doi.org/10.1029/2019GL084689>
- Segall, P., Anderson, K. R., Pulvirenti, F., Wang, T., & Johanson, I. (2020). Caldera collapse geometry revealed by near-field GPS displacements at Kilauea Volcano in 2018. *Geophysical Research Letters*, 47, 1–17. <https://doi.org/10.1029/2020GL088867>

- Shearer, P. M. (2009). *Introduction to seismology* (2nd ed.), (Vol. 40). Cambridge University Press. <https://doi.org/10.1017/CBO9780511841552>
- Shelly, D. R., & Thelen, W. A. (2019). Anatomy of a caldera collapse: Kilauea 2018 summit seismicity sequence in high resolution. *Geophysical Research Letters*, *46*(24), 14395–14403. <https://doi.org/10.1029/2019GL085636>
- Shuler, A., & Ekström, G. (2009). Anomalous earthquakes associated with Nyiragongo Volcano: Observations and potential mechanisms. *Journal of Volcanology and Geothermal Research*, *181*(3–4), 219–230. <https://doi.org/10.1016/j.jvolgeores.2009.01.011>
- Shuler, A., Ekström, G., & Nettles, M. (2013). Physical mechanisms for vertical-CLVD earthquakes at active volcanoes. *Journal of Geophysical Research: Solid Earth*, *118*(4), 1569–1586. <https://doi.org/10.1002/jgrb.50131>
- Shuler, A., Nettles, M., & Ekström, G. (2013). Global observation of vertical-CLVD earthquakes at active volcanoes. *Journal of Geophysical Research: Solid Earth*, *118*(1), 138–164. <https://doi.org/10.1029/2012JB009721>
- Silver, P. G., & Jordan, T. H. (1982). Optimal estimation of scalar seismic moment. *Geophysical Journal of the Royal Astronomical Society*, *70*(3), 755–787. <https://doi.org/10.1111/j.1365-246X.1982.tb05982.x>
- Tadono, T., Ishida, H., Oda, F., Naito, S., Minakawa, K., & Iwamoto, H. (2014). Precise global DEM generation by ALOS PRISM. *ISPRS Annals of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, *II-4*, 71–76. <https://doi.org/10.5194/isprsannals-ii-4-71-2014>
- Takeuchi, H., & Saito, M. (1972). Seismic surface waves. *Methods in computational physics: Advances in research and applications* (Vol. 11, pp. 217–295). <https://doi.org/10.1016/B978-0-12-460811-5.50010-6>
- Vasconez, F., Ramón, P., Hernandez, S., Hidalgo, S., Bernard, B., Ruiz, M., et al. (2018). The different characteristics of the recent eruptions of Fernandina and Sierra Negra volcanoes (Galápagos, Ecuador). *Volcanica*, *1*(2), 127–133. <https://doi.org/10.30909/vol.01.02.127133>
- Wimpenny, S., & Watson, C. S. (2020). gWFM: A global catalog of moderate-magnitude earthquakes studied using teleseismic body waves. *Seismological Research Letters*, *92*, 212–226. <https://doi.org/10.1785/0220200218>
- Yun, S.-H. (2007). *A mechanical model of the large-deformation 2005 Sierra Negra volcanic eruption derived from InSAR measurements* (PhD Thesis). Department of Geophysics, Stanford University.
- Yun, S., Segall, P., & Zebker, H. (2006). Constraints on magma chamber geometry at Sierra Negra Volcano, Galápagos Islands, based on InSAR observations. *Journal of Volcanology and Geothermal Research*, *150*(1–3), 232–243. <https://doi.org/10.1016/j.jvolgeores.2005.07.009>