

Towards an innovative combined process coupling biodegradation and photo-oxidation for the removal of pharmaceutical residues

Claire Joannis-Cassan, Alfredo S Rodriguez Castillo, Chloé Dezani, Cristian Gómez-canela, Brice Reoyo-Prats, Carole Calas-blanchard, Carlos Barata, Silvia Lacorte, Gaël Plantard

▶ To cite this version:

Claire Joannis-Cassan, Alfredo S Rodriguez Castillo, Chloé Dezani, Cristian Gómez-canela, Brice Reoyo-Prats, et al.. Towards an innovative combined process coupling biodegradation and photo-oxidation for the removal of pharmaceutical residues. Journal of Chemical Technology and Biotechnology, 2021, 96 (3), pp.755 - 763. 10.1002/jctb.6589 . hal-03451090

HAL Id: hal-03451090 https://hal.science/hal-03451090v1

Submitted on 26 Nov 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Towards an innovative combined process coupling biodegradation and photo-oxidation for the removal of pharmaceutical residues

Journal:	Journal of Chemical Technology & Biotechnology
Manuscript ID	JCTB-20-0440
Wiley - Manuscript type:	Research Article
Date Submitted by the Author:	04-Jun-2020
Complete List of Authors:	Joannis-Cassan, Claire; Laboratoire de Génie Chimique, INP-ENSIACET Rodriguez-Castillo, Alfredo Santiago; Laboratoire de Génie Chimique, INP-ENSIACET DEZANI, Chloé; PROMES, UPVD GOMEZ CANELA, Cristiano; IDAEA, Department of Environmental Chemistry REOYO-PRATS, Brice; PROMES, UPVD Calas-Blanchard, Carole; UPVD, Biocapteur-Analyse-Environnement BARATA, Carlos; IDAEA, Department of Environmental Chemistry Lacorte, S; IDAEA, Department of Environmental Chemistry Plantard, G.; PROMES, UPVD
Key Words:	Photocatalysis, Pharmaceuticals, Bioreactors, Waste-Water, Removal, Process Intensification



2		
3	1	Towards an innovative combined process coupling biodegradation and photo-oxidation for the
4 5	2	removal of pharmaceutical residues
6 7	3	Claire Joannis-Cassan ^{1,*} , Alfredo Santiago Rodriguez Castillo ¹ , Chloé Dezani ² , Cristiano Gómez-
8 9	4	Canela ⁵ , Brice Reoyo Prats ² , Carole Calas-Blanchard ^{3,4} , Carlos Barata ⁵ , Silvia Lacorte ⁵ , Gaël Plantard ²
10 11	_	
12	5	¹ Laboratoire de Génie Chimique, Université de Toulouse, CNRS, INPT, UPS, France
13 14	6	² Laboratoire PROcédés, Matériaux et Energie Solaire, PROMES-CNRS UPR8521, Rambla de la
15 16	7	Thermodynamique, Tecnosud, 66100 Perpignan, France
17 18	8	³ Université de Perpignan Via Domitia, Biocapteur-Analyse-Environnement, 66860 Perpignan cedex –
19 20	9	France
21		
22 23	10 11	⁴ Laboratoire de Biodiversité et Biotechnologies Microbiennes, USR 3579 Sorbonne Universités (UPMC) Paris 6 et CNRS Observatoire Océanologique, 66650, Banyuls-sur-Mer, France
23 24	12	
25	13	⁵ IDAEA-CSIC, Department of Environmental Chemistry, Jordi Girona 18-26, 08034 Barcelona,
26 27	14	Catalonia, Spain
28 29	15	* Corresponding author : Claire Joannis-Cassan, Laboratoire de Génie Chimique, 4 allée Emile Monso,
30 31	16	CS 84234, F-31432 Toulouse cedex4, France. Email: <u>claire.joanniscassan@ensiacet.fr</u> , +33(5) 34 32 36
32 33	17	22
34 35	18	22
36 37	19	
38		
39 40	20	
41 42	21	
42 43		
44 45	22	
46 47	23	
48 49 50	24	
51 52	25	
53 54 55	26	
56 57	27	
58 59	28	
60	29	

1 Abstract

BACKGROUND: Occurrence of pharmaceutical compounds in wastewater has become a major concern for human health and the environment. Therefore, it is challenging to improve the conventional wastewater treatment to remove these compounds. Coupling a biological treatment with an advanced oxidation technology has been widely studied in the literature, but only sequential associations of the two processes have been used. This study proposes an innovative concept based on a real integration of the photocatalytic oxidation process in a continuous recycling loop on a membrane bioreactor. The role of the oxidation is not here to completely degrade pharmaceuticals, but to oxidize them moderately to increase their biodegradability so that they can be eliminated by the biological process.

10 RESULTS: Preliminary experiments on oxidation process indicated that a flux density of 5 W.m⁻² was 11 sufficient to increase biodegradability and decrease toxicity of a cocktail of 3 pharmaceuticals. Then 12 performances of a 20-L continuous membrane bioreactor treating wastewater with 7 pharmaceuticals, 13 without and with pre-oxidation at 5 W.m⁻² were compared. Pre-oxidation has increased the global 14 removal for some recalcitrant pharmaceuticals (from 3 to 47 % for diclofenac and for 1 to 44 % for 15 furosemide) without affecting neither the removal of carbon, nitrogen and phosphorous by activated 16 sludge neither the removal of already highly removed pharmaceuticals.

17 CONCLUSION: This work proves the feasibility and interest of the innovative concept of a continuous
hybrid process coupling a photocatalytic oxidation process and a membrane bioreactor for the treatment
19 of pharmaceuticals in wastewater, with a low cost and size.

Key words: membrane bioreactor, photocatalytic oxidation, micropollutants, pharmaceuticals, hybrid
 process, wastewater treatment

22 Introduction

In the last three decades, an increasing number of research papers have reported the presence of
pharmaceutical compounds (PhCs) in almost all water bodies, including surface waters, ground water,
seawater but also drinking water, at range from ng.L⁻¹ to mg.L⁻¹ all around the world.^{1,2,3} European Union
(EU) monitoring found diclofenac as the most common polar pharmaceutical in natural waters.⁴ Other

molecules - such as sulfamethoxazole, gemfibrozil, atenolol, naproxen, propranolol, ibuprofen, etc. - were commonly found in the aquatic environment.⁵ Carbamazepine, an antiepileptic drug, was also frequently detected in groundwater and surface water.^{5,6} Pharmaceuticals have become one of most important class of emerging organic micropollutants since they are persistent and bioactive compounds that could affect aquatic organisms even at very low concentrations.^{1,3,6,7} Main source of pharmaceutical pollution in the environment comes from wastewater treatment plants (WWTP) effluents, mainly composed by domestic and industrial wastewaters but also receiving hospital or elderly house effluents which are released untreated to the sewage grid.^{1,3,8-10} Due to their intrinsic characteristics of high polarity and stability, most of PhCs are not removed by conventional activated sludge (CAS) in WWTP.^{2,3,5,7} They are consequently continuously released into the aquatic surfaces and their increasing occurrence has become a major environmental and human health concern. Membrane bioreactors (MBRs) have shown a higher efficiency than CAS in removing many pharmaceuticals due to longer sludge retention time and higher suspended solids that favor higher biodiversity and promote stability against high load variations.^{5,8} However, some pharmaceuticals remain poorly biodegraded even by MBR, including carbamazepine (CBZ) which is one of the most biorecalcitrant drug.^{2,5}

To improve the removal efficiency of pharmaceutical compounds, coupling the biological treatment with complementary technologies including adsorption on activated carbon, membrane separation processes or advanced oxidation processes (AOP) have been studied.^{1,11-13} Contrary to the two first technologies that only consist in a phase-transfer of micropollutants, AOP could efficiently respond to the problem posed by biorecalcitrant drugs due to their ability to non-selectively degrade micropolluant molecules.¹⁴⁻¹⁶ Recent works have shown that AOP can significantly reduce effluent toxicity, increase biodegradability or allow mineralization of many molecules: pesticides, industrial products even at high concentrations¹⁷, but also pharmaceutical emerging residues at lower concentrations.^{15,16,18-21} With these considerations, AOPs could be used as a pre-treatment of biological processes in order to increase biodegradability of the pollutants or as a post-treatment in order to degrade the micropollutants not completely removed by the biological process. These different combinations have been recently reviewed for emerging contaminants in wastewater.^{1,5,20-25} It appears that AOP could be ineffective as a pre-treatment, due to the complexity of the wastewater matrix characterized by a high concentration of biodegradable compounds and very low

concentration of the targeted micropollutants²⁵. That is why most frequent combinations of
 biological/advanced oxidation processes reported in the literature concern a biological step followed by
 AOP such as ozonation, photo-Fenton or heterogeneous photocatalysis oxidation with TiO₂.^{1,5,22}
 Nevertheless, formation of oxidation intermediates more toxic than the parent compounds may occur
 depending on the applied conditions.^{11,22,24,25}

Thus, this study aims to propose an innovative concept based on an effective integration of a biological process and a AOP, in which AOP is placed in a continuous recirculation loop on the biological process (Figure 1). The objective of the AOP is not a complete mineralization of the biorecalcitrant molecules, but a moderate oxidation to increase their biodegradability in order they could be removed by the biological process. This hybrid process would intensify the biological one thanks to the synergetic effect of the two processes. A MBR has been chosen as biological process since it is more efficient for pharmaceutical removal and less sensitive to high load variation⁵. Among AOP, heterogeneous photocatalysis with TiO₂, one on the most studied oxidation process,^{15,26} has been selected as it can be driven by solar radiation and so reduce costs and environmental impacts of the process.¹³

The main objective of this paper was to assess the feasibility and performance of this integrated system for the treatment of pharmaceutical micropollutants in wastewater. Three pharmaceuticals widely investigated in the literature: ibuprofen (IBU), diclofenac (DCF) and carbamazepine (CBZ) have been first selected as model molecules with high, moderate and low biodegradation potential respectively. Then, four additional molecules among the most frequently found in wastewater from retirement homes¹⁰ have also been added: furosemide (FUR), levetiracetam (LEV), amylmetacresol (AMY) and paracetamol (PAR). To demonstrate the feasibility of this hybrid system, this work was divided into two distinct steps. First, preliminary experiments were conducted on a continuous photo-oxidation process alone with the aim to determine the best oxidation conditions (flux density) that make the effluent biodegradable (Figure 1, experiment \mathbf{Q}). Then, a 20L-MBR was operated in a continuous mode to treat first wastewater without oxidation (with native molecules) as a reference (Figure 1, experiment **0**) and then an effluent previously oxidized with the optimal conditions (Figure 1, experiment **③**). Carbon, nitrogen, phosphorous and pharmaceutical removal performances as well as effluent toxicity using Zebra fish as model organism were investigated.

Material and methods

Pharmaceuticals. IBU, DCF, CBZ, FUR, AMY, LEV, PAR were purchased from Sigma–Aldrich
(purity >98%). Stock solutions were prepared at concentration of 10 mg.L⁻¹ per compound. All solutions
were prepared in ultrapure water (> 17.5 mΩ.cm) stored at 4°C and used within one month.

Photo-oxidation reactor experiments. Based on a plan-type model configuration illustrated in Figure 2, the experimental setup is built of a continuous photoreactor running under controlled flow rate (O) and irradiated thanks to a panel of LEDs.²⁷ The photo-reactor is a parallelepiped window (4) with a width of 10 cm, a length of 15 cm and a thickness of 1 cm. A plate of transparent PMMA UV radiation (90%) is fixed to transmit radiation coming from the LEDs. The LED panel (5) is included in a closed chamber to isolate it from any external light source. The UV flux density (I) can be modulated between 1 and 110 W.m⁻². A multi-channel peristaltic pump (Watson Marlow 205 CA) (1) feeds the photoreactor with continuous flow rate ($Q = 5 \text{ mL.min}^{-1}$) of the solution to be oxidized. A previously optimized concentration of 2 g.L⁻¹ of TiO₂ was added in the solution.¹⁸ To ensure homogeneous distribution of the photocatalyst, the photo-reactor is connected to a 0.25 L recirculation loop system (2) thanks to a variable-speed centrifugal pump (Cole-Palmer Instruments) (3). In this way, the photoreactor runs as a continuous stirred tank reactor. Oxidized samples were taken at least 60 minutes after switch on the LED panel in order to be sure that the steady state was reached.

In the first part of this work, preliminary oxidation experiments were performed with IBU, DCF and
CBZ - single or in cocktail - solutions at 10 mg.L⁻¹ in distilled or tap water. Several flux densities (2; 5;
10; 20 and 40 W.m⁻²) were tested. Other operating conditions such as flow rate (Q), pH and temperature
were kept constant. Samples of oxidized solutions were taken for biodegradability, toxicity and
micropollutant concentration measurements.

Then, photo-oxidation at 5W.m⁻² of 15 L of a solution containing all the studied pharmaceuticals (IBU,
DCF, CBZ, FUR, AMY, LEV and PAR) in tap water at a concentration of 4.5 mg.L⁻¹ each, was
performed. This solution was then diluted before being treated by the membrane bioreactor.

26 Membrane bioreactor experiments. A laboratory-scale MBR with a working volume of 20 L (Figure

27 3) was equipped with a Rushton turbine (200 rpm) and temperature, dissolved oxygen and pH probes.

28 A membrane module consisted of a ceramic tubular Membralox® (MF) membrane with surface area of

0.0055 m² and pore size of 0.2 µm (Pall Exekia, France) was located in an external loop. The tangential velocity in the membrane was set to 4 m.s⁻¹. At initial time, the bioreactor was seeded with an activated sludge from a real WWTP (Castanet-Tolosan, France) with a total suspended solids (TSS) concentration of 2 g.L⁻¹. Then, the MBR was continuously fed with a synthetic wastewater and permeate flowrate was set to 10 L.d⁻¹ (HRT = 48 h). The synthetic wastewater was composed of peptone (640 mg.L⁻¹), meat extract (440 mg.L⁻¹), K₂HPO₄ (28 mg.L⁻¹), NaCl (7 mg.L⁻¹), CaCl₂ (16 mg.L⁻¹), MgSO₄ (8 mg.L⁻¹), NH_4Cl (100 mg,L⁻¹) and NaOAc (80 mg,L⁻¹) diluted in tap water, corresponding to a chemical oxygen demand (COD) of 1000 mg.L⁻¹, a total nitrogen (TN) content of 120 mg.L⁻¹ and a total phosphorous (TP) content of 10 mg.L⁻¹. pH was maintained at 7.2. Cycles of 3 min aeration (dissolved oxygen of 4.5 mg O₂.L⁻¹) / 30 min without aeration allowed aerobic / anoxic conditions for nitrification and denitrification steps.²⁸ A part of activated sludge (1 L) was daily removed from the bioreactor to maintain sludge retention time (SRT) at 20 d. Experiments were carried out in two phases: 15 days without addition of pharmaceuticals (Phase I), then 15 more days by adding micropollutant solution (Phase II). This micropollutant solution consisted in a cocktail of the seven native pharmaceuticals (IBU, CBZ, DCF, LEV, AMY, PAR, FUR at a concentration feeding of 40 µg.L⁻¹ each) for the first campaign (MBR 1). For the second campaign (MBR 2), the same pharmaceutical cocktail was previously oxidized at 5 W.m⁻² by the photoreactor before feeding the membrane bioreactor. For each campaign, samples of the feeding solution, membrane permeate, purge and mixed liquor were taken every two days at the end of the anoxic phase to be characterized (TSS, VSS, COD, TN, NH₄⁺, NO₂⁻, NO₃⁻). During phase II, adequate volume of permeate were also sampled every three days for pharmaceutical concentration quantification and once a week for toxicity measurement. All the samples were collected in 20 mL glass vials and were frozen at -18°C until analysis. Physicochemical characterization of wastewater. A 20 mL sample were centrifuged at 13,500 g during

Physicochemical characterization of wastewater. A 20 mL sample were centrifuged at 13,500 g during
15 min and supernatant was analyzed by means of HACH Kits. The parameters and corresponding
HACH Kits were: Chemical Oxygen Demand (COD) (LCK 314 and LCK 514), Total Nitrogen (TN)
(LCK 338), NH₄-N (LCK 303 or LCK 301), NO₂-N (LCK 341), NO₃-N (LCK 340), Total Phosphorous
(TP) (LCK 350).

Sludge characterization. The concentrations of Total Suspended Solids (TSS) and Volatile Suspended
 Solids (VSS) were measured according to standard methods 2540D and 2540E.²⁹

Biodegradability assay. Biodegradability of micropollutant solution (pharmaceutical cocktail or oxidized pharmaceutical cocktail) was determined using biological oxygen demand (BOD₂₈) (OECD 301)³⁰ based on oxygen amount required by an activated sludge to metabolize micropollutants during 28 days. BOD₂₈ was measured tanks to a respirometry apparatus (OxiTop C, WTW). Flasks were prepared in duplicate with mineral solution³⁰ and either sample (S) or distilled water to measure endogenous respiration (ER) of sludge or a solution of glucose and glutamic acid³⁰ for activity control of the activated sludge. Volume of mineral solution and sample were adjusted according to their COD concentration³⁰. Activated sludge came from the WWTP of Castanet Tolosan (France) and was inoculated, after washing three times with distilled water, at a final concentration of 0.05 g.L⁻¹. Biodegradability of micropollutant solution was expressed as a percentage of oxygen depletion relative to their COD concentration:

14 Biodegradability (%) =
$$\frac{BOD_{28}^{S} - BOD_{28}^{ER}}{COD}$$
 (Eq. 1)

15 where BOD_{28}^{ER} is measured in endogenous respiration flask and BOD_{28}^{S} is the value of sample flask.

Analysis of pharmaceuticals. Water samples were unfrozen the same day of the analysis. Samples from the MBR experiment were filtered through 0.22 nylon filters to remove particulate matter. Then, aliquots of this water were collected in chromatographic amber vials. For high concentrations, a dilution of 1/100 was performed in water. Liquid chromatography coupled to tandem mass spectrometry (LC-MS/MS,TQD, Waters, Mildford, USA) was used for pharmaceutical analysis.³¹ Drugs were measured under positive electrospray ionization (ESI+), except for ASP and FUR that were detected in negative electrospray ionization (ESI-). Chromatographic separation was performed using a Synergy Polar-RP column (250 mm x 4.6 mm, particle size 4um, Phenomenex, Torrace, USA). The mobile phases were a binary mixture with 0.1% of formic acid in acetonitrile (A) and 0.1% formic acid in water (B). Gradient elution started at 10% A, increasing to 70% A in 20 minutes and to 100% in 5 minutes, held for 7 minutes and returned to initial conditions after 3 minutes. The analysis run time was 35 minutes. Flow rate was set at 0.4 mL.min⁻¹. Sample tray was maintained at 5°C. 10 µL of the sample were directly injected into the LC-MS/MS system. All data were acquired and processed using Masslynx v 4.1 software (Waters).

Two MS/MS transitions were used to monitor each compound and for confirmation their ion ratios were evaluated. Quantification was done using the most abundant transition. External standard calibration was used to calculate the concentration of pharmaceuticals. The system was linear over the range 0.01-2.5 ng.μL⁻¹ (R2>0.99) for all compounds. Compounds were efficiently recovered with the direct injection analysis (from 69 to 117%).

Toxicity assay. The procedure previously reported by Raldúa et al. (2008)³² with minor modifications was followed. Embryos from wild type zebrafish were obtained by natural mating and maintained in fish water [reverse-osmosis purified water containing 90 µg.mL⁻¹ of Instant Ocean (Aquarium Systems, Sarrebourg, France) and 0.58 mM $CaSO_4 \cdot 2H_2O$ at 28.5°C on a 12 h light: 12 h dark cycle. Zebrafish embryos were transferred to 48-well microplates (1 larva per well) each well containing 1 mL of media, and exposed from 6 hpf to 120 hpf, 24 embryos were used for each condition. Viability of embryos was checked at 24, 48 and 120 h. Dead embryos or malformations were reported as endpoints at the end of the experiment. All procedures were conducted in the animal facility of CID-CSIC in accordance with institutional guidelines under a license from the local government (agreement number 9027) and approved by the Institutional Animal Care and Use Committee. Water samples were kept frozen at -20°C until toxicological analyses. Firstly range finding test were conducted to determine the optimal dilution to achieve mortalities in initial samples lower or closer to 100% but greater than 50%. Then all samples were assayed at the dilution having the greater number of responses ($\leq 100\%$) across treatments. Samples were diluted using zebrafish water. Dilutions ranged from no dilution (x 1) to 1/16. CBZ alone did not produce embryotoxic effects in zebrafish at 10 mg.L⁻¹, thus this drug alone was not assayed. Each trial has a control with zebrafish water and the assay was considered valid if mortality (arrest or embryo malformation) in controls was < 5%.

Performance of pollutants (COD, N, P) or pharmaceutical removal for both MBR and photo-oxidation
processes were assessed with global removal efficiencies (RE), calculated as follow:

26 RE (%) =
$$\frac{(C_{IN} - C_{OUT})}{C_{IN}}$$
 (Eq. 27 2)

Where C_{IN} and C_{OUT} are the concentrations of the pollutants or pharmaceuticals in the inlet and outlet of
 the processes. For MBR process, C_{OUT} is the concentration in the permeate.

3 Results and discussion

4 Photocatalytic experiments

5 Photo-oxidation of separate pharmaceuticals

Constant operating conditions with a flux density fixed at $I = 10 \text{ W.m}^{-2}$ were used to oxidize solutions containing IBU, DCF and CBZ alone at 10 mg.L⁻¹. Figure 4.a presents the removal efficiency of pharmaceutical photo-oxidation when molecules were oxidized separately. Different behaviors have been observed depending on the molecules: photo-degradation varied from 12% for CBZ, which was the most resistant to oxidation up to 39 % for IBU, which was the most sensitive to oxidation in these experimental conditions. These results confirm that degradation rate depends on the catalyst / molecule pair.¹⁸ Indeed, heterogeneous oxidation mechanism begins with mass transfer from the solution to the catalyst. Since pollutants can only be photo-degraded close to in catalyst surface, which is site of radical production, interactions between pollutant and catalyst are driven by physicochemical characteristics of both molecules (hydrophobicity) and solution (salinity, pH, organic matter content). The impact of the oxidation on biodegradability of these 3 molecules can been seen on Figure 4.b. The biodegradability of CBZ and DCF was zero both before and after photo-oxidation, despite the efficiency of the oxidation process to reduce CBZ and DCF concentrations. It seems that DCF, CBZ and their oxidized transformation products could not be used or transform by activated sludge microorganisms in the conditions used for the biodegradability test. On the contrary, oxidation of DCF solution decreased its toxicity (Figure 4.c) indicating that oxidation transformation products seemed less toxic for the environment even if their could not be biodegraded in the tested conditions. Concerning IBU, its biodegradability before oxidation was quite high (\sim 70%) and increased up to 83% after oxidation, probably due to the higher biodegradability of its oxidation products coupling with a toxicity divided by two after oxidation (Figure 4.c). These first results show the positive effect of the photo-oxidation at I = 10 W.m^{-2} on the biodegradability and toxicity of the three selected micropollutants.

59
60 27 Cocktail effect on oxidation efficiency

The same constant operating conditions with a flux density fixed at $I = 10 \text{ W.m}^{-2}$ were applied on a solution containing a cocktail of CBZ, DCF and IBU at an initial concentration of 10 mg.L⁻¹ each. When in cocktail, the three pharmaceuticals were more recalcitrant to oxidation as photodegradation efficiency varied between 1 and 5 % (Figure 4.d). This could be due to competition phenomena between the molecules and their byproducts on catalyst surfaces that strongly limit photodegradation rate. However, despite the lower photodegradation, the biodegradability of the oxidized cocktail was quite the double of the non-oxidized cocktail (Figure 4.e) and toxicity decreased by 60% (Figure 4.f). Even if they are not well explained by the literature, synergetic effects between native molecules as well as photo-oxidation products clearly influence their impact on living beings, as it can be observed with biodegradability and toxicity tests.

11 Influence of flux density on DCF, IBU and CBZ cocktail

Photo-oxidation experiments were then conducted with the cocktail of DCF, IBU and CBZ, at a concentration of 10 mg.L⁻¹ each, with different flux densities (2; 5; 10; 20 and 40 W.m²). Overall, the photodegradation removal efficiency (Figure 5.a) increased with the flux density. For DCF, that was the most sensitive to photo-oxidation in these conditions, photo-oxidation removal efficiency increased from 0 to 10 W.m⁻² and seemed to stabilize for higher flux densities.

Biodegradability and toxicity of the oxidized solutions also depends on the applied flux density (Figure 5.b). Significant increase was observed for biodegradability until 5 W.m⁻². Above this flux density, biodegradability level was quite constant around a maximal value of 40%. A higher biodegradability was linked to a lower toxicity. Indeed, toxicity decreased when flux density increased and stabilized was around 15%. This demonstrates that photo-oxidation allows to increase the biodegradability of the pharmaceutical solution while reducing its toxicity in the tested conditions. Besides, an increasing the flux density above 5 W.m⁻² does not improve significantly this biodegradability. Thus, with the objective to couple photo-oxidation step with a biological treatment, a flux density value of 5 W.m⁻² was selected to oxidize a synthetic wastewater before its treatment by a membrane bioreactor

26 Membrane Bioreactor experiments

27 Biological treatment of non-oxidized pharmaceuticals

As a reference, the 20-L membrane bioreactor experiment (MBR 1) was performed in a continuous mode to treat a synthetic wastewater containing seven micropollutants frequently detected at the outlet of retirement homes (IBU, DCF, CBZ, LEV, AMY, PAR, FUR) at concentration of 40 µg.L⁻¹ each (Figure 1- Experiment **0**). These pharmaceuticals were added in the synthetic wastewater after a first stage of stabilization of the biological process without pharmaceutical addition. Table 1 summarizes the sludge characteristics and the carbon, nitrogen and phosphorous removal efficiencies before (phase I) and after (phase II) addition of the pharmaceuticals. As can be seen, pharmaceutical addition had little impact on MBR running, excepted for nitrogen removal, which was higher after the addition of the micropollutants. This could be due to a longer adaption time needed to nitrifying biomass to be efficient rather than micropollutant addition. Indeed, before spiking with pharmaceuticals, NH₄⁺ concentration in permeate was about 25 mg.L⁻¹ at the beginning of the experiment and decreased to 6 mg.L⁻¹ after 15 days of running which correspond to the time of micropollutant addition. However, nitrogen removal was limited by the denitrification step as a concentration of NO_3^- in permeate was between 30 and 50 mg.L-1 all along the experiment. This limited impact of native pharmaceutical compounds on COD and TN removal has been often reported in the literature for several pharmaceuticals³³. Only in some studies dealing with high concentration of antibiotics, a decrease in denitrification step was observed.^{34,35} To go further in comprehension, pharmaceutical apparent removals in continuous MBR are reported in Table 2. Three molecules (IBU, PAR, AMY) were highly removed (> 70 %) by the activated sludge, one (LEV) was moderately removed (between 30 and 70 %) and the other three (DCF, CBZ, FUR) were poorly removed (< 30%). For CBZ, apparent removal was negative due to poor biodegradability and possible accumulation in MBR.⁵ This behavior has already been observed in CAS or MBR for the treatment of real effluent and could be explained by the inflow of pharmaceuticals in the conjugated form that are transformed into the original compounds during treatment.³³ For IBU, DCF, CBZ and PAR, the apparent removal efficiencies are in the range of those reported in the literature for MBR experiments (Table 2).^{5,37-39} For FUR removal, only two papers were found,^{38,39} so the comparison with literature should be done with care. To our best knowledge, removal efficiencies in MBR have never been reported before for LEV and AMY. As CBZ, FUR and DCF were poorly biotranformed, coupling of the MBR with the photo-oxidation process is of great interest for global removal of these molecules.

Biological treatment of oxidized pharmaceuticals

A second MBR experiment (Figure 1- Experiment ⁽⁶⁾), called MBR 2 experiment, was performed in the same conditions as MBR 1 experiment except that pharmaceutical solution was previously oxidized at 5 W.m⁻² (Figure 1- Experiment **2**). As for MBR 1, pre-oxidized pharmaceuticals were added after a stage of 15 days without drug supply. As for native pharmaceuticals, no significant difference was observed between the two phases (Table 1). This result is promising since feeding MBR with the oxidized solution did not impact its global removal performances in terms of carbon, nitrogen or phosphorous. Besides pre-oxidation of the pharmaceutical solution at 5 W.m⁻² seems to affect positively the removal of the selected pharmaceuticals. Indeed, considering the MBR performance alone (Table 2 /MBR 2), when the pharmaceutical cocktail has been pre-oxidized at 5 W.m⁻², apparent removal increased for DCF, FUR and LEV. Molecules already highly biodegraded in MBR 1, maintain their high removal efficiency. Only CBZ removal remained negative. These results are in agreement with the increased of biodegradability observed above and the lower toxicity of the effluent. By focusing on pre-oxidation, a slight decrease was observed in concentrations of the parent compound, corresponding to removal efficiencies ranging from 0 % for FUR up to 36 % for PAR (Table 2/Oxidation), as well as a decrease in toxicity from 15 ± 3 % before oxidation to 0 % after oxidation. This could increase the biodegradability of the oxidized solution as previously observed for the cocktail of IBU, DCF and CBZ at higher concentration and so decrease the potential negative impact on sludge. Removal efficiencies of the oxidation / MBR combination reported in Table 2 (Oxidation + MBR 2) were calculated as follow:

$$_{+ MBR_{2}} (\%) = RE_{OX} + (1 - RE_{OX}).RE_{MBR_{2}}$$
 (Eq.

22 3)

REOX

For all pharmaceuticals, removal efficiency increased with addition of the oxidation step comparing to MBR alone (MBR_1). Thus flux density of 5 W.m⁻² was enough to improve the biodegradation of the selected pharmaceuticals by MBR without changing its performance of wastewater treatment. This result validates the feasibility of the concept described in Figure 1 of coupling a MBR with a photooxidation process. A higher removal performance for the less degraded molecules (DCF, CBZ and FUR)

is expected with the continuous coupling of the two processes since continuous recirculation in the photo-oxidation process will generate several oxidation/biodegradation cycles.

Conclusion

The concept of coupling in one process, a biological treatment by a MBR and a photo-oxidation process has been proven for the treatment of pharmaceuticals in wastewater. A flux density of 5 W.m⁻² was sufficient to improve the removal of most of the selected pharmaceuticals by a MBR without changing its performance in carbon, nitrogen and phosphorous treatment. Particularly, global removal (oxidation + MBR) of some recalcitrant compounds such as DCF or FUR, and in a lesser extend CBZ were improved comparing with the MBR without oxidation step. The observed decrease in toxicity of the treated pharmaceutical solutions corroborates pharmaceutical removal and indicates negligible toxicity of the by-products formed. Comparing with a sequential association of biological process and photo-oxidation process usually described in the literature, this innovative concept is expected to be more compact and less expensive and is very promising for an efficient removal of pharmaceuticals in wastewater.

Acknowledgements

This work was supported by the Program "SUDOE" on the project Innovec'EAU 2016-19 under award number SUDOE SOE1/P1/F0173. We thank R. Garcia, and J. J. Huc for their help in designing and building the demonstrator and Victor Pueyo for doing the analysis.

1 References

- Patel M, Kumar R, Kishor K, Mlsna T, Pittman Jr CU, Mohan D. Pharmaceuticals of emerging
 concern in aquatic systems: chemistry, occurrence, effects, and removal methods. *Chem rev* 119(6),
 3510-3673 (2019).
 - 2. Couto CF, Lange LC, Amaral MC. Occurrence, fate and removal of pharmaceutically active compounds (PhACs) in water and wastewater treatment plants—A review. *J Water Process Eng* **32**:100927 (2019).
 - 3. Gogoi A, Mazumder P, Tyagi VK, Chaminda GT, An AK, Kumar M. Occurrence and fate of emerging contaminants in water environment: a review. *Groundw Sustain Dev* 6:169-180 (2018).
- Schröder P, Helmreich B, Škrbić B, Carballa M, Papa M, Pastore C, Dvarioniene J. Status of hormones and painkillers in wastewater effluents across several European states—considerations for the EU watch list concerning estradiols and diclofenac. *Environ Sci Pollut Res* 23(13):12835-12866
 (2016).
- Millanar-Marfa JMJ, Borea L, Hasan SW, de Luna, MDG, Belgiorno V, Naddeo V. Advanced membrane bioreactors for emerging contaminant removal and quorum sensing control, *in Current Developments in Biotechnology and Bioengineering*, ed by Mannina G, Pandey A, Larroche C, Yong Ng H and Hao Ngo H. Elsevier, pp 117-147 (2020).
 - 6. Mompelat S, Le Bot B, Thomas O. Occurrence and fate of pharmaceutical products and by-products, from resource to drinking water. *Environ Int* **35(5)**:803-814 (2009).
- 7. Verlicchi P, Al Aukidy M, Zambello E. Occurrence of pharmaceutical compounds in urban
 wastewater: removal, mass load and environmental risk after a secondary treatment—a review. *Sci Total Environ* 429:123-155 (2012).
 - 8. Clara, M, Strenn, B, Gans O, Martinez E, Kreuzinger N, Kroiss H. Removal of selected pharmaceuticals, fragrances and endocrine disrupting compounds in a membrane bioreactor and conventional wastewater treatment plants. *Water Res* **39(19)** 4797-4807 (2005).
 - 9. Verlicchi P, Al Aukidy M, Galletti A, Petrovic M, Barceló D. Hospital effluent: investigation of the concentrations and distribution of pharmaceuticals and environmental risk assessment. *Sci Total Environ* **430**:109-118 (2012).
- 10.Lacorte S, Luis S, Gómez-Canela C, Sala-Comorera T, Courtier A, Roig B, Oliveira-Brett AM,
 Joannis-Cassan C, Aragonés JI, Poggio L, Noguer T, Lima L, Barata C, Calas-Blanchard
 Pharmaceuticals released from senior residences: occurrence and risk evaluation. *Environ Sci Pollut Res* 25(7):6095-6106 (2018).
- 11.Rivera-Utrilla J, Sánchez-Polo M, Ferro-García MÁ, Prados-Joya G, Ocampo-Pérez R.
 Pharmaceuticals as emerging contaminants and their removal from water. A review. *Chemosphere* 93(7):1268-1287 (2013).
- 12.Luo Y, Guo W, Ngo HH, Nghiem LD, Hai FI, Zhang J, Liang S, Wang XC. A review on the
 occurrence of micropollutants in the aquatic environment and their fate and removal during
 wastewater treatment. *Sci Total Environ* 473:619-641 (2014).
- 13.Prieto-Rodríguez L, Oller I, Klamerth N, Agüera A, Rodríguez EM, Malato S. Application of solar
 AOPs and ozonation for elimination of micropollutants in municipal wastewater treatment plant
 effluents. *Water Res* 47(4):1521-1528 (2013).
- 42 14.Oller I, Malato S, Sánchez-Pérez J. Combination of advanced oxidation processes and biological
 43 treatments for wastewater decontamination—a review. *Sci Total Environ* 409(20): 4141-4166
 44 (2011).
- 45 15.Kanakaraju D, Glass BD, Oelgemöller M. Advanced oxidation process-mediated removal of
 46 pharmaceuticals from water: A review. *J Environ Manage* 219:189-207 (2018).
 - 16.Monteil H, Péchaud Y, Oturan N, Oturan M. A. A review on efficiency and cost effectiveness of
 electro-and bio-electro-Fenton processes: application to the treatment of pharmaceutical pollutants
 in water. *Chem Eng J* 376:119577 (2019).
- 17. Janin T, Goetz V, Brosillon S, Plantard G. Solar photocatalytic mineralization of 2,4-dichlorophenol
 and mixtures of pesticides: kinetic model of mineralization. *Sol Energy* 87:127-135 (2013).
- 58 52 18.Brienza M, Ahmed MM, Escande A, Plantard G, Scrano L, Chiron S, Goetz V. Use of solar advanced
 53 oxidation processes for wastewater treatment: Follow-up on degradation products, acute toxicity,
- 60 54 genotoxicity and estrogenicity. *Chemosphere* **148**:473-480 (2016).

1		
2		
3	1	19. Mahmoud WM, Rastogi T, Kümmerer K. Application of titanium dioxide nanoparticles as a
4	2	photocatalyst for the removal of micropollutants such as pharmaceuticals from water. Cur Opin
5	3	Green and Sustain Chem 6:1-10 (2017).
6	4	20. Yahiat S, Fourcade F, Brosillon S, Amrane A. Removal of antibiotics by an integrated process
7	5	coupling photocatalysis and biological treatment-case of tetracycline and tylosin. Int Biodeter
8	6	Biodegr 65(7):997-1003 (2011).
9	7	21.Almomani F, Bhosale R, Kumar A, Khraisheh M. Potential use of solar photocatalytic oxidation in
10	8	removing emerging pharmaceuticals from wastewater: A pilot plant study. Sol Energy 172:128-140
11	9	(2018).
12	10	22. Ahmed MB, Zhou JL, Ngo HH, Guo W, Thomaidis NS, Xu J. Progress in the biological and chemical
13	11	treatment technologies for emerging contaminant removal from wastewater: a critical review. J
14	12	Hazard Mater 323:274-298 (2017).
15	13	23.Mohajerani M, Mehrvar M, Ein-Mozaffari F. An overview of the integration of advanced oxidation
16	13 14	technologies and other processes for water and wastewater treatment. <i>Int J Eng</i> 3(2) :120-46 (2009).
17		
18 10	15	24. Akpotu S O, Oseghe E O, Ayanda OS, Skelton AA, Msagati TA, Ofomaja AE. Photocatalysis and
19 20	16	biodegradation of pharmaceuticals in wastewater: effect of abiotic and biotic factors. <i>Clean Technol</i>
20	17	<i>Environl</i> 1-21 (2019).
21	18	25.Laera G, Chong MN, Jin B, Lopez, A. An integrated MBR-TiO2 photocatalysis process for the
22	19	removal of Carbamazepine from simulated pharmaceutical industrial effluent. Bioresour Technol,
23	20	102(13) :7012-7015 (2011).
24 25	21	26.Kanakaraju D, Glass BD, Oelgemöller M. Titanium dioxide photocatalysis for pharmaceutical
25 26	22	wastewater treatment. Environ Chem Lett 12(1):27-47 (2014).
26 27	23	27.Kacem M, Plantard G, Brienza M, Goetz V. Continuous-Flow Aqueous System for Heterogeneous
27	24	Photocatalytic Disinfection of Gram-Negative Escherichia coli. Ind Eng Chem Res 56(51):15001-
28 29	25	15007 (2017).
29 30	26	28.Seira J, Sablayrolles C, Montréjaud-Vignoles M, Albasi C, Joannis-Cassan C. Elimination of an
31	27	anticancer drug (cyclophosphamide) by a membrane bioreactor: Comprehensive study of
32	28	mechanisms. <i>Biochem Eng J</i> 114 :155-163 (2016).
33	29	29. American Public Health Association, Eaton, A. D., American Water Works Association & Water
34	30	Environment Federation. Standard methods for the examination of water and wastewater.
35	31	Washington, D.C: APHA-AWWA-WEF (2005).
36	32	30. Test No. 301: Ready Biodegradability. OECD Publishing; 1992. doi:10.1787/9789264070349-en.
37	33	31.Gómez-Canela C, Sala-Comorera T, Pueyo V, Barata C, Lacorte S Analysis of 44 pharmaceuticals
38	34	consumed by elderly using liquid chromatography coupled to tandem mass spectrometry. J
39	35	Pharmaceut Biomed Anal 168:55-63 (2019).
40	36	32.Raldúa D, André M, Babin PJ. Clofibrate and gemfibrozil induce an embryonic malabsorption
41	37	syndrome in zebrafish. <i>Toxicol Appl Pharm</i> 228 :301-314 (2008).
42	38	33.Besha AT, Gebreyohannes AY, Tufa RA, Bekele DN, Curcio E, Giorno L. Removal of emerging
43	39	micropollutants by activated sludge process and membrane bioreactors and the effects of
44	40	micropollutants of activated studge process and memorane of the encets of micropollutants on membrane fouling: A review. <i>J Environ Chem Eng</i> 5(3) :2395-2414 (2017).
45	40 41	
46		34. Meng F, Gao G, Yang TT, Chen X, Chao Y, Na G, Huang LN. Effects of fluoroquinolone antibiotics
47	42	on reactor performance and microbial community structure of a membrane bioreactor. <i>Chem Eng J</i>
48	43	280 :448-458 (2015).
49	44	35.Meng F, Wang Z, Li, Y. Cure of filament-caused MBR fouling in the presence of antibiotics: taking
50	45	ciprofloxacin exposure as an example. <i>Ind Eng Chem Res</i> 51(42) :13784-13791(2012).
51	46	36.Radjenović J, Petrović M. Barceló D. Fate and distribution of pharmaceuticals in wastewater and
52	47	sewage sludge of the conventional activated sludge (CAS) and advanced membrane bioreactor
53	48	(MBR) treatment. Water Res 43(3):831-841 (2009).
54	49	37.Tadkaew N, Hai F I, McDonald JA, Khan SJ, Nghiem LD. Removal of trace organics by MBR
55	50	treatment: the role of molecular properties. Water Res 45(8):2439-2451 (2011).
56	51	38.Kim M, Guerra P, Shah A, Parsa M, Alaee M, Smyth SA. Removal of pharmaceuticals and personal
57	52	care products in a membrane bioreactor wastewater treatment plant. Water Sci Technol 69(11):2221-
58	53	2229 (2014).
59		
60		

39.Park J, Yamashita N, Park C, Shimono T, Takeuchi DM, Tanaka H. Removal characteristics of pharmaceuticals and personal care products: comparison between membrane bioreactor and various biological treatment processes. *Chemosphere* **179**:347-358 (2017).

Table 1. Comparison of mean values of sludge characteristics of continuous MBR before and after addition of native pharmaceuticals (MBR_1) or pre-oxidized pharmaceuticals (MBR_2) during 15 days. (Pharmaceuticals: IBU, DCF, CBZ, LEV, AMY, PAR and FUR at 40 μg.L⁻¹ in synthetic wastewater). TSS: total suspended solid; VSS: volatile suspended solid; COD: chemical oxygen demand; TN: total nitrogen; TP: total phosphorous.

	ME	3R_1	MB R_2			
	Native pharma	ceutical addition	Pre-oxidized pharm	naceutical additio		
	Before adding	After adding	Before adding	After adding		
	micropolluants	micropolluants	micropolluants	micropolluants		
TSS (g.L ⁻¹)	3.2 ± 0.2	4.4 ± 1	2.9 ± 0.1	3.3 ± 0.3		
VSS/TSS (%)	75 ± 4	74 ± 7	77 ± 6	75 ± 8		
COD removal (%)	89.2 ± 2.2	89.2 ± 1.7	90.9 ± 0.8	92.9 ± 1		
TN removal (%)	12.3 ± 5.8	23.6 ± 5.7	41.5 ± 6.2	38.2 ± 4.1		
TP removal (%)	99.8 ± 0.1	99.8 ± 0.1	99.8 ± 0.1	99.8 ± 0.1		

Table 2. Mean apparent removal efficiencies in continuous MBR for a cocktail of pharmaceuticals

2 without pre-oxidation (MBR_1) or with pre-oxidation at a flux density of 5 W.m⁻² (MBR_2)

		IBU	DCF	CBZ	FUR	AMY	LEV	PAR
Without pharmaceutical pre-oxidation	MBR_1 (Figure 1. Exp ●)	97 ± 6 %	12 ±10 %	< 0 %	1 ± 30 %	100 ± 0 %	46 ± 27 %	98 ± 3 %
	Literature range	73/100 ^{5,37,38}	0.2/87 ^{5,37}	-42/51 ^{5,37,38}	65 ^{38,39}	Not found	Not found	>95 ^{5,37}
With pharmaceutical	Oxidation (Figure 1. Exp. ❷)	nd	3%	7%	0%	10%	8 %	36%
	MBR_2 (Figure 1. Exp. �)	nd	45 ± 13 %	< 0 %	44 ± 9 %	74 ± 10 %	84 ± 2 %	97 ± 5 %
pre-oxidation	Oxidation + MBR_2 (Figure 1. Exp. ❷ + ❸)	nd	47%	3%	44%	79%	85 %	98%









