



# Mesures de l'épaisseur de films liquides entre deux surfaces mécaniques en mouvement relatif par conductimétrie : Application pour la lubrification hydrodynamique

Fethi Aloui, Lamia Gaied, Wafik Abassi, Marc Lippert, Maxence Bigerelle

## ► To cite this version:

Fethi Aloui, Lamia Gaied, Wafik Abassi, Marc Lippert, Maxence Bigerelle. Mesures de l'épaisseur de films liquides entre deux surfaces mécaniques en mouvement relatif par conductimétrie : Application pour la lubrification hydrodynamique. CFM 2017 - 23ème Congrès Français de Mécanique, Aug 2017, Lille, France. hal-03465773

**HAL Id: hal-03465773**

**<https://hal.science/hal-03465773>**

Submitted on 3 Dec 2021

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Measurement of thin liquid film thickness between two mechanical surfaces in relative movement using the conductimetry technique: Application for hydrodynamic lubrication

Fethi Aloui <sup>a\*</sup>, Lamia Gaied <sup>a</sup>, Wafik Abassi <sup>b</sup>, Marc Lippert <sup>a</sup> and Maxence Bigerelle <sup>a</sup>

<sup>a</sup> LAMIH CNRS UMR 8201, Department of Mechanical Engineering, University of Valenciennes and Hainaut-Cambrésis (UVHC), Campus Mont Houy, 59313 Valenciennes Cedex 9 - France

<sup>b</sup> IPSA, Department of Mechanical Engineering Energetics and Aerodynamics, 63 Boulevard de Brandebourg, 94200 Ivry-sur-Seine - France

\* Corresponding author: [fethi.aloui@univ-valenciennes.fr](mailto:fethi.aloui@univ-valenciennes.fr)

## Abstract:

*This paper presents an approach for the measurement of liquid film thickness in contact with a rough surface, based on electrical conductance sensor. This type of sensor consists of electrodes implanted on the wall and flush with an electrolyte solution representing the liquid film. Assessing of the generated current between a pair of electrode is used as a measure of the film thickness. The liquid film is contained between two parallel surfaces that one of which is coated with a certain roughness, while the other is smooth. The electrical probes are fixed on the smooth surface and the facing rough surface is removable allowing a free move of the wall. In this way, a rotational or a sliding motion is imposed on the rough wall allowing a browse of an entire surface relative to the electrode, in order to determine the influence of roughness on the film thickness measurements. In addition, a series of signal acquisition was carried out with imposed pressures on the upper plate for the characterization of the effect of the compression of the film on the measured thicknesses. The principle of this electrochemical technique is briefly explained, as well as how the lateral distance between the electrodes impacts the measuring range limit. The experimental setup is described and used to study liquid film flow with several configuration of the wall surface. The obtained results demonstrated the feasibility of this type of non-intrusive estimation, as it was possible to estimate the variable film thickness which is depending on the peaks and valleys of the rough surface. This is promising because measuring this parameter remains difficult. Finally, the analysis of the results made it possible to synthesize the advantages and limitations of this method.*

**Keywords:** Conductimetry, rough surface, film thickness, electrochemical probes