



HAL
open science

Sahayak -An Autonomous COVID Aid Bot

Karthik Raman, Prathamesh S Ringe, Sania Subhedar, Sushlok Shah,
Yagnesh Devada, Aayush Fadia, Kushagra Srivastava, Varad Vaidya, Harshad
Zade, Ajinkya Kamat, et al.

► **To cite this version:**

Karthik Raman, Prathamesh S Ringe, Sania Subhedar, Sushlok Shah, Yagnesh Devada, et al.. Sahayak -An Autonomous COVID Aid Bot. International Symposium of Medical Robotics, GeorgiaTech; IEEE Robotics and Automation Society; National Science Foundation; IEEE; Georgia Center for Medical Robotics, Nov 2021, Atlanta, Georgia, United States. hal-03476539

HAL Id: hal-03476539

<https://hal.science/hal-03476539>

Submitted on 30 Dec 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Sahayak - An Autonomous COVID Aid Bot

Karthik Raman¹, Prathamesh Ringe¹, Sania Subhedar¹, Sushlok Shah¹, Yagnesh Devada¹, Aayush Fadia¹, Kushagra Srivastava¹, Varad Vaidya¹, Harshad Zade¹, Ajinkya Kamat¹, Anshul Paigwar¹, Shital Chiddarwar¹

Abstract—During this COVID-19 pandemic, the need to reduce person-to-person contact in hospitals and quarantine facilities has increased exponentially. Developing an autonomous robot for hospital environments is a potential solution aiming to reduce the risk of infection. This work proposes a general framework for developing medical assistive robots capable of delivering food and medicine to patients and facilitating teleconferencing with doctors. The ideas presented here have been validated extensively in simulated environments employing a Navigation Stack for autonomous mobility, while a teleoperated prototype was deployed at AIIMS Nagpur, India.

I. INTRODUCTION

Healthcare workers are expected to wear uncomfortable and bulky PPE kits for long periods to treat patients infected with highly communicable diseases. There is an acute need for a technological solution that can protect these frontline healthcare workers. We present Sahayak, a COVID Aid Bot that can perform routine tasks, thereby reducing the spread of diseases among the medical personnel [1]. The key contributions of this work are as follows:-

- We present the system architecture of a telepresence robot that can be used for distant consultation and to deliver food and medicines. A prototype based on this design is currently deployed at AIIMS Nagpur, India.
- We open-source the design and framework of Sahayak that can be used to test complex algorithms for autonomous navigation in a hospital environment [2].




Fig. 1: Mechanical Design of Sahayak

II. MECHANICAL DESIGN

Hospital environments have narrow passages and sharp turns that require precise maneuvers. Considering these

¹All authors are associated with Visvesvaraya National Institute of Technology, Nagpur, India and are members of IvLabs

constraints and feedback from the doctors, a 4-wheel drive design was adopted. Sahayak is driven by four planetary DC geared motors. It has heavy-duty disc wheels, a payload capacity of 20 Kg, and a 20Ah lithium-ion battery. Fig. 1(b) illustrates the sensor stack deployed on this robot.

III. AUTONOMOUS NAVIGATION

Autonomous Navigation consists of several cohesive modules, as indicated in Fig 2. Visual Odometry was computed through 3D-2D and 3D-3D motion estimation methods by using a sparse optical flow-based feature tracking method [3]. This odometry information was fused with the IMU readings using an Extended Kalman Filter (EKF). Alternatively, odometry from the RP LiDAR was calculated through an incremental laser scan matcher. The environment was mapped using Real-Time Appearance-Based (RTAB) mapping[4]. Hector SLAM[5] and GMapping [6] were also used since a 2D occupancy grid was sufficient for the locomotion of the robot. The robot was localized on a pre-built map using Adaptive Monte Carlo Localization (AMCL). Point-to-point navigation was achieved through a Global Planner, and a Dynamic Window Approach (DWA) based Local Planner.




Fig. 2: Overview of Autonomous Navigation Pipeline

IV. CONCLUSION AND FUTURE WORKS

We present the design of an autonomously navigating robot that can be deployed at hospitals to reduce the contact between healthcare workers and their patients. Future works will involve provisions for Dynamic Obstacle Avoidance and solutions for the Global Localization problem.

REFERENCES

- [1] AidBots. Aidbots. [Online]. Available: <https://www.aidbots.in/#/>
- [2] IvLabs, “Sahayak,” <https://github.com/IvLabs/Sahayak-v3>, 2021.
- [3] D. Scaramuzza and F. Fraundorfer, “Visual odometry [tutorial],” *IEEE Robotics Automation Magazine*, vol. 18, no. 4, pp. 80–92, 2011.
- [4] M. Labbé and F. Michaud, “Rtab-map as an open-source lidar and visual simultaneous localization and mapping library for large-scale and long-term online operation: Labbé and michaud,” *Journal of Field Robotics*, vol. 36, 10 2018.
- [5] S. Kohlbrecher, J. Meyer, T. Graber, K. Petersen, U. Klingauf, and O. Von Stryk, “Hector open source modules for autonomous mapping and navigation with rescue robots,” 01 2014, pp. 624–631.
- [6] ROS. Ros navigation. [Online]. Available: <http://wiki.ros.org/navigation>