



HAL
open science

Constrained Consensus Sequence Algorithm for DNA Archiving

Dominique Lavenier

► **To cite this version:**

Dominique Lavenier. Constrained Consensus Sequence Algorithm for DNA Archiving. [Research Report] CNRS IRISA. 2021. hal-03479083

HAL Id: hal-03479083

<https://hal.science/hal-03479083>

Submitted on 14 Dec 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Constrained Consensus Sequence Algorithm for DNA Archiving

Dominique Lavenier
Univ. Rennes, CNRS-IRISA, Inria
dominique.lavenier@irisa.fr

Abstract

The paper describes an algorithm to compute a consensus sequence from a set of DNA sequences of approximatively identical length generated by 3rd sequencing generation technologies. Its purpose targets DNA storage and is guided by specific features that cannot be exhibited from biological data such as the exact length of the consensus sequences, the precise location of known patterns, the kmer composition, etc.

1. Introduction

Third generation sequencing technologies provide long reads with a relatively high error rate [1]. An important task in genome assembly, for instance, is to correct these reads using the redundancy resulting from sequencing [2]. Several reads from the same part of the genome are then aligned together in order to generate a DNA consensus sequence. In principle, for de-novo genome assembly, the size and the content of the sequence are unknown.

Here we're posing the problem in a different frame. The sequence to be restored do not come from living organisms, but from sequences that have been synthesized. The target application is the DNA storage or the DNA archiving [3] [4]. Digital files are transcribed into DNA sequences with well-defined structures. For example, a file can be cut into pieces of the same size, each piece having an identifier allowing the original text to be retrieved. The corresponding DNA sequences are therefore of known size and are surrounded by tags that are also known. In addition, since third-generation sequencing technologies are more prone to producing errors in homopolymer zones, the synthesized sequences avoid this type of situation. Consequently, in the DNA sequences, some combinations of nucleotides are forbidden.

Knowing these different constraints (size of known sequences, combination of forbidden nucleotides, known tags surrounding the sequences), the problem of building a consensus sequence can be approached differently.

2. Method

The input is a set of DNA sequences after base calling. We suppose that a pre-processing step has been performed to group the sequences representing the same information. The sequences have thus roughly the same size. Let N be the number of sequences from which we want to find a consensus.

The main idea to get the consensus is to split the N sequences into kmers and to find the best suite of overlapping kmers that represent the information to restore. The method proceeds in two main steps:

1. Construct a kmer overlap graph
2. Search constrained paths into this graph

2.1 Kmer overlap graph

A Kmer overlap graph (KOG) is a directed graph. Nodes of the graph are solid kmers extracted from the N sequences. A solid kmer is defined as a kmer that has been seen more than T times in a data set. Thus, the N sequences are split into overlapping kmers of size K . The value of T , the solid kmer threshold, depends of the number of available sequences.

An edge between two nodes n_i and n_j exists if a suffix of node n_i of size at least L is equal to the prefix of same size of node n_j . Edges are weighted by $K-l$, l being the overlap length between n_i and n_j . The following figure exemplifies the concept.




Figure 1: Principle of the kmer overlap graph. $K = 13$. The suffix of the left node of size 12 (TGACTGGATGAC) is equal to the prefix of the upper node. The weight between these two nodes is thus equal to $13 - 12 = 1$

The expected layout of a kmer overlap graph is an elongated graph. Its shape strongly depends of the kmer size. Short values of K will tend to create loops. Large one may split the graph into different components. Figure 2 shows 3 different kmer overlap graphs built from 100 x 1 Kbp MinION sequences with 3 different values of K (10, 16, 26).




Figure 2: kmer overlap graph built from 100 1Kbp MinION sequences. Left: kmer size = 10. Center: kmer size = 16. Right: kmer size = 26

To get a graph made of a single connected component, with as lowest as possible loops, a strategy is to test different values of K , starting by the highest one, as follows:

```

function makeKOG (Reads)
  K = Kmax
  loop
    Skmer = extractSolidKmer(Reads, K)
    Graph = buildKmerOverlapGraph(Skmer)
    if numberOfConnectComponents(Graph) == 1 then break
    K = K-1
  return Graph

```


The number of connected components is expected to decrease with K . The value of L , the minimum overlapping size between kmers, can also influence the graph connectivity. By default, based on different experimentations, this value is set to $2K/3$.

To minimize loops in the graph, solid kmers have been enhanced with positions. Identical kmers that appear at different positions in the set of reads will be considered as different kmers.

2.2 Search constrained paths

We know that the reads are surrounded by two known short strings. We also know exactly the size of the resulting consensus sequence. As the graph contain kmers of the two surrounding strings, we chose a starting and an ending kmer. A starting kmer (START_KMER) is a solid kmer that belongs to the left surrounding string. Identically, an ending kmer (END_KMER) is a solid kmer that belongs to the right surrounding string. Having identified these two kmers, finding a consensus sequence of length P consists in finding a path of size P between START_KMER and END_KMER in the kmer overlap graph.

Paths are searched as follows: for each node of the graph, we associate a list of paths of different lengths. This list is constructed from the predecessor nodes. Suppose that we want to build the list associated to the right blue dark node (GTGAC) in the example below, and that the lists of the predecessor nodes have already been computed:



The node `GTGAC` has three predecessors. Node `AGTGA` has a list of two paths of length 18 and 17. Node `CAGTG` has a list of one path of length 16. Node `CGTGA` has a list of one path of length 19. Paths are scored according to the solidity of the kmers. The weight of a node is the number of times the kmer is present. The score of a path is the sum of the node weights from the starting kmer to the current node.

More precisely, to compute a list of paths, all paths from the predecessor nodes are updated according to the edge weight and the node weight of the current node. If the edge weight is l , the path is increased by l nucleotides and the score is increased by l times the node weight. If two or more paths with identical length are present, we only keep the path with the highest score.

On the above example, if we suppose that node `GTGAC` has a weight of 22, the path of length 17 (score = 234) of node `AGTGA` generates a new path of length 18 with a score of 256 ($234 + 1 \times 22$). The path of length 16 (score = 209) of node `CAGTG` generates a new path of length 18 with a score of 253 ($209 + 2 \times 22$). Thus, only the path of length 18 with the score of 256 will be kept.

All the paths begin with the starting kmer. After the search process, the `END_KMER` node will gather all the paths we are interested in.

2.3 Implementation

The method has been implemented in python and available through a software called CCSA (constrained consensus sequence algorithm). The following arguments are required:

- Reads in fastq format
- Left and right surrounding sequences in fasta format
- Length of the expected consensus sequence

The CCSA software generates a list of consensus sequences ordered by length in fasta format.

Before the construction of the kmer overlap graph, a few preprocessing steps are performed:

- Reads shorter than the expected consensus sequence length are suppressed.
- Reads are trimmed based on the surrounding sequence similarity. A read can be trimmed if, for each extremity, it has at least one kmer belonging to the left and right surrounding sequences. Reads that don't respect this rule are discarded.


The CCSA software (python code) can be downloaded here from the author web page [5]

3. Experimentation

The evaluation of the CCSA algorithm have been performed on several data sets of synthetic data with and without small homopolymers (≤ 3 nt), and sequenced with a MinION device. The various datasets have the following properties:

	Homopolymers	Seq length	Surrounding. Seq. length
<u>A_900_1</u>	yes	900	42 / 42
<u>A_900_2</u>	yes	900	42 / 45
<u>A_900_3</u>	yes	900	41 / 42
<u>U1_400_1</u>	no	416	42 / 42
<u>U1_400_2</u>	no	416	42 / 42
<u>U2_900_1</u>	no	916	42 / 41
<u>U2_900_2</u>	no	916	41 / 42
<u>U2_900_3</u>	no	916	41 / 42

The CCSA algorithm has then been evaluated for different coverage values. For a coverage C , a subset of C reads (of length larger than the expected length) is randomly extracted from the corresponding dataset, and the CCSA software is run. The process is repeated 100 times.



The following tables report the number of times a consensus sequence of expected length has been found (column #seq), the total number of errors (column #err), and the percentage error computed as $(\#seq \times \text{expected length}) / \#err$ (column %err).

Dataset A_900: sequences with homopolymers

Coverage	A_900_1			A_900_2			A_900_3		
	#seq	#err	%err	#seq	#err	%err	#seq	#err	%err
100	100	0	0	100	63	7.0e-4	100	34	3.8e-4
80	100	1	1.1e-5	98	46	5.2e-4	100	28	3.1e-4
60	100	2	2.2e-5	98	56	6.3e-4	99	34	3.8e-4
40	100	24	2.7e-4	97	68	7.8e-4	96	46	5.3e-4
30	98	35	4.0e-4	90	74	9.1e-4	87	46	6.1e-4
20	84	48	6.3e-4	75	65	9.6e-4	61	40	7.3e-4

Dataset U_400: sequences without homopolymers

Coverage	U1_400_1			U1_400_2		
	#seq	#err	%err	#seq	#err	%err
100	100	0	0	91	1	2.6e-5
80	100	1	2.4e-5	83	1	2.9e-5
60	98	1	2.5e-5	85	4	1.1e-4
40	96	6	1.8e-4	79	16	4.9e-4
30	93	30	7.8e-4	73	20	6.6e-4
20	69	28	9.8e-4	58	25	1.0e-3

Dataset U2_900: sequences without homopolymers

Coverage	U2_900_1			U2_900_2			U2_900_3		
	#seq	#err	%err	#seq	#err	%err	#seq	#err	%err
100	100	0	0	100	2	2.1e-5	100	14	1.5e-4
80	100	2	2.1e-5	100	2	2.1e-5	99	12	1.3e-4
60	100	3	3.2e-5	100	5	5.4e-5	99	31	3.4e-4
40	96	111	1.2e-3	97	51	5.7e-4	96	135	1.5e-3
30	89	354	3.3e-3	89	209	2.5e-3	78	414	5.7e-3
20	77	522	7.2e-3	74	294	4.3e-3	60	638	1.1e-2

The sequences with small homopolymers provide better results. Actually, suppressing homopolymers leads to increase locally the number of short repetitions and, consequently, create small cycles in the graph that prevent correct paths to be found.

For a reasonable coverage, the error rate is quite low, but not null. Error correcting code are still needed to recover the correct information.

Bibliography

- [1] S. Nasrin and A. Rahman, "Exploring Systematic Errors in Sequencing Technologies," *2019 IEEE 19th International Conference on Bioinformatics and Bioengineering (BIBE)*, 2019, pp. 132-137, doi: 10.1109/BIBE.2019.00032.
- [2] Zhang, H., Jain, C. & Aluru, S. A comprehensive evaluation of long read error correction methods. *BMC Genomics* **21**, 889 (2020). <https://doi.org/10.1186/s12864-020-07227-0>
- [3] Yiming Dong, Fajia Sun, Zhi Ping, Qi Ouyang, Long Qian, DNA storage: research landscape and future prospects, *National Science Review*, Volume 7, Issue 6, June 2020, Pages 1092–1107, <https://doi.org/10.1093/nsr/nwaa007>
- [4] Ceze, L., Nivala, J. & Strauss, K. Molecular digital data storage using DNA. *Nat Rev Genet* **20**, 456–466 (2019). <https://doi.org/10.1038/s41576-019-0125-3>
- [5] http://lavenier.net/homepage/?page_id=707

Annex

A_900_1

Primers sequence

left CCAACAACAAGGCACTCATTAACTAAGGTGGAAGCAACTGTT
right ACAACCAGTCGCTGGACAATACAGAAGTAGAAACAACCTCAAC

Reference sequence

CTCCGTCGACAGACATACCATGCCATGAACAGATACCATTTCATGCCGTAAGACCGTAGTTCATCATCCGCTGCGGACCTGCTA
AGACGACGACATACCTGTATACAAACAGGACAAGACGACGTATATATAAGACCATCTATCGCACTAGTTCTATAGACCATACG
GGACCTCGTCATCCGTAACATACCGTACTGGACAGATGGACTACAATTCGACGGACATATGAACAGGACAGACAGGGACGTC
GTCATGTAGGCAAGACGACAAACATGCGGATATCAGGCAAGATATCGAACAAAGCAGAATGTATAGACATGTATAAGGCGAGTT
CGACATAAGGTTCCGCGCTGCTGAATGGATAGATAAGGCCATACGAACATGTATACAGTGCGAACCTGCAAACGTAACAGACT
GCAAGACTCATATAAGACAAACGGACCTGCTATATAAACGTAGTGAATGCCGACGTCAGATATATATACCGTGAGCTAGACAT
ACCGTACGAACCGACAAACGGGACAGGACTCGAACCAGGGGCTATGAATAAGTGTAGACATGCCGTTCTAGACATATAGACCAT
CATAGGACATCATGCTAGAACGGATATACAAACCGAGACAGTGTACGGGCCGACAAACACTGAATGCCGACAGGACAAACCGT
AGATAGTCAAGACGTACGAATAGATGAACGCCAAGCTCAGTTCTCAGGCCGACACTAAAACAAGACCGACAGGGACGAACT
CAGTGCAGCCTCACTGAGCCATGAATAAGACTAGTTTCGAGCGCCGAATATGTATGAACGCAAACATCCGATTCCGACCTCAT
CTACAAACATAGTGCAAGGCAATTCGAACTCCTTCATTGACAGTCATCATACCGTGAATCAGACACTA

A_900_2

Primers sequence

left CCAACAACAAGGCACTCATTACAGCTGGTAATGATGGAACAT
right TTCTTTCAGATTTTTCAAGTTGGACAGAAGTAGAAACAACCTCAAC

Reference sequence

AGGGATAAAGAACAGTCGCCACTGGGCAGTCATTGCAACCAATCCGCGCAACACAGGGCAACATAAGGCGTAACGCATGCTTCC
ATACCTCATATCATGACAAAAGTCTGTGCAGGACCGGACCGCTCGACAGACCTCGGATCGCAAACCGGGATGGACTACAGTGG
TAGTCATCCTCAGGACCGAATAGAATGCTAGCGCACACTGAGCTCATTTCGCTGCGGGATACGGATCGTAGGGCATGGAACGT
AAACGGATGTGAACAGACATCATTTCGACGGGACAAACGCTCTAGTAAACGTACCAGTCGCCGAGCGTATCTAGCTGCAACAAAC
GTACCGTGCAAGTGCCCAACGAATGTGACTAAGAATAAGGCTATACCGTGCAAGCATATAGGACCAAGTATGAGACTCCGCGC
CATACAATCCGGGGACTGGGACACTGTAACCTAAGATATGGAATCATCCGAACACCGGGCCTCAGGCGCGCGTCAAGTGCACC
TACAAGGCCCTTCATATCAAGTCAACAGGCGACAAACAGGGCAGTCCGGATCAAGGGCCTCAGGCAAAAACAGAATACCGAACGA
TTCAAGGCAAGTTCAAATAAGTGGCGTAACGGATAGTATGACGTATGATTCTCCTGGGCGGTGAGACAGTCTACTGAGCCTA
CTAGAACCGGAATACAGACACTATACTAGTAGACTAAGAACATATCAGACAAGGCCGACTCCGTACGCGAATGTGCGCGTAGA
CGCGCGAATGTACGCGAACAGTCGCAGATATCCGTAGAGTTCAACAGGGCCTCGACCGGTGCCTCGACGTGTATACCGGTGCG
GCAGACGAATCAGTCAGTGACATCCTCGCGACACCGACAGGACCGGGATATGGACGCGACGTGCTAGA

A_900_3

Primers sequence

left CCAACAACAAGGCACTCATTACAATTCATCTGTCTTCATTC
right ACTCAACACAATTAACAACGGACAGAAGTAGAAACAACCTCAAC

Reference sequence

GACGAACATCAGACCATCTCAGGTTTCATTCATGTGACTCAGATATATGAGTTTCGACAGACATTCGTATACCATCAGACAGG
TTCATCGAACTCATCATATGAGCAGACATATAAGTTTCATGCCATCCGTCAGGACGTAGACGAACGTGCCATCAGACTCGAATA
GTGTATACCATCGCGGACTCATGTAGGTTTCGTAGACATTCGGTTCATCAAACGAATAGACATGGACCATCGAACAGGCAGACT
CATCAGACGGACCGACAAGACAGGACAGACGGACGAACATCAGGACAAGACATCGAACAGACATCAAACATATGCCATCTCAT
CATATAGACCATTTCGACAGGACCGACATATAGGACGAAACATAGACATATATGAACTCGAACCATCGCCATGCCGTGTAGACGT
ATAGTCGAATAGTCAAACATATGTAGACGAACGTGAATATAGACCGTAGTCGTCAAACGAACCGTATAGGATACCATCAGACT
CGAACCGCGTGTAGTGTAGGATATAGGACATCATCCGTCGTCATGTCATCGAACGTGAACGTAGGTTTCGTGGACTCGACAGGA
TACCATGTGCATCATATAGTCAAGTTCGTCTAGACTCGAACAGGTTTCGTGACTCAGGTTTCGTCAGATATAGTGTATAG
GACATTCAGGACCATCAGGTTTCATTCATCATATCAGACGTTTCATCGACATCAGGACAGGCAAACATAGTGGACTCGCGTGAAC
AAGACATGAGCATCAGGCGAACTCAAACAGACGGACGAACATGCCATCATCAGACGTTTCGTATAGGATATAGTTCAGGCAGACA
GGATAGGACAAACGAACAGACATGTATATGAGCCATCGAACCATCAGACAAACGAACGTCAGACCGTAGT

U1_400_1 / U1_400_2

Primers sequence

left TAGTGTTCATGTATCTCGTCTCATCGTCGTATCTCGTCATCTA
right GCGCTCGACAGATACAGACATCGTGAGCGACGAGCGACGAGC

Reference sequence (U1_400_1) - noHP

GCGACTCATCTGCAGCTCGAGTACAGTCTCTGTAGCGTGTACGATCACATGCATACATGATGTGCATGAGCATGTGTACACAT
ACGATAGTGAGATGTGACTATCGACGAGTCCACAGATACTCTCTCAGATAGTACGCACGAGTCAGCAGTCAGAGCGACGCGCAG
CTCACATCGCGTATGTCTGATATATGTGCGAGATGCTCTCACGACAGAGATACACATCAGTCGACTACAGATACACGTATAACA
GTAGTAGCAGTCTGAGAGATCGACTGCAGCACTGCTCGTACGTGCTGTATGCACGTGAGCTGTGCATCTACGATGATGAGT
GTATGTATATCGATCAGTGTAGCGCATGTAGTCATCGATACTACGCACGATGACACACTAGTCAGTACATCACTCATGTCCGTG
T

Reference sequence (U1_400_2) - DiffMax

GCGACTCGTCTGCTGATCTAGTATAGTCTCTGTGCGCTCGACGATCTCATGTATGTATCGTGTGCATCAGTATGTGTACTCGT
GTGATAGTGTGATGTGAGTGTGATGTGTGCACAGATGATCTCTCAGATCGTATGTACTCGTCTGCAGTCTGTGCGTCTCGCAT
GTCACGTCTCGTGTGTCTGATAGATGTGCTCGATGATCTCATCTCAGTGATAGACGTCAGTCGACTATCGATAGACGTCGACA
GTAGTATCAGTCTGTCAGATCGACTATCTCAGTGATCGTATGTGCTGTGTATGTACGTCGAGTGTATCGACGATGATGTGT
GTATCGATATCGATCAGTGTAGTGTATCTAGTCGTCGATAGTATGTACGATGTCACCTAGTCAGTGTATCTCTCGTGTCCGT
T

U2_900_1

Primers sequence

left CCAACAACAAGGCACTCATTAGTTTATATTTGACTGGCGAAG
right CTGACTCTGCGATCAAGACACAGAAGTAGAAACAACCAAC

Reference sequence (U2_900_1) - noHP

GCGACTCATCTGCAGCTCGAGTACAGTCTCTGTAGCGTGTACGATCACATGCATACATGATGTGCATGAGCATGTGTACACAT
ACGATAGTGAGATGTGACTATCGACGAGTCCACAGATACTCTCTCAGATAGTACGCACGAGTCAGCAGTCAGAGCGACGCGCAG
CTCACATCGCGTATGTCTGATATATGTGCGAGATGCTCTCACGACAGAGATACACATCAGTCGACTACAGATACACGTATAACA
GTAGTAGCAGTCTGAGAGATCGACTGCAGCACTGCTCGTACGTGCTGTATGCACGTGAGCTGTGCATCTACGATGATGAGT
GTATGTATATCGATCAGTGTAGCGCATGTAGTCATCGATACTACGCACGATGACACACTAGTCAGTACATCACTCATGTCCGTG
TATCTGTGACGAGTCTCGATCGCGCTGTCTGATGCAGTGCAGACGACGTACACAGTACGCAGCTCGCTCGTGTGACTCAT
GCAGAGCAGAGCGCTAGAGACTAGAGCACGTAGTGTCTGCTATCGACTCGTCACATATCATCTGTCACTCTGTAGTGACAGTG
ACTACTCTCGTAGCTAGTGACGCTACAGCGCAGCTCGCTGAGCTACGTGAGTATCACATAGACTCAGTCTATCTACTGTGCGAC
TCGTGATCACAGTCTCGTGAGTGTGTCTAGCTGAGTCTGATGACGTGTACGTCCTCACACTGTCACACTCAGCATATACGAGCAGC
ACTATATGCGACTCGTAGCGTGCACGCTCACAGATGCGCAGTCACTATCTCTACAGCTCACATACAGCTGTGTGCTCTGCTA
TCACTAGAGACTCTCGCACTCGTAGCGCTGATGTCTGTATCTACGCACATATCATATATGCATGATAGTCTCTCAGCGTGTCTG
CAG

U2_900_2

Primers sequence

left CCAACAACAAGGCACTCATTAGCAGCGAAAGCCAACCTAGA
right GCATACGACGTCACAAGGAAACAGAAGTAGAAACAACCAAC

Reference sequence (U2_900_2) - incHPMax

GGTTACATGTGCGCTCGACTAGATCGTGTCTGTCTGTCTGTCTAGTGCAGTATCTCGTGTCTAGATGTATAGATAGATAG
ACGATGTGTGCTCAGTGTGTGATCTCTCTAGATGAGTATGAGTGTAGTGTATCGATCTCATAGATACAGTCGTACAGATCATG
ATGTACTGCGTGTCTGTCTGTGCATAGAGCACTCGTCGATGATATACTGATCGTGACGATGTGCGCGCGTGTGTGATGTCTGTA
GTCTGTCTGTCTGTGCGCTCGATATGTGCGCACTGTGCAGACAGATGCTGATGATAGAGTCGTGCTATCTCATACAGACAGATA
GCACGTGTAGCTCGAGCGCTCACTCACTCTCGTGCAGCAGTAGTACTCGTCTCTAGTGTATAGATAGATAGATATGTGACGCTAG
TATAGTGTGCGTATCGACATCGTGCATAGACTCGACGTGTCTGACTATCTGTCTCAGCGATAGTGTAGAGTCACTCACAGCT
AGTACTCAGTGACTGATACGAGACGCGCTGAGCGGATATGCGCGTGTCTTAGATCGTACGTGCGTGTGTGTAGTGTGTAGTGTG
TCTGTCTGTGCTCGATCGTCACTGAGTCTCGACACGCTGAGCGATATCTCTCAGTGTAGTGTAGATGTCTCGCTAGATAGATA
GTGTCTGATGTGCTGTGCTCGTGTATAGACACTCACTCTACTCGACATGCTACGCTAGAGTCGTGCTCATGCTCACTAGTCTCG

