



HAL
open science

Influence of experimental conditions on visco-hyperelastic properties of skeletal muscle tissue using a Box–Behnken design

Naïm Jalal, Mustapha Zidi

► **To cite this version:**

Naïm Jalal, Mustapha Zidi. Influence of experimental conditions on visco-hyperelastic properties of skeletal muscle tissue using a Box–Behnken design. *Journal of Biomechanics*, 2019, 85, pp.204 - 209. 10.1016/j.jbiomech.2019.01.020 . hal-03486040

HAL Id: hal-03486040

<https://hal.science/hal-03486040>

Submitted on 20 Dec 2021

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

1 **Influence of experimental conditions on visco-hyperelastic properties of**
2 **skeletal muscle tissue using a Box–Behnken design**

3 **Naïm JALAL^a, Mustapha ZIDI^{a,*}**

4 ^a Bioengineering, Tissues and Neuroplasticity, EA 7377, Université Paris-Est Créteil, Faculté
5 de Médecine, 8 rue du Général Sarrail, 94010 Créteil, France

6

7 * Corresponding author : Professor Mustapha Zidi
8 BIOTN - EA 7377, Université Paris-Est Créteil
9 Faculté de Médecine
10 8 rue du Général Sarrail
11 94010 Créteil, France
12 E-mail: zidi@u-pec.fr
13 Phone: +33 1 49 81 35 57

14

15

16 **Keywords:** Skeletal muscle; Relaxation tests; Visco-hyperelasticity; Design of experiments

17

18 Word count (Introduction to Discussion): 2492

19

20

21

22 **Abstract (186 words)**

23 The Mechanical characterization of skeletal muscles is strongly dependent on numerous
24 experimental design factors. Nevertheless, significant knowledge gaps remain on the
25 characterization of muscle mechanics and a large number of **experiments** should be
26 implemented to test the influence of a large number of factors. In this study, we propose a
27 design of experiment method (DOE) to study the parameter sensitivity while minimizing the
28 number of tests. A Box-Behnken design was then implemented to study the influence of strain
29 rate, preconditioning and preloading conditions on visco-hyperelastic mechanical parameters
30 of two rat forearm muscles. The results show that the strain rate affects the visco-hyperelastic
31 parameters for both muscles. These results are consistent with previous work demonstrating
32 that stiffness and viscoelastic contributions increase with strain rate. Thus, DOE has been
33 shown to be a valid method to determine the effect of the experimental conditions on the
34 mechanical behaviour of biological tissues such as skeletal muscle. This method considerably
35 reduces the number of experiments. Indeed, the presented study using 3 parameters at 3 levels
36 would have required at least 54 tests per muscle against 14 for the proposed DOE method.

37 **1. Introduction**

38 Skeletal muscle is a complex tissue that can be affected by numerous neurological and
39 musculoskeletal diseases. Relevant constitutive models can allow for the monitoring and the
40 understanding of a disease development. To this end, significant research efforts have been
41 made to understand its biomechanical properties. At the tissue scale, the majority of
42 experimental studies are made by using uniaxial testing machines. Whole or sectioned
43 muscles were thus both subjected to either tension (Calvo et al., 2010; Mohammadkhah et al.,
44 2016; Wheatley et al., 2016a) or compression (Böl et al., 2014; Jalal and Zidi, 2018; Pietsch et

45 al., 2014). Muscle tissue exhibits a highly nonlinear behaviour and may be described by
46 hyperelastic (Calvo et al., 2010; Gras et al., 2012; Johansson et al., 2000; Latorre et al., 2018)
47 and visco-hyperelastic (Calvo et al., 2014; Gras et al., 2013; Van Loocke et al., 2008;
48 Wheatley et al., 2016a) constitutive laws. Note that the experimental conditions **could**
49 influence the mechanical behaviour of muscle tissue such as strain rate, preloading,
50 preconditioning, hydration, lubrication, ambient temperature, sectioning, bathing, **etc...** No
51 experimental conditions consensus has been reached from literature yet, and for numerous
52 factors, the incidence on mechanical behaviour has been poorly documented. For instance,
53 some authors used to preconditioned samples (Calvo et al., 2014; Gras et al., 2012; Nagle et
54 al., 2014; Pietsch et al., 2014; Van Ee et al., 2000) whereas others have considered that
55 precondition can lead to permanent deformation (Van Loocke et al., 2008) and consequently
56 do not precondition the samples (Böl et al., 2016; Jalal and Zidi, 2018; Mohammadkhah et al.,
57 2016; Takaza et al., 2013). Furthermore, most of the studies described the application of a
58 preload before testing, but the amount of preload can greatly vary between studies. Thus,
59 preload have ranged from corresponding force of half of the sample mass (Takaza et al.,
60 2013), and 1/40 (Mohammadkhah et al., 2016) to 1/1000 of a maximal load obtained on
61 preliminary tests (Abraham et al., 2013).

62 Note that the influence of some experimental conditions such as tissue conservation (Böl et
63 al., 2016; Jalal and Zidi, 2018; Van Ee et al., 2000) or sectioning and bathing muscle
64 (Abraham et al., 2013) was investigated on skeletal muscle passive behaviour. Abraham et al.
65 (2013) shown a significantly different viscous tissue response between a section of muscle
66 tissue or a whole muscle as well as between dry or wet testing conditions. Consequently, it is
67 crucial to investigate the influence of various experimental conditions in order to better
68 control mechanical tests. However, numerous factors could be studied which could lead to a

69 large number of tests. Traditionally this type of studies has been performed by monitoring the
70 influence of one factor at a time on an experimental response. While only one factor is
71 changed, others are kept at a constant level. Usually, studies are performed with at least 6 tests
72 per group (Abraham et al., 2013; Jalal and Zidi, 2018; Van Loocke et al., 2008; Wheatley et
73 al., 2016b). In this way, for example, studies with four parameters that could take three
74 different values would then require 72 tests.

75 Design of experiments (DOE) is a potential means to evaluate the effect of factors on the
76 response while minimizing the number of required experiments. Basically, the method
77 consists in changing the value of several factors at the same time in a specific sequence. Note
78 that DOE is widely used in some disciplines such as chemistry (Bezerra et al., 2008; Ferreira
79 et al., 2007) or food research (Deng et al., 2016; Tajabadi et al., 2016). Although this method
80 is rarely used in biomechanics, it is noticeable that some DOE sensitivity analysis based on
81 finite element analyses was used on bone and cartilage tissues (Bahraminasab et al., 2013;
82 Isaksson et al., 2009; Wang et al., 2005).

83 The purpose of this paper is to propose an affordable approach to study the parameter
84 sensitivity while minimizing the number of necessary tests. In this way, as we know that
85 viscoelastic behaviour depends on strain rates (Van Loocke et al., 2008), we choose to
86 investigate the effect of this parameter as well as preconditioning and preloading conditions.
87 A Box–Behnken designs (Box and Behnken, 1960) is then proposed to address this issue.

88 **2. Material and methods**

89 *2.1 Sample preparation and tensile tests*

90 **Rat flexor carpi radialis (FCR) and palmaris longus (PL) muscles (N=14) was extracted from**
91 **the forearm of 15 healthy rats by an authorized person in accordance with the local ethic**

92 committee ANSES/ENVA/UPEC (n°13/12/16-10). After sacrifice of the animals, the muscles
93 were harvested from the forearm of each animal. The muscles were then stored in saline
94 solution at 4°C until testing. Testing was conducted within 6 hours after the death of the
95 animal in order to minimize *rigour mortis* effect (Böl et al., 2016; Van Ee et al., 2000; Van
96 Loocke et al., 2006).

97 After positioning of the muscle between mechanical jaws, the initial sample height was
98 recorded using a calibrated camera, then muscles images were acquired for both front and side
99 view. Hence, under the assumption that the muscle cross-sections were rectangular, the
100 average cross-section area (CSA) was determined from these images by a custom Matlab
101 scripts (Matlab® R2017b, The Mathworks, Inc). FCR and PL muscles were respectively
102 $9.8 \pm 1.6\text{mm}$ ($8.3 \pm 2.0\text{mm}$) high with an average CSA of $9.1 \pm 2.3\text{mm}^2$ ($3.2 \pm 1.9\text{mm}^2$).

103 Tensile tests were conducted by the uniaxial mechanical testing system (MTS Insight, MTS
104 Systems Corporation) by using a 100N force sensor controlled by data processing software.
105 Global strain was recorded during experiments through internal measure of crosshead
106 movement. The slippage was reduced with sandpaper added between muscle and jaws (Calvo
107 et al., 2010). It should be emphasized that the experiments were recorded by front and side
108 cameras in order to inspect slippage at large strain.

109 Before testing, the muscles were or were not subjected to preconditioning cycles and
110 preloading, depending on Box–Behnken design as presented below in the experimental
111 designs section. The experiments consisted of 4 steps, the sample was first loaded at a chosen
112 strain rate up to 10% strain and kept constant for 300 seconds to allow stress relaxation in the
113 sample. The muscle was unloaded until a preloading force and then finally stretched again at
114 the same strain rate than initial ramp up to first onset of slippage. Those slipping were

115 determined afterward by both video inspection and substantial decrease/inflexion of stress. In
116 what follows, the first and second period of stretch is named T1 and T2 respectively.

117 *2.2 Experimental designs*

118 Preconditioning, preloading and strain rates were chosen as varying factors. In order to
119 minimize the number of tests, an experimental design is proposed. Each parameter can take 3
120 values chosen to represent the diversity of values within the literature. First, the
121 preconditioning cycles varied between 0 (Böl et al., 2016; Mohammadkhah et al., 2016), 5
122 (Calvo et al., 2014) and 15 cycles (Nagle et al., 2014; Pietsch et al., 2014). Cycles have been
123 set at a strain rate of 0.5mm/s. Then, preloading varied between 1/1000 (Abraham et al.,
124 2013), 1/40 and 1/20 (Mohammadkhah et al., 2016) of a maximum load. Since we were
125 limited by our sensor sensitivity, a no-preload condition was chosen to represent the very low
126 preloading (1/1000 of maximal load). Preliminary tests enabled us to prescribe 0,03N and
127 0.07N preloads that corresponded to roughly 1/40 and 1/20 of a maximum load. Finally, the
128 strain rate varied between 0.05% (Mohammadkhah et al., 2016), 0.5% (Jalal and Zidi, 2018)
129 and 10% (Van Loocke et al., 2008) per second.

130 A Box–Behnken experimental design with three independent variables at three levels was
131 performed to study the influence of the parameters on the visco-hyperelastic behaviour
132 described in the next section. For statistical calculations, each variable was coded as three
133 levels: -1, 0, and 1 as shown in Tab.1. The protocol was implemented for each muscle,
134 consisting of 14 experimental points carried out in random order with two repeats of the
135 centre of the design as illustrated in Fig. 1.

136

137

138 2.3 Visco-hyperelastic model

139 Since we have just tested skeletal muscle by uniaxial tensile test, we chosen a hyperelastic
140 isotropic model (Bosboom et al., 2001; Gras et al., 2012; Wheatley et al., 2016). We used
141 first-order Ogden's model coupled with second-order Maxwell's model (Jalal and Zidi, 2018).
142 The visco-hyperelastic model is briefly described in Supplementary material S1.

143 2.4 Statistics

144 The experimental data of Box–Behnken design were statistically analysed using
145 Matlab2017b® software. A three-way ANOVA was performed with preconditioning cycles,
146 preload force and strain rates as factors. Experiments were also fitted to a second-order
147 polynomial model :

$$148 \quad Y = a_0 + \sum_{i=1}^3 a_i F_i + \sum_{i=1}^3 \sum_{j=1}^3 a_{ij} F_i F_j, \quad (7)$$

149 where Y is the output $[\mu, \alpha, E_0, \tau_k, \gamma_k, \gamma_T, \lambda_{\max}]$ with λ_{\max} the ultimate elongation before any
150 slippage, F_i are preconditioning cycles (F_1), preload force (F_2), strain rates factors (F_3) and
151 a_0, a_i, a_{ii}, a_{ij} are respectively central, linear, quadratic and interaction coefficients. Finally, the
152 coefficient of determination r^2 and adjusted coefficient of determination r_a^2 were obtained.

153 3. Results

154 3.1. Model Fitting

155 An illustrative example of the stress-time response is shown in Fig. 2a. This test was carried
156 out on FCR muscle with all parameters at central levels, that is to say with 5 preconditioning
157 cycles, 0.03N preload force and strain rate at 0.5 %L0/s. The fitting of the first and second

158 stretch period using first Ogden's model is presented Fig. 2b and Fig. 2d respectively. The
159 stress relaxation fitting by Maxwell's model is given Fig. 2c. We observe that the fitting was
160 correctly performed for both first tensile part ($r^2=0.98\pm0.02$) and relaxation
161 ($r^2 = 0.985\pm0.015$) when using respectively (1) and (2) whereas the fitting of the second
162 tensile part is less suitable ($r^2 = 0.96\pm0.04$) when using (1). The fitting of this last part is
163 particularly incorrect for small strain which is a region of interest in order to estimate
164 instantaneous modulus. Therefore, in what follows, the hyperelastic parameters were obtained
165 from the fitting of the initial 10% ramp (T1).

166

167 3.2. Box-Behnken experiment

168 An ANOVA and second-order polynomial regression were conducted on Box-Behnken
169 experiments with as outputs results ($\mu(T_1), \alpha(T_1), E_0(T_1)$) for the first tensile part, ($\tau_k, \gamma_k, \gamma_T$)
170 for relaxation part and the ultimate elongation λ_{\max} . The second-order model coefficients a_0
171 to a_{33} were obtained for both muscles. Central (a_0) and linear (a_1 to a_3), coefficients, as well
172 as coefficients of determination (r^2, r_a^2) and p-value for preconditioning cycles, preloading
173 and strain rates factors are given in Tab.2 and Tab.3 for respectively PL and FCR muscles.

174

175 For hyperelastic contribution, in the case of FCR muscle, we note a non-significant trend of
176 strain rate on $\mu(T_1)$ and $\alpha(T_1)$ ($p = [0.05 - 0.1]$). For viscoelastic contribution, in the case
177 of both muscles, we found a strong influence of strain rate on τ_1, γ_1 ($p \leq 0.01$) and a
178 significant influence on γ_T ($p \leq 0.05$).

179 Eq. (8) and (9) show the relationship between the 3 factors and the output τ_1 for respectively
180 PL and FCR muscles. Response surfaces are presented in Fig.3a-c for PL muscles and in
181 Fig.3d-f for FCR muscles. They were obtained by varying 2 factors within the experimental
182 range [-1 1] and holding the other one at the central level [0].

$$183 \tau_1 = 3.94 - 0.64F_1 - 0.17F_2 - 2.70F_3 + 0.88F_1.F_3 + 0.09F_1.F_2 - 0.04F_2.F_3 - 0.89F_1^2 + 0.65F_2^2 + 0.68F_3^2, \\ 184 \tag{8}$$

$$185 \tau_1 = 3.74 - 0.01F_1 - 1.09F_2 - 3.44F_3 + 0.70F_1.F_3 + 0.54F_1.F_2 - 1.47F_2.F_3 - 0.76F_1^2 + 0.19F_2^2 + 1.26F_3^2, \\ 186 \tag{9}$$

187 4. Discussion

188 This study was motivated by the importance of the experimental conditions on the mechanical
189 response of muscle subjected to the relaxation-tensile test. The study factors include preload,
190 preconditioning cycle and strain rate. The only factor affecting the behaviour of both muscles
191 is strain rates. Indeed, this parameter has been shown to have a great impact on viscoelastic
192 properties, and more specifically on τ_1 , γ_1 and γ_T parameters. Higher the strain rates, the
193 most the stress relaxed in a short period of time. Therefore, whether it is for PL or for FCR
194 muscles the coefficient of τ_1 in the polynomial model before F3 (strain rates) is negative and
195 larger in absolute value. On the contrary, the coefficient γ_1 and γ_T of the polynomial model
196 before F3 are positive and also higher in absolute value. These results are consistent with
197 previous work demonstrating that the viscoelastic contributions, which corresponds to γ_T ,
198 increased with the strain rate in muscle compression tests (Van Loocke et al., 2008). A trend
199 towards significance can be noted between an increase of strain rates and an increase of $\mu(T_1)$
200 as well as a decrease of $\alpha(T_1)$ ($p = 0.07$ and $p = 0.094$) for FCR muscles. **Note that a**

201 similar trend can be observed for PL muscles but without statistically significant. We can note
202 that Sun et al. (1995) did not show behavior differences in the context of small strain. Thus, it
203 is not surprising to show only slight differences due to strain rate. Consequently, these
204 similarities with previous work strongly suggest that this method is robust enough to be used
205 as tools to determine the effect of experimental conditions on mechanical tests. The main
206 interest of this method is to substantially reduce the number of experiments. Indeed, if we
207 applied the usual single variable method with at least 6 tests per group (Jalal and Zidi, 2018;
208 Van Loocke et al., 2008; Wheatley et al., 2016b), this study with 3 parameters at 3 levels
209 would required at least 54 tests per muscle against 14 for the DOE proposed method.

210 It should be noted that only the second-order polynomial regression with a coefficient of
211 determination r^2 above 0.8 should be considered according to Joglekar and AT May (1987)
212 (Joglekar and May, 1987). Nevertheless, the more coefficients, the higher will the r^2 value
213 will be. Thus, the adjusted coefficient of determination r_a^2 was also determined, this
214 coefficient is corrected by including a penalty for the numbers of predictors variables (here 9).
215 In that respect, although correlation for τ_1 , γ_1 and γ_T results are acceptable for FCR muscle
216 with $r_a^2 \geq 0.8$, correlations for PL muscles should be made carefully ($r_a^2 \geq 0.657$, $r_a^2 \geq 0.674$
217 for τ_1 and γ_T results).

218 Furthermore, it is worth noting that neither the preloading nor the preconditioning does not
219 seem to have a significant effect on the visco-hyperelastic skeletal muscle behaviour. It is
220 important, nevertheless, to nuance such a conclusion. Indeed, it is difficult to isolate one
221 factor without others factors interaction. For instance, the preconditioning of sample may
222 (depending on experimental device) require a substantially longer handling involving an
223 increased tissue drying. Thus, the initial preconditioning study would, in fact, be an

224 investigation including preconditioning and drying. Clearly, more works have to be done
225 considering more parameters carefully chosen while using the proposed DOE. Finally, none
226 of these factors seems to have an influence on the ultimate elongation value (λ_{max}). This
227 observation means that the specimen slippage that is an experimental limitation does not seem
228 to be affected by those factors.

229 **5. Limitations**

230 (see Supplementary material S2).

231 **6. Conclusion**

232 A Box–Behnken design was proposed to investigate the influence of strain rates,
233 preconditioning and preloading conditions on mechanical behaviour were investigated on two
234 rat forearm muscles. Visco-hyperelastic parameters are derived from the Ogden model
235 coupled with Maxwell's model. The results showed that strain rate affects the behaviour of
236 both muscles. These results are consistent with previous work suggesting that design of
237 experiment is a valid method to determine the effect of experimental conditions on the
238 mechanical behaviour of skeletal muscle subjected to tensile test. This method lets
239 considerably reduce the number of experiments. Thus, it may be worth investigating the effect
240 of various experimental factors such as drying, jaws tightening, and also testing temperature.

241

242 **Acknowledgements**

243 This work was supported by University Paris-Est Créteil. We thank Cécile Lecointe and
244 Richard Souktani (technical surgical platform of the small animal, IMRB, University Paris-
245 Est Créteil).

246

247 **Conflict of interest statement**

248 No conflict of interests is associated with the present study.

249

250 **Références**

- 251 Abraham, A.C., Kaufman, K.R., Donahue, T.L.H., 2013. Phenomenological consequences of
252 sectioning and bathing on passive muscle mechanics of the New Zealand white rabbit
253 tibialis anterior. *J. Mech. Behav. Biomed. Mater.* 17, 290–295.
254 <https://doi.org/10.1016/j.jmbbm.2012.10.003>
- 255 Bahraminasab, M., Jahan, A., Sahari, B., Arumugam, M., Shamsborhan, M., Hassan, M.R.,
256 2013. Using Design of Experiments Methods for Assessing Peak Contact Pressure to
257 Material Properties of Soft Tissue in Human Knee. *J. Med. Eng.* 2013, 891759.
258 <https://doi.org/10.1155/2013/891759>
- 259 Bezerra, M.A., Santelli, R.E., Oliveira, E.P., Villar, L.S., Escalera, L.A., 2008. Response
260 surface methodology (RSM) as a tool for optimization in analytical chemistry. *Talanta*
261 76, 965–977. <https://doi.org/10.1016/j.talanta.2008.05.019>
- 262 Böl, M., Ehret, A.E., Leichsenring, K., Weichert, C., Kruse, R., 2014. On the anisotropy of
263 skeletal muscle tissue under compression. *Acta Biomater.* 10, 3225–3234.
264 <https://doi.org/10.1016/j.actbio.2014.03.003>
- 265 Böl, M., Leichsenring, K., Ernst, M., Ehret, A.E., 2016. Long-term mechanical behaviour of
266 skeletal muscle tissue in semi-confined compression experiments. *J. Mech. Behav.*
267 *Biomed. Mater.* 63, 115–124. <https://doi.org/10.1016/j.jmbbm.2016.06.012>
- 268 Box, G.E.P., Behnken, D.W., 1960. Some New Three Level Designs for the Study of
269 Quantitative Variables. *Technometrics* 2, 455–475.
270 <https://doi.org/10.1080/00401706.1960.10489912>

271 Calvo, B., Ramírez, A., Alonso, A., Grasa, J., Soteras, F., Osta, R., Muñoz, M.J., 2010.
272 Passive nonlinear elastic behaviour of skeletal muscle: Experimental results and model
273 formulation. *J. Biomech.* 43, 318–325. <https://doi.org/10.1016/j.jbiomech.2009.08.032>

274 Calvo, B., Sierra, M., Grasa, J., Muñoz, M.J., Peña, E., 2014. Determination of passive
275 viscoelastic response of the abdominal muscle and related constitutive modeling:
276 Stress-relaxation behavior. *J. Mech. Behav. Biomed. Mater.* 36, 47–58.
277 <https://doi.org/10.1016/j.jmbbm.2014.04.006>

278 Deng, S., Wang, D., Zhang, M., Geng, Z., Sun, C., Bian, H., Xu, W., Zhu, Y., Liu, F., Wu, H.,
279 2016. Application and optimization of the tenderization of pig Longissimus dorsi
280 muscle by adenosine 5'-monophosphate (AMP) using the response surface
281 methodology. *Anim. Sci. J. Nihon Chikusan Gakkaiho* 87, 439–448.
282 <https://doi.org/10.1111/asj.12434>

283 Ferreira, S.L.C., Bruns, R.E., Ferreira, H.S., Matos, G.D., David, J.M., Brandão, G.C., da
284 Silva, E.G.P., Portugal, L.A., dos Reis, P.S., Souza, A.S., dos Santos, W.N.L., 2007.
285 Box-Behnken design: An alternative for the optimization of analytical methods. *Anal.*
286 *Chim. Acta* 597, 179–186. <https://doi.org/10.1016/j.aca.2007.07.011>

287 Gras, L.-L., Mitton, D., Viot, P., Laporte, S., 2013. Viscoelastic properties of the human
288 sternocleidomastoideus muscle of aged women in relaxation. *J. Mech. Behav. Biomed.*
289 *Mater.* 27, 77–83. <https://doi.org/10.1016/j.jmbbm.2013.06.010>

290 Gras, L.-L., Mitton, D., Viot, P., Laporte, S., 2012. Hyper-elastic properties of the human
291 sternocleidomastoideus muscle in tension. *J. Mech. Behav. Biomed. Mater.* 15, 131–
292 140. <https://doi.org/10.1016/j.jmbbm.2012.06.013>

293 Isaksson, H., Donkelaar, C.C. van, Ito, K., 2009. Sensitivity of tissue differentiation and bone
294 healing predictions to tissue properties. *J. Biomech.* 42, 555–564.
295 <https://doi.org/10.1016/j.jbiomech.2009.01.001>

296 Jalal, N., Zidi, M., 2018. Effect of cryopreservation at –80°C on visco-hyperelastic properties
297 of skeletal muscle tissue. *J. Mech. Behav. Biomed. Mater.* 77, 572–577.
298 <https://doi.org/10.1016/j.jmbbm.2017.10.006>

299 Joglekar, A.M., May, A., 1987. Product Excellence through Design of Experiments. *Cereal*
300 *Foods World* 32, 857–868.

301 Johansson, T., Meier, P., Blickhan, R., 2000. A Finite-Element Model for the Mechanical
302 Analysis of Skeletal Muscles. *J. Theor. Biol.* 206, 131–149.
303 <https://doi.org/10.1006/jtbi.2000.2109>

304 Latorre, M., Mohammadkhah, M., Simms, C.K., Montáns, F.J., 2018. A continuum model for
305 tension-compression asymmetry in skeletal muscle. *J. Mech. Behav. Biomed. Mater.*
306 77, 455–460. <https://doi.org/10.1016/j.jmbbm.2017.09.012>

307 Mohammadkhah, M., Murphy, P., Simms, C.K., 2016. The in vitro passive elastic response of
308 chicken pectoralis muscle to applied tensile and compressive deformation. *J. Mech.*
309 *Behav. Biomed. Mater.* 62, 468–480. <https://doi.org/10.1016/j.jmbbm.2016.05.021>

310 Nagle, A.S., Barker, M.A., Kleeman, S.D., Haridas, B., Mast, T.D., 2014. Passive
311 biomechanical properties of human cadaveric levator ani muscle at low strains. *J.*
312 *Biomech.* 47, 583–586. <https://doi.org/10.1016/j.jbiomech.2013.11.033>

313 Pietsch, R., Wheatley, B.B., Haut Donahue, T.L., Gilbrech, R., Prabhu, R., Liao, J., Williams,
314 L.N., 2014. Anisotropic compressive properties of passive porcine muscle tissue. *J.*
315 *Biomech. Eng.* 136. <https://doi.org/10.1115/1.4028088>

316 Sun, J.-S., Tsuang, Y.-H., Liu, T.-K., Hang, Y.-S., Cheng, C.-K., Lee, W.W.-L., 1995.
317 *Viscoplasticity of rabbit skeletal muscle under dynamic cyclic loading. Clin. Biomech.*
318 *Bristol Avon* 10, 258–262.

319 Tajabadi, F., Ghambarian, M., Yamini, Y., Yazdanfar, N., 2016. Combination of hollow fiber
320 liquid phase microextraction followed by HPLC-DAD and multivariate curve
321 resolution to determine antibacterial residues in foods of animal origin. *Talanta* 160,
322 400–409. <https://doi.org/10.1016/j.talanta.2016.07.035>

323 Takaza, M., Moerman, K.M., Gindre, J., Lyons, G., Simms, C.K., 2013. The anisotropic
324 mechanical behaviour of passive skeletal muscle tissue subjected to large tensile
325 strain. *J. Mech. Behav. Biomed. Mater.* 17, 209–220.
326 <https://doi.org/10.1016/j.jmbbm.2012.09.001>

327 Van Ee, C.A., Chasse, A.L., Myers, B.S., 2000. Quantifying skeletal muscle properties in
328 cadaveric test specimens: effects of mechanical loading, postmortem time, and freezer
329 storage. *J. Biomech. Eng.* 122, 9–14.

330 Van Loocke, M., Lyons, C.G., Simms, C.K., 2008. Viscoelastic properties of passive skeletal
331 muscle in compression: Stress-relaxation behaviour and constitutive modelling. *J.*
332 *Biomech.* 41, 1555–1566. <https://doi.org/10.1016/j.jbiomech.2008.02.007>

333 Van Loocke, M., Lyons, C.G., Simms, C.K., 2006. A validated model of passive muscle in
334 compression. *J. Biomech.* 39, 2999–3009.
335 <https://doi.org/10.1016/j.jbiomech.2005.10.016>

336 Wang, J.-L., Shirazi-Adl, A., Parnianpour, M., 2005. Search for critical loading condition of
337 the spine—A meta analysis of a nonlinear viscoelastic finite element model. *Comput.*
338 *Methods Biomech. Biomed. Engin.* 8, 323–330.
339 <https://doi.org/10.1080/10255840500317631>

340 Wheatley, B.B., Morrow, D.A., Odegard, G.M., Kaufman, K.R., Haut Donahue, T.L., 2016a.
341 Skeletal muscle tensile strain dependence: Hyperviscoelastic nonlinearity. *J. Mech.*
342 *Behav. Biomed. Mater.* 53, 445–454. <https://doi.org/10.1016/j.jmbbm.2015.08.041>

343 Wheatley, B.B., Odegard, G.M., Kaufman, K.R., Donahue, T.L.H., 2016b. How does tissue
344 preparation affect skeletal muscle transverse isotropy? *J. Biomech.*
345 <https://doi.org/10.1016/j.jbiomech.2016.06.034>

1 **List of figures**

2 **Fig. 1.** Schematic illustration of Box-Behnken design. Blue points were only completed once
3 whereas green point was repeated twice.

4


5 **Fig. 2.** Illustrative examples (FCR centre point) of stress-time response (a), stress-stretch
6 fitting using first-order Ogden's model for first $r^2 = 0.98 \pm 0.02$ (b) and the second tensile part
7 $r^2 = 0.96 \pm 0.04$ (d), and stress-time fitting using second-order Maxwell's model
8 $r^2 = 0.985 \pm 0.015$ (c).

9

10 **Fig. 3.** Response surface and contour plot showing the effect of preload, preconditioning
11 cycles and strain rates ($\dot{\epsilon}$) on first relaxation time τ_1 on PL (a-c) and FCR (d-f) muscles.

12





13 **Fig. 1.**



14

15


16 **Fig. 2.**



17

18

19 **Fig. 3.**



20

1 **List of tables**

2 **Table 1 :**

3 Factors and levels of Box-Behnken design

4

5 **Table 2**

6 Central (a_0) and linear (a_1 to a_3) coefficients of the second-order polynomial model for outputs
7 obtained on PL muscles mechanical tests. Coefficients of determination r^2 and adjusted coefficient of
8 determination r_a^2 of polynomial model. P-values for preload, preconditioning cycles and strain rates
9 ($\dot{\epsilon}$) obtained by ANOVA.

10

11 **Table 3**

12 Central (a_0) and linear (a_1 to a_3) coefficients of the second-order polynomial model for outputs
13 obtained on FCR muscles mechanical tests. Coefficients of determination r^2 and adjusted coefficient
14 of determination r_a^2 of polynomial model. P-values for preload, preconditioning cycles and strain rates
15 ($\dot{\epsilon}$) obtained by ANOVA.

16

17

18 **Table 1.**

Variables	Levels		
	-1	0	1
Preconditioning cycles	0	5	15
Preload Force (N)	0	0.03	0.07
Strain rate (%L ₀ /s)	0.05	0.5	10

19

20 **Table 2.**

	a_0	a_1	a_2	a_3	r^2	r_a^2	P-Value Preload	P-Value Cycle	P-Value $\dot{\epsilon}$
$\mu(T_1)$	263,60	218,04	82,25	190,64	0,674	-0,061	0,359	0,848	0,393
$\alpha(T_1)$	0,53	-0,42	-0,76	-4,30	0,855	0,530	0,461	0,756	0,569
$E_0(T_1)$	180,13	225,86	213,52	-142,93	0,728	0,117	0,223	0,178	0,290
γ_1	0,39	-0,03	0,03	0,19	0,964	0,882	0,740	0,250	0,002
τ_1	3,94	-0,64	-0,17	-2,70	0,894	0,657	0,240	0,637	0,002
γ_2	0,40	-0,05	0,01	0,04	0,734	0,136	0,449	0,192	0,540
τ_2	94,79	-24,36	6,58	-8,68	0,934	0,784	0,201	0,407	0,631
γ_T	0,79	-0,07	0,04	0,23	0,900	0,674	0,530	0,182	0,023
λ_{max}	1,53	-0,14	-0,05	0,06	0,628	-0,209	0,122	0,731	0,284

21

22 **Table 3.**

	a_0	a_1	a_2	a_3	r^2	r_a^2	P-Value Preload	P-Value Cycle	P-Value $\dot{\epsilon}$
$\mu(T_1)$	38,20	32,85	70,25	103,83	0,834	0,462	0,519	0,592	0,070
$\alpha(T_1)$	6,54	1,02	2,24	-5,97	0,677	-0,050	0,465	0,512	0,094
$E_0(T_1)$	122,05	11,81	20,14	18,97	0,907	0,697	0,119	0,471	0,790
γ_1	0,38	0,01	-0,01	0,13	0,991	0,970	0,256	0,317	0,000
τ_1	3,74	-0,01	-1,09	-3,44	0,957	0,860	0,738	0,365	0,001
γ_2	0,33	0,04	0,02	-0,06	0,905	0,690	0,033	0,415	0,030
τ_2	84,12	2,38	-8,76	-16,56	0,650	-0,138	0,473	0,652	0,147
γ_T	0,71	0,04	0,02	0,07	0,972	0,910	0,006	0,370	0,010
λ_{max}	1,38	0,00	0,02	0,04	0,545	-0,479	0,802	0,903	0,907

23

24