

Development of high-definition muon telescopes and muography of the Great Pyramid

Sébastien Procureur, David Attié

▶ To cite this version:

Sébastien Procureur, David Attié. Development of high-definition muon telescopes and muography of the Great Pyramid. Comptes Rendus. Physique, 2019, 20, pp.521 - 528. 10.1016/j.crhy.2019.09.003 . hal-03489103

HAL Id: hal-03489103 https://hal.science/hal-03489103

Submitted on 20 Jul2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution - NonCommercial 4.0 International License

Development of high-definition muon telescopes and 1 muography of the Great Pyramid 2

S. Procureur^a, D. Attié^b

^aCEA, Centre de Saclay, Irfu/DPhP, 91191 Gif sur Yvette, France. 4 5

^bCEA, Centre de Saclay, Irfu/Dedip, 91191 Gif sur Yvette, France.

Abstract 6

3

Several muon telescopes have been developed in the last years at CEA-Saclay. Benefitting from a 15 year R&D on Micro-Pattern Gaseous Detectors (MPGDs) and on several recent innovations, these telescopes yield unprecedented resolution for real time instruments, and allow for high definition muography imaging. As a first application, 3 of them were deployed around Khufu's Pyramid from 2015 to 2017, showing very good performance and stability in harsh conditions. They also provided the first detection ever of internal structures of a pyramid from the outside, and participated to the discovery of a large void above the Grand Gallery.

Plusieurs télescopes à muons ont été mis au point ces dernières années au CEA-Saclay. Bénéficiant de 15 années de R&D sur les détecteurs gazeux à micro-pistes (MPGDs) et de plusieurs innovations récentes, ces télescopes offrent une résolution inégalée pour des instruments temps réel, et ouvrent la voie à la muographie haute définition. 3 de ces instruments ont été déployés autour de la pyramide de Kheops entre 2015 et 2017, démontrant de très bonnes performances et une grande stabilité dans des conditions particulièrement difficiles. Ils ont également fourni la toute première détection de structures internes d'une pyramide depuis l'extérieur, et participé à la découverte d'un grand vide situé au-dessus de la Grande Galerie.

- 7 Key words: Muography, Micro Pattern Gaseous Detectors, MPGD,
- Micromegas, Pyramid, Khufu

Preprint submitted to C. R. Physique

September 19, 2019

9 1. Introduction

10 1.1. Cosmic rays and muons

Most of our Universe is a hostile place for life. In every galaxy, ionizing 11 particles are produced and accelerated during violent cosmic phenomena like 12 supernovae. The energy of these particles, essentially protons, can reach 13 the kinetic energy of a tennis ball hit at 150 km/h. In the Universe quasi-14 perfect vacuum, they can travel during millions of year before being stopped 15 or absorbed. And every second, billions of such particles end their long 16 journey when approaching the Earth. The collisions with atoms of the upper 17 layers of our atmosphere create cascades, or showers of less energetic particles 18 like pions, kaons, neutrons and many more. At the sea level, the particle 19 flux is dominated by muons, with a rate of approximately $150 \,\mathrm{Hz/m^2}$. The 20 atmosphere thus acts as a giant, protecting umbrella converting hazardous 21 particles into a cosmic rain which actively participates to the evolution of 22 life. The production and propagation of muons derive from several complex 23 processes: 24

- their copious production from pions and kaons is a consequence of he licity conservation [1];
- though unstable with a life time of about $2 \mu s$, they can travel several kilometers thanks to the time dilatation described by special relativity;

200 times more massive than electrons, they are much more penetrating
 due to the (somehow counter-intuitive) phenomenon of Bremstrahlung
 radiation.

The penetration capability of cosmic muons is remarkable: about 50% of them can cross 10 m of water, and 1% survive to 100 m of rocks, making them much more penetrating than artificial sources like X-rays or neutrons. Still, as a charged particle, muons interact with matter, and these interactions give hints on the amount of material they crossed.

37 1.2. Principles of muography

The electromagnetic interactions between muons and matter result in an energy loss described by the Bethe-Bloch [2] equation, and in a deviation of their trajectory by collisions with nuclei forming the material (multiple scattering) [3].

In the first case, the Bethe-Bloch equation shows that the fraction of cosmic 42 muons which is absorbed in a certain length of material of local density $\rho(x)$ 43 is determined by the integral $\int \rho(x) dx$, called the opacity. Measuring the 44 muon absorption (or transmission) factor in a given direction thus provides 45 the average density in this direction, as the length is usually known. With 46 a set of muon detectors pointing to the structure to study, one obtains a 2D 47 map of its density, called *muography*. A muography can be formed either 48 using transmitted or absorbed muons, the former being the most common 49 mode for large objects. Because of the modest flux and the small amount of 50 information available in this mode, a transmission or absorption muography 51 usually takes from a few hours to a few months, depending on the configu-52 ration and on the size of the object. 53

In the deviation mode, a set of detectors placed on both sides of the object 54 measures the upstream and downstream muon trajectory [4]. According to 55 Moliere theory, the typical scattering angle is also determined by the opacity 56 of the material, and to some extent to its atomic weight Z. The advantage 57 of this method is that it uses much more information from every muon, and 58 gives access to the scattering point in 3D. A deviation muography, also called 59 muon tomography because of its 3D nature, can be obtained in a few minutes 60 only. However, it is restricted to relatively small objects in practice (typically 61 a few cubic meters) because of the surface to cover and also because of the 62 blurring of the image for thick materials. 63

⁶⁴ The three muon imaging modes are schematically represented in Fig. 1, and

⁶⁵ more details about the muography principles and applications can be found ⁶⁶ in [5].



Figure 1: Principle of muon imaging using transmission (left), absorption (middle) and deviation (right) modes with particle detectors (in blue). Muon trajectories are represented in bold and bold dotted, but only the former are actually used for a given mode.

⁶⁹ 2. The CEA muon telescopes

Charged particles like muons have been routinely detected by particle
physicists for about a century. The specificities of muography however impose
a number of requirements which are difficult to satisfy simultaneously:

- a large detection area to compensate for the modest muon flux, as for
 any optical telescope
- a good angular resolution to obtain precise images
- robustness, in the (likely) case of transportation and *in situ* measurements
- compactness, for the same reason as well as for an easy manipulation
 or insertion in confined areas
- real time capabilities, in the case of dynamical studies
- minimal consumption (electric, gas, *etc.*) in the case of operation in the wild
- a reasonable price

Historically, 3 technologies have been mainly used in muography: nuclear 84 emulsions, scintillators and gaseous detectors. Nuclear emulsions have the 85 advantages to be completely passive and extremely precise, but quite sensi-86 tive to the environment and with a very long and complex analysis procedure. 87 Scintillators are particularly robust and offer real time analysis, but with a 88 low resolution. Gaseous detectors somehow combine the advantages of the 89 first two, with a good resolution, robustness, and real time capabilities. Up 90 to recently, its use was however limited because of an expensive electronic 91 equipment and because its poor performance stability in outdoor conditions. 92 93

68

94 2.1. Detectors

The telescopes developed at Irfu are based on the Micromegas [6], one of 95 the main Micro-Pattern Gaseous Detectors (MPGDs). Its active volume is 96 separated into a conversion gap where the charged incident particle ionizes 97 the gas, and an amplification gap where the charges from primary ioniza-98 tions are multiplied through an avalanche process. The generated electrons 99 and ions then induce a charge on copper strips etched on a Printed Circuit 100 Board, which allows for the localization of the incident particle. The accu-101 racy of this localization is determined by the pitch of the copper strips, and 102 typically yields 100-500 microns. However such a high density of strips results 103 in a large number of electronic channels leading to an expensive equipment 104 and a large electric consumption. 105

This difficulty was solved during the R&D for another project, where a specific multiplexing scheme was introduced [7]. In this scheme, 2 given channels are connected to *neighbouring* strips at most once in the detector, thus allowing for a non ambiguous demultiplexing, as illustrated in Fig. 2. Thanks to the modest muon flux, a large multiplexing factor can be used, and a single channel could be connected to 17 strips while keeping the detection efficiency above 95% for a single detector.

Benefitting further from several technological improvements, in particular the bulk technology [8] and the resistive film [9], robust 50x50 cm² detectors were first manufactured in the CERN and Saclay MPGD workshops in 2014 [10], and assembled in a telescope.

117 118

119 2.2. Validation of the first telescope prototype: the WatTo experiment

The first telescope consisted in 4 detectors with a 2D readout. It was controlled with a Hummingboard nano-PC interfaced with all the electronic equipments:

- a dedicated High Voltage Power Supply card equipped with miniaturized CAEN A750x modules to set and monitor the high voltages on each detector
- a Front End Unit card based on the DREAM Asic [11] ensuring the
 readout, triggering, collection and digitization of the signals generated
 by incoming muons



Figure 2: Typical muon event in a 4 detector telescope. Each histogram represents the signal amplitude (color scale) as a function of the detector position (horizontal axis) and time (vertical axis). The complex pattern results from the multiplexing scheme, but the muon position can be easily identified as the biggest colored structures in each detector, resulting in a nearly vertical track.

 environmental probes measuring the outside temperature, pressure and humidity

• a disk for data storage

Thanks to the reduction of the channel number and the miniturization of the different modules, all the electronic equipment fitted in a 20 cm side box, with an overall consumption of only 30 W.

The 4 detectors were attached to an inclinable, mechanical frame allowing to point in different directions. A non flamable gas bottle (Ar-iC₄H₁₀-CF₄, 95-2-3, called T2K gas) with a manual flowmeter ensured the serial gas circulation in the detectors, with a typical flow of 1.5 L/h.

In May 2015 this telescope was assembled and tested in outdoor conditions 139 in front of the CEA-Saclay water tower. During 3.5 months, different im-140 ages were obtained validating the performance level of the instrument (see 141 Fig. 3, the first muography of a structure that can be recognized by eve). 142 The dynamical sensitivity was also established by detecting variations of the 143 water level in the tank [12]. During the last month, the telescope was also 144 operated successfully with 2 solar boards, resulting in a slight increase of the 145 electronics noise. 146

147

This experiment also revealed a certain number of problems, and in particular very large fluctuations of the signal amplitude in the detectors related



Figure 3: Muographies of the CEA-Saclay water tower, obtained during the WatTo experiment with a 50×50 cm² telescope. Data were accumulated during 4 days each, with a full (left) then empty (right) tank.

essentially to the temperature. These fluctuations translate into a signal saturation during the nights, and an efficiency drop during the days. A first HV, online feedback was empirically implemented based on the measurement of the outside temperature and pressure, and partially corrected for these fluctuations.

155 3. Muography of Khufu's pyramid

The WatTo experiment ended on September 2015, and the telescope was brought back to the lab for various muon scattering measurements. By a nice coincidence, the Scanpyramids mission [13] was announced a month later in the media.

160 3.1. The Scanpyramids mission

Scanpyramids is an internal mission gathering scientists of different disci-161 plines, with the aim to study the 4 largest pyramids of the IVth dynasty with 162 modern, non destructive techniques. Coordinated by Prof. H. Helal from 163 Cairo University and M. Tayoubi from HIP Institute, under the autority of 164 the Egyptian Ministry of Antiquities, ScanPyramids is the latest generation 165 of a long series of scientific explorations of the Egyptian pyramids. The 166 proposed techniques include thermal measurements and muography for pen-167 etrating imaging, as well as photogrammetry, simulation and 3D modeling. 168 The muography programme was initially ensured by two Japanese teams from 169 Nagoya University and KEK. They respectively developed nuclear emulsions 170

and scintillator instruments to be installed inside the pyramids. In 2015 a
first test was conducted with the emulsions on the Bent pyramid in Dahshour,
allowing to detect the Upper Chamber from the Lower one.

¹⁷⁴ From a historical point of view, it is worth mentioning here that the muog-¹⁷⁵ raphy imaging of a pyramid was actually first proposed by the Nobel Prize

¹⁷⁵ raphy imaging of a pyramid was actually first proposed by the Nobel Prize ¹⁷⁶ physicist L. Alvarez in the late 1960s and applied to the Khafre pyramid [14].

¹⁷⁷ More recently, a team led by A. Menchaca Rocha also conducted extensive

measurements on the Sun Pyramid in Teotihuacan (Mexico) [15].

179

180 3.2. Telescope improvements

The quality of the muographies obtained with the first prototype convinced the coordinators of the telescope interest and it was decided that the CEA will deploy instruments outside the pyramid to complement Japanese inside measurements. Neither the emulsions nor the scintillators could indeed be operated outdoors, the former suffering from high temperatures and the latter from low spatial resolution.

Three new Micromegas-based telescopes¹ were therefore built from January to April 2016 with several improvements to cope with the expected environment:

- a fly-case box embedding each telescope for an easy and safe trans portation
- a thermal protection tapped on the fly-case walls to limit the temperature variations
- a 3G/4G key for remote access and control
- an online track reconstruction and analysis in order to reduce the data transfer to Saclay (one telescope produced in average 20 Gb of raw data per day but only 20 Mb of processed data)
- temperature probes inserted within the gas circuit for a more precise
 high voltage feedback.

¹named after the three famous scientists Alhazen, Alvarez and Brahic who sadly passed away during the preparation of the telescopes

This feedback was replaced in the last outdoor mission by an amplitude
one, updating the high voltages from the measurements of the mean signal
amplitude in each detector [16]. This feedback provided a nearly constant
amplitude with time, as illustrated in Fig. 4.



Figure 4: Time evolution of the mean amplitude in the detectors for the 3 outdoor missions. The vertical scale is identical on the 3 plots. High voltages were adjusted every 15 minutes using the outside temperature and pressure (left), the gas temperature and pressure (middle), and the mean signal amplitude from the online reconstruction (right).

203

The 3 telescopes were transported by plane to Cairo in April (Alhazen) and 204 May (Alvarez and Brahic) 2016, reassembled and connected in Cairo Univer-205 sity, and finally brought to the Giza plateau by car in end of May. Even if a 206 solar board power supply was prepared, a 220 V cable was finally provided. 207 The necessity to guard the telescopes 24/7 on the plateau offered some unex-208 pected comfort, in particular protection tents and air-conditioning. Because 209 of the latter, temperatures did not exceed 45 degrees during the hottest days, 210 *i.e.* safely below the 55 degrees tested at Saclay in an oven. 211

212 3.3. Data taking and analysis

As a first goal to validate their capability, the CEA telescopes were as-213 signed the detection of a known cavity along the North-East edge, already 214 described from XIXth century explorations. Accessible via the largest notch 215 of the pyramid, its volume yields about $15 \,\mathrm{m}^3$ and is invisible from the ground. 216 Simulations were first performed to identify the telescope positions with the 217 optimal sensitivity, taking into account the observation zenith angle, the dis-218 tance to the cavity and the relative opacity variation. The two best positions 219 were localized 37 m away from the basis, and 25 m from the pyramid central 220 $axes^2$, see Fig. 5. Alhazen was therefore positioned on the North side, while 221

²by an unfortunate coincidence which was not predicted by our simulation, the East position turned out to be the exact place of the camel WC.



Figure 5: Simulation showing the sensitivity (in arbitrary units) to detect the known cavity along the North-East edge, as a function of the telescope position. The time needed for an unambiguous detection at 5 sigma level is inversely proportional to the sensitivity. Because of the pyramid symmetry, two best positions are identified, on the North and East sides.

²²² Brahic and Alvarez were installed on the East, see Fig. 6.

223

The simulation further indicated that 2 months of data taking would be re-224 quired for each telescope to be able to detect this cavity. Six 5L bottles 225 containing high pressure T2K gas were thus procured to provide enough gas 226 for a 3 month campaign. In total, around 75 millions of triggers were accu-227 mulated by the three telescopes. Though the Alvarez telescope collected less 228 data because of some gas issues, Alhazen and Brahic were able to detect a 229 significant muon excess (above 5 sigma) at the position of the known cavity. 230 Surprisingly, the data analysis further revealed a very similar excess, about 231 30 m higher than the first one, interpreted as another cavity, see Fig. 7. 232

233

²³⁴ After this first campaign, the telescopes were redeployed in January 2017



Figure 6: Photography of Alvarez and Brahic telescopes during their installation in the East tent.



Figure 7: Result of the first CEA campaign in 2016, showing the positions of the known (C2) and new (C1) cavities on the North-East edge.

 $_{235}$ around the other edges of the pyramid³ to check for the presence of more cav-

³Alhazen looking at the North-West edge, Brahic at the South-East and Alvarez at the South-West

ities, as shown in Fig. 8. More than 88 millions of triggers were accumulated 236 in the second campaign, but splitted on the different edges. This campaign 237 was interrupted in May 2017 after the Nagoya team reported on a large muon 238 excess close to the Grand Gallery, as it was decided to point the telescopes on 239 this zone to confirm the excess. This decision was further motivated by the 240 necessity to get another observation point for a precise triangulation, as all 241 Japanese instruments were located in the Queen's Chamber. After 2 months 242 of data taking, Alhazen and Brahic confirmed at a (combined) 8.4 sigma level 243 the presence of the Grand Gallery, and observed a second excess above it, 244 at a (combined) 5.8 sigma level, see Fig. 9. The 3D model confirmed that 245 this excess nicely overlapped with the excess observed by the Nagoya team. 246 To our knowledge, the observations of the Grand Gallery and of the cavity 247 above⁴ are the first detections of inner structures of a pyramid ever obtained 248 from outside.



Figure 8: Positions of the CEA telescopes during the 3 measurements campaigns.

249

250

251

4. Conclusion and perspectives

Initiated by a lab R&D for the characterization of nuclear physics detectors, the muography activity has turned into a fantastic scientific and human adventure. The telescopes deployed by the CEA team has shown a remarkable robustness in harsh conditions, and opened the way to real time, high definition muography. In order to study in more details the Pyramid and its Big Void, the team has then built in 2018 two new telescopes which have

⁴called the ScanPyramids Big Void



Figure 9: Result of the third CEA campaign in 2017, showing the muon excesses (see red numbers, obtained from a fit) measured in both telescopes and corresponding to the Grand Gallery (bottom) and to the ScanPyramids Big Void (top). θ_x and θ_y represent the angles of the muon tracks in the x - z and y - z planes, z being the axis perpendicular to the telescope and x,y its horizontal and vertical.

²⁵⁹ been installed inside the Grand Galery of the pyramid, where they faced
²⁶⁰ additional challenges: transportation within the small corridors, extreme hu²⁶¹ midity brought by the touristic activity, presence of cable-eating mice, etc.
²⁶² To cope with this new environment, additional improvements have been im²⁶³ plemented, in particular on the gas circuit, with the goal to build completely
²⁶⁴ sealed instruments in the next years.

Beyond the ScanPyramids mission, the possibility to explore unaccessible worlds in a non destructive way evidently elicited a large interest. Several *Proofs of Concepts* are in progress, both experimentally and with simulations, and a collaboration has been recently initiated with Iris Instruments to commercialize these telescopes in a near future.

Interestingly, the required R&D to improve the telescopes has in turn benefitted to high energy physics, via a better understanding and control of the
gas quality of particle detectors. These telescopes are also now adapted, with
very little changes, to build a precise tracker for an anti-matter experiment
at CERN.

275 5. Acknowledgments

This work could not have been done without the unvaluable help of the muography team at IRFU, and to all the people who helped in the preparation of the instruments. The ELVIA group and the CERN MPGD workshop also had a decisive contribution by manufacturing a large part of the Micromegas detectors. We are particularly grateful to P. Chomaz, A-I. Etienvre, E. Delagnes and H. Goutte who have strongly supported this activity. Part of these instruments have been built with the financial support of the Région Ile-de-France (within the SESAME call) and the P2IO LabEx. More importantly, we are indebted to Khufu's architects, who have managed to hide these cavities to all the explorators during 4,500 years. We wish that this small work will contribute to the recognition of their phenomenal genius.

287 References

- [1] D. Griffiths, Introduction to elementary particles, second edition, Wiley VCH (2008), section 9.4
- ²⁹⁰ [2] H. A. Bethe, Phys. Rev. **89** (1953), 256
- [3] C. Patrignani *et al.* (Particle Data Group), Chin. Phys. C, 40 (2016),
 100001
- ²⁹³ [4] K. N. Borozdin *et al.*, Nature **422** (2003), 277
- ²⁹⁴ [5] S. Procureur, Nucl. Instrum. Methods A 878 (2018) 169
- ²⁹⁵ [6] I. Giomataris *et al.*, Nucl. Instrum. Methods A **376** (1996) 29
- [7] S. Procureur, R. Dupré and S. Aune, Nucl. Instrum. Methods A 729 (2014) 888
- ²⁹⁸ [8] Y. Giomataris *et al.*, Nucl. Instrum. Methods A **560** (2006) 405
- ²⁹⁹ [9] T. Alexopoulos *et al.*, Nucl. Instrum. Methods A **640** (2011) 110
- ³⁰⁰ [10] S. Bouteille *et al.*, Nucl. Instrum. Methods A **834** (2016), 187
- [11] C. Flouzat *et al.*, Dream: a 64-channel Front-end Chip with Analogue
 Trigger Latency Buffer for the Micromegas Tracker of the Clas12 Experiment, TWEPP conference (2014)
- ³⁰⁴ [12] S. Bouteille *et al.*, Nucl. Instrum. Methods A **834** (2016), 223
- 305 [13] http://www.scanpyramids.org/
- ³⁰⁶ [14] L. W. Alvarez *et al.*, Science 167 (1970), 832

- ³⁰⁷ [15] S. Aguilar *et al.*, Proceedings of the 33^{rd} international cosmic ray con-³⁰⁸ ference, Rio de Janeiro (2013)
- [16] S. Bouteille and S. Procureur, Procédé et dispositif de rétroaction sur la haute tension d'un détecteur gazeux (patent 17 57755)