



Influence of surface termination on electronic configurations at FASnI₃/C₆₀ interfaces

Pingping Jiang, Boubacar Traore, Mikaël Kepenekian, George Volonakis,
Claudine Katan, Laurent Pedesseau, Jacky Even

► To cite this version:

Pingping Jiang, Boubacar Traore, Mikaël Kepenekian, George Volonakis, Claudine Katan, et al.. Influence of surface termination on electronic configurations at FASnI₃/C₆₀ interfaces. nanoGe Fall Meeting 2021, Oct 2021, Online, France. 10.29363/nanoge.nfm.2021.070 . hal-03500082

HAL Id: hal-03500082

<https://hal.science/hal-03500082>

Submitted on 22 Sep 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



Distributed under a Creative Commons Attribution 4.0 International License

Influence of surface termination on electronic configurations at FASnI₃/C₆₀ interfaces

Pingping JIANG (1), Boubacar TRAORE (2), Mikael KEPENEKIAN (2), George VOLONAKIS (2), Claudine KATAN (2), Laurent PEDESSEAU (1), and Jacky EVEN (1)

(1) Univ Rennes, INSA Rennes, CNRS, Institut FOTON - UMR 6082, F-35000 Rennes, France

(2) Univ Rennes, ENSCR, INSA Rennes, CNRS, ISCR (Institut des Sciences Chimiques de Rennes) - UMR 6226, F-35000 Rennes, France

Ever since organic-inorganic halide perovskites have been employed in electronics and optoelectronics, their unique and excellent photophysical and electrical properties[1–3] have guaranteed their versatile applications in solar cells, LEDs, lasers, photodetectors and beyond[4,5]. Sn-based perovskites along with their surface and interface functionalization after assembling with charge transport layers (CTLs) are considered promising ways to achieve a win-win between environmental friendliness and cell performance [6–10]. In view of the sophisticated chemical and physical properties of Sn-based perovskites, the theoretical calculation based on density functional theory (DFT) has been employed to feasibly and flexibly model the interplay between absorbers and CTLs. In order to understand the fundamental physico-chemical mechanisms of that interplay, the influence of surface termination on structural and electronic properties at FASnI₃/C₆₀ (as ETL) interfaces, in particular, the dependence of vacuum level (and by that work function) within surface alone and interface integrated frameworks, thereupon constructing the heterostructure energy level alignment, has been investigated thoroughly. The resulting type-II heterostructures coupled with the increased surface dipole moments and charge carrier mobilities tell an effective charge transport from FASnI₃ to C₆₀. Our findings contribute to discovering other promising alternatives as ETLs for lead-free perovskites in the light of surface and interface engineering.

This DROP-IT project¹ has received funding from the European Union's Horizon 2020 research and innovation Program under the grant agreement N° 862656. The information and views set out in the abstracts and presentations are those of the authors and do not necessarily reflect the official opinion of the European Union. Neither the European Union institutions and bodies nor any person acting on their behalf may be held responsible for the use which may be made of the information contained herein.

References:

- Shao, S.; Loi, M.A. The Role of the Interfaces in Perovskite Solar Cells. *Adv. Mater. Interfaces* **2020**, *7*, 1901469, doi:10.1002/admi.201901469.
- Li, J.; Duan, J.; Yang, X.; Duan, Y.; Yang, P.; Tang, Q. Review on Recent Progress of Lead-Free Halide Perovskites in Optoelectronic Applications. *Nano Energy* **2021**, *80*, 105526, doi:10.1016/j.nanoen.2020.105526.
- Dong, Q.; Fang, Y.; Shao, Y.; Mulligan, P.; Qiu, J.; Cao, L.; Huang, J. Electron-Hole Diffusion Lengths > 175 Mm in Solution-Grown CH₃NH₃PbI₃ Single Crystals. *Science* **2015**, *347*, 967–970, doi:10.1126/science.aaa5760.
- Li, X.; Bi, D.; Yi, C.; Décuppet, J.-D.; Luo, J.; Zakeeruddin, S.M.; Hagfeldt, A.; Grätzel, M. A Vacuum Flash-Assisted Solution Process for High-Efficiency Large-Area Perovskite Solar Cells. *Science* **2016**, *353*, 58–62, doi:10.1126/science.aaf8060.
- Li, B.; Long, R.; Xia, Y.; Mi, Q. All-Inorganic Perovskite CsSnBr₃ as a Thermally Stable, Free-Carrier Semiconductor. *Angew. Chem. Int. Ed.* **2018**, *57*, 13154–13158, doi:10.1002/anie.201807674.
- Gao, C.; Jiang, Y.; Sun, C.; Han, J.; He, T.; Huang, Y.; Yao, K.; Han, M.; Wang, X.; Wang, Y.; et al. Multifunctional Naphthal Sulfonic Salt Incorporated in Lead-Free 2D Tin Halide Perovskite for Red Light-Emitting Diodes. *ACS Photonics* **2020**, *7*, 1915–1922, doi:10.1021/acspophotonics.0c00497.
- Lazemi, M.; Asgharizadeh, S.; Bellucci, S. A Computational Approach to Interface Engineering of Lead-Free CH₃NH₃SnI₃ Highly-Efficient Perovskite Solar Cells. *Phys. Chem. Chem. Phys.* **2018**, *20*, 25683–25692, doi:10.1039/C8CP03660H.
- Chen, M.; Dong, Q.; Eickemeyer, F.T.; Liu, Y.; Dai, Z.; Carl, A.D.; Bahrami, B.; Chowdhury, A.H.; Grimmel, R.L.; Shi, Y.; et al. High-Performance Lead-Free Solar Cells Based on Tin-Halide Perovskite Thin Films Functionalized by a Divalent Organic Cation. *ACS Energy Lett.* **2020**, *5*, 2223–2230, doi:10.1021/acsenergylett.0c00888.
- Pantaler, M.; Cho, K.T.; Queloz, V.; Benito, I.G.; Fettkenhauer, C.; Anusca, I.; Nazeeruddin, M.K.; Lupascu, D.C.; Grancini, G. Hysteresis-Free Lead-Free Double Perovskite Solar Cells by Interface Engineering. *ACS Energy Letters* **2018**, *3*, 22.
- Peng, L.; Xie, W. Theoretical and Experimental Investigations on the Bulk Photovoltaic Effect in Lead-Free Perovskites MASnI₃ and FASnI₃. *RSC Advances* **2020**, *10*, 14679–14688, doi:10.1039/D0RA02584D.