

Vaporization at high reduced pressure induced by very rapid power input

Dispersed two phase flow

Jean Muller, Pierre Ruyer, Romuald Rullière, Marc Clausse



12 Octobre 2021




INSTITUT NATIONAL
DES SCIENCES
APPLIQUÉES
LYON



Context



- High pressure transient (2MPa)
 - Massive creation of vapour
- Atmospheric pressure and temperature*



Main question

How the test conditions influence the thermal shock consequences ?

Results extracted from : Sugiyama, T. and Fuketa, T. (2000). Mechanical Energy Generation during High Burnup Fuel Failure under Reactivity Initiated Accident Conditions. *Journal of Nuclear Science and Technology*, 37(10) :877–886.


➤ I. EDITE

- Test section
- Acquisition
- Tests performed

EDITE (Etude d'un Dépôt Intense et Transitoire d'Energie)

Discharge 9 condensers

**Discharge: 1 kJ
within 5 ms**




EDITE (Etude d'un Dépôt Intense et Transitoire d'Energie)

Temperature and static pressure
1 Hz

Dynamic pressure (P_1, P_2, P_3) – Voltage and Current
500 kHz


$$(\mathbf{U}, \mathbf{I}) \rightarrow R_W(T) \rightarrow T_W$$



c1




c2



15 kHz
9.2 px/mm

3 kHz
7.63 px/mm


Tests performed



200 tests

$P \in [25 \text{ bar} ; 62 \text{ bar}]$
 $T \in [-15 \text{ }^{\circ}\text{C} ; 24 \text{ }^{\circ}\text{C}]$
 $E \in [75 \text{ J} ; 340 \text{ J}]$

Ensemble des essais





200 tests

$P \in [25 \text{ bar} ; 62 \text{ bar}]$
 $T \in [-15^\circ\text{C} ; 24^\circ\text{C}]$
 $E \in [75 \text{ J} ; 340 \text{ J}]$

Test chosen

$$\begin{cases} P = 25,6 \text{ bar} \\ T = -12^\circ\text{C} \\ E = 240 \text{ J} \end{cases}$$

Test chosen



Camera 1
Slow down : x100
Resolution : 7.6 px/mm



I. EDITE

- Test section
- Acquisition
- Tests performed



➤ II. Pressure peak

- Phenomena
- Influence of the test conditions

Phenomena



Phénomena




Pressure increase
 P [Zhao et al.]

$$\frac{d^2 V_v}{dt^2} > 0$$

Pressure decrease P


$$\frac{d^2 V_v}{dt^2} < 0$$

+ acoustic rebounds




[Zhao et al.] : Zhao, Z., Glod, S., and Poulikakos, D. (2000). Pressure and power generation during explosive vaporization on a thin- μ m microheater. *Int. J. Heat Mass Transfer*, page 16.

Influence of test conditions on the thermal shock




- Reduced pressure
 $P_r = P_i/P_c$
- Theta
 $\Theta = \frac{E}{\Delta H_{i \rightarrow v}} \frac{1}{m_f}$
- Jakob
 $Ja = \frac{\rho_l}{\rho_v} \frac{c_{p,l}(T-T_{sat}(P))}{L(P)}$

$$P_r = P/P_c$$



$$\Theta = \frac{E}{\Delta H_{i \rightarrow v}} \frac{1}{m_f}$$



Decrease of P_m for an increasing P_r

Incertitudes en annexe

Increase of P_m with Θ for low P_r
Saturation of P_m with Θ for high P_r

I. EDITE

- Test section
- Acquisition
- Tests performed

II. Pressure peak


- Phenomena
- Influence of the test conditions

➤ III. Vapour created

- Compression of the buffer layer
- Influence of the test conditions




Buffer layer compression

The fluid is considered incompressible




Buffer layer compression

The fluid is considered incompressible




Asumption:
Isentropic compression of
the buffer layer composed
of a non ideal gas

Buffer layer compression




Slower kinetic for
 $V_v(\text{real})$

Storage of thermal
energy in the
tungsten




Asumption:
Isentropic compression of
the buffer layer composed
of a real gas

Test conditions influence on the volume created




Recondensation of the vapour with an increasing Jakob




V_v decreases with an increasing Ja

Incertitudes en annexe

Test conditions influence on the volume created



Recondensation of the vapour with an increasing Jakob



V_v decreases with an increasing Ja

Incertitudes en annexe

Conclusion

EDITE

Experimental study of the consequences of a thermal shock

Influence of the test conditions on the phenomena

Theoretical study of the transient phase change

Prospectives

- Improvement of the thermal analysis
- Use of the theoretical model for all the tests

